

ThinkCentre Edge 72 Small and Tower



Lenovo ThinkCentre Edge 72 Small and
Lenovo ThinkCentre Edge 72 Tower



Lenovo ThinkCentre Edge 72 Small
with Dual Lenovo ThinkVision Monitors



Lenovo ThinkCentre Edge 72 Small



Lenovo ThinkCentre Edge 72 Small



Lenovo ThinkCentre Edge 72 Tower




Lenovo ThinkCentre Edge 72 Tower

ThinkCentre Edge 72 Small (3493) - TopSeller

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^a | SATA disk GB rpm | SATA optical | Graphics | PCIe Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Floor stand | Win7 Global preload | Ann date (mm/dd/yy) |
|------------|------------|-----------|---------------------|------------------|--------------|----------|---------------------|------------|--------------|---------------|-------------|-------------|---------------------|---------------------|
| 3493-ELG | 3x3 | G640 | 2GBx1 1600MHz | 250G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Pro 64 06/19/12 |
| 3493-EMG | 3x3 | G640 | 2GBx1 1600MHz | 250G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Prem 64 06/19/12 |
| 3493-ENG | 3x3 | G850 | 2GBx1 1600MHz | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Pro 64 06/19/12 |
| 3493-EPG | 3x3 | i3-2120 | 2GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2000 | None | None | Media | Parallel | Serial | None | None | Pro 64 06/19/12 |
| 3493-EQG | 3x3 | i3-2120 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2000 | None | None | Media | Parallel | Serial | None | None | Pro 64 06/19/12 |

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year limited warranty

| | | | | | | | | | | | | | | |
|-------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | Preloaded operating system | | | |
| Processor | Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G850 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket | | | | | | | | | | Some: Genuine Windows® 7 Professional 64 Some: Genuine Windows 7 Home Premium 64 | | | |
| Implementation | | | | | | | | | | | Ready to install applications (only some listed) | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i> | | | | | | | | | | Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) | | | |
| Graphics | Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i> | | | | | | | | | | | | | |
| DP dongle | None | | | | | | | | | | | | | |
| Disk | SATA 3.0Gb/s 7200 rpm | | | | | | | | | | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | | | |
| Onboard SATA eSATA port | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | | | |
| Media reader | 9-in-1 media reader, internal USB 2.0 | | | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | | | |
| IEEE 1394 | None | | | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | | | |
| Modem | None | | | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | | | |
| Keyboard | Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo | | | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | | | |
| Floor Stand | None | | | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.9" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access | | | | | | | | | | | | | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, opt reader* *bay only available on models with media reader installed | | | | | | | | | | | | | |
| Slot | Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1 | | | | | | | | | |  | | | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement RoHS-compliant Supports ThinkVantage Technologies | | | |

See footnotes for important warranty information
 WE model(s) announced June 19, 2012
 WE models withdrawn effective May 2014


©Lenovo
 (G-TAPI1-1) May 2014

ThinkCentre Edge 72 Small (3493) - TopSeller - II

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^a | SATA disk GB rpm | SATA optical | Graphics | PCIe Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Floor stand | Win7 Global preload | Ann date (mm/dd/yy) |
|------------|------------|-----------|---------------------|------------------|--------------|----------|---------------------|------------|--------------|---------------|-------------|-------------|---------------------|---------------------|
| 3493-ERG | 3x3 | i5-3470S | 4GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None Pro 64 | 06/19/12 |
| 3493-ESG | 3x3 | i7-3770S | 4GBx1 1600MHz | 1TB 7200 | DVD±RW | HD 4000 | None | None | Media | Parallel | Serial | None | None Pro 64 | 06/19/12 |

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year limited warranty

| | | | | | | | | | | | | |
|--------------------|--|--|--|--|--|--|--|--|--|--|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | | |
| Processor | Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket | | | | | | | | | | | |
| Implementation | Processor in LGA1155 socket | | | | | | | | | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets | | | | | | | | | | | |
| Graphics | Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i> | | | | | | | | | | | |
| DP dongle | None | | | | | | | | | | | |
| Disk | SATA 3.0Gb/s 7200 rpm | | | | | | | | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | |
| Onboard SATA | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | |
| eSATA port | None | | | | | | | | | | | |
| Media reader | 9-in-1 media reader, internal USB 2.0 | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | |
| IEEE 1394 | None | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | |
| Modem | None | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | |
| Keyboard | Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | |
| Floor Stand | None | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.9" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access | | | | | | | | | | | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, opt reader* *bay only available on models with media reader installed | | | | | | | | | | | |
| Slot | Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1 | | | | | | | | | | | |
| |  | | | | | | | | | | | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | | |
| | Preloaded operating system Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) | | | | | | | | | | | |
| | Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement | | | | | | | | | | | |
| | RoHS-compliant | | | | | | | | | | | |
| | Supports ThinkVantage Technologies | | | | | | | | | | | |


See footnotes for important warranty information
 WE model(s) announced June 19, 2012
 WE models withdrawn effective May 2014

©Lenovo
 (G-TAPI1-2) May 2014

ThinkCentre Edge 72 Small (3493) - TopSeller (Win 8)

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^a | SATA disk GB rpm | SATA optical | Graphics | PCle Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Floor stand | Global | Preload | Ann date (mm/dd/yy) |
|------------|------------|-----------|---------------------|------------------|--------------|----------|---------------------|------------|--------------|---------------|-------------|-------------|--------|------------|---------------------|
| 3493-BAG | 3x3 | G645 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Win8 Pro64 | 10/23/12 |
| 3493-BBG | 3x3 | G645 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Win8 64 | 10/23/12 |
| 3493-BCG | 3x3 | i3-3220 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Win8 Pro64 | 10/23/12 |
| 3493-BDG | 3x3 | i3-3220 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Win8 64 | 10/23/12 |
| 3493-BEG | 3x3 | G870 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Win8 Pro64 | 10/23/12 |
| 3493-BFG | 3x3 | i5-3470S | 4GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Win8 Pro64 | 10/23/12 |
| 3493-BGG | 3x3 | i7-3770S | 4GBx1 1600MHz | 1TB 7200 | DVD±RW | HD 4000 | None | None | Media | Parallel | Serial | None | None | Win8 Pro64 | 10/23/12 |
| 3493-FBG | 3x3 | i3-2130 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2000 | None | None | Media | Parallel | Serial | None | None | Win8 Pro64 | 10/23/12 |
| 3493-AVG | 3x3 | G645 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Win8 Pro64 | 10/23/12 |
| 3493-AWG | 3x3 | G870 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Win7 Pro64 | 10/23/12 |
| 3493-AYG | 3x3 | i3-3220 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Win7 Pro64 | 10/23/12 |
| 3493-AZG | 3x3 | i5-3470S | 4GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Win7 Pro64 | 10/23/12 |
| 3493-DEG | 3x3 | i7-3770S | 4GBx1 1600MHz | 1TB 7200 | DVD±RW | HD 4000 | None | None | Media | Parallel | Serial | None | None | Win7 Pro64 | 10/23/12 |
| 3493-G6G | 3x3 | i3-2130 | 4GBx1 1600MHz | 500G 7200 | DVD±RW | HD 2000 | None | None | Media | Parallel | Serial | None | None | Win7 Pro64 | 11/20/12 |

| | | | | | | | | | | | | | | | | | |
|--------------------|--|--|--|--|--|--|--|--|--|--|--|----------------|--|--|------------------------------------|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | Preloaded operating system | | | | | | |
| Processor | <p>Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1066MHz)</p> <p>Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz)</p> <p>Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated DDR3 memory controller (up to 1333MHz)</p> <p>Intel Core i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz)</p> <p>Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> | | | | | | | | | | <p>Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit</p> <p>Some: Windows 8 64-bit</p> <p>Some: Windows 8 Pro 64-bit</p> | | | | | | |
| Implementation | Processor in LGA1155 socket | | | | | | | | | | Preloaded applications (only some listed) | | | | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets | | | | | | | | | | <p>- Windows 7 models</p> <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Power Manager • ThinkVantage Communication Utility • Lenovo® Message Center Plus • Lenovo SimpleTap • Adobe® Reader® • Windows Live™ Essentials • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) | | | | | | |
| Graphics | Intel HD Graphics / 2000 / 2500 / 4000 in processor, uses main memory, one VGA, one DVI-D, supports dual independent display <i>Maximum resolution: 2560x1600 (VGA) @60Hz; 1920x1200 (DVI-D) @60Hz</i> | | | | | | | | | | <p>- Windows 8 models</p> <ul style="list-style-type: none"> • Lenovo Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Norton™ Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Intel Small Business Advantage • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) | | | | | | |
| DP dongle | None | | | | | | | | | | | | | | | | |
| Disk | SATA 3.0Gb/s 7200 rpm | | | | | | | | | | | | | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | | | | | | |
| Onboard SATA | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | | | | | | |
| eSATA port | None | | | | | | | | | | | | | | | | |
| Media reader | 9-in-1 media reader, internal USB 2.0 | | | | | | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | | | | | | |
| Keyboard | Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo | | | | | | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | | | | | | |
| Floor Stand | None | | | | | | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.9" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access | | | | | | | | | | Security | | | | | | |
| Bay | <p>Bay 1: 5.25", 1.6" high, access, std optical</p> <p>Bay 2: 3.5", 1" high, no access, std disk</p> <p>Bay 3: 1.5", .35" high, access, opt reader*</p> <p>*bay only available on models with media reader installed</p> | | | | | | | | | | <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement | | | | | | |
| Slot | <p>Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max)</p> <p>Slot 2: Low Profile, PCIe 2.0 x1</p> <p>Slot 3: Low Profile, PCIe 2.0 x1</p> | | | | | | | | | |  | | | | | | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | RoHS-compliant | | | Supports ThinkVantage Technologies | | |


See footnotes for important warranty information
 WE model(s) announced October 23 or November 20, 2012
 WE models withdrawn effective May 2014

©Lenovo
 (G-TAPI1-5) May 2014

ThinkCentre Edge 72 Small (3493) - TopSeller (Win 8) - II

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^a | SATA disk GB rpm | SATA optical | Graphics | PCIe Mini Card | Blue-tooth | Media reader | Parallel port | Serial port | Floor stand | Global | Keyboard | Preload | Ann date (mm/dd/yy) |
|------------|------------|-----------|---------------------|------------------|--------------|----------|----------------|------------|--------------|---------------|-------------|-------------|--------|----------|------------|---------------------|
| 3493-HFG | 3x3 | G2020 | 4GBx1 | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Slim | Win7 Pro64 | 03/05/13 |
| 3493-HJG | 3x3 | G2020 | 4GBx1 | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Full | Win7 Pro64 | 03/05/13 |
| 3493-HKG | 3x3 | G2120 | 4GBx1 | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Slim | Win7 Pro64 | 03/05/13 |
| 3493-HLG | 3x3 | G2020 | 4GBx1 | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Slim | Win8 64 | 03/05/13 |
| 3493-K9G | 3x3 | G2130 | 4GBx1 | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Slim | Win7 Pro64 | 05/28/13 |
| 3493-KAG | 3x3 | i3-3240 | 4GBx1 | 500G 7200 | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Slim | Win7 Pro64 | 05/28/13 |
| 3493-KBG | 3x3 | i3-3240 | 4GBx1 | 500G 7200 | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Full | Win7 Pro64 | 05/28/13 |
| 3493-KPG | 3x3 | G2030 | 4GBx1 | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Slim | Win8 64 | 06/11/13 |
| 3493-KQG | 3x3 | G2030 | 4GBx1 | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Slim | Win7 Pro64 | 06/11/13 |
| 3493-KRG | 3x3 | G2030 | 4GBx1 | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Full | Win7 Pro64 | 06/11/13 |
| 3493-L5G | 3x3 | i5-3470S | 4+2GB | 128G SSD | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Slim | Win7 Pro64 | 06/25/13 |
| 3493-L6G | 3x3 | G2030 | 4GBx1 | 500G 7200 | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | None | Slim | Win8 64 | 07/09/13 |
| 3493-MDG | 3x3 | i5-3330S | 4GBx1 | 500G 7200 | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Full | Win7 Pro64 | 09/03/13 |
| 3493-MHG | 3x3 | i5-3330S | 4GBx1 | 128G SSD | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | None | Full | Win7 Pro64 | 09/03/13 |

| | | | | | | | | | | | | | | | | |
|--------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | | Preloaded operating system | | | | |
| Processor | Intel® Pentium® G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache) , integrated Intel HD Graphics, 1333MHz dual-channel DDR3 memory controller Intel Pentium G2030 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache) , integrated Intel HD Graphics, 1333MHz dual-channel DDR3 memory controller Intel Pentium G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache) , integrated Intel HD Graphics, 1600MHz dual-channel DDR3 memory controller Intel Pentium G2130 Processor (2 cores / 2 threads, 3.2GHz, 3MB cache) , integrated Intel HD Graphics, 1600MHz dual-channel DDR3 memory controller Intel Core™ i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache) , integrated Intel HD Graphics 2500, 1600MHz dual-channel DDR3 memory controller Intel Core i5-3330S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache) , Turbo Boost 2.0 (3.2GHz), Intel HD 2500 Graphics, 1600MHz DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache) , Turbo Boost 2.0 (3.6GHz), Intel HD 2500 Graphics, 1600MHz DDR3 memory controller | | | | | | | | | | | Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 64-bit | | | | |
| Implementation | Processor in LGA1155 socket | | | | | | | | | | | Preloaded applications (only some listed) | | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i> | | | | | | | | | | | - Windows 7 models <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Power Manager • ThinkVantage Communication Utility • Lenovo® Message Center Plus • Lenovo SimpleTap • Adobe® Reader® • Windows Live™ Essentials • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) | | | | |
| Graphics | Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i> | | | | | | | | | | | - Windows 8 models <ul style="list-style-type: none"> • Lenovo Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Norton™ Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Intel Small Business Advantage • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) | | | | |
| DP dongle | None | | | | | | | | | | | - All models | | | | |
| Disk | Hard Disk Drive (SATA 3.0Gb/s 7200 rpm) or Solid State Drive (SSD) | | | | | | | | | | | <ul style="list-style-type: none"> • ThinkVantage System Update • Lenovo Solution Center • View Management Utility • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Skype™ | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | | | | | |
| Onboard SATA | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | | | | | |
| eSATA port | None | | | | | | | | | | | | | | | |
| Media reader | 9-in-1 media reader, internal USB 2.0 | | | | | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | | | | | |
| Keyboard | Some: Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Some: Lenovo Slim USB Keyboard (USB connector), black, Lenovo logo | | | | | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | | | | | |
| Floor Stand | None | | | | | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.9" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access | | | | | | | | | | |  | | | | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, opt reader (bay 3 only comes with opt media reader) | | | | | | | | | | | | | | | |
| Slot | Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1 | | | | | | | | | | | | | | | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | | Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement | | | | |
| | | | | | | | | | | | | RoHS-compliant | | | | |
| | | | | | | | | | | | | Supports ThinkVantage Technologies | | | | |


See footnotes for important warranty information
 WE model(s) announced March 5, May 28, June 11, June 25, July 9, or September 3, 2013
 WE models withdrawn effective May 2014

ThinkCentre Edge 72 Tower (3485) - TopSeller

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ⁸ | SATA disk GB rpm | 2nd Disk Bay | SATA optical | Graphics | PCIe Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Global Keyboard | Preload | Ann date (mm/dd/yy) | |
|------------|------------|-----------|---------------------|------------------|--------------|--------------|----------|---------------------|------------|--------------|---------------|-------------|-----------------|---------|---------------------|----------|
| 3485-H7G | 3x3 | G2020 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Full | None | 03/12/13 |

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year limited warranty

| | | | | | | | | | | | | | | |
|--------------------|---|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | | Preloaded operating system | | |
| Processor | Intel® Pentium® G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache) , integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket | | | | | | | | | | | No operating system | | |
| Implementation | Processor in LGA1155 socket | | | | | | | | | | | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i> | | | | | | | | | | | | | |
| Graphics | Intel HD Graphics in processor, uses main memory, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i> | | | | | | | | | | | | | |
| DP dongle | None | | | | | | | | | | | | | |
| Disk | SATA 3.0Gb/s 7200 rpm | | | | | | | | | | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | | | |
| Onboard SATA | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | | | |
| eSATA port | None | | | | | | | | | | | | | |
| Media reader | 9-in-1 media reader, internal USB 2.0 | | | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | | | |
| IEEE 1394 | None | | | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | | | |
| Modem | None | | | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | | | |
| Keyboard | Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo | | | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 399mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access | | | | | | | | | | | | | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 1.5", .35" high, access, opt reader* Bay 3: 3.5", 1" high, no access, std disk *bay only available on models with media reader installed | | | | | | | | | | | | | |
| Slot | Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 | | | | | | | | | | |  | | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | | Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement | | |
| | | | | | | | | | | | | RoHS-compliant | | |
| | | | | | | | | | | | | Supports ThinkVantage Technologies | | |

See footnotes for important warranty information
 WE model(s) announced March 12, 2013
 WE models withdrawn effective May 2014


©Lenovo
 (G-TAPI1-8) May 2014

ThinkCentre Edge 72 Tower (3484) - TopSeller

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^a | SATA disk GB rpm | 2nd Disk Bay | SATA optical | Graphics | PCIe Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Global | Win7 preload | Ann date (mm/dd/yy) |
|------------|------------|-----------|---------------------|------------------|--------------|--------------|----------|---------------------|------------|--------------|---------------|-------------|--------|--------------|---------------------|
| 3484-FMG | 3x3 | G640 | 2GBx1 1600MHz | 250G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Pro 64 | 06/19/12 |
| 3484-FNG | 3x3 | G850 | 2GBx1 1600MHz | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Pro 64 | 06/19/12 |
| 3484-FPG | 3x3 | i3-2120 | 2GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2000 | None | None | Media | Parallel | Serial | None | Pro 64 | 06/19/12 |
| 3484-FQG | 3x3 | i3-2120 | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2000 | None | None | Media | Parallel | Serial | None | Pro 64 | 06/19/12 |
| 3484-CTG | 3x3 | G640 | 2GBx1 1600MHz | 500G 7200 | None | DVD±RW | Intel HD | None | None | None | Parallel | None | None | Prem 64 | 08/21/12 |
| 3484-CUG | 3x3 | i3-2120 | 2GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2000 | None | None | None | Parallel | None | None | Prem 64 | 08/21/12 |

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year limited warranty

| | | | | | | | | | | | | | | | |
|--------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | Preloaded operating system | | | | |
| Processor | Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G850 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket | | | | | | | | | | Some: Genuine Windows® 7 Professional 64 Some: Genuine Windows 7 Home Premium 64 | | | | |
| Implementation | | | | | | | | | | | Ready to install applications (only some listed) | | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i> | | | | | | | | | | • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) | | | | |
| Graphics | Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i> | | | | | | | | | | • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) | | | | |
| DP dongle | None | | | | | | | | | | | | | | |
| Disk | SATA 3.0Gb/s 7200 rpm | | | | | | | | | | | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | | | | |
| Onboard SATA | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | | | | |
| eSATA port | None | | | | | | | | | | | | | | |
| Media reader | Some: 9-in-1 media reader, internal USB 2.0 | | | | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | | | | |
| IEEE 1394 | None | | | | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | | | | |
| Modem | None | | | | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | | | | |
| Keyboard | Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo | | | | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 399mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access | | | | | | | | | |  | | | | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 1.5", .35" high, access, opt reader* Bay 3: 3.5", 1" high, no access, std disk *bay only available on models with media reader installed | | | | | | | | | | | | | | |
| Slot | Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 | | | | | | | | | | | | | | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement | | | | |
| | | | | | | | | | | | RoHS-compliant | | | | |
| | | | | | | | | | | | Supports ThinkVantage Technologies | | | | |

See footnotes for important warranty information
 WE model(s) announced June 19 or August 21, 2012
 WE models withdrawn effective May 2014


©Lenovo
 (G-TAPI1-3) May 2014

ThinkCentre Edge 72 Tower (3484) - TopSeller - II

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^o | SATA disk GB rpm | 2nd Disk Bay | SATA optical | Graphics | PCIe Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Global Keyboard | Preload | Ann date (mm/dd/yy) | |
|------------|------------|-----------|---------------------|------------------|--------------|--------------|----------|---------------------|------------|--------------|---------------|-------------|-----------------|---------|---------------------|----------|
| 3484-FRG | 3x3 | i5-3470S | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | Pro 64 | 06/19/12 |
| 3484-KJG | 3x3 | G2020 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Slim | None | 03/12/13 |
| 3484-KKG | 3x3 | G2020 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Full | None | 03/12/13 |
| 3484-KLG | 3x3 | i3-3220 | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | None | 03/26/13 |
| 3484-KMG | 3x3 | i5-3470S | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | None | 03/26/13 |
| 3484-L3G | 3x3 | i3-3240 | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | None | 05/28/13 |
| 3484-LAG | 3x3 | G2030 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Slim | None | 06/11/13 |
| 3484-LBG | 3x3 | G2030 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Full | None | 06/11/13 |
| 3484-LHG | 3x3 | i5-3470S | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Full | None | 06/11/13 |
| 3484-LJG | 3x3 | i3-3240 | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Full | None | 06/11/13 |
| 3484-LZG | 3x3 | i5-3330S | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | None | 09/03/13 |
| 3484-N1G | 3x3 | i5-3330S | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Full | None | 09/03/13 |

| | | |
|--------------------|--|---|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | Preloaded operating system <i>Some:</i> No operating system <i>Some:</i> Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Power Manager ThinkVantage Communication Utility View Management Utility Lenovo Solution Center Lenovo Message Center Plus Lenovo SimpleTap Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ for Windows Windows Live™ Essentials Microsoft® Office preloaded; purchase a product key to activate Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW) |
| Processor | Intel® Pentium® G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache) , integrated Intel HD Graphics, 1333MHz dual-channel DDR3 memory controller Intel Pentium G2030 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache) , integrated Intel HD Graphics, 1333MHz dual-channel DDR3 memory controller Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache) , integrated Intel HD Graphics 2500, 1600MHz dual-channel DDR3 memory controller Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache) , integrated Intel HD Graphics 2500, 1600MHz dual-channel DDR3 memory controller Intel Core i5-3330S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache) , Turbo Boost 2.0 (3.2GHz), Intel HD 2500 Graphics, 1600MHz DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache) , Turbo Boost 2.0 (3.6GHz), Intel HD 2500 Graphics, 1600MHz DDR3 memory controller Processor in LGA1155 socket | |
| Implementation | Processor in LGA1155 socket | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i> | |
| Graphics | Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i> | |
| DP dongle | None | |
| Disk | SATA 3.0Gb/s 7200 rpm | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | |
| Onboard SATA | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | |
| eSATA port | None | |
| Media reader | 9-in-1 media reader, internal USB 2.0 | |
| Chipset | Intel H61 Express Chipset | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | |
| PCIe WLAN | None | |
| Bluetooth | None | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | |
| Speaker | Internal speaker for business audio | |
| IEEE 1394 | None | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | |
| Intel AMT | None | |
| Modem | None | |
| Security chip | None | |
| Keyboard | <i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Lenovo Slim USB Keyboard (USB connector), black, Lenovo logo | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | |
| Power supply | 180 watts, universal, manual switch | |
| Machine | <ul style="list-style-type: none"> Glossy black bezel; metal case 6.3" W X 15.7" D X 15.6" H (with handle) 160mm W X 399mm D X 397mm H 16.5 lb (7.5 kg) in maximum configuration Ergonomic rubberized handle Highlighted optical drive button for easy access | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 1.5", .35" high, access, opt reader* Bay 3: 3.5", 1" high, no access, std disk *bay only available on models with media reader installed | |
| Slot | Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | |



- Security**
- One lock to secure both cover and entire system to fixed object:
 - Padlock loop (in rear for opt padlock)
 - Security slot (in rear for optional Kensington® MicroSaver® cable)
 - Power-on password
 - Administrator password
 - Hard disk password
 - Boot sequence control
 - Boot without keyboard and mouse
 - Individual USB port disablement

RoHS-compliant
Supports ThinkVantage Technologies

See footnotes for important warranty information


WE model(s) announced June 19, 2012 or March 12, March 26, May 28, June 11, or September 3, 2013
WE models withdrawn effective May 2014

©Lenovo
(G-TAPI1-4) May 2014

ThinkCentre Edge 72 Tower (3484) - TopSeller (Win 8)

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^a | SATA disk GB rpm | 2nd Disk Bay | SATA optical | Graphics | PCIe Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Global | Preload | Ann date (mm/dd/yy) |
|------------|------------|-----------|---------------------|------------------|--------------|--------------|----------|---------------------|------------|--------------|---------------|-------------|--------|------------|---------------------|
| 3484-BAG | 3x3 | G645 | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Win8 Pro64 | 10/23/12 |
| 3484-BBG | 3x3 | G870 | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Win8 Pro64 | 10/23/12 |
| 3484-BCG | 3x3 | i3-3220 | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Win8 Pro64 | 10/23/12 |
| 3484-BDG | 3x3 | i3-3220 | 4GBx1 1600MHz | 1TB 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Win8 Pro64 | 10/23/12 |
| 3484-BEG | 3x3 | i5-3570S | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Win8 Pro64 | 10/23/12 |
| 3484-GEG | 3x3 | i3-2130 | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2000 | None | None | Media | Parallel | Serial | None | Win8 Pro64 | 10/23/12 |
| 3484-CZG | 3x3 | G645 | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Win7 Pro64 | 10/23/12 |
| 3484-DAG | 3x3 | G870 | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Win7 Pro64 | 10/23/12 |
| 3484-DBG | 3x3 | i3-3220 | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Win7 Pro64 | 10/23/12 |
| 3484-DCG | 3x3 | i3-3220 | 4GBx1 1600MHz | 1TB 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Win7 Pro64 | 10/23/12 |
| 3484-DDG | 3x3 | i5-3470S | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Win7 Pro64 | 10/23/12 |
| 3484-DUG | 3x3 | i3-2130 | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2000 | None | None | Media | Parallel | Serial | None | Win7 Pro64 | 11/20/12 |
| 3484-HMG | 3x3 | i5-3470S | 4GBx1 1600MHz | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Win8 Pro64 | 12/04/12 |

| | | | | | | | | | | | | | | | |
|--|---|--|--|--|--|--|--|--|--|--|---|--|--|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | Preloaded operating system | | | | |
| Processor | Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1066MHz) Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated DDR3 memory controller (up to 1333MHz) Intel Core i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz) Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology | | | | | | | | | | Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Power Manager • ThinkVantage Communication Utility • Lenovo® Message Center Plus • Lenovo SimpleTap • Adobe® Reader® • Windows Live™ Essentials • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none"> • Lenovo Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Norton™ Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Intel Small Business Advantage • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none"> • ThinkVantage System Update • Lenovo Solution Center • View Management Utility • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Skype™ | | | | |
| Implementation | Processor in LGA1155 socket | | | | | | | | | | | | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i> | | | | | | | | | | | | | | |
| Graphics | Intel HD Graphics, Intel HD Graphics 2000, or Intel HD Graphics 2500 in processor, uses main memory, one VGA, one DVI-D, supports dual independent display <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i> | | | | | | | | | | | | | | |
| DP dongle | None | | | | | | | | | | | | | | |
| Disk | SATA 3.0Gb/s 7200 rpm | | | | | | | | | | | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | | | | |
| Onboard SATA | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | | | | |
| eSATA port | None | | | | | | | | | | | | | | |
| Media reader | 9-in-1 media reader, internal USB 2.0 | | | | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | | | | |
| Keyboard | Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo | | | | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 399mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access | | | | | | | | | |  | | | | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 1.5", .35" high, access, opt reader* Bay 3: 3.5", 1" high, no access, std disk *bay only available on models with media reader installed | | | | | | | | | | | | | | |
| Slot | Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 | | | | | | | | | | | | | | |
| Limited Warranty | 1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | | | | | |
| Security | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> - Padlock loop (in rear for opt padlock) - Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement | | | | | | | | | | | | | | | |
| RoHS-compliant | | | | | | | | | | | | | | | |
| Supports ThinkVantage Technologies | | | | | | | | | | | | | | | |

See footnotes for important warranty information

WE model(s) announced October 23, November 20, or December 4, 2012


WE models withdrawn effective May 2014

©Lenovo
(G-TAPI-6) May 2014

ThinkCentre Edge 72 Tower (3484) - TopSeller (Win 8) - II

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^a | SATA disk GB rpm | 2nd Disk Bay | SATA optical | Graphics | PCIe Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Global Keyboard | Preload | Ann date (mm/dd/yy) | |
|------------|------------|-----------|---------------------|------------------|--------------|--------------|----------|---------------------|------------|--------------|---------------|-------------|-----------------|---------|---------------------|----------|
| 3484-JPG | 3x3 | G2020 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 03/05/13 |
| 3484-JQG | 3x3 | G2020 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 03/05/13 |
| 3484-JRG | 3x3 | G2020 | 4GBx1 | 1TB 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 03/05/13 |
| 3484-JSG | 3x3 | G2020 | 4GBx1 | 1TB 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 03/05/13 |
| 3484-JTG | 3x3 | G2120 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 03/05/13 |
| 3484-JUG | 3x3 | G2120 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 03/05/13 |
| 3484-JVG | 3x3 | i5-3470S | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 03/05/13 |
| 3484-JWG | 3x3 | i5-3470S | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 03/05/13 |
| 3484-JYG | 3x3 | i5-3470S | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 7450 | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 03/05/13 |
| 3484-JZG | 3x3 | i5-3470S | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 7450 | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 03/05/13 |

| | | | | | | | | | | | | | | | |
|--------------------|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | Preloaded operating system | | | | |
| Processor | Intel® Pentium® G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache) , integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache) , integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache) , Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket | | | | | | | | | | Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager | | | | |
| Implementation | | | | | | | | | | | Preloaded applications (only some listed) | | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i> | | | | | | | | | | <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo Simple Tap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) | | | | |
| Graphics | <i>Some:</i> Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution:</i> 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz <i>Some:</i> AMD Radeon™ HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort™, 25 watts; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors | | | | | | | | | | | | | | |
| DP dongle | None | | | | | | | | | | | | | | |
| Disk | SATA 3.0Gb/s 7200 rpm | | | | | | | | | | | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | | | | |
| Onboard SATA | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | | | | |
| eSATA port | None | | | | | | | | | | | | | | |
| Media reader | 9-in-1 media reader, internal USB 2.0 | | | | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | | | | |
| Keyboard | <i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Lenovo Slim USB Keyboard (USB connector), black, Lenovo logo | | | | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 399mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access | | | | | | | | | |  | | | | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 1.5", .35" high, access, opt reader* Bay 3: 3.5", 1" high, no access, std disk *bay only available on models with media reader installed | | | | | | | | | | | | | | |
| Slot | Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 | | | | | | | | | | | | | | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | | | | | |
| | | | | | | | | | | Security | | | | | |
| | | | | | | | | | | <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement | | | | | |
| | | | | | | | | | | RoHS-compliant | | | | | |
| | | | | | | | | | | Supports ThinkVantage Technologies | | | | | |


See footnotes for important warranty information
 WE model(s) announced March 5, 2013
 WE models withdrawn effective May 2014

©Lenovo
 (G-TAPI1-7) May 2014

ThinkCentre Edge 72 Tower (3484) - TopSeller (Win 8) - III

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^a | SATA disk GB rpm | 2nd Disk Bay | SATA optical | Graphics | PCle Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Global Keyboard | Preload | Ann date (mm/dd/yy) | |
|------------|------------|-----------|---------------------|------------------|--------------|--------------|----------|---------------------|------------|--------------|---------------|-------------|-----------------|---------|---------------------|----------|
| 3484-L4G | 3x3 | i3-3240 | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 05/28/13 |
| 3484-L5G | 3x3 | i3-3240 | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 05/28/13 |
| 3484-L6G | 3x3 | i3-3240 | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 05/28/13 |
| 3484-L7G | 3x3 | i3-3240 | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 05/28/13 |
| 3484-L8G | 3x3 | G2130 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 05/28/13 |
| 3484-L9G | 3x3 | G2130 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 05/28/13 |
| 3484-LCG | 3x3 | G2030 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 06/11/13 |
| 3484-LDG | 3x3 | G2030 | 4GBx1 | 500G 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 06/11/13 |
| 3484-LEG | 3x3 | G2030 | 4GBx1 | 1TB 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 06/11/13 |
| 3484-LFG | 3x3 | G2030 | 4GBx1 | 1TB 7200 | None | DVD±RW | Intel HD | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 06/11/13 |

| | | | | | | | | | | | | | | | |
|-------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | Preloaded operating system | | | | |
| Processor | Intel® Pentium® G2030 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache) , integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2130 Processor (2 cores / 2 threads, 3.2GHz, 3MB cache) , integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache) , integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Processor in LGA1155 socket | | | | | | | | | | Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager | | | | |
| Implementation | Processor in LGA1155 socket | | | | | | | | | | Preloaded applications (only some listed) | | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i> | | | | | | | | | | <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo Simple Tap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) | | | | |
| Graphics | Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA) @60Hz; 1920x1200 (DVI-D) @60Hz</i> | | | | | | | | | | | | | | |
| DP dongle | None | | | | | | | | | | | | | | |
| Disk | SATA 3.0Gb/s 7200 rpm | | | | | | | | | | | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | | | | |
| Onboard SATA eSATA port | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | | | | |
| Media reader | None | | | | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | | | | |
| Keyboard | <i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Lenovo Slim USB Keyboard (USB connector), black, Lenovo logo | | | | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 399mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access | | | | | | | | | | | | | | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 1.5", .35" high, access, opt reader* Bay 3: 3.5", 1" high, no access, std disk *bay only available on models with media reader installed | | | | | | | | | |  | | | | |
| Slot | Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 | | | | | | | | | | | | | | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | | | | | |
| | | | | | | | | | | | Security | | | | |
| | | | | | | | | | | | <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement | | | | |
| | | | | | | | | | | | RoHS-compliant | | | | |
| | | | | | | | | | | | Supports ThinkVantage Technologies | | | | |


See footnotes for important warranty information
 WE model(s) announced May 28, 2013 or June 11, 2013
 WE models withdrawn effective May 2014

ThinkCentre Edge 72 Tower (3484) - TopSeller (Win 8) - IV

Product Specifications Reference (PSREF)

| Type-model | Slot x bay | Processor | Memory ^a | SATA disk GB rpm | 2nd Disk Bay | SATA optical | Graphics | PCe Mini Card WLAN | Blue-tooth | Media reader | Parallel port | Serial port | Global Keyboard | Preload | Ann date (mm/dd/yy) | |
|------------|------------|-----------|---------------------|------------------|--------------|--------------|----------|--------------------|------------|--------------|---------------|-------------|-----------------|---------|---------------------|----------|
| 3484-LPG | 3x3 | i5-3330S | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 09/03/13 |
| 3484-N2G | 3x3 | i5-3330S | 4GBx1 | 500G 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 09/03/13 |
| 3484-N4G | 3x3 | i5-3330S | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 09/03/13 |
| 3484-N5G | 3x3 | i5-3330S | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 2500 | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 09/03/13 |
| 3484-N6G | 3x3 | i5-3330S | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 7450 | None | None | Media | Parallel | Serial | None | Full | Win7 Pro64 | 09/03/13 |
| 3484-N7G | 3x3 | i5-3330S | 4GBx1 | 1TB 7200 | None | DVD±RW | HD 7450 | None | None | Media | Parallel | Serial | None | Slim | Win7 Pro64 | 09/03/13 |

• Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program

| | | | | | | | | | | | | | | | |
|--------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Positioning | <i>Stylish design, reliability, and productivity for small/medium businesses</i> | | | | | | | | | | | Preloaded operating system | | | |
| Processor | Intel® Core™ i5-3330S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology | | | | | | | | | | | Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit | | | |
| Implementation | Processor in LGA1155 socket | | | | | | | | | | | Ready to install applications (only some listed) | | | |
| Memory | 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i> | | | | | | | | | | | <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager | | | |
| Graphics | <i>Some: Intel HD Graphics 2500</i> in processor, uses main memory, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i> <i>Some: AMD Radeon™ HD 7450</i> , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort™, 25 watts; <i>Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz;</i> works along with Intel HD Graphics to support up to four independent monitors | | | | | | | | | | | Preloaded applications (only some listed) | | | |
| DP dongle | None | | | | | | | | | | | <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo Simple Tap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) | | | |
| Disk | SATA 3.0Gb/s 7200 rpm | | | | | | | | | | | | | | |
| Optical | Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive | | | | | | | | | | | | | | |
| SATA controller | Serial ATA, SATA 3.0Gb/s, integrated in chipset | | | | | | | | | | | | | | |
| Onboard SATA | Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar | | | | | | | | | | | | | | |
| eSATA port | None | | | | | | | | | | | | | | |
| Media reader | 9-in-1 media reader, internal USB 2.0 | | | | | | | | | | | | | | |
| Chipset | Intel H61 Express Chipset | | | | | | | | | | | | | | |
| Front ports | Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Rear ports | Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D | | | | | | | | | | | | | | |
| Rear audio ports | Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) | | | | | | | | | | | | | | |
| Internal connector | Three USB 2.0 planar conn (1 used; two open for additional USB devices) | | | | | | | | | | | | | | |
| PCIe WLAN | None | | | | | | | | | | | | | | |
| Bluetooth | None | | | | | | | | | | | | | | |
| Audio | High Definition (HD) Audio, Realtek® ALC662 codec | | | | | | | | | | | | | | |
| Speaker | Internal speaker for business audio | | | | | | | | | | | | | | |
| Ethernet | Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® | | | | | | | | | | | | | | |
| Intel AMT | None | | | | | | | | | | | | | | |
| Security chip | None | | | | | | | | | | | | | | |
| Keyboard | <i>Some: Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo</i> <i>Some: Lenovo Slim USB Keyboard (USB connector), black, Lenovo logo</i> | | | | | | | | | | | | | | |
| Mouse | Enhanced Optical USB Mouse, black, Lenovo logo | | | | | | | | | | | | | | |
| Power supply | 180 watts, universal, manual switch | | | | | | | | | | | | | | |
| Machine | <ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 399mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access | | | | | | | | | | | | | | |
| Bay | Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 1.5", .35" high, access, opt reader* Bay 3: 3.5", 1" high, no access, std disk *bay only available on models with media reader installed | | | | | | | | | | | | | | |
| Slot | Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 | | | | | | | | | | |  | | | |
| Limited Warranty | 1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available | | | | | | | | | | | Security | | | |
| | | | | | | | | | | | | <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement | | | |
| | | | | | | | | | | | | RoHS-compliant | | | |
| | | | | | | | | | | | | Supports ThinkVantage Technologies | | | |

See footnotes for important warranty information
 WE model(s) announced September 3, 2013
 WE models withdrawn effective May 2014

©Lenovo
 (G-TAPI1-11) May 2014