DOUBLE CONCENTRATE (DC) & TRIPLE CONCENTRATE (TC)

**** MATERIAL SAFETY DATA SHEET ****

SECTION 1 – PRODUCT INDENTIFICATION

TRADE NAME: ECURI Cosmetics **CODE:** Cosmetic Organic & Inorganic Colors **SUPPLIER:** ECURI Cosmetics B.V. Lisbaan 15 2908 LN Capelle aan den IJssel The Netherlands Tel.No.: +31 10 450 7790

DESCRIPTION

Purified colors are colorants manufactured for use in a variety of food, drug and cosmetic applications.

SECTION 2 – HAZARDS INDETIFICATION

EMERGENCY OVERVIEW:

CAUTION!

Vapors form from this product and may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static dischargers or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

SECTION 3 – COMPOSITION OF INGREDIENTS

This product is not considered to be an hazardous substance as defined under OSHA's Hazard Communication Standard (29 CFR 1910. 1200).

Refer to 'Ingredient Sheet' for the complete specific list of ingredients for color/shade. The main ingredients are as follows:

<u>Inorganic Pigments:</u> Iron Oxides, Glycerin, Isopropyl Alcohol, Purified Water (Aqua). May contain: Titanium Dioxide, Ultramarine Blue & Violet, Chromium Oxide Greens and Chromium Hydroxide Greens.



<u>Organic Pigments:</u> Iron Oxides, Glycerin, Isopropyl Alcohol, Purified Water (Aqua). May Contain: Titanium Dioxide, Ultramarine Blue & Violet, Chromium Oxide Greens and Chromium Hydroxide Greens, Certified D&C and FD&C Dyes. Refer to 'Ingredient Sheet' for specific Organic Ingredients listing.

<u>EINECS NUMBERS</u> MOLECULAR FORMULAS & CAS NUMBERS

EINECS No.: 215-185-5: Purified Water (Aqua) CAS No.: 7732-18-5 EINECS No.: 200-289-5: Glycerin CAS No.: 56-81-5 EINECS No.: 200-661-7: Isopropyl Alcohol CAS No.: 67-63-0 EINECS No.: 236-675-5: Titanium Dioxide (TiO₂O₄) CAS No.: 13463-67-7 EINECS No.: 235-442-5: Black Iron Oxide (Fe₃O₄) CAS No.: 12227-89-3 EINECS No.: 215-60-9: Carbon Black (D&C Black 2) CAS No.: 1333-86-4 EINECS No.: 215-168-2:Red Iron Oxide (Fe₂O₃) CAS No.: 1332-37-2 EINECS No.: 215-27-80: Yellow Iron Oxide (Fe₂O₃) CAS No.: 51274-00-1 EINECS No.: 215-160-9: Chromium Oxide Green (Cr₂O₃) CAS No.: 1308-38-9 EINECS No.: 215-160-9: Hydrated Chromium Oxide Green (Cr₃O₃.H₂O) CAS No.: 12001-99-9 EINECS No.: 309-92-83: Ultramarine Blue & Violet CAS No.: 12769-96-9; 57455-3735 EINECS No.: 215-27-80:Yellow Iron Oxide (Fe₂O₃) CAS No.: 51274-00-1 EINECS No.: 239-897-0: FD&C Blue No. 1 Aluminum Lake (C₃₇H₃₄N₂O₉S₃.Al) CAS No.: 15792-67-3 EINECS No.: 241-806-4: D&C Red No. 6 Barium Lake (C₁₈H₁₂N₂O₆SNa₂.Ba) CAS No.: 17852-98-1 EINECS No.: 231-754-4: Barium Sulfate CAS No.: 7727-43-7

EINECS No.: 231-820-9: Sodium Sulfate CAS No.: 7757-82-6 EINECS No.: 232-475-7: Rosin CAS No.: 8050-09-7 EINECS No.: 226-109-5: D&C Red No. 7 Calcium Lake (C₁₈H₁₂N₂O₆S.Ca) CAS No.: 5281-04-9; 8050-09-7 EINECS No.: 240-569-4: D&C Red No. 21 Aluminum Lake (C₂₀H₈O₅Br₄.Al) CAS No.: 15086-94-9 EINECS No.: 282-941-9: D&C Red No. 27 Aluminum Lake (C₂₀H₄O₅CI₄Br₄.Al) CAS No.: 84473-86-9; 15876-58-1 EINECS No.: 242-355-6: D&C Red No. 28 Aluminum Lake (C₂₀H₄O₅CI₄Br₄Na₂.Al) CAS No.: 18472-87-2 EINECS No.: 219-163-6: D&C Red No. 30 Aluminum Lake (C₁₈H₁₀O₂S₂CI₂) CAS No.: 2379-74-0 EINECS No.: 220-562-2: D&C Red No. 36 Aluminum Lake (C₁₆H₁ON₃O₃CI) CAS No.: 002814-77-9 EINECS No.: 271-524-7: FD&C Red No. 40 Aluminum Lake (C₁₈H₁₄N₂O₈S₂Na₂) CAS No.: 68583-95-9; 25956-17-6 EINECS No.: 235-428-9: FD&C Yellow No. 5 Aluminum Lake (C₁₆H₉N₄O₉S₂.Al) CAS No.: 12225-21-7 EINECS No.: 239-888-1: FD&C Yellow No. 6 Aluminum Lake (C₁₆H₁₀N₂O₇S₂.Al) CAS No.: 15790-07-5 EINECS No.: 285-989-9: D&C Yellow No. 10 Aluminum Lake (C18H9NO8S2.Al) CAS No.: 68814-04-0

*Triple Concentrate Pigments DO NOT contain Purified Water. Water percentage (%) applies into Glycerin.

SECTION 4 – FIRST AID MEASURES

GENERAL INFORMATION:

On the basis of Animal Toxicity Data this product is expected to be non-irritating to the eyes and skin and essentially non-toxic by ingestion.

EYE CONTACT:

Flush eyes thoroughly with large amounts of water, lifting lids periodically for at least fifteen minutes. Get medical attention if redness or irritation occurs.

SKIN CONTACT:

Not expected to be harmful. Wash skin thoroughly with soap and water. Remove severely contaminated clothing. Seek medical attention in the unlikely event that skin irritation occurs (redness etc.).



INHALATION:

Remove to fresh air. Get medical attention if breathing is difficult or lung irritation is present.

INGESTION:

Do not give anything by mouth to an unconscious person. Do not induce vomiting. Get immediate medical attention.

Please note that there has been no evidence of the health effects listed for this product, nor would it anticipate the occurrence of these health effects when the product is used under normal conditions.

conditions.

HUMAN HEALTH DATA

Primary Route(s) of Exposure: Eye Contact; Skin Contact; Inhalation

Human Effect and Symptoms of Overexposure:

<u>Acute</u>

On the basis of Animal Toxicity Data, **ECURI Cosmetics** expects this product to be nonirritating to the eyes and skin and essentially non-toxic by ingestion. However excessive exposure to airborne dust (*from pigment that has dried*) may reduce visibility and/or cause unpleasant deposits in the eyes, ears and nose. Injury to the skin or mucous membrane can occur by direct mechanical action or by rigorous skin cleaning necessary for removal of pigment.

<u>Other</u>

Prolonged inhalation (6 to 10 years) of iron oxide fume has been reported to produce changes in lung x-rays of exposed individuals. This condition, siderosis, is considered to be a benign pneumoconiosis that exhibits no adverse health effects. Siderosis has been observed among occupations such as arc-welders where iron oxide fumes are present. To the best of our knowledge, this condition has not been observed after prolonged exposure to iron oxide pigments.

Medical Conditions Aggraveted by Exposure

None known.

Carcinogenicity

- NTP: Not listed
- IARC: Not listed
- OSHA: Not listed
- Other: Based on information currently available, this product is not considered a carcinogen.

SECTION 5 – FIRE FIGHTING MEASURES

FLAMMABILITY DATA

Flash Point (°C) >24Flammable Limits:LEL: 2 Vol%UEL: 12 Vol%Autoignition Temperture:NDust Cloud Ignition Temperture:NDust Layer Ignition Temperture:N

No data No data No data

Extinguishing Media:

Suitable Extinguishing Media:

- Regular foam, carbon dioxide, dry chemical or alcohol resistant foam recommended.
- Apply water spray to cool exposed closed containers.

Special Fire-Fighting Procedures:

• NIOSH-approved Self-Contained Breathing Apparatus (SCBA) and full protective clothing/equipment recommended.

Special hazards arising from the substance or mixture:

Unusual Fire and Explosion Hazards:

• Flammable liquid and vapor.

Hazardous Combustion Product:

• Oxides of carbon and nitrogen, various hydrocarbons

NFPA H	IAZARD	RATINGS:
Uaalth	0	

Health – 0 Flammability – 1 Chemical Reactivity – 0

HMIS HAZARD RATINGS:

Health – 0 Flammability – 1 Chemical Reactivity – 0

HMIS & NFPA RATINGS:

0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions

Remove possible causes of ignition – Do not smoke. Keep away from heat, sparks, and flame. Ensure sufficient supply of air/ventilation. Avoid inhalation and contact with eyes and skin. Airborne *Organic* pigment dust (caused by drying of liquid pigment) may be an explosive hazard. Secure possible sources of ignition and avoid dusting.



Small Spill

For liquid pigments, collect using absorbent materials. Diluting with water is possible. Flush residue using copious water. For dry powder spills, inert materials such as sand may be added to control dusting prior to cleanup. Avoid excessive generation of dust. If dust is generated, use appropriate respiratory protection. Industrial grade vacuum sweepers are also recommended. Place spilled material into appropriate waste containers for disposal.

Large Spill

For liquid pigments, collect using absorbent materials. Diluting with water is possible. Flush residue using copious water. Dispose at suitable refuse site according to local and national official regulations. For dry powders, contain spilled material immediately with an inert substance such as sand or earth. Use plastic or aluminum shovel to transfer diluted waste material into appropriate containers for disposal. Materials, which cannot be recycled into your process, should be land filled in accordance with Federal, State and Local environmental control regulations.

SECTION 7 – HANDLING AND STORAGE

<u>Handling</u>

Provide adequate ventilation in storage area. Keep away from sources of ignition – Do not smoke. Keep away from heat, sparks, and flame. Keep container closed when not in use.

Storage

Store at 4° C to 32° C (40° F to 90° F) away from direct sources of heat or ignition. Avoid extreme temperatures. Empty containers may contain product residues and should be handled appropriately. Position containers so that any labeling information is visible.

Special Precautions & Storage Data:

Average Shelf Life: Up to 10 years when Unopened Usage After Open: Up to 12 months when Opened

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation:

Local Exhaust: None required Mechanical (General): Provide adequate ventilation.

Personal Protection

Eye Protection: Safety glasses. Wear approved safety glasses with side shields



Hand Protection:

Wear rubber gloves

Skin Protection:

Wear protective working garments (e.g. safety shoes, long-sleeved protective working garments). Launder contaminated clothing before reuse.

Respiratory Protection:

Liquid Pigment: None required in well-ventilated areas. *Raw Powders (should pigment dry to dust form)*: Use NIOSH approved respiratory protection where exposure levels exceed regulatory limits for hazardous components and/or for nuisance dust.

Exposure Limits

There are no ACGIH TLV's or OSHA PEL's established for this product. The OSHA PEL for nuisance dust is 15 mg/m3 (total dust), and 5 mg/m3 (respirable dust) recommended. The recommended ACGIH TLV for nuisance dust is 10 mg/m3.

SECTION 9 – PHYSICAL AND CHEMCIAL PROPERTIES

PHYSICAL APPEARANCE: Liquid COLOR: According to specification ODOR: Slight Alcoholic pH: 4-10 (water extract) pH-VALUE UNDILUTED: Not applicable RELATIVE DENSITY: Not applicable MELTING POINT: No data SPECIFIC GRAVITY: 4.5-5.2 SOLUBILITY: Mixable PERCENT VOLATILE: None VAPOR PRESSURE: Not applicable BOILING POINT: No data VOLATILE ORGANIC COMPOUNDS (VOC's) (EPA METHOD 24/24A): None

SECTION 10 – STABILITY AND REACTIVITY

GENERAL:

This product is a stable compound and hazardous polymerization will not occur. **CONDITIONS TO AVOID:**

Temperatures of 100° C (212°) or over will boil water away.

INCOMPATABILITY:

Avoid strong oxidizing agents such as peroxides, chlorates, perchlorates, nitrates and permanganates. Oxidizing materials may vigorously evolve oxygen in large amounts. Avoid heating, open flames, ignition sources and electrostatic charge.

HAZARDOUS DECOMPOSITION PRODUCTS:

When involved in a fire, decomposition on burning of pigments may evolve noxious gases, which are toxic. These compounds may include carbon monoxide, carbon dioxide, nitrous oxides or hydrogen chloride, depending on the pigment type.

SECTION 11 – TOXICOLOGICAL INFORMATION

GENERAL

Based upon industry-wide experience over many years of manufacturing and published toxicological studies, cosmetic pigments in general are considered to have low levels of toxicity. There is no evidence of harmful effects from available information.

There are no established permissible exposure limits for this product.

ACUTE (SHORT-TERM) TOXICITY

Skin contact: May cause minor irritation with itching and possible slight local redness.Prolonged or repeated contact may cause drying of the skin. No evidence of harmful effects from available information.

Eye contact: Accidental <u>Direct Eye Contact</u> may cause abrasion and irritation. Corneal injury may occur.

Inhalation: Not expected to be an inhalation hazard. However, high concentrations of vapor may cause irritation of the respiratory tract with coughing and chest discomfort. May also cause headache and drowsiness. Excessive levels of fumes may result in discomfort after repeated or prolonged exposures.

Ingestion: Maybe harmful if swallowed. Contact Physician Immediately.

CHRONIC (LONG-TERM TOXICITY)

No known published data available and no adverse effects expected.

Sensitization: Data not established for this product

Chronic Toxicity: Data not established for this product

Reproductive Toxicity: Data not established for this product

MUTAGENICITY

No mutagenic effects known or expected.

Toxicological tests performed on chemically identical products.

SECTION 12 – ECOLOGICAL INFORMATION

This product has not been evaluated for its ecotoxicity. However, the biodegradation of *Organic & Inorganic* colorants under aerobic conditions is expected to be poor and there is no evidence to suggest they create any significant ecological problems when released into the environment. Since *Organic & Inorganic* pigments are generally insoluble compounds, they are believed to have minimal bioaccumulation and bioavailability characteristics.

SECTION 13 – DISPOSAL CONSIDERATIONS

<u>General</u>

This product must be disposed of in accordance with all applicable Federal, State and local regulations. If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste (40 CFR 261.20-24).

In the cases of spills, leaks or release, review sections: 'FIRE FIGHTING MEASURES'; 'ACCIDENTAL RELEASE MEASURES' & 'EXPOSURE CONTROLS/PERSONAL PROTECTION'

Waste Management

- Incineration or land filling are recommended disposal techniques. Contact the state and local environmental agency for specific rules.
- This product is not identified as a RCRA hazardous waste under 40 CFR 261, and is not regulated under CERCLA (Superfund).

D.O.T. SHIPPING NAME (49 CFR 172.101-102)	: Not regulated
D.O.T. HAZARD CLASS (49 CFR 172.101-102)	: None
D.O.T. LABEL	: None
D.O.T. PLACARD	: None
BILL OF LADING DESCRIPTION	: Pigments NOI Dry
CERCLA SUBSTANCE (49 CFR)	: Not regulated
REPORTABLE QUANTITY (RQ)	: None



INTERNATIONAL UN/NA NUMBER IMDG/IACO CLASSIFICATION IATA CLASSIFICATION

: Not regulated

- : Not regulated
- : Not regulated

SECTION 15 – REGULATORY INFORMATION

OSHA Hazard Communication Standard Status

This product is not considered to be a hazardous substance under OSHA's Federal Hazard Communication Standard 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA) Status

All of the ingredients of this material have been reported to the U.S. EPA and are included in the TSCA chemical inventory.

SARA Title III

Section 302 (EHS) : None Section 311/312 (Acute) : None

<u>RCRA</u>

Not regulated as a hazardous waste under RCRA.

Supplemental State Compliance Information

California State: Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

Warning: This product may contain such chemicals as Lead (Pb); Arsenic (As); Mercury (Hg); Chromium Extract (2% HaOH); Antimony (Sb), Beryllium (Be), Cobalt (Co), Nickel (Na) and Selenium (Se) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm. This product is considered to have no significant risk under the *safe harbor levels* pursuant to the Proposition 65 Safe Harbor Levels.

While this product may contain detectable amounts of the above listed chemicals, we can assure you our products meet all the Federal requirements under the Food, Drug and Cosmetic Act for safety and effectiveness.

SECTION 16 – OTHER INFORMATION

Updated-September 2014

The information and recommendations contained herein is based on data considered accurate and has been complied from sources believed to be reliable and represent the most reasonable opinion on the subject when the MSDS was prepared. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. **ECURI Cosmetics** assumes no responsibility for the personal injury or property damage caused by the material. Users assume all risks associated with the use of the material.

Important Notice: The information presented herein is based on experimental data submitted by the manufacturers of the raw materials and is considered scientifically correct; however, no warrant or representation, express or implied, is made as to the accuracy or suitability of this information for application to the purchaser's intended purpose or for consequences of its use and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of its use. Use these materials only as directed. If you have any questions regarding the proper interpretation of this sheet or the meanings of any terms used, we strongly urge you to speak with your physician. For further information concerning product safety and proper use, call the number listed on the front of the MSDS.

ECURI COSMETICS

COLOR:

Super Strokes

Sensation XL-Brown

Ecuri Cosmetics

2908 LN - 15

Category: Inorganic Classification: Suspension Mixture

Capelle aan den Ijssel

	ICID (International Cosmetic Ingredient Dictionary)					
Ingredients	(INCI) Color Index Code	(INCI) Color Index Name	Chemical Analysis Safety CAS#	EINECS No.	CFR Section	Purpose
Sterile Water (Aqua)*	N/A	N/A	7732-18-5	231-791-2	N/A	Wetting Agent
Isopropyl Alcohol	N/A	N/A	67-63-0	200-661-7	N/A	Wetting Agent
Glycerin	N/A	N/A	56-81-5	200-289-5	N/A	Wetting Agent
Iron Oxide Red	77491	Pigment Red 101	1309-37-1	215-168-2	732250	Color Agent
Iron Oxide Yellow	77492	Pigment Yellow 42	51274-00-1	251-098-5	732250	Color Agent
Iron Oxide Black	77499	Pigment Black 11	12227-89-3	235-442-5	732250	Color Agent
Manganese Violet	77742	Pigment Violet 16	10101-66-3	233-257-4	73.2575	Color Agent
CONFIDENTIAL				For refer	ence 1156	only