









LOW VOLTAGE POWER SUPPLIES

Note: Tempo reserves the right to change or modify driver specifications and/or manufacturer without notification either due to inventory availability from third party vendors or as part of the company's continuing product improvement program.

12v Output Drivers				
Catalog Number	Description	Mfg	Mfg Part Number	Dimensions
PWR-120-EL-040-T 	120V AC Input 12V DC Output 40W Triac Dimming (to 1%)	Lutron	LTEA4U1UKN-AV120	3.00" (76mm) W 1.00" (25mm) H 4.90" (124mm) L
PWR-120-EL-040-T-1 	120V AC Input 12V DC Output 40W Triac Dimming (to 1%)	Lutron	LTEA4U1UMN-AV120	1.18" (30mm) W 1.00" (25mm) H 14.25" (362mm) L
PWR-UNV-EL-060 	120-277V AC Input 12V DC Output 60W Non-Dimming	Fulham	T1120012V-60LE	1.69" (43mm) W 1.22" (31mm) H 8.32" (211mm) L
PWR-UNV-EL-060-Z 	120-277V AC Input 12V DC Output 60W 0-10V Dimming (to <10%)	Fulham	T1M1UNV012V-60L	1.69" (43mm) W 1.22" (31mm) H 8.32" (211mm) L
12v Output Transformers				
PWR-T010012/2 	120V AC Input, 12V AC Output, 100W, 2 Circuit, Class II Magnetic, NEMA 3R Case	Sebco	1107	6.75" (171mm) H 5.0" (127mm) W 4.5" (114mm) D
PWR-T015012/2 	120V AC Input, 12V AC Output, 150W, 3 Circuit, Class II Magnetic, NEMA 3R Case	Sebco	1108	6.75" (171mm) H 5.0" (127mm) W 4.5" (114mm) D
PWR-T025012/2 	120V AC Input, 12V AC Output, 250W, 4 Circuit, Class II Magnetic, NEMA 3R Case	Sebco	1109	6.75" (171mm) H 5.0" (127mm) W 4.5" (114mm) D




LOW VOLTAGE POWER SUPPLIES

Note: Tempo reserves the right to change or modify driver specifications and/or manufacturer without notification either due to inventory availability from third party vendors or as part of the company's continuing product improvement program.

24v Output Drivers				
Catalog Number	Description	Mfg	Mfg Part Number	Dimensions
PWR-120-EM-040-T 	120V AC Input 24V DC Output 40W Triac Dimming (to 1%)	Lutron	LTEA4U1UKN-AV240	3.00" (76mm) W 1.00" (25mm) H 4.90" (124mm) L
PWR-120-EM-040-T-1 	120V AC Input 24V DC Output 40W Triac Dimming (to 1%)	Lutron	LTEA4U1UMN-AV240	1.18" (30mm) W 1.00" (25mm) H 14.25" (362mm) L
PWR-UNV-EM-060 	120-277V AC Input 24V DC Output 60W Non-Dimming	Fulham	T1UNV024V-60L	1.70" (43mm) W 1.21" (31mm) H 9.49" (241mm) L
PWR-UNV-EM-100 	120-277V AC Input 24V DC Output 100W Non-Dimming	Fulham	T1UNV024V-100LE	1.70" (43mm) W 1.21" (31mm) H 9.49" (241mm) L
PWR-UNV-EM-100-Z 	120-277V AC Input 24V DC Output 100W 0-10V Dimming (to <1%)	EPT	VD100-C41V24-UNV-P	2.30" (58mm) W 1.22" (31mm) H 7.50" (190mm) L
PWR-UNV-EM-100-Z-JB 	Plenum Rated 120-277V AC Input 24V DC Output 100W 0-10V dimming (to <1%)	Magtech	Q2-U24-LP	2.50" (64mm) W 1.70" (42mm) H 12.40" (314mm) L

LOW VOLTAGE POWER SUPPLIES

Note: Tempo reserves the right to change or modify driver specifications and/or manufacturer without notification either due to inventory availability from third party vendors or as part of the company's continuing product improvement program.

DMX & DALI Drivers				
Catalog Number	Description	Mfg	Mfg Part Number	Dimensions
PWR-UNV-EM-96-DMX 	120-277V AC Input 24V DC Output 96W DMX Dimming (dim to 0)	proprietary		2.52" (64mm) W 1.26" (32mm) H 9.61" (244mm) L
PWR-UNV-EM-100-N 	120-277V AC Input 24V DC Output 100W DMX & DALI Dimming	Fulham	T4N4UNV024V-100B	3.17" (81mm) W 1.20" (30mm) H 9.08" (229mm) L
<i>Discontinued - Consult Tempo for availability</i>				
PWR-UNV-EM-100-N-1 	120-277V AC Input 24V DC Output 100W DMX & DALI Dimming	Fulham	T4N4UNV024V-100K	11.62" (41mm) W 1.19" (30mm) H 14.56" (370mm) L
<i>Discontinued - Consult Tempo for availability</i>				