Holly Wall-mounted LED **Outdoor** Luminaire



Elegant in appearance, Holly is the perfect match for any wall

- Elegant and timeless design
- 3 different designs (round, square, can)
- Versions with up/downlight or only downlight available
- Zero uplight versions available to reduce light pollution
- Special designed back plate provides mounting flexibility
- Fast and easy installation thanks to a well positioned 3 pole terminal block





Sealed to IP65

for protected

applications

exterior



50 000 hours

lifetime



IK04 rated impact resistance

Ideal for...





Building facades


Residential


Special designed back plate provides more flexibility in mounting






Can version







Ordering guide

Description	SAP Code
HOLLY CONE ROUND DOWN IP65 300 830	96633683
HOLLY CONE ROUND UP/DOWN IP65 500 830	96633684
HOLLY CONE SQUARE DOWN IP65 300 830	96633685
HOLLY CONE SQUARE UP/DOWN IP65 500 830	96633686
HOLLY WALL CAN DOWN IP65 250 830	96633687


Installation/Mounting

- Fast and easy installation thanks to a well positioned 3 pole terminal block
- Special designed back plate provides more flexibility in mounting

Material/Finish

- Body: Aluminium die-cast RAL7016
- Front cover: clear glass

Light distribution






Holly DOWN cd/klm ULOR: 0% DLOR: 100%

LOR: 100%

- 250-500 lm
- 3000K
- Lifetime: 50000 hours rated life (@L80, Ta 25°C)
- CRI 80



±180

C 500 250

-150

750

-30


150

120

60

- ClassI electrical
- IP65
- IK04
- Ambient operating
 - temperature: -20 to +40 °C

Light output



*No light pollution, zero uplight

