

Xerox® WorkCentre® 7830i/7835i/ 7845i/7855i Color Multifunction Printer

The WorkCentre 7800i Series Color Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



System Specifications	WorkCentre 7830i	WorkCentre 7835i	WorkCentre 7845i	WorkCentre 7855i
Speed				
Color / Black-and-white	Up to 30 / 30 ppm	Up to 35 / 35 ppm	Up to 45 / 45 ppm	Up to 50 / 55 ppm
Monthly Duty Cycle ¹	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages
Recommended Average Monthly Print Volume ²	8,000 to 12,000 pages	10,000 to 15,000 pages	16,000 to 20,000 pages	18,000 to 22,000 pages
Hard Drive / Processor / Memory	Minimum 250 GB HDD / 1.2 GHz Dud	ıl-core / 2 GB system plus 1 GB page me	emory	
Connectivity	10/100/1000Base-T Ethernet, High-Sp	eed USB 2.0 direct print, Wi-Fi Direct with	Optional Xerox® USB Wireless Adapter	
Controller Features	Unified Address Book, Remote Control F	Panel, Online Support (accessed from the	user interface and print driver), Configurat	ion Cloning
Optional Controller	EFI™ Fiery® Network Server			
Copy and Print				
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up t	o 1200 x 2400 dpi		
First-print-out Time Color / Black-and-white	As fast as 9 / 7.7 seconds		As fast as 7.5 / 6.4 seconds	As fast as 7.1 / 5.9 seconds
Page Description Languages	Adobe® PostScript® 3™, Adobe® PDF v	ersion 1.7, PCL® 5c / PCL 6, XML Paper S	pecification (XPS®) (Optional)	
Print Features	Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring, Xerox® Color By Words			
Mobile Printing and Apps	Standard: Apple® AirPrint™, Mopria® Certified, QR Code App, Xerox® App Gallery App, @PrintByXerox App; Free Download: Xerox® Print Service Plug-in for Android™, Xerox® Mobile Link App; Optional: Xerox® Mobile Print, Xerox® Mobile Print Cloud, Xerox® Easy Translator Service			
Scan				
Standard Features	Destinations : Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; File Formats : PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features : Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearized PDF / PDF/A			
Optional Features	ConnectKey® for DocuShare®, Xerox® Scan to PC Desktop® SE and Professional, other solutions available through various Xerox Business Innovation Partners			
Standard Features	Internet Fax, Fax Build Job, Network S	erver Fax Enablement		
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax)			
Security				
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, AES 256-bit Encryption (FIPS 140-2 compliant), SHA-256 Hash Message Authentication, Common Criteria Certification (ISO 15408) (undergoing evaluation), Encrypted Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, TLS, SNMPv3, Audit Log, Access Controls, User Permissions			
Optional Features	McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET), Xerox® PrintSafe Software			
Accounting				
Standard Features	Xerox® Standard Accounting (Copy, Pr	rint, Scan, Fax, Email), Network Accounti	ng Enablement	
Optional Features	Equitrac Express®, Equitrac Office®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Business Innovation Partners			

Device Specifications					
Control Panel Languages	US English, International English, Inte Finnish, Turkish, Greek, Russian, Czech		nternational Spanish, Dutch, Brazilian Port Ian, Arabic	tuguese, Swedish, Norwegian, Danish,	
Accessories		<u>-</u>			
Optional	High Capacity Feeder (HCF) Envelope Tray (Replaces Tray 1) Integrated Office Finisher (optional with 7830i/7835i only) Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Professional Finisher Convenience Stapler (includes Work Surface) Smart Card Enablement Kit EFI™ Fiery® Network Server Walk up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit				
Xerox® Adaptable Accessibility Solution	This assistive, Section 508-compliant technology provides an alternative to the existing user interface on the multifunction printer, enabling wheelchair users and those who are blind or visually impaired to easily release their Secure Print jobs. These are jobs submitted with a PIN, that are held at the printer. Users can also easily program jobs for email, scanning and faxing. The Android™ tablet is attached to a rotatable bracket, giving wheelchair users easy, viewable accessibility. For the blind and visually impaired, a talkback feature is included, as well as increased magnification of the UI. In addition, the USB keyboard (included in the kit) is integrated with Common Access Card (CAC) solutions.				
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Device	e, this is an interface to third party a	ccess control devices, such as coin machir	nes and card readers.	
Electrical Requirements	'				
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A				
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 10 A				
Power Consumption	WorkCentre 7830i	WorkCentre 7835i	WorkCentre 7845i	WorkCentre 7855i	
Running (Average)	110V: 641 watts 220V: 643 watts	110V: 673 watts 220V: 691 watts	110V: 750 watts 220V: 764 watts	110V: 828 watts 220V: 862 watts	
Standby Mode	110V and 220V: 62 watts		110V: 98.6 watts 220V: 95.9 watts	110V: 85.7 watts 220V: 121 watts	
Low Power Mode	110V and 220V: 59 watts		110V and 220V: 80.5 watts	110V: 80 watts 220V: 94.6 watts	
Auto Off / Sleep mode	110V: 4.2 watts 220V: 4.8 watts (Default time to Sleep mode = 2 mins) 110V: 4.3 watts (Default time to Sleep mode = 2 mins)				
Warm-up	Time from power off to when services are displayed: WorkCentre 7830i/7835i: As fast as 157 seconds WorkCentre 7845i/7855i: As fast as 151 seconds				
Low Power Recovery	< 9 seconds				
Operating Environment					
Required Temperature Range	50° to 82° F (10° to 28° C)				
Required Relative Humidity	15% to 85%	1		1	
Sound Power Levels Operating Standby	6.5 LwAd (B) 3.5 LwAd (B)	6.5 LwAd (B) 3.4 LwAd (B)	6.6 LwAd (B) 3.6 LwAd (B)	6.8 LwAd (B) 3.6 LwAd (B)	
Sound Pressure Levels Operating Standby	54 LpAd (dBA) 16.5 LpAd (dBA)	54.3 LpAd (dBA) 16.5 LpAd (dBA)	55.7 LpAd (dBA) 18.5 LpAd (dBA)	55.8 LpAd (dBA) 18.5 LpAd (dBA)	
Dimensions and Weight	Width	Depth	Height	Weight	
Base Configuration	25.2 in. / 640 mm	27.5 in. / 699 mm	45.2 in. / 1,149.2 mm	334.2 lbs. / 151.9 kg	
	44.4 in. / 1,129 mm 27.5 in. / 699 mm 45.2 in. / 1,149 mm 348 lbs. / 158 kg				
With Integrated Office Finisher (7830i/7835i only)	65.6 in. / 1,666 mm 27.9 in. / 709 mm 45.2 in. / 1,149 mm 403 lbs. / 183 kg				
_	65.6 in. / 1,666 mm	27.9 in. / 709 mm	45.2 in. / 1,149 mm	403 lbs. / 183 kg	
(7830i/7835i only) With Office Finisher LX (with	65.6 in. / 1,666 mm 75.7 in. / 1,922 mm	27.9 in. / 709 mm 27.5 in. / 699 mm	45.2 in. / 1,149 mm 45.2 in. / 1,149 mm	403 lbs. / 183 kg 526 lbs. / 239 kg	

Certifications			
Certifications	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) ENERGY STAR® 2.0 EPEAT (United States) GOST NOM Apple® AirPrint™ 1.4 Certification Mopria® Certified Wi-Fi Direct Certification Blue Angel ECOLOGO® CE Mark Common Criteria (IEEE 2600.2 standard) (undergoing evaluation) Citrix® Certified WHQL IPv6 Ready Cerner MEDITECH SAP To view the latest list of certifications, go to www.xerox.com/OfficeCertifications	ations.	
Paper Handling	WorkCentre 7830i WorkCentre 7835i	WorkCentre 7845i	WorkCentre 7855i
Duplex Automatic Document Fee	der		
Capacity ³	110 sheets	130 sheets (Single-pass DAE	DF)
Speed	up to 70 image per minute black-and-white and color (simplex)	up to 80 images per minute black-and-white and color (simplex) / up to 133 images per minute black-and-white and color (duplex)	
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 lb. bond to 32 lb. bond / 60 to 128 gsm		
Bypass Tray			
Capacity ³	100 sheets		
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in. / 89 x 98 mm to 320 x 483 mm		
Weights	16 lb. bond to 110 lb. cover / 60 to 300 gsm		
Types	Bond Card Stock, Card Stock Reloaded Custom Envelopes Glossy Card Stock, Glossy Card Stock Reloaded Heavyweight Card Stock, Heavyweight Card Stock Reloaded, Heavyweight G Hole punched Labels Letterhead Lightweight, Lightweight Card Stock, Lightweight Card Stock Reloaded, Light Plain, Plain Reloaded Preprinted Recycled Transparencies		
	s) (Optional with WorkCentre 7830i/7835i only)		
Capacity ³ Sizes	Trays 1-4: 520 sheets each Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 182 r		
Weighte	Trays 2-4: Custom Sizes from 5.5 x 7.2 in. SEF to 12.6 x 18 in. SEF / 139.7 x	182 INM to 320 x 457.2 mm	
Weights Types	16 lb. bond to 140 lb. index / 60 to 256 gsm Bond		
2000	Card Stock, Card Stock Reloaded Custom Glossy Card Stock, Glossy Card Stock Reloaded Heavyweight Card Stock, Heavyweight Card Stock Reloaded, Heavyweight G Hole punched Labels Letterhead Lightweight, Lightweight Card Stock, Lightweight Card Stock Reloaded, Light Plain, Plain Reloaded Preprinted Recycled Transparencies		

High Capacity Tandem Tray (Total	3,140 sheets) (Available with all configurations)
Capacity ³	Tray 1: 520 sheets Tray 2: 520 sheets Tray 3: 867 sheets Tray 4: 1,133 sheets
Sizes	Tray 1: Custom Sizes from 5.5 \times 7.2 in. SEF to 11.7 \times 17 in. SEF / 140 \times 182 mm to 297 \times 432 mm Tray 2: Custom Sizes from 5.5 \times 7.2 in. SEF to 12.6 \times 18 in. SEF / 140 \times 182 mm to 320 \times 457.2 mm Trays 3-4: Standard Sizes: 8.5 \times 11 in. LEF / A4, JIS B5, Executive (7.25 \times 10.5 in.)
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm
Types	Bond Card Stock Custom Glossy Card Stock Hole punched Labels Letterhead Lightweight Card Stock, Lightweight Glossy Card Stock Plain Preprinted
High Capacity Feeder (HCF) (Option	onal)
Capacity ³	2000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. / A4 LEF
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm
Envelope Tray (Optional – Replace	s Tray 1)
Capacity ³	Up to 60 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm
Total Capacity	
Device Total Capacity ³	5,140 sheets
Finishing	
Output Trays (Standard)	
Stacking Trays³	Dual Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheets
Integrated Office Finisher (Option	al with 7830i/7835i)
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 256 gsm
Stapling	
	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher LX (Optional)	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher LX (Optional) Capacity³	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers)
<u> </u>	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
Capacity ³	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers) Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Capacity ³ Sizes	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers) Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) 8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm
Capacity³ Sizes Weights Multiposition Stapling Hole Punch (Optional) North America:	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers) Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) 8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm 16 lb. bond to 80 lb. cover / 60 to 256 gsm 50 sheets of 24 lb. bond / 90 gsm 2-3 Hole Punch
Capacity³ Sizes Weights Multiposition Stapling Hole Punch (Optional) North America: Europe:	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers) Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) 8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm 16 lb. bond to 80 lb. cover / 60 to 256 gsm 50 sheets of 24 lb. bond / 90 gsm 2-3 Hole Punch 2-4 Hole Punch
Capacity ³ Sizes Weights Multiposition Stapling Hole Punch (Optional) North America: Europe: Booklet Maker for Office Finisher	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers) Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) 8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm 16 lb. bond to 80 lb. cover / 60 to 256 gsm 50 sheets of 24 lb. bond / 90 gsm 2-3 Hole Punch 2-4 Hole Punch LX (Score/Crease, Saddle-stitch Staple) (Optional)
Capacity³ Sizes Weights Multiposition Stapling Hole Punch (Optional) North America: Europe:	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers) Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) 8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm 16 lb. bond to 80 lb. cover / 60 to 256 gsm 50 sheets of 24 lb. bond / 90 gsm 2-3 Hole Punch 2-4 Hole Punch
Capacity ³ Sizes Weights Multiposition Stapling Hole Punch (Optional) North America: Europe: Booklet Maker for Office Finisher Capacity ³	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers) Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) 8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm 16 lb. bond to 80 lb. cover / 60 to 256 gsm 50 sheets of 24 lb. bond / 90 gsm 2-3 Hole Punch 2-4 Hole Punch LX (Score/Crease, Saddle-stitch Staple) (Optional) 40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less) Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF

Professional Finisher (Optional)						
Capacity ³	Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled					
	Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 or 100 stapled sets of 11 x 17 in. / A3 / SRA3					
Sizes	7.2 x 7.2 in. to 12.6 x 19 in. / 182 x 18 8.0 x 7.2 in. to 11.7 x 17 in. / 203 x 18	3				
Weights	16 lb. bond to 80 lb. cover / 60 to 220	gsm				
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – Letter, Legal, Tabloid, A3, A4, B4 and B					
Hole Punch (Standard) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)					
Booklet Maker	Saddle-stitch 2 to 15 sheets (14 sheet Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, SRA3 sup	s of 90 gsm or less plus 1 sheet of 169 opported	gsm)			
Convenience Stapler (Optional – In	cludes Work Surface)					
Capacity³	50-sheet stapling 5,000 staples Requires a separate outlet					
Сору	WorkCentre 7830i	WorkCentre 7835i	WorkCentre 7845i	WorkCentre 7855i		
First-copy-out Time (Letter/A4-size, from Platen to Center Tray) (Color / Black-and-white)	As fast as 8.4 seconds / As fast as 8.2 seconds / As fast as 7.5 seconds / As fast as 7.1 seconds / As fast as 6.7 seconds As fast as 6.2 seconds As fast as 5.5 seconds					
Sides (input:output)	1-1, 1-2, 2-2, 2-1					
Quantity	1 to 9,999					
Resolution (max.)	Up to 600 x 600 dpi					
Reduction / Enlargement	Variable zoom from 25% to 400% in	1% increments				
Concurrency	Program-ahead to allow job to be initi	ated while initial job is processed (Copy	, Print, Fax and Scan)			
Copy Features	Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan) Annotation and Bates™ stamping (with color capability and font size adjustment) Author Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Transparencies					
Xerox® Copier Assistant®	Xerox® Copier Assistant® Software pro attached via the USB port, this softwa		interface touchscreen. Used in conjunc nification and easy PC keyboard access ssistant for free, visit www.xerox.com.			

Print	WorkCentre 7830i	WorkCentre 7835i	WorkCentre 7845i	WorkCentre 7855i
Print Resolution	Up to 1200 x 2400 dpi			
Print Features	Layout / Watermark N-up (up to 16 pages per sheet) Booklet layout Finishing Fit to new paper size Hold All Jobs Paper Selection by Attribute LAN Fax (requires optional Fax Kit) Sample Set Saved Job (color jobs can be printe Secure Print with Timed Deletion Special Pages (exception page pros Store and Recall Driver Settings	ution (Standard, Enhanced, High) er, Print ID in margins on first page onl	ges)	Hold All Jobs)
Print from USB	Allows walk-up printing from Type A Supports direct printing from comp Supported file formats: PDF, JPEG, Color jobs can be printed as monoc	uter via Type B USB port TIFF, PS, XPS4, PCL		
Operating Systems	Microsoft® Windows® XP SP3 (32-0 Windows Server 2003 SP2 R2 (32-0 Windows Server 2008 and R2 (32-0 Windows Server 2012 and R2 (64-0 Windows Vista SP2 (32-0 and 64-bit) Windows R (32-0 and 64-bit) Windows R (32-0 and 64-bit) Windows Ration (32-0 and 64-bit) Windows Ration (32-0 and 64-bit) Windows Ration (32-0 and 64-bit) Mac OS 10.8, 10.9, 10.10, 10.11 Linux® Redhat® Fedora® Core 20 x8 Ubuntu® 14.04 x64 openSUSE® 13.1 x64	and 64-bit) and 64-bit) bit))		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Print		ing/Port 9100, IPv4/IPv6, WSD	
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP	, HTTPS, DHCP Autonet, TLS, NTP, MDI	NS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer of PostScript 3: 173 Type 1 fonts, 2 M	and bitmap font (including Cyrillic font sultiple Master fonts	support)	
Xerox [®] Mobile Express Driver [®]	Driver automatically discovers avail	3	apability information. Save a list of	Plug into a new network, and Mobile Express "favorite" printers for each location, store
Xerox® Global Print Driver®		s IT administrators install, upgrade and r end-users, reducing the number of sup	3	vices from a single driver. It provides a vices management.
Xerox [®] Pull Print Driver	single driver. The Xerox® Pull Print D		ad range of printing assets. IT adm	int environment. Uses a single queue and inistrators no longer need to manage and

Print Solutions				
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.			
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.			
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.			
Xerox [®] Mobile Link App (Free at Google Play Store and Apple [®] App Store)	The Xerox® Mobile Link App allows you to scan, email and fax from your phon- print data from cloud storage. It is easy to create Mobile Link One-Touch Work address or QR code identification for pairing, automatic device discovery make printer.	flows between a mobile device	and a multifunction printer. Using a manual	
Unified Address Book for Fax, Inter	rnet Fax, Email and Scan to			
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported			
Scan	WorkCentre 7830i WorkCentre 7835i	WorkCentre 7845i	WorkCentre 7855i	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to ne concurrent jobs)	etwork or fax jobs (priority is for	return of scanned originals and printing	
Input Speed	Scan at up to 70 ipm color scanning, up to 70 ipm black-and-white – $8.5\mathrm{x}$ 11 in. / A4 LEF	Scan at up to 133 ipm color s x 11 in. / A4 LEF	scanning, up to 133 ipm black-and-white – 8.5	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)			
Maximum Scan Area	11 x 17 in. / A3			
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options			
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS			
File Compression	Color TIFF (1FF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearized PDF / PDF/A			
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input			
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)			
Scan to Email (Standard)				
Scan Features	Email signatures (6 lines each of 128 character max), email message body Scan to Email S/MIME Encryption Email Signing (requires Smart Card option) Auto send to self	(user configurable), email Centi	reWare IS confirmation sheet options	
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilizes the Unified Address Book			
Scan to (Standard)				
	Scan to USB			

Network Scanning – Software Sc	olutions
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools: • PaperPort Professional image viewing and file management software — Complete PDF functionality — Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) — Professional OCR software for digital archiving and document conversion • Image Retriever — provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability
Xerox® ConnectKey® for DocuShare® (optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer.
Security	
Features	 Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP authentication Local Authentication (internal database) Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) /.NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted Password Protected PDF (when using Email and Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite / Securely delete jobs using approved algorithms On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorization SA access based on network credentials Authorization per user per service User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec Identity Services Engine (ISE) integration, Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 (undergoing evaluation)
Xerox® PrintSαfe Software	This authentication software integrates with trusted industry cards and readers and provides PIN access to nearly any printer in a customer's secured print environment. It works with both Xerox® devices and devices from other vendors. This software is open to work with a variety of industry standard secure readers and cards.
Fax	
Network Server Fax Features	
Compatibility	ITU (CCITT) group 3 Various Xerox Business Innovation Partner Solutions
Maximum Scan Area	11 x 17 in. / A3
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Directory Access	Utilizes the Unified Address Book
Send / Receive	Multi-page TIFF, Image only PDF
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features (Optional	(Customer-installable) – 1 and 2 lines)
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilizing T38 (optional)
Compression / Speed	MH/G3, MMR/SG3

Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode — Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report
Directory Access	Utilizes the Unified Address Book Group fax available
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals
Auto Resend	Up to 5 attempts
Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher. • CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®
Novell NDPS/NEPS	Server gateway application: centralized management tool.
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions
CentreWare Internet Services – Int	regrated Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel

Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS*, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese, Arabic
Remote Services	
Xerox [®] MeterAssistαnt [®]	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.
Accounting	
Xerox® Standard Accounting (Star	ndard)
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file
Accounting Options – Network Ac	counting (Allows central server to manage all accounting)
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface
EFI™ Fiery® Network Server (Option	
Processor	2.9 GHz, Intel® Pentium® G850 Dual-Core
Memory (ESS)	1 GB
System Disk	500 GB HDD
Print Languages (PDL)	PostScript v 3020
Features	Fiery Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties PANTONE® Color Tables Expert Color Settings: Profile, Rendering and Simulation Fiery FreeForm – Variable Data capabilities Booklet Maker – booklet wizard to create booklets Print from USB flash drive Secure Erase EFI PrintMe Fiery® VUE Calibration Secure Printing User Authentication Drag and Drop job Management with CWS Importing Jobs
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet
Optional	Fiery Options Bundle (Spot-On, Auto Trapping, Hot folders, Virtual Printers) Network Switch to connect both printer and Fiery Server to Network

Supplies					
Toner Cartridges (Metered) ⁵	Black	26,000 pages	006R01509		
	Cyan	15,000 pages	006R01512		
	Magenta	15,000 pages	006R01511		
	Yellow	15,000 pages	006R01510		
Toner Cartridges (Sold)⁵	Black	26,000 pages	006R01513		
	Cyan	15,000 pages	006R01516		
	Magenta	15,000 pages	006R01515		
	Yellow	15,000 pages	006R01514		
Transfer Belt Cleaner	1 Assembly	160,000 pages	001R00613		
Second Bias Transfer Roll	1 Assembly	200,000 pages	008R13064		
Staple Cartridges	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964		
	for Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897		
	for Professional Finisher Booklet Maker (4 cartridges per carton)	5,000 each cartridge	008R12925		
Staple Refills	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941		
Xerox® Smart Kit®	Xerox® Smart Kit®				
Drum Cartridge ⁶	1 Cartridge per Color	125,000	013R00662		
Waste Toner Container ⁷	1 Cartridge	43,000	008R13061		

 $^{^{1}}$ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office



² Expected regular monthly throughput

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ XPS option is required to print XPS files.

⁵ Assumptions: Toner cartridge yield is based on 5 % area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality setpoints.

⁶ Average drum yield is based on a run length of 5 pages of 8.5 x 11 in. / A4 LEF pages, with split of 30% color / 70% black-and-white pages.

⁷ Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.