



## Overview



1. 3 External 5.25" Bays
  2. Power Button
  3. Front I/O: 2 USB 2.0, 1 IEEE 1394a, Headphone, Microphone
-

Overview



- 4. 3 External 5.25" Bays
- 5. 4-DIMM slots/ 6-DIMM slots (depending on base unit model) for DDR3 ECC memory
- 6. 2 Internal 3.5" Bays
- 7. 475W, 85% efficient Power Supply
- 8. Dual/Quad/Six Core Intel 3500/3600 Series Processors
- 9. Rear I/O: 6 USB 2.0, PS/2 keyboard/mouse  
1 RJ-45 to Integrated Gigabit LAN  
1 Audio Line In, 1 Audio Line Out, 1 Microphone In
- 10. 2 PCIe x16 Gen2 Slots
- 11. 1 PCIe x4 Gen2, 1 PCIe x4 Gen1, 2 PCI Slots
- 12. 4 Internal USB 2.0 ports

<b>Form Factor</b>	Convertible Minitower
<b>Operating Systems</b>	<p>Genuine Windows® 7 Ultimate 64-Bit*</p> <p>Genuine Windows® 7 Professional 32-Bit*</p> <p>Genuine Windows® 7 Professional 64-Bit*</p> <p>* Systems may require upgraded and/or separately purchased hardware and/or a DVD drive to install the Windows 7 software and take full advantage of Windows 7 functionality. See <a href="http://www.microsoft.com/windows/windows-7/">http://www.microsoft.com/windows/windows-7/</a> for details.</p> <p>HP Linux Installer Kit for Linux [includes drivers for 32-bit &amp; 64-bit OS versions of Red Hat Enterprise Linux(RHEL) 4 Workstation, Red Hat Enterprise Linux (RHEL) 5 Workstation, Red Hat Enterprise Linux (RHEL) 6 Workstation, 64-bit SUSE Linux Enterprise Desktop (SLED) 11] See <a href="http://www.hp.com/workstations/software/linux">http://www.hp.com/workstations/software/linux</a> for details. SUSE Linux Enterprise Desktop 11 Linux preloaded Red Hat Enterprise Linux (as Drop-in-the-box paper license only) For detailed OS/hardware support information for Linux, see: <a href="http://www.hp.com/support/linux_hardware_matrix">http://www.hp.com/support/linux_hardware_matrix</a></p>
<b>Available Processors</b>	<p>Intel® Xeon® Processor W3503 2.40 GHz, 4MB cache, 1066 memory, 4.8GT/s QPI, Dual-Core</p> <p>Intel Xeon Processor W3505 2.53 GHz, 4MB cache, 1066 memory, 4.8GT/s QPI, Dual-Core</p> <p>Intel Xeon Processor W3520 2.66 GHz, 8MB cache, 1066 memory, 4.8 GT/s QPI, Quad-Core, HT,</p>



### Overview

	<p>Turbo Intel Xeon Processor W3550 3.06 GHz, 8MB cache, 1066 memory, 4.8 GT/s QPI, Quad-Core, HT, Turbo Intel Xeon Processor W3565 3.20 GHz, 8MB cache, 1066 memory, 4.8 GT/s QPI, Quad-Core, HT, Turbo Intel Xeon Processor W3670 3.20 GHz, 12MB cache, 1066 memory, 4.8 GT/s QPI, Six-Core, HT, Turbo Intel Xeon Processor W3680 3.33 GHz, 12MB cache, 1333 memory, 6.4 GT/s QPI, Six-Core, HT, Turbo Intel Xeon Processor W3690 3.46 GHz, 12MB cache, 1333 memory, 6.4 GT/s QPI, Six-Core, HT, Turbo</p>	
<b>Available Processor Disclaimers</b>	<p>Intel's numbering is not a measurement of higher performance. Processor numbers differentiate features within each processor family, not across different processor families. See: <a href="http://www.intel.com/products/processor_number/">http://www.intel.com/products/processor_number/</a> for details. 64-bit computing on Intel® 64 architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel 64 architecture. Processor will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Dual-Core, Quad-Core and Six-Core technologies are designed to improve performance of multithreaded software products and hardware-aware multitasking operating systems and may require appropriate operating system software for full benefits. Check with software provider to determine suitability. Not all customers or software applications will necessarily benefit from use of these technologies.</p>	
<b>Chipset</b>	Intel® X58 Express	
<b>Convertibility</b>	Yes. 5.25" drives rotate for Minitower or Desktop orientation.	
<b>Expansion Slots</b> (see system board section for more details)	<ul style="list-style-type: none"> <li>● 2 PCI slots (full-height, full-length)</li> <li>● 1 PCI Express Gen1 slot x8 mechanical/x4 electrical</li> <li>● 1 PCI Express Gen2 slot x8 mechanical/x4 electrical</li> <li>● 2 PCI Express Gen2 slots x16 (one dedicated for graphics)</li> </ul> <p><b>NOTE:</b> The PCIe x8 connectors are open ended, allowing a PCIe x16 card to be seated in the slot.</p>	
<b>Expansion Bays</b> (see storage section for more details)	<ul style="list-style-type: none"> <li>● 2 internal 3.5" bays</li> <li>● 3 external 5.25" bays</li> </ul> <p><b>NOTE:</b> Third external 5.25" bay is not full depth; maximum depth 170 mm (6.7 inches)</p>	
<b>Memory</b>	PC3-10600 DDR3-1333 ECC Unbuffered DIMMs	
<b>Front I/O</b>	2 USB 2.0, 1 IEEE 1394a standard, 1 audio out, and 1 microphone.	
<b>Internal I/O</b>	4 USB 2.0 ports available by two separate 2x5 headers: supports either up to two HP Internal USB Port Kits, AMO- EM165AA (one port on each Kit), or up to two USB Media Card Readers, or one Internal Port kit and one USB Media Card Reader.	
<b>Rear I/O</b>	6 USB 2.0, 2 USB 3.0 (requires optional PCIe card), 1 optional serial port, 2 optional IEEE 1394a or 1394b ports (requires PCI card), 2 PS/2, RJ-45 (NIC), 1 audio line in, 1 audio line out, 1 microphone in; audio ports can be retasked to function as line in, line out, microphone, or headphone.	
<b>Interfaces Supported</b>	22-in-1 Media Card Reader (optional)	
<b>Chassis Dimensions (HxWxD)</b>	Standard minitower orientation: 45.02 x 16.79 x 45.53 cm (17.7 x 6.6 x 17.9 in) Converted desktop orientation: 45.02 x 16.79 x 45.53 cm (17.7 x 6.6 x 17.9 in)	
<b>Weight</b>	Exact weights depend upon configuration Minimum: 13.5 kg (29.8 lbs) Standard: 15.1 kg (33.2 lbs) Maximum: 19.6 kg (43.2 lbs)	
<b>Temperature</b>	Operating:	5° to 35°C (40° to 95°F)
	Non-operating	-40° to 60°C (-40° to 140°F)



### Overview

<b>Humidity</b>	Operating:	8% to 85%
	Non-operating	8% to 90%
<b>Maximum Altitude</b> (non-pressurized)	Operating:	3,000 m; 10,000 feet
	Non-operating	9,100 m; 30,000 feet
<b>Power Supply</b>	475 watts wide-ranging, active Power Factor Correction, 85% Efficient The Z400 475W power supply efficiency report can be found at this link: <a href="http://www.plugloadsolutions.com/psu_reports/HP_DPS_475CBA_475W_Report.pdf">http://www.plugloadsolutions.com/psu_reports/HP_DPS_475CBA_475W_Report.pdf</a> (Optional) 600 watts wide-ranging, active Power Factor Correction, 80% Efficient The Z400 600W power supply efficiency report can be found at this link: <a href="http://www.plugloadsolutions.com/psu_reports/HEWLETT%20PACKARD_626322-001_ECOS%202171.1_600W_Report.pdf">http://www.plugloadsolutions.com/psu_reports/HEWLETT%20PACKARD_626322-001_ECOS%202171.1_600W_Report.pdf</a>	
<b>Color</b>	Jack Black/Alloy metallic	
<b>Tape Backup</b>	For a complete listing of compatible tape offerings, please visit: <a href="http://www.hp.com/products1/storage/compatibility/tapebackup/Workstations/index.html">http://www.hp.com/products1/storage/compatibility/tapebackup/Workstations/index.html</a>	



## Supported Components

### Processors

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
<b>Quad/Six-Core Intel® Xeon® Processor 3500/3600 Series with Intel® 64 Architecture</b>				
Intel Xeon W3503, 2.40GHz, 4MB cache, 1066 memory, 4.8GT/s QPI, Dual-Core	Y	N		
Intel Xeon W3505, 2.53GHz, 4MB cache, 1066 memory, 4.8GT/s QPI, Dual-Core	Y	N		
Intel Xeon W3520, 2.66GHz, 8MB cache, 1066 memory, 4.8GT/s QPI, Quad-Core, HT, Turbo	Y	N		
Intel Xeon W3550, 3.06GHz, 8MB cache, 1066 memory, 4.8GT/s QPI, Quad-Core, HT, Turbo	Y	N		
Intel Xeon W3565, 3.20GHz, 8MB cache, 1066 memory, 4.8GT/s QPI, Quad-Core, HT, Turbo	Y	N		
Intel Xeon W3670, 3.20GHz, 12MB cache, 1066 memory, 4.8GT/s QPI, Six-Core, HT, Turbo	Y	N		
Intel Xeon W3680, 3.33GHz, 12MB cache, 1333 memory, 6.4GT/s, Six-Core, HT, Turbo	Y	N		
Intel Xeon W3690, 3.46GHz, 12MB cache, 1333 memory, 6.4GT/s QPI, Six-Core, HT, Turbo	Y	N		

HP Liquid Cooling Option is available for all the above processors.  
Intel's numbering is not a measurement of higher performance.

### SAS Hard Drives

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
<b>HP SAS (Serial Attached SCSI) Hard Drives for HP Workstations</b>				
300GB SAS 15K rpm 6Gb/s 3.5" HDD	N	Y	LU967AA	
450GB SAS 15K rpm 6Gb/s 3.5" HDD	N	Y	LU968AA	
600GB SAS 15K rpm 6Gb/s 3.5" HDD	Y	Y	VM647AA	

#### Sub-Section Description/Notes

**NOTE:** SAS controller add-in card required

Up to (4) 3.5-inch 15K rpm SAS drives: 300, 450, 600 GB; 2.4 TB max

#### Removable Boot Drive option

### SATA Hard Drives

#### SATA (Serial ATA) Hard Drives for HP Workstations

160GB SATA 7200 rpm 3Gb/s 3.5" HDD	Y	Y	PV944A	
250GB SATA 7200 rpm 3Gb/s 3.5" HDD	Y	Y	PY278AA	
320GB SATA 7200 rpm 3Gb/s 3.5" HDD	Y	Y	FH963AA	
500GB SATA 7200 rpm 3Gb/s 3.5" HDD	Y	Y	PV943A	
1TB SATA 7200 rpm 3.0Gb/s 3.5" HDD	Y	Y	GE262AA	
1.5TB SATA 7200 rpm 3Gb/s 3.5" HDD	Y	Y	VH997AA	



## Supported Components

2.0TB SATA 7200 rpm 3Gb/s 3.5" HDD	Y	Y	WE464AA
160GB SATA 10K rpm SFF in 3.5" Frame HDD	Y	Y	EW222AA
300GB SATA 10K rpm SFF in 3.5" Frame HDD	Y	Y	FM802AA
600GB SATA 10K rpm SFF in 3.5" Frame HDD	Y	Y	XP309AA

### Sub-Section Description/Notes

Up to (4) 3.5-inch 7200 rpm SATA drives: 160, 250, 320, 500 GB, 1.0, 1.5, 2.0 TB; 8.0 TB max

Up to (4) 2.5-inch 10K rpm SATA drives: 160, 300, 600 GB; 2.4 TB max

### Removable Boot Drive option

#### SATA Solid State Drives

#### HP Solid State Drives for Workstations

HP 160GB SATA X25-M SSD	Y	Y	WV915AA
HP 160GB SATA SSD	Y	Y	LZ704AA
HP 300GB SATA SSD	Y	Y	LZ069AA

For hard drives, 1 GB = 1 billion bytes; TB = 1 trillion bytes. Actual formatted capacity is less.

#### Hard Drive Controllers

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
<b>Integrated SATA 3.0 Gb/s Controller</b>				
Integrated SATA 3.0 Gb/s Controller	Y	N		
<b>Factory integrated RAID on motherboard for SATA drives</b>				
RAID 0 Configuration - Striped Array	Y	N		Note 1
RAID 0 Data Configuration -- Boot/OS Drive + 2 Drive Striped Array	Y	N		Notes 1 and 2
RAID 1 Configuration - Mirrored Array	Y	N		Note 1
<b>LSI 9212 4-Port SAS 6Gb/s RAID Card</b>				
LSI 9212 4-Port SAS 6Gb/s RAID Card	Y	Y	XP310AA	Notes 2 and 3
<b>LSI MegaRAID® SAS 8888ELP Host Bus Adapter (HBA)</b>				
LSI 8888ELP 8-port SAS HW RAID Card	N	Y	GE258AA	
<b>LSI MegaRAID® 9260-8i SAS 6Gb/s ROC RAID Card and iBBU08 Battery Backup Unit</b>				
LSI MegaRAID® 9260-8i SAS 6Gb/s ROC RAID Card	N	Y	WE465AA	
Optional: LSI iBBU08 Battery Backup Unit for LSI 9260-8i	N	Y	LA783AA	

**NOTE 1:** All drives must be identical in size, speed, and type for RAID arrays. Specific user-configured hardware SAS RAID configurations are supported on Linux systems. Please visit: [http://www.hp.com/support/linux\\_hardware\\_matrix](http://www.hp.com/support/linux_hardware_matrix) for details.

**NOTE 2:** In RAID 0 Data Configuration, Boot/OS Drive must be SATA.

**NOTE 3:** Specific user-configured hardware SAS RAID configurations are supported on this Linux system. Please visit: [http://www.hp.com/support/linux\\_hardware\\_matrix](http://www.hp.com/support/linux_hardware_matrix) for details. SATA hardware RAID is not supported on Linux systems. The Linux kernel, with built-in software RAID,



## Supported Components

provides excellent functionality and performance and is a good alternative to hardware-based RAID. Please visit: <http://h20000.www2.hp.com/bc/docs/support/SupportManual/c00060684/c00060684.pdf> for RAID capabilities with Linux.

All RAID arrays must be less than 2 TB, except for SATA RAID 0 Data Arrays.

### Graphics

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes	Supported Multi Mixed
<b>Professional 2D</b>					
NVIDIA Quadro NVS 295 256MB PCIe Graphics Card	Y	Y	FY943AA	Note 1	2
NVIDIA NVS300 512MB PCIe Graphics Card	Y	Y	XP612AA	Note 2	2
AMD FirePro 2270 512MB Graphics Card	Y	Y	LA524AA	Note 3	2
NVIDIA Quadro NVS 450 512 MB PCIe Graphics Card	Y	Y	FH519AA	Note 4	2
<b>Entry 3D</b>					
NVIDIA Quadro FX 380 256MB PCIe Graphics Card	Y	Y	NB769AA		2
NVIDIA Quadro 400 512MB Graphics Card	Y	Y	LD542AA		2
NVIDIA Quadro 600 1GB Graphics Card	Y	Y	WS093AA		2
ATI FirePro V3800 512MB PCIe Graphics Card	Y	Y	WL048AA		2
ATI FirePro V4800 1GB Graphics Card	Y	Y	WL049AA		2
<b>Mid-range 3D</b>					
NVIDIA Quadro 2000 1GB Graphics Card	Y	Y	WS094AA		2
AMD FirePro V5900 2GB Graphics	Y	Y	LS992AA		2
<b>High End 3D</b>					
AMD FirePro V7900 2GB Graphics	Y	Y	LS993AA		1
NVIDIA Quadro 4000 2GB Graphics Card	Y	Y	WS095AA		1
NVIDIA Quadro 5000 2.5GB Graphics Card	Y	Y	WS096AA		1

**NOTE 1:** If 1st graphics card is NVS 295, 2nd graphics card must be NVS 295

**NOTE 2:** If 1st graphics card is NVS 300, 2nd graphics card must be NVS 300

**NOTE 3:** If 1st graphics card is AMD FirePro 2270, 2nd graphics card must be AMD FirePro 2270

**NOTE 4:** If 1st graphics card is NVS 450, 2nd graphics card must be NVS 450, NVS 295, or NVS 300



## Supported Components

### High Performance GPU Computing

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
NVIDIA Tesla C2050 Compute Processor	Y	Y	WT428AA	Note 1
NVIDIA Tesla C2075 Compute Processor	Y	Y	QB035AA	Note 1

**NOTE 1:** Supported only with 600W power supply

### Memory

#### CTO

#### PC3-10600 DDR3-1333 ECC Unbuffered DIMMs CTO

- 1GB (1x1GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 2GB (2x1GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 3GB (3x1GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 4GB (4x1GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 4GB (2x2GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 6GB (3x2GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 8GB (2x4GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 8GB (4x2GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 12GB (3x4GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 12GB (6x2GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 16GB (4x4GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 24GB (6x4GB) DDR3-1333 ECC Unbuffered RAM 1-CPU

#### Sub-Section Description/Notes

**NOTE:** DIMMs should be distributed across all three memory channels for optimal performance. Each processor supports up to 3 channels of DDR3 memory. To realize full performance at least 1 DIMM must be inserted into each channel. The CPUs determine the speed at which the memory is clocked. If a 1066MHz capable CPU is used in the system, the maximum speed the memory will run at is 1066MHz regardless of the specified speed of the memory.

#### AMO

#### PC3-10600 DDR3-1333 ECC Unbuffered DIMMs AMO

1GB (1x1GB) DDR3-1333 ECC Unbuffered RAM	FX698AA
2GB (1x2GB) DDR3-1333 ECC Unbuffered RAM	FX699AA
4GB (1x4GB) DDR3-1333 ECC Unbuffered RAM	NL797AA

**NOTE:** Only unbuffered DDR3 DIMMs are supported.





### Supported Components

#### Multimedia and Audio Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Integrated Intel/Realtek HD ALC262 Audio	Y	N		
HP Thin USB Powered Speakers	Y	Y	KK912AA	
Creative X-Fi Titanium PCIe Audio Card	Y	Y	Y	Notes 1 and 2

**NOTE 1:** The SoundBlaster X-Fi Titanium audio card is supported on Windows 7 Professional 32-Bit and 64-Bit and Windows 7 Ultimate 64-bit.

**NOTE 2:** The SoundBlaster X-Fi Titanium audio card is supported on specific Linux operating systems. Please visit: [http://www.hp.com/support/linux\\_hardware\\_matrix](http://www.hp.com/support/linux_hardware_matrix) for details.

#### Optical and Removable Storage

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP 16X DVD-ROM SATA Drive	Y	Y	AR629AA	Notes 1 and 2
HP 16X DVD+/-RW SuperMulti SATA Drive	Y	Y	AR630AA	Note 2
HP Blu-ray Writer	Y	Y	AR482AA	Note 3
HP 22-in-1 Media Card Reader Kit (Workstations)	Y	Y	NK361AA	

**NOTE 1:** Not supported as a 2nd drive option.

**NOTE 2:** Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players.

**NOTE 3:** As Blu-ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.

#### Controller Cards

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP FireWire/IEEE 1394a PCI Card	Y	Y	PA997A	
HP IEEE 1394b FireWire PCIe Card	Y	Y	NK653AA	
HP USB 3.0 2x2 Port SuperSpeed PCIe x1 Card	Y	Y	QT587AA	
HP SuperSpeed USB 3.0 PCIe x1 Card	Y	Y	BM867AA	



### Supported Components

#### Monitors

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP LP2065 20-inch LCD Monitor	Y	Y	EF227A	
HP LP2475w 24-inch Widescreen LCD Monitor	Y	Y	KD911A	
HP DreamColor LP2480zx Professional Display	Y	Y	GV546A	
HP LP3065 30-inch Widescreen LCD Monitor	Y	Y	EZ320A	
HP ZR22w 21.5-inch S-IPS LCD Monitor	Y	Y	VM626A4	
HP ZR24w 24-inch S-IPS LCD Monitor	Y	Y	VM633A4	
HP ZR30w 30-inch S-IPS LCD Monitor	Y	Y	VM617A4	

Supported by all Operating Systems available from HP

Screen Size Diagonally Measured

#### Networking and Communications

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Integrated Broadcom 5764 PCIe LOM Controller	Y	N		
Broadcom NetXtreme Gigabit Ethernet Plus NIC (PCIe)	Y	Y	FS215AA	Note 1
Intel Gigabit CT Desktop NIC	N	Y	FH969AA	

**NOTE 1:** This is a PCI Express card based on the Broadcom 5761 chip.

"Gigabit" Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/sec. For high speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

The Broadcom (5761) NetXtreme Gigabit Ethernet Plus NIC and the Intel Gigabit CT NIC are supported on the following Linux operating systems:

Red Hat Enterprise Linux(RHEL) WS4, 5 Desktop/Workstation

Novell SLED 10 & 11

#### Racking and Physical Security

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Security Cable with Kensington Lock	N	Y	PC766A	
HP Solenoid Hood Lock & Hood Sensor	Y	N		
HP (CMT) Solenoid Lock	N	Y	DE618A	
HP xw4/Z4 Depth Adjustable Fixed Rail Rack Kit	N	Y	EK729AA	



### Supported Components

#### Input Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP PS/2 Standard Keyboard	Y	Y	DT527A	
HP USB Standard Keyboard	Y	Y	DT528A	
HP PS/2 Optical Scroll Mouse	Y	Y	EY703AA	
HP USB 2-Button Optical Scroll Mouse	Y	Y	DC172B	
HP USB Laser Mouse	Y	Y	GW405AA	
HP USB Optical 3-Button Mouse	Y	Y	DY651A	
HP USB Smart Card Keyboard	N	Y	ED707AA	
HP 2.4GHz Wireless Keyboard & Mouse	N	Y	NB896AA	
HP USB Optical 3-Button 2.9M OEM Mouse	N	Y	ET424AA	
HP SpaceExplorer 3D USB Controller	N	Y	RY429AA	
HP SpacePilot 3D USB Intelligent Controller	N	Y	EF390AA	

#### Other Hardware

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Configure minitower in desktop orientation	Y	N		
HP ENERGY STAR 5.0 Enabled Configuration	Y	N		
HP Workstation Mouse Pad	Y	N		Japan only
HP eSATA PCI Cable Kit	Y	Y	GM110AA	
HP Power Cord Kit	N	Y	DM293A	
HP Serial Port Adapter	N	Y	PA716A	
HP Internal USB Port Kit	N	Y	EM165AA	
HP Optical Bay HDD Mounting Bracket	N	Y	NQ099AA	
HP Workstation to LTO SAS Int. Cable	N	Y	EH925A	
HP Z4 Fan and Front Card Guide Kit	Y	Y	VH190AA	



## Supported Components

### Software

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Performance Advisor	Y	N		
Roxio Easy Media Creator (DVD/Blu-ray Disc burner software)	Y	N		
Intervideo WinDVD (DVD player/burner software)	Y	N		
HP ProtectTools Security	Y	N		Note 1
PDF Complete - Trial Edition	Y	N		
HP Client Manager Software v6.2 (optional download)	Y	N		
HP Power Assistant	Y	N		
MS Office Home & Business 2010	Y	N		

**NOTE 1:** Must select as a Configure to Order Option. Delivered as a "Drop in the Box" CD

### Operating Systems

	Support Notes
Genuine Windows® 7 Ultimate 64-bit	Note 1
Genuine Windows® 7 Professional 32-bit	Note 1
Genuine Windows® 7 Professional 64-bit	Note 1
HP Linux Installer Kit	Note 2
SUSE Linux Enterprise Desktop 11	Note 2
Red Hat Enterprise Linux (RHEL) Workstation - Paper License (1yr)	Note 3

**NOTE 1:** See <http://www.microsoft.com/windows/windows-7/> for support details.

**NOTE 2:** See: <http://www.hp.com/workstations/software/linux>

**NOTE 3:** This second OS must be ordered with the HPIKL as the first OS.



## System Technical Specifications

	<b>NOTE:</b> Restricted Material Usage updated to match GSE.
<b>System Board</b>	
System Board Form Factor	ATX 243.84 x 304.8 mm (9.6 x 12 inches)
Processor Socket	Single LGA1366
CPU Bus Speed	QPI: Up to 6.4GT/sec
Chipset	Intel® X58 Express
Super I/O Controller	SMSC SCH5327, Rev B
Memory Expansion Slots	6 DDR3 memory slots
Memory Type Supported	DDR3, UDIMM (Unbuffered), ECC
Memory Modes	Channel Interleaved
Memory Speed Supported	800MHz, 1066MHz, and 1333MHz DDR3
Memory Protection	ECC available on data, parity on address and command

Memory Size (GB)	HP Z400 4-DIMM				HP Z400 6-DIMM					
	DIMM1	DIMM2	DIMM3	DIMM4	DIMM1	DIMM2	DIMM3	DIMM4	DIMM5	DIMM6
1	1 GB				1 GB					
2	1 GB	1 GB			1 GB	1 GB				
3	1 GB	1 GB	1 GB		1 GB	1 GB	1 GB			
4	1 GB	1 GB	1 GB	1 GB	1 GB	1 GB	1 GB	1 GB		
4	2 GB	2 GB			2 GB	2 GB				
6	2 GB	2 GB	2 GB		2 GB	2 GB	2 GB			
8	2 GB	2 GB	2 GB	2 GB	2 GB	2 GB	2 GB	2 GB		
8	4 GB	4 GB			4 GB	4 GB				
12	NA				2 GB	2 GB	2 GB	2 GB	2 GB	2 GB
12	4 GB	4 GB	2 GB	2 GB	4 GB	4 GB	2 GB	2 GB		
12	4 GB	4 GB	4 GB		4 GB	4 GB	4 GB			
16	4 GB	4 GB	4 GB	4 GB	4 GB	4 GB	4 GB	4 GB		
24	NA				4 GB	4 GB	4 GB	4 GB	4 GB	4 GB

Memory Configuration (Supported)	<ul style="list-style-type: none"> <li>The 4GB DIMM for Z400 and Z600 is NOT compatible with the 4GB DIMMs offered on the Z800.</li> <li>They are NOT interchangeable.</li> <li>Only ECC DIMMs are supported.</li> </ul>
Note on Maximum Memory	*Maximum memory capacities assume 64-bit operating systems, such as genuine Windows® Vista Business 64, XP Professional x64 Edition, Red Hat Linux 64-bit. Genuine Windows Vista Business 32 and XP Professional (32-bit) support up to 4 GB. 32-bit Linux supports up to 8 GB.
PCI Express Connectors	2 x16 PCIe Gen2 1 x8 PCIe (x4) Gen2 1 x8 PCIe (x4) Gen1



## System Technical Specifications

PCI Connectors (5.0V)	2 PCI	
Supported Drive Interfaces	SATA	Integrated 6-channel SATA 3.0Gb/sec controller with RAID 0, 1, 5, 10 and NCQ. (Factory integrated RAID is Microsoft Windows only)
	Serial Attached SCSI	Hardware RAID is not supported on Linux systems. The Linux kernel, with built-in software RAID, provides excellent functionality and performance. It is a good alternative to hardware-based RAID. Please visit: <a href="http://h20000.www2.hp.com/bc/docs/support/SupportManual/c00060684/c00060684.pdf">http://h20000.www2.hp.com/bc/docs/support/SupportManual/c00060684/c00060684.pdf</a> for RAID capabilities with Linux.
	Integrated RAID	<b>NOTE:</b> Requires identical hard drives (speeds, capacity, interface)
	Integrated Graphics	No
	Network Controller	Integrated HP Gbit LAN by Broadcom with the following management capabilities: WOL, PXE 2.1 and ASF 2.0
	External SATA (eSATA)	4 ports are eSATA configurable with optional eSATA After-Market Option cable kit.
	IDE connector	No
	Floppy connector	Yes
	Audio	High Definition Integrated Realtek ALC262 Audio with Line in, Line Out, Microphone, Headphone
	CD-ROM input (Audio)	No
	AUX INPUT (Audio)	Yes
IEEE 1394 Connector(s)	Front	6-DIMM Z400: 1 IEEE 1394a standard
	Rear	2 optional IEEE 1394a or IEEE 1394b, requires optional PCI card
	Internal	No
USB Connector(s)	Front	2 USB 2.0
	Rear	6 USB 2.0; 2 USB 3.0, requires optional PCIe card
	Internal	4 USB 2.0 ports available by two separate 2x5 headers: supports either up to two HP Internal USB Port Kits, AMO- EM165AA (one port on each Kit), or up to two USB Media Card Readers, or one Internal Port kit and one USB Media Card Reader.
HD Integrated Audio	High Definition Integrated Realtek ALC262 Audio with Line in, Line Out, Microphone, Headphone	
Flash ROM	Yes	
CPU Fan Header	Yes	
Chassis Fan Header	1 Rear System Chassis Fan Header, 1 Optional Front Chassis Fan Header	
Front PCI Fan Header	Yes	
Front Control Panel/Speaker Header	Yes	
CMOS Battery Holder - Lithium	Yes	
Integrated Trusted Platform Module	Integrated TPM 1.2	
Power Supply Headers	Yes	



## System Technical Specifications

Power Switch, Power LED & Hard Drive LED Header	Yes
Clear Password Jumper	Yes
Serial Port	Single Port (Requires optional Serial Port Adapter)
Parallel Port	No
Keyboard/Mouse	USB or PS/2
Hood Lock Header	Yes
Hood Sensor Header	Yes

### Z400 Required power supply info

Power Supply	475W Custom PSU - (Wide Ranging, Active PFC)		600W Custom PSU - (Wide Ranging, Active PFC)	
Operating Voltage Range	90 - 269 VAC		90 - 269 VAC	
Rated Voltage Range	100 - 127 VAC 200 - 240 VAC	118 VAC	100 - 127 VAC 200 - 240 VAC	118 VAC
Rated Line Frequency	50-60 Hz	400Hz	50-60 Hz	400Hz
Operating Line Frequency Range	47 - 66 Hz	393-407 Hz	47 - 66 Hz	393-407 Hz
Rated Input Current	10A @ 100-127 VAC 6A @ 200-240 VAC	10A @ 118 VAC	10A @ 100-127 VAC 6A @ 200-240 VAC	10A @ 118 VAC
Heat Dissipation (Configuration & software dependent)	Typical 954 btu/hr (240.3 kg-cal/hr) Max 1977 btu/hr (498.2 kg-cal/hr)		Typical 1536 btu/hr (387 kg-cal/hr) Max 2560 btu/hr (645 kg-cal/hr)	
Power Supply Fan	92x25 mm variable speed		92x25 mm variable speed	
ENERGY STAR Qualified (Configuration dependent)	YES		NO	
80 PLUS® Compliant	YES, 85%		YES, 80%	
FEMP Standby Power Compliant @115V (Wake-on LAN disabled) (<2W in S5 - Power Off)	YES		YES	
EuP Compliant @ 230V (<1 W in S5 - Power Off)	YES		YES	
Power Consumption in sleep mode (as defined by ENERGY STAR) - Suspend to RAM (S3) (Instantly Available PC) measured at 115V.	<6W		<6W	
Built-in Self Test LED	YES		YES	
Surge Tolerant Full Ranging Power Supply (withstands power surges up to 2000V)	YES		YES	

### System Configuration



### System Technical Specifications

<b>Example Configuration #1</b>	<b>Processor Info</b>	1x Intel Xeon W3503					
	<b>Memory Info</b>	1x1GB DDR3 1333 (UDIMM)					
	<b>Graphics Info</b>	NVS295					
	<b>Disks/Optical/Floppy</b>	1x160GB SATA / 1 Optical / 0 Floppy					
	<b>PSU</b>	475W 85%					
<b>Energy Consumption</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	86.23 W		85.26 W		85.90 W	
	Windows Busy Typ (S0)	140.90 W		137.85 W		140.40 W	
	Windows Busy Max (S0)	153.20 W		152.96 W		155.00 W	
	Sleep (S3)	4.17 W	3.96 W	4.03 W	3.79 W	4.14 W	3.90W
	Off (S5)	1.25 W	1.14 W	1.51 W	1.35 W	1.23 W	1.12 W
	Zero Power Mode (EuP)	0.31 W		0.61 W		0.29W	
<b>Heat Dissipation**</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	294.30 btu/hr		290.99 btu/hr		293.18 btu/hr	
	Windows Busy Typ (S0)	480.89 btu/hr		470.48 btu/hr		479.19 btu/hr	
	Windows Busy Max (S0)	522.87 btu/hr		522.05 btu/hr		529.02 btu/hr	
	Sleep (S3)	14.2 btu/hr	13.5 btu/hr	13.8 btu/hr	12.9 btu/hr	14.1 btu/hr	13.3 btu/hr
	Off (S5)	4.27 btu/hr	3.89 btu/hr	5.15 btu/hr	4.61 btu/hr	4.20 btu/hr	3.82 btu/hr
	Zero Power Mode (EuP)	1.04 btu/hr		2.06 btu/hr		0.98 btu/hr	
<b>Example Configuration #2</b>	<b>Processor Info</b>	1 x Intel Xeon W3570					
	<b>Memory Info</b>	4x4GB DDR3 1333MHz (UDIMM)					
	<b>Graphics Info</b>	1xFX4800					
	<b>Disks/Optical/Floppy</b>	4x450GB SAS / 1 Optical / 0 Floppy					
	<b>PSU</b>	475W 85%					
<b>Energy Consumption</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	180.70 W		178.30 W		181.00 W	
	Windows Busy Typ (S0)	404.60 W		393.20 W		407.50 W	
	Windows Busy Max (S0)	482.80 W		469.10 W		488.60 W	
	Sleep (S3)	4.84 W	4.65 W	5.13 W	4.94 W	4.85 W	4.66 W
	Off (S5)	1.18 W	1.07 W	1.61 W	1.37 W	1.16 W	1.05W
	Zero Power Mode (EuP)	0.32 W		0.61 W		0.29 W	
<b>Heat Dissipation**</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	616.73 btu/hr		608.54 btu/hr		617.75 btu/hr	
	Windows Busy Typ (S0)	1380.90 btu/hr		1341.99 btu/hr		1390.80 btu/hr	
	Windows Busy Max (S0)	1647.80 btu/hr		1601.04 btu/hr		1667.59 btu/hr	
	Sleep (S3)	16.5 btu/hr	15.9 btu/hr	17.5 btu/hr	16.9 btu/hr	16.6 btu/hr	15.9 btu/hr
	Off (S5)	4.03 btu/hr	3.65 btu/hr	5.49 btu/hr	4.68 btu/hr	3.96 btu/hr	3.58 btu/hr
	Zero Power Mode (EuP)	1.08 btu/hr		2.06 btu/hr		0.98 btu/hr	





### System Technical Specifications

<b>Example Configuration #3</b>	Processor Info	1 x Intel Xeon W3520					
	Memory Info	3x1GB DDR3 1333MHz (UDIMM)					
	Graphics Info	1xFX1800					
	Disks/Optical/Floppy	1x250GB SATA / 1 Optical / 0 Floppy					
	PSU	475W 85%					
<b>Energy Consumption</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	96.70 W		95.10 W		97.71 W	
	Windows Busy Typ (S0)	237.99 W		233.03 W		239.04 W	
	Windows Busy Max (S0)	268.79 W		267.95 W		274.90 W	
	Sleep (S3)	3.89 W	3.65 W	4.20 W	3.96 W	3.83 W	3.61 W
	Off (S5)	1.20 W	1.06 W	1.51 W	1.35 W	1.17 W	1.02 W
	Zero Power Mode (EuP)	0.31 W		0.60 W		0.29 W	
<b>Heat Dissipation**</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	330.04 btu/hr		324.58 btu/hr		333.48 btu/hr	
	Windows Busy Typ (S0)	812.26 btu/hr		795.33 btu/hr		815.84 btu/hr	
	Windows Busy Max (S0)	917.38 btu/hr		914.51 btu/hr		938.23 btu/hr	
	Sleep (S3)	13.3 btu/hr	12.5 btu/hr	14.3 btu/hr	13.5 btu/hr	13.1 btu/hr	12.3 btu/hr
	Off (S5)	4.10 btu/hr	3.60 btu/hr	5.15 btu/hr	4.61 btu/hr	3.99 btu/hr	3.48 btu/hr
	Zero Power Mode (EuP)	1.05 btu/hr		2.05 btu/hr		0.97 btu/hr	

<b>Example Configuration #4</b>	Processor Info	1 x Intel Xeon W3680					
	Memory Info	6x2GB DDR3 1333MHz (UDIMM)					
	Graphics Info	1xTesla C2050					
	Disks/Optical/Floppy	2x500GB SATA / 1 Optical / 0 Floppy					
	PSU	600W 80%					
<b>Energy Consumption</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	114.11 W		112.80 W		113.10 W	
	Windows Busy Typ (S0)	411.11 W		403.4 W		409.50 W	
	Windows Busy Max (S0)	460.0 W		460.40 W		458.10 W	
	Sleep (S3)	3.67 W	3.41 W	4.12 W	3.85 W	3.64 W	3.41 W
	Off (S5)	1.19 W	1.05 W	1.61 W	1.47 W	1.15 W	1.01 W
	Zero Power Mode (EuP)	0.38 W		0.79 W		0.35W	
<b>Heat Dissipation**</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	389.46 btu/hr		384.99 btu/hr		386.01 btu/hr	
	Windows Busy Typ (S0)	1403.12 btu/hr		1376.80 btu/hr		1397.62 btu/hr	
	Windows Busy Max (S0)	1569.98 btu/hr		1571.35 btu/hr		1563.50 btu/hr	
	Sleep (S3)	12.53 btu/hr	11.64 btu/hr	14.06 btu/hr	13.14 btu/hr	12.42 btu/hr	11.64 btu/hr
	Off (S5)	4.06 btu/hr	3.58 btu/hr	5.49 btu/hr	5.02 btu/hr	3.92 btu/hr	3.45btu/hr
	Zero Power Mode (EuP)	1.31 btu/hr		2.69 btu/hr		1.19 btu/hr	



## System Technical Specifications

<b>Example Configuration #5</b> <i>(ENERGY STAR Qualified)</i>	<b>Processor Info</b>	1x Intel Xeon W3570					
	<b>Memory Info</b>	4x2GB DDR3 1333MHz (UDIMM)					
	<b>Graphics Info</b>	1 x FX4800					
	<b>Disks/Optical/Floppy</b>	2x1000GB SATA / 1 Optical / 0 Floppy					
	<b>I/O</b>	1xBroadcom 5761 Gigabit PCIe NIC					
	<b>PSU</b>	475W 85%					
<b>Energy Consumption</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	<b>On-Idle (ENERGY STAR® Idle (S0))</b>	99.8 W		97.7 W		100.3 W	
	<b>ENERGY STAR® PMAX Windows running Linpack and Viewperf</b>	323.1 W		316.6 W		325.4 W	
	<b>ENERGY STAR® "Sleep" (S3)</b>	4.6 W	-	4.8 W	-	4.6 W	-
	<b>ENERGY STAR® "Standby" (Off) (S5)</b>	1.8 W	-	2.1 W	-	1.7 W	-
<b>Heat Dissipation**</b>		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	<b>On-Idle (ENERGY STAR® Idle (S0))</b>	340.6 btu/hr		333.5 btu/hr		342.3 btu/hr	
	<b>ENERGY STAR® PMAX Windows running Linpack and Viewperf</b>	1102.7 btu/hr		1080.6 btu/hr		1110.6 btu/hr	
	<b>ENERGY STAR® "Sleep" (S3)</b>	15.7 btu/hr	-	16.4 btu/hr	-	15.7 btu/hr	-
	<b>ENERGY STAR® "Standby" (Off) (S5)</b>	1.8 btu/hr	-	2.1 btu/hr	-	1.7 btu/hr	-

**NOTES:**

\* Energy Star low energy mode

\*\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

This product is in compliance with US executive order 13221, WOL (wake on LAN) disabled.

Declared Noise Emissions (Entry-level and High-end configurations)		
<b>System Configuration (Entry level)</b>	<b>Processor Info</b>	Intel Xeon Processor W3505 2.53 GHz
	<b>Memory Info</b>	4 x 1GB DDR3 1333 MHz
	<b>Graphics Info</b>	NVIDIA Quadro NVS 295
	<b>Disks/Optical/Floppy</b>	1 x 160 GB 7200 RPM SATA / DVD-ROM / No Floppy



## System Technical Specifications

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power ( LWAd, bels )	Deskside Sound Pressure
	Idle	3.9 Bels	23 dB
	SATA Hard drive Operating (random reads)	4.2 Bels	25 dB
	Floppy Drive Operating (continuous copy)	4.7 Bels	29 dB
	DVD-ROM Operating (sequential reads)	5.1 Bels	38 dB

System Configuration (High-end)	Processor Info	Intel Xeon Processor W3570 3.20 GHz
	Memory Info	4 x 1GB DDR3 1333 MHz
	Graphics Info	NVIDIA Quadro FX 4600
	Disks/Optical/Floppy	2 x 450 GB 15K SAS / DVD-ROM / No Floppy

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power ( LWAd, bels )	Deskside Sound Pressure
	Idle	4.6 Bels	27 dB
	SATA Hard drive Operating (random reads)	5.2 Bels	35 dB
	Floppy Drive Operating (continuous copy)		
	DVD-ROM Operating (sequential reads)	5.3 Bels	38 dB

Environmental Requirements	Temperature	Operating: 5° to 35° C (40° to 95° F) Non-operating: -40° to 60° C (-40° to 140° F)
	Humidity	Operating: 8% to 85% RH, non-condensing Non-operating: 8% to 90% RH, non-condensing
	Maximum Altitude	Operating: 3,000 m (10,000 feet) Non-operating: 9,100 m (30,000 feet)
	Dynamic (new)	Shock Operating: ½-sine: 40g, 2-3ms Non-operating: ½-sine: 160 cm/s, 2-3ms (~100g) square: 422 cm/s, 20g <b>NOTE:</b> Values represent individual shock events and do not indicate repetitive shock events.  Vibration Operating random: 0.5g (rms), 5-300 Hz Non-operating random: 2.0g (rms), 10-500 Hz <b>NOTE:</b> Values do not indicate continuous vibration.
	Cooling	Above 1524 m (5,000 ft) altitude, maximum operating temperature is de-rated by 1° C (1.8° F) per 305 m (1,000 ft) elevation increase



## System Technical Specifications

Physical Security and Serviceability	
Access Panel	Tool-less Includes system board and memory information
Optical Drive	Tool-less
Floppy Drive	Tool-less
Hard Drives	Tool-less
Expansion Cards	Tool-less
Processor Socket	Tool-less
Green User Touch Points	Yes, on tool-free internal chassis components
Color-coordinated Cables and Connectors	Yes
Memory	Tool-less
System Board	Tool-less
Dual Color Power and HD LED on Front of Computer	Yes
Configuration Record SW	Yes
Over-Temp Warning on Screen	Yes
Restore CD Set	Restores the computer to its original factory shipping image - Can be obtained via HP Support
Dual Function Front Power Switch	Yes, causes a fail-safe power off when held for 4 seconds
Padlock Support	Yes (optional): Locks side cover and secures chassis from theft 5.56 mm (0.2188 in) diameter padlock loop at rear of system
Cable Lock Support	Yes, Kensington Cable Lock (optional): Locks side cover and secures chassis from theft 3 mm x 7 mm slot at rear of system
Universal Chassis Clamp Lock Support	Yes (optional): Locks side cover and locks cables to chassis. Secures chassis from theft and allows multiple units to be chained together when used with optional cable Threaded feature at rear of system
Solenoid Lock and Hood Sensor	Yes (optional) The Solenoid Hood Lock eliminates the need for a physical key by making the chassis lockable through software and a password. You can also lock and unlock the chassis remotely over the network. The Sensor Kit detects when the access panel has been removed
Rear Port Control Cover	Yes, locks rear IO cables to prevent cable theft
Serial, Parallel, USB, Audio, Network, Enable/Disable Port Control	Yes, enables or disables serial, USB, audio, and network ports
Removable Media Write/Boot Control	Yes, prevents ability to boot from removable media on supported devices (and can disable writes to media)
Power-On Password	Yes, prevents an unauthorized person from booting up the workstation
Setup Password	Yes, prevents an unauthorized person from changing the workstation configuration
3.3V Aux Power LED on System PCA	Yes



## System Technical Specifications

NIC LEDs (integrated) (Green & Amber)	Yes
CPUs and Heatsinks	A T-15 Torx or flat blade screwdriver is needed to remove the CPU heatsink before the CPU can be removed. CPU removal is tool-less
Power supply diagnostic LED	Yes
Power Button	Yes, ACPI multi-function
Power LED	Yes, blue (normal), red (fault)
Hard drive activity LED	Yes, green
Internal speaker	Yes
System/Emergency ROM Flash Recovery	Recovers corrupted system BIOS.
Alert Standard Format (ASF) Specification	Version 2.0 support Industry-standard specification for network alerting in operating system-absent environments
Cooling Solutions	Air cooled forced convection, Optional processor liquid cooling solution
Power Supply Fans	92 mm x 92 mm x 25 mm 2-wire (non-serviceable)
CPU Heatsink Fan(s)	Mainstream (<=95W): 80 mm x 80 mm x 15 mm 5-wire PWM Performance (>95W): 92 mm x 92 mm x 25 mm 5-wire PWM
Chassis Fans	92 mm x 92mm x 25 mm 4-wire PWM
Memory Fans	No
HP Vision Diagnostics Offline Edition	<p><b>HP Vision Diagnostics Offline Edition</b></p> <p>The diagnostics utility enables you to perform testing and to view critical computer hardware and software configuration information from various sources. This utility enables you to:</p> <ul style="list-style-type: none"> <li>● Run diagnostics</li> <li>● View the hardware configuration of the system</li> </ul> <p><b>Key features and benefits</b></p> <p>HP Vision Diagnostics simplifies the process of effectively identifying, diagnosing, and isolating the hardware issues. In addition to robust management tools, service tools can be invaluable in quickly resolving system problems. To streamline the service process and resolve problems quickly, it is necessary to have the right information available at the time that a service call is placed. The primary information requirement, which is also the one that provides the greatest Vision into potential system issues, is the configuration of the system. Vision Diagnostics helps provide higher system availability.</p> <p>Typical uses of the Vision Diagnostics are:</p> <ul style="list-style-type: none"> <li>● Testing and diagnosing apparent hardware failures</li> <li>● Documenting system configurations for upgrade planning, standardization, inventory tracking, disaster recovery, and maintenance</li> <li>● Sending configuration information to another location for more in-depth analysis</li> </ul>
Access Panel Key Lock	No
ACPI-Ready Hardware	Advanced Configuration and Power Management Interface (ACPI). <ul style="list-style-type: none"> <li>● Allows the system to wake from a low power mode.</li> <li>● Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system</li> </ul>



## System Technical Specifications

Trusted Platform Module Chip with optional ProtectTools Software	Yes, Infineon SLB9635TT1.2
Integrated Chassis Handles	No
Power Supply	Requires T15 Torx or flat blade screwdriver
PCI Card Retention	Yes, rear (all), middle (none), front (full-length cards with extender)
Flash ROM	Yes
Diagnostic Power Switch LED on board	Yes
Clear Password Jumper	Yes
Clear CMOS Button	Yes
CMOS Battery Holder for easy Replacement	Yes
DIMM Connectors for easy Upgrade	Yes
HP ProtectTools Security Manager	Yes - Not supported on Microsoft XP x64 or Linux

<b>BIOS</b>	
BIOS 32-bit Services	Standard BIOS 32-bit Service Directory Proposal v0.4
PCI 3.0 Support	Full BIOS support for PCI Express through industry standard interfaces.
ATAPI	ATAPI Removable Media Device BIOS Specification Version 1.0.
BBS	BIOS Boot Specification v1.01.
WMI Support	WMI is Microsoft's implementation of Web-Based Enterprise Management (WBEM) for Windows. WMI is fully compliant with the Distributed Management Task Force (DMTF) Common Information Model (CIM) and WBEM specifications.
BIOS Boot Spec 1.01 +	Provides more control over how and from what devices the workstation will boot.
BIOS Power On	Users can define a specific date and time for the system to power on.
ROM Based Computer Setup Utility (F10)	Review and customize system configuration settings controlled by the BIOS.
System/Emergency ROM Flash Recovery with Video	Recovers system BIOS in corrupted Flash ROM.
Replicated Setup	Saves BIOS settings to diskette or USB flash device in human readable file. Repset.exe utility can then replicate these settings on machines being deployed without entering Computer Configuration Utility (F10 Setup).
SMBIOS	System Management BIOS 2.6, for system management information.
Boot Control	Disables the ability to boot from removable media on supported devices.
Memory Change Alert	Alerts management console if memory is removed or changed.
Thermal Alert	Monitors the temperature state within the chassis. Three modes: <ul style="list-style-type: none"> <li>● NORMAL - normal temperature ranges</li> <li>● ALERTED - excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown</li> </ul>



## System Technical Specifications

	<ul style="list-style-type: none"> <li>● SHUTDOWN - excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs</li> </ul>
<b>Remote ROM Flash</b>	Provides secure, fail-safe ROM image management from a central network console.
<b>ACPI (Advanced Configuration and Power Management Interface)</b>	<ul style="list-style-type: none"> <li>● Allows the system to enter and resume from low power modes (sleep states).</li> <li>● Enables an operating system to control system power consumption based on the dynamic workload.</li> <li>● Makes it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system.</li> <li>● Supports ACPI 2.0 for full compatibility with 64-bit operating systems.</li> </ul>
<b>Ownership Tag</b>	A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen.
<b>Remote Wakeup/Remote Shutdown</b>	System administrators can power on, restart, and power off a client computer from a remote location.
<b>Instantly Available PC (Suspend to RAM - ACPI sleep state S3)</b>	Allows for very low power consumption with quick resume time.
<b>Remote System Installation via F12 (PXE 2.1) (Remote Boot from Server)</b>	Allows a new or existing system to boot over the network and download software, including the operating system.
<b>ROM revision levels</b>	Reports the system BIOS revision level in Computer Configuration Utility (F10 Setup). Version is available through an industry standard interface (SMBIOS) so that management SW applications can use and report this information.
<b>System board revision level</b>	<ul style="list-style-type: none"> <li>● Allows management SW to read the revision level of the system board</li> <li>● Revision level is digitally encoded into the HW and cannot be modified.</li> </ul>
<b>Start-up Diagnostics (Power-on Self-Test)</b>	Assesses system health at boot time with selectable levels of testing.
<b>Auto Setup when new hardware installed</b>	System automatically detects addition of new hardware.
<b>Keyboard-less Operation</b>	The system can be booted without a keyboard.
<b>Localized ROM Setup</b>	Common BIOS image supports System Configuration Utility (F10 Setup) menus in 12 languages with local keyboard mappings.
<b>Asset Tag</b>	The user or MIS to set a unique tag string in non-volatile memory.
<b>Per-slot Control</b>	Allows I/O slot parameters (option ROM enable/disable, bus latency) to be configured individually.
<b>Adaptive Cooling</b>	Control parameters are set according to detected hardware configuration for optimal acoustics.
<b>Pre-boot Diagnostics</b>	(Pre-video) critical errors are reported via beeps and blinks on the power LED.
<b>Industry Standard Specification Support</b>	
<b>Industry Standard</b>	Revision Supported by the BIOS
<b>ACPI</b>	Advanced Configuration and Power Management Interface, Version 2.0c
<b>ASF</b>	Alert Standard Format Specification, Version 2.0
<b>ATA (IDE)</b>	ATA Attachment 6 with Packet Interface (ATA/ATAPI-6), Revision 3b
<b>CD Boot</b>	"El Torito" Bootable CD-ROM Format Specification Version 1.0
<b>EDD</b>	<ul style="list-style-type: none"> <li>● Enhanced Disk Drive Specification Version 1.1</li> <li>● BIOS Enhanced Disk Drive Specification Version 3.0</li> </ul>
<b>EHCI</b>	Enhanced Host Controller Interface for Universal Serial Bus, Revision 1.0



## System Technical Specifications

PCI	<ul style="list-style-type: none"> <li>● PCI Local Bus Specification, Revision 2.3</li> <li>● PCI Power Management Specification, Revision 1.1</li> <li>● PCI Firmware Specification, Revision 3.0, Draft .7</li> </ul>
PCI Express	PCI Express Base Specification, Revision 2.0
PMM	POST Memory Manager Specification, Version 1.01
SATA	<ul style="list-style-type: none"> <li>● Serial ATA Specification, Revision 1.0a</li> <li>● Serial ATA 3 Gb/s: Extensions to Serial ATA 1.5Gb/s, Revision 1.0</li> </ul>
SPD	PC SDRAM Serial Presence Detect (SPD) Specification, Revision 1.2B
TPM	Trusted Computing Group TPM Specification Version 1.2
UHCI	Universal Host Controller Interface Design Guide, Revision 1.1
USB	Universal Serial Bus Revision 1.1 Specification  Universal Serial Bus Revision 2.0 Specification  Universal Serial Bus Revision 3.0 Specification
SMBIOS	System Management BIOS Reference Specification, Version 2.6

## Social and Environmental Responsibility

Eco-Label Certifications & Declarations	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>● ENERGY STAR® (energy-saving features available on selected configurations -Windows only)</li> <li>● US Federal Energy Management Program (FEMP)</li> <li>● EPEAT Gold® for all ENERGY STAR® configurations. For more details and a list of countries in which this product is registered, please visit the following link:  <a href="http://www.epeat.net/ProductDisplay.aspx?return=search&amp;action=view&amp;search=true&amp;productid=2478&amp;ProductType=5&amp;epeatcountryid=1">http://www.epeat.net/ProductDisplay.aspx?return=search&amp;action=view&amp;search=true&amp;productid=2478&amp;ProductType=5&amp;epeatcountryid=1</a></li> <li>● China Energy Conservation Program</li> <li>● IT ECO declaration</li> <li>● Japan PC Green label*</li> </ul> <p>*This product conforms to the examination standards (2003 version) under JEITA's 'PC Green Label System.'</p>
Batteries	<p>This product complies with ISO standards:</p> <ul style="list-style-type: none"> <li>● EU Directive 91/ 157/ EEC</li> <li>● EU Directive 93/ 86/ EEC</li> <li>● EU Directive 98/ 101/ EEC</li> </ul> <p>Batteries used in the product do not contain:</p> <ul style="list-style-type: none"> <li>● Mercury greater than 5ppm by weight</li> <li>● Cadmium greater than 10ppm by weight</li> <li>● Lead greater than 40ppm by weight</li> </ul> <p>Battery size: CR2032 (coin cell)            Battery type: Lithium</p>
Restricted Material Usage	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at</p>





## System Technical Specifications

	<p><a href="http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html">http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html</a>):</p> <ul style="list-style-type: none"> <li>● Asbestos</li> <li>● Batteries - Mercury</li> <li>● Batteries - Cadmium</li> <li>● Batteries - Lead (non-rechargeable)</li> <li>● Batteries - Non-rechargeable Alkaline and Carbon-Zinc Batteries</li> <li>● Batteries - Classification as "Not Restricted" for Transport</li> <li>● Brominated Flame Retardants (PBBs, PBDEs, including DecaBDE)</li> <li>● Brominated Flame Retardants (all BFRs in external case plastic parts)</li> <li>● Cadmium and its compounds</li> <li>● Certain Azo Colorants</li> <li>● Chlorinated Hydrocarbons</li> <li>● Chlorinated Paraffins</li> <li>● Formaldehyde</li> <li>● Formaldehyde - emissions</li> <li>● Hexavalent Chromium and its compounds in metallic applications</li> <li>● Hexavalent Chromium and its compounds in non-metallic applications</li> <li>● Lead and its compounds</li> <li>● Lead in paint</li> <li>● Lead in Polyvinyl Chloride (PVC) coating of external cables, wires and cords</li> <li>● Mercury and its compounds</li> <li>● Nickel on external surfaces</li> <li>● Ozone Depleting Substances (ODS)</li> <li>● Polycyclic Aromatic Hydrocarbons (PAH)</li> <li>● Perfluorooctane sulfonates (PFOS) in parts</li> <li>● Perfluorooctane sulfonates (PFOS) in preparations</li> <li>● Polychlorinated Biphenyls (PCBs) and Polychlorinated Terphenyls (PCTs)</li> <li>● Polychlorinated Naphthalenes</li> <li>● Polyvinyl Chloride (PVC) in external case plastic parts</li> <li>● Radioactive Substances</li> <li>● Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>
<p><b>Packaging</b></p>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>● Eliminate the use of heavy metals such as lead, chromium, mercury, and cadmium in packaging materials.</li> <li>● Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>● Design packaging materials for ease of disassembly.</li> <li>● Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>● Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>● Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>● Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<p><b>Packaging Materials</b></p>	
<p>Internal</p>	<p>LDPE Foam: .366 kg</p>
<p>External</p>	<p>Cardboard carton and insert: 1.536 kg</p>
<p><b>End-of-Life Management and Recycling</b></p>	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/recycle">http://www.hp.com/recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p>



## System Technical Specifications

<p>Hewlett-Packard Corporate Environmental Information</p>	<p>For more information about HP's commitment to the environment: Global Citizenship Report: <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a> Eco-label certifications: <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html">http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html</a> ISO 14001 certificates: <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html">http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html</a></p>
<p>Service, Support and Warranty</p>	<p>On-site Warranty and Service (<sup>Note 1</sup>): One and three-years, limited warranty and service offering delivers on-site, next business-day (<sup>Note 2</sup>) service for parts and labor and includes free telephone support (<sup>Note 3</sup>) 8am - 5pm. Global coverage (<sup>Note 2</sup>) ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering</p> <p><b>NOTE 1:</b> Terms and conditions may vary by country. Certain restrictions and exclusions apply. <b>NOTE 2:</b> On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country. <b>NOTE 3:</b> Technical telephone support applies only to HP-configured, HP and HP-qualified, third-party hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.</p> <p>HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at <a href="http://www.hp.com/go/lookuptool">http://www.hp.com/go/lookuptool</a>. Additional HP Care Pack Services information by product is available at <a href="http://www.hp.com/hps/carepack">http://www.hp.com/hps/carepack</a>. Service levels and response times for HP Care Packs may vary depending on your geographic location</p>
<p>Additional Information</p>	<ul style="list-style-type: none"> <li>• This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.</li> <li>• This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>• This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.</li> <li>• Plastic parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.</li> <li>• This product contains 0% recycled materials (by weight)</li> <li>• This product is &gt;90% recycle-able when properly disposed of at end of life.</li> </ul>

<p><b>Manageability</b></p>	
<p>Remote Manageability Software Solutions</p>	<p>Visit: <a href="http://www.hp.com/go/easydeploy">http://www.hp.com/go/easydeploy</a></p>
<p>System Software Manager</p>	<p>Visit: <a href="http://www.hp.com/go/ssm">http://www.hp.com/go/ssm</a></p>
<p>Product Change Notification</p>	<ul style="list-style-type: none"> <li>• Program to proactively communicate Product Change Notifications (PCNs) and Customer Advisories by email to customers, based on a user-defined profile.</li> <li>• PCNs provide advance notification of hardware and software changes to be implemented in the factory providing time to plan for transition.</li> <li>• Customer Advisories provide concise, effective problem resolution, greatly reducing the need to call technical support.</li> </ul>



### Stable & Consistent Offerings

As part of its commitment to hardware, software, and solution innovation, HP is proud to introduce this breakthrough platform configuration stability to HP Workstation customers. HP Stable & Consistent Offerings are built on the foundation of a carefully chosen set of hardware and software designed and tested to work with all HP Z Workstation platforms through their end of life. These components and their corresponding HP Workstation platform compatibility are outlined in this section.

HP Stable & Consistent Offerings are available worldwide to all HP Workstation customers-no special programs, no additional cost-no kidding. Simply select your hardware and software components when you customize your HP Workstation and be assured that you'll be able to buy that same configuration throughout the lifecycle of the product.

Processors	Product #	Offering
	NF136AV	Intel Xeon W3520, 2.66GHz, 8MB cache, 1066 memory, 4.8GT/s QPI, Quad-Core, HT, Turbo
	VU898AV	Intel Xeon W3565, 3.20GHz, 8MB cache, 1066 memory, 4.8GT/s QPI, Quad-Core, HT, Turbo
	WH058AV	Intel Xeon W3680, 3.33GHz, 12MB cache, 1333 memory, 6.4GT/s QPI, Six-Core, HT, Turbo

Hard Drives	Product #	Offering
	FX638AV	HP 250GB SATA 7200 1st HDD
	FX648AV	HP 250GB SATA 7200 2nd HDD
	FX658AV	HP 250GB SATA 7200 3rd HDD
	FX640AV	HP 500GB SATA 7200 1st HDD
	FX650AV	HP 500GB SATA 7200 2nd HDD
	FX660AV	HP 500GB SATA 7200 3rd HDD
	XB107AV	HP 500GB SATA 7200 4th HDD

Graphics	Product #	Offering
	FZ347AV	NVIDIA Quadro NVS 295 256MB Graphics Card
	FZ356AV	NVIDIA Quadro NVS 295 256MB Graphics (2nd)
	WS070AV	NVIDIA Quadro 2000 1GB Graphics
	WS071AV	NVIDIA Quadro 2000 1GB Graphics (2nd)

Memory	Product #	Offering
	NL980AV	3GB (3x1GB) DDR3-1333 ECC Unbuffered RAM
	NL982AV	6GB (3x2GB) DDR3-1333 ECC Unbuffered RAM
	NL984AV	12GB (3x4GB) DDR3-1333 ECC Unbuffered RAM

Optical and Removable Storage	Product #	Offering
	FX681AV	HP 16X DVD+-RW SuperMulti SATA 1st Drive
	FX682AV	HP 16X DVD+-RW SuperMulti SATA 2nd Drive



## *Stable & Consistent Offerings*

Input Devices	Product #	Offering
	FX677AV	HP USB Optical Scroll Mouse
	FZ362AV	HP USB Standard Keyboard

---

Operating Systems	Product #	Offering
	VM432AV	Genuine Windows® 7 Professional 64-bit



### Technical Specifications - Processors

Processors	Intel Xeon W3503, 2.40GHz, 4MB cache, 1066 memory, 4.8GT/s QPI, Dual-Core
	Intel Xeon W3505, 2.53GHz, 4MB cache, 1066 memory, 4.8GT/s QPI, Dual-Core
	Intel Xeon W3520, 2.66GHz, 8MB cache, 1066 memory, 4.8GT/s QPI, Quad-Core, HT, Turbo
	Intel Xeon W3550, 3.06GHz, 8MB cache, 1066 memory, 4.8GT/s QPI, Quad-Core, HT, Turbo
	Intel Xeon W3565, 3.20GHz, 8MB cache, 1066 memory, 4.8GT/s QPI, Quad-Core, HT, Turbo
	Intel Xeon W3670, 3.20GHz, 12MB cache, 1066 memory, 4.8GT/s QPI, Six-Core, HT, Turbo
	Intel Xeon W3680, 3.33GHz, 12MB cache, 1333 memory, 6.4GT/s QPI, Six-Core, HT, Turbo
	Intel Xeon W3690, 3.46GHz, 12MB cache, 1333 memory, 6.4GT/s QPI, Six-Core, HT, Turbo

## Introduction

Intel's latest-generation microarchitecture represents the next step in unprecedented processor performance and dynamic scalability. Designed from the ground up, Intel® Microarchitecture unleashes parallel processing performance technology providing an integrated memory controller and high-speed interconnect per independent processing core.

## Performance and Features

Intel® Microarchitecture offers the latest in processor innovation, including:

- Dynamic scalability, managed cores, threads, cache, interfaces, and power for energy-efficient performance on demand
- Design and performance scalability for servers, workstations, notebooks and desktops with support for 2-8+ cores and up to 16+ threads with Intel® Hyper-Threading Technology (Intel® HT Technology), and scalable cache sizes, system interconnects, and integrated memory controllers
- Intel® Turbo Boost Technology delivers additional performance automatically when needed by taking advantage of the processor's power and thermal headroom. This enables increased performance of both multi-threaded and single-threaded workloads.
- Intel Hyper-Threading Technology brings high-performance applications into mainstream computing with 1-16+ threads optimized for a new generation multi-core processor architecture.
- Scalable shared memory of Intel® QuickPath technology features memory distributed to each processor with integrated memory controllers and high-speed point-to-point interconnects to unleash the performance of future versions of next-generation Intel® multi-core processors.
- Multi-level shared cache improves performance and efficiency by reducing latency to frequently used data.

## Turbo Boost Technology

This technology, now built into Xeon 3500 Series Quad-Core and Xeon 3600 6-Core processors, will increase the speed of your processor on demand if the CPU is operating below power or thermal specifications:

- Benefit of Turbo Boost (how much the CPU speeds up) depends on number of active cores
- Likelihood of Turbo Boost operation increases when less cores are active and when dynamic power management is enabled



### Technical Specifications - Hard Drives

HP SAS (Serial Attached SCSI) Hard Drives for HP Workstations

600GB SAS 15K rpm  
6Gb/s 3.5" HDD

<b>Capacity</b>	600GB
<b>Height</b>	1 in; 2.54 cm
<b>Width</b>	<b>Media Diameter</b> 3.5 in; 8.9 cm
	<b>Physical Size</b> 4 in; 10.17 cm
<b>Interface</b>	SAS
<b>Synchronous Transfer Rate (Maximum)</b>	6.0 Gb/s
<b>Buffer</b>	16 MB
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b> 0.2 ms
	<b>Average</b> 3.4 ms
	<b>Full Stroke</b> 6.6 ms
<b>Rotational Speed</b>	15,000 rpm
<b>Logical Blocks</b>	1,172,123,568 - 512 byte blocks
<b>Operating Temperature</b>	50° to 95° F (10° to 35° C)

450GB SAS 15K rpm  
6Gb/s 3.5" HDD

<b>Capacity</b>	450GB
<b>Height</b>	1 in; 2.54 cm
<b>Width</b>	<b>Media Diameter</b> 3.5 in; 8.9 cm
	<b>Physical Size</b> 4 in; 10.17 cm
<b>Interface</b>	SAS
<b>Synchronous Transfer Rate (Maximum)</b>	6Gb/s
<b>Buffer</b>	16MB
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b> 0.2 ms
	<b>Average</b> 3.4 ms
	<b>Full Stroke</b> 6.6 ms
<b>Rotational Speed</b>	15,000 rpm
<b>Operating Temperature</b>	50° to 95° F (10° to 35° C)

300GB SAS 15K rpm  
6Gb/s 3.5" HDD

<b>Capacity</b>	300GB
<b>Height</b>	1 in; 2.54 cm
<b>Width</b>	<b>Media Diameter</b> 3.5 in; 8.9 cm
	<b>Physical Size</b> 4 in; 10.17 cm
<b>Interface</b>	SAS
<b>Synchronous Transfer Rate (Maximum)</b>	6Gb/s
<b>Buffer</b>	16MB
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b> 0.2 ms
	<b>Average</b> 3.4 ms
	<b>Full Stroke</b> 6.6 ms



## Technical Specifications - Hard Drives

		<b>Rotational Speed</b>	15,000 rpm		
		<b>Operating Temperature</b>	50° to 95° F (10° to 35° C)		
SATA (Serial ATA) Hard Drives for HP Workstations	600GB SATA 10K rpm SFF in 3.5" Frame HDD	<b>Capacity</b>	600GB		
		<b>Height</b>	1 in; 2.54 cm		
		<b>Width</b>	<b>Media Diameter</b>	2.5 in; 6.36 cm	
			<b>Physical Size</b>	4 in; 10.17 cm	
		<b>Interface</b>	Serial ATA (3.0Gb/s)		
		<b>Synchronous Transfer Rate (Maximum)</b>	Up to 300MB/s		
		<b>Buffer</b>	32MB		
		<b>Cache</b>	Segmentable		
		<b>Seek Time (typical reads, includes controller overhead, including settling)</b>	<b>Single Track</b>	0.4 ms (max)	
			<b>Average</b>	3.6 ms	
			<b>Full Stroke</b>	9.0 ms	
		<b>Rotational Speed</b>	10,000 rpm		
		<b>Logical Blocks</b>	1,172,123,568		
		<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)		
			300GB SATA 10K rpm SFF in 3.5" Frame HDD	<b>Capacity</b>	300,069,052,416 bytes
	<b>Height</b>	1 in; 2.54 cm			
	<b>Width</b>	<b>Media Diameter</b>		2.5 in; 6.36 cm	
		<b>Physical Size</b>		4 in; 10.17 cm	
	<b>Interface</b>	Serial ATA (3.0 Gb/s), Native Command Queuing enabled			
	<b>Synchronous Transfer Rate (Maximum)</b>	Up to 300 MB/s			
	<b>Cache</b>	16 MB			
	<b>Seek Time (typical reads, includes controller overhead, including settling)</b>	<b>Single Track</b>		0.7 ms (maximum)	
		<b>Average</b>		4.4 ms	
		<b>Full Stroke</b>		9.5 ms	
	<b>Rotational Speed</b>	10,000 rpm			
	<b>Logical Blocks</b>	586,072,368			
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)			
	160GB SATA 10K rpm SFF in 3.5" Frame HDD	<b>Capacity</b>		160,041,885,696 bytes	
		<b>Height</b>		1 in; 2.5 cm	
		<b>Width</b>	<b>Media Diameter</b>	2.5 in; 6.36 cm	
			<b>Physical Size</b>	4 in; 10.17 cm	
		<b>Interface</b>	Serial ATA (1.5 Gb/s), Native Command Queuing enabled		



## Technical Specifications - Hard Drives

	<b>Synchronous Transfer Rate (Maximum)</b>	Up to 300 MB/s	
	<b>Buffer</b>	16 MB	
	<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	0.7 ms (maximum)
		<b>Average</b>	4.4 ms
		<b>Full Stroke</b>	9.5 ms
	<b>Rotational Speed</b>	10,000 rpm	
	<b>Logical Blocks</b>	312,581,808	
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
<b>2.0TB SATA 7200 rpm 3Gb/s 3.5" HDD</b>	<b>Capacity</b>	2.0TB	
	<b>Height</b>	1 in; 2.54 cm	
	<b>Width</b>	<b>Media Diameter</b>	3.5 in; 8.9 cm
		<b>Physical Size</b>	4.0 in; 10.17 cm
	<b>Interface</b>	Serial ATA (3.0 Gb/s), Native Command Queuing Enabled	
	<b>Synchronous Transfer Rate (Maximum)</b>	Up to 300MB/s	
	<b>Buffer</b>	64MB	
	<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	1.0 ms
		<b>Average</b>	10 ms
		<b>Full Stroke</b>	Not Specified
	<b>Rotational Speed</b>	7,200 rpm	
	<b>Logical Blocks</b>	3,907,029,168	
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
<b>1.5TB SATA 7200 rpm 3Gb/s 3.5" HDD</b>	<b>Capacity</b>	1.5TB	
	<b>Height</b>	1 in; 2.54 cm	
	<b>Width</b>	<b>Media Diameter</b>	3.5 in; 8.9 cm
		<b>Physical Size</b>	4.0 in; 10.17 cm
	<b>Interface</b>	Serial ATA (3.0 Gb/s), Native Command Queuing enabled	
	<b>Synchronous Transfer Rate (Maximum)</b>	Up to 300MB/s	
	<b>Buffer</b>	32MB	
	<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	2 ms
		<b>Average</b>	11 ms
		<b>Full Stroke</b>	21 ms
	<b>Rotational Speed</b>	7,200 rpm	
	<b>Logical Blocks</b>	2,930,277,168	
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	





### Technical Specifications - Hard Drives

1TB SATA 7200 rpm 3.0Gb/s 3.5" HDD	<b>Capacity</b>	1,000,204,886,016 bytes
	<b>Height</b>	1 in; 2.5 cm
	<b>Width</b>	<b>Media Diameter</b> 3.5 in; 8.9 cm
		<b>Physical Size</b> 4 in; 10.17 cm
	<b>Interface</b>	Serial ATA (3.0 Gb/s), Native Command Queuing enabled
	<b>Synchronous Transfer Rate (Maximum)</b>	Up to 300 MB/s
	<b>Buffer</b>	32 MB
	<b>Seek Time (typical reads, includes controller overhead, including settling)</b>	<b>Single Track</b> 2 ms
		<b>Average</b> 11 ms
		<b>Full Stroke</b> 21 ms
	<b>Rotational Speed</b>	7,200 rpm
	<b>Logical Blocks</b>	1,953,525,168
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)
500GB SATA 7200 rpm 3Gb/s 3.5" HDD	<b>Capacity</b>	500,107,862,016 bytes
	<b>Height</b>	1 in; 2.5 cm
	<b>Width</b>	<b>Media Diameter</b> 3.5 in; 8.9 cm
		<b>Physical Size</b> 4 in; 10.17 cm
	<b>Interface</b>	Serial ATA (3.0 Gb/s), Native Command Queuing enabled
	<b>Synchronous Transfer Rate (Maximum)</b>	300 MB/s
	<b>Buffer</b>	16 MB
	<b>Seek Time (typical reads, includes controller overhead, including settling)</b>	<b>Single Track</b> 2 ms
		<b>Average</b> 11 ms
		<b>Full Stroke</b> 21 ms
	<b>Rotational Speed</b>	7,200 rpm
	<b>Logical Blocks</b>	976,773,168
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)
320GB SATA 7200 rpm 3Gb/s 3.5" HDD	<b>Capacity</b>	320,072,933,376 bytes
	<b>Height</b>	0.98 in; 2.5 cm
	<b>Width</b>	<b>Media Diameter</b> 3.5 in; 8.9 cm
		<b>Physical Size</b> 4.0 in; 10.17 cm
	<b>Interface</b>	Serial ATA (3.0 Gb/s), Native Command Queuing enabled
	<b>Synchronous Transfer Rate (Maximum)</b>	300 MB/s
	<b>Buffer</b>	8 MB



### Technical Specifications - Hard Drives

	<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	2 ms	
		<b>Average</b>	12 ms	
		<b>Full Stroke</b>	21 ms	
	<b>Rotational Speed</b>	7,200 rpm		
	<b>Logical Blocks</b>	625,142,448		
	<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)		
250GB SATA 7200 rpm 3Gb/s 3.5" HDD	<b>Capacity</b>	250,059,350,016 bytes		
	<b>Height</b>	1 in; 2.54 cm		
	<b>Width</b>	<b>Media Diameter</b>	3.5 in; 8.9 cm	
		<b>Physical Size</b>	4.0 in; 10.17 cm	
	<b>Interface</b>	Serial ATA (3.0 Gb/s), Native Command Queuing enabled		
	<b>Synchronous Transfer Rate</b> (Maximum)	300 MB/s		
	<b>Buffer</b>	8 MB		
	<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	2 ms	
		<b>Average</b>	11 ms	
		<b>Full Stroke</b>	21 ms	
		<b>Rotational Speed</b>	7,200 rpm	
		<b>Logical Blocks</b>	488,397,168	
		<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
160GB SATA 7200 rpm 3Gb/s 3.5" HDD	<b>Capacity</b>	160,041,885,696 bytes		
	<b>Height</b>	1 in; 2.5 cm		
	<b>Width</b>	<b>Media Diameter</b>	3.5 in; 8.9 cm	
		<b>Physical Size</b>	4 in; 10.2 cm	
	<b>Interface</b>	Serial ATA (3.0 Gb/s), Native Command Queuing enabled		
	<b>Synchronous Transfer Rate</b> (Maximum)	300 MB/s		
	<b>Buffer</b>	8 MB		
	<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track</b>	2 ms	
		<b>Average</b>	11 ms	
		<b>Full Stroke</b>	21 ms	
		<b>Rotational Speed</b>	7,200 rpm	
		<b>Logical Blocks</b>	312,581,808	
		<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	



## Technical Specifications - Hard Drives

HP Solid State Drives for Workstations

HP 160GB SATA SSD	Capacity	160GB	
	Width	Media Diameter	NaN in; NaN cm
		Physical Size	2.5 in; 6.36 cm
	Interface	SATA	
	Synchronous Transfer Rate (Maximum)	3Gb/s	
	Operating Temperature	32° to 158° F (0° to 70° C)	
HP 300GB SATA SSD	Capacity	300GB	
	Width	Physical Size	2.5 in; 6.36 cm
	Interface	SATA	
	Synchronous Transfer Rate (Maximum)	3Gb/s	
	Operating Temperature	32° to 158° F (0° to 70° C)	
HP 160GB SATA X25-M SSD	Capacity	160,041,885,696 bytes	
	Height	0.28 in; 0.7 cm	
	Width	Media Diameter	NaN in; N/A cm
		Physical Size	2.5 in; 6.36 cm
	Interface	SATA	
	Synchronous Transfer Rate (Maximum)	3Gb/s	
	Seek Time (typical reads, includes controller overhead, including settling)	Average	Read: 75 microseconds; Write: 85 microseconds
	Logical Blocks	312,581,808	
	Operating Temperature	32° to 158° F (0° to 70° C)	



## Technical Specifications - Hard Drive Controllers

LSI 9212 4-Port SAS 6Gb/s RAID Card	PCI Bus	8-lane, 5GT/s PCI Express 2.0	
	PCI Modes	Bus Master DMA	
	RAID Levels	RAID 0, 1, 1E and 10	
	PCI Data Burst Transfer Rate	Half Duplex, x4 PCIe 2000 MB/s Full Duplex, x8 PCIe 4000 MB/s	
	SAS Bandwidth	<b>Half Duplex</b>	Single lane - 600 MB/s Wide Port (2 lanes) - 1200 MB/s Wide Port (4 lanes) - 2400 MB/s
		<b>Full Duplex</b>	Single SAS Lane - 1200 MB/s Wide Port (2 lanes) - 2400 MB/s Wide Port (4 lanes) - 4800 MB/s
	PCI Card Type	3.3V Add-in card	
	PCI Voltage	12 V ± 10%	
	PCI Power	13.5 Watts	
	Bracket	Full height and Low-profile	
	Certification Level	PCI-Express 2.0	
	IO Bus	1x4 6Gb/s SAS ports	
	SAS Processor	LSISAS2008	
	Internal Connectors	Four x1 SATA	
	External Connectors	None	
	Maximum Number of SCSI Devices	256	
	LED Indicators	Internal Activity/Fault per x4 port - Heartbeat	

LSI MegaRAID® SAS 8888ELP Host Bus Adapter (HBA)	PCI Bus	PCI-Express x8 lanes
	PCI Modes	Bus Master DMA
	RAID Levels	RAID 0, 1, and 5 RAID spans 10 and 50
	PCI Data Burst Transfer Rate	Up to 3Gb/s per port
	Full Duplex	Up to 1.5 GB/s
	PCI Voltage	+3.3V Add-in Card
	PCI Power	19.2 Watts Maximum
	Certification Level	PCI-Express 1.0a
	IO Bus	Eight 3Gb/s SAS/SATA ports
	Internal Connectors	Two SAS SFF8087 x4
	External Connectors	Two SAS SFF8088 x4
	Maximum Number of SCSI Devices	32
	LED Indicators	Connector LEDs indicate whether the internal or external connector is active for ports 0-3 and 4-7



## Technical Specifications - Hard Drive Controllers

---

LSI MegaRAID® 9260-8i	PCI Bus	PCI-Express (Gen2) V2.0 x8 lanes
SAS 6Gb/s ROC RAID	PCI Modes	Bus Master DMA
Card and iBBU08 Battery Backup Unit	RAID Levels	RAID 0, 1, 5, and 6 RAID spans 10, 50 and 60
	PCI Data Burst Transfer Rate	Up to 4GB/s
	PCI Card Type	Low profile, single PCIe slot design with full height bracket.
		The optional iBBU08 Battery Backup unit mounts on the controller card and the assembly remains within a single PCIe slot width.
	PCI Voltage	+3.3V Add-in Card
	PCI Power	12.5 Watts
	Certification Level	PCI-Express 2.0
	IO Bus	Eight 3 Gb/s and 6Gb/s compatible SAS/SATA ports
	Internal Connectors	Two SAS SFF8087 x4
	External Connectors	None
	Maximum Number of SCSI Devices	32. <b>NOTE:</b> HP Workstations do not support this many internal drives.
	LED Indicators	Connector LEDs indicate whether the internal connector is active for ports 0-3 and 4-7



### Technical Specifications - Graphics

NVIDIA Quadro NVS 295 Form Factor	2.731 inches (H) × 6.600 inches (L), Half-Height
256MB Graphics Card	
<b>Graphics Controller</b>	NVIDIA Quadro NVS 295 Graphics Board
<b>Bus Type</b>	PCI Express x16, Generation 2.0
<b>Memory</b>	256 MB GDDR3 SDRAM unified graphics memory
<b>Connectors</b>	2 DisplayPort Comes with 2 DisplayPort to DVI-D Adapters ('DisplayPort to VGA' and 'DisplayPort to DL DVI' adapters available as an accessory)
<b>Maximum Resolution</b>	Two DisplayPort outputs drive two digital displays up to 2560 x 1600
<b>Display Output</b>	<b>NOTE:</b> This card supports up to two displays <ul style="list-style-type: none"><li>• Drives DisplayPort enabled digital displays at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking</li><li>• Drives DVI enabled digital displays at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking (through DisplayPort to DVI-D (single link) cable)</li></ul>
<b>Supported Graphics APIs</b>	OpenGL 3.0 DirectX 10.0
<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) WS4 (64-bit and 32-bit) <i>* WS4 not supported on Z200 &amp; Z200 SFF</i> Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation (64-bit and 32-bit) SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>  SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>
<b>Power Consumption</b>	<24 Watts



### Technical Specifications - Graphics

<b>NVIDIA NVS 300 512MB Graphics Card</b>	<b>Form Factor</b>	2.7 inches (H) x 5.7 inches (L), Half-Height
	<b>Graphics Controller</b>	NVIDIA NVS 300 Graphics Board
	<b>Bus Type</b>	PCI Express x16, Generation 2.0
	<b>Memory</b>	512 MB GDDR3 SDRAM unified graphics memory
	<b>Connectors</b>	DMS-59 Includes DMS-59 to Dual DVI-I adapter DMS-59 to Dual DisplayPort adapter and DMS-59 to Dual VGA adapter available as an option DMS-59 to Dual DisplayPort adapter required for HP ZR30w Display
	<b>Maximum Resolution</b>	DVI: two digital displays up to 1920 x 1200 DisplayPort: two digital displays up to 2560 x 1600 VGA: two analog displays up to 1920 x 1080
	<b>Image Quality Features</b>	
	<b>Display Output</b>	This card support up to two displays: <ul style="list-style-type: none"><li>• Drives DVI enabled digital displays at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking</li><li>• Drives DisplayPort enabled digital displays at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking (through optional DMS-59 to DisplayPort adapter)</li><li>• Drives VGA enabled analog displays at resolutions up to 1920 x 1080 (through optional DMS-59 to VGA adapter)</li></ul>
	<b>Supported Graphics APIs</b>	OpenGL 3.3 DirectX 10.1
	<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>  Novell SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>
	<b>Power Consumption</b>	<18 Watts



### Technical Specifications - Graphics

AMD FirePro 2270 512MB Graphics Card	<b>Form Factor</b>	Low Profile, Half Length, 2.3" x 6.6"
	<b>Graphics Controller</b>	AMD FirePro™ 2270 Professional Graphics
	<b>Bus Type</b>	PCI Express™ x16 Generation 2.0
	<b>Memory</b>	512MB DDR3
	<b>Connectors</b>	DMS-59 connector to support breakout cables for dual DisplayPort, DVI and VGA output. DMS-59 to Dual DVI adapter included. (Display Port and VGA adapters sold separately)
	<b>Maximum Resolution</b>	Digital 2560x1600 (DisplayPort) Analog 1920x1200 (DVI 60 Hz/ VGA 75Hz)
	<b>RAMDAC</b>	400 MHz DAC, 10-bit per channel
	<b>Display Output</b>	Card supports up to two displays
	<b>Supported Graphics APIs</b>	DirectX 11 and OpenGL 4.0
	<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>
	<b>Power Consumption</b>	17W Maximum

---

NVIDIA Quadro NVS 450 512 MB PCIe Graphics Card	<b>Form Factor</b>	ATX Full Height, 1/2 length Passive cooling
	<b>Bus Type</b>	PCI Express x16, Generation 2.0
	<b>Memory</b>	512 MB GDDR3 (256MB per GPU)
	<b>Connectors</b>	Four DisplayPort; Four DisplayPort to DVI-D adapters included. (‘DisplayPort to VGA’ and ‘DisplayPort to Dual Link DVI’ adapters available as an accessory)
	<b>Maximum Resolution</b>	DisplayPort connectors support ultra-high-resolution panels (up to 2560 x 1600)
	<b>Supported Graphics APIs</b>	<b>NOTE: This card supports up to four displays</b> OpenGL 3.0 DirectX 10.0
	<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Microsoft Windows Vista (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>





### Technical Specifications - Graphics

		SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>	
	<b>Power Consumption</b>	<40 Watts	
<hr/>			
<b>NVIDIA Quadro FX 380 256MB Graphics Card</b>	<b>Form Factor</b>	4.376 inches (H) × 6.60 inches (L)	
	<b>Graphics Controller</b>	NVIDIA Quadro FX 380 Graphics Board	
	<b>Bus Type</b>	PCI Express x16, Generation 2.0	
	<b>Memory</b>	256 MB GDDR3 SDRAM unified graphics memory	
	<b>Connectors</b>	2 Dual-Link DVI-I Two DVI to VGA adapters included	
	<b>Maximum Resolution</b>	Two dual-link DVI-I outputs drive two digital displays at resolutions up to 2560 x 1600 @ 60Hz or two analog displays at resolutions up to 2048 x 1536 @ 85Hz <b>NOTE:</b> This card supports up to two displays	
	<b>RAMDAC</b>	Dual Internal 400 MHz DAC	
	<b>Shading architecture</b>	Full Shader Model 4.0 (OpenGL 2.1/DirectX 10 class) <ul style="list-style-type: none"><li>• Long fragment programs (unlimited instructions)</li><li>• Long vertex programs (unlimited instructions)</li><li>• Looping and subroutines (up to 256 loops per vertex program)</li><li>• Dynamic flow control</li><li>• Conditional execution</li></ul>	
	<b>Supported graphics APIs</b>	OpenGL 3.0 DirectX 10.0	
	<b>Available graphics drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) WS4 (64-bit and 32-bit) <b>* WS4 not supported on Z200 &amp; Z200 SFF</b> Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)	
		HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>	
		Novell SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>	
		<b>Power consumption</b>	34 Watts



## Technical Specifications - Graphics

<b>NVIDIA Quadro 400 512MB Graphics Card</b>	<b>Form Factor</b>	Low Profile, 2.7 inches (H) x 5.6 inches (L)
	<b>Graphics Controller</b>	NVIDIA Quadro 400 Graphics Board
	<b>Bus Type</b>	PCI Express x 16, Generation 2.0
	<b>Memory</b>	512MB DDR3 SDRAM
	<b>Connectors</b>	One (1) Dual-link DVI-I One (1) DisplayPort 1.1 Includes one DisplayPort to DVI-D adapter
	<b>Maximum Resolution</b>	DisplayPort 1.1: 2560 x 1600 @ 60 Hz Dual Link DVI-I: 2560 x 1600 @ 60 Hz Analog: 2048 x1536 @ 85 Hz
	<b>RAMDAC</b>	Dual internal 400 MHz DACs
	<b>Display Output</b>	This card supports up to two displays
	<b>Supported Graphics APIs</b>	OpenGL 3.2 DirectX 10.1 Shader Model 4.1
	<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) WS4 (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)
	<p>HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a></p> <p>Novell SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a></p>	
	<b>Power Consumption</b>	< 35 Watts

---

<b>NVIDIA Quadro 600 1GB Graphics Card</b>	<b>Form Factor</b>	2.731" H x 6.6" L Single Slot Small Form Factor
	<b>Graphics Controller</b>	NVIDIA Quadro 600 Graphics Card
	<b>Bus Type</b>	PCI Express 2.0 x16
	<b>Memory</b>	1 GB GDDR3 128-bit
	<b>Connectors</b>	1 DVI-I output, 1 DisplayPort output One DP to DVI adapter included with card
	<b>Maximum Resolution</b>	DVI to VGA, DisplayPort to VGA and DisplayPort to DVI adapters available as accessories DisplayPort (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz) Dual-link DVI-I output (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)
	<b>Shading Architecture</b>	Shader Model 5.0



### Technical Specifications - Graphics

<b>Supported Graphics APIs</b>	OpenGL 4.0 DirectX 11 CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) WS4 (64-bit and 32-bit) <i>* WS4 not supported on Z200 and Z200 SFF</i> Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>  SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>
<b>Power Consumption</b>	40 Watts

#### ATI FirePro V3800 512MB Graphics Card

<b>Form Factor</b>	2.71 in (H) x 6.61 in (L) "Single-Wide"
<b>Graphics Controller</b>	ATI FirePro V3800 Graphics Board
<b>Bus Type</b>	PCI Express x16, Generation 2.0
<b>Memory</b>	512 MB DDR3 SDRAM
<b>Connectors</b>	1 DL DVI, 1 DP output One DP to DVI adapter included
<b>Maximum Resolution</b>	Up to two digital displays at resolutions up to 2560 x 1600 @ 60Hz or two analog displays, one at resolutions up to 2048 x 1536 @ 85Hz, the other at up to 1920 x 1200 @ 60Hz (165 MHz dot clock) <b>NOTES:</b> This card supports up to two displays Use of more than two displays on Linux requires support for xrandr 1.2 or greater in the X server
<b>RAMDAC</b>	400 MHz DAC, 10-bits per channel
<b>Image Quality Features</b>	<ul style="list-style-type: none"><li>● Full 30-bit display pipeline for more accurate color reproduction superior image quality (30-bit monitor required for full 30-bit display)</li><li>● Advanced video capabilities, including high fidelity gamma, color correction and scaling</li><li>● Dedicated hardware (UVD2) for H.264, VC-1, and MPEG2 decode</li></ul>
<b>Shading architecture</b>	<ul style="list-style-type: none"><li>● Support for Full Shader Model 5.0</li><li>● 400 Stream Processing Units</li><li>● Dynamic load balancing and resource allocation for vertex, geometry, and pixel shaders</li><li>● Common instruction set and texture unit access supported for all types of shaders</li><li>● Dedicated branch execution units and texture address processors</li><li>● Anti-aliases Shaders and Textures as well as Polygone Edges</li></ul>



### Technical Specifications - Graphics

Supported graphics APIs	DirectX 11, OpenGL 3.2, OpenCL 1.0 and full implementation of DirectCompute 11  (OpenCL™ compliant driver and SDK release scheduled in 2010)
Available graphics drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) WS4 <i>* WS4 not supported on Z200 &amp; Z200 SFF</i> Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>
Power Consumption	43 Watts

---

ATI FirePro V4800 1GB Graphics Card	Form Factor	4.37 in (H) x 6.61 in (L)
	Graphics Controller	ATI FirePro V4800 Graphics Card
	Bus Type	PCI Express x 16, Generation 2.0
	Memory	1GB GDDR5 SDRAM
	Connectors	2 DisplayPort, 1 dual link DVI Output One DP to DVI adapter included
	Maximum Resolution	Up to three digital displays at resolutions up to 2560 x 1600 @ 60Hz or up to three analog displays, one at resolutions up to 2048 x 1536 @ 85Hz, plus two resolutions up to 1920 x 1200 @ 60Hz (165 MHz dot clock)  <b>NOTE:</b> This card supports up to three displays with Windows 7, Vista or Linux, and up to two displays on XP
	RAMDAC	400 MHz DAC, 10-bit per channel
Image Quality Features	<ul style="list-style-type: none"><li>Up to 3 independent outputs with ATI Eyefinity technology support (More information at: <a href="http://www.amd.com/us/products/technologies/eyefinity/">www.amd.com/us/products/technologies/eyefinity/</a>)</li><li>Full 30-bit display pipeline for more accurate color reproduction superior image quality<sup>2</sup></li><li>Advanced video capabilities, including high fidelity gamma, color correction and scaling</li><li>Dedicated hardware (UVD2) for H.264, VC-1, and MPEG2 decode</li></ul> <b>NOTE:</b> The use of more than two displays on Linux requires support for xrandr 1.2 or greater in the X server	
Shading architecture	<ul style="list-style-type: none"><li>Support for Full Shader Model 5.0</li><li>Dynamic load balancing and resource allocation for vertex, geometry, and pixel shaders</li><li>Common instruction set and texture unit access supported for all types of shaders</li><li>Dedicated branch execution units and texture address processors</li><li>Anti-aliases Shaders and Textures as well as Polygone Edges</li></ul>	



### Technical Specifications - Graphics

<b>Supported graphics APIs</b>	DirectX 11, OpenGL 3.2, OpenCL 1.03 and full implementation of DirectCompute 11  (OpenCL™ compliant driver and SDK release scheduled in 2010)
<b>Available graphics drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) WS4 (64-bit and 32-bit) <i>* WS4 not supported on Z200 &amp; Z200 SFF</i> Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>
<b>Power Consumption</b>	69 Watts

---

#### NVIDIA Quadro 2000 1GB Graphics Card

<b>Form Factor</b>	4.376" H x 7" L Single Slot
<b>Graphics Controller</b>	NVIDIA Quadro 2000 Graphics Card
<b>Bus Type</b>	PCI Express 2.0 x16
<b>Memory</b>	1 GB GDDR5 128-bit
<b>Connectors</b>	1 DVI-I output, 2 DisplayPort outputs One DP to DVI adapter included with card  DVI to VGA, DisplayPort to VGA and DisplayPort to DVI adapters available as accessories
<b>Maximum Resolution</b>	Dual DisplayPort (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz) Dual-link DVI-I output (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)
<b>Image Quality Features</b>	<ul style="list-style-type: none"><li>● Up to 16K x16K texture and render processing</li><li>● Transparent multisampling and super sampling</li><li>● 16x angle independent anisotropic filtering</li><li>● 128-bit floating point performance</li><li>● 32-bit per-component floating point texture filtering and blending</li><li>● Support for any combination of two connected displays</li><li>● DisplayPort 1.1a, HDMI 1.3a, and HDCP support</li><li>● NVIDIA® 3D Vision™ technology, 3D DLP, Interleaved, and other 3D stereo format support</li><li>● Full OpenGL quad buffered stereo support</li><li>● Underscan/overscan compensation and hardware scaling</li><li>● NVIDIA® nView® multi-display technology</li></ul>
<b>Shading Architecture</b>	Shader Model 5.0



### Technical Specifications - Graphics

<b>Supported Graphics APIs</b>	OpenGL 4.0 DirectX 11 CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) WS4 (64-bit and 32-bit) <i>* WS4 not supported on Z200 and Z200 SFF</i> Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>  SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>
<b>Power Consumption</b>	62 Watts

---

<b>AMD FirePro V5900 2GB Graphics Card</b>	<b>Form Factor</b>	Full-height, full length, single slot
	<b>Graphics Controller</b>	AMD FirePro™ V5900 Professional Graphics
	<b>Bus Type</b>	PCI Express™ x16, Generation 2.1
	<b>Memory</b>	2GB GDDR5
	<b>Connectors</b>	2 x Display Port 1.2 1 x Dual-link DVI
	<b>Maximum Resolution</b>	2560 x 1600
	<b>Display Output</b>	DirectX 11 and OpenGL 4.1
	<b>Supported Graphics APIs</b>	DirectX 11 and OpenGL 4.1
	<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Linux® (32-bit or 64-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>
	<b>Power Consumption</b>	< 75W
	<b>Note</b>	Monitors should be same model when using DP-DVI connections to use the Eyefinity feature. There are no additional limitations when using DisplayPort cables.

---



### Technical Specifications - Graphics

AMD FirePro V7900 2GB Graphics Card	Form Factor	Full height, full length, single slot
	Graphics Controller	AMD FirePro™ V7900 Professional Graphics
	Bus Type	PCI Express™ x16, Generation 2.1
	Memory	2GB GDDR5
	Connectors	4 x DisplayPort 1.2
	Maximum Resolution	2560 x1600
	Supported Graphics APIs	DirectX 11 and OpenGL 4.1
	Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Linux® (32-bit or 64-bit)
	Power Consumption	HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>
	Note	< 150W Monitors should be same model when using DP-DVI connections to use the Eyefinity feature. There are no additional limitations when using DisplayPort cables.

---

NVIDIA Quadro 4000 2GB Graphics Card	Form Factor	4.376" H x 9.50" L Single Slot
	Graphics Controller	NVIDIA Quadro 4000 Graphics Card
	Bus Type	PCI Express 2.0 x16
	Memory	2 GB GDDR5 256-bit
	Connectors	1 DVI-I output, 2 DisplayPort outputs; One DP to DVI adapter included with card
	Maximum Resolution	DVI to VGA, DisplayPort to VGA and DisplayPort to DVI (single-link or dual-link) adapters available as accessories (Optional stereo bracket available from 3rd party) Dual DisplayPort (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz) Dual-link DVI-I output (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)
	RAMDAC	400 MHz integrated RAMDAC
	Image Quality Features	<ul style="list-style-type: none"><li>• Up to 16K x16K texture and render processing</li><li>• Transparent multisampling and super sampling</li><li>• 16x angle independent anisotropic filtering</li><li>• 128-bit floating point performance</li><li>• 32-bit per-component floating point texture filtering and blending</li><li>• Support for any combination of two connected displays</li><li>• DisplayPort 1.1a, HDMI 1.3a, and HDCP support</li><li>• NVIDIA 3D Vision™ technology, 3D DLP, Interleaved, and other 3D stereo format support</li><li>• Full OpenGL quad buffered stereo support</li><li>• Underscan/overscan compensation and hardware scaling</li></ul>



### Technical Specifications - Graphics

	<ul style="list-style-type: none"><li>● NVIDIA nView® multi-display technology</li></ul>
<b>Shading Architecture</b>	Shader Model 5.0
<b>Supported Graphics APIs</b>	OpenGL 4.0 DirectX 11 CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) WS4 (64-bit and 32-bit) <i>* WS4 not supported on Z200 and Z200 SFF</i> Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>  Novell SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>
<b>Power Consumption</b>	142 Watts

### NVIDIA Quadro 5000 2.5GB Graphics Card

<b>Form Factor</b>	4.376" H x 9.75" L Dual Slot
<b>Graphics Controller</b>	NVIDIA Quadro 5000 Graphics Card
<b>Bus Type</b>	PCI Express 2.0 x16
<b>Memory</b>	2.5 GB GDDR5 320-bit
<b>Connectors</b>	DVI-I (1), DP (2), Stereo (1) One DP to DVI adapter included with card  DVI to VGA, DisplayPort to VGA and DisplayPort to DVI adapters available as accessories
<b>Maximum Resolution</b>	Dual DisplayPort (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz) Dual-link DVI-I output (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)
<b>Image Quality Features</b>	<ul style="list-style-type: none"><li>● Up to 16K x16K texture and render processing</li><li>● Transparent multisampling and super sampling</li><li>● 16x angle independent anisotropic filtering</li><li>● 128-bit floating point performance</li><li>● 32-bit per-component floating point texture filtering and blending</li><li>● Support for any combination of two connected displays</li><li>● DisplayPort 1.1a, HDMI 1.3a, and HDCP support</li><li>● NVIDIA 3D Vision™ technology, 3D DLP, Interleaved, and other 3D stereo format support</li><li>● Full OpenGL quad buffered stereo support</li><li>● Underscan/overscan compensation and hardware scaling</li></ul>





## Technical Specifications - Graphics

	<ul style="list-style-type: none"><li>• NVIDIA nView® multi-display technology</li></ul>
<b>Shading Architecture</b>	Shader Model 5.0
<b>Supported Graphics APIs</b>	OpenGL 4.0 DirectX 11 CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
<b>Available Graphics Drivers</b>	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) WS4 (64-bit and 32-bit) <i>* WS4 not supported on Z200 and Z200 SFF</i> Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)  HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>  Novell SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>
<b>Power Consumption</b>	152 Watts



### Technical Specifications - High Performance GPU Computing

NVIDIA Tesla C2050 Compute Processor	Form Factor	4.376 inches by 9.75 inches Dual Slot
	System Interface	PCI Express Gen2 ×16
	Video Outputs	One Dual Link DVI-I  (Consumer graphics level of performance)
	Memory	3GB GDDR5
	Peak Memory Bandwidth	+170 GB/s
	Supported APIs	CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
	Supported Operating Systems	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)
		HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>
		Novell SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>
	Processor Cores	448 CUDA cores
Power Consumption	~225 Watts <b>NOTE 1:</b> An 1110W PSU is required for Tesla C2050 on the Z800 <b>NOTE 2:</b> A 600W PSU is required for Tesla C2050 on the Z400	

---

NVIDIA Tesla C2075 Compute Processor	Form Factor	4.376 inches by 9.75 inches Dual Slot
	System Interface	PCI Express Gen2 ×16
	Video Outputs	One Dual Link DVI-I  (Entry graphics level of performance)
	Memory	6GB GDDR5
	Peak Memory Bandwidth	+170 GB/s
	Supported APIs	CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
	Supported Operating Systems	Genuine Windows 7 Professional (64-bit) Genuine Windows Vista Business (64-bit) Microsoft Windows XP Professional (64-bit) Red Hat Enterprise Linux (RHEL) 5, 6 Desktop/Workstation (64-bit) SUSE Linux Enterprise Desktop 11 (64-bit)
		HP qualified drivers may be preloaded or available from the HP support Web site: <a href="http://welcome.hp.com/country/us/en/support.html">http://welcome.hp.com/country/us/en/support.html</a>



## Technical Specifications - High Performance GPU Computing

	Novell SUSE Linux Enterprise drivers may also be obtained from: <a href="ftp://download.nvidia.com/novell">ftp://download.nvidia.com/novell</a> or <a href="http://www.nvidia.com">http://www.nvidia.com</a>
Processor Cores	448 CUDA cores
Power Consumption	~215 Watts
	<b>NOTE 1:</b> An 1110W PSU is required for Tesla C2075 on the Z800
	<b>NOTE 2:</b> A 600W PSU is required for Tesla C2075 on the Z400



## Technical Specifications - Multimedia and Audio Devices

HP Thin USB Powered Speakers	Frequency Response (-3dB, 24-bit/96kHz input)	FO to 20kHz
	Dimensions	Speakers: 14.52 x 9.50 x 2.45 cm (5.72 x 3.74 x 0.96 in) per speaker

---

SoundBlaster (Creative Labs) X-Fi Titanium PCIe Audio Card	24-bit Analog-to-Digital conversion of analog inputs	96kHz sample rate
	24-bit Digital-to-Analog conversion of digital sources	96kHz to analog 7:1 speaker output
	24-bit Digital-to-Analog conversion of stereo digital sources	8, 11.025, 16, 22.05, 24, 32, 44.1, 48 and 96kHz
	16-bit to 24-bit recording sampling rates	16-bit/44.1kHz, 16-bit/48kHz, 24-bit/44.1kHz, 24-bit/48kHz and 24-bit/96kHz with direct monitoring
	Enhanced SoundFont support	Up to 24-bit resolution
	Signal-to-Noise Ratio (20kHz Low-pass filter, A-Weighted)	109dB
	Total Harmonic Distortion + Noise at 1kHz (20kHz Low-pass filter)	.004%
	Frequency Response (-3dB, 24-bit/96kHz input)	10Hz to 46kHz
	Frequency Response (-3dB, 24-bit/192kHz input)	10Hz to 46kHz
	Speaker and Headphone connections	Stereo to 7.1 (Line Out via three 3.5mm mini jacks)
	Flexijack	Line In/ Microphone In/Optical Out via shared 3.5mm mini jack
	Front Panel Header	Intel HD Audio Compatible (2x5 pin)
	Operating System	Windows 7 Professional 32-bit and 64-bit Microsoft Windows Vista Business 32-bit and 64-bit Microsoft® Windows® XP Professional SP2 Microsoft Windows XP Professional x64 Edition
Minimum System Requirements	System RAM	512MB
	Operating System	Windows Vista 32-bit and 64-bit version or Windows XP 32-bit or 64-bit version



### Technical Specifications - Optical and Removable Storage

**NOTE 1:** Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players.

<b>HP DVD-ROM Drive</b>	<b>Description</b>	5.25-inch, half-height, tray-load	
	<b>Mounting Orientation</b>	Either horizontal or vertical	
	<b>Interface Type</b>	SATA/ATAPI	
	<b>Dimensions (WxHxD)</b>	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)	
	<b>Disc Capacity</b>	<b>DVD-ROM</b> Single layer: Up to 4.7 GB Double layer: Up to 8.5 GB	
	<b>Access Times</b>	<b>DVD-ROM Single Layer</b>	< 140 ms (typical)
		<b>CD-ROM Mode 1</b>	< 125 ms (typical)
		<b>Full Stroke DVD</b>	< 250 ms (seek)
		<b>Full Stroke CD</b>	< 210 ms (seek)
	<b>Power</b>	<b>Source</b>	SATA DC power receptacle
		<b>DC Power Requirements</b>	5 VDC ± 5%-100 mV ripple p-p
			12 VDC ± 5%-200 mV ripple p-p
	<b>Operating Environmental</b> (all conditions non-condensing)	<b>DC Current</b>	5 VDC - < 1000 mA typical, < 1600 mA maximum
		<b>Temperature</b>	5° to 50° C (41° to 122° F)
<b>Relative Humidity</b>		10% to 90%	
<b>Maximum Wet Bulb Temperature</b>		30° C (86° F)	
<b>Operating Systems Supported</b>	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation, Removed reference to "Novell" because of acquisition and changed product reference to "SUSE Linux Enterprise Desktop 10 & 11", No driver is required for this device. Native support is provided by the operating system.		

\* Certain Windows Vista product features require advanced or additional hardware. See <http://www.microsoft.com/windowsvista/getready/hardwarereqs.mspx> and <http://www.microsoft.com/windowsvista/getready/capable.mspx> for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit:



### Technical Specifications - Optical and Removable Storage

<http://www.windowsvista.com/upgradeadvisor>.  
For Windows Vista system requirements, visit:  
<http://www.windowsvista.com/systemrequirements>.

\*\* RHEL WS4 not supported on Z200/Z200SFF

HP DVD+/-RW Drive	<b>Description</b>	5.25-inch, half-height, tray-load			
	<b>Mounting Orientation</b>	Either horizontal or vertical			
	<b>Interface Type</b>	SATA/ATAPI			
	<b>Dimensions (WxHxD)</b>	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)			
	<b>Disc Formats</b>	DVD-RAM			
		DVD+R			
		DVD+RW			
		DVD+R DL			
		DVD-R DL			
		DVD-R			
		DVD-RW			
		CD-R			
	CD-RW				
	<b>Disc Capacity</b>	<b>DVD-ROM</b>	8.5 GB DL or 4.7 GB standard		
		<b>Full Stroke DVD</b>	< 250 ms (seek)		
	<b>Maximum Data Transfer Rates</b>	<b>Full Stroke CD</b>	< 210 ms (seek)		
		<b>CD ROM Read</b>	CD-ROM, CD-R Up to 40X		
			CD-RW Up to 32X		
		<b>DVD ROM Read</b>	<b>DVD-RAM</b>	Up to 12X	
			<b>DVD+RW</b>	Up to 8X	
			<b>DVD-RW</b>	Up to 8X	
			<b>DVD+R DL</b>	Up to 8X	
<b>DVD-R DL</b>			Up to 8X		
<b>DVD-ROM</b>			Up to 16X		
<b>DVD-ROM DL</b>			Up to 8X		
<b>DVD+R</b>	Up to 16X				
<b>DVD-R</b>	Up to 16X				
<b>Power</b>	<b>Source</b>	SATA DC power receptacle			
	<b>DC Power Requirements</b>	5 VDC $\pm$ 5%-100 mV ripple p-p			
		12 VDC $\pm$ 5%-200 mV ripple p-p			
<b>DC Current</b>	5 VDC -1000 mA typical, 1600 mA maximum 12 VDC -600 mA typical, 1400 mA maximum				
<b>Operating Environmental</b> (all conditions non-condensing)	<b>Temperature</b>	5° to 50° C (41° to 122° F)			
	<b>Relative Humidity</b>	10% to 90%			
	<b>Maximum Wet Bulb Temperature</b>	30° C (86° F)			
	<b>Operating Systems Supported</b>	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*,			



Technical Specifications - Optical and Removable Storage

Windows 2000, Windows XP Professional or Windows XP Home 32\*.  
 Red Hat Enterprise Linux(RHEL) WS4\*\*, 5, 6 Desktop/Workstation  
 SUSE Linux Enterprise Desktop 10 & 11

No driver is required for this device. Native support is provided by the operating system.

\*Certain Windows Vista product features require advanced or additional hardware. See <http://microsoft.com/windowsvista/getready/hardwarereqs.mspx> and <http://www.microsoft.com/windowsvista/getready/capable.mspx> for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: <http://www.windowsvista.com/upgradeadvisor>. For Windows Vista system requirements, visit: <http://www.windowsvista.com/systemrequirements>

\*\* RHEL WS4 not supported on Z200/Z200SFF

**Kit Contents**

HP SATA SuperMulti DVD Writer Drive, Roxio Easy Media Creator software, Intervideo WinDVD Software, installation guide, and DVD+R media.

HP Blu-Ray Writer	<b>Description</b>	5.25-inch, half-height, tray-load		
	<b>Mounting Orientation</b>	Either horizontal or vertical		
	<b>Interface Type</b>	SATA		
	<b>Dimensions (WxHxD)</b>	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)		
	<b>Disc Formats</b>	BD-ROM BD-R BD-RE DVD-RAM DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R DVD-RW CD-R CD-RW		
	<b>Disc Capacity</b>	<b>DVD-ROM</b>	8.5 GB DL or 4.7 GB standard	
		<b>Blu-ray</b>	50 GB DL or 25 GB standard	
		<b>Full Stroke DVD</b>	< 250 ms (seek)	
		<b>Full Stroke CD</b>	< 210 ms (seek)	
		<b>Blu-ray</b>	Blu-ray	
		<b>Startup Time (Time to</b>	<b>BD-ROM (SL/DL)</b>	<b>25S / 28S</b>



### Technical Specifications - Optical and Removable Storage

	drive ready from tray loading)	BD-R (SL/DL)	25S / 28S
		BD-RE (SL/DL)	25S / 28S
		DVD-ROM (SL/DL)	18S / 18S
		DVD-R (SL/DL)	25S / 25S
		DVD-RW	25S
		DVD+R (SL/DL)	25S / 25S
		DVD+RW	25S
		DVD-RAM	45S
		CD-ROM	45S
<b>Maximum Data Transfer Rates</b>	<b>CD ROM Read</b>	CD-ROM	Up to 40X
		CD-R	Up to 40X
		CD-RW	Up to 40X
	<b>DVD ROM Read</b>	DVD-RAM	Up to 5X
		DVD+RW	Up to 10X
		DVD-RW	Up to 10X
		DVD+R DL	Up to 8X
		DVD-R DL	Up to 8X
		DVD-ROM	Up to 16X
		DVD-ROM DL	Up to 8X
		DVD+R	Up to 12X
		DVD-R	Up to 12X
		<b>Blu-Ray</b>	BD-ROM
	BD-ROM DL		Up to 4.8X
	BD-R		Up to 6X
BD-R DL	Up to 4.8X		
		BD-R	Up to 6X
		BD-RE SL/DL	Up to 4.8X
<b>Power</b>	<b>Source</b>	SATA DC power receptacle	
	<b>DC Power Requirements</b>	5 VDC $\pm$ 5%-100 mV ripple p-p 12 VDC $\pm$ 10%-100 mV ripple p-p	
	<b>DC Current</b>	5 VDC -900 mA typical, 1200 mA maximum 12 VDC -1000 mA typical, 1600 mA maximum	
<b>Operating Environmental</b> (all conditions non-condensing)	<b>Temperature</b>	5° to 50° C (41° to 122° F)	
	<b>Relative Humidity</b>	15% to 80%	
	<b>Maximum Wet Bulb Temperature</b>	30° C (86° F)	
	<b>Operating Systems Supported</b>	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation, SUSE Linux Enterprise Desktop 10 & 11	





### Technical Specifications - Optical and Removable Storage

\* No driver is required for this device. Native support is provided by the operating system.

\*\* RHEL WS4 not supported on Z200/Z200SFF

#### Kit Contents

HP Blue Laser RW Drive, Roxio Easy Media Creator software, Intervideo WinDVD Software, installation guide.

#### Disclaimer

As Blu-Ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-Ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.

#### HP 22-in-1 Media Card Reader

##### Description

The Media Card Reader device uses the same physical form factor and mounting as a Floppy Disk Drive. The device connects to a 2x5 two-channel USB header on the motherboard of the system. There is no USB controller card provided. Please see the Disc Formats section below for a list of flash memory card formats that are supported.

##### Mounting Orientation

The Media Card Reader can be mounted in a dedicated Floppy Drive bay (if the chassis provides one) or in an appropriate Optical Bay adapter. It will operate in any orientation.

##### Interface Type

USB 2.0 (one channel dedicated to the separate USB port; one channel dedicated to the flash memory card slots)

##### Dimensions (WxHxD)

124.5 x 101.6 x 25.4 mm (4.9 x 4.0 x 1.0 in)

##### Disc Formats

xD-Picture  
Micro SD  
Micro SDHC  
SD  
SDHC  
SDXC  
Mini SD  
Mini SDHC  
MultiMediaCard (MMC)  
Reduced Size MultiMediaCard (RS MMC)  
MultiMedia Card 4.2 (MMC Plus, including MMC Plus HC)  
Reduced Size MultiMedia Card 4.2 (MMC Mobile, including MMC Mobile HC)  
CompactFlash Card Type I  
CompactFlash Card Type II  
MicroDrive  
Memory Stick (MS)  
MagicGate Memory Stick (MG)  
MagicGate Memory Stick Duo  
Memory Stick Select  
Memory Stick Duo (MS Duo)  
Memory Stick PRO (MS PRO)  
Memory Stick PRO Duo (MS PRO Duo)



## *Technical Specifications - Optical and Removable Storage*

Memory Stick PRO-HG Duo

Two additional formats are usable with adapters (not supplied):

MMC Micro

Memory Stick Micro (M2)



### Technical Specifications - Controller Cards

HP FireWire/IEEE 1394a PCI Card	<b>Data Transfer Rate</b>	Burst Data Rate up to 400 Mbps
	<b>Device Interface Protocol</b>	IEEE-1394a
	<b>Devices Supported</b>	IEEE-1394 compliant devices
	<b>Bus Type</b>	PCI card with brackets for low profile and full height PCI slots.
	<b>Certification Level</b>	FCC Part 15B, cULus 60950, CE Mark EN55022B(1995)/EN55024-1998 STD, Taiwan BSMI CNS13438, Korea MIC
	<b>Ports</b>	Two IEEE 1394 6-Pin Connector (Rear)
	<b>Internal Connectors</b>	One 10-Pin (9 Contacts) Custom Connector
	<b>System Requirements</b>	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. No driver is required for this device. Native support is provided by the operating system. * Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: <a href="http://www.windowsvista.com/upgradeadvisor">http://www.windowsvista.com/upgradeadvisor</a> . For Windows Vista system requirements, visit: <a href="http://www.windowsvista.com/systemrequirements">http://www.windowsvista.com/systemrequirements</a> .
		Pentium II 266 or above 128-MB RAM 1-GB Hard Drive CD-ROM drive Built-in sound system Available PCI slot
	<b>Temperature - Operating</b>	50° to 131° F (10° to 55° C)
<b>Temperature - Storage</b>	-22° to 140° F (-30° to 60° C)	
<b>Relative Humidity - Operating</b>	20% to 80%	
<b>Operating Systems Supported</b>	Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*  * Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: <a href="http://www.windowsvista.com/upgradeadvisor">http://www.windowsvista.com/upgradeadvisor</a> . For Windows Vista system requirements, visit: <a href="http://www.windowsvista.com/systemrequirements">http://www.windowsvista.com/systemrequirements</a> .	



## Technical Specifications - Controller Cards

HP IEEE 1394b FireWire PCIe Card	<b>Data Transfer Rate</b>	Supports up to 800 Mbps
	<b>Devices Supported</b>	IEEE-1394 compliant devices
	<b>Bus Type</b>	PCIe card full height PCIe slots
	<b>Ports</b>	Two IEEE-1394b bilingual 9-Pin Connector (Rear)
	<b>Internal Connectors</b>	One 10-Pin header Custom Connector
	<b>System Requirements</b>	Windows 7 Professional 32-bit and 64-bit, Microsoft® Windows® XP Professional, Windows XP Home, Windows Vista. Not supported on Linux. Pentium® III or higher processor 128-MB RAM 1-GB Hard Drive CD-ROM drive Built in sound system Available PCI slot
	<b>Temperature – Operating</b>	50° to 131° F (10° to 55° C)
	<b>Temperature – Storage</b>	-22° to 140° F (-30° to 60° C)
	<b>Relative Humidity – Operating</b>	20% to 80%
	<b>Compliances</b>	FCC Part 15B, cULus 60950, CE Mark EN55022B(1995)/EN55024-1998 STD, Taiwan BSMI CNS13438, Korea MIC
	<b>Operating Systems Supported</b>	Windows 7 Professional 32-bit and 64-bit, Windows Vista® Business 32-bit and 64-bit, Windows® XP Professional, XP Professional 64-bit. Not supported on Linux.

HP USB 3.0 2x2 Port SuperSpeed PCIe x1 Card	<b>Dimensions (HxD)</b>	TBD
	<b>Ports</b>	2 External, 2 internal
	<b>Operating Systems Supported</b>	Microsoft Windows 7, Windows Vista*, Windows XP Professional (32-bit and 64-bit); Red Hat Enterprise Linux 6.0, SuSE Linux Enterprise Desktop 11 Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: <a href="http://www.windowsvista.com/upgradeadvisor">http://www.windowsvista.com/upgradeadvisor</a> . For Windows Vista system requirements, visit: <a href="http://www.windowsvista.com/systemrequirements">http://www.windowsvista.com/systemrequirements</a> .
	<b>Kit Contents</b>	I/O and Security Software and Documentation CD with software drivers and documentation, HP SuperSpeed USB 3.0 PCIe x1 card (with full-height expansion bracket attached), SATA to SATA split power extension cable, Low profile expansion bracket to replace the full-height expansion bracket required on some computer models and HP SuperSpeed USB 3.0 PCIe x1 Card Quick Setup.
	<b>Regulatory Approvals and registrations</b>	FCC 15B, CE EN55022+ EN55024, VCCI, CISPR 22 AS/NZS CISPR 22, LCIE CB service(ITE/AV) IEC 60950-1, Korea EMC, UL USB-IF
	<b>Weight</b>	0.21 lb (95.0 g)
	<b>Warranty</b>	The HP USB 3.0 2x2 Port Super Speed PCIe x1 Card has either a one-year limited warranty or the remainder of the warranty of the HP product in which it is installed. Technical support is available seven days a week, 24 hours a day, by phone, as well as online support forums. Certain restrictions and exclusions apply.



### Technical Specifications - Controller Cards

HP SuperSpeed USB 3.0 PCIe x1 Card	<b>Dimensions (HxD)</b>	Full-height: 4.13 x 2.32 in; Low profile: 2.68 x 2.32 in (Full-height: 104.89 x 59.04 mm; Low profile: 68.09 x 59.04 mm)
	<b>Ports</b>	2 External
	<b>Operating Systems Supported</b>	Microsoft Windows 7, Windows Vista*, Windows XP Professional (32-bit and 64-bit); Red Hat Enterprise Linux 6.0, SuSE Linux Enterprise Desktop 11
		* Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: <a href="http://www.windowsvista.com/upgradeadvisor">http://www.windowsvista.com/upgradeadvisor</a> . For Windows Vista system requirements, visit: <a href="http://www.windowsvista.com/systemrequirements">http://www.windowsvista.com/systemrequirements</a> .
	<b>Kit Contents</b>	I/O and Security Software and Documentation CD with software drivers and documentation, HP SuperSpeed USB 3.0 PCIe x1 card (with full-height expansion bracket attached), SATA to SATA split power extension cable, Low profile expansion bracket to replace the full-height expansion bracket required on some computer models and HP SuperSpeed USB 3.0 PCIe x1 Card Quick Setup.
	<b>Regulatory Approvals and registrations</b>	FCC 15B, CE EN55022+ EN55024, VCCI, CISPR 22 AS/NZS CISPR 22, LCIE CB service (ITE/AV) IEC 60950-1, Korea EMC, UL USB-IF
	<b>Weight</b>	0.21 lb (95.0 g)
	<b>Warranty</b>	The HP Super Speed USB 3.0 PCIe x1 Card has either a one-year limited warranty or the remainder of the warranty of the HP product in which it is installed. Technical support is available seven days a week, 24 hours a day, by phone, as well as online support forums. Certain restrictions and exclusions apply.



## Technical Specifications - Networking and Communications

**NOTE 1:** "Gigabit" Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/sec. For high speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

<b>Integrated Broadcom 5764 PCIe LOM Controller</b>	<b>Connector</b>	RJ45
	<b>Data Rates Supported</b>	10/100/1000BT
	<b>Bus Architecture</b>	PCIe X1
	<b>Alerting</b>	ASF 2.0

<b>Broadcom (5761) NetXtreme Gigabit Ethernet Plus NIC</b>	<b>Connector</b>	RJ-45
	<b>Controller</b>	Broadcom 5761 PCI-Express LAN Controller
	<b>Memory</b>	8 MB NVRAM serial Flash
	<b>Data Rates Supported</b>	10/100/1000 Mbps
	<b>Compliance</b>	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB, 802.3u, and 802.3x
	<b>Bus Architecture</b>	PCI-Express
	<b>Data Path Width</b>	Single Channel PCI-Express
	<b>Data Transfer Mode</b>	Bus Master DMA
	<b>Hardware Certifications</b>	FCC class B, Canada and US NRTL Mark, C-Tick for Australia, BSMI for Taiwan, VCCI for Japan, MIC for Korea, GOST for Russia, UL listed (E212044), European Union Notice (CE 0682)
	<b>Power Requirement</b>	1.8W @ 3.3V
	<b>Boot ROM Support</b>	Yes
	<b>Network Transfer Mode</b>	Full-duplex Half-duplex (not available for the 1000BASE-T transceiver)
	<b>Network Transfer Rate</b>	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
	<b>Operating Temperature</b>	32° to 131°F (0° to 55° C)
	<b>Operating Humidity</b>	131° F (55° C) with 5% to 95% non-condensing humidity
	<b>Dimensions</b>	7 cm x 10.5 cm (2.75 in x 4.13 in), low profile compatible
	<b>Operating System Driver Support</b>	Windows 7 Professional 32-bit and 64-bit, Windows Vista 32-bit SP1, Windows Vista x64 SP1, Windows XP 32 bit professional, Windows XP x64 Red Hat Enterprise Linux(RHEL) WS4*, 5, 6 Desktop/Workstation Novell SLED 10 & 11
		<i>*RHEL WS4 not supported on Z200/Z200SFF</i>
	<b>Management Capabilities</b>	ACPI, WOL and DMI 2.0, PXE 2.0, WfM 2.0, Broadcom mgmt utility, ASF2.0, DASH 1.0 and DASH 1.1 profiles
	<b>Kit Contents</b>	Broadcom NetXtreme Gigabit Ethernet Plus NIC, Broadcom NetXtreme Gigabit Ethernet Plus NIC USB Cable Assembly, CD, drivers, quick install guide, product warranty statement



### Technical Specifications - Networking and Communications

Intel Gigabit CT Desktop NIC	Connector	RJ-45
	Controller	Intel WG82574L Gigabit Ethernet Controller
	Memory	Integrated Dual 48K configurable transmit receive FIFO Buffers
	Data Rates Supported	10/100/1000 Mbps
	Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
	Bus Architecture	PCI-E 1.0a
	Data Path Width	X1, 250 MB/s, Bi-directional interface
	Data Transfer Mode	Bus-master DMA
	Hardware Certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power Requirement	Aux 3.3V, 3.0 Watts in 1000base-T and 2.0 Watts in 100Base-T
	Boot ROM Support	Yes
	Network Transfer Rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
	Operating Temperature	32° to 131°F (0° to 55° C)
	Operating Humidity	85% at 131° F (55° C)
	Dimensions	12.1 x 5.7 x 2.0 cm (4.75 x 2.25 x 0.8 in)
	Operating System Driver Support	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64, Windows Vista Business 32, Windows XP Professional, Windows XP x64. Red Hat Enterprise Linux 4 (RHEL4.8 or newer)*, Red Hat Enterprise Linux 5 (RHEL5.3 or newer), Red Hat Enterprise Linux 6 <a href="#">* RHEL WS4 not supported on Z200/Z200SFF</a>
	Management Capabilities	WOL , PXE, DMI, WFM 2.0
	Kit Contents	Intel Gigabit CT Desktop NIC, low profile bracket, CD containing Intel PROset II NIC drivers, quick install guide, product warranty statement

© Copyright 2011 Hewlett-Packard Development Company, L.P.  
The information contained herein is subject to change without notice.

All rights reserved. Microsoft, Windows, Windows Vista, and Windows XP are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Intel, the Intel logo, Pentium, and Pentium Inside are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Linux is a registered trademark of Linus Torvalds in the United States and other countries.

Warranty - year(s) Protected by HP Services, including a 3 years parts, 3 years labor, and 3 years onsite service (3/3/3) standard warranty. Terms and conditions vary by country. Certain restrictions and exclusions apply.

