

PHILIPS

LED lamps



Turn off or **show off?**

Professional **LED lamps** catalogue
Quarter 4 / 2019

philips.com/ledlamps

**REAL
PROs**
**REAL
QUALITY**

What are the benefits of EyeComfort?

There are many LED lights on the market today, but they are not all created equal. This is why we developed our Philips EyeComfort range. Our LEDs all conform to our EyeComfort standard, which measures our products against a set of key comfort criteria: flicker, glare, stroboscopic effect, photobiological safety, dimmable, tuning and color rendering – factors that can



Look for the EyeComfort logo on our packaging



Photobiological safety



Reduced stroboscopic effect



Improved colour rendering



Dimmable



Tunability



Reduced flicker



No audible harm



Reduced glare



Download Digital Brochure
Find helpful tools.

www.philips.com/ledlamps



Contents



4

Our story

6

NEW product introductions



8

LED tube

10

LED spot



17

LED capsules

19

LED bulb



31

LED candles & lusters

34

LED HID Replacement



Lighting New Zealand for **over 75 years**

The Philips brand stands for quality and energy-efficiency in light. For over 127 years, Philips products have been at the forefront of innovation. As the world's leader in lighting, Philips is driving the switch to energy-efficient and connected lighting solutions.


That same principle has been at work here in **New Zealand for over 75 years**, with thousands of lighting solutions across every sector.

Today, **Philips Lighting** is an integral part of the Kiwi landscape. And just as that landscape is forever changing, so we'll continue to provide the cutting-edge solutions that will take New Zealand industry into the future.

Sports
Eden Park



Façade
Viaduct Basin



Street Lighting
Hamilton





A heritage of taking light beyond illumination



1891-2014
Conventional



2012
Connected lighting



2018
Lighting as a language
(Analytics, LiFi)

2008
Introduction of LED



2016
IoT (systems)




Innovation continues



Office
Watercare



Industry
WineWorks



New Products

Battery Lamp



7W E27 3000K
7W E27 6500K

Design highlights

- An innovative design with battery power back up
- Long Life Battery (500 Recharge Cycles)
- Back up light for more than 3 hours

Application areas

- Bed room/Living Room/Staircase/Bathroom/Foyer
- Hotel guest room/Lobby/Corridors/Lifts
- Retail check out area/common area

Sensor Lamp



8W E27 2700K
8W E27 6500K

Design highlights

- Form factor is designed as a direct retrofit of A60 shape
- Designed for a wide range of applications including damp areas
- Lit up under 110V line voltage and best performance is delivered under 220V-240V

Application area

- Ideal for a hallway, pantry, deck and main entrance

UFO



24W E27 3000K
24W E27 6500K

24W B22 3000K
24W B22 6500K

Design highlights

- Easy for installation
- Wider surface
- 50% less glare
- Last up to 15 years

Application areas

- The eye comfort light for general lighting application at home
- Corridors / Stairways / Washroom

TrueForce



E27 lamp

ND 28-30W E27 840
ND 28-30W E27 865
ND 26-30W E27 830
ND 40-40W E27 865
ND 37-40W E27 830
ND 40-40W E27 840
ND 50-50W E27 840
ND 50-50W E27 865

B22 lamp

ND 28-30W B22 865
ND 40-40W B22 865
ND 50-50W B22 865

E40 lamp

ND 54-60W E40 840
ND 54-60W E40 865

Benefits

- Short Payback LED solution to replace High Intensity Discharge (HID) Lamps
- Light on the wider working space
- Low initial investment
- Enhance lighting quality with easy adoption

Features

- High energy efficiency
- Lifetime 20,000hrs
- Wide beam angle, 240°
- Bypass ballast and save additional energy
- Pleasant white light with CRI 80

Application

- Industrial/retail - warehouses, factories, shops, transport hubs



LED tube

CorePro LED tubes offer even better value. Thanks to the new glass housing they offer a large 240D beam angle to fit more applications. Plus we've improved the energy consumption from 80 to 90 lm/W to make them even more efficient. A simple retrofit replacement, the 600mm, 1200mm and 1500mm CorePro LED tubes offer low energy consumption with instant savings. Perfect for standard applications that demand an affordable solution.



G13

CorePro LED tube T8



| Product type | LED | Lumen output | Operation | Dimmable | Beam angle | CRI | Colour temp. | Lifetime | Dimensions | Ordering Code |
|------------------------------------|-----|--------------|------------|----------|------------|-----|--------------|----------|------------|---------------|
| | W | lm | | | ° | | K | Hrs. | MM | |
| CorePro LED tube (EM/Mains) | | | | | | | | | | |
| CorePro LEDtube 600mm 8.8W 840 AU | 8.8 | 800 | EM & Mains | No | 240 | 80 | 4000 | 30,000 | 28 x 600 | 929001338619 |
| CorePro LEDtube 600mm 8.8W 865 AU | 8.8 | 800 | EM & Mains | No | 240 | 80 | 6500 | 30,000 | 28 x 600 | 929001338719 |
| CorePro LEDtube 1200mm 16W 840 AU | 16 | 1600 | EM & Mains | No | 240 | 80 | 4000 | 30,000 | 28 x 1200 | 929001338819 |
| CorePro LEDtube 1200mm 16W 865 AU | 16 | 1600 | EM & Mains | No | 240 | 80 | 6500 | 30,000 | 28 x 1200 | 929001338919 |
| CorePro LEDtube 1500mm 22W 840 AU | 22 | 2200 | EM & Mains | No | 240 | 80 | 4000 | 30,000 | 28 x 1500 | 929001337919 |
| CorePro LEDtube 1500mm 22W 865 AU | 22 | 2200 | EM & Mains | No | 240 | 80 | 6500 | 30,000 | 28 x 1500 | 929001338019 |

CorePro LED PL Lamps

General area lighting could be costly for many building owners. CorePro LED PLC is a retrofit LED PLC lamp that delivers incredible energy savings over a 30,000 hours lifetime and requires less maintenance and servicing, so you can reduce your costs.

- Up to 60% more efficient compared to fluorescent PLC lamps, saving on energy costs.
- Lifetime up to 30,000 hours, reducing maintenance costs.
- Made of shatter-proof plastic instead of glass.
- Easy upgrade from current conventional downlight fixture.
- Re-using the existing fixture without major modifications, using a similar PLC form-factor.
- Instant 100% light.
- Reduced flicker/stroboscopic effect.



CorePro LED PLC



| Product type | LED | Lumen output | Operation | Dimmable | Rotatable end cap | Beam angle | CRI | Colour temp. | Pack | Lifetime | Ordering Code |
|------------------------------------|-----|--------------|-----------|----------|-------------------|------------|-----|--------------|------|----------|---------------|
| | W | lm | | | | ° | | K | | Hrs. | |
| 2 Pin | | | | | | | | | | | |
| LED PLC 4.5W 830 2P G24d-1 | 4,5 | 475 | EM | No | Yes | 120 | 80 | 3000 | 10 | 30,000 | 929001350708 |
| LED PLC 4.5W 840 2P G24d-1 | 4,5 | 500 | EM | No | Yes | 120 | 80 | 4000 | 10 | 30,000 | 929001350808 |
| LED PLC 4.5W 865 2P G24d-1 | 4,5 | 650 | EM | No | Yes | 120 | 80 | 6500 | 10 | 30,000 | 929001350908 |
| LED PLC 6.5W 830 2P G24d-2 | 6,5 | 700 | EM | No | Yes | 120 | 80 | 3000 | 10 | 30,000 | 929001201408 |
| LED PLC 6.5W 840 2P G24d-2 | 6,5 | 950 | EM | No | Yes | 120 | 80 | 4000 | 10 | 30,000 | 929001201508 |
| LED PLC 6.5W 865 2P G24d-2 | 6,5 | 1000 | EM | No | Yes | 120 | 80 | 6500 | 10 | 30,000 | 929001280208 |
| 4 Pin | | | | | | | | | | | |
| CorePro LED PLC 6.5W 830 4P G24q-2 | 6,5 | 650 | HF | No | Yes | 120 | 80 | 3000 | 10 | 30,000 | 929001201002 |
| CorePro LED PLC 6.5W 840 4P G24q-2 | 6,5 | 700 | HF | No | Yes | 120 | 80 | 4000 | 10 | 30,000 | 929001201102 |
| CorePro LED PLC 9W 830 4P G24q-3 | 9 | 950 | HF | No | Yes | 120 | 80 | 3000 | 10 | 30,000 | 929001200802 |
| CorePro LED PLC 9W 840 4P G24q-3 | 9 | 1000 | HF | No | Yes | 120 | 80 | 4000 | 10 | 30,000 | 929001200902 |



LED spot

MASTER ExpertColour MV & LV

Create beautiful experiences with light

Now you can match the true Colour spectrum of halogens to make spaces bright, vivid and refreshing. Perfect Colour saturation (CRI97) and an enhanced red spectrum make for a warmer, richer light and vivid reds, creating a truly comfortable ambience.

Dim to the exact light level

You get deep dimming (to below 5%) for the exact light level you need and improved dimmer compatibility. There's no visible flicker giving your customers smooth and constant light for exceptionally comfortable viewing.



MASTER Expert Colour MV & LV



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Beam angle | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|---|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | ° | | K | pcs | Hrs. | MM | |
| MASTER LEDspot ExpertColour MV | | | | | | | | | | | | |
| MAS LED ExpertColour 5.5-50W GU10 927 24D | 5.5 | 50 | 355 | 70 | Yes | 24 | 97 | 2700 | 10 | 40,000 | 54 x 50 | 929001347008 |
| MAS LED ExpertColour 5.5-50W GU10 927 36D | 5.5 | 50 | 355 | 70 | Yes | 36 | 97 | 2700 | 10 | 40,000 | 54 x 50 | 929001347308 |
| MAS LED ExpertColour 5.5-50W GU10 930 24D | 5.5 | 50 | 405 | 74 | Yes | 24 | 97 | 3000 | 10 | 40,000 | 54 x 50 | 929001347108 |
| MAS LED ExpertColour 5.5-50W GU10 930 36D | 5.5 | 50 | 405 | 74 | Yes | 36 | 97 | 3000 | 10 | 40,000 | 54 x 50 | 929001347408 |
| MASTER LEDspot ExpertColour LW | | | | | | | | | | | | |
| MAS LED MR16 ExpertColour 7.2-50W 927 10D | 7.2 | 50 | 450 | 63 | Yes | 10 | 97 | 2700 | 10 | 40,000 | 46 x 50.5 | 929001241908 |
| MAS LED MR16 ExpertColour 7.2-50W 927 24D | 7.2 | 50 | 450 | 63 | Yes | 24 | 97 | 2700 | 10 | 40,000 | 46 x 50.5 | 929001242208 |
| MAS LED MR16 ExpertColour 7.2-50W 927 36D | 7.2 | 50 | 450 | 63 | Yes | 36 | 97 | 2700 | 10 | 40,000 | 46 x 50.5 | 929001242508 |
| MAS LED MR16 ExpertColour 7.2-50W 927 60D | 7.2 | 50 | 450 | 63 | Yes | 60 | 97 | 2700 | 10 | 40,000 | 46 x 50.5 | 929001341408 |
| MAS LED MR16 ExpertColour 7.2-50W 930 10D | 7.2 | 50 | 480 | 67 | Yes | 10 | 97 | 3000 | 10 | 40,000 | 46 x 50.5 | 929001242008 |
| MAS LED MR16 ExpertColour 7.2-50W 930 24D | 7.2 | 50 | 480 | 67 | Yes | 24 | 97 | 3000 | 10 | 40,000 | 46 x 50.5 | 929001242308 |
| MAS LED MR16 ExpertColour 7.2-50W 930 36D | 7.2 | 50 | 480 | 67 | Yes | 36 | 97 | 3000 | 10 | 40,000 | 46 x 50.5 | 929001242608 |
| MAS LED MR16 ExpertColour 7.2-50W 930 60D | 7.2 | 50 | 480 | 67 | Yes | 60 | 97 | 3000 | 10 | 40,000 | 46 x 50.5 | 929001341508 |
| MAS LED MR16 ExpertColour 7.2-50W 940 10D | 7.2 | 50 | 510 | 71 | Yes | 10 | 97 | 4000 | 10 | 40,000 | 46 x 50.5 | 929001242108 |
| MAS LED MR16 ExpertColour 7.2-50W 940 24D | 7.2 | 50 | 510 | 71 | Yes | 24 | 97 | 4000 | 10 | 40,000 | 46 x 50.5 | 929001242408 |
| MAS LED MR16 ExpertColour 7.2-50W 940 36D | 7.2 | 50 | 510 | 71 | Yes | 36 | 97 | 4000 | 10 | 40,000 | 46 x 50.5 | 929001242708 |
| MAS LED MR16 ExpertColour 7.2-50W 940 60D | 7.2 | 50 | 510 | 71 | Yes | 60 | 97 | 4000 | 10 | 40,000 | 46 x 50.5 | 929001341608 |

MASTER LEDspot MV & LV

Everything you value in LED

Delivering intense accent beam, MASTER LEDspot MV & LV is an ideal retrofit solution for spot lighting. MASTER LEDspot MV & LV is designed to replace halogen or incandescent spots. It realizes natural colour, enables cozy and comfortable ambience for residential, hospitality and emphasizes the beauty of merchandise in retail. New smaller housing provides perfect fitting with majority of luminaires in a market with GU10 and MR16 lamp holders. It not only employs Philips' patented solution to guarantee the broadest possible compatibility with standard 12V halogen electronic

transformers, it also delivers high beam intensity which is equivalent to halogen GU10 & MR16 spots. The dimming function enables to create the desired atmosphere and it works with broad selection of dimmers. Its high SDCM ensure stricter Colour consistency, that is maintained over product life. MASTER LEDspot MV & LV delivers huge energy savings and minimizes maintenance cost without any compromise on light quality and lifetime, enabling residential and business owners to achieve a return on their investment within short period of time.



GU10



MASTER LEDspot MV



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Beam angle | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|-----------------------------------|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|-------------|---------------|
| | W | W | lm | lm/W | | ° | | K | pcs | Hrs. | MM | |
| MASTER GU10 Dimmable | | | | | | | | | | | | |
| Master LED 5-50W GU10 927 36D Dim | 5 | 50W | 395 | 72 | Yes | 36 | 90 | 2700 | 10 | 25,000 | 46.5 x 50.5 | 929001348808 |
| Master LED 5-50W GU10 930 36D Dim | 5 | 50W | 405 | 74 | Yes | 36 | 90 | 3000 | 10 | 25,000 | 46.5 x 50.5 | 929001348908 |
| Master LED 5-50W GU10 940 36D Dim | 5 | 50W | 420 | 76 | Yes | 36 | 90 | 4000 | 10 | 25,000 | 46.5 x 50.5 | 929001349008 |



MASTER LEDspot LV



MR16



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Beam angle | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|-----------------------------------|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|-------------|---------------|
| | W | W | lm | lm/W | | ° | | K | pcs | Hrs. | MM | |
| MASTER MR16 Dimmable | | | | | | | | | | | | |
| MASTER LED 7-50W 927 MR16 10D Dim | 7 | 50 | 440 | 63 | Yes | 10 | 90 | 2700 | 10 | 40,000 | 46.5 x 50.5 | 929001879508 |
| MASTER LED 7-50W 927 MR16 15D Dim | 7 | 50 | 440 | 63 | Yes | 15 | 90 | 2700 | 10 | 40,000 | 46.5 x 50.5 | 929001152538 |
| MASTER LED 7-50W 927 MR16 24D Dim | 7 | 50 | 440 | 63 | Yes | 24 | 90 | 2700 | 10 | 40,000 | 46.5 x 50.5 | 929001879808 |
| MASTER LED 7-50W 927 MR16 36D Dim | 7 | 50 | 440 | 63 | Yes | 36 | 90 | 2700 | 10 | 40,000 | 46.5 x 50.5 | 929001880108 |
| MASTER LED 7-50W 927 MR16 60D Dim | 7 | 50 | 440 | 63 | Yes | 60 | 90 | 2700 | 10 | 40,000 | 46.5 x 50.5 | 929001880408 |
| MASTER LED 7-50W 930 MR16 10D Dim | 7 | 50 | 440 | 63 | Yes | 10 | 90 | 3000 | 10 | 40,000 | 46.5 x 50.5 | 929001879608 |
| MASTER LED 7-50W 930 MR16 15D Dim | 7 | 50 | 440 | 63 | Yes | 15 | 90 | 3000 | 10 | 40,000 | 46.5 x 50.5 | 929001152638 |
| MASTER LED 7-50W 930 MR16 24D Dim | 7 | 50 | 440 | 63 | Yes | 24 | 90 | 3000 | 10 | 40,000 | 46.5 x 50.5 | 929001879908 |
| MASTER LED 7-50W 930 MR16 36D Dim | 7 | 50 | 440 | 63 | Yes | 36 | 90 | 3000 | 10 | 40,000 | 46.5 x 50.5 | 929001880208 |
| MASTER LED 7-50W 930 MR16 60D Dim | 7 | 50 | 440 | 63 | Yes | 60 | 90 | 3000 | 10 | 40,000 | 46.5 x 50.5 | 929001880508 |
| MASTER LED 7-50W 940 MR16 10D Dim | 7 | 50 | 440 | 63 | Yes | 10 | 90 | 4000 | 10 | 40,000 | 46.5 x 50.5 | 929001879708 |
| MASTER LED 7-50W 940 MR16 15D Dim | 7 | 50 | 440 | 63 | Yes | 15 | 90 | 4000 | 10 | 40,000 | 46.5 x 50.5 | 929001152738 |
| MASTER LED 7-50W 940 MR16 24D Dim | 7 | 50 | 440 | 63 | Yes | 24 | 90 | 4000 | 10 | 40,000 | 46.5 x 50.5 | 929001880008 |
| MASTER LED 7-50W 940 MR16 36D Dim | 7 | 50 | 440 | 63 | Yes | 36 | 90 | 4000 | 10 | 40,000 | 46.5 x 50.5 | 929001880308 |
| MASTER LED 7-50W 940 MR16 60D Dim | 7 | 50 | 440 | 63 | Yes | 60 | 90 | 4000 | 10 | 40,000 | 46.5 x 50.5 | 929001880608 |
| MASTER MR16 Non-Dimmable | | | | | | | | | | | | |
| MASTER LED 4-35W 2700K MR16 24D | 4 | 35 | 240 | 60 | No | 24 | 80 | 2700 | 10 | 25,000 | 49 x 50 | 929001147408 |
| MASTER LED 4-35W 3000K MR16 24D | 4 | 35 | 240 | 60 | No | 24 | 80 | 3000 | 10 | 25,000 | 49 x 50 | 929001147708 |
| MASTER LED 4-35W 2700K MR16 36D | 4 | 35 | 240 | 60 | No | 36 | 80 | 2700 | 10 | 25,000 | 49 x 50 | 929001147508 |
| MASTER LED 4-35W 3000K MR16 36D | 4 | 35 | 240 | 60 | No | 36 | 80 | 3000 | 10 | 25,000 | 49 x 50 | 929001147608 |
| MASTER LED 5.5-50W 2700K MR16 24D | 5.5 | 50 | 415 | 75 | No | 24 | 80 | 2700 | 10 | 25,000 | 49 x 50.2 | 929001145908 |
| MASTER LED 5.5-50W 2700K MR16 36D | 5.5 | 50 | 415 | 75 | No | 36 | 80 | 2700 | 10 | 25,000 | 49 x 50.2 | 929001146108 |
| MASTER LED 5.5-50W 3000K MR16 24D | 5.5 | 50 | 415 | 75 | No | 24 | 80 | 3000 | 10 | 25,000 | 49 x 50.2 | 929001146708 |
| MASTER LED 5.5-50W 3000K MR16 36D | 5.5 | 50 | 415 | 75 | No | 36 | 80 | 3000 | 10 | 25,000 | 49 x 50.2 | 929001146608 |
| MASTER LED 5.5-50W 4000K MR16 24D | 5.5 | 50 | 415 | 75 | No | 24 | 80 | 4000 | 10 | 25,000 | 49 x 50.2 | 929001146808 |
| MASTER LED 5.5-50W 4000K MR16 36D | 5.5 | 50 | 415 | 75 | No | 36 | 80 | 4000 | 10 | 25,000 | 49 x 50.2 | 929001146908 |

CLASSIC LEDspot MV & LV

LEDspot MV & LV Classic offers an archetypal halogen-like design while delivering the benefits of LED technology, saving around 85% on energy consumption, minimising maintenance cost.

It is compatible with most existing fixtures with a MR16 and GU10 lamp holders and is designed as a retrofit replacement for halogen or incandescent spots.



CLASSIC LEDspot MV & LV



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Beam angle | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering code |
|--|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|-------------|---------------|
| | W | W | lm | lm/W | | ° | | K | pcs | Hrs. | MM. | |
| Classic Non Dim GU10 | | | | | | | | | | | | |
| LEDClassic 4.5-50W GU10 830 60D 1BC/10 | 4.5 | 50 | 405 | 90 | No | 60 | 80 | 3000 | 10 | 15,000 | 46 x 51 | 929001287619 |
| LEDClassic 4.5-50W GU10 840 60D 1BC/10 | 4.5 | 50 | 405 | 90 | No | 60 | 80 | 4000 | 10 | 15,000 | 46 x 51 | 929001287719 |
| Classic Dim GU10 | | | | | | | | | | | | |
| LEDClassic 5-50W GU10 830 60D D 1BC/10 | 5 | 50 | 365 | 66 | Yes | 60 | 80 | 3000 | 10 | 15,000 | 46.5 x 50.5 | 929001364419 |
| Classic Non Dim MR16 | | | | | | | | | | | | |
| LEDClassic 5-50W MR16 830 60D 1BC/10 | 5 | 50 | 390 | 78 | No | 60 | 80 | 3000 | 10 | 15,000 | 46 x 51 | 929001280419 |
| LEDClassic 5-50W MR16 840 60D 1BC/10 | 5 | 50 | 410 | 82 | No | 60 | 80 | 4000 | 10 | 15,000 | 46 x 51 | 929001280519 |
| Classic Dim MR16 | | | | | | | | | | | | |
| LED 8-50W MR16 60D 830 DIM 1BC/10 | 8 | 50 | 650 | 81 | Yes | 60 | 80 | 3000 | 10 | 15,000 | 46.5 x 50.5 | 929001241519 |
| LED 8-50W MR16 60D 840 DIM 1BC/10 | 8 | 50 | 670 | 84 | Yes | 60 | 80 | 4000 | 10 | 15,000 | 46.5 x 50.5 | 929001280719 |

DimSure Dimmer Accessory

Reduce LED lamps flickering

Provide a corrected load for dimmers, making them compatible with LED lamps.

Easy to use for retrofit

Used across current Live and Neutral wires of lighting channel, it 's to be fitted between the dimmer and LED lamps.

No need to physically modify existing dimmer installation

It's connected to the output of dimmer or single output dimming channel, provide a corrected load and additional load for improve compatibility with LED lamps.

DimSure Dimming Accessory



| Product type | LED | Voltage | Current | Frequency | Dimensions | Ordering Code |
|---------------------------|-----|---------|---------|-----------|---------------|---------------|
| DimSure Dimming Accessory | W | V | mA | Hz | MM | |
| DimSure dimmer accessory | 6 | 220-240 | 30 | 50/60 | 160 x 63 x 50 | 929001242808 |



MASTER ExpertColour LEDspot LV AR111

With its new Perfect-fit design, the MASTER ExpertColour AR111 now works with most luminaires in the market as a true retrofit. The lamp creates a brilliant visual effect for retail and hospitality applications like shops, showrooms and galleries. The high quality light brings out the true colours in merchandise, including reds. MASTER ExpertColour AR111 is an ideal retrofit solution for spot, track and general lighting applications in the hospitality and retail industry. The robustly designed MASTER ExpertColour AR111 offers a well defined beam with a multitude of beam angles to suit various applications. This replacement lamp on 12V provides the light intensity and quality produced by traditional halogen lamps of 75W or 100W*

- Up to 80% energy saving compared to standard halogen spots
- Long lifetime of 40,000 hours for 15W lamp and 25,000 hours for 20W lamp (F50, L70)
- Retrofits into the vast majority of G53 based fixtures
- 12, 24 & 40 degrees beam angle for a clearly defined beam spread
- CCT: 2700K, 3000K, 4000K
- Compatible with a broad selection of transformers
- No UV and Cool Beam (no IR), making it suitable for illuminating heat-sensitive objects (food, organic materials, paintings, etc.)
- Environmental friendly (free of mercury and other hazardous materials)

MASTER LEDspot LV AR111



G53



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Beam angle | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|--|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | ° | | | | | | |
| 1 MAS LED ExpertColour 15-75W 927 AR111 24D | 15W | 75W | 800 | 55 | Yes | 24 | 90 | 2700 | 6 | 40,000 | 62 x 111 | 929002239008 |
| MAS LED ExpertColour 15-75W 927 AR111 40D | 15W | 75W | 800 | 55 | Yes | 40 | 90 | 2700 | 6 | 40,000 | 63 x 111 | 929002239308 |
| 2 MAS LED SpotLV 20-100W 930 AR111 12D | 20W | 100W | 1350 | 68 | Yes | 12 | 90 | 3000 | 6 | 25,000 | 64 x 111 | 929002239608 |
| MAS LED SpotLV 20-100W 940 AR111 12D | 20W | 100W | 1400 | 70 | Yes | 12 | 90 | 4000 | 6 | 25,000 | 65 x 111 | 929002239708 |
| MAS LED SpotLV 20-100W 930 AR111 24D | 20W | 100W | 1350 | 68 | Yes | 24 | 90 | 3000 | 6 | 25,000 | 66 x 111 | 929002239908 |
| MAS LED SpotLV 20-100W 940 AR111 24D | 20W | 100W | 1400 | 70 | Yes | 24 | 90 | 4000 | 6 | 25,000 | 67 x 111 | 929002240008 |
| MAS LED SpotLV 20-100W 930 AR111 40D | 20W | 100W | 1350 | 68 | Yes | 40 | 90 | 3000 | 6 | 25,000 | 68 x 111 | 929002240208 |
| MAS LED SpotLV 20-100W 940 AR111 40D | 20W | 100W | 1400 | 70 | Yes | 40 | 90 | 4000 | 6 | 25,000 | 69 x 111 | 929002240308 |

MASTER LEDspot PAR

The energy-saving alternative for lighting in public areas

With its robust design and warm-white beam of light, these new-generation PAR lamps are ideal for general lighting and spot lighting in the hospitality industry. They are especially suitable for public areas such as lobbies, corridors, staircases, where the light is always on.

- Up to 80% energy saving compared to halogen lamps
- Retrofitable and compatible with existing fixtures with E27 holder
- Lower maintenance costs



MASTER LEDspot PAR



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Beam angle | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering code |
|--|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| MASTER LEDspot PAR | W | W | lm | lm/W | | ° | | K | pcs | Hrs. | MM | |
| LEDClassic 11-80WPAR38 827 25D 1BC/3 SRT | 11 | 80 | 900 | 82 | No | 25 | 80 | 2700 | 3 | 15,000 | 134 x 122 | 929001322719 |

LEDspot Reflectors

- Halogen Replacement
- Available in R50, R63, R80 diameters
- Designed for spot and general lighting applications



LED Spot Reflector



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Beam angle | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|---------------------------------|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| LEDspot Reflectors | W | W | lm | lm/W | | ° | | K | pcs | Hrs. | MM | |
| 1 LED R80 9W WH FL NZ 1PF | 9 | 75 | 800 | 89 | No | 120D | 80 | 3000 | 6 | 15,000 | 90 x 80 | 929001199619 |
| 2 LED R63 WW FL E27 Dim AU 1CT | 5 | 60 | 400 | 80 | Yes | 120D | 80 | 2700 | 6 | 15,000 | 90 x 80 | 929001186049 |
| 3 LED R50 WW FL E14 Dim AU 1CT | 3.5 | 40 | 280 | 80 | Yes | 120D | 80 | 2700 | 6 | 15,000 | 90 x 80 | 929001169649 |
| 4 LED 10W E27 6500K 230V R80 AU | 10 | 80 | 950 | 95 | No | 120D | 80 | 6500 | 6 | 15,000 | 90 x 80 | 929001858119 |
| 5 LED 7W E27 6500K 230V R63 AU | 7 | 70 | 720 | 103 | No | 120D | 80 | 6500 | 6 | 15,000 | 90 x 80 | 929001857819 |
| 6 LED 4W E14 6500K 230V R50 AU | 4 | 50 | 400 | 100 | No | 120D | 80 | 6500 | 6 | 15,000 | 90 x 80 | 929001857519 |



LED capsules

CorePro LED capsule

Our LED capsule provides crisp, sparkling halogen like light. It is especially suitable for task lighting and decorative applications.

- Long lifetime
- UV- and IR-free light for less heat and protection
- For heat-sensitive objects
- Unique sparkling effect



CorePro LED capsule LV / MV



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Beam angle | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|--|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | ° | | K | pcs | Hrs. | MM | |
| CorePro LEDcapsule LV 12V G4 | | | | | | | | | | | | |
| 1 CorePro LEDcapsuleLV 0.9-10W G4 830 | 0.9 | 10 | 110 | 122 | No | n.a. | 80 | 3000 | 12 | 15,000 | 38 x 14.5 | 929001844002 |
| 2 CorePro LEDcapsuleLV 1.7-20W G4 830 | 1.7 | 20 | 205 | 121 | No | n.a. | 80 | 3000 | 12 | 15,000 | 38 x 14.5 | 929001844202 |
| CorePro LEDcapsule MV 220-240V G9 | | | | | | | | | | | | |
| 3 CorePro LEDcapsule ND 1.9-25W G9 830 | 1.9 | 25 | 210 | 111 | No | n.a. | 80 | 3000 | 12 | 15,000 | 48 x 16.5 | 929001364702 |
| 4 CorePro LEDcapsule ND 3.2-40W G9 830 | 3.2 | 40 | 400 | 125 | No | n.a. | 80 | 3000 | 12 | 15,000 | 51.5 x 17 | 929001903002 |

LED Appliance Lamp

Reduced energy and maintenance costs from increased efficacy and longer life. Not for use in microwaves or conventional ovens.



LED Appliance Lamp



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Beam angle | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|--------------------|------|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | ° | | K | pcs | Hrs. | MM | |
| LED Appliance Lamp | 1.7W | 15W | 136 | 80 | No | n.a. | 80 | 3000 | 3 | 15,000 | 146 x 90 | 929001325769 |





LED Bulb

MASTER Warm Glow Dimmable LEDbulb

The MASTER LEDbulb range delivers a dimmable warm light effect for a welcoming, warm atmosphere, making it ideal for general lighting applications. With Warm Glow the light gets warmer when dimmed which is especially suited for hospitality applications.

- Warm Glow: the more you dim the warmer the light
- High Performance Dimming
- Longest lifetime
- Superior light quality
- Maximum energy savings



MASTER LEDbulb - Warm Glow frosted



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Save up to | Base Cap | CRI | Colour temp. | Lifetime | Ordering code |
|---|-----|-------------|--------------|----------|----------------|------------|----------|-----|--------------|----------|---------------|
| | W | W | lm | lm/W | | | | | K | Hrs. | |
| 1 LEDBulb 11-75W A60 B22 2700K FR D AU/BC | 11 | 75 | 1055 | 96 | Yes, Warm Glow | 85% | B22 | 80 | 2700-2200 | 15,000 | 929001353279 |
| 2 LEDBulb 11-75W A60 E27 2700K FR D AU/BC | 11 | 75 | 1055 | 96 | Yes, Warm Glow | 85% | E27 | 80 | 2700-2200 | 15,000 | 929001352779 |
| 3 LEDBulb 8.5-60W A60 B22 2700K FR D AU/BC | 8.5 | 60 | 806 | 95 | Yes, Warm Glow | 86% | B22 | 80 | 2700-2200 | 15,000 | 929001353079 |
| 4 LEDBulb 8.5-60W A60 E27 2700K FR D AU/BC | 8.5 | 60 | 806 | 95 | Yes, Warm Glow | 86% | E27 | 80 | 2700-2200 | 15,000 | 929001352579 |

Generation 8 LED lamps

The affordable LED bulb solution

Philips MyCare LEDbulb deliver Interlaced Optics to provide comfortable brightness of GLS bulbs in indoor application. Philips MyCare LEDbulb offers over 85% energy saving and a longer lifetime of 15,000 hours (equivalent to 15 years if lit 2.7 hours per day across 365 days)

Design highlights

With form factor designed as a direct retrofit into A60 fixtures. Philips Interlaced Optics deliver:

- Reduced glare
- No visible flickering
- Last up to 15 years
- Environmental friendly, no Mercury
- Low Carbon Footprint

Generation 8 LED lamps



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Bulb Shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|---|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|--------------|---------------|
| | W | W | lm | lm/W | | | | K | pcs | Hrs. | MM | |
| 1 Bulb A60S 6-55W 560lm 3000K E27 ND | 6 | 55 | 580 | 96.67 | No | A60 | 80 | 3000 | 6 | 15,000 | 109.1 x 60.5 | 929001914999 |
| Bulb A60S 6-55W 580lm 6500K E27 ND | 6 | 55 | 580 | 96.67 | No | A60 | 80 | 6500 | 6 | 15,000 | 109.1 x 60.5 | 929001915199 |
| Bulb A60S 8-68W 770lm 3000K E27 ND | 8 | 68 | 770 | 96.25 | No | A60 | 80 | 3000 | 6 | 15,000 | 109.1 x 60.5 | 929001915399 |
| Bulb A60S 8-68W 770lm 6500K E27 ND | 8 | 68 | 770 | 96.25 | No | A60 | 80 | 6500 | 6 | 15,000 | 109.1 x 60.5 | 929001915599 |
| 2 Bulb A60S 6-55W 580lm 6500K B22 ND | 6 | 55 | 580 | 96.67 | No | A60 | 80 | 6500 | 6 | 15,000 | 107.6 x 60.5 | 929001915299 |
| Bulb A60S 6-55W 560lm 3000K B22 ND | 6 | 55 | 580 | 96.67 | No | A60 | 80 | 3000 | 6 | 15,000 | 107.6 x 60.5 | 929001915099 |
| Bulb A60S 8-68W 770lm 3000K B22 ND | 8 | 68 | 770 | 96.25 | No | A60 | 80 | 3000 | 6 | 15,000 | 107.6 x 60.5 | 929001915499 |
| Bulb A60S 8-68W 770lm 6500K B22 ND | 8 | 68 | 770 | 96.25 | No | A60 | 80 | 6500 | 6 | 15,000 | 107.6 x 60.5 | 929001915699 |
| 3 Bulb A60M 10-83W 1020lm 3000K E27 ND | 10 | 83 | 1020 | 102.00 | No | A60 | 80 | 3000 | 6 | 15,000 | 109.1 x 60.5 | 929001915799 |
| Bulb A60M 10-83W 1020lm 6500K E27 ND | 10 | 83 | 1020 | 102.00 | No | A60 | 80 | 6500 | 6 | 15,000 | 109.1 x 60.5 | 929001915999 |
| Bulb A60M 12-98W 1360lm 3000K E27 ND | 12 | 98 | 1360 | 113.33 | No | A60 | 80 | 3000 | 6 | 15,000 | 109.1 x 60.5 | 929001916199 |
| Bulb A60M 12-98W 1360lm 6500K E27 ND | 12 | 98 | 1360 | 113.33 | No | A60 | 80 | 6500 | 6 | 15,000 | 109.1 x 60.5 | 929001916399 |
| 4 Bulb A60M 10-83W 1020lm 6500K B22 ND | 10 | 83 | 1020 | 102.00 | No | A60 | 80 | 6500 | 6 | 15,000 | 107.6 x 60.5 | 929001916099 |
| Bulb A60M 10-83W 1020lm 3000K B22 ND | 10 | 83 | 1020 | 102.00 | No | A60 | 80 | 3000 | 6 | 15,000 | 107.6 x 60.5 | 929001915899 |
| Bulb A60M 12-98W 1360lm 3000K B22 ND | 12 | 98 | 1360 | 113.33 | No | A60 | 80 | 3000 | 6 | 15,000 | 107.6 x 60.5 | 929001916299 |
| Bulb A60M 12-98W 1360lm 6500K B22 ND | 12 | 98 | 1360 | 113.33 | No | A60 | 80 | 6500 | 6 | 15,000 | 107.6 x 60.5 | 929001916499 |

High Lumen LED lamps

High lumen LED Bulb in indoor application, even designed for a wide range of applications including damp areas.

The housing is made of plastic and metal and not so fragile as glass bulbs, which makes it even more popular in most applications. Under 220-240V, the product can deliver the

best performance. And even under 90V, the bulb can be lit up, which makes it work in some unstable line voltage.

LEDbulb offers up to 89% energy saving when replacing GLS and 50% when replacing a CFLi. It also has a longer lifetime of 10,000 hours (equivalent to 10 years if lit 2.7 hours per day across 365 days) conditions.



High Lumen LED bulb



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Bulb shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|---|------|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | | | K | pcs | Hrs. | MM | |
| 1 LEDBulb 14.5W E27 3000K 230V A67 1CT/6 AU | 14.5 | 120 | 1700 | 117.24 | No | A67 | 80 | 3000 | 6 | 10,000 | 132 x 67 | 929002003849 |
| | 14.5 | 120 | 1800 | 124.14 | No | A67 | 80 | 6500 | 6 | 10,000 | 132 x 67 | 929002003949 |
| 2 LEDBulb 14.5W B22 3000K 230V A67 1CT/6 AU | 14.5 | 120 | 1700 | 117.24 | No | A67 | 80 | 3000 | 6 | 10,000 | 132 x 67 | 929002004449 |
| | 14.5 | 120 | 1800 | 124.14 | No | A67 | 80 | 6500 | 6 | 10,000 | 132 x 67 | 929002004549 |
| 3 LEDBulb 19W E27 6500K 230V A80 1CT/6 AU | 19 | 160 | 2300 | 121.05 | No | A80 | 80 | 6500 | 6 | 10,000 | 154 x 80 | 929002004149 |
| | 19 | 160 | 2200 | 115.79 | No | A80 | 80 | 3000 | 6 | 10,000 | 154 x 80 | 929002004049 |
| 4 LEDBulb 19W B22 6500K 230V A80 1CT/6 AU | 19 | 160 | 2300 | 121.05 | No | A80 | 80 | 6500 | 6 | 10,000 | 154 x 80 | 929002004749 |
| | 19 | 160 | 2200 | 115.79 | No | A80 | 80 | 3000 | 6 | 10,000 | 154 x 80 | 929002004649 |

MASTER LED sticks

Philips LEDstick deliver high quality light in a compact design ideal for downlights and slim luminaire applications.

Design highlights

With optimized optical design, Philips LEDstick technology delivers:

- All around illumination
- Up to 70% less glare
- No visible flickering
-

Application areas

The compact and bright light makes it ideal for general lighting applications in the retail and hospitality industry by offering their guests a differentiating ambiance and unique experience in public areas like:

- Elite shops
- Corridors / Stairways / Washrooms
- Lobby / Reception areas
- Hotel rooms / Bars
- Home

Application notes

- Operating temperature range is between -20 °C and 45 °C ambient
- Only to apply in dry or damp locations in open fixtures

MASTER LED stick



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Bulb shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|------------------------------------|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | | | K | pcs | Hrs. | MM | |
| 1 LEDStick 5.5W E14 3000K 1PF/6 AU | 5.5 | 55 | 550 | 100.00 | No | Stick | 80 | 3000 | 6 | 15,000 | 147 x 39 | 929001900669 |
| | 5.5 | 55 | 600 | 109.09 | No | Stick | 80 | 6500 | 6 | 15,000 | 148 x 39 | 929001900869 |
| 2 LEDStick 5.5W B22 3000K 1PF/6 AU | 5.5 | 55 | 550 | 100.00 | No | Stick | 80 | 3000 | 6 | 15,000 | 149 x 39 | 929001927369 |
| | 5.5 | 55 | 600 | 109.09 | No | Stick | 80 | 6500 | 6 | 15,000 | 150 x 39 | 929001927569 |
| 3 LEDStick 7.5W E27 3000K 1PF/6 AU | 7.5 | 68 | 750 | 100.00 | No | Stick | 80 | 3000 | 6 | 15,000 | 147 x 39 | 929001901169 |
| | 7.5 | 68 | 806 | 107.47 | No | Stick | 80 | 6500 | 6 | 15,000 | 147 x 39 | 929001901369 |
| 4 LEDStick 7.5W B22 3000K 1PF/6 AU | 7.5 | 68 | 750 | 100.00 | No | Stick | 80 | 3000 | 6 | 15,000 | 147 x 39 | 929001926769 |
| | 7.5 | 68 | 806 | 107.47 | No | Stick | 80 | 6500 | 6 | 15,000 | 147 x 39 | 929001926969 |
| 5 LEDStick 9.5W E27 3000K 1PF/6 AU | 9.5 | 85 | 950 | 100.00 | No | Stick | 80 | 3000 | 6 | 15,000 | 147 x 39 | 929001901469 |
| | 9.5 | 85 | 1050 | 110.53 | No | Stick | 80 | 6500 | 6 | 15,000 | 148 x 39 | 929001901669 |
| 6 LEDStick 9.5W B22 3000K 1PF/6 AU | 9.5 | 85 | 950 | 100.00 | No | Stick | 80 | 3000 | 6 | 15,000 | 149 x 39 | 929001927069 |
| | 9.5 | 85 | 1050 | 110.53 | No | Stick | 80 | 6500 | 6 | 15,000 | 150 x 39 | 929001927269 |

LED Globe

Decorative covered standard energy saving lamp in globe shape gives a soft, diffused light with a high comfort level, suitable for applications where lamp is visible. Imitates the look of a frosted globe shaped incandescent lamp.

Design highlights

- Reduced glare and aesthetic form due to globe shaped outer bulb
- Energy savings of up to 86%
- Long lifetime of 15,000 hours (F50L70)
- Warm white CCT 2700K

Application areas

The warm light makes it ideal for general and decorative lighting applications in the retail and hospitality industry by offering their guests a differentiating ambiance and unique experience in public areas like:

- Elite shops
- Corridors / Stairways / Washrooms
- Lobby / Reception areas
- Hotel rooms / Bars
- Home

Application notes

- Operating temperature range is between -20 °C and 45 °C ambient
- Only to apply in dry or damp locations in open fixtures
- Not intended for use with emergency light fixtures or exit lights
- Not intended for enclosed luminaires

LED Globe



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Bulb shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|--|-------|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | | | K | pcs | Hrs. | MM | |
| 1 LEDGlobe9.5-60W G93 E27 WW 230V_AU | 9.5W | 60W | 806lm | 85lm/W | No | G93 | 80 | 2700 | 3 | 15,000 | 111 x 96 | 929001229269 |
| 2 LEDGlobe9.5-60W G93 B22 WW 230V_AU | 9.5W | 60W | 806lm | 85lm/W | No | G93 | 80 | 2700 | 3 | 15,000 | 111 x 96 | 929001230869 |
| 3 LEDGlobe11.5-75W G120 E27 WW 230V_AU | 11.5W | 75W | 1055lm | 92lm/W | No | G120 | 80 | 2700 | 3 | 15,000 | 168 x 120 | 929001229669 |
| 4 LEDGlobe11.5-75W G120 B22 WW 230V_AU | 11.5W | 75W | 1055lm | 92lm/W | No | G120 | 80 | 2700 | 3 | 15,000 | 168 x 120 | 929001231269 |

Philips Deco LED Giant.

Designed to be seen,
looks good on or off

New Philips decorative LED bulbs are simply too stylish to hide under a lamp shade. Inspired by the latest industrial-style trends, this collection features a range of highly stylized, large-scale filament light bulbs that demand to be seen. Striking centerpiece, distinctive standing lamp or suspended from the ceiling – this collection is designed to create an industrial-chic look and a crisp, clean ambiance in every space in the home. It's time for light bulbs to take the spotlight.



Deco LED Giant
Modern range



Deco LED Giant
Vintage range

The new Deco LED collection (bulb) transforms your home with a perfect blend of white light and a lean, minimalistic lighting experience. With very long lifetime, up to 90% energy savings, no flickering and an instant full level brightness, you will also enjoy soft and evenly distributed light with that trendy and stylish charm for a welcoming harmony in your space.

Philips Deco LED Giant features



Modern & Vintage style



High color rendering, CRI >80



Dimmable and non-dimmable version available



Energy savings up to 90%



Long lifetime - up to 15.000 h



Easy replacement



Features


- Perfect fit and high quality finishing
- High color rendering (CRI> 80) for vivid colours
- Eco-friendly: contains no mercury or other hazardous substances

Benefits

- Around 90% energy saving
- Very long lifetime that reduces the need for replacement
- Easy replacement of classic conventional lamps

Application

decorative installations / domestic applications / hospitality / restaurants and hotels



Giant LED Filament Collection



Giant LED Filament



| Product type | LED | Lumen output | Bulb shape | CRI | Colour temp. | Lifetime | Ordering code |
|-----------------------------|----------|--------------|------------|-----|--------------|-------------|---------------|
| Smokey Dim | W | lm | | | K | Hrs. | |
| 1 Classic Giant G200 Smokey | 6.5 W | 270 lm | G200 | 80 | 4000 | 15,000 | 929001903199 |
| 2 Classic Giant A160 Smokey | 6.5 W | 270 lm | A160 | 80 | 4000 | 15,000 | 929001903201 |
| 3 Classic Giant T65 Smokey | 6.5 W | 270 lm | T65 | 80 | 4000 | 15,000 | 929001903301 |
| Gold Dim | W | lm | | | K | Hrs. | |
| 4 Classic Giant G200 Smokey | 6.5 W | 470 lm | G200 | 80 | 2000 | 15,000 | 929001873499 |
| 5 Classic Giant A160 Smokey | 6.5 W | 470 lm | A160 | 80 | 2000 | 15,000 | 929001873501 |
| 6 Classic Giant T65 Smokey | 6.5 W | 470 lm | T65 | 80 | 2000 | 15,000 | 929001873601 |



Cords



| Product type | Bulb shape | Colour temp. | Lifetime | Ordering code |
|-------------------------------|-----------------|---------------|--------------|---------------|
| Cords | Cap Base | Colour | Net W | |
| CORD/VIN/E27/rose gold 1CT EU | E27 | Rose Gold | 0.432 kg | 929001977801 |
| CORD/modern/E27/black 1CT EU | E27 | Black | 0.432 kg | 929001977901 |
| CORD/classic/E27/gold 1CT EU | E27 | Gold | 0.432 kg | 929001978001 |

Classic LED bulbs

Featuring a classic heritage design, the new Philips Vintage LED lamp family is reminiscent of familiar incandescent bulbs. Available in an array of giant shapes, candles and other familiar form factors, they provide a seamless fit across your space.

When used as a statement piece, they add a sense of nostalgia and create a highly desirable atmosphere for socialization and relaxing.

Benefits

Perfect sustainable replacement for conventional bulbs with up to 90% of energy saving

- Dimmable versions can be used with most dimmers to create your desired ambience with smooth dimming to 10% of full light levels
- Warm light effect to create a cozy atmosphere

Features

- Extra warm light with Vintage design
- Available in an array of shapes and familiar form factors
- Light all around with improved light distribution effect

Application

- Perfect for decorative installations
- Domestic applications
- Hospitality: restaurants and hotels

Classic filament LED bulbs – DIM clear 40W – 100W



| Product type | | | | | Dimmable | Base Shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|---|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | LED | Traditional | Lumen output | Efficacy | | | | | | | | |
| Classic LED bulb filament dim | W | W | lm | lm/W | | | K | pcs | Hrs. | MM | | |
| 1 LEDClassic 4.5-40W P45 E27 WWCL D AU | 4.5 | 40 | 470 | 104 | Yes | P45 | 80 | 2700 | 6 | 15,000 | 89 x 45 | 929001332639 |
| 2 LED classic 40W P45 B22 WW CL D 1PF | 5 | 40 | 470 | 118 | Yes | P45 | 80 | 2700 | 6 | 15,000 | 89 x 45 | 929001332749 |
| 3 LED classic 60W G93 E27 WW CL D 1PF | 8 | 60 | 806 | 134 | Yes | G93 | 80 | 2700 | 6 | 15,000 | 150 x 95 | 929001895749 |
| 4 LED classic 50W A60 B22 FL GOLD D 1PF | 8 | 50 | 806 | 101 | Yes | A60 | 80 | 2200 | 6 | 15,000 | 102 x 60 | 929001921749 |
| 5 LED classic 50W A60 E27 FL GOLD D 1PF | 8 | 50 | 806 | 101 | Yes | A60 | 80 | 2200 | 6 | 15,000 | 102 x 60 | 929001921649 |
| 6 LED classic 50W ST64 E27 820 GOLD 1PF | 8 | 50 | 806 | 115 | Yes | ST64 | 80 | 2000 | 6 | 15,000 | 148 x 64 | 929001895949 |
| 7 LED classic 50W ST64 B22 820 GOLD D 1PF | 7 | 50 | 806 | 115 | Yes | ST64 | 80 | 2000 | 6 | 15,000 | 148 x 64 | 929001228449 |
| 8 LED classic 50W G120 E27 820 GOLD D 1PF | 8 | 50 | 806 | 115 | Yes | G120 | 80 | 2000 | 6 | 15,000 | 188 x 125 | 929001896149 |
| 9 LED classic 50W G120 B22 820 GOLD D1PF | 7 | 50 | 806 | 115 | Yes | G120 | 80 | 2000 | 6 | 15,000 | 188 x 125 | 929001257949 |
| 10 LED classic 40W B35 E14 WW CL D 1PF | 5 | 40 | 470 | 118 | Yes | B35 | 80 | 2700 | 6 | 15,000 | 118 x 35 | 929001332139 |
| 11 LED classic 40W B35 B22 WW CL D 1PF | 5 | 40 | 470 | 118 | Yes | B35 | 80 | 2700 | 6 | 15,000 | 118 x 35 | 929001332249 |
| Classic LED bulb filament Non Dim | | | | | | | | | | | | |
| 12 LED classic 2-25W P45 E14 WW CL ND 1PF/6 | 2 | 25 | 250 | 125 | No | P45 | 80 | 2700 | 6 | 15,000 | 89 x 45 | 929001238639 |
| 13 LED classic 40W B35 B15 WW CL ND | 4.3 | 40 | 470 | 85 | No | B35 | 80 | 2700 | 6 | 15,000 | 118 x 35 | 929001889838 |
| 14 LED classic 25W P45 B22 WW CL ND | 2 | 25 | 250 | 125 | No | P45 | 80 | 2700 | 6 | 15,000 | 89 x 45 | 929001815938 |



Battery lamp

Rechargeable LED Bulb

Philips rechargeable LED bulb with robust design and industry best reliable battery back up makes you feel relaxed and safe. Power outage can be harmful for the wellbeing of our elders, children and people in need of medical assistance. Philips Rechargeable LED Bulb delivers a sense of care to your loved ones.

Design highlights

- An innovative design with battery power back up
- Long Life Battery (500 Recharge Cycles)
- Intelligent Battery Management system prevents over charging / discharging to secure battery life
- Back up light for more than 3 hours
- Wide Voltage 110-240V 50/60Hz
- Long Life 15000 Hours
- Available in 3000K & 6500K CCT

Application areas

- Design for Indoor applications only
- Bed room/Living Room/Staircase/Bathroom/Foyer
- Hotel guest room/Lobby/Corridors/Lifts
- Retail check out area/common area

Application notes

- Suitable for Open Fixture only
- Battery Bulb work in two modes
 A. Mains Mode – When mains electricity is available it work like any other normal bulb
 B. Battery Mode – When mains electricity is gone and wall switch is On it turn to battery mode, to shut down the light bulb turn off the wall switch
- Not intended for use with emergency light fixtures or exit lights
- Operating temp range is in between -10 Degree C and 40 Degree C ambient

Rechargeable LED Bulb



E27



| Product type | LED | Traditional | Lumen output | Efficacy | Lumen output at black out | Dimmable | Bulb Shape | CRI | Colour temp. | Pack | Lifetime | Min hr at black out | Dimensions | Ordering Code |
|---|-----|-------------|--------------|----------|---------------------------|----------|------------|-----|--------------|------|----------|---------------------|------------|---------------|
| | W | W | lm | lm/W | lm | | | | K | pcs | Hrs. | Hrs. | MM | |
| | | | | | | | | | | | | | | |
| LEDBulb BB 7-60W E27 3000K 110-240V A67 | 7 | 60W | 700 | 100 | 100-200 | No | A67 | 80 | 3000 | 6 | 15,000 | 2.5 | 137 x 71 | 929002066707 |
| LEDBulb BB 7-60W E27 6500K 110-240V A67 | 7 | 60W | 700 | 100 | 100-200 | No | A67 | 80 | 6500 | 6 | 15,000 | 2.5 | 137 x 71 | 929002066807 |



Sensor lamp

Lights up when you need it

Introducing the new Philips motion and daylight sensor LED lamps, a clever energy efficient addition to any home. Thanks to a built-in sensor, this modern LED lamp can detect when you walk close-by and turn on automatically. Then, when the surrounding light becomes bright enough, the motion sensor automatically switches off, so the lamp will not turn on, even when there is motion around, thus saving you energy.

Design highlights

- Form factor is designed as a direct retrofit of A60 shape
- Long lifetime of 15,000 hours
- Up to 89% energy savings when replacing a GLS
- Designed for a wide range of applications including damp areas
- Lit up under 110V line voltage and best performance is delivered under 220V-240V

Application areas

- Ideal for a hallway, pantry, deck, main entrance and walk in wardrobes.

Application notes

- Only to use in dry or damp locations and most of open fixtures with E27 lamp holders that offer sufficient space (10mm free air space)
- Sensor should not be covered for optimal use
- Not intended for use with emergency light fixtures or exit lights
- Not intended for use in enclosed luminaires
- Lit up line voltage: 110V
- The motion sensor is turned on below 80lux
- Stay-on time after no motion is detected: 60s
- Detection angle: 90 degrees, which corresponds to around 2m detection distance, with a hypothesis of 2.7m height.

Sensor Lamp



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Bulb Shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|--|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | | | K | pcs | Hrs. | MM | |
| LED Sensor 60W A60 E27 WH FR ND 1PF/6 | 8 | 60W | 850 | 106.25 | No | A60 | 80 | 2700 | 6 | 15,000 | 111 x 61 | 929002058507 |
| LED Sensor 60W A60 E27 CDL FR ND 1PF/6 | 8 | 60W | 850 | 106.25 | No | A60 | 80 | 6500 | 6 | 15,000 | 111 x 61 | 929002058607 |



UFO

LED Ceiling Bulb

Philips My Care LED Ceiling Bulb delivers Quick Fix solution with high quality light to provide comfortable brightness in indoor application. Philips LED Ceiling Bulb offers over 85% energy saving and a longer lifetime of 15,000 hours (equivalent to 15 years if lit 2.7 hours per day across 365 days).

Design highlights

- Easy for installation
- Wider surface
- 50% less glare
- Last up to 15 years

Application areas

- The eye comfort light for general lighting application at home.
- Retail and Hospitality
- Corridors / Stairways / Washrooms

Application notes

- Operating temperature range is between -20 °C and 45 °C ambient
- Only to apply in dry or damp locations
- Not intended for use with emergency light fixtures or exit lights
- Not intended for enclosed luminaires

LED Ceiling Bulb



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Bulb Shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|--------------------------------------|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | | | K | pcs | Hrs. | MM | |
| UFO LEDBulb 24W E27 3000K 230V 1CT/6 | 24 | 150W | 2150 | 89.58 | No | UFO | 80 | 3000 | 6 | 15,000 | 200 x 82 | 929001971807 |
| UFO LEDBulb 24W E27 6500K 230V 1CT/6 | 24 | 150W | 2250 | 93.75 | No | UFO | 80 | 6500 | 6 | 15,000 | 200 x 82 | 929001971907 |
| UFO LEDBulb 24W B22 3000K 230V 1CT/6 | 24 | 150W | 2150 | 89.58 | No | UFO | 80 | 3000 | 6 | 15,000 | 200 x 82 | 929001972007 |
| UFO LEDBulb 24W B22 6500K 230V 1CT/6 | 24 | 150W | 2250 | 93.75 | No | UFO | 80 | 6500 | 6 | 15,000 | 200 x 82 | 929001972107 |



LED candles & lusters

MASTER LED Candles & Lusters

Thanks to a revolutionary new lens design, these candles now produce the most beautiful sparkling light. The ivory-Coloured design is a perfect match with existing luminaires.

- Philips Classic LED – Designed to be seen
- Warm Glow: the more you dim the warmer the light
- Unique, eye-catching lens design
- Huge energy savings

MASTER LED candles & lusters – Warm Glow



E14 E27 B22



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Bulb Shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|---|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | | | | | | | | | | | | |
| Master Dimmable Range | | | | | | | | | | | | |
| 1 MAS LEDcandle DT 6-40W B22 B38 CL | 6 | 40 | 470 | 78.3 | Yes | B38 | 80 | 2700-2200 | 10 | 25,000 | 113 x 38 | 929001140802 |
| 2 MAS LEDcandle DT 40W E14 827 B38 CL_APR | 6 | 40 | 470 | 78.3 | Yes | B38 | 80 | 2700-2200 | 10 | 25,000 | 113 x 38 | 929001140408 |
| MAS LEDcandle DT 8-60W B40 E14 827 CL | 8 | 60 | 806 | 100.8 | Yes | B40 | 80 | 2700-2200 | 10 | 25,000 | 127 x 40 | 929001211702 |
| 3 MAS LEDlustre DT 6-40W E14 P48 CL | 6 | 40 | 470 | 78.3 | Yes | P48 | 80 | 2700-2200 | 10 | 25,000 | 95 x 48 | 929001140602 |
| 4 MAS LEDlustre DT 40W E27 827 P48 CL | 6 | 40 | 470 | 78.3 | Yes | P48 | 80 | 2700-2200 | 10 | 25,000 | 95 x 48 | 929001140702 |
| 5 MAS LEDlustre DT 8-60W P50 E14 827 CL | 8 | 60 | 806 | 100.8 | Yes | P50 | 80 | 2700-2200 | 10 | 25,000 | 111 x 50 | 929001211902 |

Classic filament Candles & Lusters

Classic look & feel

Featuring a classic heritage design, LED Classic bulbs deliver beautiful, decorative warm-white light while saving around 90% on energy costs. The familiar shapes of the LED Classic lamps are a perfect fit for your existing fixtures.

- Around 90% energy saving
- Very long lifetime that reduces the need for replacement
- Easy replacement of classic conventional lamps

Classic filament candles and lusters



| Product type | LED | Traditional | Lumen output | Efficacy | Dimmable | Bulb Shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|---|-----|-------------|--------------|----------|----------|------------|-----|--------------|------|----------|------------|---------------|
| | W | W | lm | lm/W | | | | K | pcs | Hrs. | MM | |
| Classic LED bulb filament Non Dim | | | | | | | | | | | | |
| 1 LEDclassic 2-25W P45 E14 WW CL ND 1PF/6 | 2 | 25 | 250 | 125 | No | P45 | 80 | 2700 | 6 | 15,000 | 89 x 45 | 929001238639 |
| 2 LED classic 40W B35 B15 WW CL ND | 4.3 | 40 | 470 | 85 | No | B35 | 80 | 2700 | 6 | 15,000 | 118 x 35 | 929001889838 |
| 3 LED classic 25W P45 B22 WW CL ND | 2 | 25 | 250 | 125 | No | P45 | 80 | 2700 | 6 | 15,000 | 89 x 45 | 929001815938 |
| Classic Filament Candles and Lusters Dim | | | | | | | | | | | | |
| 4 LEDClassic 4.5-40W P45 E27 WWCL DAU | 4.5 | 40 | 470 | 104 | Yes | P45 | 80 | 2700 | 6 | 15,000 | 89 x 45 | 929001332639 |
| 5 LED classic 40W P45 B22 WW CL D 1PF | 4 | 40 | 470 | 118 | Yes | P45 | 80 | 2700 | 6 | 15,000 | 89 x 45 | 929001332749 |
| 6 LED classic 40W B35 E14 WW CL D 1PF | 4 | 40 | 470 | 118 | Yes | B35 | 80 | 2700 | 6 | 15,000 | 118 x 35 | 929001332139 |
| 7 LED classic 40W B35 B22 WW CL D 1PF | 4 | 40 | 470 | 118 | Yes | B35 | 80 | 2700 | 6 | 15,000 | 118 x 35 | 929001332249 |

LED Candles & Lusters - Non Dim

The frosted CorePro LED candle is designed for retrofit replacement of incandescent lamps.

- Non-Dimmable
- Clear and frosted
- Huge energy savings



Candles - Non Dimable



| Product type | LED | | Traditional | Lumen output | Efficacy | Dimmable | Bulb Shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|--|-----|----|-------------|--------------|----------|----------|------------|------|--------------|--------|----------|--------------|---------------|
| | W | W | lm | lm/W | | | | K | pcs | Hrs. | H x W | | |
| Clear | | | | | | | | | | | | | |
| 1 LED 4-25W E14 2700K B35 CL ND SINGLE PACK | 4 | 25 | 250 | 63 | No | B35 | 80 | 2700 | 6 | 15,000 | 106 x 35 | 929001142249 | |
| LED 5.5-35W E14 2700K B35 CL ND SINGLE PACK | 5.5 | 35 | 470 | 85 | No | B35 | 80 | 2700 | 6 | 15,000 | 106 x 35 | 929001142549 | |
| LED 5.5-35W E14 2700K B35 CL ND TWIN PACK | 5.5 | 35 | 470 | 85 | No | B35 | 80 | 2700 | 3 | 15,000 | 106 x 35 | 929001142589 | |
| 2 LED 5.5-35W E27 2700K B35 CL NDTWIN PACK | 5.5 | 35 | 470 | 85 | No | B35 | 80 | 2700 | 3 | 15,000 | 106 x 35 | 929001324789 | |
| Frosted | | | | | | | | | | | | | |
| 3 LED 4-25W B22 2700K B35 FR ND SINGLE PACK | 4 | 25 | 250 | 63 | No | B35 | 80 | 2700 | 6 | 15,000 | 106 x 35 | 929001193549 | |
| LED 5.5-35W B22 2700K 230V B35 FR ND SINGLE PACK | 5.5 | 35 | 470 | 85 | No | B35 | 80 | 2700 | 6 | 15,000 | 106 x 35 | 929001193349 | |
| 4 LED 5.5-40W E14 2700K B35 FR ND SINGLE PACK | 5.5 | 40 | 470 | 85 | No | B35 | 80 | 2700 | 6 | 15,000 | 106 x 35 | 929001157749 | |
| LEDcandle 5-50W E14 840 B35NDFR TWIN PACK | 5 | 50 | 470 | 85 | No | B35 | 80 | 2700 | 3 | 15,000 | 106 x 35 | 929001959979 | |



Lusters - Non Dimable



| Product type | LED | | Traditional | Lumen output | Efficacy | Dimmable | Bulb Shape | CRI | Colour temp. | Pack | Lifetime | Dimensions | Ordering Code |
|--|-----|----|-------------|--------------|----------|----------|------------|------|--------------|--------|----------|--------------|---------------|
| | W | W | lm | lm/W | | | | K | pcs | Hrs. | MM | | |
| Clear | | | | | | | | | | | | | |
| 1 LED 4-25W E14 2700K P45 CL ND SINGLE PACK | 4 | 25 | 250 | 62.5 | No | P45 | 80 | 2700 | 6 | 15,000 | 87 x 45 | 929001142349 | |
| LED 5.5-40W E14 2700K P45 CL ND SINGLE PACK | 5.5 | 40 | 470 | 85.5 | No | P45 | 80 | 2700 | 6 | 15,000 | 87 x 45 | 929001142649 | |
| LED 5.5-35W E14 2700K P45 CL ND TWIN PACK | 5.5 | 35 | 470 | 85.5 | No | P45 | 80 | 2700 | 3 | 15,000 | 87 x 45 | 929001142689 | |
| 2 LED 5.5-35W E27 2700K P45 CL ND TWIN PACK | 5.5 | 35 | 470 | 85.5 | No | P45 | 80 | 2700 | 3 | 15,000 | 87 x 45 | 929001175389 | |
| Frosted | | | | | | | | | | | | | |
| 3 LED 4-25W B22 2700K P45 FR ND SINGLE PACK | 4 | 25 | 250 | 62.5 | No | P45 | 80 | 2700 | 6 | 15,000 | 87 x 45 | 929001193649 | |
| LED 5.5-35W B22 2700K P45 FR ND SINGLE PACK | 5.5 | 35 | 470 | 85.5 | No | P45 | 80 | 2700 | 6 | 15,000 | 87 x 45 | 929001193449 | |
| LED 5.5-40W B22 2700K P45 FR ND TWIN PACK | 5.5 | 40 | 470 | 85.5 | No | P45 | 80 | 2700 | 3 | 15,000 | 87 x 45 | 929001193489 | |
| 4 LED Candle 5-50w E14 840 P45NDFR TWIN PACK | 5 | 50 | 470 | 94 | No | P45 | 80 | 2700 | 3 | 15,000 | 87 x 45 | 929001960279 | |



HID replacement

TrueForce Core LED Industrial and Retail – „Tshape”

The affordable LED solution for High Intensity Discharge (HID) lamp replacement

Philips TrueForce Core LED lamps offer an easy LED solution to replace High Intensity Discharge (HID) lamps.

The product enables immediate energy savings at low initial cost. Customers can easily retrofit TrueForce Core LED lamps while bypassing

the existing ballast and enhance the lighting quality.

- Low initial investment
- High energy efficiency
- Lifetime 20,000hrs
- Wide beam angle, 240D
- Direct Mains operation
- Pleasant white light with CRI 80



TrueForce Core LED



| Product type | LED | Lumen output | Efficacy | Dimmable | Bulb Shape | CRI | Colour temp | Pack | Lifetime | Dimensions | Ordering code |
|-------------------------------|-----|--------------|----------|----------|------------|-----|-------------|------|----------|------------|---------------|
| | W | W | lm/W | | | | K | | Hrs. | MM | |
| TForce Core HB 28-30W E27 840 | 30W | 2800 | 93 | No | HB | 80 | 4000 | 1 | 20,000 | 105 x 190 | 929001937708 |
| TForce Core HB 28-30W E27 865 | 30W | 2800 | 100 | No | HB | 80 | 6500 | 1 | 20,000 | 105 x 190 | 929001937808 |
| TForce Core HB 26-30W E27 830 | 30W | 2600 | 100 | No | HB | 80 | 3000 | 1 | 20,000 | 105 x 190 | 929001937608 |
| TForce Core HB 40-40W E27 865 | 40W | 4000 | 100 | No | HB | 80 | 6500 | 1 | 20,000 | 105 x 190 | 929001938108 |
| TForce Core HB 37-40W E27 830 | 40W | 3700 | 100 | No | HB | 80 | 3000 | 1 | 20,000 | 105 x 190 | 929001937908 |
| TForce Core HB 40-40W E27 840 | 40W | 4000 | 100 | No | HB | 80 | 4000 | 1 | 20,000 | 105 x 190 | 929001938008 |
| TForce Core HB 50-50W E27 840 | 50W | 5000 | 100 | No | HB | 80 | 4000 | 1 | 20,000 | 123 x 225 | 929001938308 |
| TForce Core HB 50-50W E27 865 | 50W | 5000 | 100 | No | HB | 80 | 6500 | 1 | 20,000 | 123 x 225 | 929001938408 |
| TForce Core HB 54-60W E40 840 | 60W | 5400 | 90 | No | HB | 80 | 4000 | 1 | 20,000 | 123 x 225 | 929001938608 |
| TForce Core HB 54-60W E40 865 | 60W | 5400 | 90 | No | HB | 80 | 6500 | 1 | 20,000 | 123 x 225 | 929001938708 |

Choosing the right light is as easy as 1, 2, 3

1. Choose a shape



2. Choose a base



MR16
(12V spot light)



GU10
(230V spot light)



E14
(small Edison screw)



B15
(small Bayonet)



E27 Edison screw
(most common in newer homes)



B22 Bayonet
(typically in older homes)




G4 for capsules



G9 for capsules

3. Choose brightness & ambiance

Colour temperature



Lumens vs Watts





© 2019 Signify Holding. All rights reserved. Signify reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication. Application images shown may not reflect actual products advertised.

Version: November 2019

Signify New Zealand Limited

Level 3, 123 Carlton Gore Road
Newmarket, Auckland 1023
New Zealand
T: 0800 454 448 / 0800 4 LIGHT

www.philips.com/ledlamps