

Philips **LED tube**

The right LED tube every time



Industry leading LED range of fluorescent tube replacements

- Best in class lumen performance
- Best compatibility
- Easy installation

For general applications, Universal is the tube of choice.

For more demanding applications: use our Selector tool.



Find the **right** solution in our range using the **Selector tool** productfinder.lighting.philips.com

MASTER Value LEDtube T8

- Easy and cost effective upgrade for fluorescent tubes (typical payback time within 1 year)
- 50,000 hours lifetime
- Up to 3700 lumen output
- Up to 155 lm/W

CorePro LEDtube T8 Universal

- Works on every driver technology (EM/HF/Mains)
- Up to 2700 lumen output
- 1 year typical payback time for 24/7 operation*
- Up to 3x longer lifetime*

MASTER LEDtube T5

- 50,000 hours lifetime
- Up to 155 lumen/Watt
- Up to 5600 lumen output

MASTER LEDtube T8 sensor

- Integrated motion sensor
- Automatic dimming based on movement
- No extra sensors or wiring needed
- Up to 70% energy saving*

NEW CorePro LED PL-C, PL-L, PL-S & LED Circular

- Simple retrofit for fluorescent PL-C and PL-L lamps
- 30,000 hours lifetime
- Up to 60% energy saving*

*Compared to fluorescent lamps

LED tubes

T8 Universal

www.philips.com/ledtube




Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
1 MASTER VALUES LEDtube T8 Ultra Output Universal												
MAS LEDtube VLE UN 1200mm UO 16W830 T8	36	16	2300	144	240	⊗	83	3000	50000	A++	929002333002	99739171
MAS LEDtube VLE UN 1200mm UO 16W840 T8		16	2500	156	240	⊗	83	4000	50000	A++	929002333102	99739195
MAS LEDtube VLE UN 1200mm UO 16W865 T8		16	2500	156	240	⊗	83	6500	50000	A++	929002333202	99739218
MAS LEDtube VLE UN 1500mm UO 24W830 T8	58	24	3400	142	240	⊗	83	3000	50000	A++	929002333302	99739232
MAS LEDtube VLE UN 1500mm UO 24W840 T8		24	3700	154	240	⊗	83	4000	50000	A++	929002333402	99739256
MAS LEDtube VLE UN 1500mm UO 24W865 T8		24	3700	154	240	⊗	83	6500	50000	A++	929002333502	99739270
2 CorePro LEDtube T8 High Output Universal												
CorePro LEDtube UN 600mm HO 8W830 T8 ■	18	8	850	106	240	●	80	3000	30000	A+	929002419802	99782771
CorePro LEDtube UN 600mm HO 8W840 T8 ■		8	900	113	240	●	80	4000	30000	A+	929002419902	99782795
CorePro LEDtube UN 600mm HO 8W865 T8 ■		8	900	113	240	●	80	6500	30000	A+	929002420002	99782818
CorePro LEDtube UN 1200mm HO 18W830 T8	36	18	1850	103	240	⊗	80	3000	30000	A+	929001869202	96801666
CorePro LEDtube UN 1200mm HO 18W840 T8		18	2000	111	240	⊗	80	4000	30000	A+	929001869302	96801680
CorePro LEDtube UN 1200mm HO 18W865 T8		18	2000	111	240	⊗	80	6500	30000	A+	929001869402	96801703
CorePro LEDtube UN 1500mm HO 23W830 T8	58	23	2500	109	240	⊗	80	3000	30000	A+	929001869502	96801727
CorePro LEDtube UN 1500mm HO 23W840 T8		23	2700	117	240	⊗	80	4000	30000	A+	929001869602	96801741
CorePro LEDtube UN 1500mm HO 23W865 T8		23	2700	117	240	⊗	80	6500	30000	A+	929001869702	96801765

*) "UE" stands for Ultra Efficiency. These LED tubes are identical to the Ultra Output range but have a much higher efficiency (172 Lm / W)

■ Expected September 2020

LED tubes

T8 EM/MAIN



Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
1 MASTER LEDtube T8 Sensor												
MAS LEDtube Sensor 1200mm HO 16.5W840 T8	36	16.5	2100	127	240	☉	83	4000	50000	A++	929001878502	96806029
MAS LEDtube Sensor 1200mm HO 16.5W865 T8		16.5	2100	127	240	☉	83	6500	50000	A++	929001878602	96806043
MAS LEDtube Sensor 1500mm HO 24W840 T8	58	24	3100	129	240	☉	83	4000	50000	A++	929001878702	96806067
MAS LEDtube Sensor 1500mm HO 24W865 T8		24	3100	129	240	☉	83	6500	50000	A++	929001878802	96806081
2 MASTER LEDtube T8 FOOD												
MAS LEDtube 900mm 8.5W833 T8 Food	30	8.5	750	88	160	☒	83	3300	50000	A+	929001812102	96763919
MAS LEDtube 1200mm 12W833 T8 Food	36	12	1000	83	160	☒	83	3300	50000	A+	929001812202	96763933
MAS LEDtube 1500mm 20W833 T8 Food	58	20	1680	84	160	☒	83	3300	50000	A+	929001812302	96763957
3 MASTER LEDtube T8 High Output												
MAS LEDtube 600mm HO 8W830 T8	18	8	1000	125	160	☒	83	3000	50000	A++	929001307002	96697474
MAS LEDtube 600mm HO 8W840 T8		8	1050	131	160	☒	83	4000	50000	A++	929001307102	96697498
MAS LEDtube 600mm HO 8W865 T8		8	1050	131	160	☒	83	6500	50000	A++	929001307202	96697511
MAS LEDtube 1200mm HO 12.5W 830 T8	36	12.5	2000	160	160	☒	83	3000	60000	A++	929001922602	99592356
MAS LEDtube 1200mm HO 12.5W 840 T8		12.5	2100	168	160	☒	83	4000	60000	A++	929001922702	99592370
MAS LEDtube 1200mm HO 12.5W 865 T8		12.5	2100	168	160	☒	83	6500	60000	A++	929001922802	99592394
MAS LEDtube 1500mm HO 18.2W 830 T8	58	18.2	2900	159	160	☒	83	3000	60000	A++	929001922902	99592417
MAS LEDtube 1500mm HO 18.2W 840 T8		18.2	3100	170	160	☒	83	4000	60000	A++	929001923002	99592431
MAS LEDtube 1500mm HO 18.2W 865 T8		18.2	3100	170	160	☒	83	6500	60000	A++	929001923102	99592455
MASTER LEDtube 1800mm 25W 840 T8 ROT	/	25	3700	148	160	☒	83	4000	40000	A++	929001161102	96480373
4 MASTER VALUE LEDtube T8 High Output												
MAS LEDtube VLE 600mm HO 8W 830 T8	18	8	1000	125	240	☒	83	3000	50000	A++	929002021102	99646790
MAS LEDtube VLE 600mm HO 8W 840 T8		8	1050	131	240	☒	83	4000	50000	A++	929002021202	99646813
MAS LEDtube VLE 600mm HO 8W 865 T8		8	1050	131	240	☒	83	6500	50000	A++	929002021302	99646837
MAS LEDtube VLE 1200mm HO 14W 830 T8	36	14	2000	143	240	☒	83	3000	50000	A++	929002021402	99646851
MAS LEDtube VLE 1200mm HO 14W 840 T8		14	2100	150	240	☒	83	4000	50000	A++	929002021502	99646875

Expected September 2020


T8 EM/MAIN – Continued



Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
4 MASTER VALUE LEDtube T8 High Output												
MAS LEDtube VLE 1200mm HO 14W 865 T8	36	14	2100	150	240	✗	83	6500	50000	A++	929002021602	99646899
MAS LEDtube VLE 1500mm HO 20.5W 830 T8		20.5	2900	141	240	✗	83	3000	50000	A++	929002021702	99646912
MAS LEDtube VLE 1500mm HO 20.5W 840 T8	58	20.5	3100	151	240	✗	83	4000	50000	A++	929002021802	99646936
MAS LEDtube VLE 1500mm HO 20.5W 865 T8		20.5	3100	151	240	✗	83	6500	50000	A++	929002021902	99646950
4 MASTER VALUE LEDtube Ultra Output T8												
MAS LEDtube VLE 1200mm UO 16W 830 T8	36	16	2300	144	240	✗	83	3000	50000	A++	929002022002	99646974
MAS LEDtube VLE 1200mm UO 16W 840 T8		16	2500	156	240	✗	83	4000	50000	A++	929002022102	99646998
MAS LEDtube VLE 1200mm UO 16W 865 T8		16	2500	156	240	✗	83	6500	50000	A++	929002022202	99647018
MAS LEDtube VLE 1500mm UO 24W 830 T8	58	24	3400	142	240	✗	83	3000	50000	A++	929002022302	99647032
MAS LEDtube VLE 1500mm UO 24W 840 T8		24	3700	154	240	✗	83	4000	50000	A++	929002022402	99647056
MAS LEDtube VLE 1500mm UO 24W 865 T8		24	3700	154	240	✗	83	6500	50000	A++	929002022502	99647070
5 MASTER LEDtube Ultra Output T8												
MAS LEDtube 1200mm UO 15.5W 830 T8	36	15.5	2300	148	160	✗	83	3000	60000	A++	929002020502	99647216
MAS LEDtube 1200mm UO 15.5W 840 T8		15.5	2500	161	160	✗	83	4000	60000	A++	929002020602	99647230
MAS LEDtube 1200mm UO 15.5W 865 T8		15.5	2500	161	160	✗	83	6500	60000	A++	929002020702	99647254
MAS LEDtube 1500mm UO 23W 830 T8	58	23	3400	148	160	✗	83	3000	60000	A++	929002020802	99647278
MAS LEDtube 1500mm UO 23W 840 T8		23	3700	161	160	✗	83	4000	60000	A++	929002020902	99647292
MAS LEDtube 1500mm UO 23W 865 T8		23	3700	161	160	✗	83	6500	60000	A++	929002021002	99647315
6 MASTER LEDtube T8 Ultra Efficiency												
MAS LEDtube 1200mm UE 14.5W 840 T8	36	14.5	2500	172	160	✗	83	4000	70000	A++	929001376802	96731505
MAS LEDtube 1200mm UE 14.5W 865 T8		14.5	2500	172	160	✗	83	6500	70000	A++	929001376902	96731529
MAS LEDtube 1500mm UE 21.5W 840 T8	58	21.5	3700	172	160	✗	83	4000	70000	A++	929001377002	96731543
MAS LEDtube 1500mm UE 21.5W 865 T8		21.5	3700	172	160	✗	83	6500	70000	A++	929001377102	96731567


LED tubes

T8 EM/MAIN – Continued



Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
7 CorePro LEDtube T8												
CorePro LEDtube 600mm 8W840	18	8	800	100	240	✗	80	4000	30000	A+	929001338602	96711033
CorePro LEDtube 600mm 8W865		8	800	100	240	✗	80	6500	30000	A+	929001338702	96711057
CorePro LEDtube 1200mm 14.5W840	36	14.5	1600	110	240	✗	80	4000	30000	A+	929001338802	96711071
CorePro LEDtube 1200mm 14.5W865		14.5	1600	110	240	✗	80	6500	30000	A+	929001338902	96711095
CorePro LEDtube 1500mm 20W 840	58	20	2200	110	240	✗	80	4000	30000	A+	929001337902	96710913
CorePro LEDtube 1500mm 20W 865		20	2200	110	240	✗	80	6500	30000	A+	929001338002	96710951

HF T8



Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
1 MASTER LEDtube HF T8												
MAS LEDtube HF 600mm HO 8W830 T8	18	8	1000	125	160	✗	83	3000	60000	A+	929001393102	96743539
MAS LEDtube HF 600mm HO 8W840 T8		8	1050	131	160	✗	83	4000	60000	A+	929001393202	96743553
MAS LEDtube HF 600mm HO 8W865 T8		8	1050	131	160	✗	83	6500	60000	A+	929001393302	96743676
MAS LEDtube HF 1200mm HO 14W830 T8	36	14	2000	143	160	●	83	3000	60000	A+	929001284302	96687529
MAS LEDtube HF 1200mm HO 14W840 T8		14	2100	150	160	●	83	4000	60000	A++	929001284102	96687482
MAS LEDtube HF 1200mm HO 14W865 T8		14	2100	150	160	●	83	6500	60000	A++	929001284202	96687505

Please always check before the ballast compatibility list for all HF Instant Fit Ledtube applications

HF T8 – Continued



1



2

= Dimmable

= Non-dimmable




Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
1 MASTER LEDtube HF T8												
MAS LEDtube HF 1500mm HO 20W830 T8	58	20	2900	145	160		83	3000	60000	A+	929001284602	96687581
MAS LEDtube HF 1500mm HO 20W840 T8		20	3100	155	160		83	4000	60000	A++	929001284402	96687543
MAS LEDtube HF 1500mm HO 20W865 T8		20	3100	155	160		83	6500	60000	A++	929001284502	96687567
1 MASTER LEDtube HF T8 Ultra Output												
MAS LEDtube HF 1200mm UO 16W830 T8	36	16	2350	147	160		83	3000	60000	A+	929001300202	96688007
MAS LEDtube HF 1200mm UO 16W840 T8		16	2500	156	160		83	4000	60000	A++	929001300002	96687963
MAS LEDtube HF 1200mm UO 16W865 T8		16	2500	156	160		83	6500	60000	A++	929001300102	96687987
MAS LEDtube HF 1500mm UO 24W830 T8	58	24	3500	146	160		83	3000	60000	A++	929001300502	96688069
MAS LEDtube HF 1500mm UO 24W840 T8		24	3700	154	160		83	4000	60000	A++	929001300302	96688021
MAS LEDtube HF 1500mm UO 24W865 T8		24	3700	154	160		83	6500	60000	A++	929001300402	96688045
2 CorePro LEDtube HF T8												
CorePro LEDtube HF 600mm 9W840 T8 G	18	9	800	89	240		83	4000	30000	A	929001249502	96652176
CorePro LEDtube HF 600mm 9W865 T8 G		9	800	89	240		83	6500	30000	A	929001249602	96652190

Please always check before the ballast compatibility list for all HF Instant Fit Ledtube applications

LED tubes

HF T5





Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
1 MASTER LEDtube HF T5 High Efficiency												
MAS LEDtube HF 600mm HE 8W 830 T5	14	8	1000	125	160	✗	83	3000	50000	A+	929001390702	96743232
MAS LEDtube HF 600mm HE 8W 840 T5		8	1050	131	160	✗	83	4000	50000	A+	929001390802	96743256
MAS LEDtube HF 600mm HE 8W 865 T5		8	1050	131	160	✗	83	6500	50000	A+	929001390902	96743270
MAS LEDtube HF 1200mm HE 16.5W 830 T5	28	17	2300	139	160	✗	83	3000	50000	A+	929001391002	96743294
MAS LEDtube HF 1200mm HE 16.5W 840 T5		17	2500	152	160	✗	83	4000	50000	A++	929001391102	96743317
MAS LEDtube HF 1200mm HE 16.5W 865 T5		17	2500	152	160	✗	83	6500	50000	A++	929001391202	96743331
MAS LEDtube HF 1500mm HE 20W 830 T5	35	20	2800	140	160	✗	83	3000	50000	A+	929001391302	96743355
MAS LEDtube HF 1500mm HE 20W 840 T5		20	3000	150	160	✗	83	4000	50000	A++	929001391402	96743379
MAS LEDtube HF 1500mm HE 20W 865 T5		20	3000	150	160	✗	83	6500	50000	A++	929001391502	96743393
2 MASTER LEDtube HF T5 High Output												
MAS LEDtube HF 1500mm HO 26W 830 T5	49	26	3700	142	160	●	83	3000	50000	A+	929001296102	96685525
MAS LEDtube HF 1500mm HO 26W 840 T5		26	3900	150	160	●	83	4000	50000	A++	929001296202	96685549
MAS LEDtube HF 1500mm HO 26W 865 T5		26	3900	150	160	●	83	6500	50000	A++	929001296302	96685563
MAS LEDtube HF 1500mm HO 26W 830 T5 G ■		26	3700	142	160	✗	83	3000	50000	-	929002352302	99749576
MAS LEDtube HF 1500mm HO 26W 840 T5 G ■		26	3900	150	160	✗	83	4000	50000	-	929002352402	99749590
MAS LEDtube HF 1500mm HO 26W 865 T5 G ■		26	3900	150	160	✗	83	6500	50000	-	929002352502	99749613
MAS LEDtube HF 1200mm HO 26W 830 T5	54	26	3700	142	160	✗	83	3000	50000	A+	929001338302	96705278
MAS LEDtube HF 1200mm HO 26W 840 T5		26	3900	150	160	✗	83	4000	50000	A++	929001338402	96705292
MAS LEDtube HF 1200mm HO 26W 865 T5		26	3900	150	160	✗	83	6500	50000	A++	929001338502	96705315
MAS LEDtube HF 1200mm HO 26W 830 T5 G ■		26	3700	142	160	✗	83	3000	50000	-	929002352002	99749514
MAS LEDtube HF 1200mm HO 26W 840 T5 G ■		26	3900	150	160	✗	83	4000	50000	-	929002352102	99749538
MAS LEDtube HF 1200mm HO 26W 865 T5 G ■		26	3900	150	160	✗	83	6500	50000	-	929002352202	99749552

Please always check before the ballast compatibility list for all HF Instant Fit Ledtube applications

■ Expected September 2020

HF T5 – Continued



Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
3 MASTER LEDtube HF T5 Ultra Output												
MAS LEDtube HF 1500mm UO 36W 830 T5	80	36	5200	144	160	⊗	83	3000	50000	A++	929001346102	96705995
MAS LEDtube HF 1500mm UO 36W 840 T5		36	5600	156	160	⊗	83	4000	50000	A++	929001346202	96706039
MAS LEDtube HF 1500mm UO 36W 865 T5		36	5600	156	160	⊗	83	6500	50000	A++	929001346302	96706053

Please always check before the ballast compatibility list for all HF Instant Fit Ledtube applications

LED tubes

T5 EM/MAINS



MAS LEDtube
EM/Mains T5 HO

= Dimmable

= Non-dimmable



G13

10 PACK

Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
1 MASTER LEDtube EM/Mains T5 High Output												
MAS LEDtube 1500mm HO 26W 830 T5	49	26	3600	138	200		80	3000	50000	A++	929001908802	96819296
MAS LEDtube 1500mm HO 26W 840 T5		26	3900	150	200		80	4000	50000	A++	929001908902	96819319
MAS LEDtube 1500mm HO 26W 865 T5		26	3900	150	200		80	6500	50000	A++	929001909002	96819333
MAS LEDtube 1200mm HO 26W 830 T5	54	26	3600	138	200		80	3000	50000	A++	929001908502	96819210
MAS LEDtube 1200mm HO 26W 840 T5		26	3900	150	200		80	4000	50000	A++	929001908602	96819234
MAS LEDtube 1200mm HO 26W 865 T5		26	3900	150	200		80	6500	50000	A++	929001908702	96819258
MASTER LEDtube EM/Mains T5 High Efficiency												
MAS LEDtube 600mm HE 8W 830 T5 ■	14	8	1000	125	TBC		83	3000	50000	-	929002420608	99783433
MAS LEDtube 600mm HE 8W 840 T5 ■		8	1050	131	TBC		83	4000	50000	-	929002420708	99783457
MAS LEDtube 600mm HE 8W 865 T5 ■		8	1050	131	TBC		83	6500	50000	-	929002420808	99783471
MAS LEDtube 1200mm HE 16.5W 830 T5 ■	28	16.5	2300	139	TBC		83	3000	50000	-	929002420908	99783495
MAS LEDtube 1200mm HE 16.5W 840 T5 ■		16.5	2500	152	TBC		83	4000	50000	-	929002421008	99783518
MAS LEDtube 1200mm HE 16.5W 865 T5 ■		16.5	2500	152	TBC		83	6500	50000	-	929002421108	99783532
MAS LEDtube 1500mm HE 20W 830 T5 ■	35	20	2800	140	TBC		83	3000	50000	-	929002421208	99783556
MAS LEDtube 1500mm HE 20W 840 T5 ■		20	3000	150	TBC		83	4000	50000	-	929002421308	99783570
MAS LEDtube 1500mm HE 20W 865 T5 ■		20	3000	150	TBC		83	6500	50000	-	929002421408	99783594

■ Expected September 2020

LED tubes and PL-lamps

LED starter



LED Starter



40 PACK


Product Type	12 NC	EOC code
MASTER LEDtube Starter EMP GenII OP	929001801432	96819654

LED PL-C




CorePro LED PL-C / 2-pins

1



CorePro LED PL-C / 4-pins

2



= Dimmable



= Non-dimmable

Improved light output



ROTATING END



G24d-1 / G24d-2 / G24d-3



10 PACK

Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
1 CorePro LED PLC 2 pin												
CorePro LED PLC 4.5W 830 2P G24d-1	13	4.5	475	106	-	✗	83	3000	30000	A++	929001350702	96706596
CorePro LED PLC 4.5W 840 2P G24d-1		4.5	500	111	-	✗	83	4000	30000	A++	929001350802	96706619
CorePro LED PLC 6.5W 830 2P G24d-2	18	6.5	650	100	-	✗	83	3000	30000	A+	929001201402	96541272
CorePro LED PLC 6.5W 840 2P G24d-2		6.5	700	108	-	✗	83	4000	30000	A+	929001201502	96541296
CorePro LED PLC 8.5W 830 2P G24d-3	26	8.5	950	112	-	✗	83	3000	30000	A+	929001201202	96541234
CorePro LED PLC 8.5W 840 2P G24d-3		8.5	1000	118	-	✗	83	4000	30000	A+	929001201302	96541258
2 CorePro LED PLC 4 pin												
CorePro LED PLC 4.5W 830 4P G24q-1	13	4.5	475	106	-	✗	83	3000	30000	A+	929001351002	96706633
CorePro LED PLC 4.5W 840 4P G24q-1		4.5	500	111	-	✗	83	4000	30000	A+	929001351102	96706657
CorePro LED PLC 6.5W 830 4P G24q-2	18	6.5	650	100	-	✗	83	3000	30000	A+	929001201002	96541197
CorePro LED PLC 6.5W 840 4P G24q-2		6.5	700	108	-	✗	83	4000	30000	A+	929001201102	96541210
CorePro LED PLC 9W 830 4P G24q-3	26	9	950	106	-	✗	83	3000	30000	A+	929001200802	96541159
CorePro LED PLC 9W 840 4P G24q-3		9	1000	111	-	✗	83	4000	30000	A+	929001200902	96541173

LED tubes and PL-lamps

LED PL-L



CorePro LED PL-L

= Dimmable

= Non-dimmable



ROTATING END



2G11



10 PACK

Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
CorePro LED PLL HF 16.5W 830 4P 2G11	36	16.5	2000	121	-		83	3000	30000	A+	929001381502	96739662
CorePro LED PLL HF 16.5W 840 4P 2G11		16.5	2100	127	-		83	4000	30000	A+	929001381602	96739747
CorePro LED PLL HF 16.5W 865 4P 2G11		16.5	2100	127	-		83	6500	30000	A+	929001381702	96739761
CorePro LED PLL HF 24W 830 4P 2G11	55	24	3200	133	160		83	3000	30000	A+	929001920402	96828397
CorePro LED PLL HF 24W 840 4P 2G11		24	3400	142	160		83	4000	30000	A+	929001920502	96828410
CorePro LED PLL HF 24W 865 4P 2G11		24	3400	142	160		83	6500	30000	A+	929001920602	96828434

LED PL-S



CorePro LED PL-S

= Dimmable

= Non-dimmable



ROTATING END



PL-S



20 PACK

Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
CorePro LED PLS 5W 830 2P G23	11	5	520	104	120		82	3000	30000	A+	929001926302	99596668
CorePro LED PLS 5W 840 2P G23		5	550	110	120		82	4000	30000	A+	929001926402	99596682

CorePro LED Circular



CorePro LED Circular

= Dimmable

= Non-dimmable



G10q



20 PACK

Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	Dimmable	CRI	Colour Temp	Lifetime	EEL	12 NC	EOC code
	W	W	lm	lm/W	°			K	Hrs.			
Circular												
CorePro LED Circular 20W 840 G10q	32	20	2100	105	120		80	4000	30000	A+	929002068002	99660420
CorePro LED Circular 20W 865 G10q		20	2100	105	120		80	6500	30000	A+	929002068102	99660444