

**PHILIPS**

LED lighting

**REAL  
PROs  
REAL  
QUALITY**

# Professional LED lighting catalog

Discover our wide portfolio of innovative and efficient LED lamps and luminaires for both indoor and outdoor application areas.

New generation of energy saving A-class LED lamps, tubes and strips, CoreLine projectors and wall-mounted luminaires, and Ledinaire floodlights



May  
2022

# A light for every need

Welcome to this comprehensive overview of Philips' professional LED portfolio. Lamps, luminaires, handy overviews and time-saving tools – here you'll find everything you need, whatever your project demands.

## Choose Philips LED lighting for:

### The best products

- We're setting new standards for high-quality products that result in less maintenance, fewer technical hiccups and strengthens your reputation as a reliable lighting expert.
- Our products are designed with easy installation in mind, saving you time and money.
- From connected lighting solutions to 3D printed luminaires – with Philips you get LED lighting that's setting the reference in the industry and that keeps you ahead of the competition.

### The widest portfolio

Whatever the need, whatever the budget: with our complete portfolio of LED lighting products you'll always have the right solution at hand.







Signify, previously known as Philips Lighting, is the world leader in connected LED lighting systems, software and services. We proudly market the best lighting brands in the world, including Philips and Interact.

## PHILIPS

The Philips brand stands for quality and energy-efficiency in light. For over 125 years, Philips products have been at the forefront of innovation. Today Philips is recognized as the leading brand in lighting.

## interact

Interact is the brand of our IoT software and platform that manages smart lighting systems and the data that those systems collect. Smart, simple and scalable, Interact software can be used in a wide range of application areas, from small offices to entire cities.

### You and Signify – a reliable partnership

Close cooperation before, during and after projects is important to us. Our local service teams make sure you always get the competent support and information you need.

We are closely working with local wholesalers to offer you flexible and on-time delivery – and product availability you can rely on.

To help you stay on top of your game the [Signify Lighting Academy](#) offers a comprehensive range of educational resources for you to grow your expertise and get certified.

### Brighter lives, better world

Signify is 100% carbon neutral since September 2020.

We recycle up to 90% of our manufacturing waste.

We use 100% renewable electricity.

Our paper packaging for LED lamps and luminaires is saving over 500,000 kilos of plastic waste per year.

**Thank you for choosing Philips products offered by Signify and joining us on our mission!**

# Two new regulations for more sustainability



What you need to know about the EU's Ecodesign Regulation (SLR) and Energy Labelling Regulation (ELR)


In September 2021, the EU implemented two updated regulations, both with the goal of further expanding the lighting industry's lead in sustainability by delivering significant energy savings for lighting products and systems.

## The Ecodesign Regulation – improving product performance

- Optimizing the design of light sources and separate control gear for more sustainability and efficiency
- Products that fail to meet requirements will be phased out (e.g. T8 fluorescent lamps in 2023)
- Lighting installations will have to be renovated with new energy-efficient light sources

## The Energy Labelling Regulation – empowerment through information

- Introduced a new consumer-friendly energy label to empower end users to choose energy efficient products
- New scale reflects how efficient a product is – the definition of A to G has been changed based on the new efficacy requirements
- 'Containing Products' (products in which the light source, or separate control gears, can be replaced without damaging the product) do not need an energy label on the packaging. Most luminaires fall under this category.



Class	Lm/W
A	210
B	185
C	160
D	135
E	110
F	85
G	0

For more transparency, efficiency, sustainability – and a greener future.



# Real pros don't look – they find

A partner that understands the challenges you face, saves you time. Which is why we don't only offer a comprehensive portfolio of LED luminaires and lamps, but also a couple of handy online tools that make your life easier.



## **Product finder**

- Easily find the perfect LED lamp or luminaire for every budget and application demand

## **Installer hub**

- All latest product information
- Installation videos and training
- Links to all tools
- And more!

## **Total cost of ownership calculator**

- Calculate the total cost of your product in a few simple steps

# Contents

## 11

### Interact Ready

- 11 CoreLine Panel Office compliant
- 12 CoreLine Panel Non-office compliant
- 12 CoreLine Recessed Office compliant
- 13 CoreLine Surface-mounted Office compliant
- 13 CoreLine Waterproof
- 14 CoreLine Highbay Gen4
- 14 CoreLine Wall-mounted
- 15 MasterConnect LEDspot GU10
- 15 MasterConnect LEDtube EM/mains T8
- 16 Indoor Accessories

## 22

### CoreLine LED luminaires

- 22 CoreLine Panel Office compliant
- 23 CoreLine Panel Non-office compliant
- 24 CoreLine Recessed Office compliant
- 25 CoreLine Recessed Non-office compliant
- 26 CoreLine Surface-mounted Office compliant
- 27 CoreLine Surface-mounted Non-office compliant
- 28 CoreLine Batten
- 30 CoreLine Downlight
- 32 CoreLine SlimDownlight
- 33 CoreLine Waterproof
- 35 CoreLine Recessed Spot
- 37 CoreLine Trunking Gen2
- 39 CoreLine Highbay Gen4
- 40 CoreLine Value Highbay
- 41 CoreLine Projector gen2
- 42 CoreLine Wall-mounted
- 44 CoreLine tempo X-Large
- 45 CoreLine tempo large
- 46 CoreLine tempo medium
- 46 CoreLine tempo small
- 47 CoreLine Malaga LED

## 51

### Ledinaire LED luminaires

- 51 Ledinaire Panel Office compliant
- 51 Ledinaire Panel Non-office compliant
- 52 Ledinaire Recessed Non-office compliant
- 53 Ledinaire Surface-mounted Office compliant
- 53 Ledinaire Surface-mounted Non-office compliant
- 54 Ledinaire Wall-mounted WL060V
- 54 Ledinaire Wall-mounted WL070V
- 55 Ledinaire Square Wall-mounted
- 55 Ledinaire Batten
- 56 Ledinaire High-bay
- 57 Ledinaire Waterproof
- 58 Ledinaire Waterproof Tube Housing
- 58 Ledinaire SlimDownlight DN065B
- 59 Ledinaire Recessed Downlight
- 59 Ledinaire Zadora LED
- 60 Ledinaire ClearAccent RS060/RS061
- 61 Ledinaire floodlights gen3





# Contents

## 68

### LED spots

- 68 SceneSwitch LEDspot
- 69 MASTER LEDspot ExpertColor LV
- 70 MASTER LEDspot ExpertColor MV
- 71 MASTER LEDspot ExpertColor AR111
- 72 MASTER VALUE LEDspot LV
- 73 MASTER VALUE LEDspot MV
- 74 MASTER LEDspot LV
- 75 MASTER LEDspot PAR
- 75 CorePro LEDspot PAR
- 76 CorePro LEDspot Reflectors
- 77 CorePro LEDspot LV
- 78 CorePro LEDspot MV
- 79 CorePro LEDspot AR111
- 80 CorePro LEDcapsule LV
- 81 CorePro LEDcapsule MV
- 82 CorePro LEDlinear MV

## 83

### LED bulbs

- 83 SceneSwitch LEDbulbs
- 83 Premium LED bulbs SceneSwitch
- 84 UltraEfficient LED bulb
- 84 Classic filament LEDbulbs
- 85 CorePro LEDbulbs
- 87 CorePro Glass LED bulbs
- 89 CorePro Glass High Lumen bulbs
- 89 CorePro Plastic LED Specialties
- 90 MASTER Glass LED bulbs
- 90 MASTER Plastic LEDbulbs
- 91 MASTER Value Decorative LED bulbs
- 92 MASTER Value GLASS LED bulbs

## 94

### LED candles & lusters

- 94 Candle LED
- 94 SceneSwitch LEDbulbs
- 95 CorePro GLASS LED candles and lusters
- 97 CorePro Plastic LEDcandles & lusters
- 98 CorePro Plastic LED Specialties
- 98 MASTER Value Decorative LED candles and lusters
- 99 MASTER Value GLASS LED candles and lusters
- 101 MASTER Plastic LEDcandles & lusters

## 106

### LED tubes

- 106 MASTER LEDtube EM/Mains T8
- 107 MASTER Value LEDtube T8
- 107 MASTER Value LEDtube Universal T8
- 108 MASTER LEDtube InstantFit HF T8
- 109 MASTER LEDtube InstantFit HF T5
- 110 MASTER LEDtube Mains T5
- 111 CorePro LEDtube EM/Mains T8
- 111 CorePro LED tube Universal T8

## 112

### LED PL-lamps

- 112 CorePro LED PLC 2P
- 112 CorePro LED PLC 4P
- 113 CorePro LED PLC
- 113 CorePro LED PLS
- 114 CorePro LED PLL

## 119

### TrueForce LED

- 119 Trueforce Core LED SON-T
- 119 TrueForce LED Industrial and Retail (Highbay – MH)
- 120 TrueForce LED Public (Urban/Road – HPL/SON)
- 121 Trueforce CorePro LED HPL
- 122 TrueForce Core LED Industrial and Retail (Highbay – HPI/SON/HPL)
- 122 TrueForce LED Public (Road/Area – SOX)
- 123 TrueForce LED Public (Road – SON)

# Philips Interact Ready

interact  
ready.



Office



Industry



Parking



Retail

Components



CoreLine recessed



CoreLine downlight



CoreLine highbay



CoreLine trunking



CoreLine waterproof



CoreLine slim  
downlight



RF-DALI connector kit



CoreLine surface-mounted



MasterConnect LEDspot



CoreLine waterproof



CoreLine  
wall-mounted



Wireless sensors



CoreLine panel



MasterConnect LEDtube



Wireless switches

Contents

Interact  
Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles  
& lusters

LED tubes

LED  
PL-lamps

TrueForce





# Turn on a game-changer

Discover your possibilities with smart lighting for smart businesses

Many business owners will go the extra mile to get the very best out of their most important assets – their people. The working environment has a direct impact on their morale and productivity. There are many ways to achieve a better workplace – and one of them is through the right lighting.

## Why upgrade to connected lighting?

Connected lighting means that LED lights with integrated sensors are connected to application software. As a result, it's possible to automate and optimize light settings for different areas within the building, allow users to personalize light settings and business owners to collect anonymized data on energy and cost performance. The possibilities of lighting automation boost energy savings and help your customers meet their sustainability targets.

The new Interact Pro system is the cost-efficient and wireless solution for every step of your SME customer's smart lighting journey. It includes three tiers that each provide the best solution for your customer's current need – and is also fully scalable so it can simply be upgraded when business requirements change, from smart to super-smart.

It seamlessly works with our Interact Ready luminaires and lamps which offer a direct point-for-point replacement of conventional lights.

## How the connected lighting system comes together

interact ready. lighting available from

**PHILIPS**



Smart luminaires

Smart lamps

Smart sensors

Smart wall-switches

Works with

The Interact Pro system

interact

**Step 1:**  
Start simple and lay the foundation




Just light points and an app!

**Step 2:**  
Scale up for more benefits by adding a gateway



Profit from cloud-based benefits and functionality.

**Step 3:**  
Tap the full potential of the IoT



Invaluable data helps make full use of the power of IoT.

Training and certification required

[philips.com/interact-ready](http://philips.com/interact-ready)

Turn to the next page for more details on the tiers of the system

Contents

Interact Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles & lusters

LED tubes

LED PL-lamps

TrueForce



# interact

## From smart to super-smart

The Interact Pro system always provides the best solution for your customer's needs thanks to its three tiers that can easily be upgraded by adding new hardware or software. As the system grows, you can keep and build on all previously installed light points.

### Step 1: Start simple and lay the foundation

- Install smart luminaires and lamps that contain an occupancy or daylight sensor.
- Simply connect the Philips Interact Ready luminaires and lamps with the intuitive Interact Pro app through a Bluetooth connection.
- Add sensors, switches or connector blocks for 3rd party light sources.
- Set-up is simple and straightforward: no need for additional wiring or access to the building's internet connection.
- Reduce wiring, commissioning and building modification, saving up to 80% on installation and material cost compared with more complex systems.
- Save up to 75% energy thanks to the granular dimming feature that lets sensors automatically adjust lighting to occupancy patterns and natural light levels.



<sup>1</sup>Vs legacy systems based on installer interviews. Savings calculated for a project of 100 luminaires: 10% labor, 35% materials, 35% commissioning cost.

### Step 2: Scale up for more benefits by adding a gateway


- Get access to cloud-based benefits and functionality, including regular feature updates.
- Create light schedules and easily manage light scenes via smartphone for user comfort and energy savings
- Multiple user devices can connect to the gateway to change light settings and schedules (mobile & desktop)
- Get remote access to real time lighting usage, energy consumption and scene adaptation for improved business operations
- Dashboard with lifetime and health of installed light points for efficient post-installation service, insurance of correctly running system and avoidance of system outages.
- Get a clear overview of all installed projects and users.



### Step 3: Tap the full potential of the IoT


Training and certification required

- Get access to occupancy, asset health and environmental sensing data.
- Optimize workspace quality, improve safety and productivity and boost employee engagement – even across multi-sites.
- Unlock more savings and link to other IoT applications with BMS integration.
- Minimize waste with real time way-finding and desk/room booking tools.



<sup>2</sup>By upgrading to LED with advanced lighting controls. Source: Building Energy Exchange 2017

### System building blocks:



The Interact system and software works seamlessly with all Philips Interact Ready products




# Interact Ready

Now that more and more products are being connected to the internet, they are becoming smarter. This provides more flexibility, saves extra costs and offers more comfort. This means there is an opportunity for the installation sector to be part of the smart lighting on the internet, to offer a better experience for the end user. So far, small and medium-sized enterprises (SMEs) have remained excluded from these developments, but that is now a thing of the past. The luminaires and lamps from the list below are the first Interact Ready LED products and work seamlessly with the intuitive Interact Pro app and dashboard.

## CoreLine Panel Office compliant

[www.philips.com/interact-ready](http://www.philips.com/interact-ready)





Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W		K			
RC132V G4 LED34S/830 WIA W60L60 OC	29	3400	117	-	3000	19	910505101188	97589000
RC132V G4 LED34S/830 WIA W60L60 OC W3	29	3400	117	-	3000	19	910505101294	97602600
RC132V G4 LED36/840 WIA W60L60 OC TP(a)	29	3600	123	Wireless	4000	19	910505101298	97606400
RC132V G4 LED36S/840 WIA W30L120 OC	29	3600	123	-	4000	19	910505101283	97591300
RC132V G4 LED36S/840 WIA W30L120 OC W3	29	3600	123	-	4000	19	910505101296	97604000
RC132V G4 LED36S/840 WIA W60L60 OC	29	3600	123	-	4000	19	910505101187	97588300
RC132V G4 LED36S/840 WIA W60L60 OC W3	29	3600	123	-	4000	19	910505101293	97601900
RC132V G4 LED43S/840 WIA W60L60 OC	29	4300	125	-	4000	19	910505101287	97595100
RC133V G4 LED36S/840 WIA W62L62 OC	29	3600	123	Wireless	4000	19	910505101286	97594400
RC132V G4 LED43S/840 WIA W60L60 OC W3	34.5	4300	125	-	4000	19	910505101290	97598200
RC133V G4 LED43S/840 WIA W62L62 OC	34.5	4300	125	Wireless	4000	19	910505101288	97596800

# Interact Ready

CoreLine Panel Non-office compliant


[www.philips.com/interact-ready](http://www.philips.com/interact-ready)



Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W		K			
1 RC132V G4 LED34S/830 WIA W60L60 NOC	29	3400	117	-	3000	23	910505101186	97587600
1 RC132V G4 LED34S/830 WIA W60L60 NOC W3	29	3400	117	-	3000	23	910505101292	97600200
2 RC132V G4 LED36S/840 WIA W30L120 NOC	29	3600	123	-	4000	23	910505101189	97590600
2 RC132V G4 LED36S/840 WIA W30L120 NOC W3	29	3600	123	-	4000	23	910505101295	97603300
1 RC132V G4 LED36S/840 WIA W60L60 NOC	29	3600	123	-	4000	23	910505101278	97586900
1 RC132V G4 LED36S/840 WIA W60L60 NOC W3	29	3600	123	-	4000	23	910505101291	97599900
1 RC133V G4 LED34S/830 WIA W62L62 NOC	29	3400	117	Wireless	3000	23	910505101285	97593700
1 RC133V G4 LED36S/840 WIA W62L62 NOC	29	3600	123	Wireless	4000	23	910505101284	97592000
1 RC132V G4 LED43S/840 WIA W60L60 NOC	34.5	4300	125	-	4000	23	910505101289	97597500
1 RC132V G4 LED43S/840 WIA W60L60 NOC W3	34.5	4300	125	-	4000	23	910505101297	97605700

CoreLine Recessed Office compliant

[www.philips.com/interact-ready](http://www.philips.com/interact-ready)



	Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
		W	lm	lm/W		K			
NEW	RC136B 40S/830 WIA W60L60 OC	31	4000	135	InterAct Pro	3000	19	911401896681	51504800
NEW	RC136B 40S/830 WIA W60L60 OC W3	31	4000	135	InterAct Pro	3000	19	911401867482	53239700
NEW	RC136B 43S/840 WIA W30L120 OC	31	4300	140	InterAct Pro	4000	19	911401867382	53238000
NEW	RC136B 43S/840 WIA W30L120 OC W3	31	4300	140	InterAct Pro	4000	19	911401867682	53241000
NEW	RC136B 43S/840 WIA W60L60 OC	31	4300	140	Wireless	4000	19	911401896781	51505500
NEW	RC136B 43S/840 WIA W60L60 OC W3	31	4300	140	InterAct Pro	4000	19	911401867582	53240300

# Interact Ready

CoreLine Surface-mounted Office compliant

[www.philips.com/interact-ready](http://www.philips.com/interact-ready)



	Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
		W	lm	lm/W		K			
NEW	SM136V 40S/830 WIA W20L120 OC	31	4000	135	InterAct Pro	3000	19	911401896881	51506200
NEW	SM136V 40S/830 WIA W20L120 OC W3	31	4000	135	InterAct Pro	3000	19	911401867782	53242700
NEW	SM136V 40S/830 WIA W20L150 OC	31	4000	135	InterAct Pro	3000	19	911401897081	51508600
NEW	SM136V 43S/840 WIA W20L120 OC	31	4300	140	InterAct Pro	4000	19	911401896981	51507900
NEW	SM136V 43S/840 WIA W20L120 OC W3	31	4300	140	InterAct Pro	4000	19	911401867882	53243400
NEW	SM136V 43S/840 WIA W20L150 OC	31	4300	140	InterAct Pro	4000	19	911401897181	51509300

## CoreLine Waterproof

[www.philips.com/interact-ready](http://www.philips.com/interact-ready)



	Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	Integrated emergency 3 hours	12NC	EOC code
		W	lm	lm/W		K				
	WT120C G2 LED40S/840 WIA L1200	26	4000	154	Wireless	4000	25		910505101269	97576000
	WT120C G2 LED40S/840 WIA TW3 L1200	26	4000	154	Wireless	4000	25		910505101273	97580700
	WT120C G2 LED40S/840 WIA ELB3 L1200	29	4000	138	Wireless	4000	25	Yes	910505101270	97577700
	WT120C G2 LED65S/840 WIA L1500	45.5	6500	143	Wireless	4000	25		910505101271	97578400
	WT120C G2 LED65S/840 WIA TW3 L1500	45.5	6500	143	Wireless	4000	25		910505101274	97581400
	WT120C G2 LED65S/840 WIA ELB3 L1500	48.5	6500	134	Wireless	4000	25	Yes	910505101272	97579100
	WT120C G2 LED80S/840 WIA ELB3 L1500	63	8000	126.98	InterAct Pro	4000	25		910505103014	96535500

# Interact Ready

CoreLine Highbay Gen4

[www.philips.com/interact-ready](http://www.philips.com/interact-ready)



	Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
		W	lm	lm/W		K			
NEW	BY120P G4 LED100S/840 SRD NB H4	73	10.500	144	Yes	4000	22	911401507681	52704100
NEW	BY120P G4 LED100S/840 SRD WB H4	73	10.500	144	Wireless	4000	24	911401507881	52706500
NEW	BY121P G4 LED200S/840 SRD NB H4	145	20.500	140	Wireless	4000	22	911401507781	52705800
NEW	BY121P G4 LED200S/840 SRD WB H4	145	20.500	140	Wireless	4000	26	911401507981	52707200
NEW	BY122P G4 LED250S/840 SRD NB H4	183	25.500	139	Wireless	4000	22	911401531481	52703400
NEW	BY122P G4 LED250S/840 SRD WB H4	183	25.500	139	Wireless	4000	26	911401531581	52708900

CoreLine Wall-mounted

[www.philips.com/interact-ready](http://www.philips.com/interact-ready)



	Product Type	LED	Lumen Output	Efficiency	Beam Angle	Dimmable	Color Temp.	UGR	12NC	EOC code
		W	lm	lm/W	°		K			
NEW	WL140V LED20S/830 WIA WH	22	2100	95.45	120	InterAct office	3000	24	910505101546	97860000
NEW	WL140V LED20S/840 WIA WH	22	2200	100	120	InterAct office	4000	24	910505101547	97861700
NEW	WL140V LED34S/830 WIA WH	35.5	3350	94.36	120	InterAct office	3000	25	910505101548	97862400
NEW	WL140V LED34S/840 WIA WH	35.5	3400	95.77	120	InterAct office	4000	25	910505101549	97863100

# Interact Ready

MasterConnect LEDspot GU10

[www.philips.com/interact-ready](http://www.philips.com/interact-ready)



Product Type	LED	Lumen Output	Efficiency	Luminous Intensity	Beam Angle	Dimmable	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	cd	°			K	Hrs.					
MC LEDspot IA 4.7-50W GU10 927 36D	4.7	345	73.00	500	36	Wireless Dim	90	2700	25.000	50	100	F	929002253702	69392300
MC LEDspot IA 4.7-50W GU10 930 36D	4.7	345	73.00	500	36	Wireless Dim	90	3000	25.000	50	100	F	929002253802	69394700
MC LEDspot IA 4.7-50W GU10 940 36D	4.7	345	73.00	500	36	Wireless Dim	90	4000	25.000	50	100	F	929002253902	69396100

MasterConnect LEDtube EM/mains T8

[www.philips.com/interact-ready](http://www.philips.com/interact-ready)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Dimmable	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°			K	Hrs.					
MasterConnect LEDtube IA 600mm HO 7W840 T8	7	1050	150.00	160	Wireless Dim	83	4000	60.000	25.8	600	D	929002295302	71748300
MasterConnect LEDtube IA 600mm HO 7W865 T8	7	1050	150.00	160	Wireless Dim	83	6500	60.000	25.8	600	D	929002295402	71750600
MasterConnect LEDtube IA 1200mm UO 16W840 T8	16	2500	156.00	160	Wireless Dim	83	4000	60.000	25.8	1200	D	929002210402	66970600
MasterConnect LEDtube IA 1200mm UO 16W865 T8	16	2500	156.00	160	Wireless Dim	83	6500	60.000	25.8	1200	D	929002210502	66972000
MasterConnect LEDtube IA 1500mm UO 25W840 T8	25	3700	148.00	160	Wireless Dim	83	4000	60.000	25.8	1500	D	929002210802	66976800
MasterConnect LEDtube IA 1500mm UO 25W865 T8	25	3700	148.00	160	Wireless Dim	83	6500	60.000	25.8	1500	D	929002210902	66978200



# Interact Ready

Indoor Accessories

[www.philips.com/interact-ready](http://www.philips.com/interact-ready)



1/10/20/50 PACK

Product Type	Dimmable	12NC	EOC code
OCC SENSOR IA CM IP42 WH	Wireless	929001819002	77752700
OCC-DL SENSOR IA CM IP42 WH	Wireless	929001819102	77754100
Interact Ready RF DALI Connector	Wireless	913701047003	26616200
LCN1840/05 Interact Pro wireless gateway	Wireless	913701037703	77579000
LCN3110/05 OCC SENSOR IA CM IP65 WH	Wireless	913701043903	74542400
LCN3120/05 OCC-DL SENSOR IA CM IP65 WH	Wireless	913701044003	74545500
UID8480/10 ZGP Switch Dim 4B	Wireless	913701055803	27380100

# LED luminaires for every challenge

Finding the right luminaires for different plans, needs and budgets is easy with the extensive Philips portfolio. It ensures that you always have a quality solution at the price you want.



The CoreLine range offers a number of **Interact Ready luminaires**. They come with integrated wireless communications, fully compatible with gateways, sensors and software to set up a smart lighting system.

**Product highlights include:**

**CoreLine waterproof**


Easily install durable lighting in industry and parking applications.



**CoreLine recessed and surface-mounted**

Optimize lighting and energy savings in office, public and healthcare applications.

Click here for the full range of **Interact Ready CoreLine luminaires**



# Philips CoreLine

Performance



Office



Industry



Parking



Retail



Outdoor



CoreLine recessed



CoreLine highbay



CoreLine waterproof



CoreLine projector



CoreLine malaga



CoreLine surface-mounted



CoreLine waterproof



CoreLine wall-mounted



CoreLine recessed spot



CoreLine tempo



CoreLine panel



CoreLine trunking



CoreLine batten



CoreLine slim downlight



CoreLine bollard



CoreLine downlight



CoreLine batten

Contents

Interact Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles & lusters

LED tubes

LED PL-lamps

TrueForce



# Real pros bring lighting to new levels

The Philips CoreLine range is the reference for innovative good quality, easy-to-use lighting solutions for every project where light really matters

When lighting really matters, you want to offer your customers the absolute best in quality and choice. Philips CoreLine gives you all that and more with a full range of easy to install LED luminaires for every application and situation.

All CoreLine luminaires are easy to handle and install – which makes total sense, because the quicker you can finish an installation, the sooner you can move onto the next job. And more installations mean more turnover.

Selected CoreLine luminaires offer the MultiLumen or MultiColor feature, a choice of multiple lumen outputs or light colors in one single luminaire. Giving you more flexibility and choice on the

job. Also available within the range are Interact Ready luminaires with integrated wireless communications, fully compatible with gateways, sensors and software to set up a smart lighting system.

Enjoy more performance and variety with Philips CoreLine – the complete range of high quality LED lighting that's setting the reference in the market.



#### Innovative

CoreLine luminaires are the first Interact Ready LED luminaires and work seamlessly with the intuitive Interact Pro app and dashboard.



#### Easy-to-install

The efficient design of CoreLine LED luminaires enables replacement of existing lights, with no need for expensive re-wiring or new ceiling configurations.



#### High quality

At the heart of CoreLine's high-quality light is LED technology. Its long lifetime enables you to meet every demand and provide the best lighting solution.

Contents

Interact Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles & lusters

LED tubes

LED PL-lamps

TrueForce





# Philips CoreLine projector

The new Philips CoreLine projector: enjoy high-quality LED lighting with maximum flexibility and easy installation.

- New, even more compact design (ø 80 mm × 125 mm)
- Modern and minimalistic look in white or black finish ensures the projector blends in to many interior designs
- One to one replacement to conventional CDM-standard-based projectors
- Fits to most standard 3C tracks in the European market
- Robust metal housing and hinge
- Integrated driver
- Energy-efficient: 100–110 lm/W
- High color rendering (CRI 90)
- Color temperature 3000 or 4000 K
- 25 or 38 degree beam angle with 3000 lm light output

[Click here to see all products](#)



# Philips CoreLine wall-mounted

Product highlight

The new Philips CoreLine wall-mounted provides the kind of variety, performance and cost-saving durability hard-working lighting needs.

- Suitable for indoor and outdoor installation (UV-resistant)
- Optional integrated wireless motion detection (MDU) and emergency lighting (EL) module
- Optional external smart sensor that works with connected lighting systems (Interact Ready)
- Waterproof (IP65) and vandal-proof (IK10)
- Improved efficacy: up to 110 lm/W
- MultiColor/Lumen feature – warm and cool white light, as well as two lumen packages (1200-2000 lm or 2000-3400 lm) in one luminaire
- Slim and unobtrusive design with three color choices (White, Black, Grey)

[Click here to see all products](#)





# Designed with one thing in mind: you.

You know what really matters on the job. Fast and easy installation, right? You want to be in and out, quickly, efficiently and professionally. The CoreLine range has been designed to help you do exactly that.

## No tools, no nonsense

Making your life extra easy is the 3-phase push-in connector: simply detach, wire and re-connect with the luminaire. It comes with a through wiring option for more flexibility and can be found in CoreLine recessed spots, panels, recessed and surface-mounted luminaires and battens.

Other luminaires, such as the CoreLine projectors and highbays, have preassembled connectors, so installation is as quick and straightforward as plug and play.




Push-in connector

Preassembled connector



Lightweight and compact design



Optimized sliders and locks

## Easy handling

Here's just a few examples of how we constantly improve our CoreLine luminaires to make them more pleasant to handle:

- Longer sliders and improved locks for easier opening and closing (CoreLine waterproof)
- Light weight and compact size (recessed spot and highbay)
- Modular design for easy replacement of modules or accessories (recessed spot)
- Robust details – such as the metal hinge of the CoreLine projector
- No sharp edges on the panel, recessed and surface-mounted luminaires


[Click here for a compilation of handy installation videos for most CoreLine products!](#)

# CoreLine LED luminaires

Philips CoreLine offers a full range of LED lighting solutions that keeps installation time to a minimum, while saving a maximum of energy. Whether old or new, optimal lighting can transform a building into something truly special and turn it into a place where people enjoy working and living. Give your customers that “wow” moment with Philips CoreLine: the complete range of high quality LED lighting that’s setting the reference in the market. Because when light really matters, you don’t want to take a chance.

## CoreLine Panel Office compliant

[www.philips.com/coreline](http://www.philips.com/coreline)




Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	IP rating	12NC	EOC code
	W	lm	lm/W		K				
RC132V G4 LED36_43S/830840PSUW30L120OCW3	30-35	4300	125	-	3000-4000	19	IP20/44	910505100560	96738300
RC132V G4 LED36_43S/830_840PSUW60L60OCW3	30-35	4300	125	-	3000-4000	19	IP20/44	910505100564	96742000
RC132V G4LED34_43S/830_840 PSU W60L60 OC	30-35	4300	125	-	3000-4000	19	IP20/44	911401879880	36054600
RC132V G4LED34_43S/830_840 PSUW30L120 OC	30-35	4300	125	-	3000-4000	19	IP20/44	911401880080	36056000
RC133V G4LED34_43S/830_840 PSU W62L62 OC	30-35	4300	125	-	3000-4000	19	IP20/44	911401879980	36055300
RC132V G4 LED34S/830 PSD W30L120 OC	29	3400	117	-	3000	19	IP20/44	911401879680	36052200
RC132V G4 LED34S/830 PSD W60L60 OC	29	3400	117	-	3000	19	IP20/44	911401879080	36046100
RC132V G4 LED34S/830 PSU W60L60 OC	29	3400	117	-	3000	19	IP20/44	911401878680	36042300
RC132V G4 LED36/840 PSU W60L60 OC TP(a)	29	3600	123	-	4000	19	IP20/44	911401879780	36053900
RC132V G4 LED36S/840 PSD W30L120 OC	29	3600	123	-	4000	19	IP20/44	911401879580	36051500
RC132V G4 LED36S/840 PSD W60L60 OC	29	3600	123	-	4000	19	IP20/44	911401878980	36045400
RC132V G4 LED36S/840 PSU W30L120 OC	29	3600	123	-	4000	19	IP20/44	911401878880	36044700
RC132V G4 LED36S/840 PSU W60L60 OC	29	3600	123	-	4000	19	IP20/44	911401878580	36041600
RC132V G4LED36/840 PSUW60L60 OC TPaELB3	29	3600	123	-	4000	19	IP20/44	910505100544	96722200
RC133V G4 LED34S/830 PSD W62L62 OC	29	3400	117	-	3000	19	IP20/44	911401879380	36049200
RC133V G4 LED36S/840 PSD W62L62 OC	29	3600	123	-	4000	19	IP20/44	911401879280	36048500
RC133V G4 LED36S/840 PSU W62L62 OC	29	3600	123	-	4000	19	IP20/44	911401878780	36043000
<b>NEW</b> RC132V G4 LED36S/940 PSU W60L60 OC	33	3600	123	-	4000	19	IP20	911401872182	53503900
RC132V G4 LED36S/840 PSD W30L120 OC ELB3	33	3600	123	DALI	4000	19	IP20/44	910505100537	96715400
RC132V G4 LED36S/840 PSD W60L60 OC ELB3	33	3600	123	DALI	4000	19	IP20/44	910505100532	96710900
RC132V G4 LED36S/840 PSU W30L120 OC ELB3	33	3600	123	-	4000	19	IP20/44	910505100536	96714700
RC132V G4 LED36S/840 PSU W60L60 OC ELB3	33	3600	123	-	4000	19	IP20/44	910505100533	96711600
RC132V G4 LED43S/840 PSD W60L60 OC	34.5	4300	125	-	4000	19	IP20/44	911401879180	36047800
RC133V G4 LED43S/840 PSD W62L62 OC	34.5	4300	125	-	4000	19	IP20/44	911401879480	36050800
<b>NEW</b> RC132V G4 LED40S/830 PSD W60L60 OC	35	4000	116	DALI	3000	19	IP20	911401872082	53502200
RC132V G4 LED43S/840 PSD W60L60 OC ELB3	37	4300	125	DALI	4000	19	IP20/44	910505100541	96719200



# CoreLine LED luminaires

CoreLine Panel Non-office compliant


[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Color Temp.	UGR	IP rating	12NC	EOC code
	W	lm	lm/W	K				
RC132V G4 LED345/830 PSU W60L60 NOC	29	3400	117	3000	23	IP20/44	911401878080	36036200
RC132V G4 LED365/840 PSU W30L120 NOC	29	3600	123	4000	23	IP20/44	911401878480	36040900
RC132V G4 LED365/840 PSU W60L60 NOC	29	3600	123	4000	23	IP20/44	911401877980	36035500
RC133V G4 LED345/830 PSU W62L62 NOC	29	3400	117	3000	23	IP20/44	911401878380	36039300
RC133V G4 LED365/840 PSU W62L62 NOC	29	3600	123	4000	23	IP20/44	911401878280	36038600
<b>NEW</b> RC132V G4 LED365/940 PSU W60L60 NOC	33	3600	123	4000	22	IP20	911401872282	53504600
RC132V G4 LED435/840 PSU W60L60 NOC	34.5	4300	125	4000	23	IP20/44	911401878180	36037900

## CoreLine Panel - Accessory

[www.philips.com/coreline](http://www.philips.com/coreline)




Product Type	12NC	EOC code
① RC132Z SC	911401892080	36268799
② RC132Z SMB W30L120	910930031218	07332299
③ RC132Z SMB-PLC	911401892180	36269499
④ RC133Z SMB W62L62	910930031118	07331599

# CoreLine LED luminaires

CoreLine Recessed Office compliant

[www.philips.com/coreline](http://www.philips.com/coreline)




Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W		K			
RC136B 28S_34S_40S/830 PSD W30L120 OC	22-26-31	2800-3400-4000	130	DALI	3000	19	911401880881	51222100
RC136B 28S_34S_40S/830 PSD W30L120OCELB3	25-29-34	2800-3400-4000	118	DALI	3000	19	910505101244	97551700
RC136B 28S_34S_40S/830 PSD W60L60 OC	22-26-31	2800-3400-4000	130	DALI	3000	19	911401880681	51220700
RC136B 28S_34S_40S/830 PSD W60L60 OC W5	22-26-31	2800-3400-4000	130	DALI	3000	19	911401881481	51228300
RC136B 31S_37S_43S/840 PSD W30L120 OC	22-26-31	3100-3700-4300	140	DALI	4000	19	911401880981	51223800
RC136B 31S_37S_43S/840 PSD W30L120OCELB3	25-29-34	3100-3700-4300	126	DALI	4000	19	910505101245	97552400
RC136B 31S_37S_43S/840 PSD W60L60 OC	22-26-31	3100-3700-4300	140	DALI	4000	19	911401880781	51221400
RC136B 31S_37S_43S/840 PSD W60L60 OC W5	22-26-31	3100-3700-4300	140	DALI	4000	19	911401881581	51229000
RC136B 31S_37S_43S/840 PSD W60L60 OCELB3	25-29-34	3100-3700-4300	126	DALI	4000	19	910505101241	97548700
RC136B 31S_37S_43S/840 PSDW60L60OCELB3W5	25-29-34	3100-3700-4300	126	DALI	4000	19	910505101256	97563000
RC136B 31S_37S_43S/840 PSU W60L60 OC	22-26-31	3100-3700-4300	140	-	4000	19	911401880481	51218400
RC136B 31S_37S_43S/840 PSU W60L60 OC W3	22-26-31	3100-3700-4300	140	-	4000	19	911401881281	51226900
RC136B 31S_37S_43S/840 PSUW60L60OCELB3W3	25-29-34	3100-3700-4300	126	-	4000	19	910505101257	97564700



# CoreLine LED luminaires

CoreLine Recessed Non-office compliant


[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W		K			
RC136B 28S_34S_40S/830 PSU W60L60 NOC	22-26-31	2800-3400-4000	130	-	3000	25	911401880281	51216000
RC136B 28S_34S_40S/830 PSU W60L60 NOC W3	22-26-31	2800-3400-4000	130	-	3000	25	911401881081	51224500
RC136B 31S_37S_43S/840 PSD W60L60 NOC	22-26-31	3100-3700-4300	140	DALI	4000	25	911401880581	51219100
RC136B 31S_37S_43S/840 PSD W60L60 NOC W5	22-26-31	3100-3700-4300	140	DALI	4000	25	911401881381	51227600
RC136B 31S_37S_43S/840 PSD W60L60NOCELB3	25-29-34	3100-3700-4300	126	DALI	4000	25	910505101243	97550000
RC136B 31S_37S_43S/840 PSU W60L60 NOC	22-26-31	3100-3700-4300	140	-	4000	25	911401880381	51217700
RC136B 31S_37S_43S/840 PSU W60L60 NOC W3	22-26-31	3100-3700-4300	140	-	4000	25	911401881181	51225200
RC136B 31S_37S_43S/840 PSU W60L60NOCELB3	25-29-34	3100-3700-4300	126	-	4000	25	910505101242	97549400

## CoreLine Recessed - Accessory

[www.philips.com/coreline](http://www.philips.com/coreline)



10/20 PACK


Product Type	12NC	EOC code
① RC132Z SMB W60L60	910930031018	07330899
② RC132Z SME-3 WH	911401892280	36270099
② RC132Z SME-4 WH	911401892380	36271799



# CoreLine LED luminaires

CoreLine Surface-mounted Office compliant

[www.philips.com/coreline](http://www.philips.com/coreline)




Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W		K			
SM136V 28S_34S_40S/830 PSD W20L120 OC	22-26-31	2800-3400-4000	130	DALI	3000	19	911401882081	51234400
SM136V 28S_34S_40S/830 PSD W20L120 OC W5	22-26-31	2800-3400-4000	130	DALI	3000	19	910505101253	97560900
SM136V 28S_34S_40S/830 PSD W20L150 OC	22-26-31	2800-3400-4000	130	DALI	3000	19	911401882581	51239900
SM136V 31S_37S_43S/840 PSD W20L120 OC	22-26-31	3100-3700-4300	140	DALI	4000	19	911401882181	51235100
SM136V 31S_37S_43S/840 PSD W20L120 OC W5	22-26-31	3100-3700-4300	140	DALI	4000	19	910505101250	97557900
SM136V 31S_37S_43S/840 PSD W20L120OCELB3	25-29-34	3100-3700-4300	126	DALI	4000	19	910505101247	97554800
SM136V 31S_37S_43S/840 PSD W20L150 OC	22-26-31	3100-3700-4300	140	DALI	4000	19	911401882681	51240500
SM136V 31S_37S_43S/840 PSD W20L150OCELB3	25-29-34	3100-3700-4300	126	DALI	4000	19	910505101248	97555500
SM136V 31S_37S_43S/840 PSU W20L120 OC	22-26-31	3100-3700-4300	140	-	4000	19	911401881881	51232000
SM136V 31S_37S_43S/840 PSU W20L120 OC W3	22-26-31	3100-3700-4300	140	-	4000	19	910505101254	97561600
SM136V 31S_37S_43S/840 PSU W20L150 OC	22-26-31	3100-3700-4300	140	-	4000	19	911401882481	51238200
SM136V 31S_37S_43S/840PSDW20L120OCELB3W5	25-29-34	3100-3700-4300	126	DALI	4000	19	910505101258	97565400
SM136V 31S_37S_43S/840PSUW20L120OCELB3W3	25-29-34	3100-3700-4300	126	-	4000	19	910505101259	97566100

# CoreLine LED luminaires

CoreLine Surface-mounted Non-office compliant

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W		K			
SM136V 28S_34S_40S/830 PSU W20L120 NOC	22-26-31	2800-3400-4000	130	-	3000	25	911401881681	51230600
SM136V 28S_34S_40S/830 PSU W20L120 NOCW3	22-26-31	2800-3400-4000	130	-	3000	25	910505101252	97559300
SM136V 28S_34S_40S/830 PSU W20L150 NOC	22-26-31	2800-3400-4000	130	-	3000	25	911401882281	51236800
SM136V 31S_37S_43S/840 PSD W20L120 NOC	22-26-31	3100-3700-4300	140	DALI	4000	25	911401881981	51233700
SM136V 31S_37S_43S/840 PSD W20L120 NOCW5	22-26-31	3100-3700-4300	140	DALI	4000	25	910505101255	97562300
SM136V 31S_37S_43S/840 PSU W20L120 NOC	22-26-31	3100-3700-4300	140	-	4000	25	911401881781	51231300
SM136V 31S_37S_43S/840 PSU W20L120 NOCW3	22-26-31	3100-3700-4300	140	-	4000	25	910505101251	97558600
SM136V 31S_37S_43S/840 PSU W20L150 NOC	22-26-31	3100-3700-4300	140	-	4000	25	911401882381	51237500
SM136V 31S_37S_43S/840 PSUW20L120NOCELB3	25-29-34	3100-3700-4300	126	-	4000	25	910505101246	97553100
SM136V 31S_37S_43S/840 PSUW20L150NOCELB3	25-29-34	3100-3700-4300	126	-	4000	25	910505101249	97556200

# CoreLine LED luminaires

CoreLine Batten

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W		K			
BN126C LED20S/830 PSU TW1 L600	17	2000	118	-	3000	26	911401897080	36345599
BN126C LED22S/840 PSU TW1 L600	17	2200	129	-	4000	26	911401896980	36344899
BN126C LED23S/830 PSU TW1 L1200	18	2300	128	-	3000	27	911401897280	36347999
BN126C LED25S/840 PSU TW1 L1200	18	2500	139	-	4000	27	911401897180	36346299
BN126C LED32S/830 PSU TW1 L1500	25.5	3200	125	-	3000	27	911401897880	36353099
BN126C LED35S/840 PSU TW1 L1500	25.5	3500	137	-	4000	27	911401897780	36352399
BN126C LED38S/830 PSU TW1 L1200	31	3800	123	-	3000	27	911401897480	36349399
BN126C LED41S/840 PSU TW1 L1200	31	4100	132	-	4000	27	911401897380	36348699
BN126C LED41S/840 PSD TW1 L1200	33	4100	124	DALI	4000	27	911401804681	36551099
BN126C LED41S/840 PSU ELB3 TW1 L1200	34	4100	121	-	4000	27	910505100628	96818200
BN126C LED48S/830 PSU TW1 L1500	40	4800	120	-	3000	27	911401898080	36355499
BN126C LED52S/840 PSU TW1 L1500	40	5200	130	-	4000	27	911401897980	36354799
BN126C LED52S/840 PSD TW1 L1500	41	5200	127	DALI	4000	27	911401804781	36552799
BN126C LED52S/840 PSU ELB3 TW1 L1500	43	5200	121	-	4000	27	910505100629	96820500
BN126C LED60S/830 PSU TW1 L1200	49	6000	122	-	3000	27	911401897680	36351699
BN126C LED60S/830 PSU TW1 L1800	49	6000	122	-	3000	27	911401898480	36359299
BN126C LED64S/840 PSU TW1 L1200	49	6400	131	-	4000	27	911401897580	36350999
BN126C LED64S/840 PSU TW1 L1800	49	6400	131	-	4000	27	911401898380	36358599
BN126C LED74S/830 PSU TW1 L1500	59	7400	125	-	3000	27	911401898280	36357899
BN126C LED80S/840 PSU TW1 L1500	59	8000	136	-	4000	27	911401898180	36356199
BN126C LED100S/840 PSU TW1 L1800	75	10,000	133	-	4000	27	911401898580	36360899
BN126C LED94S/830 PSU TW1 L1800	75	9400	125	-	3000	27	911401898680	36361599



# CoreLine LED luminaires

CoreLine Batten - Accessory

[www.philips.com/coreline](http://www.philips.com/coreline)



IP  
IP20

IK  
IK04


10/108 PACK

Product Type	12NC	EOC code
1 BN126Z REF A1 L1200	911401776822	36576399
1 BN126Z REF A1 L1500	911401776832	36577099
1 BN126Z REF A1 L1800	911401776842	36578799
1 BN126Z REF A1 L600	911401776812	36575699
2 BN126Z REF A2 L1200	911401776862	36580099
2 BN126Z REF A2 L1500	911401776872	36581799
2 BN126Z REF A2 L1800	911401776882	36582499
2 BN126Z REF A2 L600	911401776852	36579499
3 BN126Z SC	911401776802	36574999

# CoreLine LED luminaires

CoreLine Downlight

[www.philips.com/coreline](http://www.philips.com/coreline)




Product Type	LED	Lumen Output	Efficiency	Beam Angle	Dimmable	Color Temp.	UGR	IP rating	12NC	EOC code
	W	lm	lm/W	°		K				
1 DN140B LED10S/830 PSU C IP54 P16	9.5	1100	116	120	-	3000	22	IP20/54	911401633405	32604700
2 DN140B LED10S/830 PSU C P16	9.5	1100	116	120	-	3000	22	IP20	911401631805	32588000
3 DN140B LED10S/830 PSU WR IP54 P16	9.5	1100	116	120	-	3000	25	IP20/54	911401632605	32596500
4 DN140B LED10S/830 PSU WR P16	9.5	1100	116	120	-	3000	25	IP20	911401631005	32580400
1 DN140B LED10S/840 PSU C IP54 P16	9.5	1100	116	120	-	4000	22	IP20/54	911401633505	32605400
2 DN140B LED10S/840 PSU C P16	9.5	1100	116	120	-	4000	22	IP20	911401631905	32589700
3 DN140B LED10S/840 PSU WR IP54 P16	9.5	1100	116	120	-	4000	25	IP20/54	911401632705	32597200
4 DN140B LED10S/840 PSU WR P16	9.5	1100	116	120	-	4000	25	IP20	911401631105	32581100
4 DN140B LED10S/830 PSD-E WR	11.5	1100	96	120	DALI	3000	25	IP20	911401631205	32582800
2 DN140B LED10S/830 PSD-E C	11.5	1100	96	120	DALI	3000	22	IP20	911401632005	32590300
1 DN140B LED10S/830 PSD-E C IP54	11.5	1100	96	120	DALI	3000	22	IP20/54	911401633605	32606100
3 DN140B LED10S/830 PSD-E WR IP54	11.5	1100	96	120	DALI	3000	25	IP20/54	911401632805	32598900
4 DN140B LED10S/840 PSD-E WR	11.5	1100	96	120	DALI	4000	25	IP20	911401631305	32583500
2 DN140B LED10S/840 PSD-E C	11.5	1100	96	120	DALI	4000	22	IP20	911401632105	32591000
1 DN140B LED10S/840 PSD-E C IP54	11.5	1100	96	120	DALI	4000	22	IP20/54	911401633705	32607800
3 DN140B LED10S/840 PSD-E WR IP54	11.5	1100	96	120	DALI	4000	25	IP20/54	911401632905	32599600
2 DN140B LED10S/830 PSD-E C ELB3	14.5	1100	76	120	DALI	3000	22	IP20	911401639805	32835500
4 DN140B LED10S/830 PSD-E WR ELB3	14.5	1100	76	120	DALI	3000	25	IP20	911401639405	32831700
2 DN140B LED10S/840 PSD-E C ELB3	14.5	1100	76	120	DALI	4000	22	IP20	911401639905	32836200
4 DN140B LED10S/840 PSD-E WR ELB3	14.5	1100	76	120	DALI	4000	25	IP20	911401639505	32832400
5 DN140B LED20S/830 PSU C IP54 P16	19	2200	116	120	-	3000	22	IP20/54	911401633805	32608500
6 DN140B LED20S/830 PSU C P16	19	2200	116	120	-	3000	22	IP20	911401632205	32592700
7 DN140B LED20S/830 PSU WR IP54 P16	19	2200	116	120	-	3000	25	IP20/54	911401633005	32600900
8 DN140B LED20S/830 PSU WR P16	19	2200	116	120	-	3000	25	IP20	911401631405	32584200
5 DN140B LED20S/840 PSU C IP54 P16	19	2200	116	120	-	4000	22	IP20/54	911401633905	32609200
6 DN140B LED20S/840 PSU C P16	19	2200	116	120	-	4000	22	IP20	911401632305	32593400
7 DN140B LED20S/840 PSU WR IP54 P16	19	2200	116	120	-	4000	25	IP20/54	911401633105	32601600
8 DN140B LED20S/840 PSU WR P16	19	2200	116	120	-	4000	25	IP20	911401631505	32585900
8 DN140B LED20S/830 PSD-E WR	20.5	2200	107	120	DALI	3000	25	IP20	911401631605	32586600
6 DN140B LED20S/830 PSD-E C	20.5	2200	107	120	DALI	3000	22	IP20	911401632405	32594100



# CoreLine LED luminaires

CoreLine Downlight - Continued

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Dimmable	Color Temp.	UGR	IP rating	12NC	EOC code
	W	lm	lm/W	°		K				
1 DN140B LED20S/830 PSD-E C IP54	20.5	2200	107	120	DALI	3000	22	IP20/54	911401634005	32610800
2 DN140B LED20S/830 PSD-E WR IP54	20.5	2200	107	120	DALI	3000	25	IP20/54	911401633205	32602300
3 DN140B LED20S/840 PSD-E WR	20.5	2200	107	120	DALI	4000	25	IP20	911401631705	32587300
4 DN140B LED20S/840 PSD-E C	20.5	2200	107	120	DALI	4000	22	IP20	911401632505	32595800
1 DN140B LED20S/840 PSD-E C IP54	20.5	2200	107	120	DALI	4000	22	IP20/54	911401634105	32611500
2 DN140B LED20S/840 PSD-E WR IP54	20.5	2200	107	120	DALI	4000	25	IP20/54	911401633305	32603000
4 DN140B LED20S/830 PSD-E C ELB3	23.5	2200	94	120	DALI	3000	22	IP20	911401640005	32837900
3 DN140B LED20S/830 PSD-E WR ELB3	23.5	2200	94	120	DALI	3000	25	IP20	911401639605	32833100
4 DN140B LED20S/840 PSD-E C ELB3	23.5	2200	94	120	DALI	4000	22	IP20	911401640105	32838600
3 DN140B LED20S/840 PSD-E WR ELB3	23.5	2200	94	120	DALI	4000	25	IP20	911401639705	32834800

# CoreLine LED luminaires

CoreLine SlimDownlight

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED		Lumen Output		Efficiency	Dimmable	Color Temp.	UGR	IP rating	12NC	EOC code
	W	lm	lm/W			K					
DN145B LED6S/830 PSU II WH	6.5	650	100	-	3000	32	IP20/44	911401805780	33945099		
DN145B LED6S/840 PSU II WH	6.5	650	100	-	4000	32	IP20/44	911401805880	33946799		
DN145B LED10S/830 PSU II WH	11	1100	100	-	3000	28	IP20/44	911401805980	33947499		
DN145B LED10S/840 PSU II WH	11	1100	100	-	4000	28	IP20/44	911401806080	33948199		
DN145C LED10S/830 PSU II WH	11	1100	100	-	3000	28	IP44	911401806380	33951199		
DN145C LED10S/840 PSU II WH	11	1100	100	-	4000	28	IP44	911401806480	33952899		
NEW DN145B LED10S/830 WIA-E WH	13	1100	93	InterAct office	3000	28	IP20/44	910505101195	97638599		
NEW DN145B LED10S/840 WIA-E WH	13	1100	93	InterAct office	4000	28	IP20/44	910505101196	97640899		
DN145B LED10S/830 PSD-E II WH	13	1100	85	DALI	3000	28	IP20/44	910500465901	96100899		
DN145B LED10S/840 PSD-E II WH	13	1100	85	DALI	4000	28	IP20/44	910500465902	96101599		
DN145B LED20S/830 PSU II WH	21	2100	100	-	3000	28	IP20/44	911401806180	33949899		
DN145B LED20S/840 PSU II WH	21	2100	100	-	4000	28	IP20/44	911401806280	33950499		
DN145C LED20S/830 PSU II WH	21	2100	100	-	3000	28	IP44	911401806580	33953599		
DN145C LED20S/840 PSU II WH	21	2100	100	-	4000	28	IP44	911401806680	33954299		
NEW DN145B LED20S/830 WIA-E WH	22.5	2100	93	InterAct office	3000	28	IP20/44	910505101197	97642299		
NEW DN145B LED20S/840 WIA-E WH	22.5	2100	93	InterAct office	4000	28	IP20/44	910505101198	97644699		
DN145B LED20S/830 PSD-E II WH	22.5	2100	93	DALI	3000	28	IP20/44	910500465903	96102299		
DN145B LED20S/840 PSD-E II WH	22.5	2100	93	DALI	4000	28	IP20/44	910500465904	96103999		



# CoreLine LED luminaires

CoreLine Waterproof

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	Integrated emergency 3 hours	12NC	EOC code
	W	lm	lm/W		K				
1 WT120C G2 LED18S/840 PSU PCO L600	15	1800	120	-	4000	26		911401836980	34976399
2 WT120C G2 LED19S/840 PSU L600	15	1900	127	-	4000	25		911401823480	84045900
2 WT120C G2 LED19S/840 PSD L600	16	1900	119	DALI	4000	25		910505100038	88306800
2 WT120C G2 LED19S/840 PSU MDU L600	16	1900	119	-	4000	25		910505100036	96244900
1 WT120C G2 LED25S/840 PSU PCO L1200	20.5	2500	125	-	4000	26		911401837080	34977099
3 WT120C G2 LED27S/840 PSU L1200	20.5	2700	135	-	4000	25		911401823580	84046600
3 WT120C G2 LED27S/840 PSU TW3 L1200	21	2700	129	-	4000	25		910505100039	91685800
3 WT120C G2 LED27S/840 PSU MDU L1200	21.5	2700	126	-	4000	25		910505100040	96248700
3 WT120C G2 LED27S/840 PSU MDU TW3 L1200	21.5	2700	126	-	4000	25		910505100041	96249400
3 WT120C G2 LED27S/840 PSD L1200	22	2700	123	DALI	4000	25		910505100044	88307500
1 WT120C G2 LED31S/840 PSU PCO L1500	24.3	3100	129	-	4000	26		911401837180	34978799
4 WT120C G2 LED34S/840 PSU L1500	24.3	3400	142	-	4000	25		911401823680	84047300
4 WT120C G2 LED34S/865 PSU L1500	24.5	3400	139	-	6500	25		911401824481	36934199
4 WT120C G2 LED34S/840 PSU TW3 L1500	25	3400	136	-	4000	25		910505100058	91686500
3 WT120C G2 LED27S/840 PSU ELB3 L1200	25.5	2700	106	-	4000	25	Yes	910505100042	85418000
4 WT120C G2 LED34S/840 PSU MDU L1500	25.5	3400	133	-	4000	25		910505100059	96267800
4 WT120C G2 LED34S/840 PSU MDU TW3 L1500	25.5	3400	133	-	4000	25		910505100060	96268500
4 WT120C G2 LED34S/840 PSD L1500	26	3400	131	DALI	4000	25		910505100061	88308200
3 WT120C G2 LED27S/840 PSD ELB3 L1200	27	2700	100	DALI	4000	25	Yes	910505100045	88311200
3 WT120C G2 LED37S/830 PSU L1200	28.5	3700	130	-	3000	25		911401824681	36936599
3 WT120C G2 LED40S/865 PSU L1200	28.5	4000	140	-	6500	25		911401824381	36933499
1 WT120C G2 LED37S/840 PSU PCO L1200	28.6	3700	132	-	4000	26		911401837280	34979499
3 WT120C G2 LED40S/840 PSU L1200	28.6	4000	143	-	4000	25		911401823780	84048000
2 WT120C G2 LED40S/840 PSU TW1 WEC L1200	29	4000	138	-	4000	25		910505100051	16317400
2 WT120C G2 LED40S/840 PSU WEC L1200	29	4000	138	-	4000	25		910505100050	16316700
4 WT120C G2 LED34S/840 PSU ELB3 L1500	29.5	3400	115	-	4000	25	Yes	910505100062	85420300
3 WT120C G2 LED40S/840 PSD L1200	30	4000	133	DALI	4000	25		910505100053	88309900
3 WT120C G2 LED40S/840 PSU MDU L1200	30	4000	133	-	4000	25		910505100048	96256200
3 WT120C G2 LED40S/840 PSU MDU TW3 L1200	30	4000	133	-	4000	25		910505100049	96257900
3 WT120C G2 LED40S/840 PSU TW3 L1200	30	4000	133	-	4000	25		910505100047	91687200

# CoreLine LED luminaires

CoreLine Waterproof - Continued

[www.philips.com/coreline](http://www.philips.com/coreline)




Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	UGR	Integrated emergency 3 hours	Motion/Daylight sensor	12NC	EOC code
	W	lm	lm/W		K					
① WT120C G2 LED34S/840 PSD ELB3 L1500	30.5	3400	111	DALI	4000	25	Yes		910505100064	88313600
① WT120C G2 LED34S/840 PSU MDU ELB3 L1500	31	3400	110	-	4000	25	Yes	Yes	910505100063	96271500
② WT120C G2 LED40S/840 PSU ELB3 L1200	34	4000	118	-	4000	25	Yes		910505100054	85419700
② WT120C G2 LED40S/840 PSD ELB3 L1200	35	4000	114	DALI	4000	25	Yes		910505100057	88312900
② WT120C G2 LED40S/840 PSU MDU ELB3 L1200	35	4000	114	-	4000	25	Yes	Yes	910505100055	96263000
③ WT120C G2 LED57S/840 PSU PCO L1500	42.9	5700	136	-	4000	26			911401837380	34980099
① WT120C G2 LED60S/840 PSU L1500	42.9	6000	143	-	4000	25			911401823880	84049700
① WT120C G2 LED55S/830 PSU L1500	43	5500	128	-	3000	25			911401824781	36937299
① WT120C G2 LED60S/865 PSU L1500	43	6000	140	-	6500	25			911401824581	36935899
④ WT120C G2 LED60S/840 PSU TW1 WEC L1500	44	6000	136	-	4000	25			910505100070	16319800
① WT120C G2 LED60S/840 PSU TW3 L1500	44	6000	136	-	4000	25			910505100066	91688900
④ WT120C G2 LED60S/840 PSU WEC L1500	44	6000	136	-	4000	25			910505100069	16318100
① WT120C G2 LED60S/840 PSD L1500	45	6000	133	DALI	4000	25			910505100072	88310500
① WT120C G2 LED60S/840 PSU MDU L1500	45	6000	133	-	4000	25			910505100067	96275300
① WT120C G2 LED60S/840 PSU MDU TW3 L1500	45	6000	133	-	4000	25			910505100068	96276000
① WT120C G2 LED60S/840 PSD ELB3 L1500	49	6000	122	DALI	4000	25	Yes		910505100076	88314300
① WT120C G2 LED60S/840 PSU ELB3 L1500	49	6000	122	-	4000	25	Yes		910505100073	85421000
① WT120C G2 LED60S/840 PSU MDU ELB3 L1500	50	6000	120	-	4000	25	Yes	Yes	910505100074	96282100
③ WT120C G2 LED75S/840 PSU PCO L1500	57.1	7500	132	-	4000	28			911401837480	34981799
① WT120C G2 LED80S/840 PSU L1500	57.1	8000	140	-	4000	25			911401823980	40928900
① WT120C G2 LED80S/840 PSU TW3 L1500	60	8000	133	-	4000	25			910505100077	40930200
① WT120C G2 LED80S/840 PSD L1500	61	8000	131	DALI	4000	25			910505100079	40929600
① WT120C G2 LED80S/840 PSU MDU L1500	61	8000	131	-	4000	25			910505100078	96286900
① WT120C G2 LED80S/840 PSU L1500 ELB3	63	8000	127	-	4000	25	Yes		910505100080	40931900

# CoreLine LED luminaires

CoreLine Recessed Spot

[www.philips.com/coreline](http://www.philips.com/coreline)




Product Type	LED		Lumen Output		Efficiency	Beam Angle	Dimmable	Color Temp.	UGR	IP rating	12NC	EOC code
	W	lm	lm/W	°								
RS140B LED6-32-/827 PSR PI6 ALU	8	650	82	32	Analog	2700	22	IP65	912401483045	38287299		
RS140B LED6-32-/827 PSR PI6 WH	8	650	82	32	Analog	2700	22	IP65	912401483031	38277399		
RS140B LED6-32-/830 PSR PI6 ALU	8	650	82	32	Analog	3000	22	IP65	912401483046	38288999		
RS140B LED6-32-/830 PSR PI6 WH	8	650	82	32	Analog	3000	22	IP65	912401483032	38278099		
RS140B LED6-32-/840 PSR PI6 ALU	8	650	82	32	Analog	4000	22	IP65	912401483047	38289699		
RS140B LED6-32-/840 PSR PI6 WH	8	650	82	32	Analog	4000	22	IP65	912401483033	38279799		
RS141B LED6-32-/827 PSR PI6 ALU	8	650	82	32	Analog	2700	22	IP44	912401483048	38290299		
RS141B LED6-32-/827 PSR PI6 WH	8	650	82	32	Analog	2700	22	IP44	912401483034	38280399		
RS141B LED6-32-/830 PSR PI6 ALU	8	650	82	32	Analog	3000	22	IP44	912401483049	38291999		
RS141B LED6-32-/830 PSR PI6 WH	8	650	82	32	Analog	3000	22	IP44	912401483035	38281099		
RS141B LED6-32-/840 PSR PI6 ALU	8	650	82	32	Analog	4000	22	IP44	912401483050	38292699		
RS141B LED6-32-/840 PSR PI6 WH	8	650	82	32	Analog	4000	22	IP44	912401483036	38282799		
RS142B LED6-32-/827 PSR PI6 WH FR	8	650	82	32	Analog	2700	22	IP44	912401483119	38417399		
RS142B LED6-32-/830 PSR PI6 WH FR	8	650	82	32	Analog	3000	22	IP44	912401483120	38418099		
RS140B LED9-32-/830 PSR PI6 ALU	11	900	82	32	Analog	3000	22	IP65	912401483051	38293399		
RS140B LED9-32-/830 PSR PI6 WH	11	900	82	32	Analog	3000	22	IP65	912401483039	38285899		
RS140B LED9-32-/840 PSR PI6 ALU	11	900	82	32	Analog	4000	22	IP65	912401483052	38294099		
RS140B LED9-32-/840 PSR PI6 WH	11	900	82	32	Analog	4000	22	IP65	912401483040	38286599		
RS141B LED9-32-/830 PSR PI6 WH	11	900	82	32	Analog	3000	22	IP44	912401483037	38283499		
RS141B LED9-32-/840 PSR PI6 WH	11	900	82	32	Analog	4000	22	IP44	912401483038	38284199		
RS140B LED12-36-/830 PSR PI6 ALU	15	1200	82	36	Analog	3000	22	IP65	912401483053	38423499		
RS140B LED12-36-/830 PSR PI6 WH	15	1200	82	36	Analog	3000	22	IP65	912401483043	38421099		
RS140B LED12-36-/840 PSR PI6 ALU	15	1200	82	36	Analog	4000	22	IP65	912401483054	38424199		
RS140B LED12-36-/840 PSR PI6 WH	15	1200	82	36	Analog	4000	22	IP65	912401483044	38422799		
RS141B LED12-36-/830 PSR PI6 WH	15	1200	82	36	Analog	3000	22	IP44	912401483041	38419799		
RS141B LED12-36-/840 PSR PI6 WH	15	1200	82	36	Analog	4000	22	IP44	912401483042	38420399		

# CoreLine LED luminaires

CoreLine Recessed Spot - Accessory

[www.philips.com/coreline](http://www.philips.com/coreline)





  
 L70 at 50,000 6/12/18 PACK

Product Type	LED		Lumen Output		Efficiency	Beam Angle	Dimmable	Color Temp.	UGR	IP rating	IK rating	Warranty	12NC	EOC code
	W	lm	lm/W	°	Years									
① RS140Z MODULE LED6-32-/827	8	650	82	32	Analog	2700	22	IP65	IK02	5	912401483061	38295799		
① RS140Z MODULE LED6-32-/830	8	650	82	32	Analog	3000	22	IP65	IK02	5	912401483062	38296499		
① RS140Z MODULE LED6-32-/840	8	650	82	32	Analog	4000	22	IP65	IK02	5	912401483063	38297199		
① RS140Z MODULE LED9-32-/830	11	900	82	32	Analog	3000	22	IP65	IK02	5	912401483064	38298899		
① RS140Z MODULE LED9-32-/840	11	900	82	32	Analog	4000	22	IP65	IK02	5	912401483065	38299599		
② RS140Z CFRM RND-ADJUST D80 BK								IP20	IK03		912401483072	38448799		
③ RS140Z CFRM SQR-ADJUST ALU								IP20	IK03		912401483135	38458699		
④ RS140Z CFRM SQR-ADJUST WH								IP20	IK03		912401483134	38456299		
⑤ RS140Z CFRM SQR-FIX Darklight								IP20	IK03		912401483161	38508899		
⑥ RS143Z CFRM GRID 1x1 WH								IP20	IK03		912401483212	38832499		
⑦ RS143Z CFRM GRID 1x2 WH								IP20	IK03		912401483213	38833199		
⑧ RS143Z CFRM GRID 1x3 WH								IP20	IK03		912401483214	38834899		

# CoreLine LED luminaires

CoreLine Trunking Gen2

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Dimmable	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	°		K			
LL217X 45S/840 1x PSU WB 5x1.5	28	4500	161	120	-	4000	19	910925868234	61794000
LL212X 53S/840 1x PSD WB 7x1.5 HE	33	5300	161	120	DALI	4000	22	910925867522	10779300
LL217X 80S/840 1x PSD WB 7x1.5 HE	48.5	8000	165	120	DALI	4000	22	910925867560	10817200
LL217X 80S/840 1x PSD WB 7x2.5 HE	48.5	8000	165	120	DALI	4000	22	910925867531	10788500
LL217X 80S/840 1x PSU WB 5x2.5 HE	49	8000	163	120	-	4000	22	910925867533	10790800
LL217X 80S/840 1x PSD O 7x2.5	50	7400	144	120	DALI	4000	28	910925867535	10792200
LL217X 80S/840 1x PSU WB 5x1.5	51	8000	157	120	-	4000	22	910925867537	10794600
LL234X 90S/840 2x PSD WB 7x1.5	55	9000	164	120	DALI	4000	19	910925867561	10818900
LL234X 90S/840 2x PSU WB 5x1.5	56	9000	161	120	-	4000	19	910925868232	61792600
LL217X 120S/840 1x PSD WB 7x1.5 HE	79	12.000	152	120	DALI	4000	22	910925867526	10783000
LL217X 120S/840 1x PSU BV WB HE	80	12.000	150	120	-	4000	22	910925867525	10782300
LL217X 120S/840 1x PSU WB 5x1.5 HE	80	12.000	150	120	-	4000	22	910925867529	10786100
LL234X 160S/840 2x PSD WB 7x1.5 HE	97	16.000	165	120	DALI	4000	22	910925867540	10797700
LL234X 160S/840 2x PSD O 7x2.5	100	15.000	144	120	DALI	4000	28	910925867552	10809700
LL234X 160S/840 2x PSD WB 7x1.5	100	16.000	160	120	DALI	4000	22	910925867553	10810300
LL234X 240S/840 2x PSD WB 7x1.5 HE	158	24.000	152	120	DALI	4000	22	910925867545	10802800
LL234X 240S/840 2x PSU WB 5x1.5 HE	160	24.000	150	120	-	4000	22	910925867548	10805900






# CoreLine LED luminaires

CoreLine Trunking Gen2 - Accessory

[www.philips.com/coreline](http://www.philips.com/coreline)




Product Type	12NC	EOC code
LL212X 7x1.5 BC	910925867583	10840000
LL217X 7x1.5 BC	910925867589	10846200
LL234X 7x1.5 BC	910925867595	10852300

# CoreLine LED luminaires

CoreLine Highbay Gen4

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Dimmable	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	°		K			
BY120P G4 LED100S/840 PSU NB	69	10.000	145	55	-	4000	22	911401569851	33571100
BY120P G4 LED100S/840 PSU WB	69	10.000	145	90 x 90	-	4000	24	911401569951	33570400
BY120P G4 LED100S/865 PSU NB	69	10.000	145	55	-	6500	22	911401575251	33567400
BY120P G4 LED100S/865 PSU WB	69	10.000	145	90 x 90	-	6500	24	911401575351	33566700
BY120P G4 LED100S/840 PSD NB	73	10.000	137	55	DALI	4000	22	911401574451	33702900
BY120P G4 LED100S/840 PSD WB	73	10.000	137	90 x 90	DALI	4000	24	911401574551	33703600
BY120P G4 LED100S/865 PSD NB	73	10.000	137	55	DALI	6500	22	911401575651	33704300
BY120P G4 LED100S/865 PSD WB	73	10.000	137	90 x 90	DALI	6500	24	911401575751	33705000
BY121P G4 LED200S/840 PSU NB	138	20.000	145	55	-	4000	22	911401570051	33569800
BY121P G4 LED200S/840 PSU WB	138	20.000	145	90 x 90	-	4000	26	911401570151	33568100
BY121P G4 LED200S/865 PSU NB	138	20.000	145	55	-	6500	22	911401575451	33565000
BY121P G4 LED200S/865 PSU WB	138	20.000	145	90 x 90	-	6500	26	911401575551	33564300
BY121P G4 LED200S/840 PSD NB	146	20.000	137	55	DALI	4000	22	911401574651	33698500
BY121P G4 LED200S/840 PSD WB	146	20.000	137	90 x 90	DALI	4000	26	911401574751	33699200
BY121P G4 LED200S/865 PSD NB	146	20.000	137	55	DALI	6500	22	911401575851	33700500
BY121P G4 LED200S/865 PSD WB	146	20.000	137	90 x 90	DALI	6500	26	911401575951	33701200
BY122P G4 LED250S/840 PSU NB	172	25.000	145	55	-	4000	22	911401578351	33664000
BY122P G4 LED250S/840 PSU WB	172	25.000	145	90 x 90	-	4000	26	911401578451	33665700
BY122P G4 LED250S/865 PSU NB	172	25.000	145	55	-	6500	22	911401578551	33666400
BY122P G4 LED250S/865 PSU WB	172	25.000	145	90 x 90	-	6500	26	911401578651	33667100
BY122P G4 LED250S/840 PSD NB	183	25.000	137	55	DALI	4000	22	911401582051	33879800
BY122P G4 LED250S/840 PSD WB	183	25.000	137	90 x 90	DALI	4000	26	911401582151	33880400
BY122P G4 LED250S/865 PSD NB	183	25.000	137	55	DALI	6500	22	911401582251	33881100
BY122P G4 LED250S/865 PSD WB	183	25.000	137	90 x 90	DALI	6500	26	911401582351	33882800



# CoreLine LED luminaires

CoreLine Value Highbay

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type		LED	Lumen Output	Efficiency	Color Temp.	UGR	12NC	EOC code
		W	lm	lm/W	K			
NEW	BY100P LED100S/840 PSU WB	77	10.500	136	4000	28	911401671107	54298300
NEW	BY101P LED200S/840 PSU WB	154	20.500	133	4000	30	911401646207	52921200
NEW	BY102P LED260S/840 PSU WB	187	25.500	136	4000	29	911401646307	52922900

CoreLine Value Highbay - Accessory

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type		12NC	EOC code
NEW	BY100Z BR L215	911401676807	54602899
NEW	BY101Z ALU	911401677107	54583099
NEW	BY102Z ALU	911401677207	54584799

# CoreLine LED luminaires

CoreLine Projector gen2

[www.philips.com/coreline](http://www.philips.com/coreline)



	Product Type	LED	Lumen Output	Efficiency	Beam Angle	Color Temp.	UGR	12NC	EOC code
		W	lm	lm/W	°	K			
NEW	ST151T LED30S/940 MB BK	27	3000	110	25	4000	20	911401846682	52856799
NEW	ST151T LED30S/940 MB WH	27	3000	110	25	4000	20	911401846882	52858199
NEW	ST151T LED30S/940 WB BK	27	3000	110	38	4000	20	911401847082	52860499
NEW	ST151T LED30S/940 WB WH	27	3000	110	38	4000	20	911401847282	52862899
NEW	ST151T LED30S/930 MB BK	30	3000	100	25	3000	19	911401846582	52855099
NEW	ST151T LED30S/930 MB WH	30	3000	100	25	3000	19	911401846782	52857499
NEW	ST151T LED30S/930 WB BK	30	3000	100	38	3000	19	911401846982	52859899
NEW	ST151T LED30S/930 WB WH	30	3000	100	38	3000	19	911401847182	52861199



# CoreLine LED luminaires

CoreLine Wall-mounted

[www.philips.com/coreline](http://www.philips.com/coreline)



	Product Type	LED	Lumen Output	Efficiency	Beam Angle	Dimmable	Color Temp.	UGR	12NC	EOC code
		W	lm	lm/W	°		K			
NEW	WL140V LED12S/830 PSR MDU WH	12	1200	90	120	-	3000	22	911401851582	53082999
NEW	WL140V LED12S/830 PSU WH	12	1275	105	120	-	3000	22	911401847382	52871099
NEW	WL140V LED12S/840 PSR MDU WH	12	1250	95	120	-	4000	22	911401851682	53083699
NEW	WL140V LED12S/840 PSU WH	12	1350	110	120	-	4000	22	911401847482	52872799
NEW	WL140V LED12S/830 PSED WH	13.5	1200	88.88	120	depends on driver (1-10V, DALI...)	3000	22	910505101534	97848800
NEW	WL140V LED12S/840 PSED WH	13.5	1250	92.59	120	depends on driver (1-10V, DALI...)	4000	22	910505101535	97849500
NEW	WL140V LED12S/830 PSED ELB3 WH	16.5	1200	72.72	120	depends on driver (1-10V, DALI...)	3000	22	910505101550	97864800
NEW	WL140V LED12S/830 PSR ELB3 MDU WH	16.5	1200	72.72	120	depends on driver (1-10V, DALI...)	3000	22	910505101552	97866200
NEW	WL140V LED12S/840 PSED ELB3 WH	16.5	1250	75.75	120	depends on driver (1-10V, DALI...)	4000	22	910505101551	97865500
NEW	WL140V LED12S/840 PSR ELB3 MDU WH	16.5	1250	75.75	120	depends on driver (1-10V, DALI...)	4000	22	910505101553	97867900
NEW	WL140V LED20S/830 PSU MDU WH	19	1850	95	120	-	3000	24	911401847982	52877299
NEW	WL140V LED20S/840 PSU MDU WH	19	1950	100	120	-	4000	24	911401848082	52878999
NEW	WL140V LED12_20S/827_830_840 PSU WH	20	2000	100	120	-	4000	24	911401848182	52879699
NEW	WL140V LED20S/830 PSU WH	20	2100	105	120	-	3000	24	911401847582	52873499
NEW	WL140V LED20S/840 PSU WH	20	2200	110	120	-	4000	24	911401847682	52874199
NEW	WL140V LED20S/830 PSED WH	22	2100	95.45	120	depends on driver (1-10V, DALI...)	3000	24	910505101538	97852500
NEW	WL140V LED20S/840 PSED WH	22	2200	100	120	depends on driver (1-10V, DALI...)	4000	24	910505101539	97853200
NEW	WL140V LED20S/830 PSR MDU WH	23	2100	90	120	-	3000	24	911401851782	53084399
NEW	WL140V LED20S/840 PSR MDU WH	23	2200	95	120	-	4000	24	911401851882	53085099
NEW	WL140V LED20S/830 PSED ELB3 WH	25	2100	84	120	depends on driver (1-10V, DALI...)	3000	24	910505101554	97868600
NEW	WL140V LED20S/830 WIA ELB3 WH	25	2100	84	120	InterAct office	3000	24	910505101562	97876100
NEW	WL140V LED20S/840 PSED ELB3 WH	25	2200	88	120	depends on driver (1-10V, DALI...)	4000	24	910505101555	97869300
NEW	WL140V LED20S/840 WIA ELB3 WH	25	2200	88	120	InterAct office	4000	24	910505101563	97877800
NEW	WL140V LED20S/830 PSR ELB3 MDU WH	28.5	2100	73.68	120	depends on driver (1-10V, DALI...)	3000	24	910505101556	97870900
NEW	WL140V LED20S/840 PSR ELB3 MDU WH	28.5	2200	77.19	120	depends on driver (1-10V, DALI...)	4000	24	910505101557	97871600
NEW	WL140V LED34S/830 PSR MDU WH	30	2950	98	120	-	3000	25	911401851982	53086799
NEW	WL140V LED34S/840 PSR MDU WH	30	3100	103	120	-	4000	25	911401852082	53087499
NEW	WL140V LED34S/830 PSU WH	32	3400	105	120	-	3000	25	911401847782	52875899
NEW	WL140V LED34S/840 PSU WH	32	3550	110	120	-	4000	25	911401847882	52876599
NEW	WL140V LED20_34S/827_830_840 PSU WH	33	3300	100	120	-	4000	25	911401848282	52880299



# CoreLine LED luminaires

CoreLine Wall-mounted - Continued

[www.philips.com/coreline](http://www.philips.com/coreline)



	Product Type	LED		Efficiency	Beam Angle	Dimmable	Color Temp.	UGR	12NC	EOC code
		W	lm	lm/W	°		K			
NEW	WL140V LED34S/830 PSED WH	35.5	3350	94.36	120	depends on driver (1-10V, DALI...)	3000	25	910505101542	97856300
NEW	WL140V LED34S/840 PSED WH	35.5	3400	95.77	120	depends on driver (1-10V, DALI...)	4000	25	910505101543	97857000
NEW	WL140V LED34S/830 PSED ELB3 WH	38.5	3350	87.01	120	depends on driver (1-10V, DALI...)	3000	25	910505101558	97872300
NEW	WL140V LED34S/830 PSR ELB3 MDU WH	38.5	2950	76.62	120	depends on driver (1-10V, DALI...)	3000	25	910505101560	97874700
NEW	WL140V LED34S/830 WIA ELB3 WH	38.5	3350	87.01	120	InterAct office	3000	25	910505101564	97878500
NEW	WL140V LED34S/840 PSED ELB3 WH	38.5	3400	88.31	120	depends on driver (1-10V, DALI...)	4000	25	910505101559	97873000
NEW	WL140V LED34S/840 PSR ELB3 MDU WH	38.5	3100	80.51	120	depends on driver (1-10V, DALI...)	4000	25	910505101561	97875400
NEW	WL140V LED34S/840 WIA ELB3 WH	38.5	3400	88.31	120	InterAct office	4000	25	910505101565	97879200

# CoreLine LED luminaires

CoreLine tempo X-Large

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED		Efficiency	Dimmable	Color Temp.	12NC	EOC code
	W	lm	lm/W		K		
BVP140 LED360-4S 30K6/740 PSD OFA52 D9	225	30.600	136	DALI	4000	912300024344	87288500
BVP140 LED360-4S 30K6/740 PSU OFA52	225	30.600	136	-	4000	912300024336	87280900
BVP140 LED360-4S 31K3/740 PSD S D9	225	31.320	139	DALI	4000	912300024348	87292200
BVP140 LED360-4S 31K3/740 PSU S	225	31.320	139	-	4000	912300024340	87284700
BVP140 LED360-4S 30K6/730 PSU OFA52	245	30.600	125	-	3000	912300057776	90527900
BVP140 LED360-4S 31K3/730 PSU S	245	31.320	128	-	3000	912300057778	90530900
BVP140 LED420-4S 35K3/740 PSD OFA52 D9	250	35.280	141	DALI	4000	912300024343	87287800
BVP140 LED420-4S 35K3/740 PSU OFA52	250	35.280	141	-	4000	912300024335	87279300
BVP140 LED420-4S 36K1/740 PSD S D9	250	36.120	144	DALI	4000	912300024347	87291500
BVP140 LED420-4S 36K1/740 PSU S	250	36.120	144	-	4000	912300024339	87283000
BVP140 LED420-4S 35K3/730 PSU OFA52	275	35.280	128	-	3000	912300057775	90526200
BVP140 LED420-4S 36K1/730 PSU S	275	36.120	131	-	3000	912300057777	90529300
BVP140 LED450-4S 37K8/730 PSU OFA52	295	37.800	128	-	3000	912300057774	90522400
BVP140 LED450-4S 38K7/730 PSU S	295	38.700	131	-	3000	912300057777	90528600
BVP140 LED480-4S 40K3/740 PSD OFA52 D9	295	40.320	137	DALI	4000	912300024342	87286100
BVP140 LED480-4S 40K3/740 PSU OFA52	295	40.320	137	-	4000	912300024334	87278600
BVP140 LED480-4S 41K3/740 PSD S D9	295	41.280	140	DALI	4000	912300024346	87290800
BVP140 LED480-4S 41K3/740 PSU S	295	41.280	140	-	4000	912300024338	87282300





# CoreLine LED luminaires

CoreLine tempo large

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Color Temp.	12NC	EOC code
	W	lm	lm/W	K		
BVP130 LED160-4S/740 PSU OFA52 ALU C1KC3	126	16.000	130	4000	912300023662	09641000
BVP130 LED160-4S/740 PSU S ALU C1KC3	126	16.000	130	4000	912300023665	09644100
BVP130 LED160-4S/730 A	136	16.000	121	3000	912300057770	90520000
BVP130 LED160-4S/730 S	136	16.000	121	3000	912300057773	90525500
BVP130 LED210-4S/740 PSU OFA52 ALU C1KC3	164	21.000	130	4000	912300023661	09640300
BVP130 LED210-4S/740 PSU S ALU C1KC3	164	21.000	130	4000	912300023664	09643400
BVP130 LED205-4S/730 A	170	20.500	121	3000	912300057769	90516300
BVP130 LED205-4S/730 S	170	20.500	121	3000	912300057772	90524800
BVP130 LED260-4S/740 PSU OFA52 ALU C1KC3	220	26.000	120	4000	912300023660	09639700
BVP130 LED260-4S/740 PSU S ALU C1KC3 T35	220	26.000	120	4000	912300023663	09642700
BVP130 LED260-4S/730 A	240	26.000	110	3000	912300057768	90517000
BVP130 LED260-4S/730 S	240	26.000	110	3000	912300057771	90523100

# CoreLine LED luminaires

CoreLine tempo medium

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Color Temp.	12NC	EOC code
	W	lm	lm/W	K		
BVP125 LED80-4S/740 PSU OFA52 ALU C1KC3	66	8000	124	4000	912300024002	45588000
BVP125 LED80-4S/740 PSU S ALU C1KC3	66	8000	124	4000	912300024004	45590300
BVP125 LED80-4S/730 PSU OFA52 ALU C1KC3	72	8000	114	3000	912300057765	90518700
BVP125 LED80-4S/730 PSU S ALU C1KC3	72	8000	114	3000	912300057767	90521700
BVP125 LED120-4S/740 PSU OFA52 ALU C1KC3	98	12.000	126	4000	912300024001	45587300
BVP125 LED120-4S/740 PSU S ALU C1KC3	98	12.000	126	4000	912300024003	45589700
BVP125 LED120-4S/730 PSU OFA52 ALU C1KC3	106	12.000	116	3000	912300057764	90515600
BVP125 LED120-4S/730 PSU S ALU C1KC3	106	12.000	116	3000	912300057766	90519400

CoreLine tempo small

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Color Temp.	12NC	EOC code
	W	lm	lm/W	K		
BVP110 LED42/NW A	38	4200	111	4000	911401555231	30635300
BVP110 LED42/NW S	38	4200	111	4000	911401555331	30636000

# CoreLine LED luminaires

CoreLine Malaga LED \*

[www.philips.com/coreline](http://www.philips.com/coreline)



Product Type	LED	Lumen Output	Efficiency	Color Temp.	12NC	EOC code
	W	lm	lm/W	K		
BRP101 LED37/740 I DM	29.6	3054	103	4000	910925865338	99815100
BRP101 LED37/740 II DM	29.6	3054	103	4000	910925865339	99816800
BRP102 LED55/740 I DM	39	4600	118	4000	910925865340	99817500
BRP102 LED55/740 II DM	39	4600	118	4000	910925865341	99818200
BRP102 LED75/740 I DM	56.5	6133	109	4000	910925865342	99819900
BRP102 LED75/740 II DM	56.5	6133	109	4000	910925865343	99820500
BRP102 LED110/740 I DM	83	9006	111	4000	910925865344	99821200
BRP102 LED110/740 II DM	83	9006	111	4000	910925865345	99822900

\*Additionally, the CoreLine malaga LED is available with Warm White LED modules (730) or Dynadimmer. Please contact your Signify representative for ordering options.

# Philips Ledinaire

Value



Office



Industry



Parking



Retail



Outdoor



Ledinaire recessed



Ledinaire recessed downlight



Ledinaire batten



Ledinaire batten



Ledinaire recessed downlight



Ledinaire floodlight



Ledinaire panel



Ledinaire slim downlight



Ledinaire waterproof



Ledinaire waterproof



Ledinaire slim downlight



Ledinaire surface-mounted



Ledinaire ClearAccent



Ledinaire highbay



Ledinaire wall mounted



Ledinaire Zadora



Ledinaire wall-mounted

Contents

Interact Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles & lusters

LED tubes

LED PL-lamps

TrueForce



# Real pros count on reliable solutions for daily demands

Philips Ledinaire is the essential range of trusted products for everyday lighting jobs that need good performance

Count on honest, hard-working solutions that deliver what they promise. Get trusted performance and the results you expect with Philips-tested key components. And that for a price that's on your side! Philips Ledinaire – the essential range of trusted products for everyday lighting jobs that need good performance.



## Trusted

What you need and expect is what you get. And that's a promise you can count on every time!



## Reliable

Proven Philips quality. Every key component is tested for a maximum of reliability and long-term performance.



## Great value

Perfect results don't need to blow the budget. With Ledinaire, you have great value lighting from the leader in LED.

Contents

Interact Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles & lusters

LED tubes

LED PL-lamps

TrueForce





# Philips Ledinaire floodlight

The robust and reliable choice in floodlights just got better with improved performance and more value for money.

- Extended wattage range, including 10W to 200W options
- Increased efficacy: up to 120 lm/W
- Improved motion sensor
- Even better value and performance
- 360° bracket for greater application variety
- 50,000 hrs lifetime (L70)
- Good finish and unobtrusive design
- Reliable driver, low early failures
- Light output to meet standard applications
- Easy to install, supplied with stripped cable

[Click here to see all products](#)



# Philips Ledinaire wall-mounted

Product highlights

Your go-to choice for honest, hard-working LED luminaires that deliver what they promise.

- Wide application coverage
- Modern, unobtrusive design
- IP44 rating perfect for indoor applications
- Optional motion detection and daylight sensor
- Two lumen packages and sizes: 1100lm 30cm, 1700lm 35cm
- Full transparent cover providing homogeneous light effect

[Click here to see all products](#)



Base plate that accommodates wire looping and wall-mounted wires



Optional motion and daylight detection unit

# Ledinaire LED luminaires

Easily make the switch to LED lighting without high investments. The Philips Ledinaire portfolio consists of 9 popular LED luminaires. Choose affordable, reliable and energy-efficient lighting from the leading name in LED.

## Ledinaire Panel Office compliant

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	K			
RC065B LED34S/830 PSU W60L60 OC	34	3400	100	3000	19	911401850782	53065299
RC065B LED34S/840 PSD W60L60 OC	34	3400	100	4000	19	911401850682	53064599
RC065B LED34S/840 PSU W60L60 OC	34	3400	100	4000	19	911401884580	38647499
RC065B LED34S/865 PSU W60L60 OC	34	3400	100	6500	19	911401884680	36204599
RC066B LED34S/840 PSU W62L62 OC	34	3400	100	4000	19	911401884780	36558999

## Ledinaire Panel Non-office compliant

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)





Product Type	LED	Lumen Output	Efficiency	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	K			
RC065B LED34S/830 PSU W60L60 NOC	34	3400	100	3000	22	911401850882	53066999
RC065B LED34S/840 PSU W60L60 NOC	34	3400	100	4000	22	911401885080	79180399
RC065B LED34S/865 PSU W60L60 NOC	34	3400	100	6500	22	911401885180	36206999
RC065B LED41S/840 PSU W60L60 NOC	44	4100	93	4000	23	911401823781	36926699



# Ledinaire LED luminaires

Ledinaire Panel - Accessory

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	12NC	EOC code
1 RC065Z SC	911401892680	36274899
2 RC065Z SMB W60L60	911401892480	36272499
3 RC065Z SME-3 WH	911401805681	36592399
2 RC066Z SMB W62L62	911401892580	36273199

Ledinaire Recessed Non-office compliant

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	°	K			
RC060B LED34S/840 PSU W60L60 NOC	34	3400	100	110	4000	25	911401850780	06958500
RC060B LED40S/840 PSU W60L60 NOC	40	4000	100	110	4000	25	911401842380	35040000

# Ledinaire LED luminaires

Ledinaire Surface-mounted Office compliant

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	°	K			
SM060C LED34S/840 PSU W20L120 OC	34	3400	100	80	4000	19	911401842280	35039400

Ledinaire Surface-mounted Non-office compliant

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	°	K			
SM060C LED34S/840 PSU W20L120 NOC	34	3400	100	110	4000	25	911401850680	06962200
SM060C LED40S/840 PSU W20L120 NOC	40	4000	100	110	4000	25	911401842480	35041700

# Ledinaire LED luminaires

Ledinaire Wall-mounted WL060V

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Color Temp.	Motion/Daylight sensor	12NC	EOC code
	W	lm	lm/W	°	K			
WL060V LED11S/830 PSU II WH	12	1100	90	120	3000		911401802080	33909299
WL060V LED11S/840 PSU II WH	12	1100	90	120	4000		911401802180	33910899
WL060V LED17S/830 PSU II WH	18.5	1700	90	120	3000		911401802280	33911599
WL060V LED17S/840 PSU II WH	18.5	1700	90	120	4000		911401802380	33912299
WL060V LED17S/830 PSU MDU II WH	19.5	1700	90	120	3000	Yes	911401802480	33913999
WL060V LED17S/840 PSU MDU II WH	19.5	1700	90	120	4000	Yes	911401802580	33914699

Ledinaire Wall-mounted WL070V

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	°	K			
WL070V LED11S/830 PSU II WH	11	1100	95	120	3000	22	911401826382	52266499
WL070V LED11S/840 PSU II WH	11	1100	100	120	4000	22	911401826482	52267199
WL070V LED17S/830 PSU II WH	17	1700	95	120	3000	22	911401826582	52268899
WL070V LED17S/840 PSU II WH	17	1700	100	120	4000	22	911401826682	52269599
WL070V LED17S/830 PSU MDU II WH	19	1700	85	120	3000	22	911401826782	52270199
WL070V LED17S/840 PSU MDU II WH	19	1700	85	120	4000	22	911401826882	52271899

# Ledinaire LED luminaires

Ledinaire Square Wall-mounted


[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Dimmable	Color Temp.	Integrated emergency 3 hours	Motion/Daylight sensor	12NC	EOC code
	W	lm	lm/W	°		K				
WL055V LED6S/830 PSR MDU WH	6	600	100	110	Yes	3000		Yes	911401862580	35409599
WL055V LED6S/830 PSU WH	6	600	100	110	No	3000			911401834880	34941199
WL055V LED6S/840 PSR MDU WH	6	600	100	110	Yes	4000		Yes	911401850580	35064699
WL055V LED6S/840 PSU WH	6	600	100	110	No	4000			911401834980	34942899
WL055V LED6S/830 PSU EL3 WH	8	600	75	110	No	3000	Yes		910505100602	96774199
WL055V LED6S/840 PSU EL3 WH	8	630	79	110	No	4000	Yes		910505100601	96773499

Ledinaire Batten

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	K			
BN021C LED5S/830 L300	5	480	96	3000	27	911401841882	52785099
BN021C LED5S/840 L300	5	540	108	4000	27	911401841782	52784399
BN021C LED10S/830 L600	10	960	96	3000	27	911401842082	52787499
BN021C LED10S/840 L600	10	1050	105	4000	27	911401841982	52786799
BN021C LED14S/830 L900	15	1450	96.7	3000	27	911401842282	52789899
BN021C LED15S/840 L900	15	1600	106.7	4000	27	911401842182	52788199
BN021C LED19S/830 L1200	20	1900	95	3000	27	911401842482	52791199
BN021C LED20S/840 L1200	20	2100	105	4000	27	911401842382	52790499
BN021C LED24S/830 L1500	24	2400	100	3000	27	911401842682	52793599
BN021C LED25S/840 L1500	24	2600	108.3	4000	27	911401842582	52792899

# Ledinaire LED luminaires

Ledinaire Batten - Accessory

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



IP IP20  
IK IK02  
10 PACK

Product Type	12NC	EOC code
BN021Z C600	911401846482	52854399

Ledinaire High-bay

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



L65 at 50,000  
IP IP65  
IK IK06  
3 Years  
1 PACK

Product Type	LED	Lumen Output	Efficiency	Color Temp.	UGR	12NC	EOC code
	W	lm	lm/W	K			
BY020P G2 LED105S/840 PSU WB GR	94	10.500	112	4000	28	911401642407	52405700
BY021P G2 LED205S/840 PSU WB GR	168	20.500	122	4000	-	911401642307	52404000

# Ledinaire LED luminaires

Ledinaire High-bay - Accessory

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	12NC	EOC code
BY020Z G2 ALU	911401657907	53017199
BY021Z G2 ALU	911401658007	53016499

Ledinaire Waterproof

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Color Temp.	12NC	EOC code
	W	lm	lm/W	°	K		
WT060C LED18S/840 PSU L600	15	1800	120	120	4000	911401876480	36007299
WT060C LED25S/840 PSU L1200	20	2500	120	120	4000	911401892780	36291599
WT060C LED25S/840 PSU TW1 L1200	20	2500	120	120	4000	911401892880	36292299
WT060C LED34S/840 PSU L1500	28	3400	120	120	4000	911401892980	36293999
WT060C LED34S/840 PSU TW1 L1500	28	3400	120	120	4000	911401893080	36294699
WT060C LED36S/840 PSU L1200	30	3600	120	120	4000	911401876680	36009699
WT060C LED36S/840 PSU TW1 L1200	30	3600	120	120	4000	911401876780	36010299
WT060C LED36S/865 PSU L1200	30	3600	120	120	6500	911401877280	36015799
WT060C LED56S/840 PSU L1500	46	5600	120	120	4000	911401876880	36011999
WT060C LED56S/840 PSU TW1 L1500	46	5600	120	120	4000	911401876980	36012699
WT060C LED56S/865 PSU L1500	46	5600	120	120	6500	911401877480	36017199

# Ledinaire LED luminaires

Ledinaire Waterproof Tube Housing

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	12NC	EOC code
WT050C 1xTLED L1200	911401807381	36602999
WT050C 1xTLED L1500	911401807581	36604399
WT050C 2xTLED L1200	911401807481	36603699
WT050C 2xTLED L1500	911401807681	36605099

Ledinaire SlimDownlight DN065B

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Color Temp.	12NC	EOC code
	W	lm	lm/W	K		
DN065B G3 LDNR LED10/830 10.5W D150 RD	11	1000	90.00	3000	929002663832	32890700
DN065B G3 LDNR LED10/830 10.5W L150 SQ	11	1000	90.00	3000	929002664232	32898300
DN065B G3 LDNR LED10/840 10.5W D150 RD	11	1000	90.00	4000	929002663932	32892100
DN065B G3 LDNR LED10/840 10.5W L150 SQ	11	1000	90.00	4000	929002664332	32900300
DN065B G3 LDNR LED10/865 10.5W D150 RD	11	1000	90.00	6500	929003165102	35207000
DN065B G3 LDNR LED10/CCT 10.5W D150 RD	11	1000	90.00	4000	929002664832	32910200
DN065C G3 LDNR LED10/830 10.5W D175 RD	11	1000	90.00	3000	929002664432	32902700
DN065C G3 LDNR LED10/840 10.5W D175 RD	11	1000	90.00	4000	929002664532	32904100
DN065B G3 LDNR LED20/830 19.5W D200 RD	20	2000	100.00	3000	929002664032	32894500
DN065B G3 LDNR LED20/840 19.5W D200 RD	20	2000	100.00	4000	929002664132	32896900
DN065B G3 LDNR LED20/865 19.5W D200 RD	20	2000	100.00	6500	929003165202	35209400
DN065B G3 LDNR LED20/CCT 19.5W D200 RD	20	2000	100.00	4000	929002664932	32912600
DN065C G3 LDNR LED20/830 19.5W D225 RD	20	2000	100.00	3000	929002664632	32906500
DN065C G3 LDNR LED20/840 19.5W D225 RD	20	2000	100.00	4000	929002664732	32908900





# Ledinaire LED luminaires

Ledinaire Recessed Downlight

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



IP IK 5  
IP20/54 IK03 Years 8/12 PACK

NEW

Product Type	LED	Lumen Output	Efficiency	Color Temp.	12NC	EOC code
	W	lm	lm/W	K		
DN070B LED12/830 12W 220-240V D150 RD EU	12	1200	96.00	3000	929003165332	35398500
DN070B LED12/840 12W 220-240V D150 RD EU	12	1200	96.00	4000	929003165432	35400500
DN070B LED24/850 24W 220-240V D200 RD EU	24	2400	94.00	5000	929003247332	45260200
DN070B LED24/830 24W 220-240V D200 RD EU	24	2400	94.00	3000	929003165532	35402900
DN070B LED24/840 24W 220-240V D200 RD EU	24	2400	94.00	4000	929003165632	35404300

Ledinaire Zadora LED

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



IP IK 3  
IP20 IK02 Years 36 PACK

Product Type	LED	Lumen Output	Efficiency	Dimmable	Color Temp.	12NC	EOC code
	W	lm	lm/W		K		
RS049B LED-MS-40-5W-2700-GU10 ALU 50W	5	355	73	Yes	2700	912401483106	07014799
RS049B LED-MS-40-5W-2700-GU10 WH 50W	5	355	73	Yes	2700	912401483104	07012399
RS049B LED-MS-40-5W-3000-GU10 ALU 50W	5	365	78	Yes	3000	912401483108	07016199
RS049B LED-MS-40-5W-3000-GU10 WH 50W	5	365	75	Yes	3000	912401483107	07015499
RS049B LED-MS-40-5W-4000-GU10 WH 50W	5	380	78	Yes	4000	912401483105	07013099

# Ledinaire LED luminaires

Ledinaire ClearAccent RS060/RS061

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)




Product Type	LED		Efficiency	Dimmable	Color Temp.	12NC	EOC code
	W	lm	lm/W		K		
RS060B G2 LDNR LED5-36/827 PSR II WH	6	500	83.00	Yes	2700	929002669632	33117400
RS060B G2 LDNR LED5-36/827 WH TW	6	500	83.00	Yes	2700	929002662032	33111200
RS060B G2 LDNR LED5-36/830 PSR II WH	6	500	83.00	Yes	3000	929002669732	33119800
RS060B G2 LDNR LED5-36/830 WH TW	6	500	83.00	Yes	3000	929002662132	33113600
RS060B G2 LDNR LED5-36/840 PSR II WH	6	500	91.00	Yes	4000	929002669832	33121100
RS060B G2 LDNR LED5-36/840 WH TW	6	500	91.00	Yes	4000	929002662232	33115000
RS061B G2 LDNR LED5-36/827 PSR II WH	6	500	83.00	Yes	2700	929002669932	33123500
RS061B G2 LDNR LED5-36/827 WH TW	6	500	83.00	Yes	2700	929002662332	33105100
RS061B G2 LDNR LED5-36/830 PSR II WH	6	500	83.00	Yes	3000	929002670032	33125900
RS061B G2 LDNR LED5-36/830 WH TW	6	500	83.00	Yes	3000	929002662432	33107500
RS061B G2 LDNR LED5-36/840 PSR II WH	6	500	91.00	Yes	4000	929002670132	33127300
RS061B G2 LDNR LED5-36/840 WH TW	6	500	91.00	Yes	4000	929002662532	33109900

# Ledinaire LED luminaires

Ledinaire floodlights gen3

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)




Product Type	LED	Lumen Output	Efficiency	Color Temp.	IK rating	Warranty	12NC	EOC code
	W	lm	lm/W	K		Years		
1 BVP164 LED11/830 PSU 10W SWB CE	10	1100	110	3000	IK07	3	911401841483	53364699
2 BVP164 LED11/830 PSU 10W SWB MDU CE	10	1100	110	3000	IK07	3	911401883683	53482799
1 BVP164 LED12/840 PSU 10W SWB CE	10	1200	120	4000	IK07	3	911401851483	53356199
2 BVP164 LED12/840 PSU 10W SWB MDU CE	10	1200	120	4000	IK07	3	911401883783	53481099
1 BVP164 LED12/865 PSU 10W SWB CE	10	1200	120	6500	IK07	3	911401861483	53348699
3 BVP164 LED22/830 PSU 20W SWB CE	20	2200	110	3000	IK07	3	911401842483	53363999
4 BVP164 LED22/830 PSU 20W SWB MDU CE	20	2200	110	3000	IK07	3	911401883983	53480399
3 BVP164 LED24/840 PSU 20W SWB CE	20	2400	120	4000	IK07	3	911401852483	53355499
4 BVP164 LED24/840 PSU 20W SWB MDU CE	20	2400	120	4000	IK07	3	911401884083	53479799
3 BVP164 LED24/865 PSU 20W SWB CE	20	2400	120	6500	IK07	3	911401862483	53347999
3 BVP164 LED33/830 PSU 30W SWB CE	30	3300	110	3000	IK07	3	911401843483	53362299
4 BVP164 LED33/830 PSU 30W SWB MDU CE	30	3300	110	3000	IK07	3	911401884283	53478099
3 BVP164 LED36/840 PSU 30W SWB CE	30	3600	120	4000	IK07	3	911401853483	53354799
4 BVP164 LED36/840 PSU 30W SWB MDU CE	30	3600	120	4000	IK07	3	911401884383	53477399
3 BVP164 LED36/865 PSU 30W SWB CE	30	3600	120	6500	IK07	3	911401863483	53346299
5 BVP164 LED55/830 PSU 50W SWB CE	50	5500	110	3000	IK07	3	911401844483	53361599
4 BVP164 LED55/830 PSU 50W SWB MDU CE	50	5500	110	3000	IK07	3	911401884583	53476699
5 BVP164 LED60/840 PSU 50W SWB CE	50	6000	120	4000	IK07	3	911401854483	53353099
4 BVP164 LED60/840 PSU 50W SWB MDU CE	50	6000	120	4000	IK07	3	911401884683	53475999
5 BVP164 LED60/865 PSU 50W SWB CE	50	6000	120	6500	IK07	3	911401864483	53345599
6 BVP164 LED70/830 PSU 70W AWB CE	70	7300	105	3000	IK07	3	911401896083	53633399
6 BVP164 LED73/840 PSU 70W AWB CE	70	7300	105	4000	IK07	3	911401896183	53496499
5 BVP164 LED77/830 PSU 70W SWB CE	70	7700	110	3000	IK07	3	911401845483	53360899
4 BVP164 LED77/830 PSU 70W SWB MDU CE	70	7700	110	3000	IK07	3	911401884883	53474299
5 BVP164 LED84/840 PSU 70W SWB CE	70	8400	120	4000	IK07	3	911401855483	53352399
4 BVP164 LED84/840 PSU 70W SWB MDU CE	70	8400	120	4000	IK07	3	911401884983	53473599
5 BVP164 LED84/865 PSU 70W SWB CE	70	8400	120	6500	IK07	3	911401865483	53344899
6 BVP165 LED100/830 PSU 100W AWB CE	100	10.500	105	3000	IK07	3	911401896383	53632699
6 BVP165 LED105/840 PSU 100W AWB CE	100	10.500	105	4000	IK07	3	911401896483	53495799
7 BVP165 LED110/830 PSU 100W SWB CE	100	11.000	110	3000	IK08	5	911401846483	53359299

# Ledinaire LED luminaires

Ledinaire floodlights gen3 - Continued

[www.lighting.philips.com/main/products/ledinaire](http://www.lighting.philips.com/main/products/ledinaire)



Product Type	LED	Lumen Output	Efficiency	Color Temp.	IK rating	Warranty	12NC	EOC code
	W	lm	lm/W	K		Years		
1 BVP165 LED120/840 PSU 100W SWB CE	100	12.000	120	4000	IK07	3	911401856483	53351699
1 BVP165 LED120/865 PSU 100W SWB CE	100	12.000	120	6500	IK07	3	911401866483	53343199
2 BVP165 LED150/830 PSU 150W AWB CE	150	15.700	105	3000	IK07	3	911401896683	53631999
2 BVP165 LED157/840 PSU 150W AWB CE	150	15.700	105	4000	IK07	3	911401896783	53494099
1 BVP165 LED165/830 PSU 150W SWB CE	150	16.500	110	3000	IK08	5	911401847483	53358599
1 BVP165 LED180/840 PSU 150W SWB CE	150	18.000	120	4000	IK07	3	911401857483	53350999
1 BVP165 LED180/865 PSU 150W SWB CE	150	18.000	120	6500	IK07	3	911401867483	53342499
2 BVP165 LED200/830 PSU 200W AWB CE	200	21.000	105	3000	IK07	3	911401896983	53630299
2 BVP165 LED210/840 PSU 200W AWB CE	200	21.000	105	4000	IK07	3	911401897083	53493399
1 BVP165 LED220/830 PSU 200W SWB CE	200	22.000	110	3000	IK08	5	911401848483	53357899
1 BVP165 LED240/840 PSU 200W SWB CE	200	24.000	120	4000	IK07	3	911401858483	53349399
1 BVP165 LED240/865 PSU 200W SWB CE	200	24.000	120	6500	IK07	3	911401868483	53341799

# Philips LED lamps

## Highlight products



Office



MASTER Value LEDspot  
GU10



Warehouse



CorePro LEDspot  
GU10



Hospitality



MASTER LEDspot ExpertColor LV  
MR16



Retail



MASTER LEDspot ExpertColor MV  
GU10



CorePro glass high lumen LEDbulb  
A67 150W



MASTER LEDspot ExpertColor  
AR111



MASTER LEDspot ExpertColor LV  
MR16



CorePro glass LEDbulb  
A67 150W



MASTER Value decorative LEDbulb  
ST64 25W

Contents

Interact  
Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles  
& lusters

LED tubes

LED  
PL-lamps

TrueForce





# Real pros put LED lamps in the spotlight

From hotels to meeting rooms, from LED spots to decorative LED bulbs – the wide range of Philips LED lamps offers a lighting solution for every style and function.

Creating the perfect ambiance for any room and any occasion has never been easier. Philips LED lamps combine classic design with superior technology designed to offer exceptional light quality and high color consistency.

Our innovative features, like DimTone and SceneSwitch, offer the flexibility to go from functional lighting to an inviting and cosy atmosphere with the simple flick of a switch.

Choose CorePro LEDlamps for everyday replacement of conventional lighting in general applications. The MASTER Value range offers a broad selection of dimmable, high-performance LED lamps. With customized spectrum, high CRI, and deep dimming

feature, the MASTER range delivers superior light and the perfect ambience. MasterConnect LEDspots are Interact Ready and can be integrated into smart lighting systems for personal and automated light control.



#### Fast and easy replacements

Philips LED lamps are designed as a 1-on-1 replacement for currently installed conventional lighting



#### High quality of light

- No flickering
- True constant colors with high CRI
- Maximum dimming compatibility



#### Energy efficiency and long lifetimes

- 69% more energy efficient than conventional lamps
- Up to 40,000 hours lifetime – for peace of mind and less maintenance cost



#### Wide range

The right shape and technology for every kind of application and budget

Contents

Interact Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles & lusters

LED tubes


LED PL-lamps

TrueForce



The Philips range tiering is now valid for all our LED lamps – bulbs, candles and lusters included!

Range tiering





# Designed for your needs – inside and out

We always strive to make your job easier and less complex. That's why we are introducing a new packaging for our LED lamps – featuring a modern design that lets you identify product benefits, key specifications and range tiering at first glance. The new energy label brings more transparency about energy efficiency and is compliant with the EU's Ecodesign Regulation (SLR).

The color coding of the new packaging represents the range tiering and makes it really easy to quickly find the LED lamps that suit your demands and budget.





# Philips MasterConnect LEDspots

Take the first step into connected lighting with Philips MasterConnect LEDspots.

MasterConnect LEDspots are smart retrofit LED spots that give you an easy and seamless way to upgrade and embrace all benefits of connected lighting.

Thanks to the proven wireless connected technology, MasterConnect LEDspots maximize energy savings, while providing wireless and automated light for your comfort and convenience.

- Perfect fit design to retrofit halogen lamps
- 90% energy savings compared with halogen lamps
- Color spectrum that replicates halogen, CRI 90
- Lifetime of up to 25,000 hrs
- Perfect for hospitality, restaurant and retail

interact ready.

Works with Interact and Philips MasterConnect apps



Add switches for wireless lighting



Add sensors for automated lighting



Add a gateway for connected lighting

## Real pros upgrade to ultra-efficiency

Product highlights

Introducing the first Philips A-class LED bulb: your choice for next level savings and sustainability.

- Ultra efficient with up to 210lm/W
- Saves up to 60% energy compared to a standard LED bulb
- Ultra long lifetime of 50k hours
- Very short payback period of only 5 months<sup>1</sup>
- Full glass design
- High-quality and comfortable light



A-class rating<sup>2</sup> for first-rate savings



<sup>1</sup>When upgrading from conventional halogen bulbs (42W, 2k hrs lifetime)

<sup>2</sup>According to the updated European Energy Labelling regulation (09/2021)

# LED spots

LED lamps save you up to 69% energy and offer the same light quality as conventional lamps. Philips MASTER LED lamps provide you with constant colors, high performance and maximum dimming compatibility. CorePro lamps are good for energy savings of up to 69% and have a lifespan of 15,000 hours. The complete range of Philips LED lamps is designed as a 1-on-1 replacement for currently installed conventional lighting.

## SceneSwitch LEDspot

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	CRI	Color Temp.	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	lm/W	Intensity	Angle								
		W	W	lm	lm/W	cd	°		K	Hrs.					
NEW	LED SceneSwitch 50W GU10 WW 36D ND SRT4	50	4.8	355	73.00	600	36	80	2700-2500-2200	15.000	50	54	F	929002981857	30776600
NEW	LED SceneSwitch 50W GU10 WW 36D RF ND SRT4	50	4.8	355	73.00	600	36	80	2700-2500-2200	15.000	50	54	F	929002981855	30778000

# LED spots

MASTER LEDspot ExpertColor LV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Traditional		LED		Efficiency	Luminous Intensity	Beam Angle	Dimmable	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
		W	W	lm	lm/W												
NEW	1 MASTER LED ExpertColor 6.7-35W MR16 927 10D	35	6.7	410	61.00	4600	10	Only with specific dimmers	97	2700	40.000	50.5	46	G	929003078802	35847800	
NEW	2 MASTER LED ExpertColor 6.7-35W MR16 927 24D	35	6.7	420	62.00	2100	24	Only with specific dimmers	97	2700	40.000	50.5	46	G	929003079102	35853900	
NEW	2 MASTER LED ExpertColor 6.7-35W MR16 927 36D	35	6.7	420	62.00	1300	36	Only with specific dimmers	97	2700	40.000	50.5	46	G	929003079402	35859100	
NEW	2 MASTER LED ExpertColor 6.7-35W MR16 927 60D	35	6.7	400	59.00	410	60	Only with specific dimmers	97	2700	40.000	50.5	46	G	929003078502	35877500	
NEW	1 MASTER LED ExpertColor 6.7-35W MR16 930 10D	35	6.7	430	64.00	4800	10	Only with specific dimmers	97	3000	40.000	50.5	46	G	929003078902	35849200	
NEW	2 MASTER LED ExpertColor 6.7-35W MR16 930 24D	35	6.7	440	65.00	2200	24	Only with specific dimmers	97	3000	40.000	50.5	46	G	929003079202	35855300	
NEW	2 MASTER LED ExpertColor 6.7-35W MR16 930 36D	35	6.7	440	65.00	1400	36	Only with specific dimmers	97	3000	40.000	50.5	46	G	929003079502	35861400	
NEW	2 MASTER LED ExpertColor 6.7-35W MR16 930 60D	35	6.7	440	65.00	440	60	Only with specific dimmers	97	3000	40.000	50.5	46	G	929003078602	35843000	
NEW	1 MASTER LED ExpertColor 6.7-35W MR16 940 10D	35	6.7	440	65.00	4800	10	Only with specific dimmers	97	4000	40.000	50.5	46	G	929003079002	35851500	
NEW	2 MASTER LED ExpertColor 6.7-35W MR16 940 24D	35	6.7	460	68.00	2200	24	Only with specific dimmers	97	4000	40.000	50.5	46	G	929003079302	35857700	
NEW	2 MASTER LED ExpertColor 6.7-35W MR16 940 36D	35	6.7	460	68.00	1400	36	Only with specific dimmers	97	4000	40.000	50.5	46	G	929003079602	35863800	
NEW	2 MASTER LED ExpertColor 6.7-35W MR16 940 60D	35	6.7	440	65.00	440	60	Only with specific dimmers	97	4000	40.000	50.5	46	G	929003078702	35845400	
NEW	1 MASTER LED ExpertColor 7.5-43W MR16 927 24D	43	7.5	485	64.00	2400	24	Only with specific dimmers	92	2700	40.000	50.5	46	G	929003079702	35865200	
NEW	1 MASTER LED ExpertColor 7.5-43W MR16 927 36D	43	7.5	485	64.00	1400	36	Only with specific dimmers	92	2700	40.000	50.5	46	G	929003080002	35871300	
NEW	1 MASTER LED ExpertColor 7.5-43W MR16 930 24D	43	7.5	500	66.00	2600	24	Only with specific dimmers	92	3000	40.000	50.5	46	G	929003079802	35867600	
NEW	1 MASTER LED ExpertColor 7.5-43W MR16 930 36D	43	7.5	500	66.00	1550	36	Only with specific dimmers	92	3000	40.000	50.5	46	G	929003080102	35873700	
NEW	1 MASTER LED ExpertColor 7.5-43W MR16 940 24D	43	7.5	520	69.00	2800	24	Only with specific dimmers	92	4000	40.000	50.5	46	G	929003079902	35869000	
NEW	1 MASTER LED ExpertColor 7.5-43W MR16 940 36D	43	7.5	520	69.00	1650	36	Only with specific dimmers	92	4000	40.000	50.5	46	G	929003080202	35875100	

# LED spots

MASTER LEDspot ExpertColor MV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W	Intensity	Angle			Temp.						
	W	W	lm	lm/W	cd	°			K	Hrs.					
MASTER LED ExpertColor 3.9-35W GU10 927 25D	35	3.9	265	67.95	700	25	Only with specific dimmers	97	2700	40.000	50	54	G	929001346402	70749400
MASTER LED ExpertColor 3.9-35W GU10 927 36D	35	3.9	265	67.95	540	36	Only with specific dimmers	97	2700	40.000	50	54	G	929001346702	70755500
MASTER LED ExpertColor 3.9-35W GU10 930 25D	35	3.9	280	71.00	750	25	Only with specific dimmers	97	3000	40.000	50	54	G	929001346502	70751700
MASTER LED ExpertColor 3.9-35W GU10 930 36D	35	3.9	280	71.00	560	36	Only with specific dimmers	97	3000	40.000	50	54	G	929001346802	70757900
MASTER LED ExpertColor 3.9-35W GU10 940 25D	35	3.9	300	76.00	800	25	Only with specific dimmers	97	4000	40.000	50	54	F	929001346602	70753100
MASTER LED ExpertColor 3.9-35W GU10 940 36D	35	3.9	300	76.00	600	36	Only with specific dimmers	97	4000	40.000	50	54	F	929001346902	70759300
NEW MASLED ExpertColor 5.5-50W GU10 927 25DUK	50	5.5	355	64.00	1000	25	Only with specific dimmers	97	2700	40.000	50	54	G	929001347099	70761601
NEW MASLED ExpertColor 5.5-50W GU10 927 36DUK	50	5.5	355	64.00	800	36	Only with specific dimmers	97	2700	40.000	50	54	G	929001347398	70767801
NEW MASLED ExpertColor 5.5-50W GU10 930 36DUK	50	5.5	375	68.00	800	36	Only with specific dimmers	97	3000	40.000	50	54	G	929001347499	70769201
MASTER LED ExpertColor 5.5-50W GU10 927 25D	50	5.5	355	64.55	1000	25	Only with specific dimmers	97	2700	40.000	50	54	G	929001347002	70761600
MASTER LED ExpertColor 5.5-50W GU10 927 36D	50	5.5	355	64.55	800	36	Only with specific dimmers	97	2700	40.000	50	54	G	929001347302	70767800
MASTER LED ExpertColor 5.5-50W GU10 930 25D	50	5.5	375	68.00	1000	25	Only with specific dimmers	97	3000	40.000	50	54	G	929001347102	70763000
MASTER LED ExpertColor 5.5-50W GU10 930 36D	50	5.5	375	68.00	800	36	Only with specific dimmers	97	3000	40.000	50	54	G	929001347402	70769200
MASTER LED ExpertColor 5.5-50W GU10 940 25D	50	5.5	400	72.00	1050	25	Only with specific dimmers	97	4000	40.000	50	54	F	929001347202	70765400
MASTER LED ExpertColor 5.5-50W GU10 940 36D	50	5.5	400	72.00	800	36	Only with specific dimmers	97	4000	40.000	50	54	F	929001347502	70771500

# LED spots

MASTER LEDspot ExpertColor AR111

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	Intensity	Angle	Temp.			diameter						
		W	W	lm	lm/W	cd	°			K	Hrs.					
NEW	1 MAS ExpertColor 10.8-50W 927 AR111 24D	50	10.8	600	55.00	3000	24	Only with specific dimmers	95	2700	40.000	111	61	G	929003043302	33393200
NEW	1 MAS ExpertColor 10.8-50W 927 AR111 40D	50	10.8	600	55.00	1200	40	Only with specific dimmers	95	2700	40.000	111	61	G	929003043402	33395600
NEW	2 MAS ExpertColor 10.8-50W 927 AR111 9D	50	10.8	600	55.00	8000	9	Only with specific dimmers	95	2700	40.000	111	61	G	929003043202	33391800
NEW	1 MAS ExpertColor 10.8-50W 930 AR111 24D	50	10.8	620	57.00	3200	24	Only with specific dimmers	95	3000	40.000	111	61	G	929003043602	33399400
NEW	1 MAS ExpertColor 10.8-50W 930 AR111 40D	50	10.8	620	57.00	1200	40	Only with specific dimmers	95	3000	40.000	111	61	G	929003043702	33401400
NEW	2 MAS ExpertColor 10.8-50W 930 AR111 9D	50	10.8	620	57.00	8000	9	Only with specific dimmers	95	3000	40.000	111	61	G	929003043502	33397000
NEW	1 MAS ExpertColor 14.8-75W 927 AR111 24D	75	14.8	875	59.00	3000	24	Only with specific dimmers	95	2700	40.000	111	61	G	929003042602	33379600
NEW	1 MAS ExpertColor 14.8-75W 927 AR111 45D	75	14.8	875	59.00	1200	45	Only with specific dimmers	95	2700	40.000	111	61	G	929003042702	33381900
NEW	1 MAS ExpertColor 14.8-75W 930 AR111 24D	75	14.8	875	59.00	3000	24	Only with specific dimmers	95	3000	40.000	111	61	G	929003042802	33383300
NEW	1 MAS ExpertColor 14.8-75W 930 AR111 45D	75	14.8	875	59.00	1300	45	Only with specific dimmers	95	3000	40.000	111	61	G	929003042902	33385700
NEW	1 MAS ExpertColor 14.8-75W 940 AR111 24D	75	14.8	950	64.00	3300	24	Only with specific dimmers	95	4000	40.000	111	61	G	929003043002	33387100
NEW	1 MAS ExpertColor 14.8-75W 940 AR111 45D	75	14.8	950	64.00	1400	45	Only with specific dimmers	95	4000	40.000	111	61	G	929003043102	33389500
	1 MAS LEDspotLV D 20-100W 927 AR111 24D	100	20	1270	63.00	4300	24	Only with specific dimmers	91	2700	25.000	111	62	G	929002050302	70511400
	1 MAS LEDspotLV D 20-100W 927 AR111 45D	100	20	1270	63.00	2100	45	Only with specific dimmers	91	2700	25.000	111	62	G	929002050402	70513800
	1 MAS LEDspotLV D 20-100W 930 AR111 24D	100	20	1270	63.00	4600	24	Only with specific dimmers	91	3000	25.000	111	62	G	929002050502	70515200
	1 MAS LEDspotLV D 20-100W 930 AR111 45D	100	20	1270	63.00	2200	45	Only with specific dimmers	91	3000	25.000	111	62	G	929002050602	70517600
	1 MAS LEDspotLV D 20-100W 940 AR111 24D	100	20	1270	63.00	5000	24	Only with specific dimmers	91	4000	25.000	111	62	G	929002050702	70519000
	1 MAS LEDspotLV D 20-100W 940 AR111 45D	100	20	1270	63.00	2300	45	Only with specific dimmers	91	4000	25.000	111	62	G	929002050802	70521300

# LED spots

MASTER VALUE LEDspot LV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Traditional	LED	Lumen Output	Efficiency	Luminous Intensity	Beam Angle	Dimmable	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
		W	W	lm	lm/W	cd	°			K	Hrs.					
NEW	1 MASTER LEDspotLV 3.5-20W 827 MR11 24D	20	3.5	200	57.00	1000	24	No	80	2700	40.000	35.1	39.5	G	929003087002	35990100
NEW	2 MASTER LEDspotLV DimTone 5.8-35W MR16 36D	35	5.8	345	59.00	800	36	Only with specific dimmers	90	2200-2700	25.000	50.5	45.5	G	929002493102	30730800
	2 MASTER LED spot VLE D 5.8-35W MR16 927 36D	35	5.8	450	77.00	1300	36	Only with specific dimmers	90	2700	25.000	50.5	45.5	G	929002492502	30718600
	2 MASTER LED spot VLE D 5.8-35W MR16 927 60D	35	5.8	450	77.00	600	60	Only with specific dimmers	90	2700	25.000	50.5	45.5	G	929002492802	30724700
	2 MASTER LED spot VLE D 5.8-35W MR16 930 36D	35	5.8	460	79.00	1300	36	Only with specific dimmers	90	3000	25.000	50.5	45.5	F	929002492602	30720900
	2 MASTER LED spot VLE D 5.8-35W MR16 930 60D	35	5.8	460	79.00	600	60	Only with specific dimmers	90	3000	25.000	50.5	45.5	F	929002492902	30726100
	2 MASTER LED spot VLE D 5.8-35W MR16 940 36D	35	5.8	490	84.00	1200	36	Only with specific dimmers	90	4000	25.000	50.5	45.5	F	929002492702	30722300
	2 MASTER LED spot VLE D 5.8-35W MR16 940 60D	35	5.8	490	84.00	550	60	Only with specific dimmers	90	4000	25.000	50.5	45.5	F	929002493002	30728500
NEW	3 MASTER LEDspotLV DimTone 7.5-50W MR16 36D	50	7.5	621	82.00	1100	36	Only with specific dimmers	90	2200-2700	25.000	50.5	45.5	F	929002493802	30744500
	2 MASTER LED SPOT VLE D 7.5-50W MR16 927 36D	50	7.5	621	82.00	1600	36	Only with specific dimmers	90	2700	25.000	50.5	45.5	F	929002493202	30732200
	4 MASTER LED SPOT VLE D 7.5-50W MR16 927 60D	50	7.5	621	82.00	750	60	Only with specific dimmers	90	2700	25.000	50.5	45.5	F	929002493502	30738400
	2 MASTER LED SPOT VLE D 7.5-50W MR16 930 36D	50	7.5	630	84.00	1600	36	Only with specific dimmers	90	3000	25.000	50.5	45.5	F	929002493302	30734600
	4 MASTER LED SPOT VLE D 7.5-50W MR16 930 60D	50	7.5	630	84.00	800	60	Only with specific dimmers	90	3000	25.000	50.5	45.5	F	929002493602	30740700
	2 MASTER LED SPOT VLE D 7.5-50W MR16 940 36D	50	7.5	660	88.00	1500	36	Only with specific dimmers	90	4000	25.000	50.5	45.5	F	929002493402	30736000
	4 MASTER LED SPOT VLE D 7.5-50W MR16 940 60D	50	7.5	660	88.00	770	60	Only with specific dimmers	90	4000	25.000	50.5	45.5	F	929002493702	30742100

# LED spots

MASTER VALUE LEDspot MV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradit	LED	Lumen	Efficiency	Luminous	Beam	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		ional	W	Output	Intensity	Angle	Temp.			diameter						
		W	W	lm	lm/W	cd	°			K	Hrs.					
NEW	1 MASTER LED spot VLE D 3.7-35W GU10 927 36D	35	3.7	270	72.00	500	36	Only with specific dimmers	90	2700	25.000	50	54	F	929002979402	30811400
NEW	1 MASTER LED spot VLE D 3.7-35W GU10 927 60D	35	3.7	270	72.00	300	60	Only with specific dimmers	90	2700	25.000	50	54	F	929002979802	31226500
NEW	1 MASTER LED spot VLE D 3.7-35W GU10 930 60D	35	3.7	270	72.00	300	60	Only with specific dimmers	90	3000	25.000	50	54	F	929002979902	31230200
NEW	1 MASTER LED spot VLE DT 3.7-35W GU10 927 36D	35	3.7	270	72.00	500	36	Only with specific dimmers	90	2200-2700	25.000	50	54	F	929002979702	31228900
	2 MASTER LED spot VLE D 3.7-35W GU10 930 36D	35	3.7	270	81.08	500	36	Only with specific dimmers	90	3000	25.000	50	54	F	929001348302	70775300
	2 MASTER LED spot VLE D 3.7-35W GU10 940 36D	35	3.7	285	85.14	500	36	Only with specific dimmers	90	4000	25.000	50	54	F	929001348402	70777700
	2 MASTER LED spot VLE D 3.7-35W GU10 940 60D	35	3.7	285	85.14	350	60	Only with specific dimmers	90	4000	25.000	50	54	F	929001348702	70783800
NEW	3 MASTER LEDspot VLE D 4.7-50W GU10 82736D5CT	50	4.7	345	73.00	650	36	Only with specific dimmers	80	2700	25.000	50	54	F	929002995452	31212800
NEW	3 MASTER LEDspot VLE D 4.7-50W GU10 83036D5CT	50	4.7	345	73.00	650	36	Only with specific dimmers	80	3000	25.000	50	54	F	929002995552	31214200
NEW	1 MASTER LED spot VLE D 4.8-50W GU10 927 36D	50	4.8	355	73.00	650	36	Only with specific dimmers	90	2700	25.000	50	54	F	929002980102	30813800
NEW	2 MASTER LED spot VLEDT4.9-50W GU10 927 36DUK	50	4.9	355	72.00	650	36	Yes	90	2200-2700	25.000	50	54	F	929001350399	70811801
NEW	2 MASTER LEDspotVLE D 4.9-50W GU10 930 36D UK	50	4.9	365	74.00	650	36	Yes	90	3000	25.000	50	54	F	929001348998	70787601
NEW	2 MASTER LEDspotVLE D 4.9-50W GU10 940 36D UK	50	4.9	380	77.00	700	36	Yes	90	4000	25.000	50	54	F	929001349099	70789001
	2 MASTER LED spot VLE D 4.9-50W GU10 927 60D	50	4.9	355	80.61	400	60	Only with specific dimmers	90	2700	25.000	50	54	F	929001349102	70791300
	2 MASTER LED spot VLE D 4.9-50W GU10 930 36D	50	4.9	365	82.65	650	36	Only with specific dimmers	90	3000	25.000	50	54	F	929001348902	70787600
	2 MASTER LED spot VLE D 4.9-50W GU10 930 60D	50	4.9	365	82.65	400	60	Only with specific dimmers	90	3000	25.000	50	54	F	929001349202	70793700
	2 MASTER LED spot VLE D 4.9-50W GU10 940 36D	50	4.9	380	85.71	700	36	Only with specific dimmers	90	4000	25.000	50	54	F	929001349002	70789000
	2 MASTER LED spot VLE D 4.9-50W GU10 940 60D	50	4.9	380	85.71	400	60	Only with specific dimmers	90	4000	25.000	50	54	F	929001349302	70795100
	2 MASTER LED spot VLE DT 4.9-50W GU10 927 36D	50	4.9	355	80.61	650	36	Only with specific dimmers	90	2700	25.000	50	54	F	929001350302	70811800
NEW	4 MASTER LEDspot VLE D 650lm GU10 930 120D UK		6.2	650	104.00	200	120	Yes	90	3000	25.000	50	54	F	929002210099	70609801
NEW	4 MASTERLEDspot VLE D 6.2-80W GU10 927 36D UK	80	6.2	575	92.00	850	36	Yes	90	2700	25.000	50	54	F	929002059599	67541701
NEW	4 MASTERLEDspot VLE D 6.2-80W GU10 930 36D UK	80	6.2	575	92.00	850	36	Yes	90	3000	25.000	50	54	F	929002068499	70525101
NEW	4 MASTERLEDspot VLE D 6.2-80W GU10 940 36D UK	80	6.2	575	92.00	850	36	Yes	90	4000	25.000	50	54	F	929002066099	70523701
NEW	4 MASTERLEDspot VLE D 6.2-80W GU10 965 36D UK	80	6.2	575	92.00	850	36	Yes	90	6500	25.000	50	54	F	929002209999	70607401
	4 MASTER LED spot VLE D 6.2-80W GU10 927 36D	80	6.2	575	92.00	850	36	Only with specific dimmers	90	2700	25.000	50	54	F	929002059502	67541700
	4 MASTER LED spot VLE D 6.2-80W GU10 930 36D	80	6.2	575	92.00	850	36	Only with specific dimmers	90	3000	25.000	50	54	F	929002068402	70525100
	4 MASTER LED spot VLE D 6.2-80W GU10 940 36D	80	6.2	575	92.00	850	36	Only with specific dimmers	90	4000	25.000	50	54	F	929002066002	70523700
	4 MASTER LED spot VLE D 6.2-80W GU10 965 36D	80	6.2	575	92.00	850	36	Only with specific dimmers	90	6500	25.000	50	54	F	929002209902	70607400
	4 MASTER LED spot VLE D 650lm GU10 930 120D		6.2	650	104.00	200	120	Only with specific dimmers	90	3000	25.000	50	54	F	929002210002	70609800
	4 MASTER LED spot VLE D 680lm GU10 940 120D		6.2	680	109.00	200	120	Only with specific dimmers	90	4000	25.000	50	54	F	929002210102	70611100





# LED spots

## MASTER VALUE LEDspot MV - Continued

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W	Intensity	Angle			Temp.						
	W	W	lm	lm/W	cd	°			K	Hrs.					
MASTER LED spot VLE D 680lm GU10 965 120D		6.2	680	109.00	200	120	Only with specific dimmers	90	6500	25.000	50	54	F	929002210202	70613500
MASTER LED spot VLE DT 6.2-80W GU10 927 36D	80	6.2	575	92.00	950	36	Only with specific dimmers	90	2700	25.000	50	56	F	929002065902	66271400

## MASTER LEDspot LV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W	Intensity	Angle			Temp.						
	W	W	lm	lm/W	cd	°			K	Hrs.					
MAS LEDspotLV D 7.5-50W 927 MR16 24D	50	7.5	621	82.00	3900	24	Only with specific dimmers	90	2700	40.000	50	45.5	F	929002491902	30746900
MAS LEDspotLV D 7.5-50W 927 MR16 36D	50	7.5	621	82.00	1850	36	Only with specific dimmers	90	2700	40.000	50	45.5	F	929002492202	30752000
MAS LEDspotLV D 7.5-50W 930 MR16 24D	50	7.5	621	82.00	4000	24	Only with specific dimmers	90	3000	40.000	50	45.5	F	929002492002	30748300
MAS LEDspotLV D 7.5-50W 930 MR16 36D	50	7.5	621	82.00	2000	36	Only with specific dimmers	90	3000	40.000	50	45.5	F	929002492302	30754400
MAS LEDspotLV D 7.5-50W 940 MR16 24D	50	7.5	670	89.00	4400	24	Only with specific dimmers	90	4000	40.000	50	45.5	F	929002492102	30750600
MAS LEDspotLV D 7.5-50W 940 MR16 36D	50	7.5	670	89.00	2200	36	Only with specific dimmers	90	4000	40.000	50	45.5	F	929002492402	30756800





# LED spots

## MASTER LEDspot PAR

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional		Output		Intensity	Angle			Temp.						
	W	W	lm	lm/W	cd	°			K	Hrs.					
1 MAS LEDspot CLA D 6-50W 827 PAR20 25D	50	6	500	83.00	1500	25	Only with specific dimmers	80	2700	25.000	68	87	F	929002338002	76846100
1 MAS LEDspot CLA D 6-50W 827 PAR20 40D	50	6	500	83.00	900	40	Only with specific dimmers	80	2700	25.000	68	87	F	929002338302	76852200
1 MAS LEDspot CLA D 6-50W 830 PAR20 25D	50	6	515	85.00	1500	25	Only with specific dimmers	80	3000	25.000	68	87	F	929002338102	76848500
2 MAS LEDspot CLA D 6-50W 830 PAR20 40D	50	6	515	85.00	900	40	Only with specific dimmers	80	3000	25.000	68	87	F	929002338402	76854600
1 MAS LEDspot CLA D 6-50W 840 PAR20 25D	50	6	540	90.00	1500	25	Only with specific dimmers	80	4000	25.000	68	87	F	929002338202	76850800
2 MAS LEDspot CLA D 6-50W 840 PAR20 40D	50	6	540	90.00	900	40	Only with specific dimmers	80	4000	25.000	68	87	F	929002338502	76856000
3 MAS LEDspot CLA D 9.5-75W 827 PAR30S 25D	75	9.5	740	77.00	2400	25	Only with specific dimmers	80	2700	25.000	96	88	F	929002338602	76860700
3 MAS LEDspot CLA D 9.5-75W 830 PAR30S 25D	75	9.5	760	80.00	2400	25	Only with specific dimmers	80	3000	25.000	96	88	F	929002338702	76862100
3 MAS LEDspot CLA D 9.5-75W 840 PAR30S 25D	75	9.5	820	86.00	2400	25	Only with specific dimmers	80	4000	25.000	96	88	F	929002338802	76864500
4 MAS LEDspot CLA D 13-100W 827 PAR38 25D	100	13	1000	76.00	3500	25	Only with specific dimmers	80	2700	25.000	124	130	F	929002339002	76870600

## CorePro LEDspot PAR

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	CRI	Color	Lifetime	EEL	12NC	EOC
	tional		Output		Intensity	Angle		Temp.				
	W	W	lm	lm/W	cd	°		K	Hrs.			
NEW CorePro LEDspot ND 9-60W 827 PAR38 25D	60	9	750	83.00	1800	25	80	2700	15.000	F	929001322732	38873400

# LED spots

CorePro LEDspot Reflectors

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W	Intensity	Angle			Temp.						
	W	lm	lm/W	cd	°	K	Hrs.								
1 CoreProLEDspot ND1.4-25W R50 E14 827 36D	25	1.4	105	75.00	210	36	No	80	2700	15.000	50	84	F	929001891002	81173300
2 CoreProLEDspot ND1.8-30W R39 E14 827 36D	30	1.8	150	83.00	250	36	No	80	2700	15.000	39	65	F	929001890902	81171900
1 CoreProLEDspot ND2.8-40W R50 E14 827 36D	40	2.8	210	75.00	400	36	No	80	2700	15.000	50	84	F	929001891102	81175700
3 CoreProLEDspot ND 3-40W R63 E27 827 36D	40	3	210	70.00	400	36	No	80	2700	15.000	63	102	G	929001891302	81179500
4 CoreProLEDspot ND 4-60W R80 E27 827 36D	60	4	345	86.00	620	36	No	80	2700	15.000	80	112	F	929001891502	81183200
1 CoreProLEDspot D 4.3-60W R50 E14 827 36D	60	4.3	320	74.00	550	36	Only with specific dimmers	80	2700	15.000	50	84	F	929001891202	81177100
3 CoreProLEDspot D 4.5-60W R63 E27 827 36D	60	4.5	345	76.00	620	36	Only with specific dimmers	80	2700	15.000	63	102	F	929001891402	81181800
4 CoreProLEDspot ND 8-100W R80 E27 827 36D	100	8	670	83.00	1100	36	No	80	2700	15.000	80	112	F	929001891602	81185600
4 CoreProLEDspot D8.5-100W R80 E27 827 36D	100	9	670	74.00	1400	36	Only with specific dimmers	80	2700	15.000	80	112	F	929002996902	31236400

NEW

# LED spots

CorePro LEDspot LV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	lm/W	Intensity	Angle		Temp.	Hrs.	diameter	length			code
		W	W	lm	lm/W	cd	°		K						
	1 CorePro LED spot 2.3-20W MR11 36D	20	2.3	184	80.00	400	36	80	2700	25.000	35.5	39.5	F	929002066402	65948600
NEW	2 CorePro LED spot ND 2.9-20W MR16 827 36D	20	2.9	230	79.00	560	36	80	2700	15.000	50.5	45.5	F	929002494502	30704900
NEW	3 CorePro LED spot ND 4.4-35W MR16 827 36D	35	4.4	345	78.00	650	36	80	2700	15.000	50.5	45.5	F	929002494602	30706300
NEW	3 CorePro LED spot ND 4.4-35W MR16 840 36D	35	4.4	390	88.00	750	36	80	4000	15.000	50.5	45.5	F	929002494702	30708700
NEW	3 CorePro LED spot ND4.4-35W MR16 827 36DUK	35	4.4	345	78.00	650	36	80	2700	15.000	50.5	45.5	F	929002494699	30706301
NEW	3 CorePro LED spot ND4.4-35W MR16 840 36DUK	35	4.4	390	88.00	750	36	80	4000	15.000	50.5	45.5	F	929002494799	30708701
NEW	3 CorePro LEDspot 4.4-35W MR16 827 36D 5CT	35	4.4	345	78.00	650	36	80	2700	15.000	50.5	45.5	F	929002494652	30758200
	4 CorePro LED spot ND 7-50W MR16 827 36D	50	7	621	88.00	1400	36	80	2700	15.000	50.5	45	F	929001904802	81471000
	4 CorePro LED spot ND 7-50W MR16 830 36D	50	7	621	88.00	1400	36	80	3000	15.000	50.5	45	F	929001904902	81477200
	4 CorePro LED spot ND 7-50W MR16 840 36D	50	7	660	94.00	1500	36	80	4000	15.000	50.5	45	F	929001905002	81479600

# LED spots

CorePro LEDspot MV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	Im/W	Intensity	Angle			Temp.						
		W	W	lm	lm/W	cd	°			K	Hrs.					
	1 Corepro LEDspot 2.7-25W GU10 827 36D	25	2.7	215	79.00	470	36	No	80	2700	15.000	50	53	F	929001217532	75209800
	2 Corepro LEDspot 2.7-25W GU10 830 36D	25	2.7	225	83.00	490	36	No	80	3000	15.000	50	54	F	929001217602	72829100
	2 Corepro LEDspot 2.7-25W GU10 840 36D	25	2.7	230	85.00	500	36	No	80	4000	15.000	50	54	F	929001217702	72831400
NEW	3 CorePro LEDspot 3-35W GU10 827 36D DIM	35	3	230	76.00	500	36	Only with specific dimmers	80	2700	15.000	50	54	F	929002495802	72133900
NEW	3 CorePro LEDspot 3-35W GU10 830 36D DIM	35	3	230	76.00	500	36	Only with specific dimmers	80	3000	15.000	50	54	F	929002068202	72135300
NEW	3 CorePro LEDspot 3-35W GU10 840 36D DIM	35	3	240	80.00	500	36	Only with specific dimmers	80	4000	15.000	50	54	F	929002065602	73022500
NEW	3 CoreProLEDspot 3-35W GU10 830 36D DIM UK	35	3	230	76.00	500	36	Yes	80	3000	15.000	50	54	F	929002068299	72135301
NEW	1 Corepro LEDspot 3.5-35W GU10 827 36D UK	35	3.5	255	72.00	545	36	No	80	2700	15.000	50	54	F	929001217897	75253101
NEW	2 Corepro LEDspot 3.5-35W GU10 830 36D UK	35	3.5	265	75.00	565	36	No	80	3000	15.000	50	54	F	929001217999	72833801
NEW	2 Corepro LEDspot 3.5-35W GU10 840 36D UK	35	3.5	275	78.00	590	36	No	80	4000	15.000	50	54	F	929001218099	72835201
	1 Corepro LEDspot 3.5-35W GU10 827 36D	35	3.5	255	72.00	545	36	No	80	2700	15.000	50	54	F	929001217862	75253100
	2 Corepro LEDspot 3.5-35W GU10 830 36D	35	3.5	265	75.00	565	36	No	80	3000	15.000	50	54	F	929001217902	72833800
	2 Corepro LEDspot 3.5-35W GU10 840 36D	35	3.5	275	78.00	590	36	No	80	4000	15.000	50	54	F	929001218002	72835200
NEW	3 CorePro LEDspot 4-50W GU10 827 36D DIM	50	4	345	86.00	700	36	Only with specific dimmers	80	2700	15.000	50	54	F	929002495902	72137700
NEW	4 CorePro LEDspot 4-50W GU10 830 36D DIM	50	4	345	86.00	700	36	Only with specific dimmers	80	3000	15.000	50	54	F	929002068302	35883600
NEW	4 CorePro LEDspot 4-50W GU10 840 36D DIM	50	4	350	87.00	700	36	Only with specific dimmers	80	4000	15.000	50	54	F	929002065802	35885000
NEW	3 CoreProLEDspot 4-50W GU10 827 36D DIM UK	50	4	345	86.00	700	36	Yes	80	2700	15.000	50	54	F	929002495999	72137701
NEW	4 CoreProLEDspot 4-50W GU10 830 36D DIM UK	50	4	345	86.00	700	36	Yes	80	3000	15.000	50	54	F	929002068399	35883601
NEW	4 CoreProLEDspot 4-50W GU10 840 36D DIM UK	50	4	350	87.00	700	36	Yes	80	4000	15.000	50	54	F	929002065899	35885001
NEW	1 Corepro LEDspot 4.6-50W GU10 827 36D UK	50	4.6	355	77.00	700	36	No	80	2700	15.000	50	54	F	929001215268	75251701
NEW	2 Corepro LEDspot 4.6-50W GU10 830 36D UK	50	4.6	370	80.00	740	36	No	80	3000	15.000	50	54	F	929001218199	72837601
NEW	2 Corepro LEDspot 4.6-50W GU10 840 36D UK	50	4.6	390	84.00	770	36	No	80	4000	15.000	50	54	F	929001218299	72839001
NEW	2 Corepro LEDspot 4.6-50W GU10 865 36D UK	50	4.6	390	84.00	770	36	No	80	6500	15.000	50	54	F	929001218399	72841301
	1 Corepro LEDspot 4.6-50W GU10 827 36D	50	4.6	355	77.00	700	36	No	80	2700	15.000	50	54	F	929001215232	75251700
	1 CorePro LEDspot 4.6-50W GU10 827 36D 5CT	50	4.6	355	77.00	700	36	No	80	2700	15.000	50	54	F	929001215252	70029400
	2 Corepro LEDspot 4.6-50W GU10 830 36D	50	4.6	370	80.00	740	36	No	80	3000	15.000	50	54	F	929001218102	72837600
	2 Corepro LEDspot 4.6-50W GU10 840 36D	50	4.6	390	84.00	770	36	No	80	4000	15.000	50	54	F	929001218202	72839000
	2 Corepro LEDspot 4.6-50W GU10 865 36D	50	4.6	390	84.00	770	36	No	80	6500	15.000	50	54	F	929001218302	72841300
NEW	5 LEDspot GU10 50W 830 36D 6CT	50	4.7	345	73.00	700	36	No	80	3000	15.000	50	54	F	929003132390	42063200
NEW	4 CorePro LEDspot 4.9-65W GU10 830 36D ND	65	4.9	460	93.00	800	36	No	80	3000	15.000	50	54	E	929002981002	30871800

# LED spots

CorePro LEDspot MV - Continued

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional		Output		Intensity	Angle		Temp.		diameter	length			code
		W	W	lm	lm/W	cd	°		K	Hrs.					
NEW	1 CorePro LEDspot 4.9-65W GU10 840 36D ND	65	4.9	485	98.00	800	36	80	4000	15.000	50	54	E	929002981102	30861900
NEW	2 Corepro LEDspot 550lm GU10 830 120D		4.9	550	112.00		120	80	3000	15.000	50	54	E	929002981202	30875600
NEW	2 Corepro LEDspot 550lm GU10 840 120D		4.9	550	112.00		120	80	4000	15.000	50	54	E	929002981302	30865700
NEW	2 Corepro LEDspot 550lm GU10 865 120D		4.9	550	112.00		120	80	6500	15.000	50	54	E	929002981402	30867100
	3 Corepro LEDspot 670lm GU10 830 60D	90	6.7	670	100.00	750	60	80	3000	25.000	50	54	E	929002466702	81333101
	3 Corepro LEDspot 730lm GU10 840 60D	100	6.7	730	108.00	750	60	80	4000	25.000	50	54	E	929002466802	81335501
	3 Corepro LEDspot 730lm GU10 865 60D	100	6.7	730	108.00	750	60	80	6500	25.000	50	54	E	929002466902	81337901

CorePro LEDspot AR111

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficiency	Luminous	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional		Output		Intensity	Angle		Temp.		diameter	length			code
		W	W	lm	lm/W	cd	°		K	Hrs.					
NEW	CorePro LEDspot 7-50W 830 AR111 40D	50	7	550	78.00	1100	40	>80	3000	15.000	110.7	55	F	929002965002	30538000
NEW	CorePro LEDspot 10-75W 830 AR111 40D	75	10	800	80.00	1700	40	>80	3000	15.000	110.7	55	F	929002965102	30534200
NEW	CorePro LEDspot 14-100W 830 AR111 40D	100	14	1160	82.00	2200	40	>80	3000	15.000	110.7	55	F	929002965202	30536600

# LED spots

CorePro LEDcapsule LV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficiency	Beam	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional		Output		Angle			Temp.	Hrs.					
	W	W	lm	lm/W	°			K						
1 CorePro LEDcapsuleLV 1-10W G4 827	10	1	115	115.00	300	No	80	2700	15.000	13	35	F	929002388802	76761700
1 CorePro LEDcapsuleLV 1-10W G4 830	10	1	120	120.00	300	No	80	3000	15.000	13	35	E	929002388902	76759400
2 CorePro LEDcapsuleLV 1.8-20W G4 827	20	1.8	205	113.00	300	No	80	2700	15.000	13	35	F	929002389002	76765500
2 CorePro LEDcapsuleLV 1.8-20W G4 830	20	1.8	215	119.00	300	No	80	3000	15.000	13	35	E	929002389102	76769300
3 CorePro LEDcapsuleLV 1.8-20W GY6.35 827	20	1.8	205	113.00	300	No	80	2700	15.000	13	35	F	929002389702	76779200
3 CorePro LEDcapsuleLV 1.8-20W GY6.35 830	20	1.8	215	119.00	300	No	80	3000	15.000	13	35	E	929002389802	76783900
4 CorePro LEDcapsuleLV 2.1-20W G4 827 D	20	2.1	210	100.00	300	Only with specific dimmers	80	2700	15.000	15	40	F	929002389402	76753200
4 CorePro LEDcapsuleLV 2.7-28W G4 827	28	2.7	315	116.00	300	No	80	2700	15.000	15	40	F	929002389202	76775400
4 CorePro LEDcapsuleLV 2.7-28W G4 830	28	2.7	330	122.00	300	No	80	3000	15.000	15	40	E	929002389302	76777800

# LED spots

CorePro LEDcapsule MV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)




	Product Type	Tradi	LED	Lumen	Efficiency	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	lm/W			Temp.	Hrs.	diameter	length			
		W	W	lm	lm/W			K						
NEW	1 CorePro LEDcapsule 2-25W ND G9 827	25	2	220	110.00	No	80	2700	15.000	14.5	48	E	929002495202	30389800
NEW	1 CorePro LEDcapsule 2-25W ND G9 830	25	2	220	110.00	No	80	3000	15.000	14.5	48	E	929002495302	30391100
NEW	2 CorePro LEDcapsuleMV 2.6-25W G9 827 D UK	25	2.6	300	115.00	Yes	80	2700	15.000	15	52	E	929002389999	76669601
	2 CorePro LEDcapsuleMV 2.6-25W G9 827 D	25	2.6	300	115.00	Only with specific dimmers	80	2700	15.000	15	52	E	929002389902	76669600
NEW	3 CorePro LEDcapsule 3.2-40W ND G9 827	40	3.2	400	125.00	No	80	2700	15.000	16.5	54	E	929002495502	30393500
NEW	3 CorePro LEDcapsule 3.2-40W ND G9 830	40	3.2	400	125.00	No	80	3000	15.000	16.5	54	E	929002495602	30395900
	4 CorePro LEDcapsuleMV 4-40W G9 827 D	40	4	480	120.00	Only with specific dimmers	80	2700	15.000	18	59	E	929002390002	76673300
	5 CorePro LEDcapsule ND 4.8-60W G9 827	60	4.8	570	118.00	No	80	2700	15.000	19	60	E	929002055102	65780200
	5 CorePro LEDcapsule ND 4.8-60W G9 830	60	4.8	570	118.00	No	80	3000	15.000	19	60	E	929002059802	65818200

# LED spots

CorePro LEDlinear MV

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficiency	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	lm/W			Temp.	Hrs.	diameter	length			
		W	W	lm	lm/W			K		mm	mm			
NEW	1 CorePro LED linear R7S 118mm 7.2-60W 830	60	7.2	810	112.00	No	80	3000	15.000	15	118	E	929002495002	30397300
NEW	2 CorePro LED linear R7S 118mm 7.2-60W 840	60	7.2	850	118.00	No	80	4000	15.000	15	118	E	929002495102	30399700
	3 CorePro LEDlinear ND 7.5-60W R7S 78mm830	60	7.5	950	126.67	No	80	3000	15.000	29	78	E	929001339002	71394500
	3 CorePro LEDlinear ND 7.5-60W R7S 78mm840	60	7.5	1000	133.33	No	80	4000	15.000	29	78	E	929001339102	71396900
	4 CorePro LED linear D 14-120W R7S 118 830	120	14	2000	142.86	Yes	80	3000	15.000	29	118	D	929001353602	71400300
	4 CorePro LED linear D 14-120W R7S 118 840	120	14	2000	142.86	Yes	80	4000	15.000	29	118	D	929001353702	71406500
	5 CorePro LED linear R7S 118mm 14-100W 830 D	100	14	1600	114.29	Only with specific dimmers	80	3000	15.000	29	118	E	929001243702	57879700
	6 CorePro LED linear R7S 118mm 14-100W 840 D	100	14	1800	128.57	Only with specific dimmers	80	4000	15.000	29	118	E	929001243802	57881000
	7 CoreProLED linearD 17.5-150W R7S 118 830	150	17.5	2460	140.00	Only with specific dimmers	80	3000	15.000	42	118	D	929002016602	64673800
	7 CoreProLED linearD 17.5-150W R7S 118 840	150	17.5	2460	140.00	Only with specific dimmers	80	4000	15.000	42	118	D	929002016702	64675200





# LED bulbs

SceneSwitch LEDbulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	LED	Lumen Output	Efficacy	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W		K	Hrs.					
LEDClassic SSW 60W A60 E27WWCLND RF1SRT4	7.5	806-320-150	107.00	80	2700-2500-2200	15.000	60	104	F	929001888655	77213001

Premium LED bulbs SceneSwitch

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	LED	Lumen Output	Efficacy	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W		K	Hrs.					
LEDClassic SSW 60W A60 E27 WW FRND 1SRT4	7.5	806-320-150	107.00	80	2700-2500-2200	15.000	60	104	F	929002445558	26396300
LEDClassic SSW 60W A60 E27WWFR ND 1PF/10	7.5	806-320-150	107.00	80	2700-2500-2200	15.000	60	104	F	929002445517	26396301

# LED bulbs

UltraEfficient LED bulb

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	Im/W		Temp.	Hrs.	diameter	length			code
		W	W	lm	lm/W		K						
NEW	1 MAS LEDBulbND2.3-40W E27830 A60CL G EELA	40	2.3	485	210.00	80	3000	50.000	60	105	A	929003066402	42073100
NEW	2 MAS LEDBulbND2.3-40W E27840 A60CL G EELA	40	2.3	485	210.00	80	4000	50.000	60	105	A	929003066502	42075500
NEW	3 MAS LEDBulbND4-60W E27 830 A60 CL G EELA	60	4	840	210.00	80	3000	50.000	60	105	A	929003066702	42077900
NEW	4 MAS LEDBulbND4-60W E27 840 A60 CL G EELA	60	4	840	210.00	80	4000	50.000	60	105	A	929003066802	42079300

## Classic filament LEDbulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	12NC	EOC
		tional	W	Output	Im/W		Temp.	Hrs.			code
		W	W	lm	lm/W		K				
	1 LED double layers 20W E27 smoky DIM	20	6.5	200	30.00	Yes	80	1800	15.000	929002982301	31372900
	2 LED giant 20W E27 A160 1800K smoky D	20	6.5	200	30.00	Yes	80	1800	15.000	929002982501	31537200
	3 LED giant 20W E27 G200 1800K smoky D	20	6.5	200	30.00	Yes	80	1800	15.000	929002982601	31539600
	4 LED giant 20W E27 T65 1800K smoky D	20	6.5	200	30.00	Yes	80	1800	15.000	929002982701	31541900
	5 LED classic 25W G93 E27 GOLD SP D SRT4	25	4	250	62.00	Yes	80	1800	15.000	929002983001	31547100
	6 LED giant crystal 26W E27 smoky DIM	26	7	270	38.00	Yes	80	1800	15.000	929002982401	31374300
	7 LED classic-giant 28W E27 A160 GOLD ND	28	4.5	300	66.00	No	80	1800	15.000	929002983801	31382800
	8 LED classic-giant 28W E27 G200 GOLD ND	28	4.5	300	66.00	No	80	1800	15.000	929002983901	31384200
	9 LED classic-giant 40W E27 A160 GOLD DIM	40	7	470	67.00	Yes	80	1800	15.000	929002983501	31376700
	10 LED classic-giant 40W E27 G200 GOLD DIM	40	7	470	67.00	Yes	80	1800	15.000	929002983601	31378100
	11 LED classic-giant 40W E27 T65 GOLD DIM	40	7	470	67.00	Yes	80	1800	15.000	929002983701	31380400
	12 LEDClassic 40W Mushroom E27 1800K GOLD D	40	5.5	470	85.00	No	80	1800	15.000	929002984001	31386600

# LED bulbs

CorePro LEDbulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	W	lm	lm/W	°		K	Hrs.					
1 CorePro LEDbulb ND 5-40W A60 B22 930	40	5	470	94.00	200	90	3000	15.000	60	110	F	929003001602	32972000
2 CorePro LEDbulb ND 5-40W A60 E27 830	40	5	470	94.00	200	80	3000	15.000	60	110	F	929001304532	57993000
2 CorePro LEDbulb ND 5-40W A60 E27 840	40	5	470	94.00	200	80	4000	15.000	60	110	F	929001234602	57779000
3 CorePro LEDbulb ND 5-40W A60 E27 930	40	5	470	94.00	200	90	3000	15.000	60	110	F	929003001502	32956000
3 CorePro LEDbulb ND 5-40W A60 E27 940	40	5	470	94.00	200	90	4000	15.000	60	110	F	929003001702	32958400
4 CorePro LEDbulb ND 5.5-40W A60 B22 827	40	5.5	470	85.00	200	80	2700	15.000	60	110	F	929001233802	57765300
2 CorePro LEDbulb ND 5.5-40W A60 E27 827	40	5.5	470	85.00	200	80	2700	15.000	60	110	F	929001234202	57757800
4 CorePro LEDbulb ND 5.5-40W A60 B22 827 UK	40	5.5	470	85.00	200	80	2700	15.000	60	110	F	929001233899	57765301
2 CorePro LEDbulb ND 5.5-40W A60 E27 827 UK	40	5.5	470	85.00	200	80	2700	15.000	60	110	F	929001234299	57757801
NEW 5 LEDbulb ND 8-60W A60 E27 827 6CT	60	8	806	100.00	180	80	2700	15.000	60	108	F	929002306202	42067000
2 CorePro LED bulb ND 7.5-60W A60 E27 865	60	7.5	806	107.00	200	80	6500	15.000	60	110	F	929001304832	57785100
1 CorePro LEDbulb ND 7.5-60W A60 B22 930	60	7.5	806	107.00	200	90	3000	15.000	60	110	F	929003002402	32974400
2 CorePro LEDbulb ND 7.5-60W A60 E27 830	60	7.5	806	107.00	200	80	3000	15.000	60	110	F	929001304732	57771400
2 CorePro LEDbulb ND 7.5-60W A60 E27 840	60	7.5	806	107.00	200	80	4000	15.000	60	110	F	929001234702	57777600
3 CorePro LEDbulb ND 7.5-60W A60 E27 930	60	7.5	806	107.00	200	90	3000	15.000	60	110	F	929003002302	32960700
3 CorePro LEDbulb ND 7.5-60W A60 E27 940	60	7.5	806	107.00	200	90	4000	15.000	60	110	F	929003002502	32962100
4 CorePro LEDbulb ND 8-60W A60 B22 827	60	8	806	100.00	200	80	2700	15.000	60	110	F	929001233902	57763900
4 CorePro LEDbulb ND 8-60W A60 B22 827 UK	60	8	806	100.00	200	80	2700	15.000	60	110	F	929001233997	57763901
2 CorePro LEDbulb ND 8-60W A60 E27 827	60	8	806	100.00	200	80	2700	15.000	60	110	F	929001234302	57755400
2 CorePro LEDbulb ND 8-60W A60 E27 827 SKT	60	8	806	100.00	200	80	2700	15.000	60	110	F	929001234350	40437300
2 CorePro LEDbulb ND 8-60W A60 E27 827 UK	60	8	806	100.00	200	80	2700	15.000	60	110	F	929001234385	57755401
2 CorePro LEDbulb ND 8-60W A60 E27 827 3CT/8	60	8	806	100.00	200	80	2700	15.000	60	110	F	929001234332	70033100
1 CorePro LEDbulb ND 7.5-60W A60 B22 930 UK	60	7.5	806	107.00	200	90	3000	15.000	60	110	F	929003002499	32974401
NEW 6 LEDbulb ND 10-75W A60 E27 827 6CT	75	10	1055	105.00	180	80	2700	15.000	60	108	F	929002306502	42069400
7 CorePro LEDbulb ND 10-75W A60 E27 840	75	10	1055	105.00	200	80	4000	15.000	60	110	F	929001234802	51032200
8 CorePro LEDbulb ND 10-75W A60 E27 865	75	10	1055	105.00	200	80	6500	15.000	60	110	F	929001163832	49758600
9 CorePro LEDbulb ND 10-75W A60 E27 940	75	10	1055	105.00	200	90	4000	15.000	60	110	F	929003003302	32966900
10 CorePro LEDbulb ND 10.5-75W A60 B22 930	75	10.5	1055	100.00	200	90	3000	15.000	60	110	F	929003003202	32976800
8 CorePro LEDbulb ND 10.5-75W A60 E27 830	75	10.5	1055	100.00	200	80	3000	15.000	60	110	F	929001162332	49752400
9 CorePro LEDbulb ND 10.5-75W A60 E27 930	75	10.5	1055	100.00	200	90	3000	15.000	60	110	F	929003003102	32964500

# LED bulbs

CorePro LEDbulbs - Continued

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W	Angle		Temp.	Hrs.	diameter	length			code
	W	W	lm	lm/W	°		K						
1 CorePro LEDbulb ND 11-75W A60 B22 827	75	11	1055	95.00	200	80	2700	15.000	60	110	F	929001234002	57761500
1 CorePro LEDbulb ND 11-75W A60 B22 827 UK	75	11	1055	95.00	200	80	2700	15.000	60	110	F	929001234098	51004901
2 CorePro LEDbulb ND 11-75W A60 E27 827	75	11	1055	95.00	200	80	2700	15.000	60	110	F	929001234402	49076100
2 CorePro LEDbulb ND 12.5-100W A60 E27 840	100	12.5	1521	121.00	200	80	4000	15.000	60	110	E	929001312402	51030800
2 CorePro LEDbulb ND 12.5-100W A60 E27 865	100	12.5	1521	121.00	200	80	6500	15.000	60	110	E	929001312502	57781300
3 CorePro LEDbulb ND 12.5-100W A60 E27 940	100	12.5	1521	121.00	200	90	4000	15.000	60	110	E	929003004102	32970600
1 CorePro LEDbulb ND 13-100W A60 B22 827	100	13	1521	117.00	200	80	2700	15.000	60	110	E	929001234102	51002500
4 CorePro LEDbulb ND 13-100W A60 B22 930	100	13	1521	117.00	200	90	3000	15.000	60	110	E	929003004002	32978200
2 CorePro LEDbulb ND 13-100W A60 E27 827	100	13	1521	117.00	200	80	2700	15.000	60	110	E	929001234502	49074700
2 CorePro LEDbulb ND 13-100W A60 E27 830	100	13	1521	117.00	200	80	3000	15.000	60	110	E	929001235002	57767700
3 CorePro LEDbulb ND 13-100W A60 E27 930	100	13	1521	117.00	200	90	3000	15.000	60	110	E	929003003902	32968300
1 CoreProLEDbulb ND 13-100W A60 B22 827 UK	100	13	1521	117.00	200	80	2700	15.000	60	110	E	929001234199	51002501
4 CoreProLEDbulb ND 13-100W A60 B22 930 UK	100	13	1521	117.00	200	90	3000	15.000	60	110	E	929003004099	32978201
2 CoreProLEDbulb ND 13-100W A60 E27 827 UK	100	13	1521	117.00	200	80	2700	15.000	60	110	E	929001234564	49074701
3 CoreProLEDbulb ND 13-100W A60 E27 930 UK	100	13	1521	117.00	200	90	3000	15.000	60	110	E	929003003999	32968301

# LED bulbs

CorePro Glass LED bulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W		Temp.	Hrs.	diameter	length			code
1 CorePro LEDBulbND 4-40W E27 ST64 827 CLG	40	4	470	117.00	80	2700	15.000	64	140	E	929001237392	34687100
2 CorePro LEDBulbND 4.3-40W E27 A60827 CLG	40	4.3	470	109.00	80	2700	15.000	60	104	F	929001890092	34716800
3 CorePro LEDBulbND 4.3-40W E27 A60840 CLG	40	4.3	540	125.00	80	4000	15.000	60	104	E	929001890692	35493700
4 CorePro LEDBulbND 4.5-40W E27 A60830 FRG	40	4.5	470	104.00	80	3000	15.000	60	106	F	929002424992	34702100
5 CorePro LEDBulbND 4.5-40W E27 A60 827FR G	40	4.5	470	104.00	80	2700	15.000	60	110	F	929001242992	36130000
4 CorePro LEDBulb7-60W E27 A60 840 FR G	60	7	806	115.00	80	4000	15.000	60	106	E	929001323592	37751600
6 CorePro LEDBulbND 7-60W B22 A60 827 CL G	60	7	806	115.00	80	2700	15.000	60	104	E	929001387492	34673400
7 CorePro LEDBulbND 7-60W E27 A60 827FR G	60	7	806	115.00	80	2700	15.000	60	110	E	929001243002	36124900
4 CorePro LEDBulbND 7-60W E27 A60 830 FR G	60	7	806	115.00	80	3000	15.000	60	106	E	929002425092	34647500
8 CorePro LEDBulbND 7-60W E27 A60 840 CL G	60	7	850	121.00	80	4000	15.000	60	106	E	929001815092	35491300
9 CorePro LEDBulbND 7-60W E27 G93 827 CL G	60	7	806	115.00	80	2700	15.000	95	140	E	929001387992	34677200
10 CorePro LEDBulbND 7-60W E27 ST64 827CL G	60	7	806	115.00	80	2700	15.000	64	140	E	929001387692	34675800
11 CorePro LEDBulbND 7-60W E27 WW A60 CL G	60	7	806	115.00	80	2700	15.000	60	104	E	929001387362	38003500
11 CorePro LEDBulbND 7-60W E27 WW A60 CLG3pk	60	7	806	115.00	80	2700	15.000	60	104	E	929001387314	38996000
4 CorePro LEDBulb8.5-75W E27 A60 840 FR G	75	8.5	1055	124.00	80	4000	15.000	60	104	E	929002025892	37753000
12 CorePro LEDBulbND 8.5-75W E27 A60 827CLG	75	8.5	1055	124.00	80	2700	15.000	60	104	E	929002025492	34712000
4 CorePro LEDBulbND 8.5-75W E27 A60 830FRG	75	8.5	1055	124.00	80	3000	15.000	60	104	E	929002425192	34704500
12 CorePro LEDBulbND 8.5-75W E27 A60 840CLG	75	8.5	1055	124.00	80	4000	15.000	60	104	E	929002025592	34708300
4 CorePro LEDBulbND 8.5-75W E27 A60 827FR G	75	8.5	1055	124.00	80	2700	15.000	60	104	E	929002025702	36126300

# LED bulbs

CorePro Glass LED bulbs - Continued

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	Im/W		Temp.	Hrs.	diameter	length			code
	W	W	lm			K						
1 CorePro LEDBulb 10.5-100W E27 A60 840 FRG	100	10.5	1521	144.00	80	4000	15.000	60	104	D	929002026592	37755400
2 CorePro LEDBulbND 10.5-100W E27A60 827CLG	100	10.5	1521	144.00	80	2700	15.000	60	104	D	929002026192	34714400
1 CorePro LEDBulbND 10.5-100W E27A60 827FRG	100	10.5	1521	144.00	80	2700	15.000	60	104	D	929002026402	36128700
3 CorePro LEDBulbND 10.5-100W E27A60 830FRG	100	10.5	1521	144.00	80	3000	15.000	60	104	D	929002425292	34706900
2 CorePro LEDBulbND 10.5-100W E27A60 840CLG	100	10.5	1521	144.00	80	4000	15.000	60	104	D	929002026292	34710600

# LED bulbs

CorePro Glass High Lumen bulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional		Output			Temp.		diameter	length			code
	W	W	lm	lm/W		K	Hrs.					
1 CorePro LEDBulbND 120W E27 A67 827 CL G	120	13	2000	153.00	80	2700	15.000	70	121	D	929002371502	34649900
2 CorePro LEDBulbND 120W E27 A67 827 FR G	120	13	2000	153.00	80	2700	15.000	70	121	D	929002371802	34653600
1 CorePro LEDBulbND 120W E27 A67 840 CL G	120	13	2000	153.00	80	4000	15.000	70	121	D	929002371602	34651200
2 CorePro LEDBulbND 120W E27 A67 840 FR G	120	13	2000	153.00	80	4000	15.000	70	121	D	929002371902	34655000
3 CorePro LEDBulbND 120W E27 A67 865 FR G	120	13	2000	153.00	80	6500	15.000	70	121	D	929002372002	34657400
3 CorePro LEDBulbND 150W E27 A67 827 FR G	150	17.5	2452	140.00	80	2700	15.000	70	121	D	929002372602	34661100
4 CorePro LEDBulbND 150W E27 A67 840 CL G	150	17	2452	144.00	80	4000	15.000	70	121	D	929002372402	34659800
3 CorePro LEDBulbND 150W E27 A67 840 FR G	150	17.5	2452	140.00	80	4000	15.000	70	121	D	929002372702	34663500
3 CorePro LEDBulbND 150W E27 A67 865 FR G	150	17.5	2452	140.00	80	6500	15.000	70	121	D	929002372802	34665900
5 CorePro LEDBulbND17-150W E27 A67 827 CLG	150	17	2452	144.00	80	2700	15.000	70	128	D	929002055092	34744100
6 CorePro LEDBulbND 200W E27 A95 827 FR G	200	23	3452	150.00	80	2700	15.000	95	165	D	929002372902	34667300
6 CorePro LEDBulbND 200W E27 A95 840 FR G	200	23	3452	150.00	80	4000	15.000	95	165	D	929002373002	34669700
6 CorePro LEDBulbND 200W E27 A95 865 FR G	200	23	3452	150.00	80	6500	15.000	95	165	D	929002373102	34671000

CorePro Plastic LED Specialties

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional		Output		Angle		Temp.		diameter	length			code
	W	W	lm	lm/W	°		K	Hrs.					
CorePro LED Stick ND 9.5-68W T38 E27 830	68	9.5	950	100.00	240	80	3000	15.000	37.2	114.3	F	929001901402	81451200
CorePro LED Stick ND 9.5-75W T38 E27 840	75	9.5	1050	110.00	240	80	4000	15.000	37.2	114.3	E	929001901502	81453600

# LED bulbs

## MASTER Glass LED bulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional		Output				Temp.						
	W	W	lm	lm/W			K	Hrs.					
MAS LEDBulbDT3.4 -40W E27 927 A60 FR G	40	3.4	470	138.00	Only with specific dimmers	90	2200-2700	25.000	60	104	D	929003010002	32467100
MAS LEDBulb DT5.9-60W E27 927 A60 FR G	60	5.9	806	136.00	Only with specific dimmers	90	2200-2700	25.000	60	104	D	929003010402	32475600
MAS LEDBulb DT7.2-75W E27 927 A60 FR G	75	7.2	1055	146.00	Only with specific dimmers	90	2200-2700	25.000	60	104	D	929003011302	32493000
MAS LEDBulb DT10.5-100W E27 927A60 FR G	100	10.5	1521	144.00	Only with specific dimmers	90	2200-2700	25.000	60	108	D	929003011702	32501200

## MASTER Plastic LEDbulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional		Output				Temp.						
	W	W	lm	lm/W			K	Hrs.					
<b>NEW</b> ① MASTER LEDbulb DT 5.5-40W B22 A60 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	60.5	108	F	929002490102	30624000
<b>NEW</b> ② MASTER LEDbulb DT 5.5-40W E27 A60 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	60.5	109	F	929002490002	30630100
<b>NEW</b> ③ MASTER LEDbulb DT 8-60W B22 A60 CL	60	8	806	100.00	Only with specific dimmers	80	2200-2700	25.000	60.5	110	F	929002490332	30628800
<b>NEW</b> ③ MASTER LEDbulb DT 8-60W B22 A60 CL UK	60	8	806	100.00	Yes	80	2200-2700	25.000	60.5	110	F	929002490399	30628801
<b>NEW</b> ④ MASTER LEDbulb DT 8-60W E27 A60 CL	60	8	806	100.00	Only with specific dimmers	80	2200-2700	25.000	60.5	110	F	929002490232	30634900
<b>NEW</b> ④ MASTER LEDbulb DT 8-60W E27 A60 CL UK	60	8	806	100.00	Yes	80	2200-2700	25.000	60.5	110	F	929002490299	30634901



# LED bulbs

MASTER Value Decorative LED bulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	12NC	EOC
	tional		Output				Temp.	Hrs.		
	W	W	lm	lm/W			K			
1 MAS VLE LEDBulbD4-25W E27 A60 GOLD SP G	25	4	250	62.00	Yes	80	1800	15.000	929002982802	31551800
2 MAS VLE LEDBulbD4-25W E27 ST64 GOLD SP G	25	4	250	62.00	Yes	80	1800	15.000	929002982902	31553200
3 MAS VLE LEDBulbD4-25W E27 T32 GOLD SP G	25	4	250	62.00	Yes	80	1800	15.000	929002983102	31555600
4 MAS VLE LEDBulbD4-25WE27 G93GOLD SP G	25	4	250	62.00	Yes	80	1800	15.000	929002983002	38548100

# LED bulbs

MASTER Value GLASS LED bulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W			Temp.						
	W	W	lm	lm/W			K	Hrs.					
1 MASTER VLE LEDBulb DT3.4-40W E27 927A60CL G	40	3.4	470	138.00	Only with specific dimmers	90	2200-2700	15.000	60	104	D	929003009902	32465700
2 MASTER VLE LEDBulbD 3.4-40W B22 A60 927FR G	40	3.4	470	138.00	Only with specific dimmers	90	2700	15.000	60	103	D	929003010202	32471800
3 MASTER VLE LEDBulbD3.4-40W E27 927 A60 CL G	40	3.4	470	138.00	Only with specific dimmers	90	2700	15.000	60	104	D	929003070502	35481400
4 MASTER VLE LEDBulbD3.4-40W E27 927 A60 FR G	40	3.4	470	138.00	Only with specific dimmers	90	2700	15.000	60	104	D	929003070702	35483800
5 MASTER VLELEDBulbDT3.4-40W B22 927A60CL G	40	3.4	470	138.00	Only with specific dimmers	90	2200-2700	15.000	60	103	D	929003010102	32469500
5 MASTER VLELEDBulbDT3.4-40WB22 927A60CL G UK	40	3.4	470	138.00	Yes	90	2200-2700	15.000	60	103	D	929003010199	32469501
6 MASTER VLE LEDBulbD7.2-50W E27 A60 827 CM G	50	7.2	650	90.00	Only with specific dimmers	80	2700	15.000	60	106	F	929002412802	36122500
7 MASTER VLE EDBulbDT5.9-60W B22 927 G93CL G	60	5.9	806	136.00	Only with specific dimmers	90	2200-2700	15.000	95	136	D	929003011002	32487900
8 MASTER VLE EDBulbDT5.9-60W B22 927 ST64CL G	60	5.9	806	136.00	Only with specific dimmers	90	2200-2700	15.000	64	139	D	929003010802	32483100
9 MASTER VLE LEDBulb D5.9-60W E27 927 A60CLG	60	5.9	806	136.00	Only with specific dimmers	90	2700	15.000	60	104	D	929003057502	34784700
4 MASTER VLE LEDBulb D5.9-60W E27 927 A60 FRG	60	5.9	806	136.00	Only with specific dimmers	90	2700	15.000	60	104	D	929003057702	34786100
10 MASTER VLE LEDBulb D5.9-60W E27 927 G120CLG	60	5.9	806	136.00	Only with specific dimmers	90	2700	15.000	124	178	D	929003059302	34798400
11 MASTER VLE LEDBulb D5.9-60W E27 927 ST64CLG	60	5.9	806	136.00	Only with specific dimmers	90	2700	15.000	64	140	D	929003059402	34796000
12 MASTER VLE LEDBulb DT5.9-60W B22 927A60CL G	60	5.9	806	136.00	Only with specific dimmers	90	2200-2700	15.000	60	103	D	929003010502	32477000

# LED bulbs

MASTER Value GLASS LED bulbs - Continued

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W			Temp.						
	W	W	lm	lm/W			K	Hrs.					
1 MASTER VLE LEDBulb DT5.9-60W E27 927G93CL G	60	5.9	806	136.00	Only with specific dimmers	90	2200-2700	15.000	95	137	D	929003010902	32485500
2 MASTER VLE LEDBulb DT5.9-60W E27 927ST64CLG	60	5.9	806	136.00	Only with specific dimmers	90	2200-2700	15.000	64	140	D	929003010702	32481700
3 MASTER VLE LEDBulbD5.9-60W B22 A60 927FR G	60	5.9	806	136.00	Only with specific dimmers	90	2700	15.000	60	103	D	929003010602	32479400
4 MASTER VLE LEDBulbDT5.9-60W E27 927A60CL G	60	5.9	806	136.00	Only with specific dimmers	90	2200-2700	15.000	60	104	D	929003010302	32473200
3 MASTERVLE LEDBulbD5.9-60W B22A60 927FR G UK	60	5.9	806	136.00	Yes	90	2200-2700	15.000	60	103	D	929003010699	32479401
5 MASTERVLE LEDBulbDT5.9-60WB22 927A60CL G UK	60	5.9	806	136.00	Yes	90	2200-2700	15.000	60	103	D	929003010598	32477001
6 MASTERVLELEDBulb D5.9-60W E27 927A60FR G UK	60	5.9	806	136.00	Yes	90	2700	15.000	60	104	D	929003057799	34786101
4 MASTERVLELEDBulbDT5.9-60W E27 927A60CL G UK	60	5.9	806	136.00	Yes	90	2200-2700	15.000	60	104	D	929003010398	32473201
7 MASTER VLE LEDBulb D7.8-75W E27 927 A60 CLG	75	7.8	1055	135.00	Only with specific dimmers	90	2700	15.000	60	104	D	929003057902	34788500
6 MASTER VLE LEDBulb D7.8-75W E27 927 A60 FRG	75	7.8	1055	135.00	Only with specific dimmers	90	2700	15.000	60	104	D	929003058102	34790800
8 MASTER VLE LEDBulb DT7.2-75W B22 927A60CL G	75	7.2	1055	146.00	Only with specific dimmers	90	2200-2700	15.000	60	103	D	929003011202	32491600
9 MASTER VLE LEDBulb DT7.2-75W E27 927A60CL G	75	7.2	1055	146.00	Only with specific dimmers	90	2200-2700	15.000	60	104	D	929003011102	32489300
3 MASTER VLE LEDBulbD7.2-75W B22 A60 927 FR G	75	7.2	1055	146.00	Only with specific dimmers	90	2700	15.000	60	103	D	929003011402	32495400
3 MASTER VLE LEDBulbD10.5-100W B22 A60 927FRG	100	10.5	1521	144.00	Only with specific dimmers	90	2700	15.000	60	107	D	929003011802	32503600
10 MASTER VLE LEDBulbD11.2-100W E27 927 A60CLG	100	11.2	1521	135.00	Only with specific dimmers	90	2700	15.000	60	108	D	929003058302	34792200
6 MASTER VLE LEDBulbD11.2-100W E27 927 A60FRG	100	11.2	1521	135.00	Only with specific dimmers	90	2700	15.000	60	108	D	929003058502	34794600
11 MASTER VLE LEDBulbDT10.5-100W B22 927A60CLG	100	10.5	1521	144.00	Only with specific dimmers	90	2200-2700	15.000	60	107	D	929003011602	32499200
12 MASTER VLE LEDBulbDT10.5-100W E27 927A60CLG	100	10.5	1521	144.00	Only with specific dimmers	90	2200-2700	15.000	60	108	D	929003011502	32497800
3 MASTERVLE LEDBulbD10.5-100W B22A60 927FRGUK	100	10.5	1521	144.00	Yes	90	2700	15.000	60	107	D	929003011899	32503601

# LED candles & lusters

Candle LED

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficacy	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	lm/W	Angle		Temp.	Hrs.	diameter	length			code
		W	W	lm	lm/W	°		K						
	1 LED 7W T25 E14 WW FR ND 1SRT6	7	0.9	70	77.00	240	80	2700	15.000	25	59	G	929002401355	77169000
NEW	2 LED 15W T25 E14 WW FR ND RF 1SRT6	15	1.7	150	88.00	240	80	2700	15.000	25	59	F	929001325755	77193501
NEW	3 LED 25W T25 E14 WW FR ND 1SRT4	25	3.2	250	78.00	160	80	2700	15.000	25	71	G	929001325855	77195900

SceneSwitch LEDbulbs

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		W	Output	lm/W		Temp.	Hrs.	diameter	length			code
		W	lm	lm/W		K						
	LEDClassic SSW 40W B35 E14 WW CLND 1SRT4	5	470-180-90	94.00	80	2700-2500-2200	15.000	35.5	106	F	929001888855	77215400

# LED candles & lusters

CorePro GLASS LED candles and lusters

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional		Output			Temp.		diameter	length			code
	W	W	lm	lm/W		K	Hrs.					
1 CorePro LEDCandleND 2-25W B35 B22 827CLG	25	2	250	125.00	80	2700	15.000	35	93	E	929001815692	34724300
2 CorePro LEDCandleND 2-25W E14B35 827CL G	25	2	250	125.00	80	2700	15.000	35	97	E	929001238392	37757800
1 CorePro LEDCandleND2-25W B22 827 B35 CLG	25	2	250	125.00	80	2700	15.000	35	94	E	929002023992	34736600
3 CorePro LEDCandleND2-25W E14BA35 827CL G	25	2	250	125.00	80	2700	15.000	35	123	E	929001238492	37759200
4 CorePro LEDCandleND2-25W ST35 E14 827CLG	25	2	250	125.00	80	2700	15.000	35	97	E	929001238592	34772400
5 CorePro LEDLusterND2-25W P45 E14 827 CLG	25	2	250	125.00	80	2700	15.000	45	80	E	929001238692	34774800
6 CorePro LEDLusterND2-25W P45 E27 827 CLG	25	2	250	125.00	80	2700	15.000	45	78	E	929001238792	34776200
7 CorePro LEDCandle ND 2.2-25W B35 E14 FRG	25	2.2	250	113.00	80	2700	15.000	35	97	E	929001345292	34679600
8 CorePro LEDCandleND 2.2-25W BA35 E14 FRG	25	2.2	250	113.00	80	2700	15.000	35	123	E	929001345892	34685700
9 CorePro LEDCandleND2.2-25W E14 840B35CLG	25	2.2	250	113.00	80	4000	15.000	35	97	E	929002023792	34734200
10 CorePro LEDLuster ND 2.2-25W P45 E14 FRG	25	2.2	250	113.00	80	2700	15.000	45	80	E	929001345492	34681900
11 CorePro LEDLuster ND 2.2-25W P45 E27 FRG	25	2.2	250	113.00	80	2700	15.000	45	78	E	929001345692	34683300
12 CorePro LEDLusterND2.2-25W E14 840P45CLG	25	2.2	250	113.00	80	4000	15.000	45	80	E	929002024092	34738000
13 CorePro LEDCandleND4.3-40W B22 827B35CLG	40	4.3	470	109.00	80	2700	15.000	35	93	F	929001889992	34728100
14 CorePro LEDCandleND4.3-40W E14 827B35CLG	40	4.3	470	109.00	80	2700	15.000	35	97	F	929001889792	34726700

# LED candles & lusters

CorePro GLASS LED candles and lusters - Continued

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



10 PACK B22 /E27 /E14

Product Type	Tradi	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	Im/W		Temp.	Hrs.	diameter	length			code
1 CorePro LEDCandleND4.3-40W E14 827B35FRG	40	4.3	470	109.00	80	2700	15.000	35	97	F	929001345392	34718200
2 CorePro LEDCandleND4.3-40W E14 840B35CLG	40	4.3	470	109.00	80	4000	15.000	35	97	F	929002024392	34740300
3 CorePro LEDLusterND4.3-40W E14 827P45CLG	40	4.3	470	109.00	80	2700	15.000	45	82	F	929001890492	34730400
4 CorePro LEDLusterND4.3-40W E14 827P45FRG	40	4.3	470	109.00	80	2700	15.000	45	80	F	929001345592	34720500
5 CorePro LEDLusterND4.3-40W E14 840P45CLG	40	4.3	470	109.00	80	4000	15.000	45	80	F	929002024692	34742700
6 CorePro LEDLusterND4.3-40W E27 827P45CLG	40	4.3	470	109.00	80	2700	15.000	45	82	F	929001890592	34732800
7 CorePro LEDLusterND4.3-40W E27 827P45FRG	40	4.3	470	109.00	80	2700	15.000	45	78	F	929001345792	34722900
8 CorePro LEDCandleND4.3-40WE14 827B35CLGUK	40	4.3	470	109.00	80	2700	15.000	35	97	F	929001889719	34726701
9 CorePro LEDCandle ND6.5-60W B35E 14827CLG	60	6.5	806	124.00	80	2700	15.000	35	97	E	929002028092	34746500
10 CorePro LEDCandleND6.5-60W B35 E14827FRG	60	6.5	806	124.00	80	2700	15.000	35	97	E	929002028292	34750200
9 CorePro LEDCandleND6.5-60W B35 E14840CLG	60	6.5	806	124.00	80	4000	15.000	35	97	E	929002028192	34748900
10 CorePro LEDCandleND6.5-60W B35E14 865FRG	60	6.5	806	124.00	80	6500	15.000	35	97	E	929002028492	34754000
10 CorePro LEDCandleND6.5-60WB35 E14 840FRG	60	6.5	806	124.00	80	4000	15.000	35	97	E	929002028392	34752600
11 CorePro LEDLusterND6.5-60W P45 E14827CLG	60	6.5	806	124.00	80	2700	15.000	45	80	E	929002028592	34756400
12 CorePro LEDLusterND6.5-60W P45 E14827FRG	60	6.5	806	124.00	80	2700	15.000	45	80	E	929002028792	34760100
11 CorePro LEDLusterND6.5-60W P45 E14840CLG	60	6.5	806	124.00	80	4000	15.000	45	80	E	929002028692	34758800
12 CorePro LEDLusterND6.5-60W P45 E14840FRG	60	6.5	806	124.00	80	4000	15.000	45	80	E	929002028892	34762500
12 CorePro LEDLusterND6.5-60W P45 E14865FRG	60	6.5	806	124.00	80	6500	15.000	45	80	E	929002028992	34764900
13 CorePro LEDLusterND6.5-60W P45 E27827CLG	60	6.5	806	124.00	80	2700	15.000	45	78	E	929002029092	34766300
7 CorePro LEDLusterND6.5-60W P45 E27827FRG	60	6.5	806	124.00	80	2700	15.000	45	78	E	929002029292	34768700
7 CorePro LEDLusterND6.5-60W P45 E27840FRG	60	6.5	806	124.00	80	4000	15.000	45	78	E	929002029392	34770000

# LED candles & lusters

CorePro Plastic LEDcandles & lusters

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	lm/W		Temp.	Hrs.	diameter	length			code
		W	W	lm			K						
NEW	1 CorePro LEDcandle ND 2.8-25W E14 827 B35 FR	25	2.8	250	89.00	80	2700	15.000	35	106	F	929002966802	31240100
NEW	2 CorePro LEDcandle ND 2.8-25W E14 840 B35 FR	25	2.8	250	89.00	80	4000	15.000	35	106	F	929002967402	31246300
NEW	3 CorePro lustre ND 2.8-25W E14 827 P45 FR	25	2.8	250	89.00	80	2700	15.000	35	106	F	929002967102	31244900
NEW	3 CorePro lustre ND 2.8-25W E14 840 P45 FR	25	2.8	250	89.00	80	4000	15.000	45	88	F	929002967702	31248700
NEW	4 CorePro lustre ND 2.8-25W E27 827 P45 FR	25	2.8	250	89.00	80	2700	15.000	45	88	F	929002966902	31242500
NEW	1 CorePro LEDcandle ND 5-40W E14 827 B35 FR	40	5	470	94.00	80	2700	15.000	45	87	F	929002968402	31250000
NEW	2 CorePro LEDcandle ND 5-40W E14 840 B35 FR	40	5	470	94.00	80	4000	15.000	38	114	F	929002968802	31254800
NEW	2 CorePro LEDcandle ND 5-40W E14 865 B35 FR	40	5	470	94.00	80	6500	15.000	35	106	F	929002969202	31258600
NEW	3 CorePro lustre ND 5-40W E14 827 P45 FR	40	5	470	94.00	80	2700	15.000	45	87	F	929002969602	31264700
NEW	3 CorePro lustre ND 5-40W E14 840 P45 FR	40	5	470	94.00	80	4000	15.000	45	88	F	929002970002	31268500
NEW	3 CorePro lustre ND 5-40W E14 865 P45 FR	40	5	470	94.00	80	6500	15.000	45	88	F	929002970402	31272200
NEW	5 CorePro Lustre ND 5-40W E27 827 P45 FR	40	5	470	94.00	80	2700	15.000	45	88	F	929002969402	31262300
NEW	6 CorePro LEDcandle ND 7-60W E14 827 B38 FR	60	7	806	115.00	80	2700	15.000	38	114	E	929002972502	31296800
NEW	6 CorePro LEDcandle ND 7-60W E14 840 B38 FR	60	7	806	115.00	80	4000	15.000	38	114	E	929002972702	31298200
NEW	6 CorePro LEDcandle ND 7-60W E14 865 B38 FR	60	7	806	115.00	80	6500	15.000	48	93	E	929002972902	31300200
NEW	7 CorePro lustre ND 7-60W E14 827 P48 FR	60	7	806	115.00	80	2700	15.000	48	93	E	929002973102	31304000
NEW	7 CorePro lustre ND 7-60W E14 840 P48 FR	60	7	806	115.00	80	4000	15.000	48	95	E	929002973302	31308800
NEW	7 CorePro lustre ND 7-60W E14 865 P48 FR	60	7	806	115.00	80	6500	15.000	35	106	E	929002973502	31310100
NEW	8 CorePro lustre ND 7-60W E27 827 P48 FR	60	7	806	115.00	80	2700	15.000	48	95	E	929002973002	31302600
NEW	8 CorePro lustre ND 7-60W E27 840 P48 FR	60	7	806	115.00	80	4000	15.000	48	95	E	929002973202	31306400

# LED candles & lusters

CorePro Plastic LED Specialties

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)




12 PACK E14

Product Type	Tradi	LED	Lumen	Efficacy	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W	Angle		Temp.	Hrs.	diameter	length			code
1 Corepro LED T25 ND 1.7-15W E14 827	15	1.7	150	88.00	240	80	2700	15.000	25	59	F	929001325702	38986100
2 Corepro LED T25 ND 3.2-25W E14 827	25	3.2	250	78.00	160	80	2700	15.000	25	71	G	929001325802	38984700

## MASTER Value Decorative LED candles and lusters

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



10 PACK E27/E14

Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	12NC	EOC
	tional	W	Output	lm/W			Temp.	Hrs.		code
1 MAS VLE LEDCandleD2.5-15WE14 B35GOLDSP G	15	2.5	136	54.00	Yes	80	1800	15.000	929002983202	31603400
2 MAS VLE LEDBulbD2.6-15W E27 GOLDP45SP G	15	2.6	136	52.00	Yes	80	1800	15.000	929002983402	31607200
3 MAS VLE LEDLusterD2.6-15W E14 P45 SP G	15	2.6	136	52.00	Yes	80	1800	15.000	929002983302	31605800



# LED candles & lusters

MASTER Value GLASS LED candles and lusters

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W			Temp.						
	W	W	lm	lm/W			K	Hrs.					
1 MASTER VLE LEDCandleDT2.5-25W E14 B35CL G	25	2.5	340	136.00	Only with specific dimmers	90	2200-2700	15.000	35	97	D	929003011902	32505000
2 MASTER VLE LEDLusterDT2.5-25W E14 927P45CLG	25	2.5	340	136.00	Only with specific dimmers	90	2200-2700	15.000	45	80	D	929003012002	32507400
3 MASTER VLE LEDLusterDT2.5-25W E27 927P45CLG	25	2.5	340	136.00	Only with specific dimmers	90	2200-2700	15.000	45	78	D	929003012102	32509800
4 MASTER VLE LEDCandleD3.4-40W E14 B35 927CLG	40	3.4	470	138.00	Only with specific dimmers	90	2700	15.000	35	97	D	929003059502	35543900
5 MASTER VLE LEDCandleD3.4-40W E14 B35 927FRG	40	3.4	470	138.00	Only with specific dimmers	90	2700	15.000	35	97	D	929003059702	35545300
6 MASTER VLE LEDCandleDT3.4-40W B15 927B35CLG	40	3.4	470	138.00	Only with specific dimmers	90	2200-2700	15.000	35	96	D	929003012502	32517300
7 MASTER VLE LEDCandleDT3.4-40W B22 927B35CLG	40	3.4	470	138.00	Only with specific dimmers	90	2200-2700	15.000	35	94	D	929003012402	32515900
8 MASTER VLE LEDCandleDT3.4-40W E14 927B35CLG	40	3.4	470	138.00	Only with specific dimmers	90	2200-2700	15.000	35	97	D	929003012202	32511100
9 MASTER VLE LEDCandleDT3.4-40W E14927BA35CLG	40	3.4	470	138.00	Only with specific dimmers	90	2200-2700	15.000	35	119	D	929003013002	32519700
10 MASTER VLE LEDCandleDT3.4-40W E27 927B35CLG	40	3.4	470	138.00	Only with specific dimmers	90	2200-2700	15.000	35	95	D	929003012302	32513500
11 MASTER VLE LEDLusterD3.4-40W E14 P45 927CLG	40	3.4	470	138.00	Only with specific dimmers	90	2700	15.000	45	80	D	929003060002	35547700
12 MASTER VLE LEDLusterD3.4-40W E14 P45 927FRG	40	3.4	470	138.00	Only with specific dimmers	90	2700	15.000	45	80	D	929003060202	35549100
13 MASTER VLE LEDLusterD3.4-40W E27 P45 927CLG	40	3.4	470	138.00	Only with specific dimmers	90	2700	15.000	45	78	D	929003060402	35551400
14 MASTER VLE LEDLusterD3.4-40W E27 P45 927FRG	40	3.4	470	138.00	Only with specific dimmers	90	2700	15.000	45	78	D	929003060602	35553800

# LED candles & lusters

MASTER Value GLASS LED candles and lusters - Continued

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	Im/W			Temp.	Hrs.	diameter	length			
1 MASTER VLE LEDLusterDT3.4-40W E14 927P45CLG	40	3.4	470	138.00	Only with specific dimmers	90	2200-2700	15.000	45	80	D	929003013102	32521000
2 MASTERVLE LEDCandleDT3.4-40WE14 927B35CLGUK	40	3.4	470	138.00	Yes	90	2200-2700	15.000	35	97	D	929003012298	32511101
3 MASTER VLE LEDLusterDT3.5-40W E27 927P45CLG	40	3.5	470	134.00	Yes	90	2200-2700	15.000	45	78	D	929003013202	38774400
4 MASTER VLE LEDLusterDT3.5-40W E27 927P45FRG	40	3.5	470	134.00	Yes	90	2200-2700	15.000	45	78	D	929003013602	38800000

# LED candles & lusters

MASTER Plastic LEDcandles & lusters

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



	Product Type	Tradi	LED	Lumen	Efficacy	Dimmable	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	lm/W			Temp.	Hrs.	diameter	length			
		W	W	lm	lm/W			K						
NEW	1 MASTER LEDcandle DT 2.8-25W B22 B38 CL	25	2.8	250	89.00	Only with specific dimmers	80	2200-2700	25.000	38	111	F	929002490502	30610300
NEW	2 MASTER LEDcandle DT 2.8-25W E14 B38 CL	25	2.8	250	89.00	Only with specific dimmers	80	2200-2700	25.000	38	113	F	929002490402	30602800
NEW	3 MASTER LEDcandle DT 2.8-25W E14 BA38 CL	25	2.8	250	89.00	Only with specific dimmers	80	2200-2700	25.000	38	129	F	929002490602	30604200
NEW	4 MASTER LEDlustre DT 2.8-25W E14 P48 CL	25	2.8	250	89.00	Only with specific dimmers	80	2200-2700	25.000	50	95	F	929002490702	30606600
NEW	5 MASTER LEDlustre DT 2.8-25W E27 P48 CL	25	2.8	250	89.00	Only with specific dimmers	80	2200-2700	25.000	50	93	F	929002490802	30608000
NEW	6 MASTER LEDcandle DT 5.5-40W B15 B38 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	38	113	F	929002490902	30612700
NEW	6 MASTER LEDcandle DT 5.5-40W B15 B38 CL UK	40	5.5	470	85.00	Yes	80	2200-2700	25.000	38	113	F	929002490999	30612701
NEW	1 MASTER LEDcandle DT 5.5-40W B22 B38 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	38	111	F	929002491102	30622600
NEW	1 MASTER LEDcandle DT 5.5-40W B22 B38 CL UK	40	5.5	470	85.00	Yes	80	2200-2700	25.000	38	111	F	929002491199	30622601
NEW	2 MASTER LEDcandle DT 5.5-40W E14 B38 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	38	113	F	929002491002	30614100
NEW	2 MASTER LEDcandle DT 5.5-40W E14 B38 CL UK	40	5.5	470	85.00	Yes	80	2200-2700	25.000	38	113	F	929002491099	30614101
NEW	3 MASTER LEDcandle DT 5.5-40W E14 BA38 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	38	129	F	929002491302	30616500
NEW	7 MASTER LEDcandle DT 5.5-40W E27 B38 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	38	112	F	929002491202	30638700
NEW	7 MASTER LEDcandle DT 5.5-40W E27 B38 CL UK	40	5.5	470	85.00	Yes	80	2200-2700	25.000	38	112	F	929002491299	30638701
NEW	8 MASTER LEDlustre DT 5.5-40W B22 P48 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	50	93	F	929002491502	30636300
NEW	4 MASTER LEDlustre DT 5.5-40W E14 P48 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	50	95	F	929002491402	30618900
NEW	5 MASTER LEDlustre DT 5.5-40W E27 P48 CL	40	5.5	470	85.00	Only with specific dimmers	80	2200-2700	25.000	50	93	F	929002491602	30620200
NEW	9 MASTER LEDcandle DT 8-60W B40 E14 827 CL	60	8	806	100.00	Only with specific dimmers	80	2200-2700	25.000	42	127	F	929002491702	30640000
NEW	10 MASTER LEDlustre DT 8-60W P50 E14 827 CL	60	8	806	100.00	Only with specific dimmers	80	2200-2700	25.000	54	109	F	929002491802	30642400

# Philips LED tubes

 Office	 Industry	 Parking	 Retail	 Public building
 <b>MasterConnect LEDtube T8</b> up to 3700 lm	 <b>MasterConnect LEDtube T8</b> up to 3700 lm	 <b>MasterConnect LEDtube T8</b> up to 3700 lm	 <b>MasterConnect LEDtube T8</b> up to 3700 lm	 <b>MasterConnect LEDtube T8</b> up to 3700 lm
 <b>MASTER LEDtube T8</b> HO up to 3100 lm UO up to 3700 lm UE up to 3700 lm	 <b>MASTER LEDtube T8</b> HO up to 3100 lm UO up to 3700 lm UE up to 3700 lm	 <b>MASTER LEDtube T8</b> HO up to 3100 lm	 <b>MASTER LEDtube T8</b> HO up to 3100 lm UO up to 3700 lm	 <b>MASTER LEDtube T8</b> HO up to 3100 lm
 <b>MASTER LEDtube T5</b> HE up to 3000 lm	 <b>MASTER LEDtube T5</b> HO up to 3900 lm UO up to 5600 lm	 <b>MASTER LEDtube T5</b> HO up to 3900 lm	 <b>MASTER LEDtube T5</b> HO up to 3900 lm	 <b>MASTER LEDtube T5</b> HE up to 3000 lm HO up to 3900 lm
 <b>MASTER Value LEDtube T8</b> HO up to 3100 lm UO up to 3700 lm	 <b>MASTER Value LEDtube T8</b> HO up to 3100 lm UO up to 3700 lm	 <b>MASTER Value LEDtube T8</b> HO up to 3100 lm	 <b>MASTER Value LEDtube T8</b> HO up to 3100 lm UO up to 3700 lm	 <b>MASTER Value LEDtube T8</b> HO up to 3100 lm
 <b>CorePro LEDtube T8</b> SO up to 2200 lm				

# Real pros have the perfect LED tube for every job

Simplicity and ultra-efficiency make Philips LED tubes the quickest and easiest way to upgrade to LED for immediate energy savings over a long and reliable lifetime.

We have an LED tube for every application: bright easy-to-fit tubes that last and last. All our LED tubes have the industry's lowest failure rates for ultra reliable operation and lifetime – and they won't flicker or cause glare.

Our range has the widest ballast compatibility in the market, including the great majority of 600, 1200 and 1500mm versions.

Choose CorePro LEDtubes for everyday replacement of fluorescent tubes in general applications. The MASTER Value range offers strong performance in

more demanding applications with intense usage, while the MASTER range is the right choice for every project that calls for best in class performance. MasterConnect LEDtubes are Interact Ready and can be integrated into smart lighting systems for personal and automated light control.

All Philips LED tubes offer safe and hassle-free installation with a simple tube-for-tube replacement. Our EM/Mains, InstantFit HF and universal tubes fit straight into existing luminaires.



#### Fast and easy installation

Philips LED tubes are true retro-fit, making it the fastest-to-install solution.



#### Hassle-free compatibility

- No wires to replace or drivers to change
- InstantFit solutions work with HF electronic ballasts
- Universal LED tubes available – compatible with all ballast types



#### Pin safety

- Safe to touch the end cap when installing
- Integrated driver isolated from touchable parts
- Meets UL and IEC pin safety requirements



#### Trusted performance

- Low early failures
- Warranty up to 7 years
- High resistance to switching cycles

Contents

Interact Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles & lusters

LED tubes

LED PL-lamps


TrueForce





Finding the right LED tubes for different plans, needs and budgets is easy with the extensive Philips portfolio. It ensures that you always have a quality solution at the price you want.

Range tiering



# Philips MasterConnect LEDtubes

Take the first step into connected lighting with Philips MasterConnect LEDtubes.

MasterConnect LEDtubes are smart retrofit LED tubes that give you an easy and seamless way to upgrade and embrace all benefits of connected lighting.

Thanks to the proven wireless connected technology, MasterConnect LEDtubes maximize energy savings, while providing wireless and automated light for your comfort and convenience.

- Retrofit to T8 lamps on EM ballast or mains
- 55% energy savings compared with fluorescent lamps
- Extra-long lifetime of 60,000 hrs
- Perfect for office, school, retail, healthcare, parking and warehouse

interact ready.



Works with Interact and Philips MasterConnect apps

# Philips MASTER LEDtube UE

The new Philips MASTER LEDtube UE: our most energy-efficient LED tube yet.

## Best-in-class efficiency

- Ultra energy efficient with up to 185 lm/W
- Class B energy efficiency rating
- Saves up to 72% energy compared to a conventional fluorescent equivalence
- Payback period of only 6.5 months
- 70,000 hrs lifetime: reduces maintenance cycle by 4.7x
- 7 years warranty\* to ensure peace of mind


## General benefits of the MASTER LEDtube range

- Ultra high lumen package – up to 3700 lumen
- True shatterproof according to IEC standards
- Uniform directional light due to rotatable endcap design
- High flux – thanks to small beam angle of 160 degrees

[Click here to see all products](#)

Product highlights

New!



\* For warranty conditions, visit [www.lighting.philips.com/main/support/support/warranty](http://www.lighting.philips.com/main/support/support/warranty)



Add switches for wireless lighting



Add sensors for automated lighting



Add a gateway for connected lighting



# LED tubes

MASTER LEDtube EM/Mains T8

[www.philips.com/ledtube](http://www.philips.com/ledtube)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
1 MASTER LEDtube 600mm HO 8W830 T8	8	1000	125.00	160	83	3000	70.000	25.78	600	E	929001307002	69747400
1 MASTER LEDtube 600mm HO 8W840 T8	8	1050	131.00	160	83	4000	70.000	25.78	600	E	929001307102	69749800
1 MASTER LEDtube 600mm HO 8W865 T8	8	1050	131.00	160	83	6500	70.000	25.78	600	E	929001307202	69751100
1 MASTER LEDtube 900mm HO 12W 840 T8	12	1575	131.00	160	80	4000	70.000	25.78	900	E	929001298402	68708600
1 MASTER LEDtube 900mm HO 12W 865 T8	12	1575	131.00	160	80	6500	70.000	25.78	900	E	929001298502	68710900
2 MASTER LEDtube 1200mm HO 12.5W 830 T8	12.5	2000	160.00	160	80	3000	70.000	25.8	1200	C	929001922602	59235600
2 MASTER LEDtube 1200mm HO 12.5W 840 T8	12.5	2100	168.00	160	80	4000	70.000	25.8	1200	C	929001922702	59237000
2 MASTER LEDtube 1200mm HO 12.5W 865 T8	12.5	2100	168.00	160	80	6500	70.000	25.8	1200	C	929001922802	59239400
3 MASTER LEDtube 1200mm UE 13.5W 840 T8	13.5	2500	185.00	160	80	4000	70.000	25.8	1200	B	929003067002	33972900
3 MASTER LEDtube 1200mm UE 13.5W 865 T8	13.5	2500	185.00	160	80	6500	70.000	25.8	1200	B	929003067102	33974300
4 MASTER LEDtube 1200mm UO 14.7W 830 T8	14.7	2300	156.00	160	80	3000	70.000	25.8	1200	D	929002998202	31656000
4 MASTER LEDtube 1200mm UO 14.7W 840 T8	14.7	2500	170.00	160	80	4000	70.000	25.8	1200	C	929002998302	31658400
4 MASTER LEDtube 1200mm UO 14.7W 865 T8	14.7	2500	170.00	160	80	6500	70.000	25.8	1200	C	929002998402	31660700
5 MASTER LEDtube 1050mm 16W 830 T8	16	2300	143.00	160	80	3000	70.000	25.8	1100	D	929001375602	72855000
2 MASTER LEDtube 1050mm 16W 840 T8	16	2500	156.00	160	80	4000	70.000	25.8	1100	D	929001961102	61602100
2 MASTER LEDtube 1500mm HO 18.2W 830 T8	18.2	2900	159.00	160	80	3000	70.000	25.8	1500	D	929001922902	59241700
2 MASTER LEDtube 1500mm HO 18.2W 840 T8	18.2	3100	170.00	160	80	4000	70.000	25.8	1500	C	929001923002	59243100
2 MASTER LEDtube 1500mm HO 18.2W 865 T8	18.2	3100	170.00	160	80	6500	70.000	25.8	1500	C	929001923102	59245500
3 MASTER LEDtube 1500mm UE 20W 840 T8	20	3700	185.00	160	80	4000	70.000	25.8	1500	B	929003067202	33976700
3 MASTER LEDtube 1500mm UE 20W 865 T8	20	3700	185.00	160	80	6500	70.000	25.8	1500	B	929003067302	33978100
4 MASTER LEDtube 1500mm UO 21.7W 830 T8	21.7	3400	156.00	160	80	3000	70.000	25.8	1500	D	929002998502	31662100
4 MASTER LEDtube 1500mm UO 21.7W 840 T8	21.7	3700	170.00	160	80	4000	70.000	25.8	1500	C	929002998602	31664500
4 MASTER LEDtube 1500mm UO 21.7W 865 T8	21.7	3700	170.00	160	80	6500	70.000	25.8	1500	C	929002998702	31666900



# LED tubes

## MASTER Value LEDtube T8

[www.philips.com/ledtube](http://www.philips.com/ledtube)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
1 MASTER LEDtube VLE 600mm HO 8W 830 T8	8	1000	125.00	190	80	3000	60.000	25.8	600	E	929002021102	64679000
1 MASTER LEDtube VLE 600mm HO 8W 840 T8	8	1050	131.00	190	80	4000	60.000	25.8	600	E	929002021202	64681300
1 MASTER LEDtube VLE 600mm HO 8W 865 T8	8	1050	131.00	190	80	6500	60.000	25.8	600	E	929002021302	64683700
2 MASTER LEDtube VLE 1200mm HO 14W 830 T8	14	2000	142.00	190	80	3000	60.000	25.8	1200	D	929002021402	64685100
2 MASTER LEDtube VLE 1200mm HO 14W 840 T8	14	2100	150.00	190	80	4000	60.000	25.8	1200	D	929002021502	64687500
2 MASTER LEDtube VLE 1200mm HO 14W 865 T8	14	2100	150.00	190	80	6500	60.000	25.8	1200	D	929002021602	64689900
2 MASTER LEDtube VLE 1200mm UO 15.5W 830 T8	15.5	2300	148.00	190	80	3000	60.000	25.8	1200	D	929002997602	31680500
2 MASTER LEDtube VLE 1200mm UO 15.5W 840 T8	15.5	2500	161.00	190	80	4000	60.000	25.8	1200	C	929002997702	31682900
2 MASTER LEDtube VLE 1200mm UO 15.5W 865 T8	15.5	2500	161.00	190	80	6500	60.000	25.8	1200	C	929002997802	31684300
3 MASTER LEDtube VLE 1500mm HO 20.5W 830 T8	20.5	2900	141.00	190	80	3000	60.000	25.8	1500	D	929002021702	64691200
3 MASTER LEDtube VLE 1500mm HO 20.5W 840 T8	20.5	3100	151.00	190	80	4000	60.000	25.8	1500	D	929002021802	64693600
3 MASTER LEDtube VLE 1500mm HO 20.5W 865 T8	20.5	3100	151.00	190	80	6500	60.000	25.8	1500	D	929002021902	64695000
2 MASTER LEDtube VLE 1500mm UO 23W 830 T8	23	3400	147.00	190	80	3000	60.000	25.8	1500	D	929002997902	31686700
2 MASTER LEDtube VLE 1500mm UO 23W 840 T8	23	3700	160.00	190	80	4000	60.000	25.8	1500	C	929002998002	31688100
2 MASTER LEDtube VLE 1500mm UO 23W 865 T8	23	3700	160.00	190	80	6500	60.000	25.8	1500	C	929002998102	31690400

## MASTER Value LEDtube Universal T8

[www.philips.com/ledtube](http://www.philips.com/ledtube)




Product Type	LED	Lumen Output	Efficiency	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
MAS LEDtube VLE UN 1200mm UO 15.5W830 T8	15.5	2300	148.00	190	80	3000	60.000	26	1200	D	929002997002	31668300
MAS LEDtube VLE UN 1200mm UO 15.5W840 T8	15.5	2500	161.00	190	80	4000	60.000	26	1200	C	929002997102	31670600
MAS LEDtube VLE UN 1200mm UO 15.5W865 T8	15.5	2500	161.00	190	80	6500	60.000	26	1200	C	929002997202	31672000
MAS LEDtube VLE UN 1500mm UO 23W830 T8	23	3400	147.00	190	80	3000	60.000	26	1500	D	929002997302	31674400
MAS LEDtube VLE UN 1500mm UO 23W840 T8	23	3700	160.00	190	80	4000	60.000	26	1500	C	929002997402	31676800
MAS LEDtube VLE UN 1500mm UO 23W865 T8	23	3700	160.00	190	80	6500	60.000	26	1500	C	929002997502	31678200

# LED tubes

MASTER LEDtube InstantFit HF T8

[www.philips.com/ledtube](http://www.philips.com/ledtube)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
1 MASTER LEDtube HF 600mm HO 8W830 T8	8	1000	125.00	160	83	3000	60.000	25.6	600	E	929001393102	74353900
1 MASTER LEDtube HF 600mm HO 8W840 T8	8	1050	131.00	160	83	4000	60.000	25.6	600	E	929001393202	74355300
1 MASTER LEDtube HF 600mm HO 8W865 T8	8	1050	131.00	160	83	6500	60.000	25.6	600	E	929001393302	74367600
2 MASTER LEDtube HF 1200mm 14W 833 T8 FOOD	14	1000	71.00	160	80	3300	60.000	25.6	1200	n/a	929002479402	29616900
2 MASTER LEDtube HF 1200mm HO 14W830 T8	14	2000	142.00	160	83	3000	60.000	25.6	1200	E	929001284302	68752900
2 MASTER LEDtube HF 1200mm HO 14W840 T8	14	2100	150.00	160	83	4000	60.000	25.6	1200	D	929001284102	68748200
2 MASTER LEDtube HF 1200mm HO 14W865 T8	14	2100	150.00	160	83	6500	60.000	25.6	1200	D	929001284202	68750500
2 MASTER LEDtube HF 1200mm UO 16W830 T8	16	2350	146.00	160	83	3000	60.000	25.6	1200	D	929001300202	68800700
2 MASTER LEDtube HF 1200mm UO 16W840 T8	16	2500	156.00	160	83	4000	60.000	25.6	1200	D	929001300002	68796300
2 MASTER LEDtube HF 1200mm UO 16W865 T8	16	2500	156.00	160	83	6500	60.000	25.6	1200	D	929001300102	68798700
2 MASTER LEDtube HF 1500mm HO 20W830 T8	20	2900	145.00	160	83	3000	60.000	25.6	1500	E	929001284602	68758100
2 MASTER LEDtube HF 1500mm HO 20W840 T8	20	3100	155.00	160	83	4000	60.000	25.6	1500	D	929001284402	68754300
2 MASTER LEDtube HF 1500mm HO 20W865 T8	20	3100	155.00	160	83	6500	60.000	25.6	1500	D	929001284502	68756700
2 MASTER LEDtube HF 1500mm UO 24W830 T8	24	3500	145.00	160	83	3000	60.000	25.6	1500	D	929001300502	68806900
2 MASTER LEDtube HF 1500mm UO 24W840 T8	24	3700	154.00	160	83	4000	60.000	25.6	1500	D	929001300302	68802100
2 MASTER LEDtube HF 1500mm UO 24W865 T8	24	3700	154.00	160	83	6500	60.000	25.6	1500	D	929001300402	68804500

# LED tubes

MASTER LEDtube InstantFit HF T5

[www.philips.com/ledtube](http://www.philips.com/ledtube)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	Dimmable	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°			K	Hrs.					
1 Master LEDtube HF 600mm HE 8W 830 T5	8	1000	125.00	200	Yes - Check ballast compatibility	80	3000	60.000	15.5	600	E	929001390702	74323200
1 Master LEDtube HF 600mm HE 8W 840 T5	8	1050	131.00	200	Yes - Check ballast compatibility	80	4000	60.000	15.5	600	E	929001390802	74325600
1 Master LEDtube HF 600mm HE 8W 865 T5	8	1050	131.00	200	Yes - Check ballast compatibility	80	6500	60.000	15.5	600	E	929001390902	74327000
1 Master LEDtube HF 1200mm HE 16.5W 830 T5	16.5	2300	139.00	200	Yes - Check ballast compatibility	80	3000	60.000	15.5	1200	E	929001391002	74329400
1 Master LEDtube HF 1200mm HE 16.5W 840 T5	16.5	2500	151.00	200	Yes - Check ballast compatibility	80	4000	60.000	15.5	1200	D	929001391102	74331700
1 Master LEDtube HF 1200mm HE 16.5W 865 T5	16.5	2500	151.00	200	Yes - Check ballast compatibility	80	6500	60.000	15.5	1200	D	929001391202	74333100
1 Master LEDtube HF 1500mm HE 20W 830 T5	20	2800	140.00	200	Yes - Check ballast compatibility	80	3000	60.000	15.5	1500	E	929001391302	74335500
1 Master LEDtube HF 1500mm HE 20W 840 T5	20	3000	150.00	200	Yes - Check ballast compatibility	80	4000	60.000	15.5	1500	D	929001391402	74337900
1 Master LEDtube HF 1500mm HE 20W 865 T5	20	3000	150.00	200	Yes - Check ballast compatibility	80	6500	60.000	15.5	1500	D	929001391502	74339300
2 Master LEDtube HF 1200mm HO 26W 830 T5 OE	26	3700	142.00	200	Yes - Check ballast compatibility	80	3000	60.000	15.5	1200	E	929002352002	74951400
2 Master LEDtube HF 1200mm HO 26W 840 T5 OE	26	3900	150.00	200	Yes - Check ballast compatibility	80	4000	60.000	15.5	1200	D	929002352102	74953800
2 Master LEDtube HF 1200mm HO 26W 865 T5 OE	26	3900	150.00	200	Yes - Check ballast compatibility	80	6500	60.000	15.5	1200	D	929002352202	74955200
2 Master LEDtube HF 1500mm HO 26W 830 T5 OE	26	3700	142.00	200	Yes - Check ballast compatibility	80	3000	60.000	15.5	1500	E	929002352302	74957600
2 Master LEDtube HF 1500mm HO 26W 840 T5 OE	26	3900	150.00	200	Yes - Check ballast compatibility	80	4000	60.000	15.5	1500	D	929002352402	74959000
2 Master LEDtube HF 1500mm HO 26W 865 T5 OE	26	3900	150.00	200	Yes - Check ballast compatibility	80	6500	60.000	15.5	1500	D	929002352502	74961300
NEW 3 Master LEDtube HF 1500mm UO 36W 830 T5	36	5200	144.00	200	Yes - Check ballast compatibility	80	3000	60.000	15.5	1500	E	929003153902	41905600
NEW 3 Master LEDtube HF 1500mm UO 36W 840 T5	36	5600	155.00	200	Yes - Check ballast compatibility	80	4000	60.000	15.5	1500	D	929003154002	41907000
NEW 3 Master LEDtube HF 1500mm UO 36W 865 T5	36	5600	155.00	200	Yes - Check ballast compatibility	80	6500	60.000	15.5	1500	D	929003154102	41909400

OE: Office Enabled LED tube light with the following benefits:

- True Retrofit due to High Compatibility
- Dimmable (1-10V and Dali Ballast)
- Compatible with Multi- Watt ballasts
- Supports UGR 19 applications due to Glass Design with wider beam angle

[Please visit the website for the compatibility list of dimmable and non-dimmable ballasts.](#)

# LED tubes

MASTER LEDtube Mains T5

[www.philips.com/ledtube](http://www.philips.com/ledtube)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
1 MASTER LEDtube 600mm HE 8W 830 T5 EU	8	1000	125.00	200	80	3000	50.000		600	E	929003044102	33425000
1 MASTER LEDtube 600mm HE 8W 840 T5 EU	8	1050	131.00	200	80	4000	50.000		600	E	929003044202	33427400
1 MASTER LEDtube 600mm HE 8W 865 T5 EU	8	1050	131.00	200	80	6500	50.000		600	E	929003044302	33429800
1 MASTER LEDtube 1200mm HE 16.5W 830 T5 EU	16.5	2300	139.00	200	80	3000	50.000		1200	D	929003044402	33431100
1 MASTER LEDtube 1200mm HE 16.5W 840 T5 EU	16.5	2500	151.00	200	80	4000	50.000		1200	D	929003044502	33433500
1 MASTER LEDtube 1200mm HE 16.5W 865 T5 EU	16.5	2500	151.00	200	80	6500	50.000		1200	D	929003044602	33435900
1 MASTER LEDtube 1500mm HE 20W 830 T5 EU	20	2800	140.00	200	80	3000	50.000	15.8	1500	D	929002421202	33437300
1 MASTER LEDtube 1500mm HE 20W 840 T5 EU	20	3000	150.00	200	80	4000	50.000	15.8	1500	D	929002421302	33439700
1 MASTER LEDtube 1500mm HE 20W 865 T5 EU	20	3000	150.00	200	80	6500	50.000	15.8	1500	D	929002421402	33441000
1 MASTER LEDtube 1200mm HO 26W 830 T5	26	3600	138.00	200	80	3000	50.000	15	1200	D	929001908502	81921000
1 MASTER LEDtube 1200mm HO 26W 840 T5	26	3900	150.00	200	80	4000	50.000	15	1200	D	929001908602	81923400
1 MASTER LEDtube 1200mm HO 26W 865 T5	26	3900	150.00	200	80	6500	50.000	15	1200	D	929001908702	81925800
1 MASTER LEDtube 1500mm HO 26W 830 T5	26	3600	138.00	200	80	3000	50.000	15	1500	D	929001908802	81929600
1 MASTER LEDtube 1500mm HO 26W 840 T5	26	3900	150.00	200	80	4000	50.000	15	1500	D	929001908902	81931900
1 MASTER LEDtube 1500mm HO 26W 865 T5	26	3900	150.00	200	80	6500	50.000	15	1500	D	929001909002	81933300
2 MASTER LEDtube 1500mm UO 36W 830 T5	36	5200	144.00	200	80	3000	50.000	15.5	1500	D	929002474802	29050100
2 MASTER LEDtube 1500mm UO 36W 840 T5	36	5600	155.00	200	80	4000	50.000	15.5	1500	D	929002474902	29052500
2 MASTER LEDtube 1500mm UO 36W 865 T5	36	5600	155.00	200	80	6500	50.000	15.5	1500	D	929002475002	29054900

# LED tubes

## CorePro LEDtube EM/Mains T8

[www.philips.com/ledtube](http://www.philips.com/ledtube)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
CorePro LEDtube 600mm 8W 840 T8	8	800	100.00	240	80	4000	30.000	25.7	600	F	929003022102	32531900
CorePro LEDtube 600mm 8W 865 T8	8	800	100.00	240	80	6500	30.000	25.7	600	F	929003022202	32533300
CorePro LEDtube 1200mm 14.5W840	14.5	1600	110.00	240	80	4000	30.000	25.7	1200	E	929003022302	32535700
CorePro LEDtube 1200mm 14.5W865	14.5	1600	110.00	240	80	6500	30.000	25.7	1200	E	929003022402	32537100
CorePro LEDtube 1200mm HO 18W 840 T8	18	2000	111.00	240	80	4000	30.000	25.7	1200	E	929001874902	80613500
CorePro LEDtube 1200mm HO 18W 865 T8	18	2000	111.00	240	80	6500	30.000	25.7	1200	E	929001874802	80611100
CorePro LEDtube 1500mm 20W 840 T8	20	2200	110.00	240	80	4000	30.000	25.7	1500	E	929003022502	32539500
CorePro LEDtube 1500mm 20W 865 T8	20	2200	110.00	240	80	6500	30.000	25.7	1500	E	929003022602	32541800
CorePro LEDtube 1500mm HO 24W 840 T8	24	2700	112.00	240	80	4000	30.000	25.7	1500	E	929001875102	80617300
CorePro LEDtube 1500mm HO 24W 865 T8	24	2700	112.00	240	80	6500	30.000	25.7	1500	E	929001875002	80615900

## CorePro LED tube Universal T8

[www.philips.com/ledtube](http://www.philips.com/ledtube)



Product Type	LED	Lumen Output	Efficiency	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
CorePro LEDtube UN 600mm HO 8W830 T8	8	850	106.00	240	80	3000	30.000	25.7	600	F	929002419802	78277100
CorePro LEDtube UN 600mm HO 8W840 T8	8	900	112.00	240	80	4000	30.000	25.7	600	E	929002419902	78279500
CorePro LEDtube UN 600mm HO 8W865 T8	8	900	112.00	240	80	6500	30.000	25.7	600	E	929002420002	78281800
CorePro LEDtube UN 1200mm HO 18W830 T8	18	1850	102.00	240	80	3000	30.000	27.9	1200	F	929001869202	80166600
CorePro LEDtube UN 1200mm HO 18W840 T8	18	2000	111.00	240	80	4000	30.000	27.9	1200	E	929001869302	80168000
CorePro LEDtube UN 1200mm HO 18W865 T8	18	2000	111.00	240	80	6500	30.000	27.9	1200	E	929001869402	80170300
CorePro LEDtube UN 1500mm HO 23W830 T8	23	2500	108.00	240	80	3000	30.000	27.9	1500	F	929001869502	80172700
CorePro LEDtube UN 1500mm HO 23W840 T8	23	2700	117.00	240	80	4000	30.000	27.9	1500	E	929001869602	80174100
CorePro LEDtube UN 1500mm HO 23W865 T8	23	2700	117.00	240	80	6500	30.000	27.9	1500	E	929001869702	80176500

# LED PL-lamps

## CorePro LED PLC 2P

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	LED	Lumen Output	Efficacy	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
1 CorePro LED PLC 6.5W 830 2P G24d-2	6.5	650	92.31	120	83	3000	30.000	24.3	100	F	929001201402	54127200
1 CorePro LED PLC 6.5W 840 2P G24d-2	6.5	700	92.31	120	83	4000	30.000	24.3	100	F	929001201502	54129600
2 CorePro LED PLC 8.5W 830 2P G24d-3	8.5	950	105.88	120	83	3000	30.000	24.3	200	F	929001201202	54123400
2 CorePro LED PLC 8.5W 840 2P G24d-3	8.5	1000	105.88	120	83	4000	30.000	24.3	200	F	929001201302	54125800

## CorePro LED PLC 4P

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	LED	Lumen Output	Efficacy	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
1 CorePro LED PLC 6.5W 830 4P G24q-2	6.5	650	92.31	120	83	3000	30.000	24.3	100	F	929001201002	54119700
1 CorePro LED PLC 6.5W 840 4P G24q-2	6.5	700	92.31	120	83	4000	30.000	24.3	100	F	929001201102	54121000
2 CorePro LED PLC 9W 830 4P G24q-3	9	950	100.00	120	83	3000	30.000	24.3	200	F	929001200802	54115900
2 CorePro LED PLC 9W 840 4P G24q-3	9	1000	100.00	120	83	4000	30.000	24.3	200	F	929001200902	54117300

# LED PL-lamps

## CorePro LED PLC

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	LED	Lumen Output	Efficacy	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
1 CorePro LED PLC 4.5W 830 2P G24d-1	4.5	475	105.00	120	83	3000	30.000	24.3	100	F	929001350702	70659600
2 CorePro LED PLC 4.5W 830 4P G24q-1	4.5	475	105.56	120	83	3000	30.000	24.3	100	F	929001351002	70663300
1 CorePro LED PLC 4.5W 840 2P G24d-1	4.5	500	111.00	120	83	4000	30.000	24.3	100	F	929001350802	70661900
2 CorePro LED PLC 4.5W 840 4P G24q-1	4.5	500	111.11	120	83	4000	30.000	24.3	100	F	929001351102	70665700

## CorePro LED PLS

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	LED	Lumen Output	Efficacy	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
CorePro LED PLS 5W 830 2P G23	5	520	104.00	120	82	3000	30.000	15.8	170	F	929001926302	59666800
CorePro LED PLS 5W 840 2P G23	5	550	110.00	120	82	4000	30.000	15.8	170	F	929001926402	59668200

# LED PL-lamps

CorePro LED PLL

[www.philips.com/ledlamps](http://www.philips.com/ledlamps)



Product Type	LED	Lumen Output	Efficacy	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	lm	lm/W	°		K	Hrs.					
1 CorePro LED PLL HF 16.5W 830 4P 2G11	16.5	2000	121.00	160	83	3000	30.000	43.6	400	E	929001381502	73966200
1 CorePro LED PLL HF 16.5W 840 4P 2G11	16.5	2100	127.00	160	83	4000	30.000	43.6	400	E	929001381602	73974700
1 CorePro LED PLL HF 16.5W 865 4P 2G11	16.5	2100	127.00	160	83	6500	30.000	43.6	400	E	929001381702	73976100
2 CorePro LED PLL HF 24W 830 4P 2G11	24	3200	133.00	160	83	3000	30.000	17	540	E	929001920402	82839700
2 CorePro LED PLL HF 24W 840 4P 2G11	24	3400	141.00	160	83	4000	30.000	17	540	E	929001920502	82841000
2 CorePro LED PLL HF 24W 865 4P 2G11	24	3400	141.00	160	83	6500	30.000	17	540	E	929001920602	82843400



# Philips TrueForce



Urban



Retail



Industry



Road & Street



TrueForce Core LED HPL



TrueForce Core LED HPL



TrueForce Core LED highbay HPL



TrueForce Core LED SON-T



TrueForce LED HPL



TrueForce LED highbay universal HPI



TrueForce LED highbay universal HPI



TrueForce LED HPL



TrueForce LED SON-T



TrueForce LED SOX

Contents

Interact  
Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles  
& lusters

LED tubes

LED  
PL-lamps

TrueForce



# Real pros have powerful substitutes for HID

Philips TrueForce LED lamps provide an easy LED solution to replace HPL, HID, SOX as well as SON-T lamps.

Enjoy the benefits of LED like improved energy efficiency and long lifetime, while keeping your initial investment low. With the right lamp size and light distribution, you can easily fit TrueForce LED lamps into your customers existing system, thereby enhancing the light quality without having to change the light fixtures or sacrifice the light effect. Our highest standard LED technology guarantees low maintenance and has a five-year warranty.

Great light should go anywhere, which is why the Philips TrueForce LED range feels at home in a number of applications, from industry and retail to urban, street, and road.

And because budgets can be as varied as applications, the TrueForce family comes in TrueForce LED and the even more cost-effective TrueForce Core LED. Both offer outstanding performance that lasts and performs longer.



#### Easy adoption

No need to change the fixture!



#### Fast payback

It usually takes less than two years for LED lamps to pay for themselves.



#### Low investment, long lifetime

The long lifetime of up to 50,000 hours makes LED a clever investment.



#### Sustainability

Low energy consumption and a longer lifetime make LED lighting the sustainable choice.



#### Right light distribution

Enhances comfort and safety in multiple application areas.



#### Highest standard LED technology

Low maintenance and up to 5 years warranty pay off!

Contents

Interact Ready

CoreLine

Ledinaire

LED spots

LED bulbs

LED candles & lusters

LED tubes

LED PL-lamps

TrueForce





Finding the right lamps for different plans, needs and budgets is easy with the extensive Philips portfolio. It ensures that you always have a quality solution at the price you want.

Range tiering



### Everywhere amazing




#### Industry and Retail

Replace conventional HPL lamps to improve light quality, safety and productivity.



#### Urban

Easily fit TrueForce LED lamps into existing systems and make urban locations more sustainable, brighter and safer.



#### Road, Street and Landscape

Big in performance and low in maintenance: use TrueForce LED lamps to replace conventional SOX, SON-T and CDO lamps.

# Philips TrueForce Core LED SON-T

Product highlight

Discover the new Philips TrueForce Core LED SON-T – the first full glass LED lamp for road lighting.

## Benefits and features

- First LED lamp for road lighting made from glass
- Enables up to 60% energy saving compared to conventional road lighting
- Lower initial investment, shorter payback time
- High efficiency thanks to advanced driver design (GaN technology)
- Lifetime of 25,000 hours
- Direct retrofit solution with E27/E40 cap
- Up to 7500 lm output thanks to mega-filament
- IP65 for long-lasting outdoor use
- Good color rendering (Ra 70) and color temperatures of 3000 and 4000 K

[Click here to see all products](#)



## Instant savings ahead

	Conventional SON-T	TrueForce Core LED SON-T
Energy savings	82W <sup>1</sup>	26W
Lifetime	15,000 hrs	25,000 hrs
Number of lamps	100	Installation cost/light source ≈35 €
Burning hours per year	4380 hrs <sup>2</sup>	Lamp cost 43.50 €
Energy costs	0.12 €/kWh <sup>3</sup>	Relative annual cost/lamp 7.62 €

**2,882 €**  
Energy savings/year

**< 14 months**  
Payback time

**Make the sustainable choice: Over its lifetime, the new Philips TrueForce Core LED SON-T saves the equivalent of the CO<sub>2</sub> emissions absorbed by 2,673 trees!**

<sup>1</sup> Including ballast loss. Lamp consumption is 70W.

<sup>2</sup> Energy use. Based on 12h burning per day, 365 days per year.

<sup>3</sup> Energy price. Based on the European average of 12 cent/kWh.

# TrueForce LED

Trueforce Core LED SON-T

[www.philips.com/trueforce-led-lamps](http://www.philips.com/trueforce-led-lamps)



	Product Type	Tradi	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	lm/W		Temp.	Hrs.	diameter	length			code
		W	W	lm	lm/W		K						
NEW	1 TForce Core LED road 17W 730 E27 MV	50	17	2800	164.00	70	3000	25.000	38	170	C	929002484802	31625600
NEW	1 TForce Core LED road 17W 740 E27 MV	50	17	3000	176.00	70	4000	25.000	38	170	C	929002484902	31627000
NEW	2 TForce Core LED road 26W 730 E27 MV	70	26	4200	161.00	70	3000	25.000	38	210	C	929002485002	31629400
NEW	2 TForce Core LED road 26W 740 E27 MV	70	26	4500	173.00	70	4000	25.000	38	210	C	929002485102	31631700
NEW	3 TForce Core LED road 40W 730 E40 MV	100	40	7200	180.00	70	3000	25.000	46	225	C	929002485202	31633100
NEW	3 TForce Core LED road 40W 740 E40 MV	100	40	7500	187.00	70	4000	25.000	46	225	B	929002485302	31635500

TrueForce LED Industrial and Retail (Highbay – MH)

[www.philips.com/trueforce-led-lamps](http://www.philips.com/trueforce-led-lamps)



	Product Type	Tradi	LED	Lumen	Efficacy	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
		tional	W	Output	lm/W	Angle		Temp.	Hrs.	diameter	length			code
		W	W	lm	lm/W	°		K						
	TrueForce LED HPI UN 95W E40 840 NB	250	95	13.000	136.00	60	80	4000	50.000	250	290	F	929002350702	75367200
	TrueForce LED HPI UN 95W E40 840 WB	250	95	13.000	136.00	120	80	4000	50.000	250	290	E	929002350802	75369600
	TrueForce LED HPI UN 140W E40 840 NB	400	140	20.000	142.00	60	80	4000	50.000	250	290	F	929002350902	75371900
	TrueForce LED HPI UN 140W E40 840 WB	400	140	20.000	142.00	120	80	4000	50.000	250	290	D	929002351002	75373300

# TrueForce LED

TrueForce LED Public (Urban/Road – HPL/SON)

[www.philips.com/trueforce-led-lamps](http://www.philips.com/trueforce-led-lamps)



Product Type	Tradi	LED	Lumen	Efficacy	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W	Angle		Temp.	Hrs.	diameter	length			code
	W	W	lm		°		K						
1 TrueForce LED HPL ND 28-21W E27 830	50	21	2850	135.00	360	80	3000	50.000	75	178	D	929002006102	63814600
1 TrueForce LED HPL ND 30-21W E27 840	50	21	3000	142.00	360	80	4000	50.000	75	178	D	929002006202	63816000
1 TrueForce LED HPL ND 38-28W E27 830	80	28	3800	135.00	360	80	3000	50.000	75	178	D	929002006302	63818400
1 TrueForce LED HPL ND 40-28W E27 840	80	28	4000	142.00	360	80	4000	50.000	75	178	D	929002006402	63820700
2 TrueForce LED HPL ND 57-42W E27 830	125	42	5700	135.00	360	80	3000	50.000	84	178	D	929002006502	63822100
3 TrueForce LED HPL ND 57-42W E40 830	125	42	5700	135.00	360	80	3000	50.000	84	191	D	929002006702	63826900
2 TrueForce LED HPL ND 60-42W E27 840	125	42	6000	142.00	360	80	4000	50.000	84	178	D	929002006602	63824500
3 TrueForce LED HPL ND 60-42W E40 840	125	42	6000	142.00	360	80	4000	50.000	84	191	D	929002006802	63828300

# TrueForce LED

Trueforce CorePro LED HPL

[www.philips.com/trueforce-led-lamps](http://www.philips.com/trueforce-led-lamps)



Product Type	Tradi	LED	Lumen	Efficacy	Beam	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	lm/W	Angle		Temp.	Hrs.	diameter	length			code
	W	W	lm		°		K						
1 TForce Core LED HPL 13W E27 830 FR	50	13	2000	153.00	300	80	3000	25.000	75	180	D	929002349702	75025100
1 TForce Core LED HPL 13W E27 840 FR	50	13	2000	153.00	300	80	4000	25.000	75	180	D	929002349802	75027500
1 TForce Core LED HPL 18W E27 830 FR	80	18	3000	166.00	300	80	3000	25.000	75	180	C	929002349902	75029900
1 TForce Core LED HPL 18W E27 840 FR	80	18	3000	166.00	300	80	4000	25.000	75	180	C	929002350002	75031200
2 TForce Core LED HPL 26W E27 830 FR	125	26	4000	153.00	300	80	3000	25.000	90	245	D	929002350102	75033600
2 TForce Core LED HPL 26W E27 840 FR	125	26	4000	153.00	300	80	4000	25.000	90	245	D	929002350202	75035000
2 TForce Core LED HPL 36W E27 830 FR	200	36	5500	152.00	300	80	3000	25.000	90	245	D	929002481202	29927600
2 TForce Core LED HPL 36W E27 840 FR	200	36	6000	166.00	300	80	4000	25.000	90	245	C	929002481302	29929000
3 TForce Core LED HPL 36W E40 830 FR	200	36	5500	152.00	300	80	3000	25.000	90	230	D	929002481402	29931300
3 TForce Core LED HPL 36W E40 840 FR	200	36	6000	166.00	300	80	4000	25.000	90	230	C	929002481502	29933700

# TrueForce LED

TrueForce Core LED Industrial and Retail (Highbay – HPI/SON/HPL)

[www.philips.com/trueforce-led-lamps](http://www.philips.com/trueforce-led-lamps)



Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	W	lm	lm/W	°		K	Hrs.					
1 TrueForce Core HB MV ND 40-35W E27 840	55	35	4000	114.00	240	80	4000	20.000	105	190		929001938002	59734400
2 TrueForce Core HB MV ND 48-42W E27 830	70	42	4800	114.00	240	80	3000	20.000	123	225		929001938202	59716000
3 TrueForce Core HB MV ND 50-42W E27 840	70	42	5000	119.00	240	80	4000	20.000	123	225		929001938302	59718400
4 TrueForce Core HB MV ND 20W E27 830 G3	80	20	2600	130.00	150	80	3000	15.000	80	139	E	929002405702	78101900
4 TrueForce Core HB MV ND 20W E27 840 G3	80	20	2700	135.00	150	80	4000	15.000	80	139	D	929002405802	78103300
5 TrueForce Core HB MV ND 30W E27 830 G3	125	30	3700	123.00	180	80	3000	15.000	100	165	E	929002406302	78095100
5 TrueForce Core HB MV ND 30W E27 840 G3	125	30	4000	133.00	180	80	4000	15.000	100	165	E	929002406402	78097500
6 TrueForce Core HB MV ND 35W E27 830 G3	125	35	4800	137.00	180	80	3000	15.000	118	193	D	929002406602	78105700
6 TrueForce Core HB MV ND 35W E27 840 G3	125	35	5000	142.00	180	80	4000	15.000	118	193	D	929002406702	78107100

TrueForce LED Public (Road/Area – SOX)

[www.philips.com/trueforce-led-lamps](http://www.philips.com/trueforce-led-lamps)



Product Type	Traditional	LED	Lumen Output	Efficacy	Beam Angle	CRI	Color Temp.	Lifetime	Lamp diameter	Total length	EEL	12NC	EOC code
	W	W	lm	lm/W	°		K	Hrs.					
1 TrueForce LED SOX 18W B22 840 FR	26	18	2500	138.00	230	80	4000	50.000	52	312	D	929002496802	30562500
2 TrueForce LED SOX 28W B22 840 FR	36	28	4000	142.00	230	80	4000	50.000	52	425	D	929002496902	30564900
2 TrueForce LED SOX 36W B22 840 FR	55	36	5000	138.00	230	80	4000	50.000	52	425	D	929002497002	30566300



# TrueForce LED

TrueForce LED Public (Road – SON)

[www.philips.com/trueforce-led-lamps](http://www.philips.com/trueforce-led-lamps)



Product Type	Tradi	LED	Lumen	Efficacy	CRI	Color	Lifetime	Lamp	Total	EEL	12NC	EOC
	tional	W	Output	Im/W		Temp.	Hrs.	diameter	length			code
	W	W	lm			K						
1 TrueForce LED Road 25W E27 730 MV	50	25	4000	160.00	70	3000	50.000	61	200	C	929003041408	33157000
1 TrueForce LED Road 25W E27 740 MV	50	25	4200	168.00	70	4000	50.000	61	200	C	929003041508	33159400
2 TrueForce LED Road 40-25W E27 730	50	25	4000	160.00	70	3000	50.000	61	200	D	929001999402	63251900
2 TrueForce LED Road 42-25W E27 740	50	25	4200	168.00	70	4000	50.000	61	200	D	929001999502	63253300
1 TrueForce LED Road 35W E27 730 MV	70	35	5500	157.00	70	3000	50.000	61	200	D	929002221708	67483000
1 TrueForce LED Road 35W E27 740 MV	70	35	6000	171.00	70	4000	50.000	61	200	C	929002068508	67485400
1 TrueForce LED Road 55-35W E27 730	70	35	5500	157.00	70	3000	50.000	61	200	D	929001898402	81115300
1 TrueForce LED Road 60-35W E27 740	70	35	6000	171.00	70	4000	50.000	61	200	D	929001898502	81117700
3 TrueForce LED Road 112-68W E40 730	100	68	11.200	164.00	70	3000	50.000	71	262	D	929002007602	63908200
3 TrueForce LED Road 120-68W E40 740	100	68	12.000	176.00	70	4000	50.000	71	262	C	929002007702	63910500
4 TrueForce LED Road 55W E40 740 MV	100	55	9000	163.00	70	4000	50.000	71	262	C	929002068708	67479300
4 TrueForce LED Road 84-55W E40 730	100	55	8400	152.00	70	3000	50.000	71	262	D	929002007402	63904400
4 TrueForce LED Road 90-55W E40 740	100	55	9000	163.00	70	4000	50.000	71	262	D	929002007502	63906800

# All you need to know, right at your finger tips

We know that installation is about finding the right solutions. Visit our webpage created especially for installers and find:

- All latest product information
- Selector tools to help you select the right product for your customers
- Installation videos
- Training



© 2022 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

