



PHILIPS

**CorePro LED PLC
CorePro LED PLL
CorePro LED PLT
compatibility list
Professional Q1 2023**



Table of content

Philips CorePro LED PLC

| | |
|--|---|
| • Philips CorePro LED PLC 4.5W 8xx 4P G24q-1 | 2 |
| • Philips CorePro LED PLC 6.5W 8xx 4P G24q-2 | 3 |
| • Philips CorePro LED PLC 9.0W 8xx 4P G24q-3 | 4 |

Philips CorePro LED PLL

| | |
|--|---|
| • Philips CorePro LED PLL HF 8W 8xx 4P 2G11 | 5 |
| • Philips CorePro LED PLL HF 12W 8xx 4P 2G11 | 7 |

Philips CorePro LED PLT

| | |
|------------------------------------|----|
| • Philips CorePro LED PLT HF 6.5W | 9 |
| • Philips CorePro LED PLT HF 9W | 10 |
| • Philips CorePro LED PLT HF 15W | 12 |
| • Philips CorePro LED PLT HF 18.5W | 13 |

Philips CorePro LED PLC 4.5W 8xx 4P G24q-1



Ballast Compatibility

KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Dim |
| | Ballast is compatible and conditional released for dimming |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | Philips CorePro LED PLC 4.5W 8xx 4P G24q-1 |
|---------------------|------------------------------|--------------|--|
| | | | Model number / EOC code: 9290013510 / 871869670663300 9290013511 / 871869670665700 |
| | | | AC (50Hz) on HF Ballast Compatible |
| | Ballast type | 10nc | Lamps on ballast |
| PHILIPS | HF-M 113 TL/PLS/PLC SH | 9137004137 | 1 |
| | HF-M 113 TL/PLS/PLC LH | 9137004139 | 1 |
| | BLUE 114 LH TL/PLS/PLC | 9137004217 | 1 |
| | RED 114 SH TL/TL5/PLC/S | 9137004232 | 1 |
| | HF-P 1 13-17 PL-T/C/R EII | 9137006311 | 1 |
| | HF-P 2 13-17 PL-T/C/R EII | 9137006312 | 2 |
| | EB-C 113 PL-T/C 220 | 9137131984 | 1 |
| | EB-C 213 PL-T/C 220 | 9137131985 | 2 |
| OSRAM | QT-ECO 1X4-16/220-240 L | | 1 |
| | QT-ECO 1X4-16/220-240 S | | 1 |
| | QTP-D/E 1X10-13 | | 1 |
| | QTP-D/E 2X10-13 | | 2 |
| VOSSLOH-SCHWABE | ELXc 213.870 188698 | 188698 | 2 |
| | ELXc 213.870 188698 | 188698 | 1 |
| | ELXs 121.901 188663 | 188663 | 1 |
| | ELXs 121.904 188664 | 188664 | 1 |
| TRIDONIC | PCA 1x11/13 TC EXCEL one4all | 22185134 | 1 |
| | PCA 1x11/13 TC ECO | 22185126 | 1 |
| | PCA 2x11/13 TC EXCEL one4all | 22185135 | 2 |
| | PCA 2x11/13 TC ECO | 22185127 | 2 |
| | PC 1x5-16W BASIC | 24138830 | 1 |
| | PC 1x5-16W BASIC sl | 24138833 | 1 |
| | PC 1/2x9-13 TC PRO | 22176405 | 2 |
| | PC 1/2x9-13 TC PRO | 22176405 | 1 |
| BAG HUECO | BCD13.1-2Q-01/220-240/1-10V | 10096393 | 2 |
| | BCD13.1-2Q-01/220-240/1-10V | 10096393 | 1 |
| | BCS21.1-2LS-01/220-240 | 10095043 | 2 |
| | BCS21.1-2LS-01/220-240 | 10095043 | 1 |
| | BCS21.1-2Q-01/220-240 | 10097543 | 2 |
| | BCS21.1-2Q-01/220-240 | 10097543 | 1 |
| | BCS21.1-2QI-01/220-240 | 10095743 | 2 |
| | BCS21.1-2QI-01/220-240 | 10095743 | 1 |
| | EBS21.1C-01/220-240 | 10050990 | 1 |
| | EBS21.1M-01/220-240 | 10050994 | 1 |
| EBS16.1C-01/220-240 | 10050989 | 1 | |
| TCI | BCC 121 | 137946HTC | 1 |
| | BCC 121/2 | 137969/21MM | 1 |
| | BCC 121/2 SL | 137944/21H | 1 |
| | BCC 121 SL | 137944B/21H | 1 |
| | BCC 121 IP54 | 137969IP21MM | 1 |
| | MBQ 113/2 | 137968/113 | 1 |
| | MB213 | 137988/213 | 2 |
| | MB213/2 | 137988/2132 | 2 |
| MBQ 213/2 | 37968/213 | 2 | |

General note Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply

Philips CorePro LED PLC 6.5W 8xx 4P G24q-2



Ballast Compatibility

KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Ballast is compatible and conditional released for dimming |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | CorePro LED PLC 6.5W 8xx 4P G24q-2 |
|-----------------|--|-------------|--|
| | | | Model number / EOC code: 9290012010 / 871869654119700 9290012011 / 871869654121000 |
| | | | AC (50Hz) on HF Ballast Compatible |
| | Ballast type | 10nc | Lamps on ballast |
| PHILIPS | HF-P 118 PL-T/C III 220-240V 50/60Hz | 9137006485 | 1 |
| | HF-P 1/218 PL-T/C III 220-240V 50/60Hz | 9137006486 | 1 |
| | HF-P 218 PL-T/C III 220-240V 50/60Hz | 9137006486 | 2 |
| | Philips HF-M RED 118 SH PLC/PL-T 230-240V | 9137004234 | 1 |
| | HF-S 218 PL-T/C II SR 220-240V 50/60Hz | 9137130358 | 2 |
| | HF-S 1/218 PL-T/C II SR 220-240V 50/60Hz | 9137130358 | 1 |
| | HF-S 118 PL-T/C II SR 220-240V 50/60Hz | 9137130359 | 1 |
| | HF-P 218 PL-T/C 220-240 | 9137001553 | 2 |
| | HF-P 118 PL-T/C EII | 9137006309 | 1 |
| | HF-P 218 PL-T/C EII | 9137006310 | 2 |
| OSRAM | QTP-T/E 1X18, 2X18 - Single | | 1 |
| | QTP-T/E 1X18, 2X18 - Dual | | 2 |
| | QT-ECO T/E 2X18/220-240 | | 2 |
| | Quicktronic QT-D/E 1x18 / 230-240 | | 1 |
| | QTP-T/E 2x18 | | 2 |
| VOSSLOH-SCHWABE | ELXs 121.901 1x13/18W | 188663 | 1 |
| | ELXs 121.904 1x13/18W | 188664 | 1 |
| | ELXc 218.871 1/2x18W - Single | 188699 | 1 |
| | ELXc 218.871 1/2x18W - Dual | 188699 | 2 |
| TRIDONIC | PC 1/2x18 TC PRO sr - Single | 22176416 | 1 |
| | PC 1/2x18 TC PRO sr - Dual | 22176416 | 2 |
| | PC 1/2x18 TC PRO - Single | 1307239 | 1 |
| | PC 1/2x18 TC PRO - Dual | 1307239 | 2 |
| | PC 1x18 TC TOP | 28000073 | 1 |
| | PC 2x18 TC TOP | 28000074 | 2 |
| | PC 1/2x18 TC PRO sr - Single | 22176412 | 1 |
| | PC 1/2x18 TC PRO sr - Dual | 22176412 | 2 |
| BAG HUECO | BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single | 10097544 | 1 |
| | BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual | 10097544 | 2 |
| | BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single | 10095044 | 1 |
| | BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual | 0095044 | 2 |
| HELVAR | BCC 121 | 137946HTC | 1 |
| | BCC 121/2 | 137969/21MM | 1 |
| TCI | MBQ 118/2 | 137968/118 | 1 |
| | MBQ 218/2 | 137968/218 | 2 |
| | BCC 121 | 137946HTC | 1 |

General note Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.

This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply

Philips CorePro LED PLC 9.0W 8xx 4P G24q-3



Ballast Compatibility

KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Dim |
| | Ballast is compatible and conditional released for dimming |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | CorePro LED PLC 9W 8xx 4P G24q-3 |
|------------------------|---|------------|--|
| | | | Model number / EOC code: 9290012008 / 871869654115900 9290012009 / 871869654117300 |
| | | | AC (50Hz) on HF Ballast Compatible |
| | Ballast type | 10nc | Lamps on ballast |
| PHILIPS | HF-P 226 PL-T/C III 220-240V 50/60Hz | 9137006488 | 2 |
| | HF-P 126 PL-T/C III 220-240V 50/60Hz | 9137006487 | 1 |
| | HF-P 1 22-42 PL-T/C/L/TL5C EII 220-240V | 9137006307 | 1 |
| | HF-P 2 22-42 PL-T/C/L/TL5C EII 220-240V | 9137006308 | 2 |
| | HF-S 226 PL-T/C II SR 220-240V | | 2 |
| | HF-S 226 PL-T/C/L/TL5C II SR 220-240V | | 2 |
| | HF-S 126 PL-T/C/L/TL5C II SR 220-240V | 9137130357 | 1 |
| | HF-P 126 PL-T/C 26 | | 1 |
| | HF-P 226 PL-T/C 220-240 | | 2 |
| | HF-P 26-42 PL-T/C 220-240 | | 2 |
| OSRAM | QTP-M 1x26-42 | | 1 |
| | QTP-M 2x26-32 - Dual | | 2 |
| | QTP-M 2x26-32 - Single | | 1 |
| | QT-M 2x26-42/220-240 S | | 2 |
| | QTP-T/E 1x26-42, 2x26 - Dual | | 2 |
| | QTP-T/E 1x26-42, 2x26 - Single | | 1 |
| | QT-ECO T/E 2X26/220-240 | | 2 |
| | QT-ECO 1X26/220...240 S | | 1 |
| | Quicktronic QT-T/E 2x26 / 230-240 | | 2 |
| | QT-M 2x26-32/230-240 S | | 2 |
| QT-M 1x26-42/220-240 S | | 1 | |
| VOSSLOH-SCHWABE | ELXc 142.872 2x26W 1x26/32/42W - Dual | 188700 | 2 |
| | ELXc 142.872 2x26W 1x26/32/42W - Single | 188700 | 1 |
| | ELXc 242.837 2x26/32/42W | 188643 | 2 |
| | ELXs 126.906 1x26 | 188667 | 1 |
| TRIDONIC | PC 1/2x26 TC PRO sr - Single | 22176417 | 1 |
| | PC 1/2x26 TC PRO sr - Dual | 22176417 | 2 |
| | PC 1/2 x 26-42 TC PRO - Single | 22176408 | 1 |
| | PC 1/2 x 26-42 TC PRO - Dual | 22176408 | 2 |
| | PC 2x26-42 TC PRO | 22176410 | 2 |
| | PC 1x26-42 TC TOP | 28000075 | 1 |
| | PC 2x26 TC TOP | 28000076 | 2 |
| BAG HUECO | BCS42.1/26.2LS-01/220-240 1/2x TC-DEL/-TEL 26W - Single | 10095045 | 1 |
| | BCS42.1/26.2LS-01/220-240 1/2x TC-DEL/-TEL 26W - Dual | 10095045 | 2 |
| | BCS42.1/26.2Q-01/220-240 1/2x TC-DEL/-TEL 26W - Single | 10097545 | 1 |
| | BCS42.1/26.2Q-01/220-240 1/2x TC-DEL/-TEL 26W - Dual | 10097545 | 2 |
| | BCS70.1/42.2Q-01/220-240 1/2x TC-DEL/-TEL 26W - Single | 10097546 | 1 |
| | BCS70.1/42.2Q-01/220-240 1/2x TC-DEL/-TEL 26W - Dual | 10097546 | 2 |
| HELVAR | EL1/2x18-42TCs - Single | | 1 |
| | EL1/2x18-42TCs - Dual | | 2 |
| | EL2x32/42TCs | | 1 |
| TCI | MBQ 226/2 | 137968/226 | 2 |
| | MBQ 142/2 | 137968/142 | 1 |
| | MBQ 242/2 - Single | 137962/242 | 1 |
| | MBQ 242/2 - Dual | 137962/242 | 2 |
| | BCC 126 | 137949HTC | 1 |

General note Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.

This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply

Philips CorePro LED PLL HF 8W 8xx 4P 2G11



Ballast Compatibility

KEY

| | |
|-----|--|
| | Ballast is compatible |
| * | Ballast is compatible, light output may differ >10% compared to specifications |
| ** | Ballast is compatible, light output may differ >20% compared to specifications |
| (!) | Do not use in closed luminaires |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | CorePro LED PLL HF 8W 8** 4P 2G11 |
|---------------|---|--------------|--|
| | | | Model number / EOC code: 9290035788 / 8719514486768 9290035789 / 8719514486782 |
| | | | AC (50Hz) on HF Ballast Compatible |
| | Ballast type | 10nc | Lamps on ballast |
| PHILIPS | HF-Performer 1 22-42 PL-T/C/L/TL5C EII 220-240V | 9137 006 307 | 1 |
| | HF-Performer 2 22-42 PL-T/C/L/TL5C EII 220-240V | 9137 006 308 | 2 |
| | HF-Pi 1 14/21/24/39 TL5 EII 220-240 | 9137 006 240 | 1 |
| | HF-Pi 2 14/21/24/39 TL5 EII 220-240 | 9137 006 242 | 2 |
| | HF-Pi 3/4 14/24 TL5/PLL EII | 9137 006 576 | 4 |
| | HF-Pi 3/4 14/24 TL5/PLL EII | 9137 006 576 | 3 |
| | HF-MATCHBOX BLUE 124 LH TL/TL5/PLL | 9137 004 180 | 1 |
| | HF-MATCHBOX BLUE 124 SH TL/TL5/PLL | 9137 004 179 | 1 |
| | HF-MATCHBOX RED 124 SH TL/TL5/PLL | 9137 004 206 | 1 |
| | HF-P 1 18-24 PL-L | 9137 001 931 | 1 |
| OSRAM | QT-ECO 1x18-24/220-240 S | | 1 |
| | QT-FIT8 1x18 | | 1 |
| | QT-M 1x26-42/230-240 S | | 1 |
| | QTP-M 1X26-42 | | 1 |
| | QTP-M 2X26-32 | | 2 |
| | QTP-OPTIMAL 1x18-40 | | 1 |
| | QTP-OPTIMAL 2x18-40 | | 2 |
| | | | |
| TRIDONIC ATCO | PC 1/2x26-42 TC PRO | 22 176 408 | 2 |
| | PC 1/2x26-42 TC PRO | 22 176 408 | 1 |
| | PC 1x18-24W BASIC sl | 22 176 000 | 1 |
| | PC 2x26-42 TC PRO | 22 176 410 | 2 |
| | PC 2/14-21/24/39 T5 PRO-M lp | 22176185 | 2 |
| VOSSLOH | ELXc 142.872 | 188700 | 2 |
| | ELXc 142.872 | 188700 | 1 |
| | ELXc 142.876 | 188888 | 2 |
| | ELXc 142.876 | 188888 | 1 |
| | ELXc 242.837 | 188643 | 2 |
| | ELXc 242.877 | 188889 | 2 |
| BAG-HUECO | BCS39.1FX-11/220-240 | 1007 7581 | 1 |
| | BCS39.2FX-11/220-240 | 1007 7582 | 2 |
| | BCS42.1/26.2LS-01/220-240 | 1009 5045 | 2 |
| | BCS42.1/26.2LS-01/220-240 | 1009 5045 | 1 |
| | BCS42.1/26.2Q-01/220-240 | 1009 7545 | 2 |
| | BCS42.1/26.2Q-01/220-240 | 1009 7545 | 1 |
| | BCS42.1/26.2QI-01/220-240 | 1009 5745 | 2 |
| | BCS42.1/26.2QI-01/220-240 | 1009 5745 | 1 |
| | BCS42.1Q-01/220-240 | 1009 7535 | 1 |
| | MLS14/24.3-4.FR-11/220-240 | 1009 5345 | 4 |
| | MLS14/24.3-4.FR-11/220-240 | 1009 5345 | 3 |
| | MLS39.1-2FR-11/220-240 | 10092026 | 2 |
| | MLS39.1-2FR-11/220-240 | 10092026 | 1 |
| | | | |

Philips CorePro LED PLL HF 8W 8xx 4P 2G11



Ballast Compatibility

KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Ballast is compatible, light output may differ >20% compared to specifications |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | CorePro LED PLL HF 8W 8** 4P 2G11 | |
|--------------|--------------------------|------------------|--|----|
| | | | Model number / EOC code: 9290035788 / 8719514486768 9290035789 / 8719514486782 | |
| | | | AC (50Hz) on HF Ballast Compatible | |
| Ballast type | 10nc | Lamps on ballast | | |
| TCI | BCC 124 | 137947HTC | 1 | ** |
| | BCC 124 SL | 137944B/24H | 1 | ** |
| | BCC 124/2 | 137969/24MM | 1 | ** |
| | BCC 124/2 SL | 137944H | 1 | ** |
| | MBQ 224/2 | 137968/224 | 2 | ** |
| | BTL8 118 | 137963/118 | 1 | ** |
| | MB 226/2 | 137989TC | 2 | ** |
| HELVAR | EL1x36/40/18s | | 1 | * |
| | EL1/2x18-42TCs | | 2 | |
| | EL1/2x18-42TCs | | 1 | * |
| HUCO | EVG-HP 1x/2x 15-42W HC | 09 7545 | 2 | * |
| | EVG-HP 1x/2x 15-42W HC | 09 7545 | 1 | * |
| OTHERS | Direct mains | | | |
| | Electro Magnetic Ballast | | | |

General note Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLL HF 12W 8xx 4P 2G11



Ballast Compatibility

KEY

| | |
|-----|--|
| | Ballast is compatible |
| * | Ballast is compatible, light output may differ >10% compared to specifications |
| ** | Ballast is compatible, light output may differ >20% compared to specifications |
| (!) | Ballast Do not use in closed luminaires |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | CorePro LED PLL HF 12W 8** 4P 2G11 |
|---------------|---|--------------|--|
| | | | Model number / EOC code: 9290035790 / 8719514486805 9290035791 / 8719514486829 |
| | | | AC (50Hz) on HF Ballast Compatible |
| | Ballast type | 10nc | Lamps on ballast |
| PHILIPS | HF-Performer 1 22-42 PL-T/C/L/TL5C EII 220-240V | 9137 006 307 | 1 |
| | HF-Performer 2 22-42 PL-T/C/L/TL5C EII 220-240V | 9137 006 308 | 2 |
| | HF-Pi 1 14/21/24/39 TL5 EII 220-240 | 9137 006 240 | 1 |
| | HF-Pi 2 14/21/24/39 TL5 EII 220-240 | 9137 006 242 | 2 |
| | HF-Pi 3/4 14/24 TL5/PLL EII | 9137 006 576 | 4 |
| | HF-Pi 3/4 14/24 TL5/PLL EII | 9137 006 576 | 3 |
| | HF-MATCHBOX BLUE 124 LH TL/TL5/PLL | 9137 004 180 | 1 |
| | HF-MATCHBOX BLUE 124 SH TL/TL5/PLL | 9137 004 179 | 1 |
| | HF-MATCHBOX RED 124 SH TL/TL5/PLL | 9137 004 206 | 1 |
| | HF-P 1 18-24 PL-L | 9137 001 931 | 1 |
| OSRAM | QT-ECO 1x18-24/220-240 S | | 1 |
| | QT-M 1x26-42/230-240 S | | 1 |
| | QT-M 2x26-42/220-240 S | | 2 |
| | QTP-M 1X26-42 | | 1 |
| | QTP-M 2X26-32 | | 2 |
| | QT-T/E 2x26/230-240 | | 2 |
| | QTP-OPTIMAL 1x18-40 | | 1 |
| | QTP-OPTIMAL 2x18-40 | | 2 |
| TRIDONIC ATCO | PC 1/2x26-42 TC PRO | 22 176 408 | 2 |
| | PC 1/2x26-42 TC PRO | 22 176 408 | 1 |
| | PC 1x18-24W BASIC sl | 22 176 000 | 1 |
| | PC 2x26-42 TC PRO | 22 176 410 | 2 |
| | PC 1x24 T5 TOP lp | 22185159 | 1 |
| | PC 2x24 T5 TOP lp | 22185160 | 2 |
| VOSSLÖH | ELXc 142.872 | 188700 | 2 |
| | ELXc 142.872 | 188700 | 1 |
| | ELXc 142.876 | 188888 | 2 |
| | ELXc 142.876 | 188888 | 1 |
| | ELXc 242.837 | 188643 | 2 |
| | ELXc 242.877 | 188889 | 2 |
| | ELXc 128.869 | 188589 | 1 |
| | ELXc 126.906 | 188667 | 1 |
| BAG-HUECO | BCS39.1FX-11/220-240 | 1007 7581 | 1 |
| | BCS39.2FX-11/220-240 | 1007 7582 | 2 |
| | BCS42.1/26.2LS-01/220-240 | 1009 5045 | 2 |
| | BCS42.1/26.2LS-01/220-240 | 1009 5045 | 1 |
| | BCS42.1/26.2Q-01/220-240 | 1009 7545 | 2 |
| | BCS42.1/26.2Q-01/220-240 | 1009 7545 | 1 |
| | BCS42.1/26.2QI-01/220-240 | 1009 5745 | 2 |
| | BCS42.1/26.2QI-01/220-240 | 1009 5745 | 1 |
| | BCS42.1Q-01/220-240 | 1009 7535 | 1 |
| | MLS14/24.3-4.FR-11/220-240 | 1009 5345 | 4 |
| | MLS14/24.3-4.FR-11/220-240 | 1009 5345 | 3 |
| | MLS39.1-2FR-11/220-240 | 10092026 | 2 |
| | MLS39.1-2FR-11/220-240 | 10092026 | 1 |

Philips CorePro LED PLL HF 12W 8xx 4P 2G11



Ballast Compatibility

KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Ballast is compatible, light output may differ >20% compared to specifications |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | CorePro LED PLL HF 12W 8** 4P 2G11 | |
|--------|--------------------------|-------------|--|----|
| | | | Model number / EOC code: 9290035790 / 8719514486805 9290035791 / 8719514486829 | |
| | | | AC (50Hz) on HF Ballast Compatible | |
| | Ballast type | 10nc | Lamps on ballast | |
| TCI | BCC 124 | 137947HTC | 1 | ** |
| | BCC 124 SL | 137944B/24H | 1 | ** |
| | BCC 124/2 | 137969/24MM | 1 | ** |
| | BCC 124/2 SL | 137944H | 1 | ** |
| | MBQ 224/2 | 137968/224 | 2 | * |
| | MB 226/2 | 137989TC | 2 | * |
| | BCC 126 | 137949HTC | 1 | * |
| HELVAR | EL1/2x18-42TCs | | 2 | |
| | EL1/2x18-42TCs | | 1 | * |
| HUCO | EVG-HP 1x/2x 15-42W HC | 09 7545 | 2 | |
| | EVG-HP 1x/2x 15-42W HC | 09 7545 | 1 | * |
| OTHERS | Direct mains | | | |
| | Electro Magnetic Ballast | | | |

General note Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF 6.5W

Ballast Compatibility



KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Ballast is compatible, light output may differ >20% compared to specifications |
| | Ballast Do not use in closed luminaires |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | LED PLT HF 6.5W | |
|-------------------------|--|--------------------|--|-------|
| | | | Model number / EOC code: 9290035763 9290035764 | |
| | | | AC (50Hz) on HF Ballast Compatible | |
| | Ballast type | 10nc | Lamps on ballast | |
| PHILIPS | EB-S 218 PLT/C 220-240 | 9137100653 | 2 | |
| | HF-P 118 PL-T/C EII | 9137006309 | 1 | |
| | HF-P 118 PL-T/C III | 9137006485 | 1 | |
| | HF-M RED 118 SH PL-C/PL-T | 9137004234 | 1 | * |
| | HF-P 118 PL-T/C 220-240 | 9137001104 | 1 | |
| | HF-P 1/218 PL-T/C III | 9137006486 | 1 | * |
| | HF-P 1/218 PL-T/C III | 9137006486 | 2 | * |
| | HF-P 218 PL-T/C EII | 9137006310 | 2 | |
| | HF-P 218 PL-T/C III 220-240V 50/60Hz | 9137006486 | 2 | * |
| | HF-P 218 PL-T/C 220-240 | 9137001553 | 2 | |
| | HF-S 218 PL-T/C II SR | 9137130358 | 2 | * |
| | HF-S 1/218 PL-T/C II SR 220-240V 50/60Hz | 9137130358 | 1 | |
| | HF-S 1/218 PL-T/C II SR 220-240V 50/60Hz | 9137130358 | 2 | * |
| | OSRAM | QTP-T/E 1X18, 2X18 | A72031900DG | 1 |
| QTP-T/E 1X18, 2X18 | | A72031900DG | 2 | |
| QTP-T/E 2x18 | | A57063200DG | 2 | |
| QT-D/E 1x18/230-240 | | | 1 | |
| QT-ECO T/E 2X18/220-240 | | A72924F00DG | 2 | |
| TRIDONIC/ATCO | PC 1x18 TC TOP | 28000073 | 1 | |
| | PC 2x18 TC TOP | 28000074 | 2 | |
| | PC 2X18 TC TOP sr | 28000078 | 2 | |
| | PC 1/2x18 TC PRO | 22176407 | 1 | |
| | PC 1/2x18 TC PRO | 22176407 | 2 | |
| | PC 1/2x18 TC PRO sr | 22176416 | 1 | |
| | PC 1/2x18 TC PRO sr | 22176416 | 2 | |
| | PC PRO 18 FSQ b101 | 22082606 | 1 | * |
| | PC 1X18-24W BASIC sl | 22176000 | 1 | |
| VOSSLOH | ELXs 121.901 | 188663 | 1 | * |
| | ELXs 121.904 | 188664 | 1 | * |
| | ELXc 218.871 | 188699 | 1 | * |
| | ELXc 218.871 | 188699 | 2 | * |
| | ELXc 142.872 | 188700 | 1 | **(1) |
| | ELXc 142.872 | 188700 | 2 | **(1) |
| BAG-HUECO | BCS18.1-2LS-01 / 220-240 | 10095044 | 1 | |
| | BCS18.1-2LS-01 / 220-240 | 10095044 | 2 | |
| | BCS18.1-2Q-01 / 220-240 | 10097544 | 1 | * |
| | BCS18.1-2Q-01 / 220-240 | 10097544 | 2 | * |
| TCI | MBQ 118/2 | 137968/118 | 1 | |
| | MBQ 218/2 | 137968/218 | 2 | |
| | BCC 121 | 137946HTC | 1 | * |
| HELVAR | EL1/2x18TCs | 4217001P30402078 8 | 1 | |
| | EL1/2x18TCs | 4217001P30402078 8 | 2 | |
| OTHERS | BE 218-TC-5 | | 1 | |
| | BE 218-TC-5 | | 2 | * |

General note Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLT 4P range is designed to work on HF ballasts only.

This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF 9W

Ballast Compatibility



KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Ballast is compatible, light output may differ >20% compared to specifications |
| | Ballast Do not use in closed luminaires |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | LED PLT HF 9W |
|---------------|---|----------------------------|---|
| | | | Model number / EOC code: 9290035765 9290035766 */* |
| | | | AC (50Hz) on HF Ballast Compatible |
| | Ballast type | 10nc | Lamps on ballast |
| PHILIPS | HF-P 126 PL-T/C III | 9137006487 | 1 |
| | HF-P 1 22-42 PL-T/C/L/T5C EI | 9137006307 | 1 |
| | HF-P 1 26-42 PL-T/C | 9137001932 | 1 |
| | HF-P 1/226 PL-T/C III 220-240V 50/60Hz | 9137006488 | 1 |
| | HF-P 1/226 PL-T/C III 220-240V 50/60Hz | 9137006488 | 2 |
| | HF-P 226 PL-T/C III | 9137006488 | 2 |
| | HF-P 2 22-42 PL-T/C/L/TL5C EII | 9137006308 | 2 |
| | HF-P 2 26-42 PL-T/C 220-240 | 9137001950 | 2 |
| | HFP 226 (Philips Luminaires) | 441134730331 | 2 |
| | HF-S 226 PL-T/C/L/TL5C II SR | 9137130356 | 2 |
| | HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz | 9137130356 | 1 |
| | HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz | 9137130356 | 2 |
| | HF-S 226 PL-T/C II SR | 9137130356 | 2 |
| OSRAM | QTP-M 1X26-42 | A6979600455 | 1 |
| | QTP-M 2x26-32 | A6979950455 A69799501DG | 2 |
| | QTP-T/E 1x26-42, 2x26 | A72032500DG | 1 |
| | QTP-T/E 1X26-42,2X26 | A72032500DG | 2 |
| | QT-ECO 1X26/220...240 S | A48946102DG | 1 |
| | QT-ECO T/E 2X26/220-240 | A53702300DG | 2 |
| | QT-M 2x26-42/220-240 S | A5267550355 A52675500DG | 2 |
| | QT-T/E 2x26/230-240 | | 2 |
| TRIDONIC ATCO | PC 1/2x26 TC PRO sr | 22176417 | 1 |
| | PC 1/2x26 TC PRO sr | 22176417 | 2 |
| | PC 1/2 x 26-42 TC PRO | 22176408 | 1 |
| | PC 1/2 x 26-42 TC PRO | 22176408 | 2 |
| | PC 1x26-42 TC TOP | 28000075 | 1 |
| | PC 2x26 TC TOP | 28000076 | 2 |
| | PC 2x26-42 TC PRO | 22176410 | 2 |
| VOSSLÖH | ELXs 126.906 | 188667 | 1 |
| | CBC-226142 | 540426 | 2 |
| | ELXc 142.872 | 188700 | 1 |
| | ELXc 142.872 | 188700 | 2 |
| | ELXc 142.876 | 188888 | 1 |
| | ELXc 142.876 | 188888 | 2 |
| | ELXc 242.837 | 188643 | 2 |
| | ELXc 242.877 | 188889 | 2 |

Philips CorePro LED PLT HF 9W

Ballast Compatibility



KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Ballast is compatible, light output may differ >20% compared to specifications |
| | Ballast Do not use in closed luminaires |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | LED PLT HF 9W | |
|-----------|---------------------------|--------------------|---|--|
| | | | Model number / EOC code: 9290035765 9290035766 */* | |
| | | | AC (50Hz) on HF Ballast Compatible | |
| | Ballast type | 10nc | Lamps on ballast | |
| BAG-HUECO | BCS42.1/26.2LS-01/220-240 | 10095045 | 1 | |
| | BCS42.1/26.2LS-01/220-240 | 10095045 | 2 | |
| | BCS42.1/26.2QI-01/220-240 | 10095745 | 1 | |
| | BCS42.1/26.2QI-01/220-240 | 10095745 | 2 | |
| | BCS70.1/42.2Q-01/220-240 | 10097546 | 1 | |
| | BCS70.1/42.2Q-01/220-240 | 10097546 | 2 | |
| | BCS42.1Q-01/220-240 | 10097535 | 1 | |
| | BCS42.1/26.2Q-01/220-240 | 10097545 | 1 | |
| | BCS42.1/26.2Q-01/220-240 | 10097545 | 2 | |
| TCI | BCC 126. | 137949HTC | 1 | |
| | MB226/2 | 137989Tc | 2 | |
| | MBQ 226/2 | 137968/226 | 2 | |
| | MBQ 142/2 | 137968/142 | 1 | |
| | MBQ 242/2 | 137962/242 | 1 | |
| | MBQ 242/2 | 137962/242 | 2 | |
| HELVAR | EL1/2x18-42TCs | 4219001Q09604620 1 | 1 | |
| | EL1/2x18-42TCs | 4219001Q09604620 1 | 2 | |
| | EL2x32/42TCs | 4218001K03102451 9 | 2 | |
| HUCCO | EVG-HP 1x/2x 15-42W HC | 097545 | 1 | |
| | EVG-HP 1x/2x 15-42W HC | 097545 | 2 | |

General note Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF 15W

Ballast Compatibility



KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Ballast is compatible, light output may differ >20% compared to specifications |
| | Ballast Do not use in closed luminaires |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | LED PLT HF 15W |
|---------------|--------------------------------|----------------------------|---|
| | | | Model number / EOC code: 9290035767 9290035768 */* |
| | | | AC (50Hz) on HF Ballast Compatible |
| | Ballast type | 10nc | Lamps on ballast |
| PHILIPS | HF-P 1 22-42 PL-T/C/L/T5C EI | 9137006307 | 1 |
| | HF-P 1 26-42 PL-T/C | 9137001932 | 1 |
| | HF-P 2 22-42 PL-T/C/L/TL5C EII | 9137006308 | 2 |
| | HF-P 2 26-42 PL-T/C 220-240 | 9137001950 | 2 |
| OSRAM | QTP-M 1X26-42 | A6979600455 | 1 |
| | QTP-M 2x26-32 | A6979950455 A69799501DG | 2 |
| | QTP-T/E 1x26-42, 2x26 | A72032500DG | 1 |
| | QT-M 2x26-42/220-240 S | A5267550355 | 2 |
| TRIDONIC ATCO | PC 1/2x26 TC PRO sr | 22176417 | 1 |
| | PC 1/2 x 26-42 TC PRO | 22176408 | 1 |
| | PC 1x26-42 TC TOP | 28000075 | 1 |
| | PC 2x26-42 TC PRO | 22176410 | 2 |
| VOSSLÖH | ELXc 142.872 | 188700 | 1 |
| | ELXc 142.876 | 188888 | 1 |
| | ELXc 242.837 | 188643 | 2 |
| | ELXc 242.877 | 188889 | 2 |
| BAG-HUECO | BCS42.1/26.2LS-01/220-240 | 10095045 | 1 |
| | BCS42.1/26.2QI-01/220-240 | 10095745 | 1 |
| | BCS70.1/42.2Q-01/220-240 | 10097546 | 1 |
| | BCS70.1/42.2Q-01/220-240 | 10097546 | 2 |
| | BCS42.1Q-01/220-240 | 10097535 | 1 |
| | BCS42.1/26.2Q-01/220-240 | 10097545 | 1 |
| TCI | MBQ 142/2 | 137968/142 | 1 |
| | MBQ 242/2 | 137962/242 | 1 |
| | MBQ 242/2 | 137962/242 | 2 |
| HELVAR | EL1/2x18-42TCs | 4219001Q09604620 1 | 1 |
| | EL2x32/42TCs | 4218001K03102451 9 | 2 |
| HUCO | EVG-HP 1x/2x 15-42W HC | 097545 | 1 |

General note Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF 18.5W

Ballast Compatibility



KEY

| | |
|--|--|
| | Ballast is compatible |
| | Ballast is compatible, light output may differ >10% compared to specifications |
| | Ballast is compatible, light output may differ >20% compared to specifications |
| | Ballast Do not use in closed luminaires |
| | Ballast is not compatible |

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

| | | | LED PLT HF 18.5W |
|---------------|--------------------------------|----------------------------|--|
| | | | Model number / EOC code: 9290035769 9290035770 */ |
| | | | AC (50Hz) on HF Ballast Compatible |
| | Ballast type | 10nc | Lamps on ballast |
| PHILIPS | HF-P 1 22-42 PL-T/C/L/T5C EI | 9137006307 | 1 |
| | HF-P 1 26-42 PL-T/C | 9137001932 | 1 |
| | HF-P 2 22-42 PL-T/C/L/TL5C EII | 9137006308 | 2 |
| | HF-P 2 26-42 PL-T/C 220-240 | 9137001950 | 2 |
| OSRAM | QTP-M 1X26-42 | A6979600455 | 1 |
| | QTP-M 2x26-32 | A6979950455 A69799501DG | 2 |
| | QTP-T/E 1x26-42, 2x26 | A72032500DG | 1 |
| | QT-M 2x26-42/220-240 S | A5267550355 | 2 |
| TRIDONIC ATCO | PC 1/2x26 TC PRO sr | 22176417 | 1 |
| | PC 1/2 x 26-42 TC PRO | 22176408 | 1 |
| | PC 1x26-42 TC TOP | 28000075 | 1 |
| | PC 2x26-42 TC PRO | 22176410 | 2 |
| VOSSLOH | CBC-226142 | 540426 | 2 |
| | ELXc 142.872 | 188700 | 1 |
| | ELXc 142.876 | 188888 | 1 |
| | ELXc 242.837 | 188643 | 2 |
| | ELXc 242.877 | 188889 | 2 |
| BAG-HUECO | BCS42.1/26.2LS-01/220-240 | 10095045 | 1 |
| | BCS42.1/26.2QI-01/220-240 | 10095745 | 1 |
| | BCS70.1/42.2Q-01/220-240 | 10097546 | 1 |
| | BCS70.1/42.2Q-01/220-240 | 10097546 | 2 |
| | BCS42.1Q-01/220-240 | 10097535 | 1 |
| | BCS42.1/26.2Q-01/220-240 | 10097545 | 1 |
| TCI | MBQ 142/2 | 137968/142 | 1 |
| | MBQ 242/2 | 137962/242 | 1 |
| | MBQ 242/2 | 137962/242 | 2 |
| HELVAR | EL1/2x18-42TCs | 4219001Q09604620 1 | 1 |
| | EL2x32/42TCs | 4218001K03102451 9 | 2 |
| HUCO | EVG-HP 1x/2x 15-42W HC | 097545 | 1 |

General note Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.



© 2023 Signify Holding. All rights reserved. The information provided here in is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

01/2023
Data subject to change.

www.philips.com/LEDtube