

Baaske "MediTouch" Keyboard USB

Waterproof and disinfected, IP68 silicone keypad with VESA 75 mounting



Now, mouse is no longer required. Convince yourself of our silicone keyboard with integrated Touchpad. It is easy and thoroughly to clean, and especially chemical resistant to commercial sollutions, acids and bases. An excellent tactile feedback with high quality carbon contacts and a capacitive touchpad allows comfortable handling with rubber gloves.

- ► Integrated capacitive Touchpad operate even with using rubber gloves
- excellent, tactile feedback due to the Key Technology made from silicone
- can be dipped in liquids, IP 68
- Special coating for excellent chemical resistance
- ► Keypad can be switched off for easy cleaning during operation
- durable carbon coating of the switch contacts

MediTouch



Basic Japan Co.,Ltd Mitaka-City,Tokyo Japan Phone: 0422-29-9875 Fax: 0422-29-9877 E-mail: mail@basicjp.com



Baaske "MediTouch" Keyboard USB

Waterproof and disinfected, IP68 silicone keypad with VESA 75 mounting





Baaske "MediTouch" Keyboard USB

Technical Specification Touchpad:

| Operating Principle: | Capacitive |
|----------------------|-------------|
| Resolution: | Max 500 dpi |
| Dimensions: | 65 x 59 mm |
| Sensing Area: | 59 x 42 mm |

► Baaske "MediTouch" Keyboard USB

Technical Specification Keyboard:

| Housing Design: | Plastic Housing |
|--------------------------|------------------------------------|
| Material (surface): | Silicone |
| Material (button panel): | Plastic |
| Touchpad: | Capacitive |
| Max. Protection Level: | IP68 |
| Waterproof: | UW-1 |
| Vesa holes: | 75 mm |
| Number of Keys: | 104 |
| Interfaces: | USB |
| Key Switch Technology: | Carbon Contact |
| Operating Force: | 2N |
| Switch Travel: | 1,0 mm |
| Switching Cycles: | Approx. 2 million (per key) |
| Operating Temperature: | 0°C to +70°C |
| Storage Temperature: | -25°C to +80°C |
| Dimensions: | 340 x 165 x 16,3 mm |
| Weight: | 800 g |
| Layout: | available in international layouts |
| Color: | Light Grey |
| | |