

# LED prewarner AV-LED – the flexible add-on prewarner.



## Flexible use of the AV-LED add-on prewarner, for example on a flatbed vehicle.

**Our proven MV-LED mobile prewarner is also available in a version without chassis. The AV-LED add-on prewarner can be placed quickly and easily on the loading area of any flatbed vehicle or trailer.**

To this end, we have fitted receiver shoes for a forklift truck to the frame structure already ex works, together with fastening eyes for lashing straps so that the unit can be securely lashed down on the loading area. A non-slip rubber mat can also be supplied on request as an additional load restraint. The AV-LED is ideal for customers who only need to use an LED prewarner from time to time. It is also interesting to note that another prewarner or mobile warning trailer can also be coupled onto the flatbed vehicle with AV-LED.

When using our AM 4 TL model for this purpose, the loading area still has space to take an additional MV-LED. This makes it possible to use two LED prewarners and a mobile warning trailer with just one vehicle!

Apart from the omitted chassis, in technical terms the AV-LED is the same as the model with trailer. As an option, a radio remote control with graphic display is available for standard operation of the coloured display directly at the LED prewarner. On request, the LED prewarners can also be supplied completely in red/white or RGB technology.

## LED prewarner for flexible use.

Technical data	
Overall length	2,750 mm
Overall width	1,690 mm
Height (hinged down)	1,520 mm
Loading width	1,690 mm
Loading length	1,940 mm
Weight	approx. 460 kg
Battery casing (LxWxH)	540x1,120x300 mm
Signalling technology	BASt-tested double LED warning light system Ø 340 mm; display signs as self-contained LED systems, protection rating IP 54; lighting test as per EN 12966;
upper LED display sign	1,115 x 1,115 mm, resolution 48 x 48 px, LED colours red/white;
lower LED display sign	1,405 x 1,720 mm, resolution 64 x 80 px, LED colour white; red/white on request; all LEDs also available in RGB as an option
Scope of supply	without chassis and without battery



When the need arises, simply use a forklift truck to place on the loading area of the required transport vehicle: secured at the fastening eyes, the AV-LED is immediately ready for professional traffic safety use with practically any flatbed vehicle.



Control unit with colour display directly at the prewarner.



Radio remote control with colour display available as option.