



Handel



Gastronomie



Ticketdruck



Kiosk

# MEHR FLEXIBILITÄT DANK VERBESSERTER FUNKTIONEN

## 3-Zoll-POS-Bondrucker SRP-350III



### Wesentliche Merkmale



#### Ausgezeichnete Druckeigenschaften

- schnelles Drucken mit bis zu 250 mm/ Sekunde (25 % schneller als der SRP-350II)
- 4 Dithering-Optionen für Grafikdruck
- aus der Familie der erstklassigen SRP-350-Reihe



#### Mehrere Schnittstellenoptionen

- USB integriert
- Optional: seriell, parallel oder Ethernet



#### Benutzerfreundliches Design

- Anti-Papierstau-Führung
- Einzelplatzinstallation oder platzsparende Wandmontage
- Wahl zwischen 2- oder 3-Zoll-Papier



**BIXOLON**<sup>®</sup>  
a Better Solution for your Business<sup>™</sup>

# 3-Zoll-POS-Bondrucker SRP-350III

## Technische Daten

### Print Characteristics

**Print Method**

Direct Thermal

**Print Speed**

SRP-350III: 250 mm/sec

SRP-352III: 230 mm/sec

**Print Resolution**

SRP-350III: 180 dpi

SRP-352III: 203 dpi

**Print Width**

Up to 72 mm

**Sensor**

Paper End, Paper Near End, Cover Open

### Media Characteristics

**Media Type**

Receipt

**Media Width**

80 mm

Optional 58 mm (with 2 inch Partition)

**Media Roll Diameter**

Up to 83 mm

**Media Thickness**

0.062 ~ 0.075 mm

**Supply Method**

Easy Paper Loading

### Physical Characteristics

**Dimensions (WxLxD)**

145 x 204 x 146 mm

(5.70 x 8.03 x 5.74 inch)

**Weight**

1.55kg (3.41 lbs)

**Power**

EnergyStar Certified,

External Power Adaptor 100-240V AV,

50/60Hz

**Drawer Port**

2 ports (via y-type adaptor)

### Performance Characteristics

**Memory**

64 Mbit SDRAM, 32 Mbit FlashROM

**NV Image Memory**

256 Kbytes (mono)

**Receive Buffer**

4 Kbytes

**User Define Buffer**

12 Kbytes

**Interface**

Dual Interface

USB V2.0 FS + Serial

USB V2.0 FS + Parallel

USB V2.0 FS + Ethernet

### Environment Characteristics

**Temperature**

Operating: 0 ~ 45°C (32 ~ 113°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity**

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

### Reliability

**Printer Unit (MCFB)**

70 Million Lines

**Thermal Print Head (TPH)**

150 km

**Auto Cutter**

1.8 Million Cuts

### Software

**Emulation**

BXL / POS

**Driver / Utility**

Windows Driver, OPOS Driver, JPOS Driver,

Linux CUPS Driver, Mac Driver,

Virtual COM USB/Ethernet Driver,

Utility Program

**SDK**

iOS SDK, Android SDK

### Fonts / Graphics / Symbologies

**Character Size**

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24

KOR, CHN, JPN: 24 x 24

**Characters Per Line**

SRP-350III: Font A: 42 Font B, C: 56

KOR, CHN, JPN: 21

SRP-352III: Font A: 48 Font B, C: 64

KOR, CHN, JPN: 24

**Character Sets**

Alphanumeric: 95

Extended Graphics: 128 x 37 page

International: 32

**Graphics**

Supporting user-defined fonts, graphics,

formats, and logos

**Barcode Symbologies**

1D: Codabar, Code 39, Code 93, Code 128,

EAN-8, EAN-13, ITF, UPC-A, UPC-E

2D: Data Matrix, PDF417, QR code

