

Technical Data Sheet

1-Ear Clamps, 2-Ear Clamps

Product Group 153/154, 101 & 151



Connecting Technology



Compact one-piece clamp: for robust, secure connections, miniature sizes

Clamp ear: fast and simple installation, visible deformation provides evidence of proper closure

Deburred edges: reduced risk of damage to parts being clamped

With insert

Pre-shaped insert: effective and powerful all-round seal

1-Ear Clamps Product Group 153 & 154

Material

PG 153 Stainless Steel, Material no. 1.4307/UNS S30403

PG 154 Clamp: Stainless Steel, Material no. 1.4307/
UNS S30403

Insert: Stainless Steel, Material no. 1.4310/UNS S30100

Corrosion resistance according to DIN EN ISO 9227

PG 153 ≥ 800 h

PG 154 ≥ 800 h

Size range

PG 153 3.3 – 30.7 mm

PG 154 2.9 – 30.0 mm

Some sizes are only available if an appropriate minimum quantity is ordered.

Process

The manufacturing process for Oetiker 1-Ear and 2-Ear Clamps commences with the spiral roll-forming and welding of raw material into lengths of tube, a technique developed to obtain a robust, continuous welded ring.

Oetiker 1-Ear Clamps with insert

This type of clamp combines the geometry and properties of the 1-Ear Clamp with an insert made of stainless steel.

These clamps are ideal for demanding applications involving soft or hard rubbers and plastics. The thin-walled insert ring (up to 0.3 mm thick), with an oval protrusion that locates in the ear space, bridges the ear gap and ensures almost uniform compression around the whole circumference of a clamp.

Edge condition

Burrs generated during the shearing and forming processes are entirely eliminated in a barrel-finishing operation.

Clamp ear (closing element)

Using tools designed or endorsed by Oetiker, the clamp is closed by drawing together the lower radii of the “ear”. The maximum diameter reduction is proportional to the open “ear” width. The maximum reduction in diameter is given by the formula:

$$\text{Max. diameter reduction} = \frac{\text{Ear width (s)}}{\pi}$$

Important

Single tool stroke closure only, do not apply secondary crimping force.

The data in this catalog are based on many years experience. They are intended for reference, not as design specifications.



2-Ear version: [extended clamping range](#)

Compact one-piece clamp: [for robust, secure connections](#)

Clamp ear: [fast and simple installation, visible deformation provides evidence of proper closure](#)

Deburred edges: [reduced risk of damage to parts being clamped](#)

2-Ear Clamps Product Group 101 & 151

Material

PG 101 [Steel, Material no. 1.0338/SAE 1008/1010, zinc-plated](#)

PG 151 [Stainless Steel, Material no. 1.4307/UNS S30403](#)

Corrosion resistance according to DIN EN ISO 9227

PG 101 [≥ 96 h](#)

PG 151 [≥ 800 h](#)

Size range

[4.1 – 46.0 mm](#)

[Some sizes are only available if an appropriate minimum quantity is ordered.](#)

Oetiker 2-Ear Clamps

The ears of these clamps do not have a dimple and nearly double the clamping range, compared to the 1-ear clamp. 2 ears provide a degree of elasticity to accommodate changes in size of the parts being joined, such as that which may be caused by thermal expansion or vibration.

Installation techniques are similar to those for 1-Ear Clamps, but the force applied when closing the second ear may react against the opposing closed ear and make a second crimping operation

necessary. For perfect sealing, the ears must be adequately closed during installation.

Assembly recommendations

The ears of these clamps should be closed with the recommended, uniform force (known as force priority). This method will result in a constant, reproducible stress within the clamp material, without overloading either the clamp or the parts being assembled. The nominal diameter of the clamp should always be chosen so that, when installed with the correct clamping force, the ears are almost closed. Complete process monitoring and 100% process documentation are available using the “Electronically Controlled Pneumatic Power Tool” Oetiker ELK.

Closing force

The following table shows the maximum applied closing force for different material dimensions.

Important

Single tool stroke closure only, do not apply secondary crimping force.

Installation data

| Size (mm) | Closing force max. (N) | | Installation tools force-monitored ¹ : | | | |
|-------------------------|------------------------|-----------|---|------------|----------|---------------------------|
| | galvanized | stainless | Manual | Pneumatic | Cordless | Electronically controlled |
| PG 153 | | | | | | |
| 3.3 – 11.0 | - | 1400 | HMK 01/S01 | HO ME 2000 | CP 01 | HO EL 2000 |
| 11.3 – 20.7 | - | 2300 | HMK 01/S01 | HO ME 3000 | CP 01 | HO EL 3000 |
| 21.0 – 30.7 | - | 2800 | - | HO ME 3000 | CP 01 | HO EL 3000 |
| PG 154 | | | | | | |
| 3.3 – 11.8 | - | 1500 | HMK 01/S01 | HO ME 2000 | CP 01 | HO EL 2000 |
| 12.0 – 20.7 | - | 2500 | HMK 01 | HO ME 3000 | CP 01 | HO EL 3000 |
| 21.0 – 30.7 | - | 3600 | - | HO ME 4000 | CP 01 | HO EL 4000 |
| PG 101 & 151 | | | | | | |
| 4.1 – 20.0 | 2200 | 2500 | HMK 01/S01 | HO ME 3000 | CP 01 | HO EL 3000 |
| 22.0 – 46.0 | 3400 | 3600 | - | HO ME 3000 | CP 01 | HO EL 4000 |

For an alternative option, see our manual pincers on page 104

¹ Further information on page 84

Important note

These figures are intended as a guide, they may vary depending on the type and tolerances of parts being clamped. To ensure optimum clamp selection, we recommend making functional tests with several assemblies.

Order information

| Item No. | Ref. No. | Ear width inside (mm) | Size range (mm) | Item No. | Ref. No. | Ear width inside (mm) | Size range (mm) |
|-------------------------|----------|-----------------------|-----------------|-------------------------|----------|-----------------------|-----------------|
| 1-Ear Clamps, stainless | | | | 1-Ear Clamps, stainless | | | |
| 15300000 | 03.3R | 1.4 | 2.9 – 3.3 | 15300021 | 13.3R | 6.5 | 11.3 – 13.3 |
| 15300001 | 03.5R | 1.4 | 3 – 3.5 | 15300022 | 13.8R | 6.5 | 11.8 – 13.8 |
| 15300002 | 04.1R | 2.5 | 3.3 – 4.1 | 15300023 | 14.0R | 6.5 | 12 – 14 |
| 15300054 | 04.6R | 3 | 3.8 – 4.6 | 15300024 | 14.5R | 6.5 | 12.5 – 14.5 |
| 15300003 | 05.1R | 3.2 | 4.1 – 5.1 | 15300025 | 15.0R | 6.5 | 13 – 15 |
| 15300055 | 05.6R | 3.2 | 4.6 – 5.6 | 15300026 | 15.5R | 6.5 | 13.5 – 15.5 |
| 15300004 | 06.1R | 3.2 | 5.1 – 6.1 | 15300027 | 16.0R | 7 | 13.8 – 16 |
| 15300005 | 06.6R | 3.2 | 5.6 – 6.6 | 15300028 | 16.5R | 8 | 14 – 16.5 |
| 15300006 | 07.0R | 3 | 6.1 – 7 | 15300029 | 16.8R | 7 | 14.6 – 16.8 |
| 15300007 | 07.5R | 3.5 | 6.5 – 7.5 | 15300030 | 17.5R | 7 | 15.3 – 17.5 |
| 15300008 | 08.0R | 4 | 6.8 – 8 | 15300031 | 18.5R | 7 | 16.3 – 18.5 |
| 15300009 | 08.3R | 4 | 7.1 – 8.3 | 15300032 | 19.5R | 7.5 | 17.2 – 19.5 |
| 15300010 | 08.7R | 4 | 7.5 – 8.7 | 15300033 | 20.0R | 7.5 | 17.7 – 20 |
| 15300011 | 09.0R | 5 | 7.5 – 9 | 15300034 | 20.7R | 9 | 17.9 – 20.7 |
| 15300012 | 09.5R | 5 | 8.1 – 9.5 | 15300035 | 21.0R | 7.5 | 18.7 – 21 |
| 15300013 | 10.0R | 5 | 8.5 – 10 | 15300036 | 21.8R | 7.5 | 19.5 – 21.8 |
| 15300014 | 10.5R | 5 | 9.1 – 10.5 | 15300037 | 22.5R | 8.5 | 19.9 – 22.5 |
| 15300015 | 11.0R | 5.5 | 9.3 – 11 | 15300038 | 23.5R | 8.5 | 21 – 23.5 |
| 15300016 | 11.3R | 5.5 | 9.6 – 11.3 | 15300040 | 24.5R | 9 | 21.7 – 24.5 |
| 15300017 | 11.8R | 5.5 | 10.1 – 11.8 | 15300041 | 25.5R | 9 | 22.7 – 25.5 |
| 15300018 | 12.0R | 6.5 | 10.1 – 12 | 15300043 | 26.3R | 8.5 | 23.6 – 26.3 |
| 15300019 | 12.3R | 6.5 | 10.3 – 12.3 | 15300044 | 27.0R | 9.5 | 24.1 – 27 |
| 15300020 | 12.8R | 6.5 | 10.8 – 12.8 | 15300045 | 30.7R | 11 | 27.2 – 30.7 |

The data in this catalog are based on many years experience. They are intended for reference, not as design specifications.

Order information

| Item No. | Ref. No. | Ear width inside (mm) | Size range (mm) | Item No. | Ref. No. | Size range (mm) |
|--|----------|--------------------------|-----------------|----------------------------------|----------|-----------------|
| 1-Ear Clamps with insert, stainless | | | | 2-Ear Clamps, zinc-plated | | |
| 15400010 | 03.3RER | 1.4 | 2.5 – 2.9 | 10100000 | 0041 | 3.1 – 4.1 |
| 15400011 | 03.5RER | 1.4 | 2.7 – 3.1 | 10100001 | 0045 | 3.5 – 4.5 |
| 15400012 | 04.1RER | 2.5 | 2.9 – 3.7 | 10100002 | 0305 | 3.4 – 5 |
| 15400063 | 04.6RER | 3 | 3.4 – 4.2 | 10100004 | 0507 | 5 – 7 |
| 15400013 | 05.1RER | 3.2 | 3.7 – 4.7 | 10100008 | 0709 | 7 – 9 |
| 15400064 | 05.6RER | 3.2 | 4.2 – 5.2 | 10100011 | 0811 | 8.1 – 11 |
| 15400014 | 06.1RER | 3.2 | 4.7 – 5.7 | 10100016 | 1113 | 10.8 – 13 |
| 15400015 | 06.6RER | 3.2 | 5.2 – 6.2 | 10100019 | 1315 | 12.5 – 15 |
| 15400016 | 07.0RER | 3 | 5.6 – 6.5 | 10100022 | 1517 | 14 – 17 |
| 15400017 | 07.5RER | 3.5 | 5.9 – 7 | 10100024 | 1518 | 15 – 18 |
| 15400018 | 08.0RER | 4 | 6.3 – 7.5 | 10100097 | 1619 | 16 – 19 |
| 15400019 | 08.3RER | 4 | 6.6 – 7.8 | 10100027 | 1720 | 16.2 – 20 |
| 15400020 | 08.7RER | 4 | 7 – 8.2 | 10100029 | 1922 | 18 – 22 |
| 15400021 | 09.0RER | 5 | 7 – 8.5 | 10100030 | 2023 | 19 – 23 |
| 15400022 | 09.5RER | 5 | 7.5 – 9 | 10100032 | 2225 | 21 – 25 |
| 15400023 | 10.0RER | 5 | 8 – 9.5 | 10100034 | 2327 | 22.5 – 27 |
| 15400024 | 10.5RER | 5 | 8.5 – 10 | 10100035 | 2528 | 24 – 28 |
| 15400025 | 11.0RER | 5.5 | 8.8 – 10.5 | 10100037 | 2731 | 26.3 – 31 |
| 15400026 | 11.3RER | 5.5 | 9.1 – 10.8 | 10100041 | 3134 | 29.3 – 34 |
| 15400027 | 11.8RER | 5.5 | 9.6 – 11.3 | 10100043 | 3437 | 32 – 37 |
| 15400028 | 12.0RER | 6.5 | 9.5 – 11.5 | 10100045 | 3740 | 35 – 40 |
| 15400029 | 12.3RER | 6.5 | 9.8 – 11.8 | 10100047 | 4043 | 37.6 – 43 |
| 15400030 | 12.8RER | 6.5 | 10.3 – 12.3 | 10100049 | 4346 | 40.6 – 46 |
| 15400031 | 13.3RER | 6.5 | 10.6 – 12.6 | 2-Ear Clamps, stainless | | |
| 15400032 | 13.8RER | 6.5 | 11.1 – 13.1 | 15100000 | 0041R | 3.1 – 4.1 |
| 15400033 | 14.0RER | 6.5 | 11.3 – 13.3 | 15100001 | 0045R | 3.5 – 4.5 |
| 15400034 | 14.5RER | 6.5 | 11.8 – 13.8 | 15100002 | 0305R | 3.4 – 5 |
| 15400035 | 15.0RER | 6.5 | 12.3 – 14.3 | 15100003 | 0507R | 5 – 7 |
| 15400036 | 15.5RER | 6.5 | 12.8 – 14.8 | 15100004 | 0709R | 7 – 9 |
| 15400037 | 16.0RER | 7 | 13.1 – 15.3 | 15100023 | 0811R | 8 – 11 |
| 15400038 | 16.5RER | 8 | 13.2 – 15.8 | 15100006 | 1113R | 11 – 13 |
| 15400039 | 16.8RER | 7 | 13.9 – 16.1 | 15100007 | 1315R | 12.5 – 15 |
| 15400040 | 17.5RER | 7 | 14.6 – 16.8 | 15100008 | 1517R | 14 – 17 |
| 15400041 | 18.5RER | 7 | 15.6 – 17.8 | 15100009 | 1518R | 15 – 18 |
| 15400042 | 19.5RER | 7.5 | 16.5 – 18.8 | 15100010 | 1720R | 16.2 – 20 |
| 15400043 | 20.0RER | 7.5 | 17.1 – 19.3 | 15100011 | 1922R | 18.1 – 22 |
| 15400044 | 20.7RER | 9 | 17.1 – 20 | 15100012 | 2023R | 19.1 – 23 |
| 15400045 | 21.0RER | 7.5 | 18 – 20.3 | 15100013 | 2225R | 21.1 – 25 |
| 15400046 | 21.8RER | 7.5 | 18.8 – 21.1 | 15100014 | 2327R | 22.5 – 27 |
| 15400065 | 22.5RER | 8.5 | 19.2 – 21.8 | 15100015 | 2528R | 24 – 28 |
| 15400048 | 23.5RER | 8.5 | 20.2 – 22.8 | 15100016 | 2731R | 26.3 – 31 |
| 15400049 | 24.5RER | 9 | 21 – 23.8 | 15100018 | 3134R | 29.3 – 34 |
| 15400050 | 25.5RER | 9 | 22 – 24.8 | 15100019 | 3437R | 32 – 37 |
| 15400051 | 26.3RER | 8.5 | 23 – 25.6 | 15100020 | 3740R | 35 – 40 |
| 15400052 | 27.0RER | 9.5 | 23.3 – 26.3 | 15100021 | 4043R | 37.6 – 43 |
| 15400053 | 30.7RER | 11 | 26.5 – 30 | 15100022 | 4346R | 40.6 – 46 |

The Oetiker Group: www.oetiker.com

Headquarters Switzerland
Hans Oetiker AG
Maschinen- und Apparatefabrik
Oberdorfstrasse 21
CH-8810 Horgen (Zürich)
T +41 44 728 55 55
info@ch.oetiker.com

Austria
Hans Oetiker
Maschinen- und Apparatebau
Ges.m.b.H.
Eduard-Klinger-Strasse 19
A-3423 St. Andrä-Wördern
T +43 2242 33 994-0
info@at.oetiker.com

Brazil
Oetiker do Brasil Imp. e Com. Ltda.
Av. Hugo Fumagali, nr. 586 - Sala B
07220-080 Cid. Industrial Satélite
Guarulhos (SP)
T +55 11 2303 7486
info@br.oetiker.com

Canada
Oetiker Limited
203 Dufferin Street South
P. O. Box 5500
Alliston, Ontario L9R 1W7
T +1 705 435 4394
info@ca.oetiker.com

P. R. China
Oetiker Industries (Tianjin) Ltd.
10 Shuangchenzhong Road
Beichen High Tech Industrial Park
Tianjin 300400
T +86 22 2697 1183
info@cn.oetiker.com

Czech Republic
Hans Oetiker spol. s r. o.
Václavská 116
CZ-37833 Nová Bystřice
T +420 384 386513
info@cz.oetiker.com

France
Oetiker Sarl
Parc d'activités du Bel Air
1, rue Charles Cordier
77164 Ferrières-en-Brie
T +33 1 79 74 10 90
info@fr.oetiker.com

Germany
Hans Oetiker
Metallwaren- & Apparatefabrik GmbH
Üsenbergerstrasse 13
D-79346 Edingen a. K.
T +49 76 42 6 84-0
info@de.oetiker.com

Kurt Allert GmbH & Co. KG
Postfach 1160
Austrasse 36
D-78727 Oberndorf a. N.
T +49 74 23 87 70-0
info@allert.oetiker.com

Hong Kong
Oetiker Far East Limited
2210 Tuen Mun Central Square
22 Hoi Wing Road
Tuen Mun NT
T +852 2459 8211
info@hk.oetiker.com

Hungary
Oetiker Hungaria KFT
Vasvári P. U. 11
H-9800 Vasvár
T +36 94 370 630
info@hu.oetiker.com

India
Oetiker India Private Ltd.
N-14, Additional Patalganga
Industrial Area
Village Chavane, Khalapur
Rasayani 410 220
Dist. Raigad, Maharashtra
T +91 2192 250107-12
info@in.oetiker.com

Japan
Oetiker Japan Co. Ltd.
Kaneko Bldg. A
5-3-5 Nakamachi-dai, Tsuzuki-ku
Yokohama 224-0041, Kanagawa
T +81 45 949 3151
info@jp.oetiker.com

Mexico
Oetiker Servicios S de RL de CV
Ave. José María Pino Suárez 853 Nte.
Col. Centro, CP 64000
Monterrey, Nuevo León
T +52 81 8390 0237
info@mx.oetiker.com

Netherlands
Oetiker Benelux B. V.
Hertzstraat 38
NL-6716 BT Ede
T +31 318 63 71 71
info@nl.oetiker.com

Spain
Oetiker España, S. A.
Pol. Ind. Las Salinas
C/Puente, 18
E-11500 El Puerto
de Santa María (Cádiz)
T +34 956 86 04 40
info@es.oetiker.com

South Korea
Oetiker Far East Limited
Korea Liaison Office
Postal Zip Code 135-880
1401 LG Twintel 1-Cha 157-8
Samseong 1-dong
Gangnam-gu, Seoul
T +82 2 2191 6100
info@kr.oetiker.com

United Kingdom
Oetiker UK Limited
Foundry Close
GB-Horsham, Sussex RH13 5TX
T +44 1403 26 04 78
info@uk.oetiker.com

USA
Oetiker, Inc.
6317 Euclid Street
Marlette, Michigan 48453-0217
T +1 989 635 3621
800 959 0398 (toll-free)
info@us.oetiker.com

www.oetiker.com

