V321LEA

32" HD Ready Super Slim LED TV with Swivel Stand and Black Gloss Finish

V321LEA

32" HD Ready Super Slim LED TV with Swivel Stand and Black Gloss Finish

Features

1366 (H) x 768 (V) pixel resolution: Widescreen Aspect Ratio
High resolution pixel density with built-in image scaler to handle inputs from a variety of digital and analogue audio/ video sources.

178°(H) x 178°(V) Viewing Angle:
Improves viewing angle, contrast, and brightness to provide consistent high quality images.

"Mega" <Dynamic Contrast Ratio/ 400Cd/m² Panel Brightness:
As two of the most important determining factors in overall picture quality, contrast and brightness levels achieve new heights in this latest generation TV's with LED technology. Videocon's new LED TV's deliver stunning images for a perfect viewing experience.

Response Time: Fast 6.5ms response time minimises blurring of moving video

Multilingual on screen displays
(23) English, French, German, Spanish, Italian, Netherlands, Portuguese, Turkish, Polish, Croatian, Norwegian, Swedish, Hungarian, Danish, Finnish, Czech, Romanian, Slovenian, Bulgarian, Russian, Greek, Serbian, Slovakian

Connections

A/V inputs: 1
HDMI in: 3
SCART: 2
Component input: 1 (3.5mm Jack – Adaptor Lead Supplied)
PC input/ PC Audio: 1/ 1
USB 2.0: 1 (Playback Only)
S-Video input: 1
SPDIF Dolby Digital Out: 1
CI Slot: 1

Specifications

Panel: Wide (16:9) LED Backlit
TV System: (Analogue) PAL, SECAM Tuner (NTSC in playback only)
TV System: (Digital) DVB Terrestrial TV and Radio reception
Tuner Preset: 999 pre-selected
Antenna: 75-ohm, IEC Type
Audio Output: 2 x 10 Watts RMS

Shipping Information

Dimensions:
Weight:

Order Code: V321LEA
EAN Code: 8903279220983

EAN CODE	8903279220983

PANEL RELATED

Screen Size	32" (80cm)
Aspect Ratio	16:9
Resolution	1366 x 768
Display Colours	16.7 Million
Dynamic Contrast Ratio	Mega
Brightness (cd/m²)	400
Fast Response Time	6.5ms
Backlight Life	30,000 Hrs (Approx.)
Viewing Angle (°)	178/ 178
HD Status	HD Ready
Colour System	PAL/ SECAM/ NTSC in AV Playback

PICTURE

Nanopix Engine	•
120Hz Motion Impact	
DCDI	•
Picture Modes	User/ Cinema/ Sport/ Vivid/ Hi-Bright
Picture Scale/ Zoom	Normal/ Auto/ Panorama/ Letter box/ Zoom 1/ Zoom 2
Colour Temperature	Normal/ Warm/ Cool
Brightness/ Contrast/ Colour Control	•
Sharpness Control	•
Tint Control (Only NTSC System)	•
Video Noise Reduction (DNR)	•
Blue Stretch	•
White Peak Limiter	•
Colour Transcient Improvement	•
Flesh Tone	•
Adaptive Luma Control	•
Black Light Adjustment Control	•
Dynamic Backlight	•
Motion Jitter Control	

AUDIO

Audio Out (RMS)	2 x 10W
SRS TruBass	•
Sound System	I/ BG/ DK/ L/ L'
Set Sound Modes	User/ Speech/ Normal/ Music
NICAM Stereo	•
Equaliser (5 Band)	•
Stereo Playback	•
Surround Mode	•
Auto Volume Limiter	•
Bass/ Treble/ Balance	**x/x/•**
Visually Impaired	•
SPDIF Select	PCM/ Dolby Digital/ Off

CONNECTIONS

RF Tuner (ANT In - 75 ohm)	•
Composite AV Input	1
SCART	2
VGA PC Input (D-sub 15pin)	1
PC Audio Input	1
S-Video Input	1
Component (Y/ Pb/ Pr) Input	1 (with adapter lead supplied)
HDMI (1.3) Input	3
CI Slot	•
USB 2.0 Input	1
FastCam (Pay per View Digital Terrestrial)	**x**
DVD Player Integrated	**x**
SPDIF Output	• (Dolby Digital/ PCM/ Off)
Headphone Out	**x**
Euro SCART Out (Always Output TV)	•
SCART Monitor Out	•

TIMER FEATURES

Clock	•
On/ Off Timer	•
Auto Switch Off (No Signal)	•
Reminder Time	•
Reminder Channel	•
Sleep Timer	•
Auto Sleep	•

CHANNEL EDIT FEATURES

LCN (Store in Sequential Name)	•
Channel Scan (Digital and Analogue)	•
Channel Scan (Digital Only)	•
Analogue Manual Scan	•
Channel Sorting	•
Channel Move	•
Channel Delete	•
Channel Skip	•
Program Naming	•
Quick View	•
Favourite Channel Accessing	•

HOTEL/ CHILD LOCK MODE

Hotel Mode	•
Password Select	•
Program Lock	•
Child Lock (Channel Lock)	•
Tuning Lock	•
Volume Lock	•
Volume Limit	•
Front Panel Key Lock	•
AV Lock	•
Complete Menu Lock	•
Start On Program Control	•
Start On Predefined Source	•
Start On Predefined Channel No	•
OSD Lock	•
Menu Disable	•

LANGUAGE FEATURES

OSD Multilanguages	23 (English, French, German, Spanish, Italian, Netherlands, Portuguese, Turkish, Polish, Croatian, Norwegian, Swedish, Hungarian, Danish, Finnish, Czech, Romanian, Slovenian, Bulgarian, Russian, Greek, Serbian, Slovakian)
OSD (HPOS/ VPOS/ Timer/ Transparency)	•
No of Teletext Page/ Languages	500/ 30
TELETEXT Decoding Language	East Eur, West Eur, Russian x 2, Greek, Turkish, Arab, Hbrw, Farsian
Teletext Level	Level 1.5/ 2.5
Teletext Disable	•

OTHER FEATURES

Finish	Steam Moulding
Swivel Stand	•
ACI (Automatic Channel Installation)	•
ATS (Automatic Channel Sorting)	•
EPG (Electronic Programme Guide)	•
Wizard (Tuning Guide)	•
PIP (Picture in Picture)	x

PARAMETRIC INFORMATION

Automatic Voltage Range (AVR)	100 - 240 V ~ 50/60Hz
Power Consumption Maximum	100W
Power Consumption in Standby	<1W
Accessories	Remote Handset, Quick Start Guide, User Guide Book, Power Cord, Component Adapter
Wall Mounting Compatibility	200mm x 100mm

LOGISTIC INFORMATION

Unit Dimensions with Stand Base (L/W/H) mm	tbc
Unit Dimensions without Stan	tbc
Net Weight (Kg)	tbc
Box Weight (Kg)	tbc
Box Dimensions (L/W/H) mm	tbc
Loading Qty Pallet	tbc
Loading Qty Truck	tbc
Loading Qty 40ft Standard	tbc
Loading Qty 40ft HQ	tbc

Note: * These specs are subject to change without notice.

VIDEOCON LED

VIDEOCON