



Features:

- Lacing cords are specifically designed for the lacing of cable forms.
- The nylon braided core ensures high tensile strength with minor extensions but has sufficient elasticity under low loads to make a neat cable form.
- The outer P.V.C. sheath acts as a cushion preventing the cord from cutting into the cable insulation and prevents rattling.
- There is a maximum limit on tensile strength to prevent excessive tension in lacing up.
- The braiding core stops any possibility of the lacing cord unwinding under tension.
- Temperature range : 40°C to +85°C
- Tropical resistance humidity : Class H5
- Properties maintained after more than 21 days of tropical testing
- Does not support mould growth.
- Wound on to cardboard spools with metal winder in 25m, 50m and 1000m reels.

Technical Information

Properties	1435764 VUL 88	3058669 VUL 173
Outside diameter	1.0mm to 1.2mm	0.75mm to 0.9mm
Working load	6.75kg tested for 5 minutes without breaking	4.5kg tested for 5 minutes without breaking
Ultimate tensile strength	16kg typical	11kg typical
Extensibility	At R.T. maximum elongation 6.75kg load is 13%	At R.T. maximum elongation 4.5kg load is 13%
Colour	Black	Black
Packaging	On reels 500 metres per reel	On reels 1000 metres per reel
NATO Part No.	4020-99-011-9481	4020-99-014-2488

Lacing Cord



The information and data is believed to be accurate at the time of printing. Our technical information should be carefully considered. We able to offer the possibility of laboratory simulation of conditions of many applications in order to advise on suitability. As conditions and methods used are beyond our control, the user must confirm suitability before adopting our products for commercial use. We reserve the right to modify characteristics with the aim of improving the product and adapting it to the requirements of the market.

Part Number Table

Description	Part Number
LACING CORD, 25M REEL	81400000
LACING CORD, 1MM, 25M	81400001

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC pro-Power is the registered trademark of the Group. © Premier Farnell plc 2010.

<http://www.farnell.com>
<http://www.newark.com>
<http://www.cpc.co.uk>

