

# 130 CVX

## Polyglass 2-way coaxial kit

- Butyl surround  
Resilient material, promoting long life

- Adjustable aluminum inverted dome tweeter  
Detailed and non directive

- 12dB/octave audiophile crossover  
Time saving during the installation, optimum sound quality

- Polyglass cone  
Neutral sound without coloration

- Aluminum protection cover  
Protects the crossover from shocks

- 25mm (1") voice coil  
on Kapton®, former  
High power handling

- 20% glass fiber filled ABS material basket  
Strong rigid, non-magnetic and non-resonant chassis

- Polypropylene condensator  
Extremely natural sound

- Air core inductor with a low serial resistance  
Insensitive to parasite



### Technical characteristics :

130mm (5") woofer  
25mm (1") voice-coil  
85mm (3-1/3") magnet  
Adjustable tweeter,  
aluminum inverted dome  
Integrated crossover (12dB/octave)  
Max. power: 120W  
Nom. power: 60W  
Sensitivity(2.8V/1m): 91dB  
Frequency response: 75Hz – 20kHz  
Accessories: grilles provided

### It makes the difference :

- Real integrated audiophile 12dB/octave crossover
- Dynamics and neutrality
- Adjustable height of the sound stage
- Installation rapidity

