

SIB XL JET BLACK

Product specification sheet

ABS structure, for low vibrations and resonances.

OAL 3/4" aluminum dome tweeter. Extended response to 35 kHz. Low directivity.


Aerodynamic ports for reduced distortion and dynamic compression.

5" Polyflex bass cone. 4 layers voice-coil for dynamic bass. Magnetically shielded

Polyfix system for on wall or stand mounting. Vertical or horizontal use.

OPC (Optimum Phase Crossover) for perfect staging.

Rotable logo.



- ◆ The high performances on wall speaker dedicated for flat screen.
- ◆ The Focal sound.
- ◆ Hop and Bop optional stands.

- ◆ "On Wall/free standing" mode.
- ◆ Rotable logo.
- ◆ Splashproof.

Type	2-way bass-reflex LCR speaker. Polyfix® wall bracket
Drivers	2x5" (2x13cm) Polyflex mid-bass. OAL 3/4" (19mm) aluminium tweeter dome
Frequency response (+/- 3dB)	67Hz - 35kHz
Low frequency point (- 6dB)	59Hz
Sensitivity (2.83V/1m)	91dB
Nom. impedance	8 ohms
Crossover frequency	3 500Hz
Recommended amplifier power	15 - 150W
Dimensions (HxWxD)	19 ^{7/8} x5 ^{5/8} x4 ^{1/4} " (505x142x108mm)
Net weight	8.8lbs (4kg)

Sib XL was created to harmonize with flat panel Plasma and LCD's. Sib XL is delivered with the Polyfix® wall mount, which allows for vertical and horizontal installation. The stands Bop (short) and Hop (tall) are available as an option to make Sib XL a totally universal solution.

