Image Scanner 17-6130 Image Scanner

# The best cost performer in its class\* The duplex color ADF scanner that is compact enough to place on your desk



The best cost performer in its class

- Comes loaded with intelligent software for more efficient scanning:
- Intelligent multifeed function
- Auto color recognition function
- Auto document size recognition function
- Auto deskew function

Color

30

A4 ppm

Α4

Mono

40

A4 ppn

DUPLEX

Comes bundled with the "automatic job separation" function armed ScandAll PRO Ver1.5 image capture software.

Imprinter option

\*This class includes A4 ADF (Automatic document feeder) and A4 ADF / flatbed tandem color image scanners that are priced between US\$300 and US\$2000. (This stood true as of March 31, 2008)

Visit the fi-Series web site for ordering and purchasing information

http://imagescanner.fujitsu.com/

#### Features

#### The best cost performer in its class

The fi-6130's ability to scan up to 40ppm or 80ipm in monochrome / grayscale (A4, 200dpi) makes it the top cost performer in its class. Its ability to continuously scan 50 page mixed batch documents containing paper of different weight, quality and sizes enables the fi-6130 to efficiently digitize large volumes of paper documents. On top of this, the fi-6130 is able to scan up to 3 (up to 1.4mm thick) plastic cards at a time.

### Loaded with "intelligent" functions for efficient operation

The fi-6130 is loaded with 2 high end fi-Series functions that enable it to efficiently scan mixed batch documents containing paper of different weights, quality and size.

#### Intelligent multifeed function

The intelligent multifeed function simplifies pre-scanning preparation and improves efficiency by ignoring documents that tend to trigger false multifeed alerts, such as photo and sticky note attached documents documents.

"Auto-color recognition", "auto-size recognition" and "auto-deskew functionality"

This functionality enables the fi-6130 to automatically recognize the size of scanned documents, correct skewed images and automatically differentiate color images from black and white ones. images and

#### Comes bundled with the "automatic job separation" function armed ScandAll PRO Ver1.5 image capture software

The fi-6130's bundled barcode and patchcode reading functionality enables it to simultaneously scan and automatically separate different jobs with its automatic job separation function. The result is improved digitizing efficiency.

#### Imprinter supportability (fi-6130 / fi-6140 option)

Use of the fi-6130's optional imprinter (fi-614PR) enables users to print dates and other information on the back of the original document, thus easing the search for original documents at a later date.



# Kofax VRS (Virtual ReScan) Professional for Workgroup bundled included Virtual ReScan (VRS) \* VRS verification and adjustment features generate perfe

- images every time. The ability to efficiently digitize large volumes of documents
  - dramatically improves scanning productivity. Easy to use. Automated functions remove the need for skilled scanner operators

#### Technical Specifications

Product name		FI-6130	
Supported operating systems		Microsoft® Windows® 2000 Professional / Microsoft® Windows® XP (32bit/64bit) /	
		Microsoft® Windows Server <sup>™</sup> 2003 (32bit/64bit) / Microsoft® Windows Vista <sup>™</sup> (32bit/64bit)	
Scanner type		ADF (Automatic Document Feeder)	
Scanning mod	des	Simplex / Duplex, Color / Grayscale / Monochrome	
Image sensor type		Color CCD (Charge-coupled device) x 2	
Light source		White cold cathode discharge lamp	
Scanning rang	ge	Maximum: A4 portrait (210 x 297mm), legal (8.5 x 14in.)	
	-	(long document scanning: 216 x 864mm or 8.5 x 34in., or 210 x 3048mm or 8.27 x 120in.)	
		Minimum: A8 (52 x 74mm or 2 x 3in.)	
ADF feedable paper weight		41 to 210g/m <sup>2</sup> (11 to 56.2lb) and only supports 127 to 210 g/m <sup>2</sup> (34 to 56.2lb) for A8 sheets.	
(Thickness)		Card feedability (ADF) <sup>11</sup> supports both portrait and landscape feedability <sup>12</sup> 1.4mm thickness or less	
Scanning	Color *4	Simplex: 30ppm (200dpi), Duplex: 60ipm (200dpi)	
speed		Simplex: 30ppm (300dpi), Duplex: 60ipm (300dpi)	
(A4 portrait)*3	Grayscale *4	Simplex: 40ppm (200dpi), Duplex: 80ipm (200dpi)	
		Simplex: 30ppm (300dpi), Duplex: 60ipm (300dpi)	
	Monochrome	Simplex: 40ppm (200dpi), Duplex: 80ipm (200dpi)	
		Simplex: 30ppm (300dpi), Duplex: 60ipm (300dpi)	
Paper chute c	apacity *5	50 sheets (A4: 80g/m <sup>2</sup> or 20lb) (Active loadable ADF)	
Background of	colors	White / Black (Selectable)	
Optical resolu	Ition	600dpi	
Output resolution <sup>*6</sup> Color (24bit) Grayscale (8bit) Monochrome (1bit)			
		50 to 600dpi (adjustable by 1dpi increments), 1200 dpi <sup>*7</sup>	
Output format		Color: 24bit, 8bit/4bit	
		Grayscale: 8bit, 4bit	
		Monochrome: 1bit	
AD converter		1024 levels (10bit)	
Interface		USB2.0 / USB1.1	
Connector sh	ape	B type	
Output mode	(half-tone)	Dither / Error diffusion	
Voltage or vol	tage range	AC 100 to 240V ±10%	
Power require		Operating: 38W or less (Sleep mode: less than 6.2W)	
Operating env	/ironment	Temperature: 5 to 35°C (42 to 95°F)	
		Relative humidity: 20 to 80% (Non-condensing)	
Dimensions: Width x Depth x Height *8			
	th x Depth x Height *8	301 x 160 x 158mm (11.8 x 6.4 x 6.2 in.)	
	th x Depth x Height *8	Installation space: 400 x 700 x 380mm (15.8 x 27.6 x 15.0 in.)	
Weight		Installation space: 400 x 700 x 380mm (15.8 x 27.6 x 15.0 in.) 4.2 kg (9.24lb)	
		Installation space: 400 x 700 x 380mm (15.8 x 27.6 x 15.0 in.)           4.2 kg (9.24lb)           TWAIN, ISIS™, ScandAll PRO, Adobe® Acrobat®, QuickScan™ Pro. Demo (Trial),	
Weight Included soft	ware / drivers	Installation space: 400 x 700 x 380mm (15.8 x 27.6 x 15.0 in.)         4.2 kg (9.24lb)         TWAIN, ISIS™, ScandAll PRO, Adobe® Acrobat®, QuickScan™ Pro. Demo (Trial),         Image Processing Software (Trial), VRS Professional	
Weight Included soft Environmenta	ware / drivers	Installation space: 400 x 700 x 380mm (15.8 x 27.6 x 15.0 in.)         4.2 kg (9.24lb)         TWAIN, ISIS™, ScandAll PRO, Adobe® Acrobat®, QuickScan™ Pro. Demo (Trial),         Image Processing Software (Trial), VRS Professional         ENERGY STAR® and RoHS	
Weight Included softwork Environmenta Others	ware / drivers Il compatibility " <sup>9</sup> Multi-feed detection	Installation space: 400 x 700 x 380mm (15.8 x 27.6 x 15.0 in.) 4.2 kg (9.24lb) TWAIN, ISIS <sup>TM</sup> , ScandAll PRO, Adobe <sup>®</sup> Acrobat <sup>®</sup> , QuickScan <sup>TM</sup> Pro. Demo (Trial), Image Processing Software (Trial), VRS Professional ENERGY STAR <sup>®</sup> and RoHS Yes(Standard) ultrasonic multi-feed detection sensor	
Weight Included soft Environmenta Others	ware / drivers Il compatibility <sup>9</sup> Multi-feed detection Long paper scanning <sup>110</sup>	Installation space: 400 x 700 x 380mm (15.8 x 27.6 x 15.0 in.) 4.2 kg (9.24lb) TWAIN, ISIS <sup>TM</sup> , ScandAll PRO, Adobe <sup>®</sup> Acrobat <sup>®</sup> , QuickScan <sup>TM</sup> Pro. Demo (Trial), Image Processing Software (Trial), VRS Professional ENERGY STAR <sup>®</sup> and RoHS Yes(Standard) ultrasonic multi-feed detection sensor 3048mm (120 in.)	
Weight Included softw Environmenta Others	ware / drivers Il compatibility <sup>9</sup> Multi-feed detection Long paper scanning <sup>10</sup>	Installation space: 400 x 700 x 380mm (15.8 x 27.6 x 15.0 in.) 4.2 kg (9.24lb) TWAIN, ISIS <sup>TM</sup> , ScandAll PRO, Adobe <sup>®</sup> Acrobat <sup>®</sup> , QuickScan <sup>TM</sup> Pro. Demo (Trial), Image Processing Software (Trial), VRS Professional ENERGY STAR <sup>®</sup> and RoHS Yes(Standard) ultrasonic multi-feed detection sensor	

\*1 \*2

- Supports ISO7810 embossed cards Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feedability.)
- Actual scanning speeds are affected by data transmission and software processing times JPEG compressed figures \*3
- Maximum capacity varies, depending upon paper weight
- \*6
- Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is
- scanning in simplex or duplex. Scanning imitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher). \*7
- \*8
- 8 Excluding the ADF paper chute and stacker
  9 PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC)
  10 Capable of scanning documents that exceed A4 sheets in length. However, the scanning of documents that exceed 863mm (34 in.) in length will be limited to using TWAIN at 200dpi or less.

### Options

/RS

Description	Part number	Comments
Post Imprinter(FI-614PR)	PA03540-D201	Assists document management by printing numbers, Roman characters and codes on
		original documents after they have been scanned.
Image Processing Software Option V2.5	PA43402-C22901	This Image Processing Software enables the scanner to efficiently binarize scanned data prior to transmission.

#### Consumables

	Description	Part number	Comments			
	Brake Roller	PA03540-0001	Lifetime: Every 200,000 sheets or one year.			
			These rollers separate documents as they are being fed into the scanner.			
	Pick Roller	PA03540-0002	Lifetime: Every 200,000 sheets or one year.			
			These rollers feed documents into the scanner.			
	Print Cartridge	CA00050-0262	Lifetime: 4,000,000 printed characters.			
			FI-614PR print head			

#### Trademarks

Please note that the scanning and printing of paper currency as well as stock and bond certificates is illegal.

- Microsoft, Windows, Windows Server and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries.
- Adobe and Adobe Acrobat are registered trademarks of Adobe Systems Incorporated in the United States and/or other countries. \* ISIS is a registered trademark of EMC Corporation of the United States.
- Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

## Japan contact PEU LIMITED

International Sales Dept., Imaging Business Div. Solid Square East Tower, 580 Horikawa-cho, Saiwai-ku, Kawasaki-city, Kanagawa 212-8563, Japan Phone: (81-44) 540-4668 Fax: (81-44) 540-4639 http://imagescanner.fujitsu.com/

## XXXXXXXX contact

 $FUJITSU \times \times \times \times \times \times$ \*\*\* \*\*\* \*\*\* \*\*\* \*\*\* \*\*\* \*\*\* \*\*\* \*\*\* Phone: (1-23) 456-7890 Fax: 123-456 http://www. ××××.com/

#### ▲ Safety Precautions

- Be sure to carefully read all safety precautions prior to using this product and use this device as instructed.
- Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.
- Be sure to limit the use of this product to listed power ratings.

