

Value for You RLP Prijslijst



Februari 2014

FUJITSU DESKTOP PC



FUJITSU NOTEBOOKS



FUJITSU SERVERS



LIFEBOOK Notebooks / STYLISTIC Tablets



LIFEBOOK A512 LIFEBOOK A532 LIFEBOOK U574 Ultrabook™ LIFEBOOK E752 LIFEBOOK E733 LIFEBOOK E733



Your Everyday Partner

Your Essential Partner

Your Ultra-thin Mobile Companion

Your Professional Desktop Replacement

Elegant Design and Functionality without Compromises

Elegant Design and Functionality without Compromises

Processor, Chipset, Memory

Processor, Chipset, Memory

Processor, Chipset, Memory

Processor, Chipset, Memory

Processor, Chipset, Memory

Processor, Chipset, Memory

Intel® Core™ i3-3110M processor (2.4 GHz), 3 MB, Intel® HM75
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Intel® Core™ i5-4200M processor
Intel® HM76
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Intel® Core™ i5-i5-4200U processor
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® HM76
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

Drives

Drives

Drives

Drives

Drives

SATA, 5400 rpm, 320 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

SSD SATA III, 128 GB, 2.5-inch

SATA, 7200 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

SSHD, 5400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

Communication, Network

Communication, Network

Communication, Network

Communication, Network

Communication, Network

Bluetooth: v4.0 + EDR
LAN: 10/100/1000 MBit/s Realtek RTL 8111F

Bluetooth: v4.0 + EDR
LAN: 10/100/1000 MBit/s Realtek RTL 8111F

WLAN: Intel® Wireless-N 7260 2x2 BGN + BT
Bluetooth: Integrated V4.0 + HS
LAN: USB to LAN (with USB to LAN adapter)

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 V

WLAN: Intel® Centrino® Wireless-N2230 b/g/n
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

WLAN: Intel® Centrino® Wireless-N2230 b/g/n
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Display, Grafic

Display, Grafic

Display, Grafic

Display, Grafic

Display, Grafic

39.6 cm (15.6-inch), TFT, (HD), LED backlight, anti-glare, 1366 x 768 pixel, 300:1 (min), 200 cd
Intel® HD Graphics or HD Graphics 3000 (depending on CPU), up to 1695 MB

39.6 cm (15.6-inch), TFT, (HD), LED backlight, anti-glare, 1366 x 768 pixel, 300:1 (min), 200 cd
Intel® HD Graphics 3000 or 4000 (depending on CPU), up to 1695 MB

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare touchscreen, 1366 x 768 pixel, 220 cd/m²
Intel® HD Graphics 4400

39.6 cm (15.6-inch), LED backlight, (HD), Anti-glare display, compound, 1366 x 768 pixel, 300:1, 220 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1 (t.b.d.), 200 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1 (t.b.d.), 200 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Keyboard and pointing devices

Keyboard and pointing devices

Keyboard and pointing devices

Keyboard and pointing devices

Keyboard and pointing devices

Touchpad, Status LED
Keyboard, N/A

Touchpad, Status LED
Keyboard, N/A

Keyboard, Multi gesture touchpad with integrated mouse button functionality

Multi gesture touchpad with two mouse buttons, Optional: Fingerprint sensor, Optional: TouchStick, Application buttons
Keyboard, N/A

Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons, Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons, Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Power supply

Power supply

Power supply

Power supply

Power supply

Power supply

Li-Ion battery 6-cell, 4400 mAh, 48 Wh
Runtime 1st battery: up to 6 h

Li-Ion battery 6-cell, 4400 mAh, 48 Wh
Runtime 1st battery: Up to 6:20 h (productivity mode)

Lithium polymer battery 4-cell, 2840 mAh, 48.8 Wh
Runtime 1st battery: up to 11 h

Runtime 1st battery: up to 12 h

Runtime 1st battery: up to 13 h (tbd)

Runtime 1st battery: up to 13 h (tbd)

Dimensions / Weight / Environmental

Dimensions / Weight / Environmental

Dimensions / Weight / Environmental

Dimensions / Weight / Environmental

Dimensions / Weight / Environmental

Dimensions / Weight / Environmental

2.5 kg
378 x 252 x 36.5 mm
Matt Matte black

2.4 kg
378 x 252 x 34.2 mm
Matt Black/silver

Approx. 1.6 kg
322 x 225 x 19.5 mm
Aluminum lid Black with red details

2.5 kg
372 x 245 x 35 mm

1.7 kg
321 x 228 x 20 (f) - 27 (r) mm

1.7 kg
321 x 228 x 20 (f) - 27 (r) mm

Operating system

Operating system

Operating system

Operating system

Operating system

Operating system

Win8Pro+Win7Load

Win8Pro+Win7Load

Win8Pro+Win7Load

Windows 8 Pro

Windows 8 Pro

Windows 8 Pro

Interfaces

Interfaces

Interfaces

Interfaces

Interfaces

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 (34 mm and 54 mm supported) x ExpressCard slots, 1 x HDMI, N/A x , 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x SD-Card Reader (SD/SDHC) x Memory card slots, 3 (1 x Anytime USB Charge functionality) x USB 2.0 total, 1 x VGA, Intel® Centrino® Wireless N2230 (IEEE 802.11b/g/n) x Integrated WLAN

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 (34 mm) x ExpressCard slots, 1 x HDMI, N/A x , 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x 4in1 Card Reader (SD/SDHC/MS/MS Pro) x Memory card slots, 1 x USB 2.0 total, 3 (1 x Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA, Intel® Centrino® Wireless N2230 (IEEE 802.11b/g/n) x Integrated WLAN

1 (HP/MIC Comb Jack) x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 x HDMI, 1 digital x Internal microphones, 1 x Kensington Lock support, via USB (with USB to LAN adapter - PXE Boot capable) x Ethernet (RJ-45), 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS), 1 (incl. 1x Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0 total, Intel® Centrino Wireless-N7260 a/b/g/n

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 (V1.1a) x DisplayPort, 1 x Docking connector for Port Replicator, 1 x eSATA & USB combo, 1 (34 / 54 mm supported) x ExpressCard slots, N/A x , 2x digital (array) microphones as option x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB, MS Pro, MS Pro Duo) x Memory card slots, 1 (optional) x Modem (RJ-11), 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 (1x with Anytime USB Charge functionality) x USB 2.0 total, 2 (1 thereof is the E-SATA & USB combo) x USB 3.0 total, 1 x VGA

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

Warranty

Warranty

Warranty

Warranty

Warranty

1 year Bring-in Service

1 year Bring-in Service

1 year Bring-in Service

1 year Bring-in Service

2 year Bring-in Service

2 year Bring-in Service

EUP (End User Price):

EUP (End User Price):

EUP (End User Price):

EUP (End User Price):

EUP (End User Price):

EUP (End User Price):

€ 449

€ 549

€ 889

€ 779

€ 889

€ 999

VFY:A5120M7311NL

VFY:A5440M7501NL

VFY:U5740M7512NL

VFY:E7520M4501NL

VFY:E7330M55A1NL

VFY:E7330MXE11NL

STYLISTIC M702

Designed for the toughest businesses
Processor, Chipset, Memory

NVIDIA® Tegra® 3
NVIDIA® Tegra® 3 AP37, Quad-Core ARM Cortex A9, 1 MB, 1.7 GHz

Drives

32GB eMMC 4.4.1 Flash Memory

Communication, Network

Texas Instruments WL1283

Display, Graphic

25.7 cm (10.1-inch), TFT, (WUXGA), 1920 x 1200 pixel, 500:1, max. 300 cd/m²

Keyboard and pointing devices
Power supply

video playback up to 15 h

Dimensions / Weight / Environmental

590 g
259 x 169 x 9.9 mm

Operating system

Android 4.0 (Ice Cream Sandwich)

Interfaces

1 x Audio: line-in / line-out, N/A x , N/A x , 1 (digital) x Internal microphones, 1 x Memory card slots, 1 x Micro USB 2.0, 1 x SIM card slot (Micro-SIM), Texas Instruments WL1283 x Integrated WLAN

STYLISTIC Q572

Your Professional BusinessPad
Processor, Chipset, Memory

AMD A68M FCH

Drives

mSATA, 128 GB, FDE

Communication, Network

UMTS Modul: Sierra Wireless Gobi 3000
10/100 Mbit/s (via cradle only)

Display, Graphic

AMD Radeon™ HD 6250

Keyboard and pointing devices
Dimensions / Weight / Environmental

0.732 kg
273.5 x 176 x 13.9 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2 (digital) x Internal microphones, 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 x USB 2.0 total

Warranty

2 year Bring-in Service

EUP (End User Price):

€ 999

VFY:Q5720M3001NL

STYLISTIC Q702

Attach or Touch - The Hybrid Business Talent
Processor, Chipset, Memory

Intel® Core™ iCore i3-3227U processor
Intel® QM77

Drives

SSD mSATA, 128 GB

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Graphic

Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices
Power supply
Dimensions / Weight / Environmental

0.850 kg
302 x 195 x 12.7 mm

Operating system

Windows 8.1 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2 (digital) x Internal microphones, 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 1 x USB 3.0 total

Warranty

2 year Bring-in Service

EUP (End User Price):

€ 1.169

VFY:Q7020M7351NL

EUP (End User Price):

€ 888

VFY:M7020MPAD1IN

ESPRIMO P410 E85+	ESPRIMO E420 E85+	ESPRIMO P420 E85+	ESPRIMO P420 E85+	ESPRIMO Q520
-------------------	-------------------	-------------------	-------------------	--------------



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Pentium® processor G2020 (2.90 GHz), 3 MB, Intel® H61
2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 250 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Operating system

Win8Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 329

VFY:P0410P5211NL



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Core™ i3-4130 processor (3.40 GHz)
Intel® H81
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

9 kg
330 x 405 x 104 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 449

VFY:E0420P7321NL



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Core™ i3-4130 processor (3.40 GHz), 3 MB
Intel® H81
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 449

VFY:P0420P7321NL



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Core™ i5-4440 processor (3.10 GHz), 6 MB,
Intel® H81
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 499

VFY:P0420P7511NL



The Mini with More PC per cm

Processor, Chipset, Memory

Intel® Core™ i3-4130T processor (2.90 GHz), 3 MB
Intel® H81
4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO

Drives

HDD SATA II, 5400 rpm, 500 GB, 2.5-inch
DVD Super Multi Slot-in slim

Communication, Network

Bluetooth: 1 (optional)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

1.6 kg
185 x 188 x 54 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 (DVI-I) x DVI, 2x 2.0 x USB front, 1 x HDMI, 1 x Kensington Lock, support, 1 x Ethernet (RJ-45), 1 x Multicardreader, 6 x USB 2.0 total, 4x 2.0 x USB rear, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 539

VFY:Q0520P7311NL

ESPRIMO E520 E85+

Your Flexible and Economic PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB
Intel® B85
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800,
DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
330 x 405 x 104 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0 x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0/ 2x 3.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 549

VFY:E0520P7551NL

ESPRIMO P520 E85+

Your Flexible and Economic PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB,
Intel® B85
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800,
DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
175 x 425 x 353 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0 x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0/ 2x 3.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 549

VFY:P0520P7551NL

ESPRIMO C720

Your Ultra Small Form Factor PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB,
Intel® Q85
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800,
DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD SuperMulti SATA slim

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

9 kg
265 x 315 x 88 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, N/A x , 1 x DisplayPort, 1 (DVI-I) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 2 x Serial (RS-232) (powered, 9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 649

VFY:C0720P7501NL

ESPRIMO E720 E90+

Combines High Efficiency with Manageability
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB,
Intel® Q85
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800,
DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
340 x 382 x 98 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 649

VFY:E0720P7501NL

ESPRIMO P720 E90+

Excellent Performance, Expandability and Efficiency
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB,
Intel® Q85
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800,
DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

EUP (End User Price):

€ 649

VFY:P0720P7501NL

ESPRIMO E920 0-Watt

The Innovative 0-Watt PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q87
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
340 x 382 x 98 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 699

VFY:E0920PXG11NL

ESPRIMO P920 0-Watt

The Innovative 0-Watt PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q87
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 699

VFY:P0920PXG21NL

ESPRIMO Q920

The Mini with More PC per cm³
Processor, Chipset, Memory

Intel® Core™ i5-4570T processor (2.90 GHz), 4 MB, Intel® Q87
4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch
DVD Super Multi Slot-in slim

Communication, Network

Bluetooth: 1 (optional with WLAN together)
LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

1.6 kg
185 x 188 x 54 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DisplayPort, 1 (DVI-I) x DVI, 2x 3.0 x USB front, N/A x , 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD, MMC) x Multicardreader, 2 x USB 2.0 total, 2x 2.0 and 2x 3.0 x USB rear, 4 x USB 3.0 total, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional with Bluetooth together) x Integrated WLAN

Slots, Bays

1 x 5.25-inch external bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 799

VFY:Q0920PXP11NL

ESPRIMO X913-T

Evolutionary PC for the Modern Office
Processor, Chipset, Memory

Intel® Core™ i5-3470T processor (2.90 GHz), 3 MB, Intel® Q77
2 x 2 GB (1 module(s) 2 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch

Communication, Network

Bluetooth: 1 (optional with WLAN module)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics#Intel® HD Graphics 2000#Intel® HD Graphics 2500, up to 1759 MB

Dimensions / Weight / Environmental

8.62 kg
533 x 224 x 419 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DVI, N/A x , optional with camera module x Internal microphones, 2 x Kensington Lock support, 1 x Ethernet (RJ-45), 2 x USB 2.0 total, 2x2.0 2x3.0 x USB rear, 4 x USB 3.0 total, 2x3.0 x USB left side, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

0 x 2.5-inch bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 1.099

VFY:X9130P7511NL

ESPRIMO P920 E90+

Excellent Performance, Expandability And Efficiency
Processor, Chipset, Memory

Intel® Core™ i7-4770 processor (3.40 GHz), 8 MB, Intel® Q87
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

SSHD SATA III, 7200 rpm, 1000 GB, 3.5-inch

MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

AMD® Radeon R9 255 FH 2GB, Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 1.099

VFY:P0920PXP51NL

FUTRO Thin Clients



FUTRO S700



De betaalbare Thin Client

Processor, Chipset, Memory

AMD A55E Controller Hub
2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM

Drives

mSATA, 2 GB, Flash drive

Communication, Network

LAN: Built-in 10/100/1000 MBit/s

Display, Graphics

ATI Radeon™ HD 6250 , up to 256 MB

Dimensions / Weight / Environmental

1,2 kg
97 x 191 x 266 mm

Operating system

eLux® RL - Embedded Linux

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, 1 x DC-in, 1 DP x DisplayPort,
1 DVI-I (integrated VGA can be used with DVI-VGA adapter) x DVI,
1 x Front audio: headphone, 1 x Front audio: line-in / microphone,
2 x USB front, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 2
x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, 2 x USB
internal

Warranty

2 year Bring-in Service

EUP (End User Price):

€ 299

VFY:S0700PF045NL/End-of-Life

FUTRO S700



De betaalbare Thin Client

Processor, Chipset, Memory

AMD A55E Controller Hub
2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM

Drives

mSATA, 4 GB, Flash drive

Communication, Network

LAN: Built-in 10/100/1000 MBit/s

Display, Graphics

ATI Radeon™ HD 6250 , up to 256 MB

Dimensions / Weight / Environmental

1,2 kg
97 x 191 x 266 mm

Operating system

Windows® Embedded Standard 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, 1 x DC-in, 1 DP x DisplayPort,
1 DVI-I (integrated VGA can be used with DVI-VGA adapter) x DVI,
1 x Front audio: headphone, 1 x Front audio: line-in / microphone,
2 x USB front, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 2
x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, 2 x USB
internal

Warranty

2 year Bring-in Service

EUP (End User Price):

€ 349

VFY:S0700PX011NL/End-of-Life

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1220v2# (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 500 GB, 3.5-inch, economic
DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

EUP (End User Price):

€ 549

VFY:T1003SC070IN

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1220v2# (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202

8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 500 GB, 3.5-inch, economic
DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 (mech x4)
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9, 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

EUP (End User Price):

€ 630

VFY:T1003SC140IN

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1230v2# (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202

2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 1 TB, 3.5-inch, business critical
DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

EUP (End User Price):

€ 849

VFY:T1003SC090IN

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1230v2# (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202

8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 2 TB, 3.5-inch, business critical
DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

EUP (End User Price):

€ 970

VFY:T1003SC160IN

PRIMERGY TX140 S2

Expandable SME all-round server

The Fujitsu Server PRIMERGY TX140 S2 is the ideal, robust and cost-efficient server for SMBs or branch offices. It not only scores with the best Intel® Xeon® E3 performance and solid expandability thanks to hot-plug hard disks, but also with its optionally redundant power supply and full server management support. The PRIMERGY TX140 S2: an excellent long-term investment.

Processor, Chipset, Memory

Intel® Xeon® processor E3-1220v3# (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 80 W)
Intel® C224
8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D3239

Drives, Controller

DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 (mech x4)
1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA
3 x 5.25/1.6-inch

Dimensions / Weight / Environmental

483 x 495 x 175 mm
177 x 560 x 455 mm

Rack: 12.5kg - 20kg; Tower: 15kg - 23 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 11, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

6 , 1 serial RS-232-C, usable for iRMC or system or shared,
1 analog graphics interface derived from iRMC (up to 1600x1200 or 1920x1080 at 16bpp),
1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s),
Management LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

EUP (End User Price):

€ 880

VFY:T1402SC040IN

PRIMERGY TX150 S8

The one-processor tower server - maximized!

The PRIMERGY TX150 S8: the right system for SMEs, branch offices or virtualized environments where the main focus is on expandability and availability. With processors of the Intel® Xeon® E5-1400 and E5-2400 family, the TX150 S8 delivers excellent energy-efficient performance. PRIMERGY TX150 S8: the one processor tower server – maximized!

Processor, Chipset, Memory

Intel® Xeon® processor E5-2420# (6C/12T, 1.90 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)
Intel® C602
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3079

Drives, Controller

DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

483 x 611 x 177 mm
177 x 651 x 456 mm

16 - 29 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 x USB 2.0 (2x front, 4x rear, 3x internal for backup, UFM and internal USB), 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

EUP (End User Price):

€ 1,099

VFY:T1508SC040IN

PRIMERGY TX200 S7

Well-balanced price- performance

The PRIMERGY TX200 S7 is a perfect server for SMEs, branch offices or virtualized infrastructures. The tower server offers dual processor performance combined with expandability and energy efficiency. Its feature set makes the TX200 S7 a great virtualization, database or communication server. The PRIMERGY TX200 S7 strikes the right balance between price and performance.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2420# (6C/12T, 1.90 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)
Intel® C602
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3099

Drives, Controller

DVD Super Multi, half height, SATA I
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu
512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

..483 x 611 x 177 mm
..177 x 651 x 456 mm

..16 kg - 29 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet (Intel Hartwell), 9 x USB 2.0 (2 x front USB, 4 x rear USB 3 x internal for backup, UFM and internal USB), 1 x serial RS-232-C (9 pin), usable for iRMC S3 or system or common use, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

3 years
On-site Service

EUP (End User Price):

€ 1,449

VFY:T2007SC040IN

PRIMERGY TX300 S8

Reliable performance for your business

The FUJITSU Server PRIMERGY TX300 S8 offers maximum performance, best expandability and highest availability without any compromises. Branches, data centers and SMEs value the performance of the two Intel® Xeon® E5 v2 processors, 1536 GB RAM and GPU card support. 10 extension slots and the redundant power supply enable top availability levels and excellent extendability options. The server is thus ideal for computing-intensive applications,

Processor, Chipset, Memory

Intel® Xeon® processor E5-2620v2# (6C/12T, 2.10 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1600 MHz, 80 W)
Intel® C602
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D2949

Drives, Controller

DVD Super Multi, half height, SATA I
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS
6G 5/6 512MB (D2616), 8 ports int.#RAID level:
0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA
3 x 5.25/1.6-inch

Dimensions / Weight / Environmental

177 x 777 x 456 mm

up to 35 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 11, vSphere 4.1, vSphere 4.1 Embedded, vSphere 4.1 Installable, vSphere 5.0 Embedded, vSphere 5.0, vSphere 5.5 Embedded, vSphere 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Hyper-V Server 2012, WindowsServer® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

x Gbit/s Ethernet, 10 , 1 x serial RS-232-C, usable for iRMC S3 or system or shared, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s), Management LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

3 years
On-site Service

EUP (End User Price):

€ 1,880

VFY:T3008SC010IN

PRIMERGY RX100 S7

Small in size and low in cost – rich in optional features

The Fujitsu PRIMERGY RX100 S7 is an entry mono socket rack server designed to meet small budgets by delivering highest energy efficiency of its class and a rich set of optional expansions to meet individual demands. Optimized for infrastructure and communication applications, this 1U server delivers up to 32GB RAM, up to 3 PCIe slots and up to 4 hard disk drives.

PRIMERGY RX200 S8

Maximum productivity in a 1U housing

The Fujitsu Server PRIMERGY RX200 S8 is a rack server that provides high performance of the new Intel® Xeon® E5 product family, expandability up to 1536 GB of memory and up to 96% energy efficiency - all in 1U space saving housing. Thus, the PRIMERGY RX200 S8 is ideal for virtualization and cloud, small databases as well as for high performance computing.

PRIMERGY R300 S8

The versatile 2U powerhouse

The Fujitsu Server PRIMERGY RX300 S8 is a 2U dual socket rack server, optimized for all types of business applications by focusing on versatility and scalability that supports up to 16 harddisk drives, up to 7 PCIe Gen 3 cards and up to 1536 GB RAM. Thanks to top performance of the new Intel® Xeon® E5 product family and the available upgrade kits, the RX300 will also ensure the demands of tomorrow are met.

Processor, Chipset, Memory

Intel® Xeon® processor E3-1230v2# (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202

2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3034

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 (mech x4)
1 x PCI-Express 2.0 x4 (mech. x8)
4x 2.5-inch hot-plug SAS/SATA or 2x 3.5-inch hot-plug SAS/SATA
1 x 5.25/0.5-inch for CD-RW/DVD#1 x 3.5/0.5-inch for ServerView Local Service Panel or front VGA + front Service LAN

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 431mm (Body) x 572 x 42.5 mm
up to 14 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, vSphere™ 5.0 Embedded, vSphere™ 5.0, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 7 , 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA (15-pin), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Management LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

EUP (End User Price):

€ 1.030

VFY:R1007SC080IN

Processor, Chipset, Memory

Intel® Xeon® processor E5-2620v2# (6C/12T, 2.10 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1600 MHz, 80 W)
Intel® C600 (Intel® Patsburg A)

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D3332

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

4 x 2.5-inch base unit or 8 x 2.5-inch base unit
1 x 5.25/0.5-inch for DVD-RW/Blu-ray (only for base unit 4x 2.5-inch HDD)

Dimensions / Weight / Environmental

482 mm (Bezel) / 431mm (Body) x 762 mm x 43 mm
up to 18 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

6 , 1 x optional, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s), Management LAN traffic can be switched to shared onboard Gbit LAN port

or optional Modular LAN 2x10 Gbit controller, Front Service LAN port as option

Warranty

3 years
On-site Service

EUP (End User Price):

€ 1.590

VFY:R2008SC010IN

Processor, Chipset, Memory

Intel® Xeon® processor E5-2620v2# (6C/12T, 2.10 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1600 MHz, 80 W)
Intel® C600 (Intel® Patsburg A)

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D2939

Drives, Controller

DVD Super Multi, slimline, SATA I
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int.#RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

2.5-inch base unit (max. 16 x 2.5) or 3.5-inch base unit (max. 6 x 3.5)
1 x 5.25/0.5-inch for ODD#1 x 5.25/0.5-inch for Local Service Display
#1 x 3.5/1.6-inch for backup devices#1 x 5.25/1.6-inch for backup devices

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 445mm (Body) x 770 x 86.9 mm
up to 25 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 11, vSphere 5.0 Embedded, vSphere 5.0, vSphere 5.5 Embedded, vSphere 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

6 , 1 x optional, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s), Management LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

3 years
On-site Service

EUP (End User Price):

€ 2.160

VFY:R3008SC030IN

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Core™ i5-4670 processor (3.40 GHz), 6 MB,
Intel® C226
8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

AMD FirePro™ V3900, 1 GB
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 833

VFY:W5300WVG11NL

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Xeon® processor E3-1270v3 (3.50 GHz), 8 MB,
Intel® C226
8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III Premium, 128 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

NVIDIA® Quadro® K2000, 2 GB
DP to DVI-D (single link) Adapter Cable
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 1.499

VFY:W5300WXP11NL

CELSIUS M720



Your "Thoroughbred" Workstation

Processor, Chipset, Memory

Intel® Xeon® processor E5-1620 (3.60 GHz), 10 MB,
Intel® C602
4 x 2 GB (1 module(s) 2 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Graphics

AMD FirePro™ V4900, 1 GB

Dimensions / Weight / Environmental

18 kg
186 x 481 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x Audio: in, 1 x Audio:
out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 1 x Ethernet
(RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB
rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI slots, 8 x 2.5-inch bays,
2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch
external bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 1.249

VFY:M7200WVG11NL

CELSIUS M720



Your "Thoroughbred" Workstation

Processor, Chipset, Memory

Intel® Xeon® processor E5-1620 (3.60 GHz), 10 MB,
Intel® C602
4 x 4 GB (1 module(s) 4 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III, 128 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Graphics

DP to DVI-D (single link) Adapter Cable
NVIDIA® Quadro® K2000, 2 GB

Dimensions / Weight / Environmental

18 kg
186 x 481 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x Audio: in, 1 x Audio:
out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 1 x Ethernet
(RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB
rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI slots, 8 x 2.5-inch bays,
2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch
external bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 1.799

VFY:M7200WXP21NL

CELSIUS R920

Uncompromising Workstation Performance for Extreme Requirements
Processor, Chipset, Memory

Intel® Xeon® processor E5-2640 (2.50 GHz), 15 MB, 7.2 GT/s
Intel® C602
4 x 4 GB (1 module(s) 4 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III, 256 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 2x Built-in 10/100/1000 MBit/s Intel® 82579 LM and Intel®

Display, Graphics

No graphics in system

Dimensions / Weight / Environmental

20 kg
186 x 618 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x eSATA, 1 x Audio: in,
1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers,
2 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB
2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB
internal

Slots, Bays

1 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-
inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 2.999

VFY:R9200WXP41NL

CELSIUS H720

Workstation Power on-the-Go
Processor, Chipset, Memory

Intel® Core™ i7-3740QM processor (2.7 GHz), 6 MB,
Intel® QM77
2 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 256 GB, 2.5-inch
DVD-RW Dual Double Layer Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000 module
10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

39.6 cm (15.6-inch), LED backlight, (Full HD), Anti-glare display,
magnesium, 1920 x 1080 pixel, 300:1, 220 cd/m
NVIDIA® Quadro® K1000M#NVIDIA® Quadro® K2000M, 2 GB (GDDR3
VRAM)

Dimensions / Weight / Environmental

2.8 kg
379.8 x 257.0 x 35.5 mm

Operating system

Win8P lic./ Win7P load / RDVD TWIN-Pack

Interfaces

1 x DC-in, 1 x DisplayPort, 1 x eSATA, 1 (34 mm) x ExpressCard slots,
1 x Audio: in, 1 x Audio: out, 2 digital array microphones x Internal
microphones, 1 x Ethernet (RJ-45), 1 (SD up to 2 GB, SDHC up to 32
GB, SDXC up to 64 GB) x Multicardreader, 1 x SIM card slot (), 1 x
SmartCard slot, 1 x USB 2.0 total, 3 x USB 3.0 total, 1 x VGA

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 1.999

VFY:H7200WXP41NL

CELSIUS H920

High-End Workstation Power on-the-Go
Processor, Chipset, Memory

Intel® Core™ i7-3740QM processor (2.7 GHz), 6 MB,
Intel® QM77
4 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch
DVD-RW Dual Double Layer Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000 module
10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

43.9 cm (17.3-inch), LED backlight, (Full HD), Anti-glare display,
1920 x 1080 pixel
NVIDIA® Quadro® K3000M, 2 GB (GDDR5 VRAM)
NVIDIA® Quadro® K3000M#NVIDIA® Quadro® K4000M, 2 / 4 GB
(GDDR5 VRAM)

Dimensions / Weight / Environmental

4.25 kg
417 x 287 x 33/44 mm

Operating system

Win8P lic./ Win7P load / RDVD TWIN-Pack

Interfaces

1 x DC-in, 1 x DisplayPort, 1 x eSATA, 1 (34/54 mm) x ExpressCard
slots, 1 x Audio: out, 1 digital array microphone x Internal
microphones, 1 x Ethernet (RJ-45), 1 (SD up to 2 GB, SDHC up to 32
GB, SDXC up to 64 GB) x Multicardreader, 1 x SIM card slot (), 1 x
SmartCard slot, 3 x USB 2.0 total, 1 x USB 3.0 total, 1 x VGA

Warranty

3 year Bring-in Service

EUP (End User Price):

€ 2.499

VFY:H9200WXP41NL