

Value for You RLP Prijslijst



Januari 2014

FUJITSU DESKTOP PC



FUJITSU NOTEBOOKS



FUJITSU SERVERS



LIFEBOOK Notebooks / STYLISTIC Tablets



LIFEBOOK A512	LIFEBOOK A532	LIFEBOOK U574 Ultrabook™	LIFEBOOK E752	LIFEBOOK E733	LIFEBOOK E733
Your Everyday Partner	Your Essential Partner	Your Ultra-thin Mobile Companion	Your Professional Desktop Replacement	Elegant Design and Functionality without Compromises	Elegant Design and Functionality without Compromises
Processor, Chipset, Memory Intel® Core™ i3-3110M processor (2.4 GHz), 3 MB, Intel® HM75 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM	Processor, Chipset, Memory Intel® Core™ i5-4200M processor Intel® HM76 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM	Processor, Chipset, Memory Intel® Core™ i5-i5-4200U processor 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM	Processor, Chipset, Memory Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® HM76 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM	Processor, Chipset, Memory Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM	Processor, Chipset, Memory Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM
Drives SATA, 5400 rpm, 320 GB, 2.5-inch, S.M.A.R.T. DVD Super Multi	Drives SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T. DVD Super Multi	Drives SSD SATA III, 128 GB, 2.5-inch	Drives SATA, 7200 rpm, 500 GB, 2.5-inch, S.M.A.R.T. DVD Super Multi	Drives SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T. DVD Super Multi	Drives SSHD, 5400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T. DVD Super Multi
Communication, Network Bluetooth: v4.0 + EDR LAN: 10/100/1000 MBit/s Realtek RTL 8111F	Communication, Network Bluetooth: v4.0 + EDR LAN: 10/100/1000 MBit/s Realtek RTL 8111F	Communication, Network WLAN: Intel® Wireless-N 7260 2x2 BGN + BT Bluetooth: Integrated V4.0 + HS LAN: USB to LAN (with USB to LAN adapter)	Communication, Network WLAN: Intel® Centrino® Wireless-N2200 b/g/n Bluetooth: Bluetooth 4.0 LAN: Built-in 10/100/1000 MBit/s Intel® 82579 V	Communication, Network WLAN: Intel® Centrino® Wireless-N2230 b/g/n LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM	Communication, Network WLAN: Intel® Centrino® Wireless-N2230 b/g/n UMTS Modul: Sierra Wireless Gobi 3000 LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM
Display, Grafic 39.6 cm (15.6-inch), TFT, (HD), LED backlight, anti-glare, 1366 x 768 pixel, 300:1 (min), 200 cd Intel® HD Graphics or HD Graphics 3000 (depending on CPU), up to 1695 MB	Display, Grafic 39.6 cm (15.6-inch), TFT, (HD), LED backlight, anti-glare, 1366 x 768 pixel, 300:1 (min), 200 cd Intel® HD Graphics 3000 or 4000 (depending on CPU), up to 1695 MB	Display, Grafic 33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare touchscreen, 1366 x 768 pixel, 220 cd/m ² Intel® HD Graphics 4400	Display, Grafic 39.6 cm (15.6-inch), LED backlight, (HD), Anti-glare display, compound, 1366 x 768 pixel, 300:1, 220 cd/m ² Intel® HD Graphics 4000 with 3rd generation Core i processors	Display, Grafic 33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1 (t.b.d.), 200 cd/m ² Intel® HD Graphics 4000 with 3rd generation Core i processors	Display, Grafic 33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1 (t.b.d.), 200 cd/m ² Intel® HD Graphics 4000 with 3rd generation Core i processors
Keyboard and pointing devices Touchpad, Status LED Keyboard, N/A	Keyboard and pointing devices Touchpad, Status LED Keyboard, N/A	Keyboard and pointing devices Keyboard, Multi gesture touchpad with integrated mouse button functionality	Keyboard and pointing devices Multi gesture touchpad with two mouse buttons, Optional: Fingerprint sensor, Optional: TouchStick, Application buttons Keyboard, N/A	Keyboard and pointing devices Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons, Optional: Fingerprint sensor, Application buttons Keyboard, N/A	Keyboard and pointing devices Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons, Optional: Fingerprint sensor, Application buttons Keyboard, N/A
Power supply Li-Ion battery 6-cell, 4400 mAh, 48 Wh Runtime 1st battery: up to 6 h	Power supply Li-Ion battery 6-cell, 4400 mAh, 48 Wh Runtime 1st battery: Up to 6:20 h (productivity mode)	Power supply Lithium polymer battery 4-cell, 2840 mAh, 48.8 Wh Runtime 1st battery: up to 11 h	Power supply Runtime 1st battery: up to 12 h	Power supply Runtime 1st battery: up to 13 h (tbd)	Power supply Runtime 1st battery: up to 13 h (tbd)
Dimensions / Weight / Environmental 2.5 kg 378 x 252 x 36.5 mm Matt Matte black	Dimensions / Weight / Environmental 2.4 kg 378 x 252 x 34.2 mm Matt Black/Silver	Dimensions / Weight / Environmental Approx. 1.6 kg 322 x 225 x 19.5 mm Aluminum lid Black with red details	Dimensions / Weight / Environmental 2.5 kg 372 x 245 x 35 mm	Dimensions / Weight / Environmental 1.7 kg 321 x 228 x 20 (f) - 27 (r) mm	Dimensions / Weight / Environmental 1.7 kg 321 x 228 x 20 (f) - 27 (r) mm
Operating system Win8Pro+Win7Load	Operating system Win8Pro+Win7Load	Operating system Win8Pro+Win7Load	Operating system Windows 8 Pro	Operating system Windows 8 Pro	Operating system Windows 8 Pro
Interfaces 1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 (34 mm and 54 mm supported) x ExpressCard slots, 1 x HDMI, N/A x , 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x SD-Card Reader (SD/SDHC) x Memory card slots, 3 (1 x Anytime USB Charge functionality) x USB 2.0 total, 1 x VGA, Intel® Centrino® Wireless N2230 (IEEE 802.11b/g/n) x Integrated WLAN	Interfaces 1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 (34 mm) x ExpressCard slots, 1 x HDMI, N/A x , 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x 4in1 Card Reader (SD/SDHC/MS/MS Pro) x Memory card slots, 1 x USB 2.0 total, 3 (1 x Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA, Intel® Centrino® Wireless N2230 (IEEE 802.11b/g/n) x Integrated WLAN	Interfaces 1 (HP/MIC Comb Jack) x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 x HDMI, 1 digital x Internal microphones, 1 x Kensington Lock support, via USB (with USB to LAN adapter - PXE Boot capable) x Ethernet (RJ-45), 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS), 1 (incl. 1x Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0 total, Intel® Centrino Wireless-N7260 a/b/g/n	Interfaces 1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 (V1.1a) x DisplayPort, 1 x Docking connector for Port Replicator, 1 x eSATA & USB combo, 1 (34 / 54 mm supported) x ExpressCard slots, N/A x , 2x digital (array) microphones as option x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, x USB 2.0 total, 2 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA	Interfaces 1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA	Interfaces 1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA
Warranty 1 year Bring-in Service	Warranty 1 year Bring-in Service	Warranty 1 year Bring-in Service	Warranty 1 year Bring-in Service	Warranty 2 year Bring-in Service	Warranty 2 year Bring-in Service
RLP (Recommended List Price): € 449 VFY:A5120M7311NL	RLP (Recommended List Price): € 549 VFY:A5440M7501NL	RLP (Recommended List Price): € 889 VFY:U5740M7512NL	RLP (Recommended List Price): € 779 VFY:E7520M4501NL	RLP (Recommended List Price): € 889 VFY:E7330M55A1NL	RLP (Recommended List Price): € 999 VFY:E7330MXE11NL

LIFEBOOK E743

LIFEBOOK E753

LIFEBOOK U772 Ultrabook™

LIFEBOOK E733

STYLISTIC T902

LIFEBOOK U772 Ultrabook™



Elegant Design and Functionality without Compromises

Processor, Chipset, Memory

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD, 5400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2230 b/g/n
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

35.6 cm (14-inch), LED backlight, (HD+), Anti-glare display, magnesium, 1600 x 900 pixel, 300:1 (t.b.d.), 250 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons,
Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 13 h (tbd)

Dimensions / Weight / Environmental

1.8 kg
338 x 231 x 20 (f) - 27 (r) mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, 1 x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 999

VFY:E7430MXE11NL

Elegant Design and Functionality without Compromises

Processor, Chipset, Memory

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD, 5400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2230 b/g/n
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

39.6 cm (15.6-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1 (t.b.d.), 200 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad (105mmx66mm) with 2 integrated mouse buttons,
Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 13 h (tbd)

Dimensions / Weight / Environmental

2.0 kg
374 x 250 x 20 (f) - 27 (r) mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, 1 x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 999

VFY:E7530MXE11NL

Business Elegance in Style

Processor, Chipset, Memory

Intel® Core™ i5-3337U processor (1.8 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

35.6 cm (14-inch), LED backlight, (HD), Anti-glare frameless display, magnesium, 1366 x 768 pixel, 200:1, 220 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with integrated mouse button functionality, Fingerprint sensor, EcoButton
Keyboard, N/A

Power supply

Runtime 1st battery: Up to 10:00 h

Dimensions / Weight / Environmental

1.4 kg
327 x 225 x 15.6 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 (mini LAN connector, Adapter included) x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 2 (1 with Anytime USB Charge functionality) x USB 3.0 total

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 1.149

VFY:U7720M4501NL

Elegant Design and Functionality without Compromises

Processor, Chipset, Memory

Intel® Core™ i7-3632QM processor (2.2 GHz), 6 MB, Intel® QM77
2 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 256 GB, 2.5-inch
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6235 802.11 a/b/g/n with Bluetooth
UMTS Modul: LTE Sierra Wireless MC7710
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1, 200 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons,
Optional: Fingerprint sensor, Application buttons, Status LED

Power supply

Runtime 1st battery: up to 13 h

Dimensions / Weight / Environmental

1.6 kg
321 x 228 x 20 (f) - 27 (r) mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows®

Interfaces

1 x Audio: line-in / microphone, N/A x , 1 x Audio: line-out / headphone, 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (only for models with integrated 3G/UMTS or 4G/LTE module), 1 (optional) x SmartCard slot, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 1.499

VFY:E7330MXP41NL

Your Excellent Flexible Companion

Processor, Chipset, Memory

Intel® Core™ i5-3340M processor (2.7 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD, 5400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

33.8 cm (13.3-inch), TFT, (HD+), Anti-glare touchscreen, 1600 x 900 pixel, 500:1, 300 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Fingerprint sensor, Launch keys, Application buttons, Tablet Pen, Touchscreen, Multi gesture touchpad with two mouse buttons

Power supply

Li-Ion battery 6-cell, 72 Wh (6.700mAh battery) mAh
Runtime 1st battery: up to 7h 40m

Dimensions / Weight / Environmental

1.89 kg
326 x 244 x 27.1 mm front / 31 mm back (without foot) mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 (1 left side with Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 1.499

VFY:T9020MXE21NL

Business Elegance in Style

Processor, Chipset, Memory

Intel® Core™ i7-3687U processor (2.1 GHz), 4 MB, Intel® QM77
8 GB (1 module(s) 8 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 256 GB, 2.5-inch

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: LTE Sierra Wireless MC7710
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

35.6 cm (14-inch), LED backlight, (HD), Anti-glare frameless display, magnesium, 1366 x 768 pixel, 200:1, 220 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with integrated mouse button functionality, Fingerprint sensor, EcoButton
Keyboard, N/A

Power supply

Runtime 1st battery: Up to 10:00 h

Dimensions / Weight / Environmental

1.4 kg
327 x 225 x 15.6 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 (mini LAN connector, Adapter included) x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 2 (1 with Anytime USB Charge functionality) x USB 3.0 total

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.699

VFY:U7720MXP42NL

STYLISTIC T902

Your Excellent Flexible Companion
Processor, Chipset, Memory

Intel® Core™ i7-3540M processor (3.0 GHz), 4 MB, (), 512 KB, Intel® QM77
2 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 256 GB, 2.5-inch
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

33.8 cm (13.3-inch), TFT, (HD+), Anti-glare touchscreen, 1600 x 900 pixel, 500:1, 300 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Fingerprint sensor, Launch keys, Application buttons, Tablet Pen, Touchscreen, Multi gesture touchpad with two mouse buttons
Keyboard, N/A

Power supply

Li-Ion battery 6-cell, 72 Wh (6.700mAh battery) mAh
Runtime 1st battery: up to 7h 40m

Dimensions / Weight / Environmental

1.89 kg
326 x 244 x 27.1 mm front / 31 mm back (without foot) mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 (1 left side with Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 1.666

VFY:T9020MXP41NL

STYLISTIC M532

Perfect Choice for Business and Private Use
Processor, Chipset, Memory

NVIDIA® Tegra® 3
NVIDIA® Tegra® 3 T30S, Quad-Core ARM Cortex A9, 1.4 GHz

Drives

32GB eMMC flash memory
64GB eMMC flash memory

Communication, Network

AzureWave AW-AH663 802.11 a/b/g/n
2x dual band WLAN, 1x UMTS, 1x GPS
Bluetooth 3.0

Display, Grafic

25.7 cm (10.1-inch), TFT, (WXGA), 1280 x 800 pixel, 800:1, max. 550 cd/m²

Keyboard and pointing devices
Power supply

video playback 8.4 h

Dimensions / Weight / Environmental

560 g
262.6 x 175.4 x 8.6 mm

Operating system

Android 4.0, upgrade to Android 4.1 available

Interfaces

1 x Audio: line-in / line-out, 1 (digital) x Internal microphones, 1 x Micro USB 2.0, 1 x Docking connector for Port Replicator, 1 x SIM card slot, 1 x Memory card slots

Warranty

1 year Collect Return Service

RLP (Recommended List Price):

€ 333

VFY:M53200MPAD11N

STYLISTIC M702

Designed for the toughest businesses
Processor, Chipset, Memory

NVIDIA® Tegra® 3
NVIDIA® Tegra® 3 AP37, Quad-Core ARM Cortex A9, 1 MB, 1.7 GHz

Drives

32GB eMMC 4.4.1 Flash Memory

Communication, Network

Texas Instruments WL1283

Display, Grafic

25.7 cm (10.1-inch), TFT, (WUXGA), 1920 x 1200 pixel, 500:1, max. 300 cd/m²

Keyboard and pointing devices
Power supply

video playback up to 15 h

Dimensions / Weight / Environmental

590 g
259 x 169 x 9.9 mm

Operating system

Android 4.0 (Ice Cream Sandwich)

Interfaces

1 x Audio: line-in / line-out, N/A x , N/A x , 1 (digital) x Internal microphones, 1 x Memory card slots, 1 x Micro USB 2.0, 1 x SIM card slot (Micro-SIM), Texas Instruments WL1283 x Integrated WLAN

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 888

VFY:M7020MPAD11N

STYLISTIC Q572

Your Professional BusinessPad
Processor, Chipset, Memory

AMD A68M FCH

Drives

mSATA, 128 GB, FDE

Communication, Network

UMTS Modul: Sierra Wireless Gobi 3000
10/100 Mbit/s (via cradle only)

Display, Grafic

AMD Radeon™ HD 6250

Keyboard and pointing devices
Power supply

video playback up to 15 h

Dimensions / Weight / Environmental

0.732 kg
273.5 x 176 x 13.9 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2 (digital) x Internal microphones, 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 x USB 2.0 total

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 999

VFY:Q5720M3001NL

STYLISTIC Q702

Attach or Touch - The Hybrid Business Talent
Processor, Chipset, Memory

Intel® Core™ iCore i3-3227U processor
Intel® QM77

Drives

SSD mSATA, 128 GB

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices
Power supply

video playback up to 15 h

Dimensions / Weight / Environmental

0.850 kg
302 x 195 x 12.7 mm

Operating system

Windows 8.1 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2 (digital) x Internal microphones, 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 1 x USB 3.0 total

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 1.169

VFY:Q7020M7351NL

ESPRIMO P410 E85+	ESPRIMO E420 E85+	ESPRIMO P420 E85+	ESPRIMO P420 E85+	ESPRIMO Q520
-------------------	-------------------	-------------------	-------------------	--------------



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Pentium® processor G2020 (2.90 GHz), 3 MB, Intel® H61
2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 250 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Operating system

Win8Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 329

VFY:P0410P5211NL



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Core™ i3-4130 processor (3.40 GHz), 3 MB, Intel® H81
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

9 kg
330 x 405 x 104 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 449

VFY:E0420P7321NL



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Core™ i3-4130 processor (3.40 GHz), 3 MB, Intel® H81
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 449

VFY:P0420P7321NL



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Core™ i5-4440 processor (3.10 GHz), 6 MB, Intel® H81
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 499

VFY:P0420P7511NL



The Mini with More PC per cm

Processor, Chipset, Memory

Intel® Core™ i3-4130T processor (2.90 GHz), 3 MB, Intel® H81
4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO

DIMM

Drives

HDD SATA II, 5400 rpm, 500 GB, 2.5-inch
DVD Super Multi Slot-in slim

Communication, Network

Bluetooth: 1 (optional)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

1.6 kg
185 x 188 x 54 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 (DVI-I) x DVI, 2x 2.0 x USB front, 1 x HDMI, 1 x Kensington Lock, support, 1 x Ethernet (RJ-45), 1 x Multicardreader, 6 x USB 2.0 total, 4x 2.0 x USB rear, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 539

VFY:Q0520P7311NL

ESPRIMO E520 E85+	ESPRIMO P520 E85+	ESPRIMO C720	ESPRIMO E720 E90+	ESPRIMO P720 E90+
--------------------------	--------------------------	---------------------	--------------------------	--------------------------



Your Flexible and Economic PC

Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB Intel® B85
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
330 x 405 x 104 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0 x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0/ 2x 3.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 549

VFY:E0520P7551NL



Your Flexible and Economic PC

Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® B85
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
175 x 425 x 353 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0 x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0/ 2x 3.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 549

VFY:P0520P7551NL



Your Ultra Small Form Factor PC

Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q85
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD SuperMulti SATA slim

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

9 kg
265 x 315 x 88 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, N/A x , 1 x DisplayPort, 1 (DVI-I) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 2 x Serial (RS-232) (powered, 9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 649

VFY:C0720P7501NL



Combines High Efficiency with Manageability

Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q85
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
340 x 382 x 98 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 649

VFY:E0720P7501NL



Excellent Performance, Expandability and Efficiency

Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q85
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 649

VFY:P0720P7501NL

ESPRIMO E920 0-Watt

The Innovative 0-Watt PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q87
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
340 x 382 x 98 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 699

VFY:E0920PXG11NL

ESPRIMO P920 0-Watt

The Innovative 0-Watt PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q87
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 699

VFY:P0920PXG21NL

ESPRIMO Q920

The Mini with More PC per cm³
Processor, Chipset, Memory

Intel® Core™ i5-4570T processor (2.90 GHz), 4 MB, Intel® Q87
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch
DVD Super Multi Slot-in slim

Communication, Network

Bluetooth: 1 (optional with WLAN together)
LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

1.6 kg
185 x 188 x 54 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DisplayPort, 1 (DVI-I) x DVI, 2x 3.0 x USB front, N/A x , 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD, MMC) x Multicardreader, 2 x USB 2.0 total, 2x 2.0 and 2x 3.0 x USB rear, 4 x USB 3.0 total, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional with Bluetooth together) x Integrated WLAN

Slots, Bays

1 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 799

VFY:Q0920PXP11NL

ESPRIMO X913

Evolutionary PC for the Modern Office
Processor, Chipset, Memory

Intel® Core™ i5-3470T processor (2.90 GHz), 3 MB, Intel® Q77
4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

HDD SATA II, 5400 rpm, 500 GB, 2.5-inch

Communication, Network

Bluetooth: 1 (optional with WLAN module)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics Intel® HD Graphics 2000 Intel® HD Graphics 2500, up to 1759 MB

Dimensions / Weight / Environmental

5.94 kg
554 x 225 x 433 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DVI, N/A x , optional with camera module x Internal microphones, 2 x Kensington Lock support, 1 x Ethernet (RJ-45), 2 x USB 2.0 total, 2x2.0 2x3.0 x USB rear, 4 x USB 3.0 total, 2x3.0 x USB left side, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

0 x 2.5-inch bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 949

VFY:X9130P7511NL

ESPRIMO X913-T

Evolutionary PC for the Modern Office
Processor, Chipset, Memory

Intel® Core™ i5-3470T processor (2.90 GHz), 3 MB, Intel® Q77
2 x 2 GB (1 module(s) 2 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch

Communication, Network

Bluetooth: 1 (optional with WLAN module)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics#Intel® HD Graphics 2000#Intel® HD Graphics 2500, up to 1759 MB

Dimensions / Weight / Environmental

8.62 kg
533 x 224 x 419 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DVI, N/A x , optional with camera module x Internal microphones, 2 x Kensington Lock support, 1 x Ethernet (RJ-45), 2 x USB 2.0 total, 2x2.0 2x3.0 x USB rear, 4 x USB 3.0 total, 2x3.0 x USB left side, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

0 x 2.5-inch bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.099

VFY:X9130P7511NL

ESPRIMO P920 E90+



Excellent Performance, Expandability And Efficiency

Processor, Chipset, Memory

Intel® Core™ i7-4770 processor (3.40 GHz), 8 MB,

Intel® Q87

2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

SSHD SATA III, 7200 rpm, 1000 GB, 3.5-inch

MultiCard Reader 24in1 USB 2.0 3.5"

DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

AMD® Radeon R9 255 FH 2GB, Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

11 kg

175 x 419 x 395 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.099

VFY:P0920PXP51NL

FUTRO Thin Clients



FUTRO S700



De betaalbare Thin Client

Processor, Chipset, Memory

AMD A55E Controller Hub
2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM

Drives

mSATA, 2 GB, Flash drive

Communication, Network

LAN: Built-in 10/100/1000 MBit/s

Display, Graphics

ATI Radeon™ HD 6250 , up to 256 MB

Dimensions / Weight / Environmental

1,2 kg
97 x 191 x 266 mm

Operating system

eLux® RL - Embedded Linux

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, 1 x DC-in, 1 DP x DisplayPort,
1 DVI-I (integrated VGA can be used with DVI-VGA adapter) x DVI,
1 x Front audio: headphone, 1 x Front audio: line-in / microphone,
2 x USB front, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 2
x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, 2 x USB
internal

Warranty

2 year Bring-in Service

FUTRO S700



De betaalbare Thin Client

Processor, Chipset, Memory

AMD A55E Controller Hub
2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM

Drives

mSATA, 4 GB, Flash drive

Communication, Network

LAN: Built-in 10/100/1000 MBit/s

Display, Graphics

ATI Radeon™ HD 6250 , up to 256 MB

Dimensions / Weight / Environmental

1,2 kg
97 x 191 x 266 mm

Operating system

Windows® Embedded Standard 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, 1 x DC-in, 1 DP x DisplayPort,
1 DVI-I (integrated VGA can be used with DVI-VGA adapter) x DVI,
1 x Front audio: headphone, 1 x Front audio: line-in / microphone,
2 x USB front, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 2
x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, 2 x USB
internal

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 299

VFY:S0700PF045NL/End-of-Life

RLP (Recommended List Price):

€ 349

VFY:S0700PX011NL/End-of-Life

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1220v2# (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 500 GB, 3.5-inch, economic DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

RLP (Recommended List Price):

€ 549

VFY:T1003SC070IN

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1220v2# (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202
8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 500 GB, 3.5-inch, economic DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 (mech x4)
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9, 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

RLP (Recommended List Price):

€ 630

VFY:T1003SC140IN

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1230v2# (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 1 TB, 3.5-inch, business critical DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

RLP (Recommended List Price):

€ 849

VFY:T1003SC090IN

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1230v2# (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202
8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 2 TB, 3.5-inch, business critical DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

RLP (Recommended List Price):

€ 970

VFY:T1003SC160IN

PRIMERGY TX140 S2

Expandable SME all-round server

The Fujitsu Server PRIMERGY TX140 S2 is the ideal, robust and cost-efficient server for SMBs or branch offices. It not only scores with the best Intel® Xeon® E3 performance and solid expandability thanks to hot-plug hard disks, but also with its optionally redundant power supply and full server management support. The PRIMERGY TX140 S2: an excellent long-term investment.

Processor, Chipset, Memory

Intel® Xeon® processor E3-1220v3# (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 80 W)
Intel® C224
8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D3239

Drives, Controller

DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 (mech x4)
1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA
3 x 5.25/1.6-inch

Dimensions / Weight / Environmental

483 x 495 x 175 mm
177 x 560 x 455 mm

Rack: 12.5kg - 20kg; Tower: 15kg - 23 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 11, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

6 , 1 serial RS-232-C, usable for iRMC or system or shared,
1 analog graphics interface derived from iRMC (up to 1600x1200 or 1920x1080 at 16bpp),
1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s),
Management LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

RLP (Recommended List Price):

€ 880

VFY:T1402SC040IN

PRIMERGY TX150 S8

The one-processor tower server - maximized!

The PRIMERGY TX150 S8: the right system for SMEs, branch offices or virtualized environments where the main focus is on expandability and availability. With processors of the Intel® Xeon® E5-1400 and E5-2400 family, the TX150 S8 delivers excellent energy-efficient performance. PRIMERGY TX150 S8: the one processor tower server – maximized!

Processor, Chipset, Memory

Intel® Xeon® processor E5-2420# (6C/12T, 1.90 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® C602

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3079

Drives, Controller

DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

483 x 611 x 177 mm
177 x 651 x 456 mm

16 - 29 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 x USB 2.0 (2x front, 4x rear, 3x internal for backup, UFM and internal USB), 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

RLP (Recommended List Price):

€ 1.099

VFY:T1508SC040IN

PRIMERGY TX200 S7

Well-balanced price- performance

The PRIMERGY TX200 S7 is a perfect server for SMEs, branch offices or virtualized infrastructures. The tower server offers dual processor performance combined with expandability and energy efficiency. Its feature set makes the TX200 S7 a great virtualization, database or communication server. The PRIMERGY TX200 S7 strikes the right balance between price and performance.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2420# (6C/12T, 1.90 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® C602

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3099

Drives, Controller

DVD Super Multi, half height, SATA I
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu
512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

..483 x 611 x 177 mm
..177 x 651 x 456 mm

..16 kg - 29 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet (Intel Hartwell), 9 x USB 2.0 (2 x front USB, 4 x rear USB 3 x internal for backup, UFM and internal USB), 1 x serial RS-232-C (9 pin), usable for iRMC S3 or system or common use, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

3 years
On-site Service

RLP (Recommended List Price):

€ 1.449

VFY:T2007SC040IN

PRIMERGY TX300 S8

Reliable performance for your business

The FUJITSU Server PRIMERGY TX300 S8 offers maximum performance, best expandability and highest availability without any compromises. Branches, data centers and SMEs value the performance of the two Intel® Xeon® E5 v2 processors, 1536 GB RAM and GPU card support. 10 extension slots and the redundant power supply enable top availability levels and excellent expandability options. The server is thus ideal for computing-intensive applications.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2620v2# (6C/12T, 2.10 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1600 MHz, 80 W)
Intel® C602

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D2949

Drives, Controller

DVD Super Multi, half height, SATA I
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS
6G 5/6 512MB (D2616), 8 ports int.#RAID level:
0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA
3 x 5.25/1.6-inch

Dimensions / Weight / Environmental

177 x 777 x 456 mm

up to 35 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 11, vSphere 4.1, vSphere 4.1 Embedded, vSphere 4.1 Installable, vSphere 5.0 Embedded, vSphere 5.0, vSphere 5.5 Embedded, vSphere 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Hyper-V Server 2012, WindowsServer® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

x Gbit/s Ethernet, 10 , 1 x serial RS-232-C, usable for iRMC S3 or system or shared, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s), Management LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

3 years
On-site Service

RLP (Recommended List Price):

€ 1.880

VFY:T3008SC010IN

PRIMERGY RX100 S7



Small in size and low in cost – rich in optional features

The Fujitsu PRIMERGY RX100 S7 is an entry mono socket rack server designed to meet small budgets by delivering highest energy efficiency of its class and a rich set of optional expansions to meet individual demands. Optimized for infrastructure and communication applications, this 1U server delivers up to 32GB RAM, up to 3 PCIe slots and up to 4 hard disk drives.

Processor, Chipset, Memory

Intel® Xeon® processor E3-1230v2# (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202

2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3034

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 (mech x4)
1 x PCI-Express 2.0 x4 (mech. x8)
4x 2.5-inch hot-plug SAS/SATA or 2x 3.5-inch hot-plug SAS/SATA
1 x 5.25/0.5-inch for CD-RW/DVD#1 x 3.5/0.5-inch for ServerView Local Service Panel or front VGA + front Service LAN

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 431mm (Body) x 572 x 42.5 mm
up to 14 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, vSphere™ 5.0 Embedded, vSphere™ 5.0, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 7 , 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA (15-pin), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Management LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

RPL (Recommended List Price):

€ 1.030

VFY:R1007SC0801N

PRIMERGY RX200 S8



Maximum productivity in a 1U housing

The Fujitsu Server PRIMERGY RX200 S8 is a rack server that provides high performance of the new Intel® Xeon® E5 product family, expandability up to 1536 GB of memory and up to 96% energy efficiency - all in 1U space saving housing. Thus, the PRIMERGY RX200 S8 is ideal for virtualization and cloud, small databases as well as for high performance computing.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2620v2# (6C/12T, 2.10 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1600 MHz, 80 W)
Intel® C600 (Intel® Patsburg A)

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D3332

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

4 x 2.5-inch base unit or 8 x 2.5-inch base unit
1 x 5.25/0.5-inch for DVD-RW/Blu-ray (only for base unit 4x 2.5-inch HDD)

Dimensions / Weight / Environmental

482 mm (Bezel) / 431mm (Body) x 762 mm x 43 mm
up to 18 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Windows Server® 2012 R2 Essentials, Windows Server® 2012 R2 Foundation, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

6 , 1 x optional, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s), Management LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

3 years
On-site Service

RPL (Recommended List Price):

€ 1.590

VFY:R2008SC0101N

PRIMERGY R300 S8



The versatile 2U powerhouse

The Fujitsu Server PRIMERGY RX300 S8 is a 2U dual socket rack server, optimized for all types of business applications by focusing on versatility and scalability that supports up to 16 harddisk drives, up to 7 PCIe Gen 3 cards and up to 1536 GB RAM. Thanks to top performance of the new Intel® Xeon® E5 product family and the available upgrade kits, the RX300 will also ensure the demands of tomorrow are met.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2620v2# (6C/12T, 2.10 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1600 MHz, 80 W)
Intel® C600 (Intel® Patsburg A)

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D2939

Drives, Controller

DVD Super Multi, slimline, SATA I
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int.#RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

2.5-inch base unit (max. 16 x 2.5) or 3.5-inch base unit (max. 6 x 3.5)
1 x 5.25/0.5-inch for ODD#1 x 5.25/0.5-inch for Local Service Display
#1 x 3.5/1.6-inch for backup devices#1 x 5.25/1.6-inch for backup devices

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 445mm (Body) x 770 x 86.9 mm
up to 25 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 11, vSphere™ 5.0 Embedded, vSphere™ 5.0, vSphere™ 5.5 Embedded, vSphere™ 5.5, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 R2 Datacenter, Hyper-V Server R2 2012, Windows Server® 2012 R2 Standard, Windows Storage Server 2012 R2 Standard, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

6 , 1 x optional, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s), Management LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

3 years
On-site Service

RPL (Recommended List Price):

€ 2.160

VFY:R3008SC0301N

or optional Modular LAN 2x10 Gbit controller, Front Service LAN port as option

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB,
Intel® C226
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

NVIDIA® Quadro® 410, 512 MB
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 755

VFY:W5300WXE11NL

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Core™ i5-4670 processor (3.40 GHz), 6 MB,
Intel® C226
8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

AMD FirePro™ V3900, 1 GB
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 833

VFY:W5300WXG11NL

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Xeon® processor E3-1245v3 (3.40 GHz), 8 MB,
Intel® C226
8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III Premium, 128 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

NVIDIA® Quadro® K600, 1 GB
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.099

VFY:W5300W6881NL

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Xeon® processor E3-1270v3 (3.50 GHz), 8 MB,
Intel® C226
8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III Premium, 128 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

NVIDIA® Quadro® K2000, 2 GB
DP to DVI-D (single link) Adapter Cable
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.499

VFY:W5300WXP11NL

CELSIUS M720	CELSIUS M720	CELSIUS R920	CELSIUS H720	CELSIUS H920
--------------	--------------	--------------	--------------	--------------



Your "Thoroughbred" Workstation

Processor, Chipset, Memory

Intel® Xeon® processor E5-1620 (3.60 GHz), 10 MB, Intel® C602
4 x 2 GB (1 module(s) 2 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Graphics

AMD FirePro™ V4900, 1 GB

Dimensions / Weight / Environmental

18 kg
186 x 481 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x Audio: in, 1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 1 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.249

VFY:M7200WXG11NL



Your "Thoroughbred" Workstation

Processor, Chipset, Memory

Intel® Xeon® processor E5-1620 (3.60 GHz), 10 MB, Intel® C602
4 x 4 GB (1 module(s) 4 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III, 128 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Graphics

DP to DVI-D (single link) Adapter Cable
NVIDIA® Quadro® K2000, 2 GB

Dimensions / Weight / Environmental

18 kg
186 x 481 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x Audio: in, 1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 1 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.799

VFY:M7200WXP21NL



Uncompromising Workstation Performance for Extreme Requirements

Processor, Chipset, Memory

Intel® Xeon® processor E5-2640 (2.50 GHz), 15 MB, 7.2 GT/s Intel® C602
4 x 4 GB (1 module(s) 4 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III, 256 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 2x Built-in 10/100/1000 MBit/s Intel® 82579 LM and Intel®

Display, Graphics

No graphics in system

Dimensions / Weight / Environmental

20 kg
186 x 618 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x eSATA, 1 x Audio: in, 1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 2 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 2.999

VFY:R9200WXP41NL



Workstation Power on-the-Go

Processor, Chipset, Memory

Intel® Core™ i7-3740QM processor (2.7 GHz), 6 MB, Intel® QM77
2 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 256 GB, 2.5-inch
DVD-RW Dual Double Layer Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000 module
10/100/1000 MBit/s Intel® 82579 LM

Display, Gratic

39.6 cm (15.6-inch), LED backlight, (Full HD), Anti-glare display, magnesium, 1920 x 1080 pixel, 300:1, 220 cd/m
NVIDIA® Quadro® K1000M#NVIDIA® Quadro® K2000M, 2 GB (GDDR3 VRAM)

Dimensions / Weight / Environmental

2.8 kg
379.8 x 257.0 x 35.5 mm

Operating system

Win8P lic./ Win7P load / RDVD TWIN-Pack

Interfaces

1 x DC-in, 1 x DisplayPort, 1 x eSATA, 1 (34 mm) x ExpressCard slots, 1 x Audio: in, 1 x Audio: out, 2 digital array microphones x Internal microphones, 1 x Ethernet (RJ-45), 1 (SD up to 2 GB, SDHC up to 32 GB, SDXC up to 64 GB) x Multicardreader, 1 x SIM card slot (), 1 x SmartCard slot, 1 x USB 2.0 total, 3 x USB 3.0 total, 1 x VGA

RLP (Recommended List Price):

€ 1.999

VFY:H7200WXP41NL



High-End Workstation Power on-the-Go

Processor, Chipset, Memory

Intel® Core™ i7-3740QM processor (2.7 GHz), 6 MB, Intel® QM77
4 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch
DVD-RW Dual Double Layer Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000 module
10/100/1000 MBit/s Intel® 82579 LM

Display, Gratic

43.9 cm (17.3-inch), LED backlight, (Full HD), Anti-glare display, 1920 x 1080 pixel
NVIDIA® Quadro® K3000M, 2 GB (GDDR5 VRAM)
NVIDIA® Quadro® K3000M#NVIDIA® Quadro® K4000M, 2 / 4 GB (GDDR5 VRAM)

Dimensions / Weight / Environmental

4.25 kg
417 x 287 x 33/44 mm

Operating system

Win8P lic./ Win7P load / RDVD TWIN-Pack

Interfaces

1 x DC-in, 1 x DisplayPort, 1 x eSATA, 1 (34/54 mm) x ExpressCard slots, 1 x Audio: out, 1 digital array microphone x Internal microphones, 1 x Ethernet (RJ-45), 1 (SD up to 2 GB, SDHC up to 32 GB, SDXC up to 64 GB) x Multicardreader, 1 x SIM card slot (), 1 x SmartCard slot, 3 x USB 2.0 total, 1 x USB 3.0 total, 1 x VGA

RLP (Recommended List Price):

€ 2.499

VFY:H9200WXP41NL