

Value for You Prijzlijst



Februari 2013

FUJITSU DESKTOP PC



FUJITSU NOTEBOOKS



FUJITSU SERVERS



LIFEBOOK A512



Your Everyday Partner

Processor, Chipset, Memory

Intel® Core™ i3-2328M processor (2.2 GHz), 3 MB,
Intel® HM75
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 5400 rpm, 320 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

Bluetooth: v4.0 + EDR
LAN: 10/100/1000 MBit/s Realtek RTL 8111F

Display, Grafic

39.6 cm (15.6-inch), TFT, (HD), LED backlight, anti-glare, 1366 x
768 pixel, 300:1 (min), 200 cd
Intel® HD Graphics or HD Graphics 3000 (depending on CPU), up to
1695 MB

Keyboard and pointing devices

Touchpad, Status LED
Keyboard, N/A

Power supply

Li-Ion battery 6-cell, 4400 mAh, 48 Wh
Runtime 1st battery: up to 6 h

Dimensions / Weight / Environmental

2.5 kg
378 x 252 x 36.5 mm
Matt Matte black

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone,
1 x DC-in, 1 (34 mm and 54 mm supported) x ExpressCard slots,
1 x HDMI, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x
SD-Card Reader (SD/SDHC) x Memory card slots, 3 (1 x Anytime
USB Charge functionality) x USB 2.0 total, 1 x VGA, Intel® Centrino®
Wireless N2230 (IEEE 802.11b/g/n) x Integrated WLAN

Warranty

1 year Bring-in Service

€ 439

VFY:A5120M3311NL

LIFEBOOK A532



Your Essential Partner

Processor, Chipset, Memory

Intel® Core™ i5-3210M processor (2.5 GHz), 3 MB,
Intel® HM76
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

Bluetooth: v4.0 + EDR
LAN: 10/100/1000 MBit/s Realtek RTL 8111F

Display, Grafic

39.6 cm (15.6-inch), TFT, (HD), LED backlight, anti-glare, 1366 x
768 pixel, 300:1 (min), 200 cd
Intel® HD Graphics 3000 or 4000 (depending on CPU), up to 1695
MB

Keyboard and pointing devices

Touchpad, Status LED
Keyboard, N/A

Power supply

Li-Ion battery 6-cell, 4400 mAh, 48 Wh
Runtime 1st battery: Up to 6:20 h (productivity mode)

Dimensions / Weight / Environmental

2.4 kg
378 x 252 x 34.2 mm
Matt Black/silver

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1
x DC-in, 1 (34 mm) x ExpressCard slots, 1 x HDMI, 1 x Kensington
Lock support, 1 x Ethernet (RJ-45), 1 x 4in1 Card Reader (SD/SDHC/
MS/MS Pro) x Memory card slots, 1 x USB 2.0 total, 3 (1 x Anytime
USB Charge functionality) x USB 3.0 total, 1 x VGA, Intel® Centrino®
Wireless N2230 (IEEE 802.11b/g/n) x Integrated WLAN

Warranty

1 year Bring-in Service

€ 589

VFY:A5320M3501NL

LIFEBOOK AH552/SL



Your Elegant Essential Partner

Processor, Chipset, Memory

Intel® Core™ i5-3210M processor (2.5 GHz), 3 MB,
Intel® HM76
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

Bluetooth: v4.0 + EDR
LAN: 10/100/1000 MBit/s Realtek RTL 8111F

Display, Grafic

39.6 cm (15.6-inch), TFT, (HD), LED backlight, glossy, 1366 x 768
pixel
Intel® HD Graphics 3000 or 4000 (depending on CPU), up to 1695
MB

Keyboard and pointing devices

Touchpad, Status LED
Keyboard, N/A

Power supply

Li-Ion battery 6-cell, 4400 mAh, 48 Wh
Runtime 1st battery: tbc

Dimensions / Weight / Environmental

2.2 kg
378 x 252 x 25.4 mm
Aluminum lid Black

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x
DC-in, 1 x HDMI, 1 x Kensington Lock support, 1 x Ethernet (RJ-45),
1 x 4in1 Card Reader (SD/SDHC/MS/MS Pro) x Memory card slots,
3 x USB 2.0 total, 1 (Anytime USB Charge functionality) x USB 3.0
total, 1 x VGA, Intel® Centrino® Wireless N2230 (IEEE 802.11b/g/n)
x Integrated WLAN

Warranty

1 year Bring-in Service

€ 629

VFY:AH552M3501NL

LIFEBOOK N532



Boost uw multimedia prestaties

Processor, Chipset, Memory

Intel® Core™ i5-3210M processor (2.5 GHz), 3 MB,
Intel® HM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Integrated V4.0 + HS
LAN: 10/100/1000 MBit/s

Display, Grafic

43.9 cm (17.3-inch), LED backlight, (HD+), Anti-glare display, 1600
x 900 pixel, 220 cd/m
NVIDIA® GeForce® GT 620M, 1 GB (DDR3 VRAM)

Keyboard and pointing devices

Touchpad, Status LED
Keyboard, N/A

Power supply

Li-Ion battery 6-cell, 5200 mAh, 57 Wh
Runtime 1st battery: up to 7 hours

Dimensions / Weight / Environmental

Approx. 3.0 kg
410 x 270 x 20.4 (front) / 35 (back) mm
Black/antracite

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x DC-in, 1 (34 / 54 mm) x
ExpressCard slots, 1 x HDMI, 1 (digital) x Internal microphones, 1 x
Kensington Lock support, 1 x Ethernet (RJ-45), 1 x 4in1 Card Reader
(SD/SDHC/MS/MS Pro) x Memory card slots, 1 x SIM card slot (usable
only with 3G/UMTS), 1 (incl. 1x eSATA/USB combo) x USB 2.0 total,
3 (incl. 1x Anytime USB Charge functionality) x USB 3.0 total, 1 x
VGA

Warranty

1 year Bring-in Service

€ 669

VFY:N5320M3501NL

LIFEBOOK E752



Your Professional Desktop Replacement

Processor, Chipset, Memory

Intel® Core™ i3-2328M processor (2.2 GHz), 3 MB,
Intel® HM76
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 5400 rpm, 320 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 V

Display, Grafic

39.6 cm (15.6-inch), LED backlight, (HD), Anti-glare display,
compound, 1366 x 768 pixel, 300:1, 220 cd/m
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with two mouse buttons, Optional:
Fingerprint sensor, Optional: TouchStick, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 12 h

Dimensions / Weight / Environmental

2.5 kg
372 x 245 x 35 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone,
1 x DC-in, 1 (V1.1a) x DisplayPort, 1 x Docking connector for Port
Replicator, 1 x eSATA & USB combo, 1 (34 / 54 mm supported)
x ExpressCard slots, 2x digital (array) microphones as option x
Internal microphones, 1 x Kensington Lock support, 1 x Ethernet
(RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB,
MS Pro, MS Pro Duo) x Memory card slots, 1 (optional) x Modem
(RJ-11), 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x
SmartCard slot, 2 (1x with Anytime USB Charge functionality) x USB
2.0 total, 2 x USB 3.0 total, 1 x VGA

Warranty

1 year Bring-in Service

€ 719

VFY:E7520M3301NL

LIFEBOOK E752



Your Professional Desktop Replacement

Processor, Chipset, Memory

Intel® Core™ i5-3210M processor (2.5 GHz), 3 MB,
Intel® HM76
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 7200 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 V

Display, Grafic

39.6 cm (15.6-inch), LED backlight, (HD), Anti-glare display,
compound, 1366 x 768 pixel, 300:1, 220 cd/m
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with two mouse buttons, Optional:
Fingerprint sensor, Optional: TouchStick, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 12 h

Dimensions / Weight / Environmental

2.5 kg
372 x 245 x 35 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone,
1 x DC-in, 1 (V1.1a) x DisplayPort, 1 x Docking connector for Port
Replicator, 1 x eSATA & USB combo, 1 (34 / 54 mm supported)
x ExpressCard slots, 2x digital (array) microphones as option x
Internal microphones, 1 x Kensington Lock support, 1 x Ethernet
(RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB,
MS Pro, MS Pro Duo) x Memory card slots, 1 (optional) x Modem
(RJ-11), 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x
SmartCard slot, 2 (1x with Anytime USB Charge functionality) x USB
2.0 total, 2 x USB 3.0 total, 1 x VGA

Warranty

1 year Bring-in Service

€ 779

VFY:E7520M3501NL

LIFEBOOK E782

Your Comprehensive Top Performer
Processor, Chipset, Memory

Intel® Core™ i5-3320M processor (2.6 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 7200 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

39.6 cm (15.6-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1, 220 cd/m
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with two mouse buttons, Optional: Fingerprint sensor, Optional: TouchStick, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 12 h

Dimensions / Weight / Environmental

2.4 kg
372 x 245 x 35 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 (V1.1a) x DisplayPort, 1 x Docking connector for Port Replicator, 1 x eSATA & USB combo, 1 (34 / 54 mm supported) x ExpressCard slots, 2x digital (array) microphones as option x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB, MS Pro, MS Pro Duo) x Memory card slots, 1 (optional) x Modem (RJ-11), 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 (1x with Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

€ 889

VFY:E7820MXP31NL

LIFEBOOK S762

Boundless Mobility on the Road
Processor, Chipset, Memory

Intel® Core™ i5-3210M processor (2.5 GHz), 3 MB, Intel® HM76
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 7200 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 V

Display, Grafic

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, compound, 1366 x 768 pixel, 300:1, 200 cd/m
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi-gesture touchpad with two mouse buttons and ergonomic ScrollWheel, Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 12 h

Dimensions / Weight / Environmental

1.8 kg
321 x 228 x 27.1-35.5 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 (V1.1a) x DisplayPort, 1 x Docking connector for Port Replicator, 1 x eSATA & USB combo, 1 (34mm/54mm supported, optional, not in combination with SmartCard Reader and SSD cache module) x ExpressCard slots, 1x digital microphone as option x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 (optional) x Modem (RJ-11), 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional, not in combination with Express Card and SSD cache module) x SmartCard slot, 1 x USB 2.0 total, 2 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

1 year Bring-in Service

€ 899

VFY:S7620M3501NL

LIFEBOOK E782

Your Comprehensive Top Performer
Processor, Chipset, Memory

Intel® Core™ i7-3632QM processor (2.2 GHz), 6 MB, Intel® QM77
2 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch
DVD Super Multi
2nd battery

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: LTE Sierra Wireless MC7710
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

39.6 cm (15.6-inch), LED backlight, (HD+), Anti-glare display, magnesium, 1600 x 900 pixel, 300:1, 220 cd/m
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with two mouse buttons, Optional: Fingerprint sensor, Optional: TouchStick, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 12 h

Dimensions / Weight / Environmental

2.4 kg
372 x 245 x 35 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 (V1.1a) x DisplayPort, 1 x Docking connector for Port Replicator, 1 x eSATA & USB combo, 1 (34 / 54 mm supported) x ExpressCard slots, 2x digital (array) microphones as option x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB, MS Pro, MS Pro Duo) x Memory card slots, 1 (optional) x Modem (RJ-11), 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 (1x with Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

€ 1.399

VFY:E7820MXP31NL

LIFEBOOK S792

Solid Mobility on the Road
Processor, Chipset, Memory

Intel® Core™ i7-3632QM processor (2.2 GHz), 6 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch
DVD Super Multi
2nd battery

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: LTE Sierra Wireless MC7710
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1, 300 cd/m
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi-gesture touchpad with two mouse buttons and ergonomic ScrollWheel, Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 12 h

Dimensions / Weight / Environmental

1.6 kg
321 x 228 x 24.7-31.9 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 (V1.1a) x DisplayPort, 1 x Docking connector for Port Replicator, 1 x eSATA & USB combo, 1 (34mm/54mm supported, optional, not in combination with SmartCard Reader and SSD cache module) x ExpressCard slots, 1x digital microphone as option x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 (optional) x Modem (RJ-11), 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional, not in combination with Express Card and SSD cache module) x SmartCard slot, 1 x USB 2.0 total, 2 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

€ 1.699

VFY:S7920MXP31NL

LIFEBOOK U772 Ultrabook™

Business Elegance in Style
Processor, Chipset, Memory

Intel® Core™ i5-3317U processor (1.7 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

35.6 cm (14-inch), LED backlight, (HD), Anti-glare frameless display, magnesium, 1366 x 768 pixel, 300:1, 220 cd/m
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with integrated mouse button functionality, Fingerprint sensor, EcoButton
Keyboard, N/A

Power supply

Runtime 1st battery: Up to 10:00 h

Dimensions / Weight / Environmental

1.4 kg
327 x 225 x 15.6 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-out / headphone, 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 (mini LAN connector, Adapter included) x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 2 (1 with Anytime USB Charge functionality) x USB 3.0 total

Warranty

2 year Bring-in Service

€ 1.149

VFY:U7720M3501NL

LIFEBOOK U772 Ultrabook™

Business Elegance in Style
Processor, Chipset, Memory

Intel® Core™ i7-3667U processor (2.0 GHz), 4 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 256 GB, 2.5-inch

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: LTE Sierra Wireless MC7710
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

35.6 cm (14-inch), LED backlight, (HD), Anti-glare frameless display, magnesium, 1366 x 768 pixel, 300:1, 220 cd/m
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with integrated mouse button functionality, Fingerprint sensor, EcoButton
Keyboard, N/A

Power supply

Runtime 1st battery: Up to 10:00 h

Dimensions / Weight / Environmental

1.4 kg
327 x 225 x 15.6 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-out / headphone, 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 (mini LAN connector, Adapter included) x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 2 (1 with Anytime USB Charge functionality) x USB 3.0 total

Warranty

2 year Bring-in Service

€ 1.699

VFY:U7720MXP32NL

STYLISTIC Q572

Your Professional BusinessPad

Processor, Chipset, Memory
AMD A68M FCH

Drives
mSATA, 128 GB, FDE

Communication, Network
UMTS Modul: Sierra Wireless Gobi 3000
10/100 Mbit/s (via cradle only)

Display, Grafic
AMD Radeon™ HD 6250

Keyboard and pointing devices

Dimensions / Weight / Environmental
0.732 kg
273.5 x 176 x 13.9 mm

Operating system
Windows 8 Pro

Interfaces
1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone,
1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2
(digital) x Internal microphones, 1 x Memory card slots, 1 x SIM card
slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 x
USB 2.0 total

Warranty
2 year Bring-in Service

€ 999
VFY:Q5720M3001NL

STYLISTIC Q702

Attach or Touch - The Hybrid Business Talent

Processor, Chipset, Memory
Intel® Core™ i5-3427U processor (1.8 GHz), 3 MB,
Intel® QM77

Drives
mSATA, 256 GB

Communication, Network
WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: LTE Sierra Wireless MC7710
Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Dimensions / Weight / Environmental
0.850 kg
302 x 195 x 12.7 mm

Operating system
Windows 8 Pro

Interfaces
1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone,
1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2
(digital) x Internal microphones, 1 x Memory card slots, 1 x SIM card
slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 1 x USB
3.0 total

Warranty
2 year Bring-in Service

€ 1.699
VFY:Q7020MXP31NL

STYLISTIC T902

Your Excellent Flexible Companion

Processor, Chipset, Memory
Intel® Core™ i7-3520M processor (2.9 GHz), 4 MB,
(), 512 KB,
Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM
Drives
SSD SATA III, 128 GB, 2.5-inch
DVD Super Multi
2nd battery

Communication, Network
WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic
33.8 cm (13.3-inch), TFT, (HD+), Anti-glare touchscreen, 1600 x 900
pixel, 500:1, 300 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices
Fingerprint sensor, Launch keys, Application buttons, Tablet Pen,
Touch-screen, Multi gesture touchpad with two mouse buttons
Keyboard, N/A
Power supply

Li-Ion battery 6-cell, 72 Wh (6.700mAh battery) mAh
Runtime 1st battery: up to 7h 40m

Dimensions / Weight / Environmental
1.89 kg
326 x 244 x 27.1 mm front / 31 mm back (without foot) mm

Operating system
Windows 8 Pro

Interfaces
1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone,
1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2
(digital) x Internal microphones, 1 x Kensington Lock support, 1 x
Ethernet (RJ-45), 1 x Memory card slots, 1 x SIM card slot (usable
only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 (1 left side with
Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0
total, 1 x VGA

Warranty
2 year Bring-in Service

€ 1.799
VFY:T9020MXP31NL

ESPRIMO Desktops

ESPRIMO E400	ESPRIMO E400 E85+	ESPRIMO P400	ESPRIMO P400	ESPRIMO E510
--------------	-------------------	--------------	--------------	--------------



Your Flexible Economy PC

Your Immediately Available Office PC

Your Immediately Available Office PC

Your Immediately Available Office PC

Your Flexible Economy PC

Processor, Chipset, Memory

Intel® Core™ i3-3220 processor (3.30 GHz), 3 MB, Intel® H61
2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM

Processor, Chipset, Memory

Intel® Pentium® processor G2020 (2.90 GHz), 3 MB, Intel® H61
2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM

Processor, Chipset, Memory

Intel® Core™ i3-3220 processor (3.30 GHz), 3 MB, Intel® H61
2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM

Processor, Chipset, Memory

Intel® Core™ i5-3330 processor (3.00 GHz), 6 MB, Intel® H61
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM

Processor, Chipset, Memory

Intel® Core™ i3-3220 processor (3.30 GHz), 3 MB, Intel® B75
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
DVD Super Multi

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

10 kg
330 x 405 x 104 mm

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Dimensions / Weight / Environmental

10 kg
340 x 382 x 98 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8/

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8/

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, 1 x Ethernet (RJ-45), 2 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, 1 x Ethernet (RJ-45), 2 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, 1 x Ethernet (RJ-45), 2 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, 1 x Ethernet (RJ-45), 2 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0/ 2x 3.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Slots, Bays

2 x PCI-Express x1, 1 x PCI slots, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

Warranty

1 year Bring-in Service

Warranty

1 year Bring-in Service

Warranty

1 year Bring-in Service

Warranty

1 year Bring-in Service

€ 449

VFY:E0400P4311NL

€ 389

VFY:P0400P4231NL

€ 449

VFY:P0400P4301NL

€ 549

VFY:P0400P4521NL

€ 499

VFY:E0510P4311NL

ESPRIMO P510

Your Flexible and Economic PC
Processor, Chipset, Memory

Intel® Core™ i3-3220 processor (3.30 GHz), 3 MB, Intel® B75
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

10 kg
175 x 425 x 353 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0/ 2x 3.0 x USB internal, 1 x VGA

Slots, Bays

2 x PCI-Express x1, 1 x PCI slots, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

€ 499

VFY:P0510P4311NL

ESPRIMO P510 E85+

Your Flexible and Economic PC
Processor, Chipset, Memory

Intel® Core™ i5-3470 processor (3.20 GHz), 6 MB, Intel® B75
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

NVIDIA® GeForce® GT630 DisplayPort 2GB FH, 2 GB
Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

10 kg
175 x 425 x 353 mm

Operating system

WIN8 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0/ 2x 3.0 x USB internal, 1 x VGA

Slots, Bays

2 x PCI-Express x1, 1 x PCI slots, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

€ 599

VFY:P0510PR562NL

ESPRIMO Q510

The Mini with More PC per cm
Processor, Chipset, Memory

Intel® Core™ i3-2120T processor (2.60 GHz), 3 MB, Intel® H61
4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

HDD SATA II, 5400 rpm, 750 GB, 2.5-inch
DVD Super Multi Slot-in slim

Communication, Network

Bluetooth: 1 (optional)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500 (depending on processor), up to 1759 MB

Dimensions / Weight / Environmental

1.6 kg
185 x 188 x 54 mm

Operating system

WIN8 64 MAIN/LIC WIN8/RDVD W8/DU DVD WIN7+8

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 (DVI-I) x DVI, 2x 2.0 x USB front, 1 x HDMI, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x Multicardreader, 6 x USB 2.0 total, 4x 2.0 x USB rear, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

€ 449

VFY:Q0510PR312NL

ESPRIMO Q510

The Mini with More PC per cm
Processor, Chipset, Memory

Intel® Core™ i3-3220T processor (2.80 GHz), 3 MB, Intel® H61
4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

HDD SATA II, 5400 rpm, 500 GB, 2.5-inch
DVD Super Multi Slot-in slim

Communication, Network

Bluetooth: 1 (optional)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500 (depending on processor), up to 1759 MB

Dimensions / Weight / Environmental

1.6 kg
185 x 188 x 54 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8/

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 (DVI-I) x DVI, 2x 2.0 x USB front, 1 x HDMI, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x Multicardreader, 6 x USB 2.0 total, 4x 2.0 x USB rear, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

€ 549

VFY:Q0510P4311NL

ESPRIMO C710

Your Ultra Small Form Factor PC
Processor, Chipset, Memory

Intel® Core™ i3-3220 processor (3.30 GHz), 3 MB, Intel® Q75
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD SuperMulti SATA slim

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 V

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

9 kg
265 x 315 x 88 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, 1 x DisplayPort, 1 (DVI-I) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 2 x Serial (RS-232) (powered, 9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

€ 549

VFY:C0710P4361NL

ESPRIMO E710

Your Desktop PC Without Any Compromises
Processor, Chipset, Memory

Intel® Core™ i3-3220 processor (3.30 GHz), 3 MB, Intel® Q75
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 V

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

10 kg
340 x 382 x 98 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8/

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 x DisplayPort, 1 (DVI-I) x DVI, 2 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 1 x PCI-Express x1, 1 x PCI slots, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

€ 549

VFY:E0710P4371NL

ESPRIMO P710

Excellent Performance, Expandability And Energy Efficiency
Processor, Chipset, Memory

Intel® Core™ i3-3220 processor (3.30 GHz), 3 MB, Intel® Q75
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 V

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8/

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 x DisplayPort, 1 (DVI-I) x DVI, 2 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 1 x PCI-Express x1, 1 x PCI slots, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

€ 549

VFY:P0710P4371NL

ESPRIMO P710

Excellent Performance, Expandability And Energy Efficiency
Processor, Chipset, Memory

Intel® Core™ i5-3570 processor (3.40 GHz), 6 MB, Intel® Q75
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 V

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8/

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 x DisplayPort, 1 (DVI-I) x DVI, 2 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 1 x PCI-Express x1, 1 x PCI slots, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

€ 779

VFY:P0710PXP61NL

ESPRIMO E910

The Innovative 0-Watt PC
Processor, Chipset, Memory

Intel® Core™ i5-3470 processor (3.20 GHz), 6 MB, Intel® Q77
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

10 kg
340 x 382 x 98 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8/

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 x DisplayPort, 1 (DVI-I) x DVI, 2 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 1 x PCI-Express x1, 1 x PCI slots, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

3 year Bring-in Service

€ 719

VFY:E0910PXC61NL

ESPRIMO P910

The Expandable Business Workhorse
Processor, Chipset, Memory

Intel® Core™ i5-3470 processor (3.20 GHz), 6 MB, Intel® Q77
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8/

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 x DisplayPort, 1 (DVI-I) x DVI, 2 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 1 x PCI-Express x1, 1 x PCI slots, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

€ 719

VFY:P0910PXC61NL

ESPRIMO P910

The Expandable Business Workhorse
Processor, Chipset, Memory

Intel® Core™ i5-3570 processor (3.40 GHz), 6 MB, Intel® Q77

2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch

MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

NVIDIA® GeForce® GT630 DisplayPort 2GB FH 0-Watt, 2 GB Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 x DisplayPort, 1 (DVI-I) x DVI, 2 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 1 x PCI-Express x1, 1 x PCI slots, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

€ 899

VFY:P0910PXP61NL

ESPRIMO P910

The Expandable Business Workhorse
Processor, Chipset, Memory

Intel® Core™ i7-3770 processor (3.40 GHz), 8 MB, Intel® Q77

2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch

SSD SATA III, 64 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

NVIDIA® GeForce® GT630 DisplayPort 2GB FH 0-Watt, 2 GB Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, 1 x DisplayPort, 1 (DVI-I) x DVI, 2 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 1 x PCI-Express x1, 1 x PCI slots, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

€ 1.099

VFY:P0910PXP71NL

ESPRIMO Q910

The Mini with More PC per cm
Processor, Chipset, Memory

Intel® Core™ i5-3470T processor (2.90 GHz), 3 MB, Intel® Q77

4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

HDD SATA II, 5400 rpm, 500 GB, 2.5-inch

DVD Super Multi Slot-in slim

Communication, Network

Bluetooth: 1 (optional)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500 (depending on processor), up to 1759 MB

Dimensions / Weight / Environmental

1.6 kg
185 x 188 x 54 mm

Operating system

WIN7 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO/DU DVD WIN7+8

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DisplayPort, 1 (DVI-I) x DVI, 2x 3.0 x USB front, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x Multicardreader, 2 x USB 2.0 total, 2x 2.0 and 2x 3.0 x USB rear, 4 x USB 3.0 total, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

1 x 5.25-inch external bays

Warranty

3 year Bring-in Service

€ 829

VFY:Q0910PXP61NL

ESPRIMO X913 Touch

Evolutionary PC for the Modern Office
Processor, Chipset, Memory

Intel® Core™ i5-3470T processor (2.90 GHz), 3 MB, Intel® Q77

4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

HDD SATA II, 5400 rpm, 500 GB, 2.5-inch

Communication, Network

Bluetooth: 1 (optional with WLAN module)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics#Intel® HD Graphics 2000#Intel® HD Graphics 2500, up to 1759 MB

Dimensions / Weight / Environmental

8.62 kg
554 x 225 x 433 mm

Operating system

WIN8 PRO64 MAIN/LIC WIN8 PRO/RDVD W7+8PRO

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DVI, optional with camera module x Internal microphones, 2 x Kensington Lock support, 1 x Ethernet (RJ-45), 2 x USB 2.0 total, 2x2.0 2x3.0 x USB rear, 4 x USB 3.0 total, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

0 x 2.5-inch bays

Warranty

3 year Bring-in Service

€ 1.149

VFY:X913TP3511NL

FUTRO Thin Clients



FUTRO S700



De betaalbare Thin Client

Processor, Chipset, Memory

AMD A55E Controller Hub
2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM

Drives

mSATA, 2 GB, Flash drive

Communication, Network

LAN: Built-in 10/100/1000 MBit/s

Display, Graphics

ATI Radeon™ HD 6250 , up to 256 MB

Dimensions / Weight / Environmental

1,2 kg
97 x 191 x 266 mm

Operating system

eLux® RL - Embedded Linux

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, 1 x DC-in, 1 DP x DisplayPort,
1 DVI-I (integrated VGA can be used with DVI-VGA adapter) x DVI,
1 x Front audio: headphone, 1 x Front audio: line-in / microphone,
2 x USB front, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 2
x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, 2 x USB
internal

Warranty

2 year Bring-in Service

€ 299

VFY:S0700PF045NL

FUTRO S700



De betaalbare Thin Client

Processor, Chipset, Memory

AMD A55E Controller Hub
2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM

Drives

mSATA, 4 GB, Flash drive

Communication, Network

LAN: Built-in 10/100/1000 MBit/s

Display, Graphics

ATI Radeon™ HD 6250 , up to 256 MB

Dimensions / Weight / Environmental

1,2 kg
97 x 191 x 266 mm

Operating system

Windows® Embedded Standard 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, 1 x DC-in, 1 DP x DisplayPort,
1 DVI-I (integrated VGA can be used with DVI-VGA adapter) x DVI,
1 x Front audio: headphone, 1 x Front audio: line-in / microphone,
2 x USB front, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 2
x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, 2 x USB
internal

Warranty

2 year Bring-in Service

€ 349

VFY:S0700PX011NL

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1220v2# (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 500 GB, 3.5-inch, economic
DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

€ 549

VFY:T1003SC070IN

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1230v2# (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 1 TB, 3.5-inch, business critical
DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

€ 849

VFY:T1003SC090IN

PRIMERGY TX120 S3p



For small environments with high demands

PRIMERGY TX120 S3p: For small environments with high demands. It is the perfect server for environments where space, high server functionality and low TCO are crucial. The unique combination of ultra-compact form factor, Intel® Xeon® processor performance, low TCO and high TX120 S3p ideal for demanding environments where space is scarce. availability features, make the PRIMERGY

Processor, Chipset, Memory

Intel® Xeon® processor E3-1265Lv2# (4C/8T, 2.50 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 45 W)
Intel® C202
4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D3049

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
1 x PCI-Express 2.0 x4 (mech. x8)
4 x 2.5-inch hot-plug SAS/SATA or 2x 3.5-inch non hot-plug SATA.
Not upgradeable in the field.
None
1 x 3.5/1.6-inch for backup devices#1 x 5.25/0.5-inch for CD-RW/DVD

Dimensions / Weight / Environmental

98 x 399 x 340 mm
up to 10 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

10 x USB 2.0 (2x front, 6x rear, 2x internal; the 2 internal ports cannot be used in parallel), 1 x RS-232-C, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Optional front service LAN port (10/100 Mbit/s)

Warranty

1 year
On-site Service

€ 669

VFY:T1203SXG10IN

PRIMERGY TX140 S1p

Expandable SME all-round server

PRIMERGY TX140 S1p: the expandable SME all-rounder. It is ideal for SME or branch customers looking for a classic file, print, mail, or database server, with high scalability, Intel® Xeon® E3 series-based performance, and optional redundant power supplies. Storing up to 12 TB, and offering an optional rack conversion kit, the TX140 S1p is an attractive long-term investment.

Processor, Chipset, Memory

Intel® Xeon® processor E3-1265Lv2#
(4C/8T, 2.50 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 45 W)
Intel® C202
4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM
Mainboard type
D3049

Drives, Controller

DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

482 x 570 x 220 mm
205 x 584 x 444 mm
21-28 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

10 x USB 2.0 (2x front, 6x rear, 2x internal; the 2 internal ports cannot be used in parallel, 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

€ 749

VFY:T1401SXG10IN

PRIMERGY TX150 S8

The one-processor tower server - maximized!

The PRIMERGY TX150 S8: the right system for SMEs, branch offices or virtualized environments where the main focus is on expandability and availability. With processors of the Intel® Xeon® E5-1400 and E5-2400 family, the TX150 S8 delivers excellent energy-efficient performance. PRIMERGY TX150 S8: the one processor tower server – maximized!

Processor, Chipset, Memory

Intel® Xeon® processor E5-2420# (6C/12T, 1.90 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® C602
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM
Mainboard type
D 3079

Drives, Controller

DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

483 x 611 x 177 mm
177 x 651 x 456 mm
16 - 29 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 x USB 2.0 (2x front, 4x rear, 3x internal for backup, UFM and internal USB), 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

€ 1.099

VFY:T1508SC040IN

PRIMERGY TX200 S7

Well-balanced price- performance

The PRIMERGY TX200 S7 is a perfect server for SMEs, branch offices or virtualized infrastructures. The tower server offers dual processor performance combined with expandability and energy efficiency. Its feature set makes the TX200 S7 a great virtualization, database or communication server. The PRIMERGY TX200 S7 strikes the right balance between price and performance.

Processor, Chipset, Memory

..Intel® Xeon® processor E5-2420# (6C/12T, 1.90 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1333 MHz, 95 W)
..Intel® C602
..8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM
Mainboard type
..D 3099

Drives, Controller

..DVD Super Multi, half height, SATA I
..RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int.#RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

..1 x PCI-Express 2.0 x4 (mech. x8)
..3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

..483 x 611 x 177 mm
..177 x 651 x 456 mm
..16 kg - 29 kg - Actual weight may vary depending on configuration

Software

..XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

..2 x Gbit/s Ethernet (Intel Hartwell), 9 x USB 2.0 (2 x front USB, 4 x rear USB 3 x internal for backup, UFM and internal USB), 1 x serial RS-232-C (9 pin), usable for iRMC S3 or system or common use, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

.. 3 years
.. On-site Service

€ 1.449

VFY:T2007SC040IN

PRIMERGY TX300 S7

No compromise tower server

PRIMERGY TX300 S7: a no compromise tower server offering maximum performance, expandability and availability. It combines the latest Intel® Xeon® processors E5 family, with up to two 6 GB GPGPUs and up to 2x 10 Gb LAN cards. Its 10 slots guarantee excellent expandability. Up to 4 hot-plug power supplies assure business continuity. It is ideal for database, virtualization or HPC scenarios.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2630# (6C/12T, 2.30 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® C600 (Intel® Patsburg A)
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM

Mainboard type
D2949

Drives, Controller

DVD Super Multi, half height, SATA I
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int.#RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

177 x 777 x 456 mm
up to 35 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows HPC Server® 2008 R2 Suite, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

x Gbit/s Ethernet, 10 x USB 2.0 (2x front, 4x rear, 2x internal for backup devices, 1x USB stick, 1x USSD), 1 x serial RS-232-C, usable for iRMC S3 or system or shared, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller, Front management LAN port as option

Warranty

3 years
On-site Service

€ 1.999

VFY:T3007SC020IN

PRIMERGY RX100 S7p proGREEN selection

Small in size and low in cost – rich in optional features

The Fujitsu PRIMERGY RX100 S7 is an entry mono socket rack server designed to meet small budgets by delivering highest energy efficiency of its class and a rich set of optional expansions to meet individual demands. Optimized for infrastructure and communication applications, this 1U server delivers up to 32GB RAM, up to 3 PCIe slots and up to 4 hard disk drives.

Processor, Chipset, Memory

Intel® Xeon® processor E3-1265Lv2# (4C/8T, 2.50 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 45 W)
Intel® C202
4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type
D 3034

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
1 x PCI-Express 2.0 x4 (mech. x8)
4x 2.5-inch hot-plug SAS/SATA
PRIMERGY RX100 S7p proGREEN selection:
4 x 2.5-inch drive bays pre-configured
1 x 5.25/0.5-inch for CD-RW/DVD#1 x
3.5/0.5-inch for ServerView Local Service Panel or front VGA + front Service LAN

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 431mm (Body) x 572 x 42.5 mm
up to 14 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, vSphere™ 4.0 Embedded, vSphere™ 4.0 Installable, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011

Interfaces

2 x Gbit/s Ethernet, 7 x (2x front, 4x back, 1x internal for UFM), 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA (15-pin), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

€ 849

VFY:R1007SXG10IN

PRIMERGY RX200 S7

Maximum productivity in a 1U housing

The Fujitsu PRIMERGY RX200 S7 is a rack server that provides high performance of the new Intel® Xeon® E5 product family, expandability up to 768GB of memory and up to 94% energy efficiency - all in 1U space saving housing. Thus, the PRIMERGY RX200 S7 is ideal for virtualization and cloud, small databases as well as for high performance computing.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2620# (6C/12T, 2.00 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® C600 (Intel® Patsburg A)
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM

Mainboard type
D3032

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

4 x 2.5-inch base unit or 8 x 2.5-inch base unit
1 x 5.25/0.5-inch for DVD-RW/Blu-ray (only for base unit 4x 2.5-inch HDD)

Dimensions / Weight / Environmental

482 mm (Bezel) / 431mm (Body) x 762 mm x 43 mm
up to 18 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows HPC Server® 2008 R2 Suite, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard, ,

Interfaces

6 x USB 2.0 (2x front, 3x rear, 1x uSSD), 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller, Front management LAN port as option

Warranty

3 years
On-site Service

€ 1.449

VFY:R2007SC010IN

PRIMERGY RX300 S7

The versatile 2U powerhouse

The Fujitsu PRIMERGY RX300 S7 is a 2U dual socket rack server, optimized for all types of business applications by focusing on versatility and scalability that supports up to 16 harddisk drives, up to 7 PCIe Gen 3 cards and up to 768GB RAM. Thanks to top performance of the new Intel® Xeon® E5 product family and the available upgrade kits, the RX300 will also ensure the demands of tomorrow are met.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2630# (6C/12T, 2.30 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)
Intel® C600 (Intel® Patsburg A)
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM

Mainboard type

D2939

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

2.5-inch base unit (max. 16 x 2.5) or 3.5-inch base unit (max. 6 x 3.5)
1 x 5.25/0.5-inch for ODD#1 x 5.25/1.6-inch for ODD or backup devices #1 x 5.25/0.5-inch for Local Service Display

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 445mm (Body) x 770 x 86.9 mm
up to 25 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows HPC Server® 2008 R2 Suite, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

10 x USB 2.0 (2x front, 4x rear, 2x internal for backup devices, 1x USB stick, 1x uSSD), 1 x serial RS-232-C, usable for iRMC or system or shared, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller, Front management LAN port as option

Warranty

3 years
On-site Service

€ 1.699

VFY:R3007SC020IN

PRIMERGY RX350 S7

Maximum expandability in a 2 way server

PRIMERGY RX350 S7: a 4U dual socket rack server offering maximum performance, expandability and availability. It combines the latest Intel® Xeon® processors E5 family, with up to two 6GB GPGPUs, up to 24 hard drives and up to 768GB RAM. Its 10 PCI slots guarantee excellent expandability. Up to 4 hot-plug power supplies assure business continuity. It is ideal for database, virtualization or HPC scenarios.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2630# (6C/12T, 2.30 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)
Intel® C600 (Intel® Patsburg A)
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM

Mainboard type

D2949

Drives, Controller

DVD Super Multi, half height, SATA I
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int.#RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
2.5-inch or 3.5-inch hot-plug SAS/SATA
1 x 5.25/0.5-inch for ODD#1 x 5.25/1.6-inch for ODD or backup devices #1 x 5.25/0.5-inch for Local Service Display

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 448 mm (Body) x 736 x 177 mm
up to 35 kg - Actual weight may vary depending on configuration

Interfaces

10 x USB 2.0 (2x front, 4x rear, 2x internal for backup devices, 1x USB stick, 1x USSD), 1 x serial RS-232-C, usable for iRMC S3 or system or shared, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller, Front management LAN port as option

Warranty

3 years
On-site Service

€ 2.149

VFY:R3507SC020IN

CELSIUS W420	CELSIUS W420	CELSIUS W520	CELSIUS W520	CELSIUS M720
--------------	--------------	--------------	--------------	--------------



The Gateway to Workstation Performance

Performance That Boosts Your Productivity

The Gateway to Workstation Performance

Performance That Boosts Your Productivity

Your "Thoroughbred" Workstation

Processor, Chipset, Memory

Intel® Core™ i7-3770 processor (3.40 GHz), 8 MB, Intel® Q77
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Processor, Chipset, Memory

Intel® Core™ i7-3770 processor (3.40 GHz), 8 MB, Intel® Q77
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Processor, Chipset, Memory

Intel® Xeon® processor E3-1240v2 (3.40 GHz), 8 MB, Intel® C216
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Processor, Chipset, Memory

Intel® Xeon® processor E3-1270v2 (3.50 GHz), 8 MB, Intel® C216
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Processor, Chipset, Memory

Intel® Xeon® processor E5-1620 (3.60 GHz), 10 MB, Intel® C602
4 x 2 GB (1 module(s) 2 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 LM

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 LM

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 LM

Communication, Network

LAN: 10/100/1000 MBit/s Intel® 82579 LM

Communication, Network

LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

AMD FirePro™ V3900, 1 GB
Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Display, Grafic

NVIDIA® Quadro® 600, 1 GB
Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Display, Grafic

AMD FirePro™ V4900, 1 GB
up to 1759 MB

Display, Grafic

DP to DVI-D (single link) Adapter Cable
NVIDIA® Quadro® 2000, 1 GB
up to 1759 MB

Display, Graphics

AMD FirePro™ V4900, 1 GB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Dimensions / Weight / Environmental

approx. 16 kg
186 x 481 x 430 mm

Dimensions / Weight / Environmental

approx. 16 kg
186 x 481 x 430 mm

Dimensions / Weight / Environmental

18 kg
186 x 481 x 430 mm

Operating system

Pre-installed: Windows 8 Pro

Operating system

Pre-installed: Windows 8 Pro

Operating system

Pre-installed: Windows 8 Pro

Operating system

Pre-installed: Windows 8 Pro

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: lineout, 1 x DisplayPort, 1 x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: lineout, 1 x DisplayPort, 1 x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0/ 2x 3.0 x USB front, 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Interfaces

2 x Audio: in (rear), 1 x Audio: out (rear), 1 x DisplayPort, 1 (depends on processor) x DVI, 1 (optional) x eSATA, 1 x Audio: in, 1 x Audio: out, 2x 2.0/ 2x 3.0 x USB front, 1 x Internal speakers, 1 x Ethernet (RJ-45), 1, optional Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 1 + 1 x USB internal, 1 (depends on processor, via DVI to VGA adapter) x VGA

Interfaces

2 x Audio: in (rear), 1 x Audio: out (rear), 1 x DisplayPort, 1 (depends on processor) x DVI, 1 (optional) x eSATA, 1 x Audio: in, 1 x Audio: out, 2x 2.0/ 2x 3.0 x USB front, 1 x Internal speakers, 1 x Ethernet (RJ-45), 1, optional Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 6x 2.0 / 2x 3.0 x USB rear, 1 + 1 x USB internal, 1 (depends on processor, via DVI to VGA adapter) x VGA

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x Audio: in, 1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 1 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI-Express 2.0 x16, 1 x PCI-Express 2.0 x4 (mech. x16), 1 x PCI-Express x1, 1 x PCI slots, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Slots, Bays

1 x PCI-Express 2.0 x16, 1 x PCI-Express 2.0 x4 (mech. x16), 1 x PCI-Express x1, 1 x PCI slots, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Slots, Bays

1 x PCI-Express 2.0 x16, 1 x PCI-Express 2.0 x4 (mech. x16), 3 x PCI-Express x1, 2 x PCI slots, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Slots, Bays

1 x PCI-Express 2.0 x16, 1 x PCI-Express 2.0 x4 (mech. x16), 3 x PCI-Express x1, 2 x PCI slots, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

Warranty

3 year Bring-in Service

Warranty

3 year Bring-in Service

Warranty

3 year Bring-in Service

Warranty

3 year Bring-in Service

€ 849

VFY:W4200WXP31NL

€ 1.199

VFY:W4200WXP31NL

€ 1.099

VFY:W5200WXP31NL

€ 1.499

VFY:W5200WXP31NL

€ 1.249

VFY:M7200WXP31NL

CELSIUS M720

Your "Thoroughbred" Workstation
Processor, Chipset, Memory

Intel® Xeon® processor E5-1620 (3.60 GHz), 10 MB, Intel® C602
4 x 4 GB (1 module(s) 4 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III, 128 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Graphics

DP to DVI-D (single link) Adapter Cable
NVIDIA® Quadro® 2000, 1 GB

Dimensions / Weight / Environmental

18 kg
186 x 481 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x Audio: in, 1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 1 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

€ 1.799

VFY:M7200WXP11NL

CELSIUS R920

Uncompromising Workstation Performance for Extreme Requirements
Processor, Chipset, Memory

Intel® Xeon® processor E5-2640 (2.50 GHz), 15 MB, 7.2 GT/s, Intel® C602
4 x 4 GB (1 module(s) 4 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III, 256 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 2x Built-in 10/100/1000 MBit/s Intel® 82579 LM and Intel® 82574L

Display, Graphics

NVIDIA® Quadro® 4000, 2 GB

Dimensions / Weight / Environmental

20 kg
186 x 618 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x eSATA, 1 x Audio: in, 1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 2 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

€ 2.999

VFY:R9200WXP21NL

CELSIUS H720

Workstation Power on-the-Go
Processor, Chipset, Memory

Intel® Core™ i7-3740QM processor (2.7 GHz), 6 MB, Intel® QM77
2 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 256 GB, 2.5-inch
DVD-RW Dual Double Layer Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000 module
10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

39.6 cm (15.6-inch), LED backlight, (Full HD), Anti-glare display, magnesium, 1920 x 1080 pixel, 300:1, 220 cd/m
NVIDIA® Quadro® K1000M#NVIDIA® Quadro® K2000M, 2 GB (GDDR3 VRAM)

Dimensions / Weight / Environmental

2.8 kg
379.8 x 257.0 x 35.5 mm

Operating system

Win8P lic./ Win7P load / RDVD TWIN-Pack

Interfaces

1 x DC-in, 1 x DisplayPort, 1 x eSATA, 1 (34 mm) x ExpressCard slots, 1 x Audio: in, 1 x Audio: out, 2 digital array microphones x Internal microphones, 1 x Ethernet (RJ-45), 1 (SD up to 2 GB, SDHC up to 32 GB, SDXC up to 64 GB) x Multicardreader, 1 x SIM card slot (), 1 x SmartCard slot, 1 x USB 2.0 total, 3 x USB 3.0 total, 1 x VGA

Warranty

3 year Bring-in Service

€ 1.999

VFY:H7200WXP41NL

CELSIUS H920

High-End Workstation Power on-the-Go
Processor, Chipset, Memory

Intel® Core™ i7-3740QM processor (2.7 GHz), 6 MB, Intel® QM77
4 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch
DVD-RW Dual Double Layer Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000 module
10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

43.9 cm (17.3-inch), LED backlight, (Full HD), Anti-glare display, 1920 x 1080 pixel
NVIDIA® Quadro® K3000M, 2 GB (GDDR5 VRAM)
NVIDIA® Quadro® K3000M#NVIDIA® Quadro® K4000M, 2 / 4 GB (GDDR5 VRAM)

Dimensions / Weight / Environmental

4.25 kg
417 x 287 x 33/44 mm

Operating system

Win8P lic./ Win7P load / RDVD TWIN-Pack

Interfaces

1 x DC-in, 1 x DisplayPort, 1 x eSATA, 1 (34/54 mm) x ExpressCard slots, 1 x Audio: out, 1 digital array microphone x Internal microphones, 1 x Ethernet (RJ-45), 1 (SD up to 2 GB, SDHC up to 32 GB, SDXC up to 64 GB) x Multicardreader, 1 x SIM card slot (), 1 x SmartCard slot, 3 x USB 2.0 total, 1 x USB 3.0 total, 1 x VGA

Warranty

3 year Bring-in Service

€ 2.499

VFY:H9200WXP41NL