

Pore Pressure Prediction using Well-Logging Data in the West Baram Delta, Offshore Sarawak Basin, Malaysia



Dejen Teklu Asfha, Haylay Tsegab Gebretsadik, Wan Ismail Wan Yusoff

Abstract: Well-predicted pore pressure is vital throughout the lifetime of an oil and gas field starting from exploration to the production stage. Here, we studied a mature field where enhanced oil recovery is of high interest and pore pressure data is crucial. Moreover, the top of the overpressure zone in west Baram Delta starts at different depths. Hence, valid pore pressure prediction prior to drilling is a prerequisite for reducing drilling risks, increasing efficient reservoir modeling and optimizing costs. Petrophysical logs such as gamma-ray, density logs, and sonic transit time were used for pore pressure prediction in the studied field. Density logs were used to predict the overburden pressure, whereas sonic transit time, and gamma-ray logs were utilized to develop observed shale compaction trend line (OSCTL) and to establish a normal compaction trend line (NCTL). Pore pressure was predicted from a locally observed shale compaction trend line of 6 wells using Eaton's and Miller's methods. The predicted pore pressure using Eaton's DT method with Eaton's exponent 3 showed a better matching with the measured pressure acquired from the repeat formation test (RFT). Hence, Eaton's DT method with Eaton's exponent 3 could be applied to predict pore pressure for drilling sites in the study area and vicinity fields with similar geological settings.

Keywords: Eaton method, Miller method, pore pressure prediction.

I. INTRODUCTION

The pressure of fluids within a porous rock is known as pore pressure or formation pressure [1]. If the change in pressure per unit depth is equivalent to the hydrostatic pressure of the formation pore pressure of the rocks it is called a normal pore pressure. Pore pressures which are found to lie above or below the normal pore pressure gradient line are called abnormal pore pressures [2]. Abnormal pore pressures could be classified into overpressure or under pressure depending on their magnitude. If the pore pressure of the

formation is greater than the hydrostatic pressure at a given depth, it is called overpressure, whereas if the formation pore pressure is lower than the hydrostatic pressure of a given depth it is known under pressure [3]. Overpressure has been one of the major global geological challenges in the drilling operations in the oil and gas industry, while predrill pore pressure remained as the basic input data for proper selection of casing optimization and specifying a reliable of a drilling fluid density [4]. Thus, implied that validated pore pressure (over or under pressure) prediction is crucial for the oil and gas industry due to its decisive impact on the safety and cost of drilling for petroleum exploration and production [5]. Hence, precise pore pressure prediction is required to minimize the risks of drilling incidents such as blowouts, kicks, instability of wellbore, whole washouts, loss of drilling fluid circulation and protect the pay formation [3]. Accurate pore pressure prediction prerequisites a better understanding of the overpressure generation mechanisms in a particular field. Tectonic setting, rate of sedimentation and lithology have a major influence on overpressure distribution mechanisms [6]. This signifies the importance of geological and tectonic understanding of the basin evolution for the analysis of overpressure mechanisms and pore pressure prediction in a given study area.

II. GEOLOGICAL SETTING

The Baram Delta Province is a Tertiary basin located in the northern part of Sarawak and extending north-eastward through Brunei into the southern part of Sabah (Fig.1). It was formed in the late Eocene following a major orogenic event that folded and uplifted the late Eocene deposits [7]. The study area is located 40 km offshore Sarawak in the south-western part of the Baram Delta Province (Fig. 1).

A. Overpressure generation mechanisms

Overpressure is the result of geological, physical, chemical, and mechanical processes [8]. According to Swarbrick and Osborne [9], the mechanisms of overpressure generation are classified into three broad categories: (1) stress-related mechanisms, (2) fluid volume increase mechanisms, (3) the fluid movement and buoyancy mechanisms. The stress-related overpressure generation mechanisms are disequilibrium compaction which is also known as under compaction and overpressure caused by tectonic structures such as faults and folds. Depending on whether the structures act as a conduit or as a seal.

Manuscript published on November 30, 2019.

* Correspondence Author

Dejen Teklu Asfha*, Department Of Geoscience, Universiti Teknologi Petronas, Seri Iskandar, Malaysia Email: Dejen_16003796@Utp.Edu.My Or Deju7.Pet@gmail.com

Haylay Tsegab Gebretsadik, Department Of Geoscience, Southeast Asia Carbonate Research Laboratory, Universiti Teknologi Petronas, Seri Iskandar, Malaysia. Email: Haylay.Tsegab@Utp.Edu.My

Wan Ismail Wan Yusoff, Department Of Geoscience, Center For Subsurface Seismic Imaging, Universiti Teknologi Petronas, Seri Iskandar, Malaysia.

© The Authors. Published by Blue Eyes Intelligence Engineering and Sciences Publication (BEIESP). This is an [open access](https://creativecommons.org/licenses/by-nc-nd/4.0/) article under the CC-BY-NC-ND license <http://creativecommons.org/licenses/by-nc-nd/4.0/>

Pore Pressure Prediction using Well-Logging Data in the West Baram Delta, Offshore Sarawak Basin, Malaysia

The increment of temperature with depth, the release of water due to the transformation of minerals (clay diagenesis), hydrocarbon maturation, and oil to gas cracking are under the category of fluid volume increase mechanisms. Buoyancy and lateral transfer are under the third category.

B. Distribution of overpressure in the study area

The distribution of overpressure in the Baram Delta is believed to be influenced by the rate of sedimentation [10]. It

is known that overpressure is mainly generated by under compaction due to the fast rate of deposition of less permeable shales in many tertiary basins [6]. However, two types of overpressure mechanisms were suggested in the study area; the disequilibrium compaction in the pro-delta shales, and fluid expansion in the outer shelf of the region [11].




Fig. 1. Location map of the Baram Delta Province (the green box), Sarawak, Malaysia [12].

III. METHODOLOGY

In this study, we have used different types of petrophysical logs such as gamma-ray (GR), density logs (RHOB), and sonic transient time (DT) to predict the pore pressure. The density logs have been used to predict the overburden pressure. Gamma-ray and sonic transit time were used to calculate the observed Shale Compaction Trend Line (OSCTL) and Normal Compaction Trend Lines (NCTL). The sonic log (DT) was used to develop the regional normal compaction trendline. Pore pressure was predicted from the locally observed shale compaction trendline, which was taken from the smoothed log response.

A. Pore pressure prediction methods

The effective stress method is the most popular pore pressure prediction method in the industry. According to Terzaghi [13], the total vertical stress is equal to the sum of rock grain pressure and the pore pressure of the formation. This is the basic theory in pore pressure prediction.

The vertical effective stress can be calculated by:

$$V_{es} = P_{OB} - \alpha PP \quad (1)$$

Where, V_{es} is the vertical effective stress, P_{OB} is the overburden stress, PP is the pore pressure, and α is the vertical effective stress coefficient which is less than 1.

The factor α is the Biot consolidation coefficient and defined as:

$$\alpha = \frac{Kf}{Ks} \quad (2)$$

Where, Kf is the bulk modulus of the dry rock frame (drained) and Ks is the bulk modulus of the solid material. For soft rocks $\alpha = 1$ and for hard rocks $\alpha = 0$. The value of α can be estimated either through laboratory measurements or field data [14]. For this purpose, two methods are briefly described in the following.

The Eaton method is based on the change in the porosity of rocks with depth. It is derived from equation (1) above. Eaton [15], developed a method by comparing the normal and observed values from sonic travel time. Therefore, the pore pressure of the formation can be estimated from the ratio of the observed and the expected values.

The equation is given as:

$$PP = P_{ob} - (P_{ob} - P_{hyd}) \left(\frac{\Delta T_n}{\Delta T_o} \right)^n \quad (3)$$

Where PP is the pore pressure of the formation, P_{ob} is the overburden stress, P_{hyd} is hydrostatic (normal) pressure, ΔT_n is the normal transit time (sonic), ΔT_o is observed sonic transit time, and n is an exponent.

Provided the normal compaction trendline is well determined, the Eaton method is applicable for pore pressure prediction of young sedimentary basins [16].

Miller's method is the second approach which bases on the relationship between the velocity in the formation and vertical effective stress, which in turn can be used to relate sonic transit time to pore pressure of the formation. Sonic is the main input data to determine the maximum velocity depth that can be associated with the existing unloading mechanism [17]. Miller's sonic velocity can also be applied for pore pressure prediction [18].

Miller's sonic velocity (loading) method is given as:

$$PP = V_{es} - \frac{1}{\lambda} \ln \left\{ \frac{vm - vml}{vm - vp} \right\} \quad (4)$$

Where, Where, PP is the pore pressure of the formation, V_{es} is the vertical effective pressure, vm is the interval velocity from sonic measurement in the matrix of the shale, vp is the velocity (compressional), vml is the interval velocity of the sediments in the mudline, λ is the empirical parameter which defines the increment rate of velocity as the function of effective stress (normally is $\lambda = 0.00025$).

Miller's sonic velocity (unloading) method is given as:

$$PP = V_{es} - \frac{1}{\lambda} \ln \left\{ am \left(1 - \frac{vm - vulo}{vm - vp} \right) \right\} \quad (5)$$

Where, PP is the pore pressure of the formation, V_{es} is the vertical effective pressure, vm is the interval velocity from sonic measurement in the matrix of the shale, vp is the velocity (compressional), vml is the interval velocity of the sediments in the mudline, λ is the an empirical parameter which is defines the increment rate of velocity as the function of effective stress (normally is $\lambda = 0.00025$), am is the ratio of the loading and unloading velocities for the effective stress curve $vulo$ (normally $am = 1.8$) and $am = vp / vulo$, $vulo$ is the effective stress from unloading of the sediment

Repeat formation test (RFT) was used to validate the pore pressure prediction at well locations. Out of the six wells, only two wells have RFT data. Hence, the RFT data of those wells was used to validate the pore pressure prediction.

IV. RESULT AND DISCUSSION

Based on Eaton DT equation (3) and Miller methods equation (5), pore pressure for the study was successfully predicted for 6 wells. As a result, the Eaton DT method with Eaton exponent 3 and Miller method with velocity exponent 3 have able to predict reasonably consistent pore pressure that matches the measured RFT data at well locations.

Well 1




Fig. 2. Pore pressure prediction for well 1 using the Eaton DT method. Grey black color is the hydrostatic pressure, purple color is the overburden stress (pressure), the red curve is the predicted pore pressure of the formation (psi) using Eaton DT method with Eaton exponent 3, and the green dots are measured RFT pressure data.



Pore Pressure Prediction using Well-Logging Data in the West Baram Delta, Offshore Sarawak Basin, Malaysia




Fig. 3. Pore pressure prediction for well 1 using the Miller method. Grey black) color is the hydrostatic pressure, (purple color) is the overburden stress (pressure), the blue curve is the predicted pore pressure of the formation (psi) using Miller method with velocity exponent 3, and the red dots are measured RFT pressure data.




Fig. 4. Pore pressure prediction for well 2 using the Eaton DT method. Grey black color is the hydrostatic pressure, purple color is the overburden stress (pressure), the red curve is the predicted pore pressure (psi) using Eaton DT method with Eaton exponent 3, and the green dots are measured RFT pressure data.




Fig. 5. Pore pressure prediction for well 2 using the Miller method. Grey black color is the hydrostatic pressure, (purple color) is the overburden pressure, the blue curve is the predicted pore pressure (psi) using the Miller method with velocity exponent 3, and the red dots are measured RFT pressure data.

The predicted pore pressure using the Eaton DT method with Eaton DT exponent 3 and Miller method with velocity exponent 3 showed a very good correlation with the measured pressure data from RFT for both wells; well 1 and well 2. The predicted pore pressure using the Eaton DT method with Eaton DT exponent 3 also showed an excellent correlation with the measured pressure (RFT) data in the shallow depths of the wells. This could be related to the fact that the overpressure generation mechanism at the shallower depth of the study area is mainly caused by disequilibrium compaction (under compaction) which is consistent with previous works of Yusoff [10]. However, the predicted pore pressure using the Miller method with velocity exponent 3 showed excellent matching with the measured RFT pressure data in the deeper depths of the studied field, where fluid expansion could be the main mechanism of over pressure in the study area.




Fig. 6. The predicted pore pressure for well 1 using the Eaton DT method with Eaton DT exponent 3 is compared with measured RFT pressure data.




Fig. 7. The predicted pore pressure for well 1 using the Miller method with velocity exponent 3 is compared with measured RFT pressure data.




Fig. 8. The predicted pressure for well 2 using the Eaton DT method with Eaton DT exponent 3 is compared with the measured RFT pressure.




Fig. 9. The predicted pore pressure for well 2 using the Miller method with velocity exponent 3 is compared with measured RFT pressure data.

V. CONCLUSION

Conventional pore pressure prediction methods such as Eaton DT and Miller methods with their standard exponents (Eaton DT exponent 3 and velocity exponent 3) have provided accurate pore pressure prediction results for a producing field in the Baram Delta of the Sarawak Basin. Eaton DT method with Eaton exponent 3 provided an excellent correlation with measured RFT pressure data. Hence, the Eaton DT method with Eaton exponent 3 could be applied to predict pore pressure for the planning and optimization of drilling operations in the study area.

ACKNOWLEDGMENT

Special gratitude to PETRONAS for providing us data for this research. We are also grateful to the Center of Excellence in Subsurface seismic Imaging and hydrocarbon prediction (CSI) for allowing us to use research facilities required to complete this research. Finally, the authors would like to Thank DUG downunder geosolutions company for free license to use Insight software.

REFERENCES

1. C. M. Sayers, L. D. Den Boer, Z. R. Nagy, and P. J. Hooyman, "Well-constrained seismic estimation of pore pressure with uncertainty SEG / New Orleans 2006 Annual Meeting SEG / New Orleans 2006 Annual Meeting," no. 5, pp. 1530–1534, 2006.
2. I. A. Satti, D. Ghosh, W. I. W. Yusoff, and M. J. Hoesni, "Origin of Overpressure in a Field in the Southwestern Malay Basin.," *SPE Drill. Complet.*, vol. 30, no. 3, p. 198, 2015.
3. Z. Jincai, "Pore pressure prediction from well logs: Methods, modifications, and new approaches," *Earth-Science Rev.*, vol. 108, no. 1–2, pp. 50–63, 2011.
4. M. Azadpour, N. Shad, and A. Kakhodaie-ilkhchi, "Journal of Petroleum Science and Engineering Pore pressure prediction and modeling using well-logging data in one of the gas fields in south of Iran," *J. Pet. Sci. Eng.*, vol. 128, pp. 15–23, 2015.
5. Z. Wang and R. Wang, "Pore pressure prediction using geophysical methods in carbonate reservoirs: Current status, challenges and way ahead," *J. Nat. Gas Sci. Eng.*, vol. 27, pp. 986–993, 2015.
6. C. M. Bethke, "Inverse hydrologic analysis of the distribution and origin of Gulf Coast-type geopressed zones," *J. Geophys. Res.*, vol. 91, no. B6, p. 6535, 1986.
7. E. J. C. Rijks, "Baram Delta and hydrocarbon occurrences," *Geol. Soc. Malaysia Bull.*, vol. 14, no. December, pp. 1–18, 1981.
8. H. Soleymani, "Pore Pressure Prediction Using Velocity-Based Methods," no. January 2013, pp. 0–28, 2014.
9. R. E. Swarbrick and M. J. Osborne, "Mechanisms that Generate Abnormal Pressures: an Overview," pp. 13–34, 1998.
10. [W. Ismail, W. Yusoff, W. N. Athirah, W. A. Muhaimi, K. Adha, and N. M. Hanapiah, "Role of Thermal Parameters in Modelling Fracture Gradient and Overpressure Mechanism in Southern Part of West Baram Delta, Sarawak, Malaysia*," 2018.
11. [N. M. Hanapiah, W. I. Wan Yusoff, and M. N. A. Zakariah, "Analysis on the overpressure characterization with respect to depositional environment facies: Case Study in Miri Area, Baram Delta," *IOP Conf. Ser. Earth Environ. Sci.*, vol. 88, no. 1, 2017.
12. K. R. P. T I N G Ay, H. Ar, D. R. Hil L I S, and E. S. War Br I C K, "Present-day stress orientation in Brunei: a snapshot of 'prograding tectonics' in a Tertiary delta," 2005.
13. K. Terzaghi, "Theoretical Soil Mechanics," *Theor. Soil Mech.*, 1943.
14. N. C. Dutta and J. Khazanehdari, "Estimation of formation fluid pressure using high-resolution velocity from inversion of seismic data and a rock physics model based on compaction and burial diagenesis of shales," *Lead. Edge (Tulsa, OK)*, vol. 25, no. 12, pp. 1528–1539, 2006.
15. B. A. Eaton, M. Spe-aime, and E. I. Houston, "E-i3rT," 1975.
16. J. Lang, S. Li, and J. Zhang, "Wellbore stability modeling and real-time surveillance for deepwater drilling to weak bedding planes and

depleted reservoirs," in *SPE/IADC Drilling Conference, Proceedings*, 2011, vol. 1, pp. 145–162.

17. J. Zhang, "Earth-Science Reviews Pore pressure prediction from well logs: Methods, modifications, and new approaches," *Earth Sci. Rev.*, vol. 108, no. 1–2, pp. 50–63, 2011.
18. J. Zhang, "Effective stress, porosity, velocity and abnormal pore pressure prediction accounting for compaction disequilibrium and unloading," *Mar. Pet. Geol.*, vol. 45, pp. 2–11, Aug. 2013.

AUTHORS PROFILE



Dejen Teklu Asfha: Dejen has received his B.sc degree in petroleum engineering in 2013 from Mekelle university, Ethiopia. He has joined the same University on the capacity of assistant lecturer and served for 4 years. During his serving as assistant lecturer he has been involved in teaching and researches related to petroleum exploration and production. Dejen is a fulltime M.Sc. student by research in the center of excellence in subsurface seismic imaging and hydrocarbon prediction (CSI) in the department of geosciences at Universiti Teknologi PETRONAS. He won the best presenter award on the conference 'International conference on recent advancements in science and technology' in Kuala Lumpur, Malaysia on 20-22 February 2019. He is expected to defend his research at the end of 2019.



Dr. Haylay Tsegab Gebretsadik: Dr Haylay Tsegab is a Senior lecturer in the Department of Geosciences, Universiti Teknologi PETRONAS (UTP), Malaysia. He has received his PhD in petroleum Geosciences from the same University he is lecturing. Haylay has received MSc degree in Petroleum Geosciences from UTP/IFP, 2009 and BSc degree from Addis Ababa University, Ethiopia (2004) in Geology and Geophysics. Dr Haylay Tsegab is a registered foreign Geologist by the Board of Geologists of Malaysia 2016), a member of Geological Society of Malaysia and member of the International Association of Sedimentologists and serving as national correspondent to Malaysia (2011- present). Prior to his current academic position, he was working as exploration and mining geologist in the Gold mining industry in Ethiopia. Dr Haylay Tsegab taught carbonate sedimentology and petrography, Mineralogy and petrography, Petroleum geochemistry, Basin Analysis and principle of stratigraphy to graduates and postgraduates. His research interests include sedimentology, geochemistry, stratigraphy, mineralogy, reservoir characterization, CO₂ sequestration and basins studies and their application to petroleum exploration and extraction.



Assoc. prof, Wan Ismail Wan Yusoff: Wan Ismail has received BSc in Geology from university of Malaysia and masters from Durham University, England in 1993. His masters research was on Geothermic of the Malay basin, offshore Malaysia. Assoc. Professor in Petroleum Geoscience Department at universiti Teknologi PETRONAS. His research area includes overpressure generation mechanisms, pore pressure prediction, elasticity, hydrocarbon reservoirs, permeability, and porosity of rocks. He has published many researches on overpressure generation mechanisms in Baram Delta province, offshore Sarawak Basin and Malay Basin, in particular, the effect on temperature in overpressure generation. Over 35 citations and 167.1 Total research interest