

FS-920

A4 MONOCHROME PRINTER

▶ print ▶ copy ▶ scan ▶ fax

THE PROFESSIONAL DESKTOP PRINTER WITH LOW NOISE.

In addition to Kyocera's own controller language PRESCRIBE, this high performance printer comes with PCL6 and PostScript 3 emulation. The cost-effective ECOSYS technology ensures long-term gains.

- 18 pages per minute with 1,200 dpi quality
- 250-sheet closed paper cassette with paper gauge
- 3,000 page starter toner
- Easy connection with USB and parallel interfaces
- Powerful controller with 32 MB RAM as standard
- PowerPC 405/266 MHz
- Long-life components



Optional network connectivity means people in a small workgroup can easily share the printer.



A microfine toner with a yield of 6,000 pages minimises user intervention and permits large print runs.



ECOSYS

KYOCERA

FS-920

A4 MONOCHROME PRINTER

ECOSYS ECOSYS devices are designed to minimise both direct costs, such as consumables and indirect cost, such as maintenance administration. The cartridge-free system requires only the toner to be replaced. The modular design concept allows you to add workflow enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

System platform:

The FS-920 offers USB and parallel connectivity as standard as well as optional network connectivity and delivers problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device on the network, from single-user desktop printers to high end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high performance paper handling expertise.

PRESCRIBE IIe:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

KM-NET for Clients/KM-NET Viewer:

The settings of all printers on the network can be checked visually and amended from any Windows® PC. KM-NET for Clients enables easy setup and monitoring of the printer status via parallel, USB or network connection. KM-NET Viewer is an advanced printer management software tool using the standardised protocol SNMP.

GENERAL

Technology: Kyocera ECOSYS, Laser
Engine speed: Max. 18 pages per minute A4
Resolution: 1,200 dpi quality (1,800 x 600)
Time to first page: 11 seconds
Warm-up time: 16 seconds from power off
Duty cycle: Max. 15,000 per month
Max. average 2,000 per month
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 315 W, Stand-by: 8 W, Power-Saving (ECOpower): 4.8 W
Noise (ISO 7779): Printing: 49 dB(A), Stand-by: 28 dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): Main unit: 380 x 390 x 245 mm
Weight: Main unit: 9.2 kg (incl. Toner 9.5 kg)
Certifications: TÜV/GS, CE, PTS
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: Universal paper cassette: 250 sheets, 60–105 g/m², A4, B5, A5, Letter, Legal, Custom (148 x 210 mm to 216 x 356 mm)
Manual feed (tray): 1 sheet, 60–163 g/m², A4, B5, A5, Letter, Legal, Custom (70 x 148 mm to 216 x 356 mm)
Output capacity: 100 sheets face down

CONTROLLER

Processor: Power PC 405/266 MHz
Memory: Standard 32 MB + ECOMemory, max. 288 MB in 1 DIMM slot
Emulations: PCL 6/PCL 5e incl. P.J.L, KPD.L 3 (PostScript 3 compatible), with automatic emulation sensing (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Print features: Manual duplex supported from printer driver

INTERFACES

Standard interface: High speed bi-directional parallel (IEEE 1284), USB 2.0 (Full speed)
Multiple Interface Connection (MIC): Allows simultaneous data transfer via up to two interfaces, with each interface having its own virtual printer.

CONSUMABLES

TK-110 Toner-kit: Microfine toner for 6,000 pages in accordance with ISO/IEC 19752
TK-110E Toner-kit: Microfine toner for 2,000 pages in accordance with ISO/IEC 19752

Capacity of starter toner is 3,000 pages in accordance with ISO/IEC 19752

WARRANTY

2-year warranty as standard. Kyocera guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

KYO LIFE KYOlife 3-year on-site warranty for extension for printer and options.

MODEL CONFIGURATIONS



Your Kyocera Business Partner:

pureprint™



CarbonNeutral® company

Printed by Beacon Press, a CarbonNeutral® company using their pureprint® environmental print technology.

KYOCERA MITA (UK) Ltd, 8 Beacontree Plaza, Gillette Way, READING RG2 0BS
Tel: 0118 931 1500, Fax: 0118 931 1108, email: info@kyoceramita.co.uk, www.kyoceramita.co.uk

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

