

Front & Rear Back Up Sensors



LED Display with Buzzer - Obstacle Distance & Visual Readout

Key Features:

- Multiple mounting options
- Volume control
- Distance displayed with color distance bar indicators

You have the option to upgrade to a visual kit, which includes everything in the standard ParkAlert kits as well as PA-DISPLAY, which gives off both an audible and visual alert for object detection.

Key Features of front and rear ParkAlert sensors kits:

- Front Sensors Detection Range: 0 m/ft to 0.75 m/2.5 ft
- Rear Sensors Detection Range: 0 m/0ft to 1.6 m/5.2 ft
- Volume control/Mute ability
- Plastic bumper friendly

- Compatible with metal bumpers when used with rubber sleeves
- Paintable for a perfect match
- IP67 water/debris-proof rating
- Operating temp: -30°C to 80°C







Color	Four Front Sensors (with speaker)	Four Rear Sensors (with speaker)
Matte Black	PS-FBP-M	PS-RBP-M



TRUCK SENSOR KIT ALSO AVAILABLE

PS-TRUCK-M

UNIVERSAL CAMERAS

Part Number	Viewing Angle	Sensor Type	LUX Rating	IP Rating	Parking Lines	Image Type	Product Photo
PHDCAM10U	170°	1/3" CMOS	0	IP67	Selectable	Mirrored/non-mirrored (selectable)	
PCAM-201-N	170°	1/4" CMOS	0.5	IP67	Selectable	Mirrored/non-mirrored (selectable)	
PCAM-360-N	170°	1/4" CMOS	0.3	IP67	Selectable	Mirrored/non-mirrored (selectable)	
PCAM-110-N	170°	1/4" CMOS	0.5	IP67	Selectable	Mirrored/non-mirrored	
PCAM-BS1-N	80°	1/4" CMOS	0.1	IP67	Selectable	Mirrored/non-mirrored (Mirrored)	
CAM-WLP	140°	1/3" CMOS	0.1	IP67	Selectable	Mirrored/non-mirrored (Mirrored)	

CALL FOR ADDITIONAL MODELS