COMMERCIAL DISPLAY



M2901S



29" LONG STRETCHED DISPLAY

Information, advertisements and broadcast content reinvented. The distinctively versatile M2901S LCD Stretch Screen is approximately half the height of a traditional LCD display allowing for a variety of installation options from stadiums, airport terminals and retail environments to smaller spaces and rooms with low ceilings, where a traditional monitor would be too large. Liven up a store front with striking product ads. Enhance a directory in a lobby or flight information with animated content. Whatever the task, stretch your possibilities with the M2901S Stretch Screens.

SPECIFICATIONS

Clear Voice II

Sound Mode

WARRANTY	3 Year Swap Out
MODEL INFO	
Screen Size (inches)	
Panel Technology	
- and recinology	
PANEL SPECIFICATION	_
Aspect Ratio	17:6
Resolution	1366 x 480
Pixels (H x V x 3)	1,967,040
Brightness (cd/m²)	420
Contrast Ratio	1,200:1
Viewing Angle Degree	178 / 178
Colour Depth	16.7M
Response Time(GTG)	8ms
Surface Treatment	Haze 10%, Hard Coating (3H)
Life time	50,000 Hr
Orientation	Landscape
VIDEO	
Max Input Resolution	1360 x 768 @ 60Hz (RGB, HDMI/DVI)
Recommended Resolution	1360 x 480 @ 60Hz (RGB, HDMI/DVI)
H-Scanning Frequency	28 ~ 70kHz (RGB, HDMI/DVI)
V-Scanning Frequency	57~63Hz(RGB, HDMI/DVI)
Pixel Frequency	80MHz(Max)
Sync Compatability	Separate / Composite / Digital
Video Input	RGB, HDMI/DVI
Picture Mode	
Colour Temperature Control	User / Cool / Normal / Warm
CONNECTIVITY	
Input (Rear)	
Digital	HDMI/DVI with HDCP
Analog	 RGB
Audio	
External Control	RS232C, RJ45, External IR
USB	
HDTV Formats	HDMI :480i / 480p / 576i / 576p / 720p / 1080i
Output (Rear)	
Digital	
Analog	RGB
Audio	
External Control	RS232C
ALIDIO	
Auto Volume	N/A
Balance	
Audio Power	
Speaker On/Off	
Speaker On/OH	

For more information please visit: www.lg.com/uk/it-products

N/A

N/A

COMMERCIAL DISPLAY



M2901S



SPECIFICATIONS

<u> </u>	
SPECIAL FEATURES	
Temperature Sensor	No
Auto Bright Sensor	No
Cooling Fan	No
Tile Mode	No
Natural Mode @ Tile Mode	No
Image Zoom	No
Source Selection	HDMI/DVI, RGB
Brightness/Contrast/Backlight	Yes
Position/Size	Yes
Auto config/Phase	Yes
Language (OSD)	English, Chinese
Language (USB Playback)	N/A
ISM Method	Normal, Orbite, White wash
Advanced	No
Time	Clock Hour / Clock Minute / Week Day / On/Off timer /
	Sleep timer / Auto Sleep / Power Saving
Information	Source / Resolution / H Frequency /
	V Frequency / Software Version
Input Label	No
Auto Power/Source Memory	Yes
Key Lock	Yes
DPM Select	Yes
Energy Saving	Yes, Level1 / Level2 / Level3
Power Indicator On/Off	Yes
Logo Light On/Off	No
File Play with USB	No
PIP/PBP	No
POWER	
Power Supply	100-240V, 50/60Hz
Power Type	Built-in Power
Power Switch	Yes
Power Consumption (Max)	90W
Power Consumption (Normal)	80W
Power Consumption (Power Off)	0.5W
CABINET DESCRIPTION	
Colour	Black
Bezel Witdth	Top/Bottom(32.8575mm), Left/Right(30.32mm)
VESA Compatible	400 x 200
STANDARD (CERTIFICATION)	
Safety	UL / c-UL / CB / TUV / CCC
EMC	FCC / CE / C-tick
ErP / Energy Star	ErP(Yes), Energy Star(No)
DIMENSIONS	
Weight (Kg	
SET (w/o stand)	11
Including stand	N/A
Packing	13.18
WxHxD (mm)	
SET (w/o stand)	763.4 x 305.8 x 85.5
Including stand	N/A
Packing (w/ stand)	864 x 447 x 196

For more information please visit: www.lg.com/uk