



CoreView G4 RC420B

RC420V G4 LED38/840 W30L120 PSU

CoreView G4 RC420B, 111 lm/W, 840 neutral white

RC420B G4 inherits the elegant and classic indirect light design from previous generation but with slimmer outlook. It offers 3 types, 600x600, 300x1200, and 600x1200 (Customized offer)mm with max: 108lm/w. Air slot option applies to 600x1200mm type to give fast and easy support to the projects where air outlet is required from the office lighting fittings. Full indirect light design provides visual comfort in the office area as well.

Product data

General Information		Number of products on MCB of 16 A type B 40	
Color Code	840 neutral white		
Light source engine type	LED	Temperature	
Value ladder	Performance	Ambient temperature range	-20 to +45 °C
CE mark	CE mark	Controls and Dimming	
Light Technical		Dimmable	No
Luminous Flux	4,000 lm	Control interface	-
Correlated Color Temperature (Nom)	4000 K	Mechanical and Housing	
Luminous Efficacy (rated) (Nom)	111 lm/W	Housing Material	Steel
Color rendering index (CRI)	>80	Optical cover material	-
Light source color	840 neutral white	Housing Color	White RAL 9003
Optical cover type	-	Optical cover finish	-
Operating and Electrical		Approval and Application	
Input Voltage	220 to 240 V	Ingress protection code	IP20 [Finger-protected]
Line Frequency	50 or 60 Hz	Mech. impact protection code	-
Power Consumption	36 W		
Power Factor (Fraction)	0.9		

CoreView G4 RC420B

Protection class IEC	Safety class II
----------------------	-----------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	RC420V G4 LED38/840 W30L120 PSU
--------------------	---------------------------------

Full product name	RC420V G4 LED38/840 W30L120 PSU
-------------------	---------------------------------

Order code	911401594071
------------	--------------

Material Nr. (12NC)	911401594071
---------------------	--------------

Numerator - Quantity Per Pack	1
-------------------------------	---

Numerator - Packs per outer box	2
---------------------------------	---

Dimensional drawing

