

PRODUCT-DETAILS

CPC12/50M

12MM POLYESTER CONDUIT



General Information

Extended Product Type	CPC12/50M
Product ID	7TCA298000R0006
EAN	5020963785856
Catalog Description	12MM POLYESTER CONDUIT
Long Description	Flame Retardant, Highly Flexible Conduit, NC Size 12/NW Size 10, Outside Diameter 13.0mm, Inside Diameter 9.4mm, Static Bend Radius 25mm, Very High UV Resistance and Fatigue Life, IP40 Rating, FR Co-Polyester, Reel Length 50 Meters, Black

Ordering

EAN	5020963785856
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	4.42 lb 2.005 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	15.75 in 400 mm

Package Level 1 Height	5.12 in 130 mm
Package Level 1 Depth / Length	15.75 in 400 mm
Package Level 2 Units	66 piece
Package Level 2 Width	39.37 in 1000 mm
Package Level 2 Height	46.46 in 1180 mm
Package Level 2 Depth / Length	47.24 in 1200 mm

Additional Information

Application	Ideal for Harness Applications Such as Engine, Body Section and Chassis. CPC is Resistant to Hydrocarbons, Greases, Fuels and Oils
Brand / Label	Harnessflex
Color	Black
Flexibility	Very High
Inside Diameter	9.4 mm
Material	Fire Resistant Co-Polyester
Nominal Size	NC12/NW10
Number of Batteries	0
Outside Diameter	13.0 mm
Product Name	HARNESSFLEX
Product Type	Flame Retardant Conduit
Radius	Static: 25 mm
Standards	RoHS, Conforms with end of life vehicle directive (ELV)EU200/53/EC
UPC	786210273679

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CPC12/50M
Declaration of Conformity - CE	9AKK107492A9616
Instructions and Manuals	CPC12/50M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5540 >> Flexible Non-Metallic Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

