



<b>Type:</b>	<b>57670</b>	<b>Systems to charge:</b>	<b>Ni-MH</b>
Designation:.....	<b>Plug Charger</b>	Cell sizes:.....	AAA, AA
		Cell Configurations:.....	AAA, AA, 2/4 pcs.

<b>Dimensions:</b>	<b>Charger:</b>
Length:.....	115± 1mm
Width:.....	30± 1mm(without plug); 68 (with plug)
Height:.....	70± 1mm
Weight:.....	120 g

<b>Charging methods:</b>	<b>AC 100-240V 50/60Hz</b>	<b>Maintenance Charge:</b>
AA:.....	Current: 450 mA ± 10%	Current: 0mA
AAA:.....	Current: 200 mA ±10%	Current: 0 mA

<b>Housing:</b>	<b>Indications: LCD display</b>
Housing Material:..... ABS	AAA, AA, cell mix:..... Rolling bars = charging Bars fixed = charging finished Battery symbol flash = short circuit or bad cell
Casing color:..... silver	

<b>Protective Functions:</b>	<b>Power:</b>
	Primary:..... 100-240 VAC 50/60 Hz
	Secondary:..... 2 X 2.8V

<b>Cut off criteria:</b>	
Ni-MH standard cells:...	Timer: backup timer 6.5 hours dV (Delta V): 10±2mV

**No publication or circulation of data to third parties without consent of VARTA Consumer Batteries**