



<https://www.mega-piles.com/>



Type: **57677**
Designation:..... **LCD Plug Charger**

Systems to charge: **Ni-MH**
Cell sizes:..... AAA, AA, 9V
Cell Configurations:..... AAA, AA 2/4 pcs.
Cell Configurations:..... 9V 1 pcs

Dimensions: **Charger:**

Lenght:..... 115mm
Widht:..... 77mm
Height:..... 57mm
Weight:..... 138g

Charging methods: **AC 220-240V 50Hz**

AA:..... Current: 450 mA ± 10%
AAA:..... Current: 200 mA ±10%
9V:..... Current: 34 mA ±10%
5V USB:..... Current: 900 mA ±10%

Housing:

Housing Material:..... PC945
Casing color:..... Black

Indications: LCD display

AAA, AA,cell mix:..... 1st bar flashing <1.39V
AAA, AA,cell mix:..... 1st bar solid and 2nd bar flashing <1.41V
AAA ,AA,cell mix:..... 1st and 2nd bars solid and 3th bar flashing <1.45V
AAA ,AA,cell mix:..... <1.45V
AAA ,AA,cell mix:..... 1st, 2nd and 3th bars solid and 4th bar flashing <1.54V
AAA ,AA,cell mix:..... All bars are solid : -dv

Protective Functions:

Reverse protection Mechanical arrangement
Short circuit protection No current , LCD flash

Power:

Primary:..... 200-240V AC 50Hz
Secondary:..... 2.8V

Cut off criteria:

Ni-MH standard cells:... Timer: backup timer 6.5 hours
-DV: 10mV +/- 2mV / Channel, function immediately
Vmax: >1.65V

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries