FLEXI GLUE



ACESSORIES Line

Ref V00131 EAN13 - 5600217588398

Box - 21 x 16 x 24 cm Weight - 4.5 Kg

Each Strip-1x1000cm; 5mm(Thickness)

Units per box - 1



FEATURES Flexi Glue

Vicoustic's Flexi Glue is designed for use with a variety of materials. Its chemical composition is non aggressive, and therefore certified in accordance with the moie is also perfect for use with polyurethane (foam) or polystyrene (EPS) Vicoustic solutions, ensuring their correct and safe application to a room's surfaces.

Flexi Glue was designed in collaboration with leading chemical industry professionals. Testing has revealed excellent strength and versatility when applied to a range of materials.

TECHNICAL DATA Flexi Glue

Base	Styrene caoutchouc, containing solvent, toluene-free		
Colour	Beige		
Density	1,15	g/cm ³	DIN 53479, bei 23°C
Consistency	pasty		
Slump	4	mm	according ASTM
Solid content	75	%	
Shear strenght	0,25	N/mm ²	after 3 days; PVC/PVC
Open time	1	min	

PROCESSING Flexi Glue

Preparation The surfaces to be bonded must be dry, clean and free of dust and grease.

Preparation: The surfaces to be borded must be dry, stear and rec or dust and grease.

Preparation: The surfaces to be borded must be dry, stear and rec or dust and grease.

Bonding: Apply the adhesive evenly with hand or pressure guns on the surfaces to be borded. Join them immediately. The layer thickness depends on the consistency of the materials to be bonded. Join them immediately. The layer thickness depends on the consistency of the materials to be bonded. Unliateral application is skin on the surface of the adhesive layer. Prossibile. Matris surfaces, join the sparas of the skin on the surface of the adhesive layer. Press well. Make sure that both surfaces are well wetted.