



Product Overview

19.06.2017 English Americas






Intelligent IP Video Solutions



Professional Video Systems Outdoor

MOBOTIX

M16 AllroundDual Camera „Mx6“

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-M16A	4047438027724	34,5 cm	C
	M16 Body, For M16/M15 Sensor Modules (Day/Night) M16 camera module for connecting one or two M16/m15 sensor modules (to be ordered individually) • Mx6 system platform with H.264, MxPEG and M-JPEG • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	85258091 2.100 g	34,0 cm 20,0 cm 23,5 l	
	Mx-M16A-6D6N041	4047438027731	34,5 cm	C
	M16 Complete Cam 6MP, 2x B041 (Day & Night) IP camera set with two installed sensor modules • Mx6 system platform with H.264, MxPEG and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box	85258091 2.400 g	34,0 cm 20,0 cm 23,5 l	
	Mx-M16A-6D6N079	4047438027748	34,5 cm	C
	M16 Complete Cam 6MP, 2x B079 (Day & Night) IP camera set with two installed sensor modules • Mx6 system platform with H.264, MxPEG and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B079 standard (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box	85258091 2.400 g	34,0 cm 20,0 cm 23,5 l	

S16 DualFlex Camera „Mx6“

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-S16A	4047438027885	22,5 cm	C
	S16 Body, For S16/S15 Sensor Modules (Day/Night/Thermal) S16 camera module (body) for connecting one or two S16/S15 sensor modules (to be ordered individually) • Mx6 system platform with H.264, MxPEG and M-JPEG • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP65, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), USB, Audio (I/O), RS232 via MX Interface Box	85258091 660 g	19,2 cm 8,5 cm 3,7 l	
	Mx-S16A-S1	4047438027854	34,5 cm	C
	S16 Complete Cam, Set 1, 6MP, 1x B016 (Day) S16 camera module (body), Mx6 system platform with H.264, MxPEG and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome • IP66 • Optional connection of a second sensor module (incl. Thermal)	85258091 720 g	34,0 cm 16,0 cm 18,8 l	
	Mx-S16A-S2	4047438027861	34,5 cm	C
	S16 Complete Cam, Set 2, 6MP, 2x B016 (Day) S16 camera module (body), Mx6 system platform with H.264, MxPEG and M-JPEG • 2x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	85258091 1.700 g	34,0 cm 16,0 cm 18,8 l	
	Mx-S16A-S3	4047438027878	34,5 cm	C
	S16 Complete Cam, Set 3, 6MP, 2x B016 (Day & Night) S16 camera module (body), Mx6 system platform with H.264, MxPEG and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	85258091 1.700 g	34,0 cm 16,0 cm 18,8 l	

V16 Vandalism Camera „Mx6“




	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-V16A-6D041	4047438027892	26,0 cm	C
	V16 Complete Cam 6MP, 1x B041 (Day) V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B041 (f/1.8, horiz. image angle 90°) • Mx6 system platform with H.264, MxPEG and M-JPEG • 3-5 mm stainless steel casing • IK10+//IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm	
	Mx-V16A-6D079	4047438027939	26,0 cm	C
	V16 Complete Cam 6MP, B079 (Day) V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B079 (f/1.8, horiz. image angle 45°) • Mx6 system platform with H.264, MxPEG and M-JPEG • 3-5 mm stainless steel casing • IK10+//IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm	
	Mx-V16A-6D6D041	4047438027908	26,0 cm	C
	V16 Complete Cam 6MP, 2x B041 (Day) V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x Color (day), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • Mx6 system platform with H.264, MxPEG and M-JPEG • 3-5 mm stainless steel casing • IK10+//IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm	
	Mx-V16A-6D6D079	4047438027946	26,0 cm	C
	V16 Complete Cam 2x 6MP, 2x B079 (Day) V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • Mx6 system platform with H.264, MxPEG and M-JPEG • 3-5 mm stainless steel casing • IK10+//IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm	
	Mx-V16A-6D6N041	4047438027915	26,0 cm	C
	V16 Complete Cam 2x 6MP, 2x B041 (Day & Night) V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • Mx6 system platform with H.264, MxPEG and M-JPEG • 3-5 mm stainless steel casing • IK10+//IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm	
	Mx-V16A-6D6N079	4047438027953	26,0 cm	C
	V16 Complete Cam 2x 6MP, 2x B079 (Day & Night) V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • Mx6 system platform with H.264, MxPEG and M-JPEG • 3-5 mm stainless steel casing • IK10+//IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm	
	Mx-V16A-6N6N041	4047438027922	26,0 cm	C
	V16 Complete Cam 2x 6MP, 2x B041 (Night) V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • Mx6 system platform with H.264, MxPEG and M-JPEG • 3-5 mm stainless steel casing • IK10+//IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm	

**Mx-V16A-6N6N079****V16 Complete Cam 2x 6MP, 2x B079 (Night)**



V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • Mx6 system platform with H.264, MxPEG and M-JPEG • 3-5 mm stainless steel casing • IK10+•+/IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing

4047438027960	26,0 cm	C
85258091	26,0 cm	
4.700 g	26,0 cm	
	17,6 l	



M26 Allround Camera „Mx6“

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-M26A-6D	4047438027977	30,5 cm	C
	M26 Body 6MP (Day)	85258091	24,0 cm	
	IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	2.000 g	16,5 cm	12,1 l
	Mx-M26A-6D016	4047438027991	30,5 cm	C
	M26 Complete Cam 6MP, B016 (Day)	85258091	24,0 cm	
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	2.000 g	16,5 cm	12,1 l
	Mx-M26A-6N	4047438027984	30,5 cm	C
	M26 Body 6MP (Night)	85258091	24,0 cm	
	IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	2.000 g	16,5 cm	12,1 l



D26 Allround Camera „Mx6“

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-D26A-6D	4047438028233	30,5 cm	C
	D26 Body 6MP (Day) D26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091	24,0 cm	
		1.580 g	16,5 cm	12,1 l
	Mx-D26A-6N	4047438028240	30,5 cm	C
	D26 Body 6MP (Night) D26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091	24,0 cm	
		1.580 g	16,5 cm	12,1 l




Q26 Hemispheric Camera „Mx6“

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-Q26A-6D016	4047438028219	30,5 cm	C
	Q26 Complete Cam 6MP, B016 (Day)	85258091	24,0 cm	
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.630 g	16,5 cm	12,1 l
	Mx-Q26A-6N016	4047438028226	30,5 cm	C
	Q26 Complete Cam 6MP, B016 (Night)	85258091	24,0 cm	
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.630 g	16,5 cm	12,1 l


S26 Flex Camera „Mx6“

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-S26A-6D016	4047438028370	22,5 cm	C
	S26 Complete Cam 6MP, B016 (Day)	85258091	19,2 cm	
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	712 g	8,5 cm	3,7 l
	Mx-S26A-6N016	4047438028387	225,0 cm	C
	S26 Complete Cam 6MP, B016 (Night)	85258091	19,2 cm	
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, BW (night) • Mx6 system platform with H.264, MxPEG and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	712 g	8,5 cm	36,7 l

M15 AllroundDual Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-M15D-Sec	4047438018258	34,5 cm	C
	M15 Body, For 1–2 Sensor Modules (Day/Night) M15 camera module for connecting one or two sensor modules (to be ordered individually) • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB, IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-5M-Blind-PW)	85258091 2.100 g	34,0 cm 20,0 cm 23,5 l	
	MX-M15D-Sec-DNIGHT-D22N22-6MP-F1.8	4047438023009	34,5 cm	C
	M15 Complete Cam 6MP, 2x B041 (Day & Night) IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L22/B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB, IO and RS232 via additional MX Interface Box	85258091 2.510 g	34,0 cm 20,0 cm 23,5 l	
	MX-M15D-Sec-DNIGHT-D43N43-6MP-F1.8	4047438023023	34,5 cm	C
	M15 Complete Cam 6MP, 2x B079 (Day & Night) IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L43/B079 standard (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB, IO and RS232 via additional MX Interface Box	85258091 2.510 g	34,0 cm 20,0 cm 23,5 l	








D15 DualDome Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-D15Di-Sec	4047438017978	34,5 cm	C
	D15 Body, For D16/D15 Sensor Modules (Day/Night)	85258091	34,0 cm	
	IP camera module for connecting one or two sensor modules or a sensor bridgeFIX/PAN (to be ordered individually) • Image sensor options (via lens unit/carrier): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): horizontal image angle from 103° to 15° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Incl. Standard lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.980 g	16,0 cm	
			18,8 l	

S15 FlexMount Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-S15D-Sec	4047438017725	22,5 cm	C
	S15D Body, For 1–2 Sensor Modules (Day/Night/Thermal) S15D camera module (body) for connecting one or two sensor modules (to be ordered individually) • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP65, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), MxBus, USB, Audio (I/O), RS232 via MX Interface Box • Connection of MOBOTIX Door Station modules	85258091 704 g	19,2 cm 8,5 cm 3,7 l	
	MX-S15D-Set1-6MP	4047438023313	34,5 cm	C
	S15D Complete Cam, Set 1, 6MP, 1x B016 (Day) S15D camera module (body) • 1x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome • IP66 • Optional connection of a second sensor module (incl. Thermal) or MOBOTIX Door Station modules	85258091 1.670 g	34,0 cm 16,0 cm 18,8 l	
	MX-S15D-Set2-6MP	4047438023320	34,5 cm	C
	S15D Complete Cam, Set 2, 6MP, 2x B016 (Day) S15D IP camera module (body) • 2x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66 • Connection of MOBOTIX Door Station modules	85258091 1.670 g	34,0 cm 16,0 cm 18,8 l	
	MX-S15D-Set3-6MP	4047438023337	34,5 cm	C
	S15D Complete Cam, Set 3, 6MP, 2x L10 (Day & Night) S15D camera module (body) • 1x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66 • Connection of MOBOTIX Door Station modules	85258091 1.670 g	34,0 cm 16,0 cm 18,8 l	
	MX-S15-D016	4047438026833	22,5 cm	C
	S15M Complete Cam 6MP, B016 (Day) Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65/IK06, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB, I/O and RS232 via Interface Box (MOBOTIX accessory) • Connection of MOBOTIX Door Station modules	85258091 720 g	19,2 cm 8,5 cm 3,7 l	
	MX-S15-N016	4047438026840	22,5 cm	C
	S15M Complete Cam 6MP, B016 (Night) Hemispheric IP camera with 6 Megapixel Moonlight Sensor, BW (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65/IK06, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB, I/O and RS232 via Interface Box (MOBOTIX accessory) • Connection of MOBOTIX Door Station modules	85258091 720 g	19,2 cm 8,5 cm 3,7 l	

V15 Vandalism Camera




	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-V15M-Sec-D22-6MP-F1.8	4047438024310	26,0 cm	C
	V15 Complete Cam 6MP, 1x B041, Day V15 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+ /IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing	85258091 4.680 g	26,0 cm 26,0 cm	17,6 l
	MX-V15M-Sec-D43-6MP-F1.8	4047438024327	26,0 cm	C
	V15 Complete Cam 6MP, 1x B079, Day V15 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens L22/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+ /IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing	85258091 4.680 g	26,0 cm 26,0 cm	17,6 l
	MX-V15D-Sec-D22D22-6MP-F1.8	4047438024334	26,0 cm	C
	V15 Complete Cam 2x 6MP, 2x B041, Day V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+ /IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing	85258091 4.680 g	26,0 cm 26,0 cm	17,6 l
	MX-V15D-Sec-DNight-D22N22-6MP-F1.8	4047438024372	26,0 cm	C
	V15 Complete Cam 2x 6MP, 2x B041, Day & Night V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+ /IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing	85258091 4.680 g	26,0 cm 26,0 cm	17,6 l
	MX-V15D-Sec-Night-N22N22-6MP-F1.8	4047438024358	26,0 cm	C
	V15 Complete Cam 2x 6MP, 2x B041, Night V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+ /IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing	85258091 4.680 g	26,0 cm 26,0 cm	17,6 l
	MX-V15D-Sec-D43D43-6MP-F1.8	4047438024341	26,0 cm	C
	V15 Complete Cam 2x 6MP, 2x B079, Day V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+ /IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing	85258091 4.680 g	26,0 cm 26,0 cm	17,6 l
	MX-V15D-Sec-DNight-D43N43-6MP-F1.8	4047438024389	26,0 cm	C
	V15 Complete Cam 2x 6MP, 2x B079, Day & Night V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+ /IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing	85258091 4.680 g	26,0 cm 26,0 cm	17,6 l

**MX-V15D-Sec-Night-N43N43-6MP-F1.8****V15 Complete Cam 2x 6MP, 2x B079, Night**



V15D Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+•+/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

4047438024365	26,0 cm	C
85258091	26,0 cm	
4.680 g	26,0 cm	
	17,6 l	



M25 Allround Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-M25-BOD1	4047438024891	30,5 cm	C
	M25 Body 6MP, Day IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	85258091	24,0 cm	
		2.000 g	16,5 cm	12,1 l
	MX-M25-BOD1-N	4047438024907	30,5 cm	C
	M25 Body 6MP, Night IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	85258091	24,0 cm	
		2.000 g	16,5 cm	12,1 l
	MX-M25-D016	4047438024914	30,5 cm	C
	M25 Complete Cam 6MP, B016, Tag Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	85258091	24,0 cm	
		2.000 g	16,5 cm	12,1 l

D25 Dome Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-D25-BOD1	4047438025249	30,5 cm	C
	D25 Body 6MP, Day D25 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB, I/O and RS232 via Interface Box (MOBOTIX accessory)	85258091	24,0 cm	
		1.580 g	16,5 cm	12,1 l
	MX-D25-BOD1-N	4047438025256	30,5 cm	C
	D25 Body 6MP, Night D25 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB, I/O and RS232 via Interface Box (MOBOTIX accessory)	85258091	24,0 cm	
		1.580 g	16,5 cm	12,1 l

Q25 Hemispheric Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-Q25-D016	4047438025829	30,5 cm	C
	Q25 Complete Cam 6MP, B016, Day	85258091	24,0 cm	
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB, I/O and RS232 via Interface Box (MOBOTIX accessory) • Color: white	1.630 g	16,5 cm	12,1 l
	MX-Q25-N016	4047438025843	30,5 cm	C
	Q25 Complete Cam 6MP, B016, Night	85258091	24,0 cm	
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB, I/O and RS232 via Interface Box (MOBOTIX accessory) • Color: white	1.630 g	16,5 cm	12,1 l















Intelligent IP Video Solutions



Professional Video Systems Indoor

MOBOTIX

c26 Indoor Camera „Mx6“








	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
 	Mx-c26A-6D016	4047438028677	17,5 cm	C
	c26 Complete Cam 6MP, B016, Day Hemispheric IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	85258091	14,0 cm	
		400 g	13,5 cm	
			3,3 l	
 	Mx-c26A-6D036	4047438028684	17,5 cm	C
	c26 Complete Cam 6MP, B036, Day IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	85258091	14,0 cm	
		400 g	13,5 cm	
			3,3 l	
 	Mx-c26A-6N016	4047438028691	17,5 cm	C
	c26 Complete Cam 6MP, B016, Night Hemispheric IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	85258091	14,0 cm	
		400 g	13,5 cm	
			3,3 l	
 	Mx-c26A-6N036	4047438028714	17,5 cm	C
	c26 Complete Cam 6MP, B036, Night IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	85258091	14,0 cm	
		400 g	13,5 cm	
			3,3 l	
 	Mx-c26A-AU-6D016	4047438028707	17,5 cm	C
	c26 Complete Cam 6MP, B016, Day, Audio Package Hemispheric IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	85258091	14,0 cm	
		400 g	13,5 cm	
			3,3 l	
 	Mx-c26A-AU-6D036	4047438028721	17,5 cm	C
	c26 Complete Cam 6MP, B036, Day, Audio Package IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	85258091	14,0 cm	
		400 g	13,5 cm	
			3,3 l	
 	Mx-c26A-AU-6N016	4047438028738	17,5 cm	C
	c26 Complete Cam 6MP, B016, Night, Audio Package Hemispheric IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	85258091	14,0 cm	
		400 g	13,5 cm	
			3,3 l	

**Mx-c26A-AU-6N036****c26 Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438028745	17,5 cm	C
85258091	14,0 cm	
400 g	13,5 cm	
	3,3 l	

i26 Indoor Camera „Mx6“








	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-i26A-6D016	4047438028592	17,5 cm	C
	i26 Complete Cam 6MP, B016, Day	85258091	14,0 cm	
	Hemispheric IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	420 g	13,5 cm	3,3 l
	Mx-i26A-6D036	4047438028608	17,5 cm	C
	i26 Complete Cam 6MP, B036, Day	85258091	14,0 cm	
	IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	420 g	13,5 cm	3,3 l
	Mx-i26A-6N016	4047438028622	17,5 cm	C
	i26 Complete Cam 6MP, B016, Night	85258091	14,0 cm	
	Hemispheric IP indoor camera for wall mounting • Mx6 system platform with H.264, M-JPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	420 g	13,5 cm	3,3 l
	Mx-i26A-6N036	4047438028639	17,5 cm	C
	i26 Complete Cam 6MP, B036, Night	85258091	14,0 cm	
	IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	420 g	13,5 cm	3,3 l
	Mx-i26A-AU-6D016	4047438028615	17,5 cm	C
	i26 Complete Cam 6MP, B016, Day, Audio Package	85258091	14,0 cm	
	Hemispheric IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	420 g	13,5 cm	3,3 l
	Mx-i26A-AU-6D036	4047438028646	17,5 cm	C
	i26 Complete Cam 6MP, B036, Day, Audio Package	85258091	14,0 cm	
	IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	420 g	13,5 cm	3,3 l
	Mx-i26A-AU-6N016	4047438028653	17,5 cm	C
	i26 Complete Cam 6MP, B016, Night, Audio Package	85258091	14,0 cm	
	Hemispheric IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	420 g	13,5 cm	3,3 l

**Mx-i26A-AU-6N036****i26 Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438028660	17,5 cm	C
85258091	14,0 cm	
420 g	13,5 cm	
	3,3 l	

p26 Indoor Camera „Mx6“






	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-p26A-6D	4047438028462	17,5 cm	C
	p26 Body 6MP, Day	85258091 480 g	14,0 cm 3,3 cm 0,8 l	
<p>p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>				
	Mx-p26A-6D016	4047438028448	17,5 cm	C
	p26 Complete Cam 6MP, B016, Day	85258091 480 g	14,0 cm 3,3 cm 0,8 l	
<p>Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>				
	Mx-p26A-6N	4047438028479	17,5 cm	C
	p26 Body 6MP, Night	85258091 480 g	14,0 cm 3,3 cm 0,8 l	
<p>p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>				
	Mx-p26A-6N016	4047438028530	17,5 cm	C
	p26 Complete Cam 6MP, B016, Night	85258091 480 g	14,0 cm 3,3 cm 0,8 l	
<p>Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>				
	Mx-p26A-AU-6D	4047438028752	17,5 cm	C
	p26 Body 6MP, Day, Audio Package	85258091 480 g	14,0 cm 3,3 cm 0,8 l	
<p>p26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>				
	Mx-p26A-AU-6D016	4047438028486	17,5 cm	C
	p26 Complete Cam 6MP, B016, Day, Audio Package	85258091 480 g	14,0 cm 3,3 cm 0,8 l	
<p>Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>				
	Mx-p26A-AU-6N	4047438028585	17,5 cm	C
	p26 Body 6MP, Night, Audio Package	85258091 480 g	14,0 cm 3,3 cm 0,8 l	
<p>p26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • Lens to be ordered individually (B036 to B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>				

**Mx-p26A-AU-6N016****p26 Complete Cam 6MP, B016, Night, Audio Package**








Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438028561	17,5 cm	C
85258091	14,0 cm	
480 g	3,3 cm	
	0,8 l	




v26 Indoor Dome Camera „Mx6“

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-v26A-6D	4047438028394	20,5 cm	C
	v26 Body 6MP, Day, White	85258091	19,8 cm	
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: white	690 g	12,3 cm	5,0 l
	Mx-v26A-6D-b	4047438028424	20,5 cm	C
	v26 Body 6MP, Day, Black	85258091	19,8 cm	
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: black	690 g	12,3 cm	5,0 l
	Mx-v26A-6D036	4047438028417	20,5 cm	C
	v26 Complete Cam 6MP, B036, Day, White	85258091	19,8 cm	
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: white	700 g	12,3 cm	5,0 l
	Mx-v26A-6N	4047438028400	20,5 cm	C
	v26 Body 6MP, Night, White	85258091	19,8 cm	
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: white	690 g	12,3 cm	5,0 l
	Mx-v26A-6N-b	4047438028431	20,5 cm	C
	v26 Body 6MP, Night, Black	85258091	19,8 cm	
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: black	690 g	12,3 cm	5,0 l















c25 Indoor Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
 	MX-c25-D016	4047438026611	17,5 cm	C
	c25 Complete Cam 6MP, B016, Day	85258091	14,0 cm	
	Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,5 cm	3,3 l
 	MX-c25-D036	4047438026635	17,5 cm	C
	c25 Complete Cam 6MP, B036, Day	85258091	14,0 cm	
	IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,5 cm	3,3 l
 	MX-c25-N016	4047438026628	17,5 cm	C
	c25 Complete Cam 6MP, B016, Night	85258091	14,0 cm	
	Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,5 cm	3,3 l
 	MX-c25-D016-AUD	4047438026659	17,5 cm	C
	c25 Complete Cam 6MP, B016, Day, Audio Package	85258091	14,0 cm	
	Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,5 cm	3,3 l



i25 Indoor Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-i25-D016	4047438026697	17,5 cm	C
	i25 Complete Cam 6MP, B016, Day Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	85258091	14,0 cm	
		420 g	13,5 cm	3,3 l
	MX-i25-D036	4047438026710	17,5 cm	C
	i25 Complete Cam 6MP, B036, Day IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	85258091	14,0 cm	
		420 g	13,5 cm	3,3 l
	MX-i25-D016-AUD	4047438026734	17,5 cm	C
	i25 Complete Cam 6MP, B016, Day, Audio Package Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	85258091	14,0 cm	
		420 g	13,5 cm	3,3 l

p25 Indoor Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
 	MX-p25-BOD1 p25 Body 6MP, Day p25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	4047438026482 85258091 480 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	C
 	MX-p25-BOD1-N p25 Body 6MP, Night p25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	4047438026499 85258091 480 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	C
 	MX-p25-BOD1-AUD p25 Body 6MP, Day, Audio Package p25 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	4047438026819 85258091 480 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	C
 	MX-p25-BOD1-N-AUD p25 Body 6MP, Night, Audio Package p25 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • Lens to be ordered individually (B036 to B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	4047438026826 85258091 480 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	C
 	MX-p25-D016 p25 Complete Cam 6MP, B016, Day Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	4047438026406 85258091 480 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	C
 	MX-p25-D036 p25 Complete Cam 6MP, B036, Day IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	4047438026420 85258091 480 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	C
 	MX-p25-D016-AUD p25 Complete Cam 6MP, B016, Day, Audio Package Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	4047438026772 85258091 480 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	C

v25 Indoor Dome Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
 	MX-v25-BOD1 v25 Body 6MP, Day, White v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: white	4047438027571 85258091 690 g	20,5 cm 19,8 cm 12,3 cm	C 5,0 l
	MX-v25-BOD1-b v25 Body 6MP, Day, Black v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: black	4047438027656 85258091 690 g	20,5 cm 19,8 cm 12,3 cm	C 5,0 l
	MX-v25-BOD1-N v25 Body 6MP, Night, White v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: white	4047438027588 85258091 690 g	20,5 cm 19,8 cm 12,3 cm	C 5,0 l
 	MX-v25-BOD1-N-b v25 Body 6MP, Night, Black v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: black	4047438027663 85258091 690 g	20,5 cm 19,8 cm 12,3 cm	C 5,0 l
	MX-v25-D036 v25 Complete Cam 6MP, B036, Day, White IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: white	4047438027649 85258091 700 g	20,5 cm 19,8 cm 12,3 cm	C 5,0 l



Professional Video Systems Thermal

M16 Thermal Camera „Mx6“

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-M16TA-R079 M16 Thermographic Camera TR, 50 mK, R079 (45°)	4047438027823 85258091 2.480 g	34,5 cm 34,0 cm 20,0 cm 23,5 l	B
	<p>IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/32° • Mx6 system platform with H.264, MxPEG and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB, IO and RS232 via additional Interface Box</p>			
	Mx-M16TA-R119 M16 Thermographic Camera TR, 50 mK, R119 (25°)	4047438027830 85258091 2.480 g	34,5 cm 34,0 cm 20,0 cm 23,5 l	B
	<p>IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • Mx6 system platform with H.264, MxPEG and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB, IO and RS232 via additional Interface Box</p>			
	Mx-M16TA-R237 M16 Thermographic Camera TR, 50 mK, R237 (17°)	4047438027847 85258091 2.480 g	34,5 cm 34,0 cm 20,0 cm 23,5 l	B
	<p>IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • Mx6 system platform with H.264, MxPEG and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB, IO and RS232 via additional Interface Box</p>			
	Mx-M16TA-T079 M16 Thermographic Camera 50 mK, T079 (45°)	4047438027793 85258091 2.460 g	34,5 cm 34,0 cm 20,0 cm 23,5 l	B
	<p>IP thermographic camera with T079 thermal lens, horizontal/vertical image angle 45°/32°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Mx6 system platform with H.264, MxPEG and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB, IO and RS232 via additional Interface Box</p>			
	Mx-M16TA-T119 M16 Thermographic Camera 50 mK, T119 (25°)	4047438027809 85258091 2.460 g	34,5 cm 34,0 cm 20,0 cm 23,5 l	B
	<p>IP thermographic camera with T119 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Mx6 system platform with H.264, MxPEG and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB, IO and RS232 via additional Interface Box</p>			

**Mx-M16TA-T237****M16 Thermographic Camera 50 mK, T237 (17°)**

IP thermographic camera with T237 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Mx6 system platform with H.264, MxPEG and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional Interface Box

4047438027816	34,5 cm	B
85258091	34,0 cm	
2.460 g	20,0 cm	
	23,5 l	

M15 Thermal Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-M15-TR079	4047438027014	34,5 cm	B
	M15 Thermographic Camera TR, 50 mK, B079 (45°) IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/32° • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	85258091	34,0 cm	
		2.480 g	20,0 cm	23,5 l
	MX-M15-TR119	4047438027021	34,5 cm	B
	M15 Thermographic Camera TR, 50 mK, B119 (25°) IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	85258091	34,0 cm	
		2.480 g	20,0 cm	23,5 l
	MX-M15-TR237	4047438027038	34,5 cm	B
	M15 Thermographic Camera TR, 50 mK, B237 (17°) IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	85258091	34,0 cm	
		2.480 g	20,0 cm	23,5 l
	MX-M15D-Thermal-L43	4047438020589	34,5 cm	B
	M15 Thermographic Camera, 50 mK, L43 (45°) IP thermographic camera with L43 thermal lens, horizontal/vertical image angle 45°/32°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	85258091	34,0 cm	
		2.460 g	20,0 cm	23,5 l
	MX-M15D-Thermal-L65	4047438020596	34,5 cm	B
	M15 Thermographic Camera, 50 mK, L65 (25°) IP thermographic camera with L65 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	85258091	34,0 cm	
		2.460 g	20,0 cm	23,5 l
	MX-M15D-Thermal-L135	4047438020602	34,5 cm	B
	M15 Thermographic Camera, 50 mK, L135 (17°) IP thermographic camera with L135 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	85258091	34,0 cm	
		2.460 g	20,0 cm	23,5 l

Sensor Modules Thermal For S16/S15

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-O-SMA-TS-R079 Thermal Sensor Module TR For S16/S15, 50 mK, B079 (45°) Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	4047438030090 90275000 650 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	B
	Mx-O-SMA-TS-R119 Thermal Sensor Module TR For S16/S15, 50 mK, B119 (25°) Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	4047438030106 90275000 650 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	B
	Mx-O-SMA-TS-R237 Thermal Sensor Module TR For S16/S15, 50 mK, B237 (17°) Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	4047438030113 90275000 650 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	B
	Mx-O-SMA-TP-R079 PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), White PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	4047438030120 90275000 890 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	B
	Mx-O-SMA-TP-R119 PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), White PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	4047438030137 90275000 890 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	B
	Mx-O-SMA-TP-R237 PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), White PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	4047438030144 90275000 890 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	B
	Mx-O-SMA-TP-R079-b PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), Black PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	4047438030151 90275000 890 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	B

	<p>Mx-O-SMA-TP-R119-b PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), Black</p> <p>PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black</p>	<p>4047438030168 90275000 890 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	B
	<p>Mx-O-SMA-TP-R237-b PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), Black</p> <p>PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black</p>	<p>4047438030175 90275000 890 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	B
	<p>Mx-O-SMA-TS-T079 Thermal Sensor Module For S16/S15, 50 mK, B079 (45°)</p> <p>Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)</p>	<p>4047438029049 90275000 535 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	B
	<p>Mx-O-SMA-TS-T119 Thermal Sensor Module For S16/S15, 50 mK, B119 (25°)</p> <p>Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)</p>	<p>4047438029056 90275000 535 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	B
	<p>Mx-O-SMA-TS-T237 Thermal Sensor Module For S16/S15, 50 mK, B237 (17°)</p> <p>Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)</p>	<p>4047438029063 90275000 535 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	B
	<p>Mx-O-SMA-TP-T079 PTMount-Thermal For S16/S15, 50 mK, B079 (45°), White</p> <p>PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White</p>	<p>4047438029070 90275000 870 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	B
	<p>Mx-O-SMA-TP-T119 PTMount-Thermal For S16/S15, 50 mK, B119 (25°), White</p> <p>PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White</p>	<p>4047438029087 90275000 870 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	B
	<p>Mx-O-SMA-TP-T237 PTMount Thermal For S16/S15, 50 mK, B237 (17°), White</p> <p>PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White</p>	<p>4047438029094 90275000 870 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	B

**Mx-O-SMA-TP-T079-b****PTMount-Thermal For S16, S15, 50 mK, B079 (45°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030021	17,5 cm	B
90275000	14,0 cm	
870 g	13,5 cm	
	3,3 l	

**Mx-O-SMA-TP-T119-b****PTMount-Thermal For S16, S15, 50 mK, B119 (25°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030038	17,5 cm	B
90275000	14,0 cm	
870 g	13,5 cm	
	3,3 l	

**Mx-O-SMA-TP-T237-b****PTMount Thermal For S16, S15, 50 mK, B237 (17°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: black








4047438030045	17,5 cm	B
90275000	14,0 cm	
870 g	13,5 cm	
	3,3 l	

Intelligent IP Video Solutions



Optics

Sensor Modules 6MP For S16/S15 And M16/M15

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-O-SMA-S-6D016	4047438029100	10,5 cm	C
	Sensor Module 6MP, B016 (Day), White Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	6,8 cm 10,5 cm	0,7 l
	Mx-O-SMA-S-6D036	4047438029117	10,5 cm	C
	Sensor Module 6MP, B036 (Day), White Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	6,8 cm 10,5 cm	0,7 l
	Mx-O-SMA-S-6D041	4047438029124	10,5 cm	C
	Sensor Module 6MP, B041 (Day), White Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	6,8 cm 10,5 cm	0,7 l
	Mx-O-SMA-S-6D061	4047438029131	10,5 cm	C
	Sensor Module 6MP, B061 (Day), White Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	6,8 cm 10,5 cm	0,7 l
	Mx-O-SMA-S-6D079	4047438029148	10,5 cm	C
	Sensor Module 6MP, B079 (Day), White Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	6,8 cm 10,5 cm	0,7 l
	Mx-O-SMA-S-6D119	4047438029155	10,5 cm	C
	Sensor Module 6MP, B119 (Day), White Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	6,8 cm 10,5 cm	0,7 l
	Mx-O-SMA-S-6D237	4047438029162	10,5 cm	C
	Sensor Module 6MP, B237 (Day), White Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	6,8 cm 10,5 cm	0,7 l

 	<p>Mx-O-SMA-S-6D500 Sensor Module 6MP, B500 (Day), White Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029179 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6DCSV Sensor Module 6MP, CSVario 4,5-10 mm (Day), White Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030052 90021900 190 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6DCS Sensor Module 6MP, CS-Mount (Day), White Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030076 90021900 146 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6N016 Sensor Module 6MP, B016 (Night), White Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029186 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6N036 Sensor Module 6MP, B036 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029193 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6N041 Sensor Module 6MP, B041 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029209 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6N061 Sensor Module 6MP, B061 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029216 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6N079 Sensor Module 6MP, B079 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029223 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>

	<p>Mx-O-SMA-S-6N119 Sensor Module 6MP, B119 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029230 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>Mx-O-SMA-S-6N237 Sensor Module 6MP, B237 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029247 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>Mx-O-SMA-S-6N500 Sensor Module 6MP, B500 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029254 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>Mx-O-SMA-S-6NCSV Sensor Module 6MP, CSVario 4,5-10 mm (Night), White Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS (focal length 4.5 -10 mm, f/1.6-2.3, 39°-89° x 29°-65°) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030069 90021900 190 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>Mx-O-SMA-S-6NCS Sensor Module 6MP, CS-Mount (Night), White Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030083 90021900 146 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>Mx-O-SMA-S-6L016 Sensor Module 6MP, B016 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029261 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>Mx-O-SMA-S-6L036 Sensor Module 6MP, B036 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029278 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>Mx-O-SMA-S-6L041 Sensor Module 6MP, B041 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029285 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>

 	<p>Mx-O-SMA-S-6L061 Sensor Module 6MP, B061 (Night LPF), White</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029292 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
 	<p>Mx-O-SMA-S-6L079 Sensor Module 6MP, B079 (Night LPF), White</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029308 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
 	<p>Mx-O-SMA-S-6L119 Sensor Module 6MP, B119 (Night LPF), White</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029315 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
 	<p>Mx-O-SMA-S-6L237 Sensor Module 6MP, B237 (Night LPF), White</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029322 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
 	<p>Mx-O-SMA-S-6L500 Sensor Module 6MP, B500 (Night LPF), White</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029339 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
 	<p>Mx-O-SMA-S-6D016-b Sensor Module 6MP, B016 (Day), Black</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029346 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
 	<p>Mx-O-SMA-S-6D036-b Sensor Module 6MP, B036 (Day), Black</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029353 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
 	<p>Mx-O-SMA-S-6D041-b Sensor Module 6MP, B041 (Day), Black</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029360 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>

 	<p>Mx-O-SMA-S-6D061-b Sensor Module 6MP, B061 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029377 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	C
 	<p>Mx-O-SMA-S-6D079-b Sensor Module 6MP, B079 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029384 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	C
 	<p>Mx-O-SMA-S-6D119-b Sensor Module 6MP, B119 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029391 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	C
 	<p>Mx-O-SMA-S-6D237-b Sensor Module 6MP, B237 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029407 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	C
 	<p>Mx-O-SMA-S-6D500-b Sensor Module 6MP, B500 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029414 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	C
 	<p>Mx-O-SMA-S-6N016-b Sensor Module 6MP, B016 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029421 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	C
 	<p>Mx-O-SMA-S-6N036-b Sensor Module 6MP, B036 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029438 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	C
 	<p>Mx-O-SMA-S-6N041-b Sensor Module 6MP, B041 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029445 90021900 144 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	C

 	Mx-O-SMA-S-6N061-b Sensor Module 6MP, B061 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029452 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
 	Mx-O-SMA-S-6N079-b Sensor Module 6MP, B079 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029469 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
 	Mx-O-SMA-S-6N119-b Sensor Module 6MP, B119 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029476 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
 	Mx-O-SMA-S-6N237-b Sensor Module 6MP, B237 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029483 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
 	Mx-O-SMA-S-6N500-b Sensor Module 6MP, B500 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029490 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
 	Mx-O-SMA-S-6L016-b Sensor Module 6MP, B016 (Night LPF), Black Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438029506 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
 	Mx-O-SMA-S-6L036-b Sensor Module 6MP, B036 (Night LPF), Black Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438029513 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
 	Mx-O-SMA-S-6L041-b Sensor Module 6MP, B041 (Night LPF), Black Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438029520 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C

 	<p>Mx-O-SMA-S-6L061-b Sensor Module 6MP, B061 (Night LPF), Black</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029537 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6L079-b Sensor Module 6MP, B079 (Night LPF), Black</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029544 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6L119-b Sensor Module 6MP, B119 (Night LPF), Black</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029551 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6L237-b Sensor Module 6MP, B237 (Night LPF), Black</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029568 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>
 	<p>Mx-O-SMA-S-6L500-b Sensor Module 6MP, B500 (Night LPF), Black</p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029575 90021900 144 g</p>	<p>10,5 cm C 6,8 cm 10,5 cm 0,7 l</p>

BlockFlexMounts 6MP für S16/S15

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-O-SMA-B-6D016	4047438029797	10,7 cm	C
	BlockFlexMount 6MP, Incl. Hemispheric B016 (Day) Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	5,2 cm 8,7 cm 0,5 l	
	Mx-O-SMA-B-6D036	4047438029803	10,7 cm	C
	BlockFlexMount 6MP, Incl. B036 (Day) Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	5,2 cm 8,7 cm 0,5 l	
	Mx-O-SMA-B-6D041	4047438029810	10,7 cm	C
	BlockFlexMount 6MP, Incl. B041 (Day) Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	5,2 cm 8,7 cm 0,5 l	
	Mx-O-SMA-B-6D061	4047438029827	10,7 cm	C
	BlockFlexMount 6MP, Incl. B061 (Day) Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	5,2 cm 8,7 cm 0,5 l	
	Mx-O-SMA-B-6D079	4047438029834	10,7 cm	C
	BlockFlexMount 6MP, Incl. B079 (Day) Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	5,2 cm 8,7 cm 0,5 l	
	Mx-O-SMA-B-6D119	4047438029841	10,7 cm	C
	BlockFlexMount 6MP, Incl. B119 (Day) Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	5,2 cm 8,7 cm 0,5 l	
	Mx-O-SMA-B-6D237	4047438029858	10,7 cm	C
	BlockFlexMount 6MP, Incl. B237 (Day) Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	5,2 cm 8,7 cm 0,5 l	


	<p>Mx-O-SMA-B-6D500 BlockFlexMount 6MP, incl. B500 (Day) Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029865 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6DCS BlockFlexMount 6MP, For CS Mount Lens (Day) Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029766 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6N016 BlockFlexMount 6MP, incl. Hemispheric B016 (Night) Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029872 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6N036 BlockFlexMount 6MP, incl. B036 (Night) Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029889 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6N041 BlockFlexMount 6MP, incl. B041 (Night) Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029896 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6N061 BlockFlexMount 6MP, incl. B061 (Night) Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029902 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6N079 BlockFlexMount 6MP, incl. B079 (Night) Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029919 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6N119 BlockFlexMount 6MP, incl. B119 (Night) Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029926 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C

	<p>Mx-O-SMA-B-6N237 BlockFlexMount 6MP, Incl. B237 (Night) Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029933 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6N500 BlockFlexMount 6MP, Incl. B500 (Night) Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029940 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6NCS BlockFlexMount 6MP, For CS Mount Lens (Night) Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029773 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6L036 BlockFlexMount 6MP, Incl. B036 (Night LPF) Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029957 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6L041 BlockFlexMount 6MP, Incl. B041 (Night LPF) Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029964 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6L061 BlockFlexMount 6MP, Incl. B061 (Night LPF) Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029971 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6L079 BlockFlexMount 6MP, Incl. B079 (Night LPF) Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029988 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C
	<p>Mx-O-SMA-B-6L119 BlockFlexMount 6MP, Incl. B119 (Night LPF) Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029995 90021900 155 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	C

**Mx-O-SMA-B-6L237****BlockFlexMount 6MP, Incl. B237 (Night LPF)**


Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030007	10,7 cm	C
90021900	5,2 cm	
155 g	8,7 cm	
	0,5 l	

**Mx-O-SMA-B-6L500****BlockFlexMount 6MP, Incl. B500 (Night LPF)**

Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030014	10,7 cm	C
90021900	5,2 cm	
155 g	8,7 cm	
	0,5 l	

















**Mx-O-SMA-B-6LCS****BlockFlexMount 6MP, For CS Mount Lens (Night LPF)**













Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029780	10,7 cm	C
90021900	5,2 cm	
155 g	8,7 cm	
	0,5 l	

Sensor Modules 6MP For D16/D15

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
 	Mx-O-SDA-F-6D6N Sensor Bridge FIX For D16/D15, 2x 6MP (Day & Night) Day & Night sensor bridge für D16/D15 Body, including two parallel aligned 6MP sensors (1x Day, 1x Night) and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B036 to B237 possible, to be ordered separately)	4047438030182 90021900 125 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	Mx-O-SDA-P-6D6D Sensor Bridge PAN/180° For D16/D15, 2x 6MP (Day) Panorama/180° sensor bridge for D16/D15 Body, including two day sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030199 90021900 125 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
 	Mx-O-SDA-P-6N6N Sensor Bridge PAN-N/180° for D16/D15, 2x 6MP (Night) Panorama/180° sensor bridge for D16/D15 Body, including two night sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030205 90021900 125 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	Mx-O-SDA-S-6D036 Sensor Module D16/D15 6MP, Incl. B036 (Day) Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029582 90021900 64 g	6,2 cm 3,9 cm 9,0 cm 0,2 l	C
 	Mx-O-SDA-S-6D041 Sensor Module D16/D15 6MP, Incl. B041 (Day) Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029599 90021900 64 g	6,2 cm 3,9 cm 9,0 cm 0,2 l	C
	Mx-O-SDA-S-6D061 Sensor Module D16/D15 6MP, Incl. B061 (Day) Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029605 90021900 64 g	6,2 cm 3,9 cm 9,0 cm 0,2 l	C
 	Mx-O-SDA-S-6D079 Sensor Module D16/D15 6MP, Incl. B079 (Day) Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029612 90021900 64 g	6,2 cm 3,9 cm 9,0 cm 0,2 l	C

 	<p>Mx-O-SDA-S-6D119 Sensor Module D16/D15 6MP, Incl. B119 (Day) Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048)</p>	<p>4047438029629 90021900 64 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
 	<p>Mx-O-SDA-S-6D237 Sensor Module D16/D15 6MP, Incl. B237 (Day) Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048)</p>	<p>4047438029636 90021900 64 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
 	<p>Mx-O-SDA-S-6N036 Sensor Module D16/D15 6MP, Incl. B036 (Night) Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)</p>	<p>4047438029643 90021900 64 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
 	<p>Mx-O-SDA-S-6N041 Sensor Module D16/D15 6MP, Incl. B041 (Night) Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029650 90021900 64 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
 	<p>Mx-O-SDA-S-6N061 Sensor Module D16/D15 6MP, Incl. B061 (Night) Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029667 90021900 64 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
 	<p>Mx-O-SDA-S-6N079 Sensor Module D16/D15 6MP, Incl. B079 (Night) Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029674 90021900 64 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
 	<p>Mx-O-SDA-S-6N119 Sensor Module D16/D15 6MP, Incl. B119 (Night) Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029681 90021900 64 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
 	<p>Mx-O-SDA-S-6N237 Sensor Module D16/D15 6MP, Incl. B237 (Night) Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029698 90021900 64 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C

 	<p>Mx-O-SDA-S-6L036 Sensor Module D16/D15 6MP, Incl. B036 (Night LPF) Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029704 90021900 64 g</p>	<p>6,2 cm C 3,9 cm 9,0 cm 0,2 l</p>
 	<p>Mx-O-SDA-S-6L041 Sensor Module D16/D15 6MP, Incl. B041 (Night LPF) Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029711 90021900 64 g</p>	<p>6,2 cm C 3,9 cm 9,0 cm 0,2 l</p>
 	<p>Mx-O-SDA-S-6L061 Sensor Module D16/D15 6MP, Incl. B061 (Night LPF) Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029728 90021900 64 g</p>	<p>6,2 cm C 3,9 cm 9,0 cm 0,2 l</p>
 	<p>Mx-O-SDA-S-6L079 Sensor Module D16/D15 6MP, Incl. B079 (Night LPF) Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029735 90021900 64 g</p>	<p>6,2 cm C 3,9 cm 9,0 cm 0,2 l</p>
 	<p>Mx-O-SDA-S-6L119 Sensor Module D16/D15 6MP, Incl. B119 (Night LPF) Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029742 90021900 64 g</p>	<p>6,2 cm C 3,9 cm 9,0 cm 0,2 l</p>
 	<p>Mx-O-SDA-S-6L237 Sensor Module D16/D15 6MP, Incl. B237 (Night LPF) Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029759 90021900 64 g</p>	<p>6,2 cm C 3,9 cm 9,0 cm 0,2 l</p>



Camera Accessories

HD Premium Lenses

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-B036	4047438026536	6,2 cm	C
	Ultra Wide Lens B036, Focal Length: 3.6 mm	90021900	3,9 cm	
	Ultra Wide lens B036 • HD premium quality • Focal length: 3.6 mm • Aperture: f/1.8	30 g	9,0 cm	
	• Image angle (horizontal x vertical, on camera with 6MP sensor): 103° x 77° (up to 5MP resolution) and 122° x 80° (6MP resolution)		0,2 l	
	MX-B041	4047438026543	6,2 cm	C
	Super Wide Lens B041, Focal Length: 4.1 mm	90021900	3,9 cm	
	Super Wide lens B041 • HD premium quality • Focal length: 4.1 mm • Aperture: f/1.8	30 g	9,0 cm	
	• Image angle (horizontal x vertical, on camera with 6MP sensor): 90° x 67° (up to 5MP resolution) and 110° x 70° (6MP resolution)		0,2 l	
	MX-B061	4047438026550	6,2 cm	C
	Wide Lens B061, Focal Length: 6.1 mm	90021900	3,9 cm	
	Wide lens B061 • HD premium quality • Focal length: 6.1 mm • Aperture: f/1.8	30 g	9,0 cm	
	• Image angle (horizontal x vertical, on camera with 6MP sensor): 60° x 45° (up to 5MP resolution) and 70.5° x 46° (6MP resolution)		0,2 l	
	MX-B079	4047438026567	6,2 cm	C
	Standard Lens B079, Focal Length: 7.9 mm	90021900	3,9 cm	
	Standard lens B079 • HD premium quality • Focal length: 7.9 mm • Aperture: f/1.8	30 g	9,0 cm	
	• Image angle (horizontal x vertical, on camera with 6MP sensor): 45° x 34° (up to 5MP resolution) and 54° x 36° (6MP resolution)		0,2 l	
	MX-B119	4047438026574	6,2 cm	C
	Tele Lens B119, Focal Length: 11.9 mm	90021900	3,9 cm	
	Tele lens B119 • HD premium quality • Focal length: 11.9 mm • Aperture: f/1.8	30 g	9,0 cm	
	• Image angle (horizontal x vertical, on camera with 6MP sensor): 31° x 23° (up to 5MP resolution) and 36° x 24.5° (6MP resolution)		0,2 l	
	MX-B237	4047438026581	6,2 cm	C
	Distant Tele Lens B237, Focal Length: 23.7 mm	90021900	3,9 cm	
	Distant Tele lens B237 • HD premium quality • Focal length: 23.7 mm • Aperture: f/1.8	30 g	9,0 cm	
	• Image angle (horizontal x vertical, on camera with 6MP sensor): 15° x 11° (up to 5MP resolution) and 17° x 11.5° (6MP resolution)		0,2 l	
	MX-B500	4047438026598	6,2 cm	C
	Super Tele Lens B500, Focal Length: 50 mm	90021900	3,9 cm	
	Super Tele lens B500 • HD premium quality • Focal length: 50 mm • Aperture: f/2.5	30 g	9,0 cm	
	• Image angle (horizontal x vertical): 8° x 6° (up to 5MP resolution) and 9° x 6° (6MP resolution) • For mounting this lens on the M2x, the extended replacement lens cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL)		0,2 l	

**MX-B045-100-CS****CSVario Lens For Cameras With CS-Mount**

CS Vario lens B045-100-CS • HD premium quality • Variable focal length: 4,5-10 mm
 • Variable aperture: f/1.6-2.3 • Variable image angle (horizontal x vertical): 39°-89° x 29°-65°

4047438026604	7,0 cm	C
90021900	5,0 cm	
60 g	5,0 cm	
	0,2 l	









**MX-SM-OPT-POL****Polarization Filter For Sensor Modules**

Suitable for all M1x/S1x sensor modules except with the lenses B016, B036, B500 and CSVario or CS Mount • Filter replaces the lens cover (made of glass) • Example: Recognition of people through the windshield of a car - the filter reduces the mirror reflection (and about 50 % of the sensor light sensitivity)

4047438019781	6,2 cm	C
90079100	3,9 cm	
20 g	9,0 cm	
	0,2 l	

Domes & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-M24M-OPT-LCSK Replacement Lens Cover M2x, Standard Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Weather lens protection made of plastic (IP66)	4047438012980 90079100 26 g	6,2 cm 3,9 cm 9,0 cm 0,2 l	C
	MX-M24M-OPT-LCSG Replacement Lens Cover M2x, With Glass Pane Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438012997 90079100 34 g	6,2 cm 3,9 cm 9,0 cm 0,2 l	C
	MX-M24M-OPT-LCGL Replacement Lens Cover M2x, Extended Suitable for: M2x and S1x/M1x sensor module with CSVario lens B045-100-CS or M2x with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438013000 90079100 50 g	6,2 cm 3,9 cm 9,0 cm 0,2 l	C
	MX-OPT-DK-L11 Replacement Cover Hemispheric Suitable for: Hemispheric sensor modules (for S1x/M1x), S26, S1xM, T2x and Q2x with Vanadism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)	4047438016469 90079100 19 g	6,2 cm 3,9 cm 9,0 cm 0,2 l	C
	MX-D15-OPT-DCT Replacement Cover D1x/v2x, Standard Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed)	4047438018227 90079100 54 g	12,0 cm 12,0 cm 8,0 cm 1,2 l	C
	MX-D15-OPT-DCS Replacement Cover D1x/v2x, Tinted Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed) • Tinted (50%) for especially bright environments	4047438018210 90079100 54 g	12,0 cm 12,0 cm 8,0 cm 1,2 l	C
	MX-D15-DCT-XL Replacement Cover D1x FIX/PAN, XL Suitable for: D1x PAN/180° and FIX/Day&Night models • Polycarbonate (1.5 mm)	4047438027519 90079100 60 g	17,5 cm 14,0 cm 13,5 cm 3,3 l	C

	<p>MX-D15-DCS-XL Replacement Cover D1x PAN/FIX, XL Tinted Suitable for: D1x PAN/180° and FIX/Day&Night models • Tinted (50%) for especially bright environments • Polycarbonate (1.5 mm)</p>	<p>4047438027526 90079100 60 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	<p>C</p>
	<p>MX-D24M-OPT-DCT Replacement Cover D2x, Standard Suitable for: D2x • With sealing ring</p>	<p>4047438011419 90079100 54 g</p>	<p>12,0 cm 12,0 cm 8,0 cm 1,2 l</p>	<p>C</p>
	<p>MX-D24M-OPT-DCS Replacement Cover D2x, Tinted Suitable for: D2x • With sealing ring • Tinted (50%) for especially bright environments</p>	<p>4047438011402 90079100 54 g</p>	<p>12,0 cm 12,0 cm 8,0 cm 1,2 l</p>	<p>C</p>
	<p>MX-D15-Vandal-ESMA Vandalism Set For D1x, Matt Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models</p>	<p>4047438018173 90079100 1.116 g</p>	<p>30,5 cm 24,0 cm 16,5 cm 12,1 l</p>	<p>C</p>
	<p>MX-D15-Vandal-ESPO Vandalism Set For D1x, Polished Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models</p>	<p>4047438018166 90079100 1.116 g</p>	<p>30,5 cm 24,0 cm 16,5 cm 12,1 l</p>	<p>C</p>
	<p>MX-D15-Vandal-PUBL Vandalism Set For D1x, Black Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models</p>	<p>4047438018203 90079100 1.116 g</p>	<p>30,5 cm 24,0 cm 16,5 cm 12,1 l</p>	<p>C</p>
	<p>MX-D15-Vandal-PUGR Vandalism Set For D1x, Gray Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models</p>	<p>4047438018180 90079100 1.116 g</p>	<p>30,5 cm 24,0 cm 16,5 cm 12,1 l</p>	<p>C</p>
	<p>MX-D15-Vandal-PUWH Vandalism Set For D1x, White Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models</p>	<p>4047438018197 90079100 1.116 g</p>	<p>30,5 cm 24,0 cm 16,5 cm 12,1 l</p>	<p>C</p>

	<p>MX-D15-DCT-V Replacement Cover D1x/v2x, Vandalism Reinforced replacement cover (polycarbonate, 3 mm) for D1x and v25 Vandalism Sets • Suitable for: D1x and v2x • Not for D1x PAN/180° and FIX/Day&Night models (XL cover needed)</p>	<p>4047438027533 90079100 60 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	<p>C</p>
	<p>MX-D24M-Vandal-ESMA Vandalism Set For D2x, Matt Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)</p>	<p>4047438011143 90079100 672 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	<p>C</p>
	<p>MX-D24M-Vandal-ESPO Vandalism Set For D2x, Polished Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)</p>	<p>4047438011150 90079100 668 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	<p>C</p>
	<p>MX-D24M-Vandal-PUBL Vandalism Set For D2x, Black Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)</p>	<p>4047438011181 90079100 676 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	<p>C</p>
	<p>MX-D24M-Vandal-PUGR Vandalism Set For D2x, Gray Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)</p>	<p>4047438011174 90079100 676 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	<p>C</p>
	<p>MX-D24M-Vandal-PUWH Vandalism Set For D2x, White Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)</p>	<p>4047438011167 90079100 682 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	<p>C</p>
	<p>MX-D25-DCT-V Replacement D2x, Vandalism Reinforced replacement cover (polycarbonate, 3 mm) for D2x Vandalism Kits • With sealing ring</p>	<p>4047438027700 90079100 60 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	<p>C</p>
	<p>MX-Q24M-Vandal-ESMA Vandalism Set For Q2x, Matt Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish matt • Incl. security screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available</p>	<p>4047438011273 90079100 736 g</p>	<p>30,5 cm 23,5 cm 12,0 cm 8,6 l</p>	<p>C</p>

**MX-Q24M-Vandal-ESPO****Vandalism Set For Q2x, Polished**

Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish polished • Incl. security screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available

4047438011280	30,5 cm	C
90079100	23,5 cm	
756 g	12,0 cm	
	8,6 l	

**MX-MT-v25-V****Vandalism Set For v2x**

Suitable for: v2x without On-Wall Mounting Set with Audio • Stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only without On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10

4047438027601	20,5 cm	C
90079100	19,8 cm	
350 g	12,3 cm	
	5,0 l	

**MX-MT-v25-V-XL****Vandalism Set For v2x With On-Wall Mounting Set**

Suitable for: v2x with On-Wall Mounting Set with Audio • XL stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only with mounted On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10

4047438027625	20,5 cm	C
90079100	19,8 cm	
450 g	12,3 cm	
	5,0 l	

Mounts For S16/S15

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-FLEX-OPT-DM-PW DualMount S1x, White For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all available sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	4047438017626 90079100 442 g	22,5 cm 19,2 cm 8,5 cm	C 3,7 l
	MX-FLEX-OPT-SM-PW SurroundMount S1x, White For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all 6MP Sensor modules (B016 to B500 and CS Mount) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	4047438016407 90079100 463 g	22,5 cm 19,2 cm 8,5 cm	C 3,7 l
	MX-PTMount-OPT-PW PTMount S1x, White Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideway tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S1x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: white	4047438021166 90079100 610 g	17,5 cm 14,0 cm 13,5 cm	C 3,3 l
	MX-FLEX-OPT-DM-BL DualMount S1x, Black For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all screwable sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	4047438021869 90079100 442 g	22,5 cm 19,2 cm 8,5 cm	C 3,7 l
	MX-FLEX-OPT-SM-BL SurroundMount S1x, Black For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all screwable sensor modules • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	4047438021845 90079100 463 g	22,5 cm 19,2 cm 8,5 cm	C 3,7 l
	MX-PTMount-OPT-BL PTMount S1x, Black Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideway tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S1x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black	4047438021852 90079100 610 g	17,5 cm 14,0 cm 13,5 cm	C 3,3 l
	MX-HALO-EXT-PW HaloMount S1x, White Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	4047438017664 90079100 175 g	13,5 cm 12,0 cm 4,5 cm	C 0,7 l






	MX-HALO-EXT-BL HaloMount S1x, Black Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •	4047438017671 90079100 175 g	13,5 cm C 12,0 cm 4,5 cm 0,7 l
	MX-HALO-EXT-CM HaloMount S1x, Matt Chrome Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •	4047438017633 90079100 175 g	13,5 cm C 12,0 cm 4,5 cm 0,7 l
	MX-HALO-EXT-CO HaloMount S1x, Chrome Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •	4047438017640 90079100 175 g	13,5 cm C 12,0 cm 4,5 cm 0,7 l
	MX-HALO-EXT-NG HaloMount S1x, Brushed Nickel Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •	4047438017657 90079100 175 g	13,5 cm C 12,0 cm 4,5 cm 0,7 l
	MX-HALO-SP-EXT-PW SpeakerMount S1x, White Integrated speaker incl. mount, white • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metal with perforated plate covering • Connection type: two-wired strand, clamp included	4047438017688 85182200 273 g	13,5 cm C 12,0 cm 4,5 cm 0,7 l
	MX-HALO-SP-EXT-CM SpeakerMount S1x, Matt Chrome Integrated speaker incl. mount, matt chrome • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metal with perforated plate covering • Connection type: two-wired strand, clamp included	4047438017695 85182200 273 g	13,5 cm C 12,0 cm 4,5 cm 0,7 l
	MX-S14-OPT-MK-CW Extension Set Sensor Module, 40 mm And 15° Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut	4047438016384 90079100 134 g	21,3 cm C 8,7 cm 8,7 cm 1,6 l
	MX-S14-OPT-MK-EX Extension Sensor Module, 40 mm 1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all (screwable) S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions	4047438016391 90079100 62 g	10,5 cm C 6,8 cm 10,5 cm 0,7 l

**MX-FLEX-OPT-AM-BL****AudioMount S26/S1xM, Self-Adhesive**

Suitable for: S26, S15M, S14M • Easy, quick and concealed mounting with adhesive foil (e.g. behind a stainless steel plate) • Speaker and microphone with camera connection cable included • Use of the camera as a door station by connecting an external doorbell (e.g., connected via MX-232-IO-Box)




4047438019873	24,0 cm	C
85299065	13,6 cm	
386 g	5,3 cm	
	1,7 l	

Camera Mounts

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-M-OWA-AU On-Wall Mounting Set With Audio For v26, White On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	4047438030328 90079100 300 g	20,5 cm 19,8 cm 12,3 cm 5,0 l	C
	Mx-M-OWA-AU-b On-Wall Mounting Set With Audio For v26, Black On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	4047438030335 90079100 300 g	20,5 cm 19,8 cm 12,3 cm 5,0 l	C
	MX-MT-OW2-AUD On-Wall Mounting Set With Audio For v25, White Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	4047438027632 90079100 300 g	20,5 cm 19,8 cm 12,3 cm 5,0 l	C
	MX-MT-OW2-AUD-b On-Wall Mounting Set With Audio For v25, Black Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	4047438027670 90079100 300 g	20,5 cm 19,8 cm 12,3 cm 5,0 l	C
	MX-MT-TUBE MxTubeMount Ceiling Suspension System For suspended ceiling installation of the cameras M1x/M2x/V2x/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D2x/Q2x/c2x/p2x (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection wire (length: 2.2 m/7.2 ft) • Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4" according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color/material of choice	4047438027557 90079100 500 g	20,5 cm 19,8 cm 12,3 cm 5,0 l	C
	MX-MT-TUBE100 MxTube, 1 m Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	4047438027687 90079100 500 g	110,0 cm 3,8 cm 3,8 cm 1,6 l	C
	MX-MT-TUBE200 MxTube, 2 m Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	4047438027564 90079100 1.000 g	201,0 cm 3,8 cm 3,8 cm 2,9 l	C

	<p>MX-OPT-UP1 Cavity Wall Installation Set i2x</p> <p>Suitable for: i2x • With cavity wall socket, stainless steel mounting plate, 2 Allen screws with washers • For installing the camera directly on the mounting plate, no dowels required • Mounting plate is screwed onto the cavity wall socket • Recommended only for wall installations</p>	<p>4047438022118 90079100 116 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>MX-OPT-AP2 On-Wall Mounting Set For i2x</p> <p>Suitable for: i25 • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera • Camera distance from the wall: ca. 25 mm • Recommended only for wall installation • Color: white</p>	<p>4047438025898 90079100 96 g</p>	<p>13,8 cm 3,5 cm 14,8 cm 0,7 l</p>	<p>C</p>
	<p>MX-MT-OW-1 On-Wall Mounting Set For c2x/p2x</p> <p>Suitable for: c2x und p2x • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera and integrates additional modules (e.g. two Interface Boxes) • Camera distance from the wall: ca. 80 mm • Diameter: 140 mm • Recommended only for ceiling installation • Color: White</p>	<p>4047438027083 90079100 700 g</p>	<p>20,5 cm 19,8 cm 12,3 cm 5,0 l</p>	<p>C</p>
	<p>MX-MT-CM-1 Corner Mounting Set For c2x</p> <p>Suitable for: c2x • Consists of on-wall mount and mounting parts • Mounting in a room corner • Mounting position plus 35° tilt angle enable one camera (e.g. c2x with 103° lens B036) to capture an entire room • Color: White</p>	<p>4047438027076 90079100 600 g</p>	<p>30,5 cm 24,0 cm 16,5 cm 12,1 l</p>	<p>C</p>
	<p>MX-OPT-AP On-Wall Mounting Set For Q2x/D2x/ExtIO</p> <p>Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm</p>	<p>4047438011358 90079100 750 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	<p>C</p>
	<p>MX-OPT-AP-10DEG On-Wall Mounting Set For Q2x/D2x/ExtIO, 10°</p> <p>Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Camera can be mounted at a 10° tilt angle • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm</p>	<p>4047438010283 90079100 712 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	<p>C</p>
	<p>MX-D15-OPT-WHMH-Set Wall & Pole/Corner Mount Set For D1x</p> <p>Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438018159 90079100 5.000 g</p>	<p>36,5 cm 34,5 cm 36,5 cm 46,0 l</p>	<p>C</p>
	<p>MX-OPT-WHMH-Set Wall & Pole/Corner Mount Set For Q2x/D2x/ExtIO</p> <p>Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438011396 90079100 2.410 g</p>	<p>30,5 cm 24,0 cm 16,5 cm 12,1 l</p>	<p>C</p>

	<p>MX-WH-Dome Wall Mount For D1x Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts</p>	<p>4047438002233 90079100 2.000 g</p>	<p>32,0 cm 30,5 cm 23,0 cm 22,4 l</p>	C
	<p>MX-OPT-WH Wall Mount For Q2x/D2x/ExtIO Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts</p>	<p>4047438011372 90079100 1.040 g</p>	<p>30,5 cm 24,0 cm 16,5 cm 12,1 l</p>	C
	<p>MX-WH-SecureFlex Wall/Ceiling Mount For M12/M10/M1 Suitable for: M12/M10/M1 (not M15) • Shock-resistant fiberglass-reinforced composite (PBT), white • Patented tamper-proof concealed cabling • Can be turned left/right 90°, tilted downwards 70° • Includes stainless steel mounting set, caps and dowels</p>	<p>4047438002219 90079100 390 g</p>	<p>20,0 cm 15,0 cm 11,0 cm 3,3 l</p>	C
	<p>MX-MH-Dome-ESWS Pole/Corner Mount For MX-WH-Dome Suitable for: D1x • Pole/corner mount for fastening of wall mount MX-WH-Dome (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438002240 90079100 3.000 g</p>	<p>34,0 cm 18,5 cm 11,5 cm 7,2 l</p>	C
	<p>MX-MH-SecureFlex-ESWS Pole Mount For M1x/M2x Suitable for: M1x, M2x • Mount for fastening the standard camera wall mount SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438002226 90079100 1.230 g</p>	<p>20,0 cm 15,2 cm 8,0 cm 2,4 l</p>	C
	<p>MX-OPT-MH Pole/Corner Mount For MX-OPT-WH Suitable for: Q2x, D2x, ExtIO • Mount for fastening the wall mount MX-OPT-WH (to be ordered separately) • A set consisting of Pole/Corner Mount and Wall Mount is also available (MX-OPT-WHMH-Set) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438011389 90079100 1.370 g</p>	<p>34,0 cm 18,5 cm 11,5 cm 7,2 l</p>	C
	<p>MX-OPT-IC-BL In-Ceiling Set For Q2x, Black Special model for the Q2x with black housing • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm</p>	<p>4047438013970 90079100 550 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	C
	<p>MX-OPT-IC-ESMA In-Ceiling Set For Q2x/D2x/ExtIO, Matt Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (matt) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm</p>	<p>4047438011433 90079100 724 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	C

	<p>MX-OPT-IC-ESPO In-Ceiling Set For Q2x/D2x/ExtIO, Polished</p> <p>Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (polished) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm</p>	<p>4047438011426 90079100 724 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	C
	<p>MX-OPT-IC In-Ceiling Set For Q2x/D2x/ExtIO, White</p> <p>Suitable for: Q2x, D2x, ExtIO • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm</p>	<p>4047438011365 90079100 550 g</p>	<p>30,5 cm 24,0 cm 12,0 cm 8,8 l</p>	C
	<p>MX-OPT-TW-Demo-1 Demo Table/Wall Mount For Q2x/D2x</p> <p>Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).</p>	<p>4047438013055 90079100 200 g</p>	<p>21,3 cm 8,7 cm 8,7 cm 1,6 l</p>	C

MOBOTIX Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-FLEX-OPT-CBL-015	4047438019941	13,5 cm	C
	Sensor Module Cable For M1x, 0.15 m	85444210	8,0 cm	
	sensor cable (HS Code 85444210)	16 g	2,0 cm	
			0,2 l	
	MX-FLEX-OPT-CBL-05	4047438018890	10,5 cm	C
	Sensor Cable For S1x, 0.5 m	85444210	6,8 cm	
	Sensor cable, length 0.5 m/1,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	120 g	10,5 cm	
			0,7 l	
	MX-FLEX-OPT-CBL-1	4047438018883	10,5 cm	C
	Sensor Cable For S1x, 1 m	85444210	6,8 cm	
	Sensor cable, length 1 m/3,3 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	120 g	10,5 cm	
			0,7 l	
	MX-FLEX-OPT-CBL-2	4047438018876	10,5 cm	C
	Sensor Cable For S1x, 2 m	85444210	6,8 cm	
	Sensor cable, length 2 m/6,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	120 g	10,5 cm	
			0,7 l	
	MX-FLEX-OPT-CBL-3	4047438024303	10,5 cm	C
	Sensor Cable For S1x (6MP/Thermal), 3 m	85444210	6,8 cm	
	Sensor cable, length 3 m/9,8 ft • For connecting optical sensor modules and BlockFlexMounts with 6MP sensors and Thermal sensor modules to the S1x camera module • Not compatible with PTMount-Thermal, S14D and 5MP modules	130 g	10,5 cm	
			0,7 l	
	MX-CBL-MU-EN-AB-05	4047438016728	10,5 cm	C
	USB Device Cable For M/Q/T2x, 0.5 m	85444210	6,8 cm	
	MiniUSB angled > USB-A straight • Length 0,5 m/1,6 ft • For M1x, M2x, Q2x, T2x • To connect ext. USB device	52 g	10,5 cm	
			0,7 l	
	MX-CBL-MU-EN-AB-2	4047438016711	10,5 cm	C
	USB Device Cable For M/Q/T2x, 2 m	85444210	6,8 cm	
	MiniUSB angled > USB-A straight • Length 2 m/6,6 ft • For M1x, M2x, Q2x, T2x • To connect ext. USB-Gerät	102 g	10,5 cm	
			0,7 l	

	MX-CBL-MU-EN-AB-5 USB Device Cable For M/Q/T2x, 5 m MiniUSB angled > USB-A straight • Length 5 m/16,4 ft • For M1x, M2x, Q2x, T2x • To connect ext. USB device	4047438016704 85444210 194 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-EN-EN-PG-05 ExtIO Cable For M/Q/T2x, 0,5 m MiniUSB angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For M1x, M2x, Q2x, T2x • To connect MX-ExtIO	4047438020947 85444210 52 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-EN-EN-PG-2 ExtIO Cable For M/Q/T2x, 2 m MiniUSB angled > MiniUSB+ angled • Length 2 m/6,6 m • For M1x, M2x, Q2x, T2x • To connect MX-ExtIO	4047438020930 85444210 102 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-EN-EN-PG-5 ExtIO Cable for M/Q/T2x, 5 m MiniUSB angled > MiniUSB+ angled • Length 5 m/16,4 ft • For M1x, M2x, Q2x, T2x • To connect MX-ExtIO	4047438020923 85444210 194 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-EN-PG-AB-05 USB Device Cable For D2x, 0,5 m MiniUSB+ angled > USB-A straight • Length 0,5 m/1,6 ft • For D2x • To connect ext. USB device	4047438020916 85444210 52 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-EN-PG-AB-2 USB Device Cable For D2x, 2 m MiniUSB+ angled > USB-A straight • Length 2 m/6,6 ft • For D2x • to connect ext. USB device	4047438020909 85444210 102 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-EN-PG-AB-5 USB Device Cable For D2x, 5 m MiniUSB+ angled > USB-A straight • Length 5 m/16,4 ft • For D2x • To connect ext. USB device	4047438020893 85444210 194 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-EN-PG-EN-PG-05 ExtIO Cable For D2x, 0,5 m MiniUSB+ angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D2x • To connect MX-ExtIO	4047438020886 85444210 52 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C

	<p>MX-CBL-MU-EN-PG-EN-PG-2 ExtIO Cable For D2x, 2 m MiniUSB+ angled > MiniUSB+ angled • Length 2 m/6,6 ft • For D2x • To connect MX-ExtIO</p>	<p>4047438020879 85444210 102 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>MX-CBL-MU-EN-PG-EN-PG-5 ExtIO Cable For D2x, 5 m MiniUSB+ angled > MiniUSB+ angled • Length 5 m/16,4 ft • For D2x • To connect MX-ExtIO</p>	<p>4047438020862 85444210 194 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>MX-CBL-MU-EN-PG-STR-05 232-IO-Box Cable For D2x, 0.5 m MiniUSB+ angled > MiniUSB straight • Length 0,5 m/1,6 ft • For D2x • To connect MX-232-IO-Box</p>	<p>4047438020855 85444210 52 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>MX-CBL-MU-EN-PG-STR-2 232-IO-Box Cable For D2x, 2 m MiniUSB+ angled > MiniUSB straight • Length 2 m/6,6 ft • For D2x • To connect MX-232-IO-Box</p>	<p>4047438020848 85444210 102 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>MX-CBL-MU-EN-PG-STR-5 232-IO-Box Cable For D2x, 5 m MiniUSB+ angled > MiniUSB straight • Length 5 m/16,4 ft • For D2x • To connect MX-232-IO-Box</p>	<p>4047438020831 85444210 194 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>MX-CBL-MU-EN-STR-05 232-IO-Box Cable For M/Q/T2x, 0.5 m MiniUSB angled > MiniUSB straight • Length 0,5 m/1,6 ft • For M1x, M2x, Q2x, T2x • To connect MX-232-IO-Box</p>	<p>4047438016667 85444210 52 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>MX-CBL-MU-EN-STR-2 232-IO-Box Cable For M/Q/T2x, 2 m MiniUSB angled > MiniUSB straight • Length 2 m/6,6 ft • For M1x, M2x, Q2x, T2x • To connect MX-232-IO-Box</p>	<p>4047438016650 85444210 102 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>MX-CBL-MU-EN-STR-5 232-IO-Box Cable For M/Q/T2x, 5 m MiniUSB angled > MiniUSB straight • Length 5 m/16,4 ft • For M1x, M2x, Q2x, T2x • To connect MX-232-IO-Box</p>	<p>4047438016643 85444210 194 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>

	MX-CBL-MU-STR-05 232-IO-Box Cable For D/S/V1x, 0.5 m MiniUSB straight > MiniUSB straight • Length 0,5 m/1,6 ft • For D1x, S1x, V1x • To connect MX-232-IO-Box	4047438016605 85444210 52 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-STR-2 232-IO-Box Cable For D/S/V1x, 2 m MiniUSB straight > MiniUSB straight • Length 2 m/6,6 ft • For D1x, S1x, V1x • To connect MX-232-IO-Box	4047438016599 85444210 102 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-STR-5 232-IO-Box Cable For D/S/V1x, 5 m MiniUSB straight > MiniUSB straight • Length 5 m/16,4 ft • For D1x, S1x, V1x • To connect MX-232-IO-Box	4047438016445 85444210 196 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-STR-AB-05 USB Device Cable For D/S/V1x, 0.5 m MiniUSB straight > USB-A straight • Length 0,5 m/1,6 ft • For D1x, S1x, V1x • To connect ext. USB device	4047438016698 85444210 52 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-STR-AB-2 USB Device Cable For D/S/V1x, 2 m MiniUSB straight > USB-A straight • Length 2 m/6,6 ft • D1x, S1x, V1x • To connect ext. USB device	4047438016681 85444210 102 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-STR-AB-5 USB Device Cable For D/S/V1x, 5 m MiniUSB straight > USB-A straight • Length 5 m /16,4 ft • For D1x, S1x, V1x • To connect ext. USB device	4047438016674 85444210 194 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-STR-EN-PG-05 ExtIO Cable For D/S/V1x, 0.5 m MiniUSB straight > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D1x, S1x, V1x • To connect MX-ExtIO	4047438020978 85444210 52 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C
	MX-CBL-MU-STR-EN-PG-2 ExtIO Cable For D/S/V1x, 2 m MiniUSB straight > MiniUSB+ angled • Length 2 m/6,6 ft • For D1x, S1x, V1x • To connect MX-ExtIO	4047438020961 85444210 102 g	10,5 cm 6,8 cm 10,5 cm 0,7 l	C

	<p>MX-CBL-MU-STR-EN-PG-5 ExtIO Cable For D/S/V1x, 5 m MiniUSB straight > MiniUSB+ angled • Length 5 m/16,4 ft • For D1x, S1x, V1x • To connect MX-ExtIO</p>	<p>4047438020954 85444210 194 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>	<p>C</p>
	<p>MX-OPT-CBL-LAN-1 Ethernet Patch Cable, 1 m Ethernet Patch Cable for MOBOTIX systems • Length 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring</p>	<p>4047438012300 85444210 36 g</p>	<p>23,5 cm 15,0 cm 2,0 cm 0,7 l</p>	<p>C</p>
	<p>MX-OPT-CBL-LAN-10 Ethernet Patch Cable, 10 m Ethernet Patch Cable for MOBOTIX systems • Length 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring</p>	<p>4047438012331 85444210 264 g</p>	<p>27,0 cm 17,0 cm 4,0 cm 1,8 l</p>	<p>C</p>
	<p>MX-OPT-CBL-LAN-2 Ethernet Patch Cable, 2 m Ethernet Patch Cable for MOBOTIX systems • Length 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring</p>	<p>4047438012317 85444210 62 g</p>	<p>23,5 cm 15,0 cm 2,0 cm 0,7 l</p>	<p>C</p>
	<p>MX-OPT-CBL-LAN-5 Ethernet Patch Cable, 5 m Ethernet Patch Cable for MOBOTIX systems • Length 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring</p>	<p>4047438012324 85444210 144 g</p>	<p>23,5 cm 15,0 cm 4,0 cm 1,4 l</p>	<p>C</p>
	<p>MX-FLEX-IO-CBL-015 IO Connection Cable For M15, 0.15 m Length: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M1x (inside camera housing)</p>	<p>4047438019958 85444210 10 g</p>	<p>13,5 cm 8,0 cm 2,0 cm 0,2 l</p>	<p>C</p>
	<p>MX-CBL-NPA-BAT-2 NPA Battery Cable, 2 m NPA-PoE Battery Cable • Provides a power supply for the camera from car batteries or other power sources from 12 to 24 Volts • With self-resetting fuse • RJ45 connector to PoE injector, „+/-“ terminals for power source • Can only be used with Mx-NPA PoE injector • Length: 2 m/6.6 ft</p>	<p>4047438013949 85444210 54 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>	<p>C</p>

Other Camera Accessories








	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	<p>MX-OPT-Ring-L10-L12-BL Sealing Ring For Hemispheric Sensor Modules, Black</p> <p>Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black</p>	<p>4047438021241 90079100 16 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
	<p>MX-OPT-Ring-L10-L12-PW Sealing Ring For Hemispheric Sensor Modules, White</p> <p>Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white</p>	<p>4047438021234 90079100 16 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
	<p>MX-OPT-SEC-SCREWS-SET Security Screw Set With Allen Bit For M1x/M2x</p> <p>Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)</p>	<p>4047438021265 90079100 120 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C
	<p>MX-SM-Blind-PW Blind Module M1x</p> <p>For M1x and M1x Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.</p>	<p>4047438019965 90079100 38 g</p>	<p>6,2 cm 3,9 cm 9,0 cm 0,2 l</p>	C




Intelligent IP Video Solutions



System Components

Interface Boxes

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-OPT-BPA1-EXT	4047438025881	10,5 cm	C
	MX-BPA-BOX Power supply for several MxBus modules of one MxBus line • 2x2 connection terminals for MxBus • 2 connection terminals for external power supply from 12 to 48 V DC (2 terminals) • Max. output rating: 9 W • IP65, -30 bis 60 °C / -22 to 140 °F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065	6,8 cm	
	MX-OPT-NPA1-EXT	4047438015424	10,5 cm	C
	MX-NPA-Box Weatherproof PoE Injector (IEEE 802.3af) and network connector • Needs external power supply units and batteries from 12 to 57 V DC • Protection class IP65, -30 to 60°C / -22 to 140°F • Important: only use with original MOBOTIX patch cables • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	85043180	6,8 cm	
	MX-Overvoltage-Protection-Box-LSA	4047438018470	10,5 cm	C
	Network Connector with Surge Protection, LSA Version Weatherproof connection of one MOBOTIX patch cable (RJ45, from camera) and the network installation cable • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065	6,8 cm	
	MX-Overvoltage-Protection-Box-RJ45	4047438018463	10,5 cm	C
	Network Connector with Surge Protection, RJ45 Version Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065	6,8 cm	
	MX-OPT-Input1-EXT	4047438021227	10,5 cm	C
	MX-Input-Box Weatherproof connection of external sensors • Connection to camera using MxBus • 6 self-powered inputs for connecting up to 6 external sensors • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065	6,8 cm	
	MX-OPT-Output1-EXT	4047438021944	10,5 cm	C
	MX-Output-Box Weatherproof connection of external devices and power relays • Connection to the camera via MxBus • Six self-powered outputs (12 V, each 10 mA) • Two isolated outputs (can be switched to "self-powered" using a jumper: 12 V, max. 50 mA) • Protection class IP65, -30 to 60 °C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	85299065	6,8 cm	
	MX-OPT-RS1-EXT	4047438015417	10,5 cm	C
	MX-232-IO-Box Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB or MxBus • 2 self-powered inputs for connecting sensors • 2 outputs: 1 powered output, 1 isolated relay output (can be switched to second powered output) • RS232 interface when using MOBOTIX USB cable to connect to camera • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	85299065	6,8 cm	

 <p>MX-GPS-Box www.mobotix.com MOBOTIX AG - Made in Germany</p>	<p>MX-OPT-GPS1-EXT</p> <p>MX-GPS-Box</p> <p>Weatherproof GPS time base for MOBOTIX systems • Includes outdoor temperature and illumination sensors • Connects via MxBus 2-wire cable • Protection class IP65, -30 to 60°C / -22 to +140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x</p>	<p>4047438015400</p> <p>85299065</p> <p>120 g</p>	<p>10,5 cm</p> <p>6,8 cm</p> <p>10,5 cm</p> <p>0,7 l</p>	<p>C</p>
 <p>MX-Proximity-Box</p>	<p>MX-PROX-BOX</p> <p>MX-Proximity-Box</p> <p>Weatherproof proximity sensor for MOBOTIX systems • Accurate detection of approaching objects based on radar microwave technology • Covered area (horizontal x vertical): 80° x 34° • Camera connection and supply via MxBus • Protection class IP66, -20 to 60°C / -4 to 140°F • Box can also be mounted behind walls (e.g. wooden, plastic, glass or dry walls) • It is not possible to install the MX-Proximity-Box behind some materials since they absorb or reflect the radar waves (e.g., metal or metal-coated surfaces). Other materials are better suited since they absorb radar waves only slightly (e.g., uncoated glass, plastics, various wood-based materials, drywall).</p>	<p>4047438025935</p> <p>85299065</p> <p>165 g</p>	<p>10,5 cm</p> <p>6,8 cm</p> <p>10,5 cm</p> <p>0,7 l</p>	<p>C</p>
 <p>MxDigitizer</p>	<p>MX-OPT-DIGI-INT</p> <p>MxDigitizer For S1x</p> <p>Interface box to connect one analog camera directly to a S1x Body as alternative image source (instead of one sensor module) • Up to two MxDigitizer boxes or two analog cameras can be connected to one S1x Body • Easy integration of analog cameras into the MOBOTIX IP video system incl. the support of MOBOTIX integrated image analysis tools (e.g. MxActivitySensor) • Box digitizes the analog signal input (NTSC/PAL) • Output format PAL: 704 x 525 pixels, up to 25 frames per second • Output format NTSC: 640 x 480 pixels, up to 30 frames per second • BNC connection of analog camera to MxDigitizer • Sensor cable connection of MxDigitizer to S1x Body (to be ordered separately, maximum length 3 m/9.8 ft) • Operating conditions: Indoors, 0 to 40°C (32 to 104°F) • Color: white</p>	<p>4047438028790</p> <p>85299065</p> <p>120 g</p>	<p>10,5 cm</p> <p>6,8 cm</p> <p>10,5 cm</p> <p>0,7 l</p>	<p>C</p>

Mx2wire+ Media Converter

Article No. / Name / Description

EAN / HS / weight dimen. DG



MX-2WirePlus-Set-PW

4047438015356 17,8 cm C

Mx2wire+ Set, Ethernet And PoE Via Two-Wire-Cable

85176200 9,5 cm

Mx2wire+ turns an existing two-wire cable into a modern multimedia cable • Ethernet and PoE data transfer using a two-wire cable • Simple connection of 10/100 Mbps Ethernet end devices (e.g., IP camera, IP telephone) • Power supply for Mx2wire+ and end device via PoE/PoE+ or 48–57 V DC, 600 mA • Connected end devices are supplied with up to 13 watts via PoE (PoE class 3) • Maximum data transfer range of 500 m and data rate of up to 50 Mbps (depending on distance) • No need for expensive and time-consuming installation of network cables • Perfect for wireless communication is not possible (due to distance to sender, thickness of walls, etc.) • Network extension, including PoE, by connecting a Cat7 cable of up to 500 m in length as a two-wire cable • Simple installation in standard sockets (surface- or flush-mounted) • Two LEDs display current connection and supply statuses • Developed, produced and patented by MOBOTIX Germany • Ambient temperature: -30 to 50°C / -22 to 122°F • Complete set consisting of two Mx2wire+ units, on-walls sockets and mounting parts

696 g 21,7 cm
3,7 l

Functional Enhancement

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	Mx-A-IOA-IC	4047438029032	10,7 cm	C
	Extension Module For c26, i26, p26 And v26 Expansion module for Indoor Cameras c26, i26, p26 and v26 (installed on the back) <ul style="list-style-type: none"> • Not suitable for x25 indoor cameras • For connecting external sensors (e.g., door and window contacts) and switches of external devices (e.g., relays with lamps and motors) • Two inputs (galvanically separated): 0 V to 48 V AC/DC • Two outputs: 2x floating (load per contact max. 30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output) • 2x MxBus terminal connector (MxBus will be supported only by later available hardware versions of the x26 cameras) • Ambient temperature: 0°C to 40°C (32°F to 104°F) • Power consumption: 1 W 	85299065	5,2 cm	
		45 g	8,7 cm	0,5 l
	Mx-A-TCLIENTA	4047438028899	13,2 cm	C
	MxThinClient PoE-supplied IP video device to transfer live pictures of cameras and door stations to a monitor/TV set <ul style="list-style-type: none"> • Password protected web interface • Automatic change of video source via sequencer (time-controlled) or via MxMessageSystem (event-controlled) • Input (connection to PoE switch): 1x Ethernet 100Base-T (RJ45) • Output (connection to monitor/TV set): 1x HDMI Type D (MicroHDMI) • Connection cables (Ethernet, HDMI) are not included • Indoor-use only: Protection class IP20, ambient temperature 0 to 40 °C (32 to 104°F) • With the supplied adhesive strips, the device can easily be attached to the backside of the monitor/TV 	84714900	12,2 cm	
		200 g	4,2 cm	0,7 l
	MX-OPT-IO3-INT	4047438025928	10,7 cm	C
	Extension Module For c25, i25, p25 And v25 Extension module for the indoor cameras x25 (to be mounted on the backside) <ul style="list-style-type: none"> • Not compatible with x26 indoor cameras • For the connection of external sensors (e.g., door or window contacts) and switching of external devices (e.g., relays with lamps and motors) • Two input lines (galvanically isolated, 0 to 48 V AC/DC) • Two output lines: 2x isolated (contact load max.30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA, per output line) • MxBus terminal (1x2) • Ambient temperature: 0 to 4°C (32 to 104°F) • Power consumption: 1 W 	85299065	5,2 cm	
		45 g	8,7 cm	0,5 l
	MX-ExtIO	4047438009850	30,5 cm	C
	ExtIO Extension Module For All MOBOTIX Cameras ExtIO Weatherproof extension for all MOBOTIX cameras (except Basic models) <ul style="list-style-type: none"> • Power supply: PoE (Class 2, IEEE 802.3af) or USB (connection cable to be ordered individually) • Microphone/speaker • Line-in / Line-out • PIR sensor for motion detection • Temperature sensor • 2 buttons (e.g., lights, door bell) • 2 galvanically separated inputs • 2 galvanically separated outputs • Protection class IP65, -30 to 60°C / -22 to 140°F • Robust housing made of fiber-reinforced plastic PBT-GF30 • Mounting to a wall or ceiling, optionally with MOBOTIX mounting accessories (to be ordered individually) • Connecting via Network or USB 	85299065	24,0 cm	
		1.158 g	16,5 cm	12,1 l
	MX-MULTISENSE1	4047438028851	10,5 cm	C
	MxMultiSense Indoor Multi-sensor module for indoor use with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor and acoustic sensor (sound pressure) <ul style="list-style-type: none"> • Camera connection and supply via MxBus • MxBus cable length up to 100 m / 330 ft. • Power consumption: typ. 0.1 W • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX sensor module mounts and standard mounts for recessed spotlights • Protection class meets IP40 • IK05 • Ambient temperature: 0 to 40°C / 32 to 104°F • Housing color: white 	85299065	6,8 cm	
		110 g	10,5 cm	0,7 l
	MX-MULTISENSE1-EXT	4047438028905	10,5 cm	C
	MxMultiSense Outdoor Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor (±0.1°C / 0.18°F) and acoustic sensor (level of sound waves) <ul style="list-style-type: none"> • Camera connection and supply via MxBus: power consumption approx. 0.3 W, MxBus cable length up to 100 m / 330 ft. • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX mounts for sensor modules and standard mounts for recessed spotlights • Protection class IP66 • IK05 • Ambient temperature -20 to 60°C / -4 to 140°F • Housing color: white 	85299065	6,8 cm	
		110 g	10,5 cm	0,7 l

PoE Power Supply

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	<p>MX-SWITCH1 MxSwitch For DIN Rail Mounting PoE+ Switch for the top-hat rail • 5x RJ45 port with 100 MBit/s (1x uplink, 4x PoE+ with max. 75 W) • Supply: 48 V DC, max. 75 W • Simplified cabling for door stations due to available connectivity for anti-theft protection, door opener and MxBus • MxBus, anti-theft protection, door and lock contact can be connected via separate wires of the ethernet cable</p>	<p>4047438028882 85176200 400 g</p>	<p>17,5 cm 14,0 cm 13,5 cm 3,3 l</p>	<p>C</p>
	<p>MX-NPA-PoE-INT-Set PoE Power Adapter Set, INT PoE injector incl. crossover function for direct connection to the PC • With 4 exchangeable power plugs for Europe, United Kingdom, USA and Australia • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug</p>	<p>4047438012256 85043180 256 g</p>	<p>16,0 cm 10,0 cm 5,5 cm 0,9 l</p>	<p>C</p>
	<p>MX-NPA-PoE-RJ PoE Power Adapter PoE injector (IEEE 802.3af) incl. crossover function for direct connection to the PC • Blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug • Without power plug, additional power supply (12 to 57 V DC) and connection cable needed</p>	<p>4047438013932 85043180 90 g</p>	<p>10,5 cm 9,0 cm 5,0 cm 0,5 l</p>	<p>C</p>
	<p>MX-SNT-INT-PoE Universal Power Supply With 4 Power Plugs For international use thanks to broad input voltage range and interchangeable power plugs (no tools required) • With 4 power plugs for Europe, United Kingdom, USA and Australia • Connections: 1x RJ45 (for adapter), 1x network (up to 4x interchangeable adapter) • Nominal data input: 100 V to 240 V, 50 to 60 Hz/400 mA • Nominal data output: DC 24 V/750 mA • Ambient temperature: 0 to 40°C / 32 to 104 °F</p>	<p>4047438013925 85043180 160 g</p>	<p>16,0 cm 10,0 cm 5,5 cm 0,9 l</p>	<p>C</p>











Building Automation















MxDisplay+

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-DISPLAY3 MxDisplay+, White MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-PW) • Color: white	4047438027151 85285291 300 g	13,8 cm 6,5 cm 14,8 cm 1,3 l	C
	MX-DISPLAY3-b MxDisplay+, Black MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-BL) • Color: black	4047438027168 85285291 300 g	13,8 cm 6,5 cm 14,8 cm 1,3 l	C
	MX-DISPLAY3-EXT MxDisplay+ Outdoor, White Weatherproof MxDisplay+ for mounting outdoors or in rooms with special requirements • Operating conditions: IP65, -30 to 60°C (-22 to 140°F) • Remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking • HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus • Ethernet, RFID and WiFi (2.4 & 5 GHz), Bluetooth V3.0 HS • MxBus and Bluetooth available with upcoming software update • 1x admin card • Mounting parts • Frame and in-wall housing to be ordered separately (e.g., FlatMount Frame MX-OPT-FlatMount-EXT-PW) • Color: white	4047438028776 85285291 300 g	13,8 cm 6,5 cm 14,8 cm 1,3 l	C
	MX-DISPLAY3-EXT-b MxDisplay+ Outdoor, Black Weatherproof MxDisplay+ for mounting outdoors or in rooms with special requirements • Operating conditions: IP65, -30 to 60°C (-22 to 140°F) • Remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking • HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus • Ethernet, RFID and WiFi (2.4 & 5 GHz), Bluetooth V3.0 HS • MxBus and Bluetooth available with upcoming software update • 1x admin card • Mounting parts • Frame and in-wall housing to be ordered separately (e.g., FlatMount Frame MX-OPT-FlatMount-EXT-BL) • Color: black	4047438028783 85285291 300 g	13,8 cm 6,5 cm 14,8 cm 1,3 l	C

T25 Complete Kits

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
 	MX-T25-SMART-SET1 T25 Smart Access Set 1	4047438028769	34,0 cm	C
	T25 IP Video Door Station with MxDisplay+ as preconfigured complete set for use in family homes • Delivery outdoor remote station (IP65, -30 to 50°C, -22 to 122°F); CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) and Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • BellRFID module with one big key with blue functional bar, 1x admin and 6x user card, MX-OPT-IO2 Ethernet board, double frame set for in-wall or on-wall installation, pen for plastic film, mounting material • Delivery indoor remote station: MX-DISPLAY3, FlatMount Frame with In-Wall-Housing • All devices and frames colored in white	85258091	34,0 cm	
		2.500 g	16,0 cm	
			18,5 l	
 	MX-T25-SMART-SET2 T25 Smart Access Set 2	4047438028875	34,0 cm	C
	T25 IP Video Door Station with MxDisplay+ and MxSwitch • Preconfigured complete set for use in family homes • Delivery outdoor remote station (IP65, -30 to 50°C, -22 to 122°F); CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) and Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • BellRFID module with one big key with blue functional bar, 1x admin and 6x user card, MX-OPT-IO2 Ethernet board, double frame set for in-wall or on-wall installation, pen for plastic film, mounting material • Delivery indoor remote station: MX-DISPLAY3, FlatMount Frame with In-Wall-Housing • All devices and frames colored in white	85258091	34,0 cm	
		2.700 g	16,0 cm	
			18,5 l	
 	MX-T25-SET1 T25 6MP Set 1, Ethernet, Keypad, White	4047438025362	34,5 cm	C
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White	85258091	34,0 cm	
		3.000 g	16,0 cm	
			18,8 l	
 	MX-T25-SET2 T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, White	4047438025379	34,5 cm	C
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White	85258091	34,0 cm	
		3.000 g	16,0 cm	
			18,8 l	
 	MX-T25-SET3 T25 6MP Set 3, Ethernet, Keypad, DoorMaster, White	4047438025386	34,5 cm	C
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White	85258091	34,0 cm	
		3.000 g	16,0 cm	
			18,8 l	

T25 Camera Module








	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
 	MX-T25-D016	4047438025263	30,5 cm	C
	CamCore T25, 6MP, B016, Day, White Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	85258091	24,0 cm	
		1.240 g	12,0 cm	8,8 l
 	MX-T25-D016-s	4047438025270	30,5 cm	C
	CamCore T25, 6MP, B016, Day, Silver Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	85258091	24,0 cm	
		1.240 g	12,0 cm	8,8 l
 	MX-T25-D016-d	4047438025287	30,5 cm	C
	CamCore T25, 6MP, B016, Day, Dark Gray Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray	85258091	23,5 cm	
		1.240 g	11,5 cm	8,2 l
 	MX-T25-D016-b	4047438025300	30,5 cm	C
	CamCore T25, 6MP, B016, Day, Black Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	85258091	24,0 cm	
		1.240 g	12,0 cm	8,8 l
 	MX-T25-N016	4047438025317	30,5 cm	C
	CamCore T25, 6MP, B016, Night, White Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	85258091	24,0 cm	
		1.240 g	12,0 cm	8,8 l
 	MX-T25-N016-s	4047438025324	30,5 cm	C
	CamCore T25, 6MP, B016, Night, Silver Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	85258091	24,0 cm	
		1.240 g	12,0 cm	8,8 l
 	MX-T25-N016-d	4047438025331	30,5 cm	C
	CamCore T25, 6MP, B016, Night, Dark Gray Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray	85258091	23,5 cm	
		1.240 g	11,5 cm	8,2 l

**MX-T25-N016-b****CamCore T25, 6MP, B016, Night, Black**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night)
• HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black

4047438025355	30,5 cm	C
85258091	24,0 cm	
1.240 g	12,0 cm	
	8,8 l	

BellRFID Module

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-Bell1-Button-F1 BellRFID Bell Button Set F1 1 big key with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017190 85299065 94 g	10,3 cm 1,7 cm 10,3 cm	C 0,2 l
	MX-Bell1-Button-F2 BellRFID Bell Button Set F2 2 medium-sized keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017176 85299065 94 g	10,3 cm 1,7 cm 10,3 cm	C 0,2 l
	MX-Bell1-Button-F3 BellRFID Bell Button Set F3 1 medium-sized and 2 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label •	4047438017527 85299065 94 g	10,3 cm 1,7 cm 10,3 cm	C 0,2 l
	MX-Bell1-Button-F4 BellRFID Bell Button Set F4 4 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017183 85299065 94 g	10,3 cm 1,7 cm 10,3 cm	C 0,2 l
	MX-Bell1-Button-05 BellRFID Bell Button Set 05 5 small keys (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017534 85299065 94 g	10,3 cm 1,7 cm 10,3 cm	C 0,2 l
	MX-Bell1-Button-XL1 BellRFID Bell Button Set XL1 1 big XL key (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017169 85299065 94 g	10,3 cm 1,7 cm 10,3 cm	C 0,2 l
	MX-Bell1-Core-EXT-PW BellRFID Base Module, White BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	4047438017152 85299065 256 g	10,5 cm 6,8 cm 10,5 cm	C 0,7 l

**MX-Bell1-Core-EXT-SV****BellRFID Base Module, Silver**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrierte RFID-Technik für schlüssellosen Zutritt • Stromversorgung über die Türkamera via Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver

4047438017114	10,5 cm	C
85299065	6,8 cm	
256 g	10,5 cm	
	0,7 l	

**MX-Bell1-Core-EXT-DG****BellRFID Base Module, Dark Gray**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to +50° C / -22 to 122°F • Color: Dark Gray

4047438017121	10,5 cm	C
85299065	10,3 cm	
256 g	6,5 cm	
	0,7 l	

**MX-Bell1-Core-EXT-BL****BellRFID Base Module, Black**





BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black

4047438017145	10,5 cm	C
85299065	6,8 cm	
256 g	10,5 cm	
	0,7 l	





KeypadRFID Module

Article No. / Name / Description	EAN / HS / weight	dimen.	DG
 <p>MX-Keypad1-EXT-PW Keypad With RFID Technology, White</p> <p>Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White</p>	4047438014946	10,5 cm	C
	85371091	6,8 cm	
	210 g	10,5 cm	0,7 l
 <p>MX-Keypad1-EXT-SV Keypad With RFID Technology, Silver</p> <p>Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrierte RFID-Technik für schlüssellosen Zutritt • Stromversorgung über die Türkamera via Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver</p>	4047438014984	10,5 cm	C
	85371091	6,8 cm	
	210 g	10,5 cm	0,7 l
 <p>MX-Keypad1-EXT-DG Keypad With RFID Technology, Dark Gray</p> <p>Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray</p>	4047438014977	10,0 cm	C
	85371091	6,5 cm	
	210 g	10,0 cm	0,7 l
 <p>MX-Keypad1-EXT-BL Keypad With RFID Technology, Black</p> <p>Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black</p>	4047438014960	10,5 cm	C
	85371091	6,8 cm	
	210 g	10,5 cm	0,7 l



Info Module

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-Info1-EXT-PW	4047438014991	10,5 cm	C
	Info Module With LEDs, White	85414090	6,8 cm	
	Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	193 g	10,5 cm	0,7 l
	MX-Info1-EXT-SV	4047438015035	10,5 cm	C
	Info Module With LEDs, Silver	85414090	6,8 cm	
	Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	193 g	10,5 cm	0,7 l
	MX-Info1-EXT-DG	4047438015028	11,0 cm	C
	Info Module With LEDs, Dark Gray	85414090	10,0 cm	
	Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	193 g	6,5 cm	0,7 l
	MX-Info1-EXT-BL	4047438015011	10,5 cm	C
	Info Module With LEDs, Black	85414090	6,8 cm	
	Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	193 g	10,5 cm	0,7 l

Info Module Mx2Wire+

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-2wirePlus-Info1-EXT-PW Info Module Mx2wire+ With LEDs, White	4047438015042 85176200 626 g	22,5 cm 19,2 cm 9,5 cm 4,1 l	C
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White			
	MX-2wirePlus-Info1-EXT-SV Info Module Mx2wire+ With LEDs, Silver	4047438015080 85176200 626 g	22,5 cm 19,2 cm 9,5 cm 4,1 l	C
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver			
	MX-2wirePlus-Info1-EXT-DG Info Module Mx2wire+ With LEDs, Dark Gray	4047438015073 85176200 626 g	23,0 cm 19,0 cm 8,5 cm 3,7 l	C
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray			
	MX-2wirePlus-Info1-EXT-BL Info Module Mx2wire+ With LEDs, Black	4047438015066 85176200 626 g	22,5 cm 19,2 cm 9,5 cm 4,1 l	C
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black			

MX-DoorMaster

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	<p>MX-Door2-INT-ON-PW DoorMaster For On-Wall Mounting</p> <p>Security Door Opener with integrated access code memory for on-wall mounting • Complete set including DoorMaster module, on-wall housing, three device frames, neutral housing covering, battery pack and mounting parts • Suitable for: IP Video Door Station with T2x and S1x as door camera • Built-in backup power supply (battery) for access modules • Doorbell • Direct connection and power supply for electric Door Opener und door sensors • Interface und power supply: MxBus • Two status LEDs, two function buttons, integrated • Speaker (doorbell) • Two galvanically separated inputs (AC/DC, selfpowered • up to 48 V) • Isolated relay output (AC/DC, 24 V/1 A) or port for standard door openers (6 to 12 V AC) • Outlet for MOBOTIX antilift protection (12 V DC) • Protection class: IP20 • Ambient temperature: -5 to 40 °C / 23 to 104 °F • Color: white</p>	<p>4047438021876 85363010 420 g</p>	<p>21,0 cm 8,5 cm 8,5 cm 1,5 l</p>	<p>C</p>
	<p>MX-Door2-INT-PW DoorMaster For In-Wall Mounting</p> <p>Security door opener with internal access code memory: A MOBOTIX door station may be coupled with the MOBOTIX MX-DoorMaster, making it impossible to open the door by forcibly removing the system and bypassing the connecting cable • 2nd product generation, suitable for: IP video door stations with an T2x and S1x as door camera • Integrated (rechargeable) battery power supply for access modules • Security door opener/bell with access code storage (protected against manipulation) • Connection for door opener, door sensor and door lock sensor • Interface and power supply: MxBus (max. 50 m distance to door station) • User interfaces: 2 status LEDs, 2 function buttons, integrated speaker (doorbell) • Inputs: 2 galvanically separated inputs with shared ground connection (AC/DC, self-powered up to 48 V) • Outputs: 1 isolated relay output (AC/DC, 24 V/1 A) or 1 connector for standard door opener (6 to 12 V AC), 1 output for MOBOTIX theft protection (12 V DC) • Protection class: IP20 (DIN EN 60529) • Operating temperature: -5 to 40°C / 23 to 104°F (DIN EN 50155) • Switch time: max. 5 s</p>	<p>4047438019934 85363010 340 g</p>	<p>21,0 cm 8,5 cm 8,5 cm 1,5 l</p>	<p>C</p>









Frames & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-OPT-Frame-1-EXT-PW Single Frame, White Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: White	4047438014892 90079100 268 g	13,5 cm 14,5 cm 5,5 cm	C 1,1 l
	MX-OPT-Frame-1-EXT-SV Single Frame, Silver Suitable for: 1 module, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Silver	4047438014939 90079100 268 g	13,5 cm 14,5 cm 5,5 cm	C 1,1 l
	MX-OPT-Frame-1-EXT-DG Single Frame, Dark Gray Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Dark Gray	4047438014922 90079100 268 g	13,5 cm 14,5 cm 5,5 cm	C 1,1 l
	MX-OPT-Frame-1-EXT-BL Single Frame, Black Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Black	4047438014915 90079100 268 g	13,5 cm 14,5 cm 5,5 cm	C 1,1 l
	MX-OPT-Box-1-EXT-ON-PW Single On-Wall-Housing, White Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: White	4047438015202 90079100 286 g	14,5 cm 13,5 cm 3,5 cm	C 0,7 l
	MX-OPT-Box-1-EXT-ON-SV Single On-Wall-Housing, Silver Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Silver	4047438015240 90079100 286 g	14,5 cm 13,5 cm 3,5 cm	C 0,7 l
	MX-OPT-Box-1-EXT-ON-DG Single On-Wall-Housing, Dark Gray Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Dark Gray	4047438015233 90079100 286 g	14,5 cm 13,5 cm 5,0 cm	C 1,0 l





	<p>MX-OPT-Box-1-EXT-ON-BL Single On-Wall-Housing, Black Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Black</p>	<p>4047438015226 90079100 286 g</p>	<p>14,5 cm C 13,5 cm 3,5 cm 0,7 l</p>
	<p>MX-OPT-Box-1-EXT-IN Single In-Wall-Housing Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities. Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm</p>	<p>4047438015271 90079100 186 g</p>	<p>14,5 cm C 13,5 cm 3,5 cm 0,7 l</p>
	<p>MX-OPT-Frame-2-EXT-PW Double Frame, White Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White</p>	<p>4047438014847 90079100 333 g</p>	<p>23,5 cm C 13,5 cm 3,5 cm 1,1 l</p>
	<p>MX-OPT-Frame-2-EXT-SV Double Frame, Silver Suitable for: 2 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver</p>	<p>4047438014885 90079100 333 g</p>	<p>23,5 cm C 13,5 cm 3,5 cm 1,1 l</p>
	<p>MX-OPT-Frame-2-EXT-DG Double Frame, Dark Gray Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438014878 90079100 333 g</p>	<p>23,5 cm C 13,5 cm 5,0 cm 1,6 l</p>
	<p>MX-OPT-Frame-2-EXT-BL Double Frame, Black Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black</p>	<p>4047438014861 90079100 333 g</p>	<p>23,5 cm C 13,5 cm 3,5 cm 1,1 l</p>
	<p>MX-OPT-Box-2-EXT-ON-PW Double On-Wall-Housing, White Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White</p>	<p>4047438015158 90079100 430 g</p>	<p>23,5 cm C 13,5 cm 3,5 cm 1,1 l</p>
	<p>MX-OPT-Box-2-EXT-ON-SV Double On-Wall-Housing, Silver Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver</p>	<p>4047438015196 90079100 430 g</p>	<p>23,5 cm C 13,5 cm 3,5 cm 1,1 l</p>

	<p>MX-OPT-Box-2-EXT-ON-DG Double On-Wall-Housing, Dark Gray Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438015189 90079100 430 g</p>	<p>23,5 cm 13,5 cm 3,0 cm 1,0 l</p>	C
	<p>MX-OPT-Box-2-EXT-ON-BL Double On-Wall-Housing, Black Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black</p>	<p>4047438015172 90079100 430 g</p>	<p>23,5 cm 13,5 cm 3,5 cm 1,1 l</p>	C
	<p>MX-OPT-Box-2-EXT-IN Double In-Wall-Housing Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm</p>	<p>4047438015264 90079100 270 g</p>	<p>23,5 cm 13,5 cm 3,5 cm 1,1 l</p>	C
	<p>MX-OPT-Frame-3-EXT-PW Triple Frame, White Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White</p>	<p>4047438014793 90079100 426 g</p>	<p>33,5 cm 13,5 cm 5,5 cm 2,5 l</p>	C
	<p>MX-OPT-Frame-3-EXT-SV Triple Frame, Silver Suitable for: 3 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver</p>	<p>4047438014830 90079100 426 g</p>	<p>33,5 cm 13,5 cm 5,5 cm 2,5 l</p>	C
	<p>MX-OPT-Frame-3-EXT-DG Triple Frame, Dark Gray Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438014823 90079100 426 g</p>	<p>33,5 cm 13,5 cm 5,0 cm 2,3 l</p>	C
	<p>MX-OPT-Frame-3-EXT-BL Triple Frame, Black Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black</p>	<p>4047438014816 90079100 426 g</p>	<p>33,5 cm 13,5 cm 5,5 cm 2,5 l</p>	C
	<p>MX-OPT-Box-3-EXT-ON-PW Triple On-Wall-Housing, White Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White</p>	<p>4047438015103 90079100 574 g</p>	<p>33,5 cm 13,5 cm 3,5 cm 1,6 l</p>	C

	<p>MX-OPT-Box-3-EXT-ON-SV Triple On-Wall-Housing, Silver</p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver</p>	<p>4047438015141 90079100 574 g</p>	<p>33,5 cm 13,5 cm 3,5 cm 1,6 l</p>	<p>C</p>
	<p>MX-OPT-Box-3-EXT-ON-DG Triple On-Wall-Housing, Dark Gray</p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438015134 90079100 574 g</p>	<p>33,5 cm 13,5 cm 3,0 cm 1,4 l</p>	<p>C</p>
	<p>MX-OPT-Box-3-EXT-ON-BL Triple On-Wall-Housing, Black</p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black</p>	<p>4047438015127 90079100 574 g</p>	<p>33,5 cm 13,5 cm 3,5 cm 1,6 l</p>	<p>C</p>
	<p>MX-OPT-Box-3-EXT-IN Triple In-Wall-Housing</p> <p>Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm</p>	<p>4047438015257 90079100 362 g</p>	<p>33,5 cm 13,5 cm 3,5 cm 1,6 l</p>	<p>C</p>
	<p>MX-OPT-Frame-4-EXT-PW Quad Frame, White</p> <p>Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: White</p>	<p>4047438017398 90079100 516 g</p>	<p>25,0 cm 25,0 cm 5,5 cm 3,4 l</p>	<p>C</p>
	<p>MX-OPT-Frame-4-EXT-SV Quad Frame, Silver</p> <p>Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Silver</p>	<p>4047438017435 90079100 516 g</p>	<p>25,0 cm 25,0 cm 5,5 cm 3,4 l</p>	<p>C</p>
	<p>MX-OPT-Frame-4-EXT-DG Quad Frame, Dark Gray</p> <p>Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438017428 90079100 516 g</p>	<p>25,0 cm 25,0 cm 5,5 cm 3,4 l</p>	<p>C</p>
	<p>MX-OPT-Frame-4-EXT-BL Quad Frame, Black</p> <p>Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Black</p>	<p>4047438017411 90079100 516 g</p>	<p>25,0 cm 25,0 cm 5,5 cm 3,4 l</p>	<p>C</p>

	MX-OPT-Box-4-EXT-ON-PW Quad On-Wall-Housing, White Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: White	4047438017442 90079100 620 g	25,0 cm 25,0 cm 3,3 cm 2,1 l	C
	MX-OPT-Box-4-EXT-ON-SV Quad On-Wall-Housing, Silver Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Silver	4047438017480 90079100 620 g	25,0 cm 25,0 cm 3,3 cm 2,1 l	C
	MX-OPT-Box-4-EXT-ON-DG Quad On-Wall-Housing, Dark Gray Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Dark Gray	4047438017473 90079100 620 g	25,0 cm 25,0 cm 5,5 cm 3,4 l	C
	MX-OPT-Box-4-EXT-ON-BL Quad On-Wall-Housing, Black Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Black	4047438017466 90079100 620 g	25,0 cm 25,0 cm 3,3 cm 2,1 l	C
	MX-OPT-Box-4-EXT-IN Quad In-Wall-Housing Suitable for: 4 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 218 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	4047438017497 90079100 434 g	25,0 cm 25,0 cm 3,3 cm 2,1 l	C
	MX-OPT-FlatMount-EXT-PW FlatMount Frame, white For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: white	4047438019811 90079100 190 g	14,7 cm 13,7 cm 5,5 cm 1,1 l	C
	MX-OPT-FlatMount-EXT-BL FlatMount Frame, black For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: black	4047438019835 90079100 190 g	14,7 cm 13,7 cm 5,5 cm 1,1 l	C
	MX-OPT-FlatMount-Box-EXT-IN FlatMount Frame In-Wall Housing In-wall housing for FlatMount Frame • To be affixed securely with the subsurface or brick work • Size of cavity for flush-mounting (W x H x D): 112 x 112 x 60 mm	4047438019866 90079100 130 g	13,8 cm 6,5 cm 13,8 cm 1,2 l	C

Building Automation Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG
	MX-AdminCard1	4047438015288	8,5 cm	C
	Admin RFID Transponder Card (Red) For system configuration IP Video Door Station via KeypadRFID and BellRFID • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	85235290	5,5 cm	2 g
	MX-UserCard1	4047438015295	8,5 cm	C
	User RFID Transponder Card (Blue) For keyless entry via with KeypadRFID or BellRFID (IP video door station) • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	85235290	5,5 cm	2 g
	MX-OPT-IO1	4047438013307	10,7 cm	C
	Extended Terminal Board (IO Module) Suitable for: T2x, delivers extended connection options for the door station (e.g., doorbell buttons, light, garage door opener, etc.) • Connect the IO Module to the camera module via MxBus, which connects it to the network. It has eight physical signal inputs that allow it to distinguish in AC operation between a pending full-wave and half-wave. This makes it possible to connect two switches to each signal input terminal so that 16 button inputs are made available. The inputs can be used for, e.g., bell buttons. The outputs can be used for external devices such as a doorbell, or for outdoor lights or garage door openers (via a power relay).	85299065	5,2 cm	86 g
	MX-OPT-IO2	4047438014786	10,7 cm	C
	Ethernet Terminal Board Suitable for: T2x • The Ethernet terminal board is used to connect the door station for the versions without Mx2wire+ technology. It securely connects the camera module with the 8 connected wires of the network patch cable via RJ45 connector. The Ethernet terminal board is screwed on to the housing (on-wall or in-wall) behind the camera module	85299065	5,2 cm	58 g