

# Product Overview

11.06.2019 English EUR



BeyondHumanVision

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.  
HS = Harmonized System Code DG = Discount Group  
MOBOTIX • 11.06.2019 • MOBOTIX accepts no liability arising from printing errors, mistakes and changes. • Revision 11.06.2019

**MOBOTIX**


# Professional Video Systems Outdoor

BeyondHumanVision

MOBOTIX


## M16B AllroundDual Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M16B</b> <b>M16B Body, For M16 Sensor Modules (Day/Night)</b> M16 camera module for connecting one or two M16/M15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	4047438030915 85258091 1.764 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16B-6D6N036</b> <b>M16B Complete Cam 6MP, 2x B036 (Day &amp; Night)</b> IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030922 85258091 1.981 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16B-6D6N041</b> <b>M16B Complete Cam 6MP, 2x B041 (Day &amp; Night)</b> IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030939 85258091 1.974 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16B-6D6N061</b> <b>M16B Complete Cam 6MP, 2x B061 (Day &amp; Night)</b> IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030946 85258091 1.980 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M16B-6D6N079</b> <b>M16B Complete Cam 6MP, 2x B079 (Day &amp; Night)</b> IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B079 standard (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030953 85258091 1.971 g	29,6 cm 19,6 cm 18,0 cm 10,4 l


**Mx-M16B-6D6N119****M16B Complete Cam 6MP, 2x B119 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030960	29,6 cm
85258091	19,6 cm
1.970 	18,0 cm
	10,4 l

**Mx-M16B-6D6N237****M16B Complete Cam 6MP, 2x B237 (Day & Night)**




IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B237 distant tele (f/1.8, horizontal image angle 15°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030977	29,6 cm
85258091	19,6 cm
1.981 	18,0 cm
	10,4 l



## D16B DualDome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-D16B</b> <b>D16B Body, For D16B/D15 Sensor Modules (Day/Night)</b> IP camera module for connecting one or two D16/D15 sensor modules or a D16/D15 lens bridge FIX/PAN (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module/bridge): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): horizontal image angle from 103° to 15° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Incl. 1x standard lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030588 85258091 1.277 g	39,5 cm 29,6 cm 9,0 cm 10,5 l
	<b>Mx-D16B-F-6D6N036</b> <b>D16B Complete Cam 6MP, 2x B036 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030595 85258091 1.646 g	39,5 cm 29,6 cm 18,0 cm 21,0 l
	<b>Mx-D16B-F-6D6N041</b> <b>D16B Complete Cam 6MP, 2x B041 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030601 85258091 1.627 g	39,5 cm 29,6 cm 18,0 cm 21,0 l
	<b>Mx-D16B-F-6D6N061</b> <b>D16B Complete Cam 6MP, 2x B061 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030618 85258091 1.642 g	39,5 cm 29,6 cm 18,0 cm 21,0 l
	<b>Mx-D16B-F-6D6N079</b> <b>D16B Complete Cam 6MP, 2x B079 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B079 wide-angle (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030625 85258091 1.645 g	39,5 cm 29,6 cm 18,0 cm 21,0 l
	<b>Mx-D16B-F-6D6N119</b> <b>D16B Complete Cam 6MP, 2x B119 (Day &amp; Night)</b> IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030632 85258091 1.630 g	39,5 cm 29,6 cm 18,0 cm 21,0 l

**Mx-D16B-F-6D6N237****D16B Complete Cam 6MP, 2x B237 (Day & Night)**

IP camera with two parallel aligned lens units • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B237 tele (f/1.8, horizontal image angle 15°) • Equipment line: Secure • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

4047438030649	39,5 cm
85258091	29,6 cm
1.641 9	18,0 cm
	21,0 l

**Mx-D16B-P-6D6D041****D16B Complete Cam 2x 6MP, Panorama 180° (Day)**

IP camera with PAN lens bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors day, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030656	39,5 cm
85258091	29,6 cm
1.650 9	18,0 cm
	21,0 l








**Mx-D16B-P-6N6N041****D16B Complete Cam 2x 6MP, Panorama 180° (Night)**

IP camera with PAN sensor bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors night, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030663	39,5 cm
85258091	29,6 cm
1.642 9	18,0 cm
	21,0 l

## V16B Vandalism Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-V16B-6D041</b>	4047438031462	26,0 cm
	<b>V16B Complete Cam 6MP, 1x B041 (Day)</b> V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D079</b>	4047438031479	26,0 cm
	<b>V16B Complete Cam 6MP, 1x B079 (Day)</b> V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D6D041</b>	4047438031486	26,0 cm
	<b>V16B Complete Cam 6MP, 2x B041 (Day)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x Color (day), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D6D079</b>	4047438031493	26,0 cm
	<b>V16B Complete Cam 2x 6MP, 2x B079 (Day)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D6N041</b>	4047438031509	26,0 cm
	<b>V16B Complete Cam 2x 6MP, 2x B041 (Day &amp; Night)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6D6N079</b>	4047438031516	26,0 cm
	<b>V16B Complete Cam 2x 6MP, 2x B079 (Day &amp; Night)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm
	<b>Mx-V16B-6N6N041</b>	4047438031523	26,0 cm
	<b>V16B Complete Cam 2x 6MP, 2x B041 (Night)</b> V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258091	26,0 cm

**Mx-V16B-6N6N079****V16B Complete Cam 2x 6MP, 2x B079 (Night)**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing

4047438031530 26,0 cm

85258091 26,0 cm

4.700 g 26,0 cm

17,6 l



## S16B DualFlex Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-S16B</b> <b>S16B Body, For S16B/S15 Sensor Modules</b> S16 camera module (body) for connecting one or two S16/S15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP66/IK06, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), MxBus, USB, Audio (I/O); RS232 via MX Interface Box	4047438031400 85258091 660 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>Mx-S16B-S1</b> <b>S16B Complete Cam, Set 1, 6MP, 1x B016 (Day)</b> S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome • IP66 • Optional connection of a second sensor module (incl. Thermal)	4047438031417 85258091 720 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	<b>Mx-S16B-S2</b> <b>S16B Complete Cam, Set 2, 6MP, 2x B016 (Day)</b> S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	4047438031424 85258091 1.700 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	<b>Mx-S16B-S3</b> <b>S16B Complete Cam, Set 3, 6MP, 2x B016 (Day &amp; Night)</b> S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	4047438031431 85258091 1.700 g	29,6 cm 19,6 cm 9,0 cm 5,2 l

## S26B Flex Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.







	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-S26B-6D016</b>	4047438031448	19,6 cm
	<b>S26B Complete Cam 6MP, B016 (Day)</b> Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091 685 g	15,0 cm 9,0 cm 2,6 l
	<b>Mx-S26B-6N016</b>	4047438031455	19,6 cm
	<b>S26B Complete Cam 6MP, B016 (Night)</b> Hemispheric IP camera with 6 Megapixel Moonlight Sensor, BW (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091 685 g	15,0 cm 9,0 cm 2,6 l



## M26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M26B-6D</b> <b>M26B Body 6MP (Day)</b> IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031042 85258091 1.337 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D016</b> <b>M26B Complete Cam 6MP, B016 (Day)</b> Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031059 85258091 1.342 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D036</b> <b>M26B Complete Cam 6MP, B036 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031066 85258091 1.365 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D041</b> <b>M26B Complete Cam 6MP, B041 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031073 85258091 1.354 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D061</b> <b>M26B Complete Cam 6MP, B061 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031080 85258091 1.361 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	<b>Mx-M26B-6D079</b> <b>M26B Complete Cam 6MP, B079 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031097 85258091 1.359 g	29,6 cm 19,6 cm 18,0 cm 10,4 l

	<p><b>Mx-M26B-6D119</b>  <b>M26B Complete Cam 6MP, B119 (Day)</b>            IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031103            85258091            1.359 G</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6D237</b>  <b>M26B Complete Cam 6MP, B237 (Day)</b>            IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031110            85258091            1.359 G</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6D500</b>  <b>M26B Complete Cam 6MP, B500 (Day)</b>            IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031127            85258091            2.000 G</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N</b>  <b>M26B Body 6MP (Night)</b>            IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031134            85258091            1.344 G</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N016</b>  <b>M26B Complete Cam 6MP, B016 (Night)</b>            Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031141            85258091            1.342 G</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>
	<p><b>Mx-M26B-6N036</b>  <b>M26B Complete Cam 6MP, B036 (Night)</b>            IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438031158            85258091            1.365 G</p>	<p>29,6 cm            19,6 cm            18,0 cm            10,4 l</p>



**Mx-M26B-6N041**

**M26B Complete Cam 6MP, B041 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031165 29,6 cm  
85258091 19,6 cm  
1.354 9 18,0 cm  
10,4 l



**Mx-M26B-6N061**

**M26B Complete Cam 6MP, B061 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031172 29,6 cm  
85258091 19,6 cm  
1.361 9 18,0 cm  
10,4 l



**Mx-M26B-6N079**

**M26B Complete Cam 6MP, B079 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031189 29,6 cm  
85258091 19,6 cm  
1.359 9 18,0 cm  
10,4 l



**Mx-M26B-6N119**

**M26B Complete Cam 6MP, B119 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031196 29,6 cm  
85258091 19,6 cm  
1.359 9 18,0 cm  
10,4 l



**Mx-M26B-6N237**

**M26B Complete Cam 6MP, B237 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031202 29,6 cm  
85258091 19,6 cm  
1.359 9 18,0 cm  
10,4 l



**Mx-M26B-6N500**








**M26B Complete Cam 6MP, B500 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)








4047438031219 29,6 cm  
85258091 19,6 cm  
1.366 9 18,0 cm  
10,4 l

## D26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.



	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-D26B-6D</b>	4047438030670	19,6 cm
	<b>D26B Body 6MP (Day)</b> D26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091	18,0 cm
	<b>Mx-D26B-6D036</b>	4047438030687	19,6 cm
	<b>D26B Complete Cam 6MP, B036 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091	18,0 cm
	<b>Mx-D26B-6D041</b>	4047438030694	19,6 cm
	<b>D26B Complete Cam 6MP, B041 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091	18,0 cm
	<b>Mx-D26B-6D061</b>	4047438030700	19,6 cm
	<b>D26B Complete Cam 6MP, B061 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091	18,0 cm
	<b>Mx-D26B-6D079</b>	4047438030717	19,6 cm
	<b>D26B Complete Cam 6MP, B079 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessor)	85258091	18,0 cm
	<b>Mx-D26B-6D119</b>	4047438030724	19,6 cm
	<b>D26B Complete Cam 6MP, B119 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091	18,0 cm
	<b>Mx-D26B-6D237</b>	4047438030731	19,6 cm
	<b>D26B Complete Cam 6MP, B237 (Day)</b> IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258091	18,0 cm



	<p><b>Mx-D26B-6N</b>  <b>D26B Body 6MP (Night)</b></p> <p>D26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030748 19,6 cm  85258091 18,0 cm  799 G 14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N036</b>  <b>D26B Complete Cam 6MP, B036 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030755 19,6 cm  85258091 18,0 cm  814 G 14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N041</b>  <b>D26B Complete Cam 6MP, B041 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030762 19,6 cm  85258091 18,0 cm  1.580 G 14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N061</b>  <b>D26B Complete Cam 6MP, B061 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030779 19,6 cm  85258091 18,0 cm  1.580 G 14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N079</b>  <b>D26B Complete Cam 6MP, B079 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030786 19,6 cm  85258091 18,0 cm  1.580 G 14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N119</b>  <b>D26B Complete Cam 6MP, B119 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030793 19,6 cm  85258091 18,0 cm  1.580 G 14,8 cm  5,2 l</p>
	<p><b>Mx-D26B-6N237</b>  <b>D26B Complete Cam 6MP, B237 (Night)</b></p> <p>IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)</p>	<p>4047438030809 19,6 cm  85258091 18,0 cm  1.580 G 14,8 cm  5,2 l</p>

## Q26B Hemispheric Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-Q26B-6D016</b>	4047438031387	29,6 cm
	<b>Q26B Complete Cam 6MP, B016 (Day)</b>	85258091	19,6 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	853 g	9,0 cm 5,2 l
	<b>Mx-Q26B-6N016</b>	4047438031394	29,6 cm
	<b>Q26B Complete Cam 6MP, B016 (Night)</b>	85258091	19,6 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	855 g	9,0 cm 5,2 l






# Professional Video Systems Indoor





BeyondHumanVision

MOBOTIX

## c26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-c26B-6D</b> <b>c26B Body 6MP (Day)</b> c26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030489 85258091 431 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-c26B-6D016</b> <b>c26B Complete Cam 6MP, B016, Day</b> Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030496 85258091 433 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-c26B-6D036</b> <b>c26B Complete Cam 6MP, B036, Day</b> IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030502 85258091 444 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-c26B-6N</b> <b>c26B Body 6MP (Night)</b> c26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030519 85258091 431 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-c26B-6N016</b> <b>c26B Complete Cam 6MP, B016, Night</b> Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030526 85258091 433 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-c26B-6N036</b> <b>c26B Complete Cam 6MP, B036, Night</b> IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030533 85258091 444 g	19,6 cm 15,0 cm 9,0 cm 2,6 l

	<p><b>Mx-c26B-AU-6D016</b>  <b>c26B Complete Cam 6MP, B016, Day, Audio Package</b>  Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>	4047438030540 19,6 cm 85258091 15,0 cm 442 9 9,0 cm 2,6 l
	<p><b>Mx-c26B-AU-6D036</b>  <b>c26B Complete Cam 6MP, B036, Day, Audio Package</b>  IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>	4047438030557 19,6 cm 85258091 15,0 cm 446 9 9,0 cm 2,6 l
	<p><b>Mx-c26B-AU-6N016</b>  <b>c26B Complete Cam 6MP, B016, Night, Audio Package</b>  Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>	4047438030564 19,6 cm 85258091 15,0 cm 452 9 9,0 cm 2,6 l
	<p><b>Mx-c26B-AU-6N036</b>  <b>c26B Complete Cam 6MP, B036, Night, Audio Package</b>  IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>	4047438030571 19,6 cm 85258091 15,0 cm 446 9 9,0 cm 2,6 l

## i26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-i26B-6D</b> <b>i26B Body 6MP (Day)</b> i26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030816 85258091 420 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6D016</b> <b>i26B Complete Cam 6MP, B016, Day</b> Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030823 85258091 423 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6D036</b> <b>i26B Complete Cam 6MP, B036, Day</b> IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030830 85258091 440 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6N</b> <b>i26B Body 6MP (Night)</b> i26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030847 85258091 420 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6N016</b> <b>i26B Complete Cam 6MP, B016, Night</b> Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030854 85258091 423 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-i26B-6N036</b> <b>i26B Complete Cam 6MP, B036, Night</b> IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	4047438030861 85258091 440 g	19,6 cm 15,0 cm 9,0 cm 2,6 l

**Mx-i26B-AU-6D016****i26B Complete Cam 6MP, B016, Day, Audio Package**

Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030878 19,6 cm  
85258091 15,0 cm  
429 g 9,0 cm  
2,6 l

**Mx-i26B-AU-6D036****i26B Complete Cam 6MP, B036, Day, Audio Package**

IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030885 19,6 cm  
85258091 15,0 cm  
437 g 9,0 cm  
2,6 l

**Mx-i26B-AU-6N016****i26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030892 19,6 cm  
85258091 15,0 cm  
429 g 9,0 cm  
2,6 l







**Mx-i26B-AU-6N036****i26B Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030908 19,6 cm  
85258091 15,0 cm  
437 g 9,0 cm  
2,6 l

## p26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-p26B-6D</b>	4047438031226	19,6 cm
	<b>p26B Body 6MP, Day</b>	85258091	18,0 cm
		582 g	14,8 cm
			5,2 l
	<p>p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>		
	<b>Mx-p26B-6D016</b>	4047438031233	19,6 cm
	<b>p26B Complete Cam 6MP, B016, Day</b>	85258091	18,0 cm
		574 g	14,8 cm
			5,2 l
	<p>Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>		
	<b>Mx-p26B-6D036</b>	4047438031240	19,6 cm
	<b>p26B Complete Cam 6MP, B036, Day</b>	85258091	18,0 cm
		596 g	14,8 cm
			5,2 l
	<p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>		
	<b>Mx-p26B-6D061</b>	4047438031257	19,6 cm
	<b>p26B Complete Cam 6MP, B061, Day</b>	85258091	18,0 cm
		480 g	14,8 cm
			5,2 l
	<p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Wide lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>		
	<b>Mx-p26B-6D079</b>	4047438031264	19,6 cm
	<b>p26B Complete Cam 6MP, B079, Day</b>	85258091	18,0 cm
		596 g	14,8 cm
			5,2 l
	<p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Standard lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>		
	<b>Mx-p26B-6D119</b>	4047438031271	19,6 cm
	<b>p26B Complete Cam 6MP, B119, Day</b>	85258091	18,0 cm
		480 g	14,8 cm
			5,2 l
	<p>IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Tele lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white</p>		





**Mx-p26B-6D237**

**p26B Complete Cam 6MP, B237, Day**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Distant Tele lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031288 19,6 cm  
85258091 18,0 cm  
480 g 14,8 cm  
5,2 l



**Mx-p26B-6N**

**p26B Body 6MP, Night**

p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031295 19,6 cm  
85258091 18,0 cm  
582 g 14,8 cm  
5,2 l



**Mx-p26B-6N016**

**p26B Complete Cam 6MP, B016, Night**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031301 19,6 cm  
85258091 18,0 cm  
574 g 14,8 cm  
5,2 l



**Mx-p26B-6N036**

**p26B Complete Cam 6MP, B036, Night**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra Wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031318 19,6 cm  
85258091 18,0 cm  
480 g 14,8 cm  
5,2 l



**Mx-p26B-AU-6D**

**p26B Body 6MP, Day, Audio Package**

p26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031325 19,6 cm  
85258091 18,0 cm  
591 g 14,8 cm  
5,2 l



**Mx-p26B-AU-6D016**

**p26B Complete Cam 6MP, B016, Day, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031332 19,6 cm  
85258091 18,0 cm  
480 g 14,8 cm  
5,2 l



**Mx-p26B-AU-6D036**

**p26B Complete Cam 6MP, B036, Day, Audio Package**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031349 19,6 cm  
85258091 18,0 cm  
480 g 14,8 cm  
5,2 l

**Mx-p26B-AU-6N****p26B Body 6MP, Night, Audio Package**

p26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031356	19,6 cm
85258091	18,0 cm
480 9	14,8 cm
	5,2 l

**Mx-p26B-AU-6N016****p26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031363	19,6 cm
85258091	18,0 cm
480 9	14,8 cm
	5,2 l






**Mx-p26B-AU-6N036****p26B Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031370	19,6 cm
85258091	18,0 cm
480 9	14,8 cm
	5,2 l

## v26B Indoor Dome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-v26B-6D</b>	4047438031547	19,6 cm
	<b>v26B Body 6MP, Day, White</b>	85258091	18,0 cm
		726 g	14,8 cm
			5,2 l
	<b>Mx-v26B-6D-b</b>	4047438031554	19,6 cm
	<b>v26B Body 6MP, Day, Black</b>	85258091	18,0 cm
		726 g	14,8 cm
			5,2 l
	<b>Mx-v26B-6D036</b>	4047438031561	19,6 cm
	<b>v26B Complete Cam 6MP, B036, Day, White</b>	85258091	18,0 cm
		737 g	14,8 cm
			5,2 l
	<b>Mx-v26B-6N</b>	4047438031578	19,6 cm
	<b>v26B Body 6MP, Night, White</b>	85258091	18,0 cm
		726 g	14,8 cm
			5,2 l
	<b>Mx-v26B-6N-b</b>	4047438031585	19,6 cm
	<b>v26B Body 6MP, Night, Black</b>	85258091	18,0 cm
		726 g	14,8 cm
			5,2 l



# Professional Video Systems Thermal

BeyondHumanVision

MOBOTIX

## M16B Thermal Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M16TB-R079</b> <b>M16B Thermographic Camera TR, 50 mK, R079 (45°)</b>	4047438030984	29,6 cm
	IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/32° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	90251920	19,6 cm
		2.480 g	18,0 cm
			10,4 l
	<b>Mx-M16TB-R119</b> <b>M16B Thermographic Camera TR, 50 mK, R119 (25°)</b>	4047438030991	29,6 cm
	IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	90251920	19,6 cm
		1.936 g	18,0 cm
			10,4 l
	<b>Mx-M16TB-R237</b> <b>M16B Thermographic Camera TR, 50 mK, R237 (17°)</b>	4047438031004	29,6 cm
	IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	90251920	19,6 cm
		1.942 g	18,0 cm
			10,4 l
	<b>Mx-M16TB-T079</b> <b>M16B Thermographic Camera 50 mK, T079 (45°)</b>	4047438031011	29,6 cm
	IP thermographic camera with T079 thermal lens, horizontal/vertical image angle 45°/32°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	90251920	19,6 cm
		2.460 g	18,0 cm
			10,4 l

**Mx-M16TB-T119****M16B Thermographic Camera 50 mK, T119 (25°)**

IP thermographic camera with T119 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031028	29,6 cm
90251920	19,6 cm
2.460 g	18,0 cm
	10,4 l

**Mx-M16TB-T237****M16B Thermographic Camera 50 mK, T237 (17°)**

IP thermographic camera with T237 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031035	29,6 cm
90251920	19,6 cm
1.946 g	18,0 cm
	10,4 l



## Sensor Modules Thermal For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-SMA-TS-R079</b>	4047438030090	17,5 cm
	<b>Thermal Sensor Module TR For S16/S15, 50 mK, B079 (45°)</b> Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	90275000	14,0 cm
		650 g	13,5 cm
			3,3 l
	<b>Mx-O-SMA-TS-R119</b>	4047438030106	17,5 cm
	<b>Thermal Sensor Module TR For S16/S15, 50 mK, B119 (25°)</b> Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	90275000	14,0 cm
		650 g	13,5 cm
			3,3 l
	<b>Mx-O-SMA-TS-R237</b>	4047438030113	17,5 cm
	<b>Thermal Sensor Module TR For S16/S15, 50 mK, B237 (17°)</b> Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	90275000	14,0 cm
		650 g	13,5 cm
			3,3 l
	<b>Mx-O-SMA-TP-R079</b>	4047438030120	19,6 cm
	<b>PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), White</b> PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	90275000	18,0 cm
		890 g	14,8 cm
			5,2 l
	<b>Mx-O-SMA-TP-R119</b>	4047438030137	19,6 cm
	<b>PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), White</b> PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	90275000	18,0 cm
		890 g	14,8 cm
			5,2 l
	<b>Mx-O-SMA-TP-R237</b>	4047438030144	19,6 cm
	<b>PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), White</b> PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	90275000	18,0 cm
		890 g	14,8 cm
			5,2 l
	<b>Mx-O-SMA-TP-R079-b</b>	4047438030151	19,6 cm
	<b>PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), Black</b> PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	90275000	18,0 cm
		890 g	14,8 cm
			5,2 l

**Mx-O-SMA-TP-R119-b****PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030168	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-SMA-TP-R237-b****PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030175	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-SMA-TS-T079****Thermal Sensor Module For S16/S15, 50 mK, B079 (45°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029049	17,5 cm
90275000	14,0 cm
650 g	13,5 cm
	3,3 l

**Mx-O-SMA-TS-T119****Thermal Sensor Module For S16/S15, 50 mK, B119 (25°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029056	17,5 cm
90275000	14,0 cm
650 g	13,5 cm
	3,3 l

**Mx-O-SMA-TS-T237****Thermal Sensor Module For S16/S15, 50 mK, B237 (17°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029063	17,5 cm
90275000	14,0 cm
650 g	13,5 cm
	3,3 l

**Mx-O-SMA-TP-T079****PTMount-Thermal For S16/S15, 50 mK, B079 (45°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029070	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T119****PTMount-Thermal For S16/S15, 50 mK, B119 (25°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029087	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T237****PTMount Thermal For S16/S15, 50 mK, B237 (17°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029094	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T079-b****PTMount-Thermal For S16, S15, 50 mK, B079 (45°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030021	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T119-b****PTMount-Thermal For S16, S15, 50 mK, B119 (25°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030038	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T237-b****PTMount Thermal For S16, S15, 50 mK, B237 (17°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: black

4047438030045	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l


# MOBOTIX MOVE Cameras

BeyondHumanVision

MOBOTIX




## MOBOTIX MOVE Speed Dome Cameras

### MOBOTIX MOVE Speed Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-SD1A-330</b> <b>MOBOTIX MOVE SpeedDome SD-330</b> MOBOTIX MOVE SpeedDome Network Camera SD-330 • Weatherproof motor-driven ONVIF S / G Dome PTZ camera • Up to 30x optical zoom • Image sensor: 3MP (2065 x 1533), 1/2.8" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 129 mm, viewing angle HxV: 62 ° - 2 ° x 47 ° - 2 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30 B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3at or DC 12V (2.12 A) or AC 24V; max 25.4 W • Warranty: 2 years	4047438031646 85258091 5.700 g	42,5 cm 26,2 cm 35,0 cm 39,0 l
	<b>Mx-SD1A-340-IR</b> <b>MOBOTIX MOVE SpeedDome SD-340-IR</b> MOBOTIX MOVE SpeedDome Network Camera SD-340-IR • Weatherproof, motorized ONVIF S / G dome PTZ camera with built-in IR LEDs (up to 200m) for day and night use • Up to 40x optical zoom • Image sensor: 3MP (2065 x 1533), 1/2.8" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 170 mm, viewing angle HxV: 62 ° - 2 ° x 49 ° - 1 °) with "One Push" autofocus and P-iris with automatic adaptation to changing light situations • IP66 • Ambient temperature -40 to 55°C, Humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30B / s (H.264 , with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: UPoE (Universal PoE) or DC 12V (3.25 A) or AC 24V; max 39 W • Warranty: 2 years	4047438031653 85258091 5.600 g	40,2 cm 25,0 cm 37,0 cm 37,2 l

## MOBOTIX MOVE Vandal Dome Cameras

### MOBOTIX MOVE Vandal Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-VD1A-4-IR</b>	4047438031639	17,5 cm
	<b>MOBOTIX MOVE VandalDome VD-4-IR</b>	85258091	17,5 cm
	MOBOTIX MOVE VandalDome Network Camera VD-4-IR • Weatherproof ONVIF S / G dome camera with integrated IR LEDs (up to 30 m) for day and night operation • Image sensor: 4MP (2688 x 1512), 1/3" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.7: 3 to 9 mm, viewing angle HxV: 103 ° -35 ° x 53 ° -23 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 65°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	1.050 g	17,0 cm 5,2 l
	<b>Mx-VD1A-4-IR-D</b>	4047438034371	17,5 cm
	<b>MOBOTIX MOVE VandalDome VD-4-IR-D</b>	85258091	17,5 cm
	MOBOTIX MOVE VandalDome Network Camera VD-4-IR-D • Weatherproof ONVIF S / G dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Image sensor: 4MP (2688 x 1512), 1/3" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6: 9 to 22 mm, viewing angle H: 35 °-15 °, V: 20 °-9 °) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	1.010 g	17,0 cm 5,2 l
	<b>Mx-VD1A-2-IR</b>	4047438034425	17,5 cm
	<b>MOBOTIX MOVE VandalDome VD-2-IR</b>	85258091	17,5 cm
	MOBOTIX MOVE VandalDome Network Camera VD-2-IR • Weatherproof ONVIF S/G dome camera with integrated IR LEDs (up to 25 m) for day and night operation • Image sensor: 2MP (1920 x 1080), 1/3" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 91 ° -34 °) • IP66 • IK10 • Ambient temperature -30 to 60°C (-22° to 140°F), humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 2MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af • Warranty: 2 years	1.010 g	17,0 cm 5,2 l



## MOBOTIX MOVE Bullet Cameras

### MOBOTIX MOVE Bullet Cameras








	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-BC1A-4-IR</b>	4047438031622	29,6 cm
	<b>MOBOTIX MOVE BulletCamera BC-4-IR</b> MOBOTIX MOVE Bullet Network Camera BC-4-IR • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 30m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.7: 3 to 9 mm, viewing angle HxV: 103 ° -35 ° x 53 ° -23 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 65°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	85258091	20,0 cm
		1.237 g	17,5 cm
			10,4 l
	<b>Mx-BC1A-4-IR-D</b>	4047438034388	29,6 cm
	<b>MOBOTIX MOVE BulletCamera BC-4-IR-D</b> MOBOTIX MOVE Bullet Network Camera BC-4-IR-D • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 40m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6: 9 to 22 mm, viewing angle H: 35 ° -15 °, V: 20 ° -9 °) with Auto Iris with automatic adaptation to changing light situations • IP66 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	85258091	20,0 cm
		1.030 g	17,5 cm
			10,4 l
	<b>Mx-VB1A-4-IR</b>	4047438034395	29,6 cm
	<b>MOBOTIX MOVE VandalBullet VB1A-4-IR</b> MOBOTIX MOVE Bullet Network Camera VB1A-4-IR • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 30m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6: 2.7 to 12 mm, viewing angle H: 99 ° -31 °, V: 53 ° -18 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	85258091	20,0 cm
		1.460 g	17,5 cm
			10,4 l
	<b>Mx-VB1A-4-IR-D</b>	4047438034401	29,6 cm
	<b>MOBOTIX MOVE VandalBullet VB1A-4-IR-D</b> MOBOTIX MOVE Bullet Network Camera VB1A-4-IR-D • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 40m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled varifocal lens (F1.6: 9 to 22 mm, viewing angle H: 35 ° -15 °, V: 20 ° -9 °) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	85258091	20,0 cm
		1.460 g	17,5 cm
			10,4 l
	<b>Mx-BC1A-2-IR</b>	4047438034418	29,6 cm
	<b>MOBOTIX MOVE BulletCamera BC-2-IR</b> MOBOTIX MOVE Bullet Network Camera BC-2-IR • Image sensor: 2MP (1920x1080), 1/3" Progressive CMOS • Weatherproof ONVIF S bullet camera with built-in IR LEDs (up to 15 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 91 ° -34 °) • IP66 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 2MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af • Warranty: 2 years	85258091	20,0 cm
		580 g	17,5 cm
			10,4 l

# Optics

BeyondHumanVision

MOBOTIX

## Sensor Modules 6MP For S16A/S16B And

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-SMA-S-6D016</b>	4047438029100	9,8 cm
	<b>Sensor Module 6MP, B016 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D036</b>	4047438029117	9,8 cm
	<b>Sensor Module 6MP, B036 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D041</b>	4047438029124	9,8 cm
	<b>Sensor Module 6MP, B041 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D061</b>	4047438029131	9,8 cm
	<b>Sensor Module 6MP, B061 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D079</b>	4047438029148	9,8 cm
	<b>Sensor Module 6MP, B079 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D119</b>	4047438029155	9,8 cm
	<b>Sensor Module 6MP, B119 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-S-6D237</b>	4047438029162	9,8 cm
	<b>Sensor Module 6MP, B237 (Day), White</b> Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	90021900 144 g	7,5 cm 9,0 cm 0,7 l

 	<p><b>Mx-O-SMA-S-6D500</b>  <b>Sensor Module 6MP, B500 (Day), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029179            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6DCSV</b>  <b>Sensor Module 6MP, CSVario 4,5-10 mm (Day), White</b>            Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030052            90021900            190 g</p>	<p>10,5 cm            6,8 cm            10,5 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6DCS</b>  <b>Sensor Module 6MP, CS-Mount (Day), White</b>            Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030076            90021900            146 g</p>	<p>10,5 cm            6,8 cm            10,5 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N016</b>  <b>Sensor Module 6MP, B016 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029186            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N036</b>  <b>Sensor Module 6MP, B036 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029193            90021900            170 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N041</b>  <b>Sensor Module 6MP, B041 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029209            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N061</b>  <b>Sensor Module 6MP, B061 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029216            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
 	<p><b>Mx-O-SMA-S-6N079</b>  <b>Sensor Module 6MP, B079 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029223            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>

	<p><b>Mx-O-SMA-S-6N119</b>  <b>Sensor Module 6MP, B119 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029230            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N237</b>  <b>Sensor Module 6MP, B237 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029247            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N500</b>  <b>Sensor Module 6MP, B500 (Night), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white</p>	<p>4047438029254            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6NCSV</b>  <b>Sensor Module 6MP, CSVario 4,5-10 mm (Night), White</b>            Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS (focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65°) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030069            90021900            190 g</p>	<p>10,5 cm            6,8 cm            10,5 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6NCS</b>  <b>Sensor Module 6MP, CS-Mount (Night), White</b>            Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white</p>	<p>4047438030083            90021900            146 g</p>	<p>10,5 cm            6,8 cm            10,5 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6L016</b>  <b>Sensor Module 6MP, B016 (Night LPF), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029261            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6L036</b>  <b>Sensor Module 6MP, B036 (Night LPF), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029278            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6L041</b>  <b>Sensor Module 6MP, B041 (Night LPF), White</b>            Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029285            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>

	<p><b>Mx-O-SMA-S-6L061</b>  <b>Sensor Module 6MP, B061 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029292  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6L079</b>  <b>Sensor Module 6MP, B079 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029308  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6L119</b>  <b>Sensor Module 6MP, B119 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029315  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6L237</b>  <b>Sensor Module 6MP, B237 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029322  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6L500</b>  <b>Sensor Module 6MP, B500 (Night LPF), White</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white</p>	<p>4047438029339  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6D016-b</b>  <b>Sensor Module 6MP, B016 (Day), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029346  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6D036-b</b>  <b>Sensor Module 6MP, B036 (Day), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029353  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>Mx-O-SMA-S-6D041-b</b>  <b>Sensor Module 6MP, B041 (Day), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029360  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>



	<p><b>Mx-O-SMA-S-6D061-b</b>  <b>Sensor Module 6MP, B061 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029377            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6D079-b</b>  <b>Sensor Module 6MP, B079 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029384            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6D119-b</b>  <b>Sensor Module 6MP, B119 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029391            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6D237-b</b>  <b>Sensor Module 6MP, B237 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029407            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6D500-b</b>  <b>Sensor Module 6MP, B500 (Day), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029414            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N016-b</b>  <b>Sensor Module 6MP, B016 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029421            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N036-b</b>  <b>Sensor Module 6MP, B036 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029438            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N041-b</b>  <b>Sensor Module 6MP, B041 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029445            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>

	<p><b>Mx-O-SMA-S-6N061-b</b>  <b>Sensor Module 6MP, B061 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029452            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N079-b</b>  <b>Sensor Module 6MP, B079 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029469            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N119-b</b>  <b>Sensor Module 6MP, B119 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029476            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N237-b</b>  <b>Sensor Module 6MP, B237 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029483            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6N500-b</b>  <b>Sensor Module 6MP, B500 (Night), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black</p>	<p>4047438029490            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6L016-b</b>  <b>Sensor Module 6MP, B016 (Night LPF), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029506            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6L036-b</b>  <b>Sensor Module 6MP, B036 (Night LPF), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029513            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-S-6L041-b</b>  <b>Sensor Module 6MP, B041 (Night LPF), Black</b>            Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029520            90021900            144 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>

 	<p><b>Mx-O-SMA-S-6L061-b</b>  <b>Sensor Module 6MP, B061 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029537  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L079-b</b>  <b>Sensor Module 6MP, B079 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029544  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L119-b</b>  <b>Sensor Module 6MP, B119 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029551  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L237-b</b>  <b>Sensor Module 6MP, B237 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029568  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
 	<p><b>Mx-O-SMA-S-6L500-b</b>  <b>Sensor Module 6MP, B500 (Night LPF), Black</b></p> <p>Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black</p>	<p>4047438029575  90021900  144 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>

## BlockFlexMounts 6MP For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-O-SMA-B-6D016</b>	4047438029797	9,8 cm
	<b>BlockFlexMount 6MP, Incl. Hemispheric B016 (Day)</b> Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D036</b>	4047438029803	9,8 cm
	<b>BlockFlexMount 6MP, Incl. B036 (Day)</b> Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 155 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D041</b>	4047438029810	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B041 (Day)</b> Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 134 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D061</b>	4047438029827	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B061 (Day)</b> Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 136 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D079</b>	4047438029834	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B079 (Day)</b> Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 134 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D119</b>	4047438029841	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B119 (Day)</b> Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 130 g	7,5 cm 9,0 cm 0,7 l
	<b>Mx-O-SMA-B-6D237</b>	4047438029858	10,0 cm
	<b>BlockFlexMount 6MP, Incl. B237 (Day)</b> Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900 134 g	7,5 cm 9,0 cm 0,7 l

	<p><b>Mx-O-SMA-B-6D500</b>  <b>BlockFlexMount 6MP, incl. B500 (Day)</b>            Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029865            90021900            150 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6DCS</b>  <b>BlockFlexMount 6MP, For CS Mount Lens (Day)</b>            Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029766            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N016</b>  <b>BlockFlexMount 6MP, Incl. Hemispheric B016 (Night)</b>            Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029872            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N036</b>  <b>BlockFlexMount 6MP, Incl. B036 (Night)</b>            Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029889            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N041</b>  <b>BlockFlexMount 6MP, Incl. B041 (Night)</b>            Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029896            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N061</b>  <b>BlockFlexMount 6MP, Incl. B061 (Night)</b>            Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029902            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N079</b>  <b>BlockFlexMount 6MP, Incl. B079 (Night)</b>            Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029919            90021900            134 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N119</b>  <b>BlockFlexMount 6MP, Incl. B119 (Night)</b>            Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029926            90021900            130 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>



	<p><b>Mx-O-SMA-B-6N237</b>  <b>BlockFlexMount 6MP, Incl. B237 (Night)</b>            Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029933            90021900            134 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6N500</b>  <b>BlockFlexMount 6MP, Incl. B500 (Night)</b>            Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029940            90021900            155 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6NCS</b>  <b>BlockFlexMount 6MP, For CS Mount Lens (Night)</b>            Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029773            90021900            102 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6L036</b>  <b>BlockFlexMount 6MP, Incl. B036 (Night LPF)</b>            Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029957            90021900            136 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6L041</b>  <b>BlockFlexMount 6MP, Incl. B041 (Night LPF)</b>            Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029964            90021900            132 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6L061</b>  <b>BlockFlexMount 6MP, Incl. B061 (Night LPF)</b>            Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029971            90021900            134 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6L079</b>  <b>BlockFlexMount 6MP, Incl. B079 (Night LPF)</b>            Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029988            90021900            134 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>Mx-O-SMA-B-6L119</b>  <b>BlockFlexMount 6MP, Incl. B119 (Night LPF)</b>            Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)</p>	<p>4047438029995            90021900            130 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>



**Mx-O-SMA-B-6L237****BlockFlexMount 6MP, Incl. B237 (Night LPF)**


Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030007	10,0 cm
90021900	7,5 cm
134 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L500****BlockFlexMount 6MP, Incl. B500 (Night LPF)**

Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030014	10,0 cm
90021900	7,5 cm
150 g	9,0 cm
	0,7 l

















**Mx-O-SMA-B-6LCS****BlockFlexMount 6MP, For CS Mount Lens (Night LPF)**













Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029780	10,0 cm
90021900	7,5 cm
104 g	9,0 cm
	0,7 l

## Sensor Modules 6MP For D16A/D16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
 	<b>Mx-O-SDA-F-6D6N</b> <b>Sensor Bridge FIX For D16/D15, 2x 6MP (Day &amp; Night)</b> Day & Night sensor bridge for D16/D15 Body, including two parallel aligned 6MP sensors (1x Day, 1x Night) and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B036 to B237 possible, to be ordered separately)	4047438030182 90021900 346 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-O-SDA-P-6D6D</b> <b>Sensor Bridge PAN/180° For D16/D15, 2x 6MP (Day)</b> Panorama/180° sensor bridge for D16/D15 Body, including two day sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030199 90021900 346 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 	<b>Mx-O-SDA-P-6N6N</b> <b>Sensor Bridge PAN-N/180° for D16/D15, 2x 6MP (Night)</b> Panorama/180° sensor bridge for D16/D15 Body, including two night sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030205 90021900 344 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 	<b>Mx-O-SDA-S-6D036</b> <b>Sensor Module D16/D15 6MP, Incl. B036 (Day)</b> Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029582 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	<b>Mx-O-SDA-S-6D041</b> <b>Sensor Module D16/D15 6MP, Incl. B041 (Day)</b> Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029599 90021900 66 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	<b>Mx-O-SDA-S-6D061</b> <b>Sensor Module D16/D15 6MP, Incl. B061 (Day)</b> Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029605 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	<b>Mx-O-SDA-S-6D079</b> <b>Sensor Module D16/D15 6MP, Incl. B079 (Day)</b> Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029612 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l

 	<p><b>Mx-O-SDA-S-6D119</b>  <b>Sensor Module D16/D15 6MP, Incl. B119 (Day)</b>            Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048)</p>	<p>4047438029629            90021900            64 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6D237</b>  <b>Sensor Module D16/D15 6MP, Incl. B237 (Day)</b>            Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048)</p>	<p>4047438029636            90021900            68 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N036</b>  <b>Sensor Module D16/D15 6MP, Incl. B036 (Night)</b>            Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)</p>	<p>4047438029643            90021900            68 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N041</b>  <b>Sensor Module D16/D15 6MP, Incl. B041 (Night)</b>            Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029650            90021900            66 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N061</b>  <b>Sensor Module D16/D15 6MP, Incl. B061 (Night)</b>            Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029667            90021900            68 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N079</b>  <b>Sensor Module D16/D15 6MP, Incl. B079 (Night)</b>            Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029674            90021900            68 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N119</b>  <b>Sensor Module D16/D15 6MP, Incl. B119 (Night)</b>            Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029681            90021900            64 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6N237</b>  <b>Sensor Module D16/D15 6MP, Incl. B237 (Night)</b>            Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048)</p>	<p>4047438029698            90021900            68 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>

 	<p><b>Mx-O-SDA-S-6L036</b>  <b>Sensor Module D16/D15 6MP, Incl. B036 (Night LPF)</b>            Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029704            90021900            64 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6L041</b>  <b>Sensor Module D16/D15 6MP, Incl. B041 (Night LPF)</b>            Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029711            90021900            64 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6L061</b>  <b>Sensor Module D16/D15 6MP, Incl. B061 (Night LPF)</b>            Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029728            90021900            64 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6L079</b>  <b>Sensor Module D16/D15 6MP, Incl. B079 (Night LPF)</b>            Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029735            90021900            64 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6L119</b>  <b>Sensor Module D16/D15 6MP, Incl. B119 (Night LPF)</b>            Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029742            90021900            64 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>
 	<p><b>Mx-O-SDA-S-6L237</b>  <b>Sensor Module D16/D15 6MP, Incl. B237 (Night LPF)</b>            Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)</p>	<p>4047438029759            90021900            64 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>

# Camera Accessories

## HD Premium Lenses

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-B036</b> <b>Ultra Wide Lens B036, Focal Length: 3.6 mm</b> Ultra Wide lens B036 • HD premium quality • Focal length: 3.6 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 103° x 77° (up to 5MP resolution) and 122° x 80° (6MP resolution)	4047438026536 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B041</b> <b>Super Wide Lens B041, Focal Length: 4.1 mm</b> Super Wide lens B041 • HD premium quality • Focal length: 4.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 90° x 67° (up to 5MP resolution) and 110° x 70° (6MP resolution)	4047438026543 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B061</b> <b>Wide Lens B061, Focal Length: 6.1 mm</b> Wide lens B061 • HD premium quality • Focal length: 6.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 60° x 45° (up to 5MP resolution) and 70.5° x 46° (6MP resolution)	4047438026550 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B079</b> <b>Standard Lens B079, Focal Length: 7.9 mm</b> Standard lens B079 • HD premium quality • Focal length: 7.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 45° x 34° (up to 5MP resolution) and 54° x 36° (6MP resolution)	4047438026567 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B119</b> <b>Tele Lens B119, Focal Length: 11.9 mm</b> Tele lens B119 • HD premium quality • Focal length: 11.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 31° x 23° (up to 5MP resolution) and 36° x 24.5° (6MP resolution)	4047438026574 90021900 30 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B237</b> <b>Distant Tele Lens B237, Focal Length: 23.7 mm</b> Distant Tele lens B237 • HD premium quality • Focal length: 23.7 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 15° x 11° (up to 5MP resolution) and 17° x 11.5° (6MP resolution)	4047438026581 90021900 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-B500</b> <b>Super Tele Lens B500, Focal Length: 50 mm</b> Super Tele lens B500 • HD premium quality • Focal length: 50 mm • Aperture: f/2.5 • Image angle (horizontal x vertical): 8° x 6° (up to 5MP resolution) and 9° x 6° (6MP resolution) • For mounting this lens on the M2x, the extended replacement lens cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL)	4047438026598 90021900 52 g	9,0 cm 7,5 cm 5,0 cm 0,3 l



**MX-B045-100-CS****CSVario Lens For Cameras With CS-Mount**

CS Vario lens B045-100-CS • HD premium quality • Variable focal length: 4,5-10 mm • Variable aperture: f/1.6-2.3 • Variable image angle (horizontal x vertical): 39°-89° x 29° -65°

4047438026604	9,0 cm
90021900	7,5 cm
66 g	5,0 cm
	0,3 l

**MX-SM-OPT-POL****Polarization Filter For Sensor Modules**

Suitable for all M1x/S1x sensor modules except with the lenses B016, B036, B500 and CSVario or CS Mount • Filter replaces the lens cover (made of glass) • Example: Recognition of people through the windshield of a car - the filter reduces the mirror reflection (and about 50 % of the sensor light sensitivity)

4047438019781	9,0 cm
90079100	7,5 cm
28 g	5,0 cm
	0,3 l

## Domes &amp; Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-M24M-OPT-LCSK</b> <b>Replacement Lens Cover M2x, Standard</b> Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Weather lens protection made of plastic (IP66)	4047438012980 90079100 32 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-M24M-OPT-LCSG</b> <b>Replacement Lens Cover M2x, With Glass Pane</b> Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438012997 90079100 38 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-M24M-OPT-LCGL</b> <b>Replacement Lens Cover M2x, Extended</b> Suitable for: M2x and S1x/M1x sensor module with CSVario lens B045-100-CS or M2x with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438013000 90079100 44 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-OPT-DK-L11</b> <b>Replacement Cover Hemispheric</b> Suitable for: Hemispheric sensor modules (for S1x/M1x), S26, S1xM, T2x and Q2x with Vanadlism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)	4047438016469 90079100 24 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-D15-OPT-DCT</b> <b>Replacement Cover D1x/v2x, Standard</b> Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed)	4047438018227 90079100 54 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>MX-D15-OPT-DCS</b> <b>Replacement Cover D1x/v2x, Tinted</b> Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed) • Tinted (50%) for especially bright environments	4047438018210 90079100 54 g	19,6 cm 14,8 cm 9,0 cm 2,6 l
	<b>MX-D15-DCT-XL</b> <b>Replacement Cover D1x FIX/PAN, XL</b> Suitable for: D1x PAN/180° and FIX/Day&Night models • Polycarbonate (1.5 mm)	4047438027519 90079100 281 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

	<p><b>MX-D15-DCS-XL</b>  <b>Replacement Cover D1x PAN/FIX, XL Tinted</b>            Suitable for: D1x PAN/180° and FIX/Day&amp;Night models • Tinted (50%) for especially bright environments • Polycarbonate (1.5 mm)</p>	<p>4047438027526            90079100            60 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>MX-D24M-OPT-DCT</b>  <b>Replacement Cover D2x, Standard</b>            Suitable for: D2x • With sealing ring</p>	<p>4047438011419            90079100            150 g</p>	<p>19,6 cm            15,0 cm            9,0 cm            2,6 l</p>
	<p><b>MX-D24M-OPT-DCS</b>  <b>Replacement Cover D2x, Tinted</b>            Suitable for: D2x • With sealing ring • Tinted (50%) for especially bright environments</p>	<p>4047438011402            90079100            150 g</p>	<p>19,6 cm            15,0 cm            9,0 cm            2,6 l</p>
	<p><b>MX-D15-Vandal-ESMA</b>  <b>Vandalism Set For D1x, Matt</b>            Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models</p>	<p>4047438018173            90079100            1.012 g</p>	<p>39,5 cm            29,6 cm            9,0 cm            10,5 l</p>
	<p><b>MX-D15-DCT-V</b>  <b>Replacement Cover D1x/v2x, Vandalism</b>            Reinforced replacement cover (polycarbonate, 3 mm) for D1x and v25 Vandalism Sets • Suitable for: D1x and v2x • Not for D1x PAN/180° and FIX/Day&amp;Night models (XL cover needed)</p>	<p>4047438027533            90079100            278 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>MX-D24M-Vandal-ESMA</b>  <b>Vandalism Set For D2x, Matt</b>            Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)</p>	<p>4047438011143            90079100            672 g</p>	<p>30,5 cm            24,0 cm            12,0 cm            8,8 l</p>
	<p><b>MX-D25-DCT-V</b>  <b>Replacement D2x, Vandalism</b>            Reinforced replacement cover (polycarbonate, 3 mm) for D2x Vandalism Kits • With sealing ring</p>	<p>4047438027700            90079100            60 g</p>	<p>19,6 cm            18,0 cm            14,8 cm            5,2 l</p>
	<p><b>MX-Q24M-Vandal-ESMA</b>  <b>Vandalism Set For Q2x, Matt</b>            Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish matt • Incl. safety screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available</p>	<p>4047438011273            90079100            590 g</p>	<p>29,6 cm            19,6 cm            9,0 cm            5,2 l</p>

**MX-MT-v25-V****Vandalism Set For v2x**

Suitable for: v2x without On-Wall Mounting Set with Audio • Stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only without On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

4047438027601	29,6 cm
90079100	19,6 cm
502 g	9,0 cm
	5,2 l


**MX-MT-v25-V-XL****Vandalism Set For v2x With On-Wall Mounting Set**

Suitable for: v2x with On-Wall Mounting Set with Audio • XL stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only with mounted On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+


4047438027625	29,6 cm
90079100	19,6 cm
680 g	9,0 cm
	5,2 l

## Mounts For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-FLEX-OPT-DM-PW</b> <b>DualMount S1x, White</b> For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all available sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	4047438017626 90079100 414 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>MX-FLEX-OPT-SM-PW</b> <b>SurroundMount S1x, White</b> For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all GMP Sensor modules (B016 to B500 and CS Mount) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	4047438016407 90079100 392 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>MX-PTMount-OPT-PW</b> <b>PTMount S1x, White</b> Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S1x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: white	4047438021166 90079100 634 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>MX-FLEX-OPT-DM-BL</b> <b>DualMount S1x, Black</b> For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all screwable sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	4047438021869 90079100 414 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>MX-FLEX-OPT-SM-BL</b> <b>SurroundMount S1x, Black</b> For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all screwable sensor modules • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	4047438021845 90079100 392 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>MX-PTMount-OPT-BL</b> <b>PTMount S1x, Black</b> Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S1x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black	4047438021852 90079100 634 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>MX-HALO-EXT-PW</b> <b>HaloMount S1x, White</b> Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	4047438017664 90079100 175 g	13,5 cm 12,0 cm 4,5 cm 0,7 l

	<p><b>MX-HALO-EXT-BL</b>  <b>HaloMount S1x, Black</b></p> <p>Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •</p>	<p>4047438017671  90079100  175 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-HALO-EXT-CM</b>  <b>HaloMount S1x, Matt Chrome</b></p> <p>Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)</p>	<p>4047438017633  90079100  175 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-HALO-EXT-CO</b>  <b>HaloMount S1x, Chrome</b></p> <p>Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)</p>	<p>4047438017640  90079100  175 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-HALO-EXT-NG</b>  <b>HaloMount S1x, Brushed Nickel</b></p> <p>Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)</p>	<p>4047438017657  90079100  175 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-HALO-SP-EXT-PW</b>  <b>SpeakerMount S1x, White</b></p> <p>Integrated speaker incl. mount, white • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included</p>	<p>4047438017688  85182200  273 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-HALO-SP-EXT-CM</b>  <b>SpeakerMount S1x, Matt Chrome</b></p> <p>Integrated speaker incl. mount, matt chrome • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included</p>	<p>4047438017695  85182200  273 g</p>	<p>13,5 cm  12,0 cm  4,5 cm  0,7 l</p>
	<p><b>MX-S14-OPT-MK-CW</b>  <b>Extension Set Sensor Module, 40 mm And 15°</b></p> <p>Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut</p>	<p>4047438016384  90079100  96 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-S14-OPT-MK-EX</b>  <b>Extension Sensor Module, 40 mm</b></p> <p>1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all (screwable) S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions</p>	<p>4047438016391  90079100  62 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>



**MX-FLEX-OPT-AM-BL****AudioMount S26/S1xM, Self-Adhesive**









Suitable for: S26, S15M, S14M • Easy, quick and concealed mounting with adhesive foil (e.g. behind a stainless steel plate) • Speaker and microphone with camera connection cable included • Use of the camera as a door station by connecting an external doorbell (e.g., connected via MX-232-IO-Box)

4047438019873	24,0 cm
85299065	13,6 cm
386 g	5,3 cm
	1,7 l

## Camera Mounts

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-M-OWA-AU</b> <b>On-Wall Mounting Set With Audio For v26, White</b> On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	4047438030328 90079100 510 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>Mx-M-OWA-AU-b</b> <b>On-Wall Mounting Set With Audio For v26, Black</b> On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	4047438030335 90079100 510 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>MX-MT-OW2-AUD</b> <b>On-Wall Mounting Set With Audio For v25, White</b> Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	4047438027632 90079100 500 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>MX-MT-OW2-AUD-b</b> <b>On-Wall Mounting Set With Audio For v25, Black</b> Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	4047438027670 90079100 500 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	<b>MX-MT-TUBE</b> <b>MxTubeMount Ceiling Suspension System</b> For suspended ceiling installation of the cameras M1x/M2x/v2x/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D2x/Q2x/c2x/p2x (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection wire (length: 2.2 m/7.2 ft) • Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4" according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color/material of choice	4047438027557 90079100 870 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	<b>MX-MT-TUBE100</b> <b>MxTube, 1 m</b> Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	4047438027687 90079100 700 g	106,0 cm 4,0 cm 4,0 cm 1,7 l
	<b>MX-MT-TUBE200</b> <b>MxTube, 2 m</b> Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	4047438027564 90079100 1.390 g	212,5 cm 4,0 cm 4,0 cm 3,4 l

	<p><b>MX-OPT-UP1</b> <b>Cavity Wall Installation Set i2x</b></p> <p>Cavity Wall Installation Set for the i2x • With cavity wall socket, stainless steel mounting plate, 2 Allen screws with washers • For installing the camera directly on the mounting plate, no dowels required • Mounting plate is screwed onto the cavity wall socket • Recommended only for wall installations</p>	<p>4047438022118 90079100 158 g</p>	<p>14,8 cm 9,8 cm 9,0 cm 1,3 l</p>
	<p><b>MX-OPT-AP2</b> <b>On-Wall Mounting Set For i2x</b></p> <p>Suitable for: i25 • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera • Camera distance from the wall: ca. 25 mm • Recommended only for wall installation • Color: white</p>	<p>4047438025898 90079100 136 g</p>	<p>14,8 cm 9,8 cm 9,0 cm 1,3 l</p>
	<p><b>MX-MT-OW-1</b> <b>On-Wall Mounting Set For c2x/p2x</b></p> <p>Suitable for: c2x und p2x • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera and integrates additional modules (e.g. two Interface Boxes) • Camera distance from the wall: ca. 80 mm • Diameter: 140 mm • Recommended only for ceiling installation • Color: White</p>	<p>4047438027083 90079100 514 g</p>	<p>19,6 cm 18,0 cm 14,8 cm 5,2 l</p>
	<p><b>MX-MT-CM-1</b> <b>Corner Mounting Set For c2x</b></p> <p>Suitable for: c2x • Consists of on-wall mount and mounting parts • Mounting in a room corner • Mounting position plus 35° tilt angle enable one camera (e.g. c2x with 103° lens B036) to capture an entire room • Color: White</p>	<p>4047438027076 90079100 448 g</p>	<p>29,6 cm 19,6 cm 9,0 cm 5,2 l</p>
	<p><b>MX-OPT-AP</b> <b>On-Wall Mounting Set For Q2x/D2x/ExtIO</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm</p>	<p>4047438011358 90079100 612 g</p>	<p>29,6 cm 19,6 cm 9,0 cm 5,2 l</p>
	<p><b>MX-OPT-AP-10DEG</b> <b>On-Wall Mounting Set For Q2x/D2x/ExtIO, 10°</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Camera can be mounted at a 10° tilt angle • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm</p>	<p>4047438010283 90079100 552 g</p>	<p>29,6 cm 19,6 cm 9,0 cm 5,2 l</p>
	<p><b>MX-D15-OPT-WHMH-Set</b> <b>Wall &amp; Pole/Corner Mount Set For D1x</b></p> <p>Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438018159 90079100 6.280 g</p>	<p>41,0 cm 31,0 cm 39,0 cm 49,6 l</p>
	<p><b>MX-OPT-WHMH-Set</b> <b>Wall &amp; Pole/Corner Mount Set For Q2x/D2x/ExtIO</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438011396 90079100 3.380 g</p>	<p>41,0 cm 31,0 cm 20,0 cm 25,4 l</p>

	<p><b>MX-WH-Dome</b>  <b>Wall Mount For D1x</b></p> <p>Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts</p>	<p>4047438002233  90079100  2.020 G</p>	<p>39,5 cm  29,6 cm  18,0 cm  21,0 l</p>
	<p><b>MX-OPT-WH</b>  <b>Wall Mount For Q2x/D2x/ExtIO</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts</p>	<p>4047438011372  90079100  886 G</p>	<p>29,6 cm  19,6 cm  18,0 cm  10,4 l</p>
	<p><b>MX-WH-SecureFlex</b>  <b>Wall/Ceiling Mount For M12/M10/M1</b></p> <p>Suitable for: M12/M10/M1 (not M15) • Shock-resistant fiberglass-reinforced composite (PBT), white • Patented tamper-proof concealed cabling • Can be turned left/right 90°, tilted downwards 70° • Includes stainless steel mounting set, caps and dowels</p>	<p>4047438002219  90079100  390 G</p>	<p>20,0 cm  15,0 cm  11,0 cm  3,3 l</p>
	<p><b>MX-MH-Dome-ESWS</b>  <b>Pole/Corner Mount For MX-WH-Dome</b></p> <p>Suitable for: D1x • Pole/corner mount for fastening of wall mount MX-WH-Dome (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438002240  90079100  3.000 G</p>	<p>34,0 cm  18,5 cm  11,5 cm  7,2 l</p>
	<p><b>MX-MH-SecureFlex-ESWS</b>  <b>Pole Mount For M1x/M2x</b></p> <p>Suitable for: M1x, M2x • Mount for fastening the standard camera wall mount SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438002226  90079100  1.230 G</p>	<p>20,0 cm  15,2 cm  8,0 cm  2,4 l</p>
	<p><b>MX-OPT-MH</b>  <b>Pole/Corner Mount For MX-OPT-WH</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Mount for fastening the wall mount MX-OPT-WH (to be ordered separately) • A set consisting of Pole/Corner Mount and Wall Mount is also available (MX-OPT-WHMH-Set) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm</p>	<p>4047438011389  90079100  2.050 G</p>	<p>21,0 cm  20,0 cm  17,0 cm  7,1 l</p>
	<p><b>MX-OPT-IC-ESMA</b>  <b>In-Ceiling Set For Q2x/D2x/ExtIO, Matt</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (matt) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm</p>	<p>4047438011433  90079100  724 G</p>	<p>29,6 cm  19,6 cm  9,0 cm  5,2 l</p>
	<p><b>MX-OPT-IC-ESPO</b>  <b>In-Ceiling Set For Q2x/D2x/ExtIO, Polished</b></p> <p>Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (polished) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm</p>	<p>4047438011426  90079100  724 G</p>	<p>29,6 cm  19,6 cm  9,0 cm  5,2 l</p>



**MX-OPT-IC**  
**In-Ceiling Set For Q2x/D2x/ExtIO, White**

Suitable for: Q2x, D2x, ExtIO • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011365	29,6 cm
90079100	19,6 cm
412 g	9,0 cm
	5,2 l



**MX-DH-M24-SecureFlex**  
**Ceiling Mount For M16/M26**

Suitable for: M16, M26, M15, M25, M24 • Mounting set to convert the VarioFlex wall mount into a ceiling mount • Incl. mount, M6x30 connection screw, washer, M6 nut and rubber seal • Turning/tilting (mechanically): 360° horizontally, -90° to +20° vertically • Suspended ceiling installation with additional MxTubeMount (MX-MT-TUBE)

4047438015653	15,0 cm
90079100	9,5 cm
160 g	9,0 cm
	1,3 l



**MX-OPT-TW-Demo-1**  
**Demo Table/Wall Mount For Q2x/D2x**

Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).

4047438013055	14,8 cm
90079100	9,8 cm
170 g	9,0 cm
	1,3 l

## MOBOTIX Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-FLEX-OPT-CBL-015</b> <b>Sensor Module Cable For M15/M16, 0.15 m</b> Length: 0.15 m/0,5 ft, to connect one sensor module (inside camera housing), angled plugs, only for M15/M16	4047438019941 85444210 16 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-FLEX-OPT-CBL-05</b> <b>Sensor Cable For S1x, 0.5 m</b> Sensor cable, length 0.5 m/1,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	4047438018890 85444210 66 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-FLEX-OPT-CBL-1</b> <b>Sensor Cable For S1x, 1 m</b> Sensor cable, length 1 m/3,3 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	4047438018883 85444210 80 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-FLEX-OPT-CBL-2</b> <b>Sensor Cable For S1x, 2 m</b> Sensor cable, length 2 m/6,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	4047438018876 85444210 116 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-FLEX-OPT-CBL-3</b> <b>Sensor Cable For S1x (6MP/Thermal), 3 m</b> Sensor cable, length 3 m/9,8 ft • For connecting optical sensor modules and BlockFlexMounts with 6MP sensors and Thermal sensor modules to the S15/S16 camera module • Not compatible with PTMount-Thermal, S14D and 5MP modules	4047438024303 85444210 144 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-AB-05</b> <b>USB Device Cable For M/Q/T2x, 0.5 m</b> MiniUSB angled > USB-A straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device	4047438016728 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-AB-2</b> <b>USB Device Cable For M/Q/T2x, 2 m</b> MiniUSB angled > USB-A straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB-Gerät	4047438016711 85444210 102 g	10,0 cm 7,5 cm 9,0 cm 0,7 l



	<b>MX-CBL-MU-EN-AB-5</b> <b>USB Device Cable For M/Q/T2x, 5 m</b> MiniUSB angled > USB-A straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device	4047438016704 85444210 194 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-EN-PG-05</b> <b>ExtIO Cable For M/Q/T2x, 0,5 m</b> MiniUSB angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO	4047438020947 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-EN-PG-2</b> <b>ExtIO Cable For M/Q/T2x, 2 m</b> MiniUSB angled > MiniUSB+ angled • Length 2 m/6,6 m • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO	4047438020930 85444210 102 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-EN-PG-5</b> <b>ExtIO Cable for M/Q/T2x, 5 m</b> MiniUSB angled > MiniUSB+ angled • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO	4047438020923 85444210 194 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-PG-AB-05</b> <b>USB Device Cable For D25/D26, 0,5 m</b> MiniUSB+ angled > USB-A straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect ext. USB device	4047438020916 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-PG-AB-2</b> <b>USB Device Cable For D25/D26, 2 m</b> MiniUSB+ angled > USB-A straight • Length 2 m/6,6 ft • For D25/D26 • to connect ext. USB device	4047438020909 85444210 102 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-PG-AB-5</b> <b>USB Device Cable For D25/D26, 5 m</b> MiniUSB+ angled > USB-A straight • Length 5 m/16,4 ft • For D25/D26 • To connect ext. USB device	4047438020893 85444210 194 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-CBL-MU-EN-PG-EN-PG-05</b> <b>ExtIO Cable For D25/D26, 0,5 m</b> MiniUSB+ angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-ExtIO	4047438020886 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

	<p><b>MX-CBL-MU-EN-PG-EN-PG-2</b>  <b>ExtIO Cable For D25/D26, 2 m</b>  MiniUSB+ angled &gt; MiniUSB+ angled • Length 2 m/6,6 ft • For D25/D26 • To connect MX-ExtIO</p>	<p>4047438020879  85444210  102 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-PG-EN-PG-5</b>  <b>ExtIO Cable For D25/D26, 5 m</b>  MiniUSB+ angled &gt; MiniUSB+ angled • Length 5 m/16,4 ft • For D25/D26 • To connect MX-ExtIO</p>	<p>4047438020862  85444210  194 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-PG-STR-05</b>  <b>232-IO-Box Cable For D25/D26, 0.5 m</b>  MiniUSB+ angled &gt; MiniUSB straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-232-IO-Box</p>	<p>4047438020855  85444210  52 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-PG-STR-2</b>  <b>232-IO-Box Cable For D25/D26, 2 m</b>  MiniUSB+ angled &gt; MiniUSB straight • Length 2 m/6,6 ft • For D25/D26 • To connect MX-232-IO-Box</p>	<p>4047438020848  85444210  102 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-PG-STR-5</b>  <b>232-IO-Box Cable For D25/D26, 5 m</b>  MiniUSB+ angled &gt; MiniUSB straight • Length 5 m/16,4 ft • For D25/D26 • To connect MX-232-IO-Box</p>	<p>4047438020831  85444210  194 g</p>	<p>9,8 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-STR-05</b>  <b>232-IO-Box Cable For M/Q/T2x, 0.5 m</b>  MiniUSB angled &gt; MiniUSB straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box</p>	<p>4047438016667  85444210  48 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-STR-2</b>  <b>232-IO-Box Cable For M/Q/T2x, 2 m</b>  MiniUSB angled &gt; MiniUSB straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box</p>	<p>4047438016650  85444210  94 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>
	<p><b>MX-CBL-MU-EN-STR-5</b>  <b>232-IO-Box Cable For M/Q/T2x, 5 m</b>  MiniUSB angled &gt; MiniUSB straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box</p>	<p>4047438016643  85444210  188 g</p>	<p>10,0 cm  7,5 cm  9,0 cm  0,7 l</p>

	<p><b>MX-CBL-MU-STR-05</b>  <b>232-IO-Box Cable For D/S/V1x, 0.5 m</b>            MiniUSB straight &gt; MiniUSB straight • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box</p>	<p>4047438016605            85444210            50 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>MX-CBL-MU-STR-2</b>  <b>232-IO-Box Cable For D/S/V1x, 2 m</b>            MiniUSB straight &gt; MiniUSB straight • Length 2 m/6,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box</p>	<p>4047438016599            85444210            94 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>MX-CBL-MU-STR-5</b>  <b>232-IO-Box Cable For D/S/V1x, 5 m</b>            MiniUSB straight &gt; MiniUSB straight • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box</p>	<p>4047438016445            85444210            184 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>MX-CBL-MU-STR-AB-05</b>  <b>USB Device Cable For D/S/V1x, 0.5 m</b>            MiniUSB straight &gt; USB-A straight • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device</p>	<p>4047438016698            85444210            56 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>MX-CBL-MU-STR-AB-2</b>  <b>USB Device Cable For D/S/V1x, 2 m</b>            MiniUSB straight &gt; USB-A straight • Length 2 m/6,6 ft • D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device</p>	<p>4047438016681            85444210            102 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>MX-CBL-MU-STR-AB-5</b>  <b>USB Device Cable For D/S/V1x, 5 m</b>            MiniUSB straight &gt; USB-A straight • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device</p>	<p>4047438016674            85444210            196 g</p>	<p>10,0 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>MX-CBL-MU-STR-EN-PG-05</b>  <b>ExtIO Cable For D/S/V1x, 0.5 m</b>            MiniUSB straight &gt; MiniUSB+ angled • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO</p>	<p>4047438020978            85444210            52 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>MX-CBL-MU-STR-EN-PG-2</b>  <b>ExtIO Cable For D/S/V1x, 2 m</b>            MiniUSB straight &gt; MiniUSB+ angled • Length 2 m/6,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO</p>	<p>4047438020961            85444210            102 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>

**MX-CBL-MU-STR-EN-PG-5****ExtIO Cable For D/S/V1x, 5 m**

MiniUSB straight > MiniUSB+ angled • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO

4047438020954	9,8 cm
85444210	7,5 cm
194 g	9,0 cm
	0,7 l

**MX-OPT-CBL-LAN-1****Ethernet Patch Cable, 1 m**

Ethernet Patch Cable for MOBOTIX systems • Length 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012300	23,5 cm
85444210	15,0 cm
36 g	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-10****Ethernet Patch Cable, 10 m**

Ethernet Patch Cable for MOBOTIX systems • Length 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012331	27,0 cm
85444210	17,0 cm
264 g	4,0 cm
	1,8 l

**MX-OPT-CBL-LAN-2****Ethernet Patch Cable, 2 m**

Ethernet Patch Cable for MOBOTIX systems • Length 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012317	23,5 cm
85444210	15,0 cm
62 g	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-5****Ethernet Patch Cable, 5 m**

Ethernet Patch Cable for MOBOTIX systems • Length 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012324	23,5 cm
85444210	15,0 cm
144 g	4,0 cm
	1,4 l

**MX-FLEX-IO-CBL-015****IO Connection Cable For M15/M16, 0.15 m**

Length: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M15/M16 (inside camera housing)

4047438019958	13,5 cm
85444210	8,0 cm
10 g	2,0 cm
	0,2 l

**MX-CBL-NPA-BAT-2****NPA Battery Cable, 2 m**

NPA-PoE Battery Cable • Provides a power supply for the camera from car batteries or other power sources from 12 to 24 Volts • With self-resetting fuse • RJ45 connector to PoE injector, „+/-“ terminals for power source • Can only be used with Mx-NPA PoE injector • Length: 2 m/6.6 ft








4047438013949	10,0 cm
85444210	7,5 cm
68 g	9,0 cm
	0,7 l







## Other Camera Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p><b>MX-OPT-Ring-L10-L12-BL</b>  <b>Sealing Ring For Hemispheric Sensor Modules, Black</b>            Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black</p>	<p>4047438021241            90079100            16 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>
	<p><b>MX-OPT-Ring-L10-L12-PW</b>  <b>Sealing Ring For Hemispheric Sensor Modules, White</b>            Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white</p>	<p>4047438021234            90079100            16 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>
	<p><b>MX-OPT-SEC-SCREWS-SET</b>  <b>Security Screw Set With Allen Bit For M1x/M2x</b>            Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)</p>	<p>4047438021265            90079100            120 g</p>	<p>7,5 cm            4,9 cm            9,0 cm            0,3 l</p>
	<p><b>MX-SM-Blind-PW</b>  <b>Blind Module M1x</b>            For M1x and M1x Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.</p>	<p>4047438019965            90079100            46 g</p>	<p>9,0 cm            7,5 cm            5,0 cm            0,3 l</p>

## MOBOTIX MOVE Accessories

### MOBOTIX MOVE Accessories








	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-A-SD-DCS</b> <b>Tinted Dome For MOBOTIX MOVE SD-330</b> Tinted replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330 • For particularly bright environments	4047438031776 90079100 300 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	<b>Mx-A-SD-DCT</b> <b>Dome (Standard) For MOBOTIX MOVE SD-330</b> Standard replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330	4047438031783 90079100 300 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	<b>Mx-A-VD-DCS</b> <b>Tinted Dome For MOBOTIX MOVE VandalDome</b> Tinted replacement dome for particularly bright environments • Suitable for all MOBOTIX MOVE VandalDome cameras	4047438031714 90079100 210 g	16,1 cm 16,1 cm 11,5 cm 3,0 l
	<b>Mx-A-VD-DCT</b> <b>Dome (Standard) For MOBOTIX MOVE VandalDome</b> VD Standard replacement dome • Suitable for all MOBOTIX MOVE VandalDome cameras	4047438031721 90079100 250 g	16,1 cm 16,1 cm 11,5 cm 3,0 l
	<b>Mx-M-BC-P</b> <b>Pole Mount For MOBOTIX MOVE 4MP BulletCamera</b> BC Pole Mount suitable for MOBOTIX MOVE BulletCameras BC-4-IR, BC-4-IR-D, VB-4-IR and VB-4-IR-D	4047438031677 90079100 1.000 g	17,3 cm 17,3 cm 16,7 cm 5,0 l
	<b>Mx-M-BC-W</b> <b>Wall Mount For MOBOTIX MOVE 4MP BulletCamera</b> BC Wall Mount suitable for MOBOTIX MOVE BulletCamera BC-4-IR, BC-4-IR-D, VB-4-IR and VB-4-IR-D	4047438031660 90079100 840 g	17,3 cm 17,3 cm 10,7 cm 3,2 l
	<b>Mx-M-SD-C</b> <b>Corner Mount For MOBOTIX MOVE SD-330/SD-340-IR</b> SD Corner Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)	4047438031769 90079100 2.170 g	21,0 cm 12,5 cm 25,0 cm 6,6 l


	<p><b>Mx-M-SD-P</b>  <b>Pole Mount For MOBOTIX MOVE SD-330/SD-340-IR</b>            SD Pole Mount suitable for MOBOTIX MOVE SpeedDome SD-330 und SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)</p>	<p>4047438031752            90079100            1.580 ₧</p>	<p>31,0 cm            15,5 cm            26,0 cm            12,5 l</p>
	<p><b>Mx-M-SD-W</b>  <b>Wall Mount For MOBOTIX MOVE SD-330/SD-340-IR</b>            SD Wall Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)</p>	<p>4047438031745            90079100            840 ₧</p>	<p>21,6 cm            12,7 cm            14,8 cm            4,1 l</p>
	<p><b>Mx-M-VD-C</b>  <b>Corner Mount For MOBOTIX MOVE VandalDome</b>            VD Corner Mount suitable for all MOBOTIX MOVE VandalDome cameras</p>	<p>4047438031738            90079100            2.170 ₧</p>	<p>21,0 cm            12,5 cm            25,0 cm            6,6 l</p>
	<p><b>Mx-M-VD-IC</b>  <b>In-Ceiling Set For MOBOTIX MOVE VandalDome</b>            VD In-Ceiling Set suitable for all MOBOTIX MOVE VandalDome cameras</p>	<p>4047438031684            90079100            800 ₧</p>	<p>23,4 cm            23,4 cm            12,8 cm            7,0 l</p>
	<p><b>Mx-M-VD-P</b>  <b>Pole Mount For MOBOTIX MOVE VandalDome</b>            VD-Pole Mount suitable for all MOBOTIX MOVE VandalDome cameras</p>	<p>4047438031707            90079100            1.580 ₧</p>	<p>31,0 cm            15,5 cm            26,0 cm            12,5 l</p>
	<p><b>Mx-M-VD-W</b>  <b>Wall Mount For MOBOTIX MOVE VandalDome</b>            VD Wall Mount Set (2-piece) suitable for all MOBOTIX MOVE VandalDome cameras</p>	<p>4047438031691            90079100            1.400 ₧</p>	<p>31,0 cm            22,0 cm            18,0 cm            12,3 l</p>



# System Components

## Interface Boxes

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-OPT-BPA1-EXT</b> <b>MX-BPA-Box</b> Power supply for several MxBus modules of one MxBus line • 2x2 connection terminals for MxBus • 2 connection terminals for external power supply from 12 to 48 V DC (2 terminals) • Max. output rating: 9 W • IP66/IK08, -30 bis 60 °C / -22 to 140 °F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	4047438025881 85299065 120 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	<b>MX-OPT-NPA1-EXT</b> <b>MX-NPA-Box</b> Weatherproof PoE Injector (IEEE 802.3af) and network connector • Needs external power supply units and batteries from 12 to 57 V DC • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Important: only use with original MOBOTIX patch cables • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	4047438015424 85043180 140 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-Overvoltage-Protection-Box-LSA</b> <b>Network Connector with Surge Protection, LSA Version</b> Weatherproof connection of one MOBOTIX patch cable (RJ45, from camera) and the network installation cable • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	4047438018470 85299065 146 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-Overvoltage-Protection-Box-RJ45</b> <b>Network Connector with Surge Protection, RJ45 Version</b> Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	4047438018463 85299065 150 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-OPT-Input1-EXT</b> <b>MX-Input-Box</b> Weatherproof connection of external sensors • Connection to camera using MxBus • 6 self-powered inputs for connecting up to 6 external sensors • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	4047438021227 85299065 148 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-OPT-Output1-EXT</b> <b>MX-Output-Box</b> Weatherproof connection of external devices and power relays • Connection to the camera via MxBus • Six self-powered outputs (12 V, each 10 mA) • Two isolated outputs (can be switched to "self-powered" using a jumper: 12 V, max. 50 mA) • Protection class IP66/IK07, -30 to 60 °C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	4047438021944 85299065 120 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	<b>MX-OPT-RS1-EXT</b> <b>MX-232-IO-Box</b> Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB or MxBus • 2 self-powered inputs for connecting sensors • 2 outputs: 1 powered output, 1 isolated relay output (can be switched to second powered output) • RS232 interface when using MOBOTIX USB cable to connect to camera • Protection class IP66/IK08, -30 to 60°C / -22 to 140° F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	4047438015417 85299065 120 g	10,5 cm 6,8 cm 10,5 cm 0,7 l


**MX-OPT-GPS1-EXT**

4047438015400 10,5 cm

**MX-GPS-Box**

85299065 6,8 cm

Weatherproof GPS time base for MOBOTIX systems • Includes outdoor temperature and illumination sensors • Connects via MxBus 2-wire cable • Protection class IP66/IK08, -30 to 60°C / -22 to +140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x

120 g 10,5 cm  
0,7 l**MX-PROX-BOX**

4047438025935 10,5 cm

**MX-Proximity-Box**

85299065 6,8 cm

Weatherproof proximity sensor for MOBOTIX systems • Accurate detection of approaching objects based on radar microwave technology • Covered area (horizontal x vertical): 80° x 34° • Detection range: up to 8m/26 ft. (person), up to 20m/66 ft. (vehicle) • Camera connection and supply via MxBus • Protection class IP66/IK07, -20 to 60°C / -4 to 140°F • Box can also be mounted behind walls (e.g. wooden, plastic, glass or dry walls) • It is not possible to install the MX-Proximity-Box behind some materials since they absorb or reflect the radar waves (e.g., metal or metal-coated surfaces). Other materials are better suited since they absorb radar waves only slightly (e.g., uncoated glass, plastics, various wood-based materials, drywall).

165 g 10,5 cm  
0,7 l**MX-OPT-DIGI-INT**

4047438028790 10,5 cm

**MxDigitizer For S1x**

85299065 6,8 cm

Interface box to connect one analog camera directly to a S1x Body as alternative image source (instead of one sensor module) • Up to two MxDigitizer boxes or two analog cameras can be connected to one S1x Body • Easy integration of analog cameras into the MOBOTIX IP video system incl. the support of MOBOTIX integrated image analysis tools (e.g. MxActivitySensor) • Box digitizes the analog signal input (NTSC/PAL) • Output format PAL: 704 x 525 pixels, up to 25 frames per second • Output format NTSC: 640 x 480 pixels, up to 30 frames per second • BNC connection of analog camera to MxDigitizer • Sensor cable connection of MxDigitizer to S1x Body (to be ordered separately, maximum length 3 m/9.8 ft) • Operating conditions: Indoors, 0 to 40°C (32 to 104°F) • Color: white

120 g 10,5 cm  
0,7 l

## Mx2wire+ Media Converter



### Article No. / Name / Description

### EAN / HS / weight dimen.

#### MX-2WirePlus-Set-PW

4047438015356 19,6 cm

#### Mx2wire+ Set, Ethernet And PoE Via Two-Wire-Cable

85176200 15,0 cm









Mx2wire+ turns an existing two-wire cable into a modern multimedia cable • Ethernet and PoE data transfer using a two-wire cable • Simple connection of 10/100 Mbps Ethernet end devices (e.g., IP camera, IP telephone) • Power supply for Mx2wire+ and end device via PoE/PoE+ or 48-57 V DC, 600 mA • Connected end devices are supplied with up to 13 watts via PoE (PoE class 3) • Maximum data transfer range of 500 m and data rate of up to 50 Mbps (depending on distance) • No need for expensive and time-consuming installation of network cables • Perfect for wireless communication is not possible (due to distance to sender, thickness of walls, etc.) • Network extension, including PoE, by connecting a Cat7 cable of up to 500 m in length as a two-wire cable • Simple installation in standard sockets (surface- or flush-mounted) • Two LEDs display current connection and supply statuses • Developed, produced and patented by MOBOTIX Germany • Ambient temperature: -30 to 50°C / -22 to 122°F • Complete set consisting of two Mx2wire+ units, on-walls sockets and mounting parts


508 g 9,0 cm

2,6 l

## Functional Enhancement & IR Illuminators


	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-A-TCLIENTA</b> <b>MxThinClient</b> PoE-supplied IP video device to transfer live pictures of cameras and door stations to a monitor/TV set • Password protected web interface • Automatic change of video source via sequencer (time-controlled) or via MxMessageSystem (event-controlled) • Input (connection to PoE switch): 1x Ethernet 100Base-T (RJ45) • Output (connection to monitor/TV set): 1x HDMI Type D (MicroHDMI) • Connection cables (Ethernet, HDMI) are not included • Indoor-use only: Protection class IP20, ambient temperature 0 to 40 °C (32 to 104°F) • With the supplied adhesive strips, the device can easily be attached to the backside of the monitor/TV	4047438028899 84714900 200 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-ExtIO</b> <b>ExtIO Extension Module For All MOBOTIX Cameras</b> ExtIO Weatherproof extension for all MOBOTIX cameras (except Basic models) • Power supply: PoE (Class 2, IEEE 802.3af) or USB (connection cable to be ordered individually) • Microphone/speaker • Line-in / Line-out • PIR sensor for motion detection • Temperature sensor • 2 buttons (e.g., lights, door bell) • 2 galvanically separated inputs • 2 galvanically separated outputs • Protection class IP65, -30 to 60° C / -22 to 140°F • Robust housing made of fiber-reinforced plastic PBT-GF30 • Mounting to a wall or ceiling, optionally with MOBOTIX mounting accessories (to be ordered individually) • Connecting via Network or USB	4047438009850 85299065 744 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	<b>MX-MULTISENSE1-EXT</b> <b>MxMultiSense Outdoor (HS code 85299065)</b> Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor (±0.1°C / 0.18°F) and acoustic sensor (level of sound waves) • Camera connection and supply via MxBus: power consumption approx. 0.3 W, MxBus cable length up to 100 m / 330 ft. • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX mounts for sensor modules and standard mounts for recessed spotlights • Protection class IP66 • IK05 • Ambient temperature -20 to 60°C / -4 to 140°F • Housing color: white	4047438028905 85299065 110 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<b>MX-OPT-IO3-INT</b> <b>Extension Module For c25, i25, p25 And v25</b> Extension module for the indoor cameras x25 (to be mounted on the backside) • Not compatible with x26 indoor cameras • For the connection of external sensors (e.g., door or window • contacts) and switching of external devices (e.g., relays with lamps and motors) • Two input lines (galvanically isolated, 0 to 48 V AC/DC) • Two output lines: 2x • isolated (contact load max.30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA • per output line) • MxBus terminal (1x2) • Ambient temperature: 0 to 4°C (32 to 104°F) • Power consumption: 1 W	4047438025928 85299065 45 g	10,7 cm 5,2 cm 8,7 cm 0,5 l
	<b>Mx-A-IOA-IC</b> <b>Extension Module For All Indoor Cameras x26A/x26B</b> Expansion module for Indoor Cameras x26A/B, i26A/B, p26A/B and v26A/B (installed on the back) • Not suitable for x25 indoor cameras • For connecting external sensors (e.g., door and window contacts) and switches of external devices (e.g., relays with lamps and motors) • Two inputs (galvanically separated): 0 V to 48 V AC/DC • Two outputs: 2x floating (load per contact max. 30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output) • 2x MxBus terminal connector (MxBus will be supported only by the x26B Indoor Cameras) • Ambient temperature: 0°C to 40°C (32°F to 104°F) • Power consumption: 1 W	4047438029032 85299065 45 g	10,7 cm 5,2 cm 8,7 cm 0,5 l
	<b>Mx-A-SPA</b> <b>MxSplitProtect Installation Box, IP66</b> Weatherproof installation box with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces (weatherproof): 1 LSA (with shield clip) for Ethernet 2 100Base-T, 2 MxRJ45 for Ethernet 100Base-T with PoE Mode A, 1 protective earth terminal • IP66 and IK08, ambient temperature: -30°C to 60°C (-22°F to 140°F) • Accessories (available separately): MxSplitProtectHR Hat Rail module (Mx-A-SPA-HR), cover with camera mount in three versions (Mx-A-SPCA-M/-H/-V), pole mount (MX-MH-SecureFlex-ESWS) • Housing color: white	4047438030229 85299065 1.184 g	30,5 cm 24,0 cm 16,0 cm 11,7 l

	<p><b>Mx-A-SPA-HR</b> <b>MxSplitProtectHR Hat Rail Module</b></p> <p>Compatible with MxSplitProtect Installation Box (Mx-A-SPA): Hat rail module (for 35 mm DIN rails) with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces: 3x RJ45 for Ethernet 100Base-T, 1x protective earth terminal • Only use in indoor areas, ambient temperature: 0°C to 40°C (32°F to 104°F) • Accessories (available separately): MxSwitch (MX-SWITCH1) • Housing color: gray</p>	<p>4047438030236 85299065 130 g</p>	<p>10,0 cm 7,5 cm 9,0 cm 0,7 l</p>
	<p><b>Mx-A-SPCA-M</b> <b>MxSplitProtect Cover, M-Cameras</b></p> <p>Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to install the standard VarioFlex wall mount of an M15/M16/M25/M26 camera directly to the cover • Color: white</p>	<p>4047438028820 85299065 514 g</p>	<p>19,6 cm 18,0 cm 14,8 cm 5,2 l</p>
	<p><b>Mx-A-SPCA-H</b> <b>MxSplitProtect Cover, Horizontal</b></p> <p>Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (vertically) install a Q2x (orD2x) camera with a 15° tilt angle without an additional mount directly to the cover • Color: white</p>	<p>4047438028837 85299065 570 g</p>	<p>19,6 cm 18,0 cm 14,8 cm 5,2 l</p>
	<p><b>Mx-A-SPCA-V</b> <b>MxSplitProtect Cover, Vertical</b></p> <p>Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (horizontally) install a Q2x/D2x camera without an additional mount directly to the cover • Color: white</p>	<p>4047438028844 85299065 482 g</p>	<p>19,6 cm 18,0 cm 14,8 cm 5,2 l</p>
	<p><b>Mx-A-IRA-120</b> <b>MxIRLight Infrared Illuminator (860 nm), 120°x120°</b></p> <p>Infrared illuminator with 120° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 20 m (66 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white</p>	<p>4047438030342 85394900 1.098 g</p>	<p>20,5 cm 17,5 cm 12,5 cm 4,5 l</p>
	<p><b>Mx-A-IRA-90</b> <b>MxIRLight Infrared Illuminator (860 nm), 90°x90°</b></p> <p>Infrared illuminator with 90° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 35 m (115 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white</p>	<p>4047438030359 85394900 1.112 g</p>	<p>20,5 cm 17,5 cm 12,5 cm 4,5 l</p>
	<p><b>Mx-A-IRA-60</b> <b>MxIRLight Infrared Illuminator (860 nm), 60°x60°</b></p> <p>Infrared illuminator with 60° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 50 m (165 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white</p>	<p>4047438030366 85394900 1.116 g</p>	<p>20,5 cm 17,5 cm 12,5 cm 4,5 l</p>
	<p><b>Mx-A-IRA-45</b> <b>MxIRLight Infrared Illuminator (860 nm), 45°x45°</b></p> <p>Infrared illuminator with 45° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 80 m (262 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white</p>	<p>4047438030373 85394900 1.124 g</p>	<p>20,5 cm 17,5 cm 12,5 cm 4,5 l</p>

**Mx-A-IRA-30****MxIRLight Infrared Illuminator (860 nm), 30°x30°**

Infrared illuminator with 30° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 120 m (394 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030380	20,5 cm
85394900	17,5 cm
1.096 9	12,5 cm
	4,5 l

**Mx-A-IRA-15****MxIRLight Infrared Illuminator (860 nm), 15°x15°**

Infrared illuminator with 15° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 160 m (525 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030397	20,5 cm
85394900	17,5 cm
1.090 9	12,5 cm
	4,5 l

**Mx-M-IRA-ML****MxIRLight Mounting Brackets For M1x**

Mounting brackets „Large“ for the MOBOTIX M15/M16 AllroundDual cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030403	19,6 cm
85399090	5,5 cm
216 9	3,5 cm
	0,4 l

**Mx-M-IRA-M****MxIRLight Mounting Brackets For M2x**

Mounting brackets for the MOBOTIX M25/M26 Allround cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030410	14,0 cm
85399090	5,5 cm
150 9	3,5 cm
	0,3 l






## PoE Power Supply

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-SWITCH1</b> <b>MxSwitch For DIN Rail Mounting</b> PoE+ Switch for the top-hat rail • 5x RJ45 port with 100 MBit/s (1x uplink, 4x PoE+ with max. 75 W) • Supply: 48 V DC, max. 75 W • Simplified cabling for door stations due to available connectivity for anti-theft protection, door opener and MxBus • MxBus, anti-theft protection, door and lock contact can be connected via separate wires of the ethernet cable	4047438028882 85176200 310 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>MX-NPA-PoE-EU-Set</b> <b>PoE Power Adapter Set, EU</b> PoE injector incl. crossover function for direct connection to the PC • With power plug for Europe • For all MOBOTIX cameras (except for M1 and M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	4047438012249 85043180 268 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>MX-NPA-PoE-INT-Set</b> <b>PoE Power Adapter Set, INT</b> PoE injector incl. crossover function for direct connection to the PC • With 4 exchangeable power plugs for Europe, United Kingdom, USA and Australia • For all MOBOTIX cameras (except for M1 and M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	4047438012256 85043180 314 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	<b>MX-NPA-PoE-RJ</b> <b>PoE Power Adapter</b> PoE injector (IEEE 802.3af) incl. crossover function for direct connection to the PC • Blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug • Without power plug, additional power supply (12 to 57 V DC) and connection cable needed	4047438013932 85043180 60 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	<b>MX-SNT-INT-PoE</b> <b>Universal Power Supply With 4 Power Plugs</b> For international use thanks to broad input voltage range and interchangeable power plugs (no tools required) • With 4 power plugs for Europe, United Kingdom, USA and Australia • Connections: 1x RJ45 (for adapter), 1x network (up to 4x interchangeable adapter) • Nominal data input: 100 V to 240 V, 50 to 60 Hz/400 mA • Nominal data output: DC 24 V/750 mA • Ambient temperature: 0 to 40°C / 32 to 104 °F	4047438013925 85043180 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l



## MOBOTIX NAS Storage Solutions

### Network Attached Storage (NAS)








	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-S-NAS2A-8</b>	4047438034036	27,0 cm
	<b>MOBOTIX NAS 2-Bay/8 Channels (NAS-251G)</b> MOBOTIX Network Attached Storage device with 2 bays and 8 ONVIF S channels • Max. Storage capacity net (with redundancy): 12 TB • Delivery without hard disks (not available on MOBOTIX) • Incl. Power cable C13 with EU plug (cable with US / GB / AU plug available on request)	84718000 2.320 g	20,2 cm 23,5 cm 12,8 l
	<b>Mx-S-NAS4A-16</b>	4047438034043	30,5 cm
	<b>MOBOTIX NAS 4-Bay/16 Channels (NAS-451G)</b> MOBOTIX Network Attached Storage device with 4 bays and 16 ONVIF S channels • Max. Storage capacity net (with redundancy): 36 TB • Delivery without hard disks (not available on MOBOTIX) • Incl. Power cable C13 with EU plug (cable with US / GB / AU plug available on request)	84718000 4.300 g	25,0 cm 31,6 cm 24,1 l
	<b>Mx-S-NAS8A-32</b>	4047438034050	72,0 cm
	<b>MOBOTIX NAS 8-Bay/32 Channels (NAS-873UG)</b> MOBOTIX Network Attached Storage device with 8 bays and 32 ONVIF S channels • Max. Storage capacity net (with redundancy): 84 TB • Delivery without hard disks (not available on MOBOTIX) • Incl. Power cable C13 with EU plug (cable with US / GB / AU plug available on request)	84718000 15.330 g	56,4 cm 26,0 cm 105,6 l

# Access Control

## MxDisplay+

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p><b>MX-DISPLAY3</b>  <b>MxDisplay+, White</b>            MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-PW) • Color: white</p>	<p>4047438027151            85285291            425 g</p>	<p>19,6 cm            15,0 cm            9,0 cm            2,6 l</p>
	<p><b>MX-DISPLAY3-b</b>  <b>MxDisplay+, Black</b>            MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-BL) • Color: black</p>	<p>4047438027168            85285291            300 g</p>	<p>13,8 cm            6,5 cm            14,8 cm            1,3 l</p>

## T26B Camera Module

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-T26B-6D016</b>	4047438032025	19,6 cm
	<b>T26 CamCore, 6MP, B016, Day, White</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	400 g	9,0 cm
			2,6 l
	<b>Mx-T26B-6N016</b>	4047438032032	19,6 cm
	<b>T26 CamCore, 6MP, B016, Night, White</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	400 g	9,0 cm
			2,6 l
	<b>Mx-T26B-6D016-b</b>	4047438032049	19,6 cm
	<b>T26 CamCore, 6MP, B016, Day, Black</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	400 g	9,0 cm
			2,6 l
	<b>Mx-T26B-6N016-b</b>	4047438032056	19,6 cm
	<b>T26 CamCore, 6MP, B016, Night, Black</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	400 g	9,0 cm
			2,6 l
	<b>Mx-T26B-6D016-s</b>	4047438032063	19,6 cm
	<b>T26 CamCore, 6MP, B016, Day, Silver</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	400 g	9,0 cm
			2,6 l
	<b>Mx-T26B-6N016-s</b>	4047438032070	19,6 cm
	<b>T26 CamCore, 6MP, B016, Night, Silver</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	400 g	9,0 cm
			2,6 l
	<b>Mx-T26B-6D016-d</b>	4047438032087	19,6 cm
	<b>T26 CamCore, 6MP, B016, Day, Dark Gray</b>	85258091	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray	400 g	9,0 cm
			2,6 l

**Mx-T26B-6N016-d****T26 CamCore, 6MP, B016, Night, Dark Gray**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night)  
 • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray





4047438032094 19,6 cm

85258091 14,8 cm

400 g 9,0 cm

2,6 l

## KeypadRFID Module

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p><b>Mx-A-KEYC</b> <b>Keypad With RFID Technology For T26, White</b></p> <p>Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White</p>	4047438034135 85371091 330 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 <p><b>Mx-A-KEYC-b</b> <b>Keypad With RFID Technology For T26, Black</b></p> <p>Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black</p>	4047438034128 85371091 330 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 <p><b>Mx-A-KEYC-d</b> <b>Keypad With RFID Technology For T26, Dark Gray</b></p> <p>Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray</p>	4047438034111 85371091 330 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 <p><b>Mx-A-KEYC-s</b> <b>Keypad With RFID Technology For T26, Silver</b></p> <p>Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver</p>	4047438034104 85371091 330 g	19,6 cm 15,0 cm 9,0 cm 2,6 l



## BellRFID Module

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-A-BELLC</b> <b>BellRFID Base Module For T26, White</b> BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	4047438034067 85299065 350 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-A-BELLC-b</b> <b>BellRFID Base Module For T26, Black</b> BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	4047438034074 85299065 350 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-A-BELLC-d</b> <b>BellRFID Base Module For T26, Dark Gray</b> BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	4047438034081 85299065 350 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>Mx-A-BELLC-s</b> <b>BellRFID Base Module For T26, Silver</b> BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	4047438034098 85299065 350 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	<b>MX-Bell1-Button-F1</b> <b>BellRFID Bell Button Set F1</b> 1 big key with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Delivery with UV resistant paper label	4047438017190 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
	<b>MX-Bell1-Button-F2</b> <b>BellRFID Bell Button Set F2</b> 2 medium-sized keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Delivery with UV resistant paper label	4047438017176 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
	<b>MX-Bell1-Button-F3</b> <b>BellRFID Bell Button Set F3</b> 1 medium-sized and 2 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Delivery with UV resistant paper label	4047438017527 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l

**MX-Bell1-Button-F4****BellRFID Bell Button Set F4**

4 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

4047438017183 10,3 cm  
85299065 1,7 cm  
94 g 10,3 cm  
0,2 l

**MX-Bell1-Button-05****BellRFID Bell Button Set 05**

5 small keys (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label





4047438017534 10,3 cm  
85299065 1,7 cm  
94 g 10,3 cm  
0,2 l

**MX-Bell1-Button-XL1****BellRFID Bell Button Set XL1**





1 big XL key (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

4047438017169 10,3 cm  
85299065 1,7 cm  
94 g 10,3 cm  
0,2 l



## Info Module

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-Info1-EXT-PW</b>	4047438014991	19,6 cm
	<b>Info Module With LEDs, White</b> Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	85414090 282 g	15,0 cm 9,0 cm 2,6 l
	<b>MX-Info1-EXT-SV</b>	4047438015035	19,6 cm
	<b>Info Module With LEDs, Silver</b> Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	85414090 282 g	15,0 cm 9,0 cm 2,6 l
	<b>MX-Info1-EXT-DG</b>	4047438015028	19,6 cm
	<b>Info Module With LEDs, Dark Gray</b> Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	85414090 282 g	15,0 cm 9,0 cm 2,6 l
	<b>MX-Info1-EXT-BL</b>	4047438015011	19,6 cm
	<b>Info Module With LEDs, Black</b> Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	85414090 282 g	15,0 cm 9,0 cm 2,6 l





## Info Module Mx2Wire+

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>MX-2wirePlus-Info1-EXT-PW</b> <b>Info Module Mx2wire+ With LEDs, White</b>	4047438015042	19,6 cm
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	85176200	15,0 cm
		520 g	9,0 cm
			2,6 l
	<b>MX-2wirePlus-Info1-EXT-SV</b> <b>Info Module Mx2wire+ With LEDs, Silver</b>	4047438015080	19,6 cm
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	85176200	15,0 cm
		522 g	9,0 cm
			2,6 l
	<b>MX-2wirePlus-Info1-EXT-DG</b> <b>Info Module Mx2wire+ With LEDs, Dark Gray</b>	4047438015073	19,6 cm
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	85176200	15,0 cm
		521 g	9,0 cm
			2,6 l
	<b>MX-2wirePlus-Info1-EXT-BL</b> <b>Info Module Mx2wire+ With LEDs, Black</b>	4047438015066	19,6 cm
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	85176200	15,0 cm
		519 g	9,0 cm
			2,6 l

## MX-DoorMaster

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p><b>MX-Door2-INT-ON-PW</b>  <b>DoorMaster For On-Wall Mounting</b>            Security Door Opener with integrated access code memory for on-wall mounting • Complete set including DoorMaster module, on-wall housing, three device frames, neutral housing covering, battery pack and mounting parts • Suitable for: IP Video Door Station with T2x and S1x as door camera • Built-in backup power supply (battery) for access modules • Doorbell • Direct connection and power supply for electric Door Opener und door sensors • Interface und power supply: MxBus • Two status LEDs, two function buttons, integrated • Speaker (doorbell) • Two galvanically separated inputs (AC/DC, selfpowered • up to 48 V) • Isolated relay output (AC/DC, 24 V/1 A) or port for standard door openers (6 to 12 V AC) • Outlet for MOBOTIX antitheft protection (12 V DC) • Protection class: IP20 • Ambient temperature: -5 to 40 °C / 23 to 104 °F • Color: white</p>	<p>4047438021876            85363010            412 g</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>
	<p><b>MX-Door2-INT-PW</b>  <b>DoorMaster For In-Wall Mounting</b>            Security door opener with internal access code memory: A MOBOTIX door station may be coupled with the MOBOTIX MX-DoorMaster, making it impossible to open the door by forcibly removing the system and bypassing the connecting cable • 2nd product generation, suitable for: IP video door stations with an T2x and S1x as door camera • Integrated (rechargeable) battery power supply for access modules • Security door opener/bell with access code storage (protected against manipulation) • Connection for door opener, door sensor and door lock sensor • Interface and power supply: MxBus (max. 50 m distance to door station) • User interfaces: 2 status LEDs, 2 function buttons, integrated speaker (doorbell) • Inputs: 2 galvanically separated inputs with shared ground connection (AC/DC, self-powered up to 48 V) • Outputs: 1 isolated relay output (AC/DC, 24 V/1 A) or 1 connector for standard door opener (6 to 12 V AC), 1 output for MOBOTIX theft protection (12 V DC) • Protection class: IP20 (DIN EN 60529) • Operating temperature: -5 to 40°C / 23 to 104°F (DIN EN 50155) • Switch time: max. 5 s</p>	<p>4047438019934            85363010            322 g</p>	<p>14,8 cm            9,8 cm            9,0 cm            1,3 l</p>

## Building Automation Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p><b>MX-AdminCard1</b>  <b>Admin RFID Transponder Card (Red)</b>            For system configuration IP Video Door Station via KeypadRFID and BellRFID •            Type/encryption: MIFARE DESFire EV1 3K3DES/AES</p>	<p>4047438015288            85235200            2 g</p>	<p>8,5 cm            5,5 cm            0,1 cm            0,0 l</p>
	<p><b>MX-UserCard1</b>  <b>User RFID Transponder Card (Blue)</b>            For keyless entry via with KeypadRFID or BellRFID (IP video door station) •            Type/encryption: MIFARE DESFire EV1 3K3DES/AES</p>	<p>4047438015295            85235200            2 g</p>	<p>8,5 cm            5,5 cm            0,1 cm            0,0 l</p>
	<p><b>MX-OPT-IO1</b>  <b>Extended Terminal Board (IO Module)</b>            Suitable for: T2x, delivers extended connection options for the door station (e.g., doorbell buttons, light, garage door opener, etc.) • Connect the IO Module to the camera module via MxBus, which connects it to the network. It has eight physical signal inputs that allow it to distinguish in AC operation between a pending full-wave and half-wave. This makes it possible to connect two switches to each signal input terminal so that 16 button inputs are made available. The inputs can be used for, e.g., bell buttons. The outputs can be used for external devices such as a doorbell, or for outdoor lights or garage door openers (via a power relay).</p>	<p>4047438013307            85299065            86 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>
	<p><b>MX-OPT-IO2</b>  <b>Ethernet Terminal Board</b>            Suitable for: T2x • The Ethernet terminal board is used to connect the door station for the versions without Mx2wire+ technology. It securely connects the camera module with the 8 connected wires of the network patch cable via RJ45 connector. The Ethernet terminal board is screwed on to the housing (on-wall or in-wall) behind the camera module</p>	<p>4047438014786            85299065            60 g</p>	<p>9,8 cm            7,5 cm            9,0 cm            0,7 l</p>

## Frames & Housings


	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-OPT-Box-1-EXT-IN-US</b> <b>Single In-Wall-Housing (USA version)</b>	4047438034463	14,5 cm
	Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	90079100	13,5 cm
		186 g	3,5 cm
			0,7 l
	<b>Mx-OPT-Box-2-EXT-IN-US</b> <b>Double In-Wall-Housing (USA version)</b>	4047438034470	23,5 cm
	Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	90079100	13,5 cm
		270 g	3,5 cm
			1,1 l
	<b>Mx-OPT-Box-3-EXT-IN-US</b> <b>Triple In-Wall-Housing (USA version)</b>	4047438034487	33,5 cm
	Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	90079100	13,5 cm
		362 g	3,5 cm
			1,6 l
	<b>MX-OPT-Frame-1-EXT-PW</b> <b>Single Frame, White</b>	4047438014892	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: White	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l
	<b>MX-OPT-Frame-1-EXT-SV</b> <b>Single Frame, Silver</b>	4047438014939	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Silver	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l
	<b>MX-OPT-Frame-1-EXT-DG</b> <b>Single Frame, Dark Gray</b>	4047438014922	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Dark Gray	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l
	<b>MX-OPT-Frame-1-EXT-BL</b> <b>Single Frame, Black</b>	4047438014915	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Black	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l



	<p><b>MX-OPT-Box-1-EXT-ON-PW</b>  <b>Single On-Wall-Housing, White</b>            Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: White</p>	<p>4047438015202            90079100            286 g</p>	<p>14,5 cm            13,5 cm            3,5 cm            0,7 l</p>
	<p><b>MX-OPT-Box-1-EXT-ON-SV</b>  <b>Single On-Wall-Housing, Silver</b>            Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Silver</p>	<p>4047438015240            90079100            286 g</p>	<p>14,5 cm            13,5 cm            3,5 cm            0,7 l</p>
	<p><b>MX-OPT-Box-1-EXT-ON-DG</b>  <b>Single On-Wall-Housing, Dark Gray</b>            Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438015233            90079100            286 g</p>	<p>14,5 cm            13,5 cm            5,0 cm            1,0 l</p>
	<p><b>MX-OPT-Box-1-EXT-ON-BL</b>  <b>Single On-Wall-Housing, Black</b>            Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Black</p>	<p>4047438015226            90079100            286 g</p>	<p>14,5 cm            13,5 cm            3,5 cm            0,7 l</p>
	<p><b>MX-OPT-Box-1-EXT-IN</b>  <b>Single In-Wall-Housing</b>            Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm</p>	<p>4047438015271            90079100            186 g</p>	<p>14,5 cm            13,5 cm            3,5 cm            0,7 l</p>
	<p><b>MX-OPT-Frame-2-EXT-PW</b>  <b>Double Frame, White</b>            Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White</p>	<p>4047438014847            90079100            333 g</p>	<p>23,5 cm            13,5 cm            3,5 cm            1,1 l</p>
	<p><b>MX-OPT-Frame-2-EXT-SV</b>  <b>Double Frame, Silver</b>            Suitable for: 2 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver</p>	<p>4047438014885            90079100            333 g</p>	<p>23,5 cm            13,5 cm            3,5 cm            1,1 l</p>
	<p><b>MX-OPT-Frame-2-EXT-DG</b>  <b>Double Frame, Dark Gray</b>            Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438014878            90079100            333 g</p>	<p>23,5 cm            13,5 cm            5,0 cm            1,6 l</p>

	<p><b>MX-OPT-Frame-2-EXT-BL</b>  <b>Double Frame, Black</b></p> <p>Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black</p>	<p>4047438014861  90079100  333 g</p>	<p>23,5 cm  13,5 cm  3,5 cm  1,1 l</p>
	<p><b>MX-OPT-Box-2-EXT-ON-PW</b>  <b>Double On-Wall-Housing, White</b></p> <p>Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White</p>	<p>4047438015158  90079100  430 g</p>	<p>23,5 cm  13,5 cm  3,5 cm  1,1 l</p>
	<p><b>MX-OPT-Box-2-EXT-ON-SV</b>  <b>Double On-Wall-Housing, Silver</b></p> <p>Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver</p>	<p>4047438015196  90079100  430 g</p>	<p>23,5 cm  13,5 cm  3,5 cm  1,1 l</p>
	<p><b>MX-OPT-Box-2-EXT-ON-DG</b>  <b>Double On-Wall-Housing, Dark Gray</b></p> <p>Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438015189  90079100  430 g</p>	<p>23,5 cm  13,5 cm  3,0 cm  1,0 l</p>
	<p><b>MX-OPT-Box-2-EXT-ON-BL</b>  <b>Double On-Wall-Housing, Black</b></p> <p>Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black</p>	<p>4047438015172  90079100  430 g</p>	<p>23,5 cm  13,5 cm  3,5 cm  1,1 l</p>
	<p><b>MX-OPT-Box-2-EXT-IN</b>  <b>Double In-Wall-Housing</b></p> <p>Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm</p>	<p>4047438015264  90079100  270 g</p>	<p>23,5 cm  13,5 cm  3,5 cm  1,1 l</p>
	<p><b>MX-OPT-Frame-3-EXT-PW</b>  <b>Triple Frame, White</b></p> <p>Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: White</p>	<p>4047438014793  90079100  426 g</p>	<p>33,5 cm  13,5 cm  5,5 cm  2,5 l</p>
	<p><b>MX-OPT-Frame-3-EXT-SV</b>  <b>Triple Frame, Silver</b></p> <p>Suitable for: 3 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Silver</p>	<p>4047438014830  90079100  426 g</p>	<p>33,5 cm  13,5 cm  5,5 cm  2,5 l</p>

	<p><b>MX-OPT-Frame-3-EXT-DG</b>  <b>Triple Frame, Dark Gray</b></p> <p>Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438014823  90079100  426 g</p>	<p>33,5 cm  13,5 cm  5,0 cm  2,3 l</p>
	<p><b>MX-OPT-Frame-3-EXT-BL</b>  <b>Triple Frame, Black</b></p> <p>Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Black</p>	<p>4047438014816  90079100  426 g</p>	<p>33,5 cm  13,5 cm  5,5 cm  2,5 l</p>
	<p><b>MX-OPT-Box-3-EXT-ON-PW</b>  <b>Triple On-Wall-Housing, White</b></p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White</p>	<p>4047438015103  90079100  574 g</p>	<p>33,5 cm  13,5 cm  3,5 cm  1,6 l</p>
	<p><b>MX-OPT-Box-3-EXT-ON-SV</b>  <b>Triple On-Wall-Housing, Silver</b></p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver</p>	<p>4047438015141  90079100  574 g</p>	<p>33,5 cm  13,5 cm  3,5 cm  1,6 l</p>
	<p><b>MX-OPT-Box-3-EXT-ON-DG</b>  <b>Triple On-Wall-Housing, Dark Gray</b></p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray</p>	<p>4047438015134  90079100  574 g</p>	<p>33,5 cm  13,5 cm  3,0 cm  1,4 l</p>
	<p><b>MX-OPT-Box-3-EXT-ON-BL</b>  <b>Triple On-Wall-Housing, Black</b></p> <p>Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black</p>	<p>4047438015127  90079100  574 g</p>	<p>33,5 cm  13,5 cm  3,5 cm  1,6 l</p>
	<p><b>MX-OPT-Box-3-EXT-IN</b>  <b>Triple In-Wall-Housing</b></p> <p>Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm</p>	<p>4047438015257  90079100  362 g</p>	<p>33,5 cm  13,5 cm  3,5 cm  1,6 l</p>
	<p><b>MX-OPT-FlatMount-EXT-PW</b>  <b>FlatMount Frame, white</b></p> <p>For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: white</p>	<p>4047438019811  90079100  190 g</p>	<p>14,7 cm  13,7 cm  5,5 cm  1,1 l</p>

**MX-OPT-FlatMount-EXT-BL****FlatMount Frame, black**

For flush-mounting of MxDisplay and door station modules in wall cavities •  
Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: black

4047438019835	14,7 cm
90079100	13,7 cm
190 g	5,5 cm
	1,1 l

**MX-OPT-FlatMount-Box-EXT-IN****FlatMount Frame In-Wall Housing**

In-wall housing for FlatMount Frame • To be affixed securely with the subsurface or  
brick work • Size of cavity for flush-mounting (W x H x D): 112 x 112 x 60 mm

4047438019866	13,8 cm
90079100	6,5 cm
130 g	13,8 cm
	1,2 l

# Software & Services

BeyondHumanVision

**MOBOTIX**




## MxManagementCenter and Additional Licences

### ONVIF-compliant Video Management System

MxManagementCenter (MxMC) is a powerful, intuitive video management system for Windows and macOS systems. MxMC can be utilized for projects and security installations of all sizes and with any number of cameras or storage media. It was designed to be user-friendly, high-performing and secure.

Please follow this link for further license-related informations: <https://www.mobotix.com/de/support/download-center/software-downloads/licenz-portal>








	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-SW-MC</b> <b>MxManagementCenter VMS For Windows/macOS</b> Free-of-charge MOBOTIX video management software MxManagementCenter (MxMC) • Certified ONVIF conformity (Profile S) • Versions 2.1 for Windows (Vista or later) or macOS (10.9 or higher) • Language packs: English, German, French, Spanish, Italian, Russian, Turkish, Portuguese, Japanese • System requirements: 2 GHz processor (min.), at least 2 GB RAM, video card with support for OpenGL V2.1 • Download free of charge: <a href="http://www.mobotix.com">www.mobotix.com</a> > Support > Download Center > Software Downloads > Cameras > MxManagementCenter	4047438034456	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC-ADCON</b> <b>MxMC Advanced Config License</b> MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034197	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC-STARTER</b> <b>MxMC Integration Starter License</b> MOBOTIX license for the general use of H.264 with a MxMC workstation (as of MxMC 2.0) for live images, playback and/or export • Unlimited number of users per workstation • No time limit for use • One additional video channel for a third-party ONVIF-S camera included • Download via external license portal (access data required)	4047438034142	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC-CHAN</b> <b>MxMC Integration Channel License</b> MOBOTIX license for using an additional video channel from an external ONVIF S compliant IP camera with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034159	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC-SDATA</b> <b>MxMC Smart Data License</b> MOBOTIX license for connecting an external data source (Smart Data Source) to a MxMC workstation (as of MxMC 2.1) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034449	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	<b>Mx-SW-MC-POS</b> <b>MxMC POS Single Cash Point License</b> MOBOTIX license for connecting a cash register to a MxMC workstation (as of MxMC 1.7) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438031615	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l

	<p><b>Mx-SW-MC-AS-1</b>  <b>MxMC Advanced Service License, 1 Year</b>            MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 1 year/12 months • Unlimited number of users per workstation • Download via external license portal (access data required)</p>	<p>4047438034166            0 g</p>	<p>0,0 cm            0,0 cm            0,0 cm            0,0 l</p>
	<p><b>Mx-SW-MC-AS-2</b>  <b>MxMC Advanced Service License, 2 Years</b>            MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 2 years/24 months • Unlimited number of users per workstation • Download via external license portal (access data required)</p>	<p>4047438034173            0 g</p>	<p>0,0 cm            0,0 cm            0,0 cm            0,0 l</p>
	<p><b>Mx-SW-MC-AS-5</b>  <b>MxMC Advanced Service License, 5 Years</b>            MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 5 years/60 months • Unlimited number of users per workstation • Download via external license portal (access data required)</p>	<p>4047438034180            0 g</p>	<p>0,0 cm            0,0 cm            0,0 cm            0,0 l</p>



## Warranty Extensions

### Warranty Extensions

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<b>Mx-WE-DTVS-1</b> <b>1 Year Warranty Extension For Dual Thermal Systems S16</b> 3+1 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031974 g	cm cm cm l
	<b>Mx-WE-DTVS-2</b> <b>2 Years Warranty Extension For Dual Thermal Systems S16</b> 3+2 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031981 g	cm cm cm l
	<b>Mx-WE-DTVS-3</b> <b>3 Years Warranty Extension For Dual Thermal Systems S16</b> 3+3 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031998 g	cm cm cm l
	<b>Mx-WE-DTVS-4</b> <b>4 Years Warranty Extension For Dual Thermal Systems S16</b> 3+4 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438032001 g	cm cm cm l
	<b>Mx-WE-DTVS-5</b> <b>5 Years Warranty Extension For Dual Thermal Systems S16</b> 3+5 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438032018 g	cm cm cm l
	<b>Mx-WE-IVS-1</b> <b>1 Year Warranty Extension For Indoor Video Systems</b> 3+1 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031820 g	cm cm cm l
	<b>Mx-WE-IVS-2</b> <b>2 Years Warranty Extension For Indoor Video Systems</b> 3+2 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031837 g	cm cm cm l

	<p><b>Mx-WE-IVS-3</b>  <b>3 Years Warranty Extension For Indoor Video Systems</b>            3+3 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	<p>4047438031844            g</p>	<p>cm            cm            cm            l</p>
	<p><b>Mx-WE-IVS-4</b>  <b>4 Years Warranty Extension For Indoor Video Systems</b>            3+4 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	<p>4047438031851            g</p>	<p>cm            cm            cm            l</p>
	<p><b>Mx-WE-IVS-5</b>  <b>5 Years Warranty Extension For Indoor Video Systems</b>            3+5 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	<p>4047438031868            g</p>	<p>cm            cm            cm            l</p>
	<p><b>Mx-WE-OVS-1</b>  <b>1 Year Warranty Extension For Outdoor Video Systems</b>            3+1 Year Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	<p>4047438031875            g</p>	<p>cm            cm            cm            l</p>
	<p><b>Mx-WE-OVS-2</b>  <b>2 Years Warranty Extension For Outdoor Video Systems</b>            3+2 Years Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	<p>4047438031882            g</p>	<p>cm            cm            cm            l</p>
	<p><b>Mx-WE-OVS-3</b>  <b>3 Years Warranty Extension For Outdoor Video Systems</b>            3+3 Years Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	<p>4047438031899            g</p>	<p>cm            cm            cm            l</p>
	<p><b>Mx-WE-OVS-4</b>  <b>4 Years Warranty Extension For Outdoor Video Systems</b>            3+4 Years Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	<p>4047438031905            g</p>	<p>cm            cm            cm            l</p>
	<p><b>Mx-WE-OVS-5</b>  <b>5 Years Warranty Extension For Outdoor Video Systems</b>            3+5 Years Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.</p>	<p>4047438031912            g</p>	<p>cm            cm            cm            l</p>

	<p><b>Mx-WE-STVS-1</b>  <b>1 Year Warranty Extension For Single Thermal Systems</b>            3+1 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031929  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-WE-STVS-2</b>  <b>2 Years Warranty Extension For Single Thermal Systems</b>            3+2 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031936  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-WE-STVS-3</b>  <b>3 Years Warranty Extension For Single Thermal Systems</b>            3+3 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031943  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-WE-STVS-4</b>  <b>4 Years Warranty Extension For Single Thermal Systems</b>            3+4 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031950  g</p>	<p>cm cm cm l</p>
	<p><b>Mx-WE-STVS-5</b>  <b>5 Years Warranty Extension For Single Thermal Systems</b>            3+5 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.</p>	<p>4047438031967  g</p>	<p>cm cm cm l</p>