



Proof, Photo & Production media PRODUCT DATASHEET



EFI CertProof Paper 6225XF Semimatt

The EFI CertProof Paper 6225XF Semimatt is a universal PE-coated, microporous paper designed for off-set and gravure proofing. It shows outstanding results with the latest ink generation of the leading printer manufacturers (K3, Lucia, Vivid, Vivera, etc.). With its very wide color gamut the media is capable of Spot-Color Proofing and meets the industry's most stringent quality and consistency requirements. The huge gamut covers paper type classes PT1, PT2 and PT3. The EFI CertProof Paper 6225XF has almost no optical brighteners which minimises metamerism and reduces measurement errors in the profiling process. It is supplied with the EFI-FOGRA print on the backside. Naturally this media is compatible for Fogra proof creation according to ISO 12647-7.



Description:

Semimatt coated paper
Wide color gamut
Very low content of optical brighteners
Fast drying (Instant-dry)
Universal use
PEFC 100% certified



Application:

Proofing
Photo



Technical data:

Weight 225 g / m²
Thickness 230 μ
Opacity 96 %
Gloss [Tappi 75°] 53 %
L*a*b* Paper white 96, 0/ 0,0/ -1,8
Storage 15 -30 °C (40 - 60% RH)



Size

Sheet		Rolls	Core	Rolls	Core
DIN A4	(210 x 297 mm)	25,4 cm x 30 m	(10") 3" *	91,4 cm x 30 m	(36") 3"*
SUPER A4	(241 x 340 mm)	32,9 cm x 10 m	(13") 2"	106,7 cm x 30 m	(42") 3"*
DIN A3	(297 x 420 mm)	32,9 cm x 30 m	(13") 3"*	111,8 cm x 30 m	(44") 3"*
DIN A3+	(330 x 483 mm)	36,0 cm x 30 m	(14,17") 3"*	127,0 cm x 30 m	(50") 3"*
A3++	(329 x 558 mm)	43,2 cm x 30 m	(17") 3"*	135,0 cm x 30 m	(53,125") 3"*
DIN A2	(420 x 594 mm)	45,7 cm x 25 m	(18") 2"	137,0 cm x 30 m	(54") 3"*
DIN A1	(594 x 841 mm)	50,8 cm x 30 m	(20") 3"*	152,4 cm x 30 m	(60") 3"*
		61,0 cm x 25 m	(24") 2"	162,6 cm x 30 m	(64") 3"*
		61,0 cm x 30 m	(24") 3"*		



Important: Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This product data sheet is intended to be used as a guideline only. Storing conditions: Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.