

EW1691e DLP® Projector

- Light and ultra portable only 1.4kg
- Native WXGA, 2500:1 contrast ratio ideal with Widescreen & HD sources for sharp detailed images
- Conference room brightness 3000 ANSI Lumens
- Ideal presentation remote with mouse control & laser pointer
- Rapid power on and shutdown saving you time & money
- Environmentally friendly design <1W standby mode
 - DLP® filter-free design virtually no maintenance

Lightweight widescreen projector



Incredible Brightness from a Portable Widescreen Projector

Light, bright and beautifully designed

Widescreen and HD Ready; the EW1691e brings together amazing brightness, portability and cutting-edge design in one travel-friendly DLP® projector.

Weighting only 1.4kg with a staggering 3000 ANSI Lumens, perfect for large rooms and light enough to be taken on the road. Ideally partnered with a widescreen notebook and HD sources, to deliver bright vivid presentations and videos.

Small doesn't mean that you miss out on specification though, this projector still comes with an HDMI input for digital clarity, filter-free, low maintenance design and our unique 5 year Optoma Colour guarantee.

STAGGERING BRIGHTNESS

Project in brightly lit locations with the powerful 3000 ANSI Lumens to define the smallest screen details clearly. Your audience will experience the EW1691e remarkable picture in almost any lighting situation.

TRUE WXGA RESOLUTION

The EW1691e is the perfect companion for widescreen laptops. Your presentations will appear as sharp and detailed as they do on your widescreen laptop in WXGA (1280 x 800). WXGA resolution gives 30% more pixels than XGA.





TRUE HDMI

Project crystal clear images using the latest HDMI v1.3 input. Hassle-free projection from a widescreen computer/HD source with a single HDMI cable – no need for separate audio cables.



CARRY BAG

A luxury carry case is provided for you to be able to take the EW1691e anywhere, anytime.



CUSTOMISED START UP SCREEN

First impressions are important so set the company logo as your start up screen to make that lasting impression.

FEATURES

- 5 preset picture modes
- Quick keystone correction
- Easy to use on the table or ceiling mounted
- Fully featured remote with mouse control & laser pointer

AMAZING COLOURS

The EW1691e incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours.

COLOUR GUARANTEE

We are so confident that the EW1691e image colour quality will remain as good as the day you bought it that Optoma will guarantee it for five years.





Image and colour enhancement technologies WITH 2500:1 contrast ratio WITHOUT 400:1 contrast ratio

Advanced colour processing for bright, vivid, lifelike colour.

The EW1601e incorporates operate social

COST OF OWNERSHIP (TCO)

The EW1691e incorporates energy saving features to conserve power and extend the lamp life:

VIRTUALLY MAINTENANCE FREE = LOWER TOTAL

EW1691e provides lower cost of ownership, longer life and improved reliability. The filter-free projector design does not require regular

filter cleaning or filter replacement, saving you time and money.



To achieve the maximum 3000hrs** lamp life time the projector should be operating in STD mode and the shut down timer should be enabled to automatically switch off the projector if it is accidentally left on when no longer required. Enabling the <1W Standby mode will ensure the minimum energy consumption when the projector is not being used.



*Simulated Images

It takes less than 10 seconds for the projector to power up and shutdown, saving both time and energy.



EW1691E SPECIFICATIONS

Native Deceletion	W// 04 1000 000
Native Resolution	WXGA 1280 x 800
Compressed Resolution	up to UXGA (1600 x 1200)
Brightness	3000 ANSI Lumens
Contrast Naise Level (CTD made)	2500:1 33dB
Noise Level (STD mode)	
Lamp Life	3000/2000 (STD/BRIGHT mode)
Display Technology	Single 0.65" WXGA type A DMD chip
Weight / Dimensions (W x D x H)	1.4 kg / 220 x 178 x 71
Remote Control	Full Function Remote Mouse with Laser and Direct
INDUTO:	Source selecting
INPUTS:	HDMI (HDCP) - Audio Supported
	15 Pin D-Sub VGA (SCART & Component via adaptor)
	S-Video 4 Pin Mini Din
	Composite
	3.5mm Stereo Jack
Audio	USB (remote mouse)
Audio	1 x 1W Speaker
Aspect Ratio	16:10 Native, 16:9, 4:3 Compatible
Keystone Correction	± 30° Vertical
On Screen Display	17 Languages: English, German, French, Italian, Spanish,
	Portuguese, Polish, Dutch, Russian, Finnish, Swedish,
	Greek, Norwegian/Danish, Hungarian, Czech,
Video Compatibility	Turkish & Arabic
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i
Uniformity Displayable Colours	80% 134.2 Million
Displayable Colours Projection Lens	F=2.55 ~ 2.72, f=21.3 ~ 24.5mm, 1.15x Manual Focus
Throw Ratio	
Projection Distance	1.5 ~ 1.8:1 (Projection Distance:Image Width) 1.2 - 12m
Image Size	0.79 - 9.43m (30.95" - 371.42") Diagonal 16:10
Horizontal / Vertical Scan Rate	15 - 91.4kHz / 43 - 87Hz
Lamp Type	220W Lamp
Power Supply	100-240V, 50-60Hz with PFC Power Supply
Power Consumption	280W BRIGHT mode < 1W Standby mode
rower consumption	230W STD mode < 1W Standby mode
Operating Conditions	Operating: 5 - 40°C, 80% Humidity (Max),
operating conditions	3000m Altitude (Max)
Security	One Kensington Lock Port, Password Protection
Standard Accessories	Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full
Standard Accessories	Function Remote, Batteries x 2, Soft Carry Bag, Quick
	Start Guide, CD User Manual, Warranty, WEEE Card
RoHS	Compliant
Lamp Warranty	6 months or 1000 hours - whichever comes sooner
Warranty	Warranty may vary by country.
waitanty	Please see www.optomaeurope.com or ask
	your local supplier for details
Colour Guarantee*	5 Years
OUIOUI GUALAIILEE	J IUGIS

EASY TO USE REMOTE CONTROL

EW1691e Remote Control

- 1 Laser
- 2 Remote Mouse
- 3 Vertical Keystone Correction
- 4 Volume Control
- 5 Brightness Adjustment
- 6 AV Mute
- 7 Direct Input Source Selection

EW1691e Connections

- 8 USB (remote mouse)
- 9 Audio In
- 10 S-Video
- 11 Composite
- **12** VGA In Component & SCART via adaptor
- 13 HDMI (audio supported)
- **14** Kensington™ Lock



Exceptional Connectivity / Multiple Terminals



Easy to use remote with buttons to change the input sources



W1691e Projection Distance 1.2 - 12m (16:10 Aspect Ratio)									
Projection Distance (m)	Max. Horizontal Image Size (m)	Min. Horizontal Image Size (m)	Max. Screen Height (m)	Min. Screen Height (m)	Max Diagonal Image Size (m)	Max Diagonal Image Size (inch)	Max. Image Offset (m)		
1.20	0.80	0.67	0.50	0.42	0.94	37.14	0.14		
2.00	1.33	1.11	0.83	0.69	1.57	61.90	0.23		
2.50	1.67	1.39	1.04	0.87	1.97	77.38	0.29		
3.00	2.00	1.67	1.25	1.04	2.36	92.85	0.35		
4.00	2.67	2.22	1.67	1.39	3.14	123.81	0.47		
5.00	3.33	2.78	2.08	1.74	3.93	154.76	0.58		
6.00	4.00	3.33	2.50	2.08	4.72	185.71	0.70		
7.00	4.67	3.89	2.92	2.43	5.50	216.66	0.82		
8.00	5.33	4.44	3.33	2.78	6.29	247.61	0.93		
9.00	6.00	5.00	3.75	3.13	7.08	278.56	1.05		
10.00	6.67	5.56	4.17	3.47	7.86	309.51	1.17		
11.00	7.33	6.11	4.58	3.82	8.65	340.47	1.28		
12.00	8.00	6.67	5.00	4.17	9.43	371.42	1.40		

For guide purposes only

EP1691e is capable of 4:3 and 16:9 aspect ratio projection. When projecting a 4:3/16:9 image the image sizes, screen height and offset information will differ from the above.

Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

www.optoma.co.uk

