# Xerox<sup>®</sup> AltaLink<sup>®</sup> Multifunction Printers

Xerox

B8145/B8155/B8170



AltaLink<sup>®</sup> B8100 Series Multifunction Printers are built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to **www.ConnectKey.com**.

System Specification	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Speed	Up to 45 ppm	Up to 55 ppm	Up to 72 ppm	
Monthly Duty Cycle <sup>1</sup>	Up to 200,000 pages	Up to 250,000 pages	Up to 300,000 pages	
Hard Drive / Processor / Memory	Minimum 128 GB SSD / <b>Optional:</b> 500 GB HDD / In	tel® Atom™ Quad Core 1.91 GHz / 4 GB system memo	òry	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0	direct print, Wi-Fi/Wi-Fi Direct with optional Xerox® D	ual Band Wireless Kit, NFC, Bluetooth (iBeacon)	
Controller Features	Unified Address Book, Remote Control Panel, Configu	uration Cloning, Fleet Orchestrator, Configuration Wat	chdog	
Copy and Print				
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 240	0 dpi		
First-Print-Out Time (as fast as)	3.8 seconds	3.2 seconds	3.0 seconds	
First-Copy-Out Time (as fast as) (from platen/ warmed up state)	4.4 seconds	3.7 seconds	3.2 seconds	
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c / PCL® 6			
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, One Drive and Google Drive), Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Long Sheet (Banner) Printing, Print Around, Print on Alternate Paper			
Mobile and Cloud Ready				
Mobile Connectivity	Near-Field Communication (NFC); <b>Optional:</b> Wi-Fi D	Direct, Wi-Fi (802.11 b/g/n/ac), AirPrint (iOS) including	g iBeacon (Bluetooth)	
Mobile Printing	AirPrint®, Mopria®, Xerox® Print Service (Android), Go	oogle Cloud Print, @PrintByXerox; <b>Optional:</b> Xerox® W	orkplace Mobile App (iOS/Android)	
Mobile Scanning	AirPrint; <b>Optional:</b> Xerox <sup>®</sup> Workplace Mobile App (iOS/Android)			
Mobile Apps and Xerox® App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize print, convert, route, collaborate and communicate. Visit <b>xerox.com/WorkplaceApps</b> to find apps by industry or workflow. Software and services: Xerox® DocuShare® ( <b>xerox.com/ecm</b> ), XMPie® ( <b>xerox.com/XMPie</b> ), Xerox® Workplace Solutions ( <b>xerox.com/WorkplaceSolutions</b> ).			
Xerox® Workplace Suite and Xerox® Workplace Cloud	<b>Optional:</b> Xerox <sup>®</sup> Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.			



Scan	
Standard Features	<b>Destinations:</b> Scan to USB / Email / Network (FTP/SMB), Scan to Cloud Repositories (Dropbox, One Drive and Google Drive) <sup>2</sup> , HTTP, HTTPS, SFTP destinations; <b>File Formats:</b> PDF, PDF/A, XPS, JPEG, TIFF; <b>Convenience Features:</b> Scan Preview, Scan to Home, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Password Protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support
Optional Features	Xerox <sup>®</sup> Scanning App for DocuShare <sup>®</sup> , other solutions available through various Xerox Business Innovation Partners at xerox.com/Software-Solutions
Fax	
Standard Features	Internet Fax, Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)
Security	
Standard Features	802.1x, IPsec, HTTPS, SFTP and Encrypted Email, McAfee <sup>®</sup> Embedded Control Whitelisting, McAfee <sup>®</sup> ePolicy Orchestrator <sup>®</sup> , McAfee Enterprise Security Manager <sup>2</sup> , LogRhythm SIEM <sup>2</sup> , Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS 1.1/1.2, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco <sup>®</sup> Identity Services Engine (ISE) integration, automated threat response through McAfee <sup>®</sup> DXL/Cisco <sup>®</sup> pxGrid integration, Local Authentication (Internal Database), FIPS 140-2. User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Firmware Verification, Job Level Encryption via HTTPS and Drivers, Signed Email Under evaluation for Common Criteria Certification (ISO 15408), Encrypted Secure Print
Optional Features	McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET) <sup>3</sup> , Xerox <sup>®</sup> Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with Image Overwrite, Xerox <sup>®</sup> Workplace Cloud/Suite Print Management and Content Security; learn more at <b>xerox.com/WorkplaceSolutions</b>
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox <sup>®</sup> Workplace Cloud/Suite, other network accounting solutions available through various Xerox Business Innovation Partners. Xerox <sup>®</sup> Virtual Print Management Service; learn more at <b>xerox.com/PrintManagement</b>

#### Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF) saves time by simultaneously scanning both sides of two-sided documents up to 250 impressions per minute (ipm).



Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in. / A3 and Tray 2 handles media sizes up to 12 x 18 in. / SRA3.



Envelope Kit (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 3.5 x 3.9 to 12.6 x 52 in. / 89 x 98 mm 🖌 to 320 x 1,320 mm.

**High Capacity** 

Feeder (optional) holds 3.000 sheets of letter/A4 paper, increasing the maximum paper capacity to 6,140 sheets.



#### LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 12.6 x 52 in. / 320 x 1.320 mm media.







#### **USER INTERFACE**



#### Intuitive Tablet-Like 10.1-inch Color Touchscreen is customizable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

Xerox<sup>®</sup> Integrated RFID Card

90 access cards.

with the MFP.

Reader (optional) adds card-based authentication with support for over

Near Field Communication (NFC)

Tap-to-Pair allows users to tap their mobile device to the AltaLink C8100 Series user panel and quickly connect

Smart Proximity Sensor detects

when users are nearby. It conserves

energy during inactive periods and automatically activates the device when a user approaches.

#### **INNOVATIVE TECHNOLOGIES**







#### **PAPER OUTPUT / FINISHERS<sup>4</sup>**



Office Finisher (optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, making it capable of 60-page booklets (2 to 15 sheets).

**Dual Offset Catch Tray** 

(available when no finishers

are installed; Single Offset

Catch Tray with finishers).

**Business Ready** (BR) Finisher (optional) gives you advanced finishing functions at a great value.



C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold to the BR Finisher or BR Booklet Maker Finisher.



**BR Booklet Maker** Finisher (optional) create 64-page saddle-stitched booklets (2 to 16 sheets).



Integrated Office Finisher (optional with C8130/C8135/ C8145/C8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



**Convenience Stapler** (optional) staples up to 50 sheets of 20 lb. / 75 gsm media.







Device Specification			
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic		
Accessories			
Optional	High Capacity Feeder 3000 A4/Letter         Envelope Tray (Replaces Tray 1)         Horizontal Transport Kit         BR (Business Ready) Finisher (requires Horizontal Transport Kit)         BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold / Z-fold Unit for BR Finisher or BR Booklet Maker         Finisher         Convenience Stapler (includes Work Surface <sup>5</sup> )         Integrated Office Finisher (Available Altalink B8145, B8155)         Office Finisher         Booklet Maker for Office Finisher         Hole Punch (2/3, 2/4, Swedish)         Office Finisher         Smart Card Enablement Kit <sup>3</sup> Xerox® EX- C 8100 Print Server Powered by Fiery         Walk Up Fax (One- or Two-line options, includes LAN Fax)         Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit         Bluetooth Kit         McAfee® Integrity Control Enablement Kit         USB Keyboard / Shelf Kit         Xerox® Integrated RFID Card Reader Kit         Unicode Font Kit         Foreign Device Interface (Also known as Auxiliary Access Device) Interface for third-party access control devices, such of Long Sheet Feed Kit (banner printing)         500GB HDD		
Electrical Requirements	AltaLink® B8145         AltaLink® B8155         AltaLink®	B8170	
North America		0-127 VAC +/- 10% 50/60 Hz +/- 3%, 20 A	
Europe		0-240 VAC +/- 10 <i>%</i> 50/60 Hz +/- 3 <i>%</i> , 10 A	

Running (Average)115V: 717 watts 230V: 674 watts115V: 806 watts 230V: 76 watts115V: 929 watts 230V: 750 wattsStandby Mode125V: 71 watts 230V: 71 watts230V: 760 watts230V: 750 watts 230V: 72 watts230V: 750 watts 230V: 72 wattsAuto Off/Siep Mode125V: 067 watts 230V: 071 watts230V: 70 watts 230V: 075 wa	Device Specification (continued)				
1000230Y: 674 watts230Y: 760 watts230Y: 908 wattsStandby Mode115V: 71 watts115V: 72 watts230Y: 79 watts2107: 70 watts230Y: 70 watts230Y: 70 watts2107: 70 watts230Y: 70 watts230Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts230Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 minutes)210Y: 70 watts210Y: 70 watts(Default time to skep mode - 0 mi	Power Consumption	AltaLink <sup>®</sup> B8145	AltaLink® B8155	AltaLink <sup>®</sup> B8170	
1200. 71 watts2300. 70 watts70 watts	Running (Average)				
200: 0.71 watts (Default time to sleep mode = 0 minutes)200: 0.75 watts (Default time to sleep mode = 0 minutes)Warn-up (from Off)A fast as 55 secondsRecovery from SleepA fast as 4,5 secondsPretraining Environment501: 82° F / 101o 28° CRequired Temperature Range (and Part 28.5.1.7.7.2.3.1.7.8.2.7.7.4.2.8.4.7.7.8.2.7.7.3.1.7.8.2.7.7.4.2.8.4.7.7.7.7.7.7.7.4.4.8.4.7.7.7.7.7.4.4.8.4.7.7.7.7	Standby Mode				
Recovery from Sleep       As fast as 4.5 seconds         Operating Environment       So to 82° F / 10 to 28° C         Required Relative Humidity       15% to 85%         Sound Power Levels       Operating: 63.7 / 64.2 dB(A)       Operating: 65.2 / 67.3 dB(A)       Operating: 70.4 dB(A)         Standby: 4.3 / 4.3 dB(A)       Standby: 4.3 / 4.3 dB(A)       Operating: 70.4 dB(A)       Standby: 4.3 dB(A)         Offenesions and Weight       Width: 24.4 in / 620 mm       Operating: 70.4 dB(A)       Standby: 4.3 dB(A)         Standby: 4.3 / 4.3 dB(A)       Standby: 4.3 dB(A)       Standby: 4.3 dB(A)       Standby: 4.3 dB(A)         Offenesions and Weight       Width: 24.4 in / 620 mm       Operthis: 24.6 in / 71.00 mm       Depth: 32.5 in / 723 mm         Bese Configuration       Width: 24.5 in / 1.20 mm       Weight: 31.0 in / 723 mm       Depth: 31.2 in / 729 mm         Weight: 28.6 in / 723 mm       Depth: 28.5 in / 723 mm       Depth: 32.5 in / 723 mm       Depth: 32.5 in / 723 mm         Weight: 30.8 in / 723 mm       Depth: 28.5 in / 723 mm       Depth: 32.5 in / 723 mm       Depth: 32.5 in / 723 mm         Business Ready (BR) Finisher       Width: 55 in / 1.395 mm       Depth: 32.5 in / 723 mm       Depth: 32.5 in / 723 mm         Business Ready (BR) Finisher       Width: 59 in / 1.466.3 mn       Depth: 32.5 in / 723 mm       Depth: 32.5 in / 723 mm <t< th=""><td>Auto Off/Sleep Mode</td><td>230V: 0.71 watts</td><td>230V: 0.71 watts</td><td>230V: 0.75 watts</td></t<>	Auto Off/Sleep Mode	230V: 0.71 watts	230V: 0.71 watts	230V: 0.75 watts	
Operating Environment         Required Temperature Range       50 to 82° F / 10 to 28° C         Required Relative Humidity       15% to 85%         Sound Power Levels       Operating: 63.7 / 64.2 dB(A) Standby: 4.3 / 4.3 dB(A)       Operating: 70.4 dB(A) Standby: 4.3 / 4.3 dB(A)         Dimensions and Weight       Width: 24.4 in / 620 mm Depth: 28.5 in / 723 mm Height: 4.45. in / 1.130 mm Weight: 28.6 bi. / 129.5 kg       Width: 24.4 in / 620 mm Depth: 32.5 in / 723 mm Height: 4.45. in / 1.130 mm Weight: 4.55. in / 1.23 mm         Base Configuration       Width: 24.4 in / 620 mm Depth: 28.5 in / 723 mm Height: 4.45. in / 1.23 mm Weight: 28.6 in / 723 mm Height: 4.45. in / 1.207 mm Depth: 28.5 in / 723 mm Height: 4.45. in / 1.30 mm Weight: 30.5 in / 1.395 mm       Width: 47.5 in / 1.097 mm Meight: 30.5 in / 1.395 mm         Base Configuration with Business Ready (BR) Finisher Best Configuration with BB Booklet Maker Finisher BR Booklet Maker	Warm-up (from Off)	As fast as 85 seconds			
Required Temperature Range 50 to 82° F / 10 to 28° C Required Relative Humidity 15% to 85%. Sound Power Levels Operating: 63.7 / 64.2 dB(A) Standby: 4.0 / 4.0 dB(A) Standby: 4.3 / 4.3 dB(A) Standby: 4.4 / 4.5 m. / 1.620 mm Deptr: 28.5 m. / 723 mm Height: 4.45 m. / 1.130 mm Weight: 250.5 m. / 1.29 s mm Height: 4.45 m. / 1.130 mm Weight: 31.2 m. / 1.20 mm Deptr: 28.5 m. / 723 mm Height: 4.45 m. / 1.130 mm Weight: 31.2 m. / 1.20 mm Deptr: 28.5 m. / 723 mm Height: 4.45 m. / 1.130 mm Weight: 31.2 m. / 1.20 mm Deptr: 28.5 m. / 723 mm Height: 4.45 m. / 1.130 mm Weight: 31.2 m. / 1.20 mm Deptr: 28.5 m. / 723 mm Height: 4.45 m. / 1.130 mm Weight: 31.2 m. / 1.20 mm Deptr: 28.5 m. / 723 mm Height: 4.45 m. / 1.130 mm Weight: 31.2 m. / 1.130 mm Weight: 31.2 m. / 1.130 mm Weight: 31.2 m. / 1.130 mm Weight: 4.45 m. / 1.30 mm Weight: 4.45 m.	Recovery from Sleep	As fast as 4.5 seconds			
Required Relative Humidity 15% to 85%. Sound Power Levels 0perating: 63.7 / 64.2 dB(A) Standby: 4.0 / 4.0 dB(A) Standby: 4.3 / 4.3 dB(A) 0perating: 70.4 dB(A) 0perating:	Operating Environment				
Sound Power LevelsOperating: 63.7 / 64.2 dB(A) Standby: 4.0 / 4.0 dB(A)Operating: 65.2 / 67.3 dB(A) Standby: 4.3 / 4.3 dB(A)Operating: 70.4 dB(A) Standby: 4.3 dB(A)Dimensions and WeightWidth: 24.4 in. / 620 mm Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1.130 mm Weight: 286 lb. / 129.5 kgWidth: 24.4 in. / 620 mm Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1.130 mm Weight: 286 lb. / 129.5 kgWidth: 24.4 in. / 620 mm Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1.130 mm Weight: 286 lb. / 129.5 kgWidth: 24.4 in. / 620 mm Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1.100 mm Weight: 31.9 lb. / 144.8 kgWith Office Finisher (with Booklet Maker)Width: 25.5 in. / 723 mm Height: 44.5 in. / 1.30 mm Weight: 30.1 b. / 168 kgWith 155 in. / 1.30 mm Weight: 40.1 b. / 168 mm Weight: 40.5 lb. / 184.2 kgBase Configuration with Business Ready (BR) Finisher BR Booklet Maker Finisher weight: 49.5 in. / 723 mm Height: 44.5 in. / 1.30 mm Weight: 49.5 in. / 723 mm Height: 44.5 in. / 1.30 mm Weight: 31.4 kgWidth: 55 in. / 1.395 mm Depth: 32.5 in. / 723 mm Height: 44.5 in. / 1.160 mm Weight: 40.5 in. / 1.406.3 mm Depth: 32.3 lb. / 13.8 mm Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1.400 mm Weight: 40.5 in. / 1.406.3 mm Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1.160 mm Weight: 45.3 lb. / 20.5 kgBase Configuration with BR Booklet Maker Finisher and C-fold / Z-fold Unit Weight: 53.6 lb. / 24.0 kgWidth: 53 in. / 1.300 mm Weight: 53.6 lb. / 240.7 kgBase Configuration with BR Booklet Maker Finisher Pith: 28.5 in. / 723 mm Height: 45.5 in. / 723 mm <br< th=""><td>Required Temperature Range</td><td>50 to 82° F / 10 to 28° C</td><td></td><td></td></br<>	Required Temperature Range	50 to 82° F / 10 to 28° C			
Standby: 4.0 / 4.0 dB(A)Standby: 4.3 / 4.3 dB(A)Standby: 4.3 dB(A)Dimensions and WeightWidth: 24.4 in. / 620 mm Depth: 31.5 in. / 723 mm Height: 44.5 in. / 1.130 mm Weight: 28.6 b. / 129.5 kgWidth: 24.4 in. / 620 mm Depth: 31.2 in. / 733 mm Height: 44.5 in. / 1.130 mm Weight: 28.6 b. / 129.5 kgWidth: 24.4 in. / 620 mm Depth: 31.2 in. / 733 mm Height: 44.5 in. / 1.130 mm Weight: 28.5 in. / 723 mm Height: 44.5 in. / 1.130 mm Weight: 30.8 in. / 723 mm Height: 44.5 in. / 1.130 mm Weight: 30.8 in. / 723 mm Height: 44.5 in. / 1.130 mm Weight: 30.8 in. / 723 mm 	Required Relative Humidity	15% to 85%			
Base ConfigurationWidth: 24,4 in. / 620 mm Depth: 28,5 in. / 723 mm Height: 445 in. / 1,130 mm Weight: 286 lb. / 129.5 kgWidth: 24,4 in. / 620 mm Depth: 31.2 in. / 733 mm Height: 445. in. / 1,130 mm Weight: 312. lb. / 144.8 kgWith Office Finisher (with Booklet Maker)Width: 47.5 in. / 1.207 mm Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 370.3 lb. / 168 kgWidth: 47.5 in. / 1.207 mm Depth: 31.2 in. / 733 mm Height: 44.5 in. / 1,130 mm Weight: 370.3 lb. / 168 kgWidth: 55 in. / 1.395 mm Depth: 31.2 in. / 733 mm Height: 44.5 in. / 1,130 mm Weight: 370.3 lb. / 168 kgBase Configuration with Business Ready (BR) Finisher Br Booklet Maker Finisher Re Booklet Maker Finisher and C-fold / Z-fold UnitWidth: 59 in. / 1.395 mm Depth: 32.3 lb. / 173.4 kgWeight: 44.5 in. / 1.395 mm Depth: 32.3 lb. / 173.9 mm Height: 44.5 in. / 1.30 mm Weight: 30.3 lb. / 173.4 kgBase Configuration with BR Booklet Maker Finisher and C-fold / Z-fold Unit Weight: 43.2 in. / 723 mm Height: 44.5 in. / 1.30 mm Weight: 43.3 lb. / 109.4 kgWidth: 59 in. / 1.395 mm Depth: 32.3 lb. / 166.3 mm Depth: 32.3 lb. / 173.4 mm Height: 44.5 in. / 1.30 mm Weight: 43.3 lb. / 1.30 mm Weight: 43.3 lb. / 20.5 kgBase Configuration with BR Booklet Maker Finisher and C-fold / Z-fold Unit Weight: 43.5 in. / 7.23 mm Height: 44.5 in. / 1.30 mm Weight: 43.2 lb. / 723 mm Height: 44.5 in. / 1.30 mm Weight: 43.5 in. / 723 mm Height: 44.5 in. / 1.30 mm Weight: 53.0 k.6 / 20.0 / kgBase Configuration with BR Booklet Maker Finisher c. Fold / Z-fold Unit Weight: 53.0 k. / 22.0 / kgWidth: 53 in. / 23.6 lm Weight: 53.0 k. / 23.0 mm Weight: 53.0 k. / 23.0 mm Weight: 53.0 k. / 23.0 mm Weight: 5	Sound Power Levels				
Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1,130 mmDepth: 31.2 in. / 793 mm Height: 44.5 in. / 1,169 mmWith Office Finisher (with Office Finisher (with Booklet Maker)Width: 47.5 in. / 1,207 mm Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 370.3 lb. / 168 kgWidth: 47.5 in. / 1207 mm Depth: 31.2 in. / 793 mm Height: 46.5 in. / 1,130 mm Weight: 370.3 lb. / 168 kgBase Configuration with Business Ready (BR) Finisher Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 320.3 lb. / 168 kgWidth: 55 in. / 1,395 mm Depth: 31.2 in. / 723 mm Height: 46.5 in. / 1,395 mm Depth: 32.3 lb. / 173.4 kgBase Configuration with BR Booklet Maker Finisher and C-fold / Z-fold UnitWidth: 59 in. / 1,496.3 mm Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1,169 mm Weight: 41.5 in. / 1,169 mm Weight: 45.3 in. / 1,231 mm Height: 44.5 in. / 1,130 mm Weight: 45.3 in. / 1,231 mm Height: 45.5 in. / 223 mm Height: 45.5 in. / 235 mm Weight: 530.6 lb. / 240.7 kgBase Configuration with BR Booklet Maker Finisher and C-fold / Z-fold Unit and Height: 45.5 in. / 723 mm Height: 45.5 in. / 723 mm 	Dimensions and Weight				
(with Booklet Maker)Depth: 28.5 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 370.3 lb. / 168 kgDepth: 31.2 in. / 793 mm Height: 46 in. / 1,169 mm Weight: 406 lb. / 184.2 kgBase Configuration with Business Ready (BR) Finisher Base Configuration with BR Booklet Maker Finisher and C-fold / Z-fold UnitWidth: 55 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 32.3 lb. / 173.4 kgWidth: 59 in. / 1,496.3 mm Depth: 31.2 in. / 723 mm Height: 44.5 in. / 1,169 mm Weight: 415.4 lb. / 188.4 kgBase Configuration with BR Booklet Maker Finisher and C-fold / Z-fold UnitWidth: 63.1 in. / 1,632 mm Depth: 23.5 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 419.7 lb. / 190.4 kgWidth: 64.3 in. / 1,632 mm Depth: 31.2 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 419.7 lb. / 190.4 kgWidth: 64.3 in. / 1,632 mm Depth: 31.2 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 453.3 lb. / 205.6 kgBase Configuration with BR Booklet Maker Finisher and C-fold / Z-fold UnitWidth: 64.3 in. / 1,632 mm Depth: 32.5 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 530.6 lb. / 240.7 kgWidth: 63.3 lb. / 205.6 kgBase Configuration with BR Booklet Maker Finisher and C-fold / Z-fold UnitWidth: 64.3 in. / 1,632 mm Depth: 32.5 in. / 723 mm Height: 44.5 in. / 1,130 mm Weight: 530.6 lb. / 240.7 kgWidth: 530.6 lb. / 240.7 kgBase Configuration with BR Booklet Maker Finisher and C-fold / Z-fold Unit and Height: 44.5 in. / 1,130 mm Weight: 530.8 lb. / 240.7 kgWidth: 530.8 lb. / 240.7 kgWidth: 530.8 lb. / 240.7 kgBread Configuration with BR Booklet Maker Finisher C-fold / Z-fold Unit and Height: 44.5 in. / 1,130 mm Weight: 538.8 lb. / 271.6 kgWid	Base Configuration	Depth: 28.5 in. / 723 mm         Depth: 31.2 in. / 793 mm           Height: 44.5 in. / 1,130 mm         Height: 46 in. / 1,169 mm		Depth: 31.2 in. / 793 mm Height: 46 in. / 1,169 mm	
Business Ready (BR) Finisher Height: 44.5 in. / 1,130 mm Weight: 382.3 lb. / 173.4 kgDepth: 28.5 in. / 723 mm Height: 44.5 in. / 1,130 mm 	With Office Finisher (with Booklet Maker)	Depth: 28.5 in. / 723 mm         Depth: 31.2 in. / 793 mm           Height: 44.5 in. / 1,130 mm         Height: 46 in. / 1,169 mm			
BR Booklet Maker Finisher Br Booklet Maker Finisher and C-fold / Z-fold UnitDepth: 28.5 in. / 723 mm Height: 44.5 in. / 1,130 mm 	Base Configuration with Business Ready (BR) Finisher	Width: 55 in. / 1,395 mm         Width: 55 in. / 1,395 mm           Depth: 28.5 in. / 723 mm         Depth: 31.2 in. / 723 mm           Height: 44.5 in. / 1,130 mm         Height: 46 in. / 1,169 mm			
BR Booklet Maker Finisher and C-fold / Z-fold UnitDepth: 28.5 in. / 723 mmDepth: 31.2 in. / 723 mmBase Configuration with BR Booklet Maker Finisher, C-fold / Z-fold Unit and 	Base Configuration with BR Booklet Maker Finisher	Width: 59 in. / 1,496.3 mm         Width: 59 in. / 1,496.3 mm           Depth: 28.5 in. / 723 mm         Depth: 31.2 in. / 723 mm           Height: 44.5 in. / 1,130 mm         Height: 46 in. / 1,169 mm			
BR Booklet Maker Finisher,         Depth: 28.5 in. / 723 mm         Depth: 31.2 in. / 723 mm           C-fold / Z-fold Unit and         Height: 44.5 in. / 1,130 mm         Height: 46 in. / 1,169 mm           High Capacity Feeder         Weight: 598.8 lb. / 271.6 kg         Weight: 632.8 lb. / 287 kg	Base Configuration with BR Booklet Maker Finisher and C-fold / Z-fold Unit	Depth: 28.5 in. / 723 mm         Depth: 31.2 in. / 723 mm           Height: 44.5 in. / 1,130 mm         Height: 46 in. / 1,169 mm			
System Certification / Regulatory Compliance	Base Configuration with BR Booklet Maker Finisher, C-fold / Z-fold Unit and High Capacity Feeder	Depth: 28.5 in. / 723 mm         Depth: 31.2 in. / 723 mm           Height: 44.5 in. / 1,130 mm         Height: 46 in. / 1,169 mm			
	System Certification / Regulatory Compliance				
Certifications To view the latest list of certifications, go to xerox.com/OfficeCertifications	Certifications	To view the latest list of certifications, go to <b>xerox.com/OfficeCertifications</b>			

Paper Handling	AltaLink® B8145	AltaLink <sup>®</sup> B8155	AltaLink® B8170		
Single-pass Duplex Automat	ic Document Feeder (DADF)				
Capacity <sup>4</sup>	130 sheets		250 sheets		
Speed (Up to)	82 ppm black-and-white (simplex)     135 ppm black-and-white (simplex)       141 ipm black-and-white (duplex)     250 ipm black-and-white (duplex)				
Paper Sizes Sensed	3.4 x 4.9 in. to 11.7 x 17 in. / 85 x 125 mm to 297	x 432 mm			
Weights	16 lb. to 32 lb. bond / 60 to 128 gsm				
Bypass Tray (Standard)					
Capacity <sup>4</sup>	100 sheets	100 sheets			
Sizes	Custom Sizes: 3.5 x 3.9 in. to 12.6 x 52 in. / 89 x 9	Custom Sizes: 3.5 x 3.9 in. to 12.6 x 52 in. / 89 x 98 mm to 320 x 1320 mm (SEF); Optional: Long Sheet Feed Kit (Banner Printing)			
Weights	16 lb. bond to 110 lb. cover / 52 to 300 gsm				
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies				
Trays 1 and 2 (Standard)					
Capacity <sup>4</sup>	520 sheets each				
Sizes	<b>Tray 1:</b> Custom Sizes: 5.5 x 7.2 in. to 11.7 x 17 in <b>Tray 2:</b> Custom Sizes: 5.5 x 7.2 in. to 12 x 18 in. / 1				
Weights	16 lb. bond to 110 lb. cover / 52 to 300 gsm				
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies				

Paper Handling (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink <sup>®</sup> B8170		
High Capacity Tandem Tray	ligh Capacity Tandem Tray (Available with all models)				
Capacity <sup>4</sup>	<b>Tray 3:</b> 867 sheets <b>Tray 4:</b> 1,133 sheets				
Sizes	8.5 x 11 in. / A4, JIS B5, Executive (7.25 x 10.5 in) LE	F			
Weights	16 lb. bond to 110 lb. cover / 52 to 300 gsm				
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted				
Envelope Tray (Optional - Re	places Tray 1)				
Capacity <sup>4</sup>	Up to 60 envelopes				
Sizes	#10 Commercial (9.25 x 4.125 in.) / Monarch, DL, CS Custom Sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148				
Weights	20 lb. to 24 lb. bond / 75 to 90 gsm				
High Capacity Feeder (HCF)	(Optional with all models)				
Capacity <sup>4</sup>	3,000 sheets				
Sizes	Standard Sizes: 8.5 x 11 in. or 7.25 x 10.5 in. / A4 or B5 LEF				
Weights	16 lb. bond to 110 lb. cover / 52 to 300 gsm				
Total Capacity					
Device Total Capacity <sup>4</sup>	Four Tray Module: 2,180 sheets Four Tray Module with High Capacity Feeder: 5,180 s High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Capa				

Finishing	AltaLink® B8145 AltaLink® B8155 AltaLink® B8170
Output Trays (Standard) (Du	al Offset Catch Trays not available with Integrated Office Finisher and limited to one with Office FInisher and BR Finishers)
Stacking Tray Capacity <sup>4</sup>	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face up Tray: Up to100 sheets
Integrated Office Finisher (C	Optional with AltaLink B8145/B8155)
Stacking Tray Capacity <sup>4</sup>	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm
Weights	16 lb. bond to 110 lb. cover / 52 to 300 gsm
Stapling	Single / Dual Position Auto-Stapling: 50 sheets maximum: Letter / A4 / B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher (Optional)	
Stacking Tray Capacity <sup>4</sup>	2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Stacking Tray Sizes	8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm
Weights	16 lb. bond to 110 lb. cover / 52 to 300 gsm
Multiposition Stapling	50 sheets maximum: Letter / A4 / B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet Maker for Office Fin	isher (Score/Crease, Saddle-stitch Staple) (Optional)
Top Tray Capacity <sup>4</sup>	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Tabloid – 11 x 17 in. / A3 SEF
Saddle-Stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 67 lb. bond / 60 to 256 gsm
Score / Crease	1-15 sheets / unstapled 18 lb. bond to 28 lb. bond / 60 to 105 gsm
Business Ready (BR) Finishe	r (Optional) (Requires Horizontal Transport Kit)
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in. / A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in / 100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in. / 182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover / 52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb. / 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
BR Booklet Maker Finisher (	Optional) (Requires Horizontal Transport Kit)
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in / 100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in. / 182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover / 52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb. / 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported

Finishing (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170		
C-fold / Z-fold Unit (Option	al with BR Finisher and BR Booklet Maker Finisher)	l with BR Finisher and BR Booklet Maker Finisher)			
Types	C-fold, Z-fold and Z-half-fold				
Capacity <sup>6</sup>	40 sheets				
Sizes	C-fold and Z-fold: Letter – 8.5 x 11 in. / A4 SEF only Z-half-fold: Tabloid – 11 x 17 in. / A3 only				
Weights	16 lb. to 24 lb. bond / 64 to 90 gsm				
Output Trays	Envelope Tray: C-fold, Z-fold and Tri-fold Stacker Tray or Top Tray: Z-half-fold				
Convenience Stapler (Optic	nal - Includes Work Surface <sup>5</sup> )				
Capacity <sup>6</sup>	50-sheet stapling 5,000 staples Requires separate power outlet				
Сору	AltaLink <sup>®</sup> B8145	AltaLink <sup>®</sup> B8155	AltaLink <sup>®</sup> B8170		
First-Copy-Out Time (from platen/warmed up)	As fast as 4.4 seconds	As fast as 3.7 seconds	As fast as 3.2 seconds		
Sides (input:output)	1-1, 1-2, 2-2, 2-1				
Quantity	1 to 9,999				
Resolution (max)	Up to 600 x 600 dpi				
Reduction / Enlargement	Variable zoom from 25 % to 400 % in 1 % incremen	ts			
Concurrency	Program-ahead to allow job to be queued while initi	al job is processed (Copy, Print, Fax and Scan)			
Copy Features	Annotation and Bates <sup>™</sup> stamping Authentication for Services Auto Paper Select Auto Reduction & Enlargement (To fit selected paper size) Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Transparencies				
Xerox® Copier Assistant®	Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508-compliant. For more information or to download Xerox® Copier Assistant® for free, visit <b>xerox.com</b>				

Print	AltaLink <sup>®</sup> B8145	AltaLink <sup>®</sup> B8155	AltaLink <sup>®</sup> B8170		
Resolution (up to)	1200 x 2400 dpi				
Print Features	LAN Fax (requires optional Fax Kit) Layout / Watermark N-up (up to 16 pages per sheet) Booklet Layout Long Sheet / Banner Finishing Fit to New Paper Size Hold All Jobs Paper Selection by Attribute Sample Saved Job Secure Print with Timed Deletion Special Pages (exception page prog Store and Recall Driver Settings	ition (Standard, Enhanced, High) er, Print ID in margins on first page only or all pages) e Set gramming: covers, inserts, exception pages) h Smart Settings, Duplex, N-up, Turn-off Banner and	Print ID, Smart Sample Set, Hold All Jobs)		
Print from USB	Allows walk-up printing from Type A Supports direct printing from comp Supported file formats: PDF, JPEG, 1 Color jobs can be printed as black-a	uter via Type B USB port TIFF, PS, XPS, PCL			
Operating Systems	Windows Server 2008 SP2 (32- and Windows Server 2008 R2 (64-bit) Windows Server 2012 and R2 (64-bit) Windows Server 2019 (64-bit) Windows 7 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.13, 10.14, 10.15 Fedora <sup>®</sup> Core Ubuntu <sup>®</sup>				
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Print Microsoft Windows Networking ove Bonjour <sup>®</sup> / AirPrint <sup>®</sup> IPv6 Most protocols not in use can be dis		, IPv4/IPv6, WSD		
Font Capability	PCL: 93 scalable fonts, line printer a	nd bitmap font (including Cyrillic font support) PostSo	cript 3: 173 Type 1 fonts, 2 Multiple Master fonts		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox <sup>®</sup> and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management.				
Xerox <sup>®</sup> Pull Print Driver	driver. The Xerox® Pull Print Driver e		ngle driver in a Pull Print environment. Uses a single queue and single assets. IT administrators no longer need to manage and configure thers.		
Unified Address Book for Fax	Unified Address Book for Fax, Internet Fax, Email and Scan to				
Features	Services supported: Fax, Internet Fa Maximum contacts: 5,000 Contacts: Supports 1 or more destir Favorites for quick access of all serv	nations			

Scan	AltaLink® B8145	AltaLink <sup>®</sup> B8155	AltaLink <sup>®</sup> B8170	
Concurrency	Scan while the system is printing, concurrent jobs)	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)		
Input Speed (up to)	82 ppm black-and-white and color (simplex)     135 ppm black-and-white and color (simplex)       141 ipm black-and-white and color (duplex)     250 ipm black-and-white and color (duplex)			
Resolution	72 x 72 dpi to 600 x 600 dpi			
Bit Depth	1-bit (black-and-white), 8-bit (gra	yscale), 24-bit (color)		
Maximum Scan Area	11 x 17 in. / A3			
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS sca	an templates and share via device cloning to other	multifunction printers' confirmation sheet options	
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS			
File Compression		MMR compression – single or multiple pages)	JBIG Arithmetic Compression, Deflate (for black-and-white and within	
Document Management Fields (Metadata)	Metadata field consists of field r	k Scan to File Templates: adata fields per network scan to file templates and u name, default value and other configurations er interface for variable data input	unlimited fields within the template –	
Scan Features	Mixed Size Originals Scan Build Job Scan Preview Compression Quality/File Size Cor Original Type (Photo and Text, Ph Auto Background and Shadow Su Size for Size (for mixed size origin TWAIN Support / WIA 2.0 Suppor Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to	oto, Text, Map, Newspaper / Magazine) ippression als) rt		
Scan to Email (Standard)				
Scan Features	Email signatures (6 lines each o Scan to Email S/MIME Encryptir Email signing (requires Smart Co Auto send to self	on	nfigurable), email Embedded Web Server confirmation sheet options	
Directory Access	Address list via LDAP (Windows A	ctive Directory, Exchange, Notes, Domino), Device A	Address Book	
Scan To (Standard)				
Features	Scan to USB Scan to Network Folder (using Sec Scan to Home Scan to Network (using Secure FT Scan to Email Scan to PC/Server Client (SMB or Scan to Mailbox Scan to Cloud Repositories (Dropl	P/HTTP/HTTPS)		
Workflow Scanning (Option	al)			
Scanning Software	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2			
Scanning Apps and Xerox App Gallery		Drive™, Microsoft® OneDrive®, Microsoft Office 365 n the Xerox App Gallery: <b>xerox.com/AppGallery</b>	™, Box®, Xerox® Workplace Mobile App (iOS/Android)	

Security	AltaLink® B8145	AltaLink® B8155	AltaLink <sup>®</sup> B8170
Features	Expanded Authentication		
-	<ul> <li>Expanded Authentication</li> <li>Network authentication to acc Windows server 2012), NDS, L</li> <li>Local Authentication (internal Smart Card authentication – 1</li> <li>Secure Data</li> <li>Digitally signed PDF (when usi Encrypted and authentication</li> <li>Encrypted and authentication</li> <li>Encrypted / Password Protecter</li> <li>Secure Print (up to 10 digit PIN</li> <li>Immediate Image Overwrite / On Demand Image Overwrite</li> <li>FIPS 140-2 256 bit Hard Disk E</li> <li>Expanded Authorization</li> <li>SA access based on network cr</li> <li>Authorization per user per serv</li> <li>User Permissions required to ac Secure Network Access</li> <li>Configuration Watchdog (Monitt Front USB Port 2</li> <li>Rear USB Port 1</li> <li>Rear USB Port 2</li> <li>Password Reset Access Control 802.1x</li> <li>Email Alerts - Group 1, 2 and 3</li> <li>Hold all jobs</li> <li>Scan to Mailbox enablement</li> <li>Fax Passcode length</li> <li>System timeout</li> <li>Show/Hide Login Name</li> <li>PostScript® Passwords</li> <li>Remote Services Setup Supplie</li> <li>Scheduled Upgrade</li> <li>SNMP V1/V2 Protocols: Enable</li> <li>Scan Workflow Management</li> <li>PII - Show Concealed Job Name</li> <li>PII - Show Concealed Job Name</li> <li>PII - Show Concealed Job Name</li> </ul>	ess device and/or device services via Kerberos (UNIX LDAP authentication database) (44k CAC / PIV Card Support (2048 bit certificate key ing Smart Card authentication) to SMTP server for Scan to Email d PDF (when using Email and Network Scan Templat N or Network Authentication) 'Securely delete jobs using approved algorithms (Scheduled, Manual), includes sanitation of unused of Encryption, TLS, IPPS, HTTPS, SFTP, SNMPv3 redentials vice ccess Print and Print Features (e.g. color access, or tim for and remediate 29 security settings):	/ Windows Server 2008), SMB (Windows Server 2008, ) / .NET es only) area of disk ne restrictions) reflects in the print driver
	<ul> <li>Hide Print Job Names</li> <li>Cisco<sup>®</sup> Identity Services Engine (</li> </ul>	(ISE) compatible	
	Security Information and Event	Management (SIEM) support for McAfee Enterprise rtified by NIAP under HD Protection Profile for Hardco	
Xerox® Integrated RFID Card Reader (Optional kit)	Integrated support for most indus the multifunction printer panel.	stry security cards providing additional security; with (	embedded multifunction printer card readers in

Fax	AltaLink <sup>®</sup> B8145	AltaLink <sup>®</sup> B8155	AltaLink® B8170
Network Server Fax Features			
Compatibility	ITU (CCITT) group 3; Various Xerox Business Innova	tion Partner Solutions	
Maximum Scan Area	11 x 17 in. / A3		
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (200 numbers maximum) Build Job, Favorites, Delay Send (specific time) Origin	al Type (photo, text or photo and text)	
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print		
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi		
Internet Fax Features			
Compatibility	Direct print-ready document transmission to remote Reception and automatic printout of documents sen		nail clients
Directory Access	Utilizes the Unified Address Book		
Send / Receive	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN,	JPEG	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)		
Network Protocols	SMTP (send), POP3 (receive)		
Compliance	ITU-T T.37 compliant		
Walk-up Fax Features (Option	nal; Customer-Installable – 1 and 2 lines)		
Compatibility	ITU (CCITT) Group 3		
Speed / Modems	One or Two V.34 moderns: 33,600 bps. Less than 4 so ATA analog terminal adapter utilizing T38 (optional)		
Compression / Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3		
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes		
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) Device Address Book (up to 5,000 contacts)		
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, her Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay	ader) / Auto	
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only		
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report		
Directory Access	Utilizes the Unified Address Book Group fax available		
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals		
Auto Resend	Up to 5 attempts		

Device Management			
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP		
	MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Configuration Orchestrator, Configuration Watchdog		
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows 7 and Internet Explorer 6.0 and higher. • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote install		
Xerox® Device Manager	<ul> <li>Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across you enterprise. Xerox® Device Manager provides:</li> <li>Device monitoring and troubleshooting</li> <li>Extensive reporting and discovery of new devices</li> <li>Usage collection, chargeback and billing capabilities</li> <li>Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install</li> </ul>		
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files.		
Novell NDPS/NEPS	Server gateway application: centralized management tool.		
Xerox <sup>®</sup> Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. As an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. office.xerox.com/Software-Solutions		
Xerox® Device Types for SAP R/3 Intelligent Bar- code Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions		
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox <sup>®</sup> multifunction printers by storing Xerox <sup>®</sup> software, as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at office.xerox.com/Software-Solutions		
Xerox <sup>®</sup> Embedded Web Serve	er – Integrated Device Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel		
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator		
Browsers	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x		
Support	Install print / scan drivers and online support available via support.xerox.com		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic		
Remote Services			
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox <sup>®</sup> device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox <sup>®</sup> Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Accounting			
Xerox <sup>®</sup> Standard Accounting	(Standard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group accounts (Department)		
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>		
Accounting Options - Netwo	rk Accounting (Allows central server to manage all accounting)		
	<ul> <li>Enhanced network accounting with up-to-the-minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>		

Supplies	Description	Yield
Toner Cartridge <sup>6</sup>	Black	52,000 pages
Transfer Belt Cleaner	1 Assembly	160,000 pages
Second Bias Transfer Roll	1 Assembly	200,000 pages
Staple Cartridges	For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge
Staple Refills	For Integrated Office Finisher, Office Finisher, BR Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill
Xerox® Smart Kit®		
Drum Cartridge <sup>8</sup>	1 Cartridge per Color	198,000 pages
Waste Toner Container w/o Suction Filter <sup>9</sup>	1 Cartridge (AltaLink B8145/8155)	121,000 pages
Waste Toner Container with Suction Filter <sup>9</sup>	1 Cartridge (AltaLink B8170)	121,000 pages

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup>Available post-launch via software update.

<sup>3</sup>Not available in all geographies. <sup>4</sup>Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>5</sup> Sold separately in some geographies.

<sup>6</sup>Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes and image quality set-points.

<sup>7</sup>Under evaluation; certification expected in Q4 2020.

\*Average drum yield is based on a run length of 5 pages of 8.5 x 11 in. / A4 LEF pages, with split of 35% color / 65% black-and-white pages.

<sup>9</sup>Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.parmetech.com



**Xelox** 

© 2020 Xerox Corporation. All rights reserved. Xerox® and AltaLink®, CentreWare®, ConnectKey®, Copier Assistant®, DocuShare®, Global Print Driver®, MeterAssistant®, SmartKit® and SuppliesAssistant® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Mopria is a trademark of the Mopria Alliance. The information in this brochure is subject to change without notice. 6/20 PN04017 AB8SS-03UA BR29565 CH994 CH998