



NOTE: This document is only for general reference. Solution Builder and related PMBs should be used for product availability, pricing, and final solution selection.

Communication Cables

USB Cables

Part Number	Picture	Description	Notes	Required Items
CBL-58926-05		USB Cable: 18 in. Straight	<ul style="list-style-type: none"> 9-Pin Female connector on scanner side Standard USB/A connector on host side 18 inch Long Straight Cable Optimal for Kiosk Integration Includes added strain relief for applications that require hand held operation 	
25-58926-05R		USB Cable: 18 in. Straight	<ul style="list-style-type: none"> Discontinued 2/2015, now use CBL-58926-05 9-Pin Female connector on scanner side Standard USB/A connector on host side 18 inch Long Straight Cable Optimal for Kiosk Integration 	
CBL-58926-04		USB Cable: 6 ft. Straight	<ul style="list-style-type: none"> 9-Pin Female connector on scanner side Standard USB/A connector on host side 6 ft. Long Straight Cable Includes added strain relief for applications that require hand held operation 	
25-58926-04R		USB Cable: 6 ft. Straight	<ul style="list-style-type: none"> Discontinued 2/2015, now use CBL-58926-04 9-Pin Female connector on scanner side Standard USB/A connector on host side 6 ft. Long Straight Cable 	
CBL-58926-06		USB Cable: 9 ft. Coiled	<ul style="list-style-type: none"> 9-Pin Female connector on scanner side Standard USB/A connector on host side 9 ft. Long Coiled Cable Includes added strain relief for applications that require hand held operation 	
25-58926-06R		USB Cable: 9 ft. Coiled	<ul style="list-style-type: none"> Discontinued 2/2015, now use CBL-58926-06 9-Pin Female connector on scanner side Standard USB/A connector on host side 9 ft. Long Coiled Cable 	
25-58925-02R		USB Cable: 6 ft. Straight with Trigger Jack and Beeper	<ul style="list-style-type: none"> 9-Pin Female connector on scanner side Standard USB/A connector on host side 6 ft. Long Straight Cable 	Trigger Cable (25-04950-01R or 25-13176-01R)

RS232 Cables









Part Number	Picture	Description	Notes	Required Items
CBL-58918-02		RS232 Cable: STD-DB9 Female, TxD on 2, 6 ft. Straight	<ul style="list-style-type: none"> 9-Pin Female connector on scanner side DB9 Female connector on host side 6 ft. Long Straight Cable Includes added strain relief for applications that require hand held operation 	Requires external power supply

25-58918-02R		RS232 Cable:STD-DB9 Female, TxD on 2, 6 ft. Straight	<ul style="list-style-type: none"> Discontinued 2/2015, now use CBL-58918-02 9-Pin Female connector on scanner side DB9 Female connector on host side 6 ft. Long Straight Cable 	Requires external power supply
CBL-58918-03		RS232 Cable:STD-DB9 Female, TxD on 2, 9 ft. Coiled	<ul style="list-style-type: none"> 9-Pin Female connector on scanner side DB9 Female connector on host side 9 ft. Long Coiled Cable Includes added strain relief for applications that require hand held operation 	Requires external power supply
25-58918-03R		RS232 Cable:STD-DB9 Female, TxD on 2, 9 ft. Coiled	<ul style="list-style-type: none"> Discontinued 2/2015, now use CBL-58918-03 9-Pin Female connector on scanner side DB9 Female connector on host side 9 ft. Long Coiled Cable 	Requires external power supply
25-13227-03R		RS232 Cable:STD-DB9 Female, TxD on 2, 6 ft. Straight with Trigger Jack	<ul style="list-style-type: none"> 9-Pin Female connector on scanner side DB9 Female connector on host side 6 ft. Long Straight Cable 	<ul style="list-style-type: none"> Requires external power supply Trigger Cable (25-04950-01R or 25-13176-01R)
25-62186-03R		RS232 Cable:STD-DB9 Female, TxD on 2, True Cvt, 6 ft. Straight	<ul style="list-style-type: none"> 9-Pin Female connector on scanner side DB9 Female connector on host side Cable converts TTL (5V) Signal at Scanner to TRUE RS-232 (+/- 12V) Signal at Host which may be needed by some older PLC's that don't support TTL signalling 6 ft. Long Straight Cable 	Requires external power supply
25-13228-03R		RS232 Cable:STD-DB9 Female, TxD on 2, 6 ft. Straight with Trigger Jack and Beeper	<ul style="list-style-type: none"> 9-Pin Female connector on scanner side DB9 Female connector on host side 6 ft. Long Straight Cable 	<ul style="list-style-type: none"> Requires external power supply Trigger Cable (25-04950-01R or 25-13176-01R)
Misc				
Part Number	Picture	Description	Notes	Required Items
20-60136-02R		Gooseneck Intellistand	<ul style="list-style-type: none"> Includes screws for mounting DS457 to the stand 	
KT-65578-01R		Miniscan Adjustable Mounting Bracket	<ul style="list-style-type: none"> Provides easier mounting of DS457 in a kiosk or other confined space locations 	

KT-152342-01		MS320x Mounting Bracket Adapter	<ul style="list-style-type: none"> Allows DS457 to use same mount as existing MS320x installations Bracket adapts DS457 to fit into holes for MS320x 	
KT-145344-01		POS Stand/Mounting Bracket	<ul style="list-style-type: none"> Walkie-talkie style clip attaches to wall/counter and allows for easy fixed mounting and removal of DS457 DS457 is positioned at a 20° angle when attached to clip DS457 bracket is Jet black color 	
25-04950-01R		Push Button Trigger Cable	<ul style="list-style-type: none"> Allows scanner to be manually triggered by the operator 	Scanner Cable with Trigger Jack
25-13176-01R		Photo Sensor Trigger Cable	<ul style="list-style-type: none"> Allows scanner to be triggered automatically when sensor detects movement. Cable is typically used on a conveyor belt Discontinued 8/2013 	Scanner Cable with Trigger Jack

Power Supplies/Power Cords (any power supply listed below can be used with DS457 cables that require an external power supply)

Part Number	Picture	Description	Notes	Required Items
PWR-WUA5V4W0US		Power Supply (US)	<ul style="list-style-type: none"> Used when connecting communication cables labeled above as "Requires external power supply". For use in US, CA, MX, JP, TW. 5.2V, 1.1A, 5.7W Provides US DOE Level VI compliance for power efficiency. Replaces PWRS-14000-253R 	
PWRS-14000-253R		Power Supply (US)	<ul style="list-style-type: none"> Discontinued 2/2017, now use PWR-WUA5V4W0US - PMB 2903. Used when connecting communication cables labeled above as "Requires external power supply". 110V/60Hz - For use in US and CA-MX-JP-TW 5VDC, 850MA Energy Star Compliant 	
50-14000-253R		Power Supply (US)	<ul style="list-style-type: none"> Discontinued 11/2010, now use PWRS-14000-253R Used when connecting communication cables labeled above as "Requires external power supply". 110V/60Hz - For use in US and other countries 	
KT-14001-001R		Power Supply (US)	<ul style="list-style-type: none"> 110V/60Hz - For use in US and other countries Includes 50-14001-001R power supply, 25-100620-01R DC Line cord, and 23844-00-00R AC Line cord Discontinued 11/08 - now use 50-14000-253R 	
50-14000-008R		Power Supply (US)	<ul style="list-style-type: none"> 110V/60Hz - For use in US and other countries Discontinued 11/1/07 - now use KT-14001-001R 	

PWR-WUA5V4W0IN		Power Supply (India)	<ul style="list-style-type: none"> ►Used when connecting communication cables labeled above as "Requires external power supply". ►For use in India. ►5.2V, 1.1A, 5.7W ►Provides US DOE Level VI compliance for power efficiency. ►Replaces PWRS-14000-254R 	
PWRS-14000-254R		Power Supply (India)	<ul style="list-style-type: none"> ►Used when connecting communication cables labeled above as "Requires external power supply". ►110V/60Hz - For use in India ►5VDC,850MA ►Energy Star Compliant ►To be discontinued 4/2018, now use PWR-WUA5V4W0IN - PMB 3047. 	
PWR-WUA5V4W0BR		Power Supply (Brazil)	<ul style="list-style-type: none"> ►Used when connecting communication cables labeled above as "Requires external power supply". ►For use in Brazil. ►5.2V, 1.1A, 5.7W ►Provides US DOE Level VI compliance for power efficiency. ►Replaces PWRS-14000-255R 	
PWRS-14000-255R		Power Supply (Brazil)	<ul style="list-style-type: none"> ►Used when connecting communication cables labeled above as "Requires external power supply". ►110V/60Hz - For use in Brazil ►5VDC,850MA ►Energy Star Compliant ►Discontinued 3/2017, now use PWR-WUA5V4W0BR - PMB 2903. 	
PWR-WUA5V4W0EU		Power Supply (EU and UK)	<ul style="list-style-type: none"> ►Used when connecting communication cables labeled above as "Requires external power supply". ►For use in EU and UK. ►5.2V, 1.1A, 5.7W ►Provides US DOE Level VI compliance for power efficiency. ►Replaces PWRS-14000-256R 	
PWRS-14000-256R		Power Supply (EU and UK)	<ul style="list-style-type: none"> ►Discontinued 2/2017, now use PWR-WUA5V4W0EU - PMB 2903. ►Used when connecting communication cables labeled above as "Requires external power supply". ►110V/60Hz - For use in EU and UK. ►5VDC,850MA ►Energy Star Compliant 	
PWR-WUA5V4W0CN		Power Supply (China)	<ul style="list-style-type: none"> ►Used when connecting communication cables labeled above as "Requires external power supply". ►For use in China. ►5.2V, 1.1A, 5.7W ►Provides US DOE Level VI compliance for power efficiency. ►Replaces PWRS-14000-257R 	
PWRS-14000-257R		Power Supply (China)	<ul style="list-style-type: none"> ►Discontinued 2/2017, now use PWR-WUA5V4W0CN - PMB 2903. ►Used when connecting communication cables labeled above as "Requires external power supply". ►110V/60Hz - For use In China ►5VDC,850MA ►Energy Star Compliant 	

Point of Sale & Barcode Solutions

POSMarket specialises in providing point of sale (POS), barcode and mobile data solutions for smart businesses. We service all industries including retail and hospitality, transport and logistics, government, healthcare, manufacturing and warehousing. Our expert team can provide solutions that can save your business money today.

Shop By Department

Barcode Scanners



- Barcode Readers
- Barcode Software
- Data Collectors



Mobile Computers

- Mobile Computers
- Data Collectors
- Vehicle Computers



Label Printers

- Desktop Printers
- Industrial Printers
- Mobile Printers



Point of Sale

- POS Systems
- Receipt Printers
- Scales



ID Card Printing

- ID Card Printers
- ID Software
- Card Printer Supplies



Media & Accessories

- Labels
- Ribbons
- Paper Rolls



Software

- Inventory Software
- Asset Tracking
- Barcode Software



Wireless

- Wifi Systems
- Pager Systems
- Site Surveys



RFID

- RFID Printers
- RFID Readers
- RFID Tags

Shop By Industry



Education/Libraries

Timesaving printing solutions to meet all your staff, student & asset identification needs. Need **Labels and Printers**? From **scanners to receipt printers**, whatever your needs, we are here to help.



Retail Stores

Keep customers coming back and keep stock from running out. Check out our range of **scanners, cash drawers, receipt printers and cash registers**.



Cafes/Restaurants

We can help you to decrease lines for your customers, complete tableside transactions, or reward patrons with **loyalty cards**. From cash registers to touch screen systems we can assist.



Warehouse Management

Our superior **warehousing solutions** will allow your business to provide comprehensive, up-to-date information and streamline your processes to improve efficiency.



Construction

Keep track of your inventory and stop inventory shrinkage. Our inventory tracking software allows you to easily keep control of your stock.



Hospitals/Healthcare

Improve patient care with the accurate identification of patients, medications, samples, treatments, lab results & records. We have a huge range of **label printers, consumables & scanners**.



Transport & Logistics

Track materials through your facility or through your supply chain using **labels, barcode scanners and portable data terminals**. Optimize your production and information flows.



Government

We can supply you with all your needs, from **receipt printers and cash drawers, to barcode scanners and label printers**. Less paperwork, data entry and time spent looking up records.



Mining

Rugged identification solutions help manage assets from the ground up. From **portable data terminals and scanners to software and printers**, we can find a solution to meet your needs.

Shop By Brand

