

Innovating your Audio/Video experience

You are here: Home > Products > EFW 8345



Accessories



EFA 8820 Tilt module L/XL

Add another dimension to your viewing position with the Vogel's tilt module. It tilts up 15 degrees and down 15 degrees so you have the best view while lying on the couch or floor.



EFA 8835 Column system 64cm + AV support

No more messy cables! Vogel's cable column system hides all unsightly cables. This ultra thin (2 cm) space saving cable column comes in lengths of 64cm/52.2" (EFA 8835) and 94cm/37" (EFA 8840) and holds up to 10 cables. One set of AV multi support is included.



EFA 8840 Column system 94cm + AV support

No more messy cables! Vogel's cable column system hides all unsightly cables. This ultra thin (2 cm) space saving cable column comes in lengths of 64cm/25.2" (EFA 6835) and 94cm/37" (EFA 6840) and holds up to 10 cables. One set of AV multi support is included.5



EFA 8895 Uni stud adapter L

The EFA 8895 is a studadapter for 16" studs; suitable for EFW 8345.

related products



EFW 8305 Wall mount Superflat L

Vogel's SuperFlat™ model EFW 8305 is suitable for flat TV's from 32 up to 50 inch. It leaves just 2 centimetres of space between the TV and the wall, just enough for ventilation and cables. The smart AutoLock® holds your screen securely in place.



EFW 8325 Wall mount Motion L

Vogel's Motion mount EFW 8325 is suitable for flat TV's from 32 up to 50 inch. It has a maximum turning range of 90 degrees (45 degrees both ways) and features the patented Cable Inlay System (CIS®) to conceals all of your cables.

EFW 8345 Wall mount Motion+ L

Article number: EFW 8345

If you want maximum flexibility and viewing pleasure, choose the Vogel's 8000 Motion+ EFW8345. It is suitable for flat TV's from 32 up to 50 inch and it has a maximum turning range of 150 degrees (75 degrees side-to-side). The 90 degree option even lets you turn your TV perpendicular to the wall.

This mount offers convenience and safety. The Smart Movement Mechanism (SMM®) lets you move even the biggest flat screen with the touch of a fingertip, while the Screen Protection System (SPS®) protects your flat screen from bumping into the wall when turning. And the Cable Inlay System (CIS®) conceals all of your cables out of sight. Installing is very easy. There's even a level in the mount to make sure it hangs perfectly straight. The smart AutoLock® holds your screen securely in place so you don't have to worry about the safety of your valuable TV. Create your own entertainment centre and combine this wall support with the 8000-series Column system and Audio/DVD multi support.

Specifications

Main Color: Black-Dolphingrey Supplemental colors: Black-Dolphingrey Turn: 150 ° Min. size: 32 " Max. size: 50 ° Minimum weight: 0 kg Max. weight: 45 kg Number of pivot points: 2 Amount of appliances: 1 Min. distance to the wall: 103 mm CIS®: Aanwezig AdvanCIS™: - SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): Aanwezig TÜV Certificate number: 1 Interface width: 830 mm Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x45	Specifications	
Turn: 150 ° Min. size: 32 " Max. size: 50 " Minimum weight: 0 kg Max. weight: 45 kg Number of pivot points: 2 Amount of appliances: 1 Min. distance to the wall: 103 mm CIS®: Aanwezig AdvancIS™: - SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): TÜV Certificate number: 1 Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System okale in the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall a full potential cables out of sight. Guarantee: Lifelong Wheels: Remote Controlled: -	Main Color:	Black-Dolphingrey
Min. size: 32 " Max. size: 50 " Minimum weight: 0 kg Max. weight: 45 kg Number of pivot points: 2 Amount of appliances: 1 Min. distance to the wall: 103 mm CIS®: Annwezig AdvanCIS™: - SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): 4anwezig TÜV Certificate number: 1 Interface width: 830 mm Interface height: 475 mm USP's: 4utolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. USP's: Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. We screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Guarantee: Lifelong Wheels: - Remote Controlled: -	Supplemental colors:	Black-Dolphingrey
Max. size: 50 " Minimum weight: 0 kg Max. weight: 45 kg Number of pivot points: 2 Amount of appliances: 1 Min. distance to the wall: 103 mm CIS®: Aanwezig AdvanCIS™: - SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): Aanwezig TÜV Certificate number: Interface width: Interface width: 830 mm Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Screen Protection System (SPS®) wich protects both screen and wall. Guarantee: Lifelong Wheels: - Remote Controlled: -	Turn:	150 °
Minimum weight: 0 kg Max. weight: 45 kg Number of pivot points: 2 Amount of appliances: 1 Min. distance to the wall: 103 mm CIS®: Aanwezig AdvanCIS™: - SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): 830 mm TÜV Certificate number: 830 mm Interface width: 830 mm Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. West on - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Screen Protection System (SPS®) wich protects both screen and wall. Guarantee: Lifelong Wheels: - Remote Controlled: -	Min. size:	32 "
Max. weight: 45 kg Number of pivot points: 2 Amount of appliances: 1 Min. distance to the wall: 103 mm CIS®: Aanwezig AdvanCIS™: - SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): Aanwezig TÜV Certificate number: 830 mm Interface width: 830 mm Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Screen Protection System (SPS®) wich protects both screen and wall. Guarantee: Lifelong Wheels: - Remote Controlled: -	Max. size:	50 "
Number of pivot points: 2 Amount of appliances: 1 Min. distance to the wall: 103 mm CIS®: Aanwezig AdvanCIS™: - SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): Aanwezig TÜV Certificate number: Interface width: Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Guarantee: Lifelong Wheels: - Remote Controlled: -	Minimum weight:	0 kg
Amount of appliances: 1 Min. distance to the wall: 103 mm CIS®: Aanwezig AdvanCIS™: - SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): Aanwezig TÜV Certificate number: Interface width: Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Screen Protection System (SPS®) wich protects both screen and wall. Guarantee: Lifelong Wheels: - Remote Controlled: -	Max. weight:	45 kg
Min. distance to the wall: CIS®: Aanwezig AdvanCIS™: SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): TÜV Certificate number: Interface width: 1830 mm Interface height: USP's: Autolock ® - secures your flat screen with a single click Integrated spirt level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Wheels: Remote Controlled:	Number of pivot points:	2
CIS®: AdvanCIS™: SPS™ (Screen Protection System): Annwezig SMM™ (Smart Movement Mechanism): TÜV Certificate number: Interface width: Interface height: USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Wheels: Remote Controlled:	Amount of appliances:	1
AdvanCIS™: SPS™ (Screen Protection System): Aanwezig Aanwezig TÜV Certificate number: Interface width: Interface height: USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Wheels: Remote Controlled:	Min. distance to the wall:	103 mm
SPS™ (Screen Protection System): Aanwezig SMM™ (Smart Movement Mechanism): TÜV Certificate number: Interface width: 830 mm Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: - Remote Controlled: -	CIS®:	Aanwezig
SMM™ (Smart Movement Mechanism): Aanwezig TÜV Certificate number: Interface width: Interface width: 830 mm Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: - Remote Controlled: -	AdvanCIS™:	-
Mechanism):STÜV Certificate number:830 mmInterface width:830 mmUSP's:Autolock ® - secures your flat screen with a single clickUSP's:Autolock ® - secures your flat screen with a single clickUSP's:Autolock ® - secures your flat screen with a single clickUSP's:Autolock ® - secures your flat screen with a single clickUSP's:Autolock ® - secures your flat screen with a single clickUSP's:Autolock ® - secures your flat screen with a single clickWESA mounting holes: 75x75mm up to 800x450mm.Autolock ® - 150° turning range.Perpendicular to the wall - full 90° corner option.Screen Protection System (SPS®) wich protects both screen and wall.Screen Protection System (SPS®) wich protects both screen and wall.Smart Movement Mechanism (SMM®) - fingertip movement.Cable Inlay System (CIS®) - all cables out of sight.Guarantee:Wheels:LifelongWheels:-Remote Controlled:-	SPS™ (Screen Protection System):	Aanwezig
Interface width: Interface height: 475 mm USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: Remote Controlled:	4	Aanwezig
Interface height: USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels:	TÜV Certificate number:	
USP's: Autolock ® - secures your flat screen with a single click Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels:	Interface width:	830 mm
Integrated spirit level - straight mounting guaranteed. VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: - Remote Controlled: -	Interface height:	475 mm
VESA mounting holes: 75x75mm up to 800x450mm. Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: - Remote Controlled: -	USP's:	Autolock ® - secures your flat screen with a single click
Motion+ - 150° turning range. Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: - Remote Controlled:		Integrated spirit level - straight mounting guaranteed.
Perpendicular to the wall - full 90° corner option. Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: - Remote Controlled: -		VESA mounting holes: 75x75mm up to 800x450mm.
Screen Protection System (SPS®) wich protects both screen and wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: - Remote Controlled: -		Motion+ - 150° turning range.
wall. Smart Movement Mechanism (SMM®) - fingertip movement. Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: - Remote Controlled: -		Perpendicular to the wall - full 90° corner option.
Cable Inlay System (CIS®) - all cables out of sight. Guarantee: Lifelong Wheels: - Remote Controlled: -		
Guarantee: Lifelong Wheels: - Remote Controlled: -		Smart Movement Mechanism (SMM®) - fingertip movement.
Wheels: - Remote Controlled: -		Cable Inlay System (CIS®) - all cables out of sight.
Remote Controlled: -	Guarantee:	Lifelong
	Wheels:	-
Adjustable depth: -	Remote Controlled:	-
	Adjustable depth:	-

LCD wall mount EFW 8345 Motion+ 8000 series