### MC9500 Accessories

### **Cradles**



### Single Bay USB Charging Cradle

CRD9500-1000UR

Cradle enables USB communication between the MC9500 and a host PC. Requires Power Supply KT-14000-148R and country specific three wire grounded AC power line cord. For communication to a host computer purchase Micro USB sync cable (25-124330-01R). Spare battery charger (SAC9500-1000R) can be purchased to enable charging of a spare battery.

Size (WxDxH): 120 mm x 154.5 mm x 189 mm (4.72 in. x 6.08 in. x 7.44 in.)

Weight: 430 g (15.17 oz)



### Single Bay USB Charging Cradle Kit

CRD9500-100UR

Includes Single Bay USB Charging Cradle (CRD9500-1000UR), Power Supply (KT-14000-148R), and US three wire grounded AC power line cord (23844-00-00R). For communication to a host computer purchase Micro USB sync cable (25-124330-01R).



### Single Bay USB Charging Cradle Kit

CRD9500-101UR

Includes Single Bay USB Charging Cradle (CRD9500-1000UR) and Power Supply (KT-14000-148R). Requires purchase of country specific three wire grounded AC power line cord. For communication to a host computer purchase Micro USB sync cable (25-124330-01R).



### Single Bay USB Charging Cradle and Battery Charger Kit

CRD9500-102UR

Includes Single Bay USB Charging Cradle (CRD9500-1000UR), Single Slot Battery Charger (SAC9500-1000R), Power Supply (KT-14000-148R), DC "Y" cable (25-122026-01R) and US three wire grounded AC power line cord (23844-00-00R). For communication to a host computer purchase Micro USB sync cable (25-124330-01R).



### Single Bay USB Charging Cradle and Battery Charger Kit

CRD9500-103UR

Includes Single Bay USB Charging Cradle (CRD9500-1000UR), Single Slot Battery Charger (SAC9500-1000R), Power Supply (KT-14000-148R) and DC "Y" cable (25-122026-01R). Requires purchase of country specific three wire grounded AC power line cord. For communication to a host computer purchase Micro USB sync cable (25-124330-01R).



### Four Bay Charge Only Cradle

CRD9500-4000CR

Charges up to four terminals simultaneously. Requires the purchase of either a Desk Mounting Bracket (KT-11 6363-01R) or Wall Mounting Bracket (KT-11 6362-01R), Power Supply (50-14000-241R), DC line cord (50-16002-029R) and country specific three wire grounded AC power line cord. Optional Guide Cup Kit (KT-122014-01R) can be purchased separately.

Specifications: Height: 113 mm (4.45 in.) / Width: 457 mm (17.99 in.) / Depth: 56 mm (2.2 in.) / Weight: 985 g (34.74 oz)



### **Desk Mount Ready Four Bay Charge Only Cradle Kit (US)**

CRD9500-400CR

Includes Four Bay Charge Only Cradle (CRD9500-4000CR), Desk Mounting Bracket (KT-116363-01R), Optional Guide Cup Kit (KT-122014-01R), Power Supply (50-14000-241R), DC line cord (50-16002-029R), and US three wire grounded AC power line cord (23844-00-00R).

### **Cradles (Continued)**



### **Desk Mount Ready Four Bay Charge Only Cradle Kit (International)**

CRD9500-401CR

Includes Four Bay Charge Only Cradle (CRD9500-4000CR), Desk Mounting Bracket (KT-116363-01R), Optional Guide Cup Kit (KT-122014-01R), Power Supply (50-14000-241R), and DC line cord (50-16002-029R). Requires purchase of country specific three wire grounded AC power line cord.



### Wall Mount Ready MC9500-K Four Bay Charge Only Cradle Kit (US)

CRD9500-420CR

Includes Wall Mounting Bracket (KT-116362-01R), Four Bay Charge Only Cradle (CRD9500-4000CR), Optional Guide Cup Kit (KT-122014-01R), Power Supply (50-14000-241R), DC Line Cord (50-16002-029R), and US AC Line Cord (23844-00-00R).



### Wall Mount Ready MC9500-K Four Bay Charge Only Cradle Kit (International)

CRD9500-421CR

Includes Wall Mounting Bracket (KT-116362-01R), Four Bay Charge Only Cradle (CRD9500-4000CR), Optional Guide Cup Kit (KT-122014-01R), Power Supply (50-14000-241R) and DC Line Cord (50-16002-029R). Requires purchase of country specific three wire grounded AC power line cord.



### Four Bay Ethernet/Charge Cradle

CRD9500-4000ER

Simultaneously charges and provides Ethernet connectivity to up to four terminals. Requires the purchase of either a Desk Mounting

Bracket (KT-11 6363-01R) or Wall Mounting Bracket (KT-116362-01R), Power Supply (50-14000-241R), DC line cord (50-16002-029R) and country specific three wire grounded AC power line cord. Optional Guide Cup Kit (KT-122014-01R) can be purchased separately.

Specifications: Height: 113 mm (4.45 in.) / Width: 457 mm (17.99 in.) / Depth: 56 mm (2.2 in.) / Weight: 1.02 kg (35.98 oz)



### Desk Mount Ready Four Bay Ethernet/Charge Cradle Kit (US)

CRD9500-400ER

Includes Four Bay Ethernet/Charge Cradle (CRD9500-4000ER), Desk Mounting Bracket (KT-116-363-01R), Optional Guide Cup Kit (KT-122014-01R), Power Supply (50-14000-241R), DC line cord (50-16002-029R), and US three wire grounded AC power line cord (23844-00-00R).



### **Desk Mount Ready Four Bay Ethernet/Charge Cradle Kit (International)**

CRD9500-401ER

Includes Four Bay Ethernet/Charge Only Cradle (CRD9500-4000ER), Desk Mounting Bracket (KT-116-363-01R), Optional Guide Cup Kit (KT-122014-01R), Power Supply (50-14000-241R), and DC line cord (50-16002-029R). Requires purchase of country specific three wire grounded AC power line cord.



### Wall Mount Ready MC9500-K Four Bay Ethernet/Charge Cradle Kit (US)

CRD9500-420ER

Includes Wall Mounting Bracket (KT-116362-01R), Four Bay Ethernet/Charge Cradle (CRD9500-4000ER), Optional Guide Cup Kit (KT-122014-01R), Power Supply (50-14000-241R), DC Line Cord (50-16002-029R), and US AC Line Cord (23844-00-00R).

### **Cradles (Continued)**



### Wall Mount Ready MC9500-K Four Bay Ethernet/Charge Cradle Kit (International)

CRD9500-421ER

Includes Wall Mounting Bracket (KT-11 6362-01R), Four Bay Ethernet/Charge Cradle (CRD9500-4000ER), Optional Guide Cup Kit (KT-122014-01R), Power Supply (50-14000-241R) and DC Line Cord (50-16002-029R). Requires purchase of country specific three wire grounded AC power line cord.



### **Vehicle Charging Cradle**

VCD9500-1000R

Enables in-vehicle charging. Bolts into dashboard and connects to vehicle fuse box via included cable. Specifications: Height: 222 .5 mm (8.76 in.) / Width: 154 mm (6.06 in.) / Depth: 97.5 mm (3.84 in.) / Weight: 805 g (28.4 oz) / Power: 12 /24V

### Charging



### **Vehicle Spare Battery Charger**

VBC9500-1000R

Charges the MC9500-K spare battery via the Vehicle Charging Cradle (VCD9500-1000R) or the Auto Charge Cable (VCA9500-01R). Charging the spare battery via the Vehicle Charging Cradle requires the purchase of a Vehicle Mounting Bracket (KT-122012-01R) and Jumper Cable (25-122028-01R), which connects the Vehicle Spare Battery Charger to the Vehicle Cradle.

Specifications: Height: 147 mm (5.79 in.) / Width: 67.5 mm (2.66 in.) / Depth: 47.5 mm (1.87 in.) / Weight: 130 g (4.59 oz) / Power: 5.4V



### **Single Slot Spare Battery Charger**

SAC9500-1000CR

Charges one MC9500-K spare battery. Requires Power Supply KT-14000-148R and country specific three wire grounded AC power line cord. Purchase DC 'Y' cable (25-122026-01R) to charge the Single Slot Spare Battery Charger and Single Bay Cradle or Two Single Slot Spare Battery Chargers from the same power supply. 100-240 VAC, 12VDC, 3.33A.

Specifications: Height: 111.5 mm (4.39 in.) / Width: 77 mm (3.03 in.) / Depth: 99.5 mm (3.92 in.) / Weight: 105 g (3.70 oz)



### **Single Slot Spare Battery Charger Kit**

SAC9500-100CR

Includes Single Slot Spare Battery Charger (SAC9500-1000CR), Power Supply (KT-14000-148R) and US three wire grounded AC power line cord (23844-00-00R).



### Single Slot Spare Battery Charger Kit

SAC9500-101CR

Kit Includes: Single Slot Spare Battery Charger (SAC9500-1000CR) and Power Supply (KT-14000-148R). Requires purchase of country specific three wire grounded AC power line cord.

BTRY-MC95IABA0-10

T4800 mAh battery (10-pack).

### **Charging (Continued) Four Slot Spare Battery Charger** SAC9500-4000CR Charges up to four MC9500-K spare batteries. When charging only one Four Slot Battery charger purchase Power Supply (KT-14000-148R) and three wire grounded AC line cord. For Charging 2 to 4 Four Slot Battery Chargers from the same power supply purchase Power Supply (50-14000-241R), 4-way DC Line Cord (25-85992-01R) and 3 wire grounded AC line cord. For desk mounting one Four Slot Battery Charger, purchase Desk Mounting Bracket (KT-116364-01R). For wall mounting two Four Slot Battery Chargers, purchase Wall Mounting Bracket (KT-116362-01R). Specifications: Height: 113 mm (4.45 in.) / Width: 220 mm (8.66 in.) / Depth: 75 mm (2.95 in.) / Weight: 386 g (13.6 oz) **Desk Mount Ready Four Slot Spare Battery Charger Kit** SAC9500-400CR Includes Four Slot Spare Battery Charger (SAC9500-4000CR), Desk Mounting Bracket (KT-116364-01R), Power Supply (KT-14000-148R) and US three wire grounded AC power line cord (23844-00-00R). **Desk Mount Ready Four Slot Spare Battery Charger Kit** SAC9500-401CR Includes: Four Slot Spare Battery Charger (SAC9500-4000CR), Desk Mounting Bracket (KT-116364-01R), and Power Supply (KT-14000-148R). Requires purchase of country specific three wire grounded AC power line cord. Wall Mount Ready MC9500-K Four Slot Spare Battery Charger Kit SAC9500-420CR Includes 2 Wall Mounting Brackets (KT-116362-01R), 4 Four Slot Battery Chargers (SAC9500-4000CR), Power Supply (50-14000-241R), 4-way DC Line Cord (25-85992-01R), and US AC Line Cord (23844-00-00R). Wall Mount Ready MC9500-K Four Slot Spare Battery Charger Kit SAC9500-421CR Includes two Wall Mounting Brackets (KT-116362-01R), four Four Slot Battery Chargers (SAC9500-4000CR), Power Supply (50-14000-241R) and 4-way DC Line Cord (25-85992-01R). Requires purchase of country specific three wire grounded AC power line cord. **Spare Battery** BTRY-MC95IABA0 4800 mAh **Spare Battery**

### **Charging (Continued)**



### **Power Supply**

KT-14000-148R

100-140 VAC, 12 VDC, 3.33A



### **Power Supply**

50-14000-241R

100-140 VAC, 12 VDC, 9A

### Cables



### **DEX Cable**

25-116366-01R

Enables the transmission of data between the MC9500-K and a customer's inventory system at the time of delivery.



### **Auto Charge Cable (Cigarette Lighter Adapter)**

VCA9500-01R

Charges the MC9500-K mobile computer or the Vehicle Spare Battery Charger (VBC9500-1000R). Includes Adapter Module, which is required for charging the MC9500-K.



### Micro USB Sync Cable

25-124330-01R

Provides USB communication with a host computer through the MC9500-K Single Bay Cradle.



### DC "Y" Cable

25-122026-01R

Connects the Single Slot Spare Battery Charger and the Single Bay USB Cradle or connects two Single Slot Spare Battery Chargers to one Power Supply (KT-14000-148R). Specifications: Length: 292 mm (11.5 in.)

No Photo Available

### 4-Way DC Cable

25-85992-01R

Cable connects up to four Four Slot Battery Chargers to one Power Supply (50-14000-241R).

No Photo Available

### Jumper Cable: Vehicle Cradle to Vehicle Spare Battery Charger Cable

25-122028-01R

Connects the Vehicle Spare Battery Charger (VBC9500-1000R) to the Vehicle Cradle (VCD9500-1000R).

### **Snap-ons**



### Magnetic Stripe Reader

MSR9500-100R

Captures data from magnetic stripe cards.

Specifications: Height: 77 mm (3.03 in.) / Width: 69 mm (2.72 in.) / Depth: 28.5 mm (1.12 in.) /

Weight: 75 g (2.65 oz)

Modem Dongle — MDM9000-100R

Provides modem connectivity to the MC9500-K. Requires modem adapter cable (25-116367-01R)

### **Soft Goods**



### **Soft Case Holster**

SG-MC9521110-01R

Allows for mounting of the MC9500-K on a users belt. MC9500-K orientation when holstered is scan exit window down which allows for easy grip of the MC9500-K.

### Miscellaneous



### **Spare Screen Protector**

KT-122010-01R

Protects the screen against scratches.



#### **Stylus**

KT-122016-03R

Spring loaded stylus for the MC9500-K (3 Pack).



### **Stylus**

KT-122016-50R

Spring loaded stylus for the MC9500-K (50 Pack).



### **Hand Strap**

SG-MC9523043-01R

Spare kit of hand straps (5 Pack)



### **Universal Wall Mounting Bracket**

KT-116362-01R

Enables mounting of two Four Slot Battery Chargers (SAC9500-4000CR) on a wall. Specifications: Height: 123 mm (4.84 in.) / Width: 458 mm (18.03 in.) / Depth: 72 mm (2.83 in.) / Weight: 1.76 kg (62.08 oz)



### Four Slot Spare Battery Charger Desk Mounting Bracket

KT-116364-01R

Enables mounting of one Four Slot Battery Charger (SAC9500-4000CR) on a flat surface, such as a desk top.

Specifications: Height: 2.3 mm (0.091 in.) / Width: 209 mm (8.23 in.) / Depth: 115 mm (4.53 in.) / Weight: 138.80 g (4.46 oz)

Miscellaneous (Continued)	
	Desk Mounting Bracket KT-116363-01R Enables mounting of the Four Bay Cradle (CRD9500-4000CR, CRD9500-4000ER) on a flat surface, such as a desk top. Specifications: Height: 190 mm (7.48 in.) / Width: 456 mm (17.95 in.) / Depth: 183 mm (7.20 in.) / Weight: 2.5 kg (88.18 oz)
	Cradle Guide (4 Pack) KT-122014-01R Helps guide the MC9500-K into the cradle.
No Photo Available	Vehicle Mounting Bracket KT-122012-01R Enables mounting of the Vehicle Cradle (VCD95000-1000R) and Vehicle Spare Battery Charger (VBC95000-1000R) side-by-side in a vehicle. Requires Jumper cable (25-122028-01R) to charge battery charger from Vehicle Cradle.
No Photo Available	Hard Case Rigid Holster SG-MC9511110-01R Allows for mounting of the MC9500-K on a users belt. MC9500-K orientation when holstered is scan exit window up which allows the MC9500-K to be holstered with an MSR snap on or cable attachment.