

LX1500

Training rooms
Staging applications
Large auditoriums
Medical training theaters
Government institutions
Executive briefing rooms
Conference centers
Houses of worship



Highest brightness, lowest operational cost

The Christie LX1500 is the world's brightest projector in its class delivering a stunning 15,000 ANSI lumens brightness from an advanced 4-lamp, 3LCD optical engine. Designed for performance applications including houses of worship, staged events and medium sized auditoriums, the LX1500 combines native XGA resolution and 2000:1 contrast ratio with the latest 10-bit image processing for flawless image reproduction.

The LX1500 is compatible with digital and analog signal formats from XGA data to 1080i video, with a range of optional input modules including digital blending/warping, SDI and HD-SDI to further extend the signal compatibility. The available lens

suite includes 11 lenses with throw ratios from 0.8:1 through 9.0:1 combined with horizontal and vertical lens shift for a broad range of installation options that enable you to position the projector almost anywhere. Staging partners can use lenses from the popular LX100 and LX120 models to maximize their assets.

The robust design includes long-life optical components, an innovative cooling system and a new air filtration system. The Christie LX1500 produces exceptional image performance with minimal maintenance which means increased reliability and worry-free presentations.

CHRISTIE®

Technical Specifications

LX1500 (103-013100-01)

Image	<ul style="list-style-type: none"> • 15,000 ANSI lumens • Contrast ratio: 2000:1
Display technology & resolution	<ul style="list-style-type: none"> • 3 X 1.8" LCD • Native XGA 1024 x 768 resolution
Input signal compatibility	<ul style="list-style-type: none"> • VGA through UXGA • Accepts and displays all currently known DTV/HDTV formats (from 480i through 1080i plus SDI and HD-SDI using optional input module) • 10-bit image processing
Scan rates	<ul style="list-style-type: none"> • Horizontal: 15–120 kHz, Vertical: 50–120 Hz
Pixel clock	<ul style="list-style-type: none"> • 230 MHz
Inputs, control & networking	<ul style="list-style-type: none"> • Input 1: HD15 and DVI-I • Input 2: RGBHV, Y,Pb,Pr, Y/C, s-video • Input 3 and 4: open slots • DB9 RS-232 in and out • USB • Wired remote jack
Dimensions	<ul style="list-style-type: none"> • Weight: 80.3 lb (36.5 kg) • Size (L x W x H): 31.9 x 22.8 x 9.9"
Lamp	<ul style="list-style-type: none"> • 330W NSH • Lamp life: 2000 hrs (max brightness) • User replaceable
Optical system	<ul style="list-style-type: none"> • Fast Lens Change (FLC™) mount • Power adjustable zoom, focus • Optional fixed lenses: 0.8:1, 1.2:1, 7.0:1 • Optional zoom lenses: 1.1–1.5:1, 1.5–2.0:1, 1.3–1.8:1, 2.0–2.6:1, 2.6–3.5:1, 3.5–4.6:1, 4.6–6.0:1, 6.3–9.0:1 • Up/down, left/right shift • Image elevation up to 5.7" • Horizontal and vertical offset up to 120% vertical and 78% horizontal (depending on lens)
Power requirements	<ul style="list-style-type: none"> • 220V AV, 9.7A • Power consumption: 1800W max
Standard accessories	<ul style="list-style-type: none"> • Line cords for US and EU operation • Wireless remote unit with laser pointer • User manual including start-up guide and CD-ROM • Computer cable • Integrated carrying handles
Optional accessories	<ul style="list-style-type: none"> • Input modules: HD15, DVI-I, 5-BNC, dual SDI/HD-SDI, Warping/Blending • Shipping case • Ceiling mount
Operating environment	<ul style="list-style-type: none"> • Temperature: 40 to 95° F (5 to 35° C) • Humidity: 20–80% (non-condensing) • Altitude: 0–8558ft (0–2700m) • Audible noise: 51 dBA
Regulatory approvals	<ul style="list-style-type: none"> • FCC Class A • EN5502 Class A, CE • RoHS compliant • CSA 22.2 No 950, UL 1950 cUL • IEC950 (EN60950)
Limited warranty	<ul style="list-style-type: none"> • 3 years parts and labor (excluding lamp) • Lamp: 120 days or 500 hrs, whichever comes first



▲ The LX1500 offers reliability, dependability, flexibility and is compatible with a full array of video and data inputs.



▲ With a range of 11 high-performance fixed and zoom lenses to choose from, the LX1500 is a choice projector.



▲ Power at your finger tips; Christie's projectors are made with you in mind.

Corporate offices

USA – Cypress
ph: 714-236-8610
Canada – Kitchener
ph: 519-744-8005

Worldwide offices

United Kingdom
ph: +44 118 977 8000
Germany
ph: +49 2161 664540
France
ph: +33 (0) 1 41 21 44 04

Hungary/Eastern Europe
ph: +36 (0) 1 47 48 100
South Africa
ph: +27 (0) 317 671 347
Singapore
ph: +65 6877 8737

Shanghai
ph: +86 21 6278 7708
Beijing
ph: +86 10 6561 0240

Korea
ph: +82 2 702 1601
Japan
ph: +81 3 3599 7481

For the most current specification information, please visit www.christiedigital.com

Copyright 2007 Christie Digital Systems, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Canadian manufacturing facility is ISO 9001 and 14001 certified. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 2239 Sept 07



CHRISTIE®

ISO 9001



ISO 14001

