



PREPACKAGED HOME STANDBY GENERATORS

AIR COOLED 7-16 kW



- Automatic Transfer Switch
- Outdoor connection box
- Pre-wired conduit
- Flexible fuel line
- Mounting pad
- Installation guide



MODEL NUMBER	ASPBS1CCA007	ASPBS1CCA010	ASPBS1CCA013	ASPBS1CCA016	ASPBA1CCA016
MODEL NAME	7 kW	10 kW	13 kW	16 kW	16 kW
RATED POWER LPG/NG kW	7/6	10/9	13/13	16/15	16/15
FREQUENCY	60Hz	60Hz	60Hz	60Hz	60Hz
HOUSEHOLD CIRCUITS	8	10	12	16	16
VOLTAGE	120/240V Single	120/240V Single	120/240V Single	120/240V Single	120/240V Single
AMPS @ 120/240V LPG	58.3/29.2	83.3/41.7	108.3/54.1	133.3/66.6	133.3/66.6
AMPS @ 120/240V NG	50.0/25.0	75.0/37.5	108.3/54.1	125/62.5	125/62.5
ENGINE/ALTERNATOR RPM	3600/3600	3600/3600	3600/3600	3600/3600	3600/3600
ENGINE	OHVI® Single Cylinder	OHVI® V-Twin	OHVI® V-Twin	OHVI® V-Twin	OHVI® V-Twin
DISPLACEMENT	410cc	530cc	992cc	992cc	992cc
FUEL CONSUMPTION @ rated power					
LPG cu.ft./hr (gal/hr)	54 (1.47)	70 (1.93)	80 (2.18)	92 (2.51)	92 (2.51)
NG cu.ft./hr	119	156	220	245	245
Ultra Quiet Mode Feature	NO	NO	NO	YES	YES
Enclosure	Steel	Steel	Steel	Steel	Aluminum
DIMENSION (L"x W"x H")	48 x 24 x 28.25	48 x 24 x 28.25	48 x 24 x 28.25	48 x 24 x 28.25	48 x 24 x 28.25
UNIT WEIGHT (LBS.)	336	375	425	445	430
UL 2200 LISTED	YES	YES	YES	YES	YES
AUTOMATIC TRANSFER SWITCH	100 Amp (NEMA 1)	100 Amp (NEMA 1)	100 Amp (NEMA 1)	100 Amp (NEMA 1)	100 Amp (NEMA 1)

*Nonprepackaged models ASPBX1CCA016 and ASPBY1CC016 include: generator, flexible fuel line & composite mounting pad.

LIQUID COOLED 25 to 45 kW



25 kW model



35 kW and 45 kW models



MODEL NUMBER	ASPDS1CCL025	ASPDA1CCL025	ASPDS1CCL035	ASPDA1CCL035	ASPDS1CCL045	ASPDA1CCL045
MODEL NAME	25 kW	25 kW	35 kW	35 kW	45 kW	45 kW
RATED POWER LPG/NG kW	25/25	25/25	35/35	35/35	45/43	45/43
FREQUENCY	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz
VOLTAGE	120/240V Single	120/240V Single	120/240V Single	120/240V Single	120/240V Single	120/240V Single
AMPS @ 120/240V LPG	208.3/104.2	208.3/104.2	291.6/145.8	291.6/145.8	375/187.5	375/187.5
AMPS @ 120/240V NG	208.3/104.2	208.3/104.2	291.6/145.8	291.6/145.8	358.3/179.2	358.3/179.2
ENGINE/ALTERNATOR RPM	3600/3600	3600/3600	3600/3600	3600/3600	3600/3600	3600/3600
ENGINE	In-Line 4-cylinder	In-Line 4-cylinder	In-Line 4-cylinder	In-Line 4-cylinder	In-Line 4-cylinder	In-Line 4-cylinder
DISPLACEMENT	1.6L	1.6L	2.4L	2.4L	2.4L	2.4L
FUEL CONSUMPTION @ rated power						
LPG cu.ft./hr (gal/hr)	175 (4.81)	175 (4.81)	222.3 (6.1)	222.3 (6.1)	286 (7.86)	286 (7.86)
NG cu.ft./hr	437	437	560	560	720	720
Ultra Quiet Mode Feature	YES	YES	YES	YES	YES	YES
DIMENSION (L"x W"x H")	71 x 29.5 x 36	71 x 29.5 x 36	77 x 33.5 x 45	77 x 33.5 x 45	77 x 33.5 x 45	77 x 33.5 x 45
ENCLOSURE	Steel	Aluminum	Steel	Aluminum	Steel	Aluminum
GENERATOR WEIGHT (lbs.)	794	704	1393	1276	1414	1297
UL 2200 LISTED	YES	YES	YES	YES	YES	YES
AUTOMATIC TRANSFER SWITCH	200 Amp*	200 Amp*	200 Amp*	200 Amp*	200 Amp*	200 Amp*

*With service disconnect - Rated for use as service entrance equipment. Not UL listed in Canada.