

NEC M260X

Order Code: 60002962

NEC M260X Professional Desktop Projector

Get great performance while saving the environment. Advanced Eco features help to substantially lower your operating cost without compromising on quality and flexibility. The M260X is particularly suited for classrooms and small to medium sized meeting rooms.



DELIVERING GENUINE BENEFITS

Get Great Performance - while not compromising on quality and ease of use.

Intuitive Use - of latest Eco and projection technology due to user-centric design.

Large Flexibility in positioning the projector and minimized cost for replacements.

Save the Environment - with latest Eco technology by minimizing your power consumption and consumables replacements.



OUTSTANDING PERFORMANCE

- **Maximum Flexibility** with large 1.7x optical zoom
- **Minimized Cost of Ownership** due to long lamp life and filter cleaning intervals
- **Innovative ECO Functions** to reduce power consumption
- **Great Connectivity** due to numerous analog and digital connection terminals as well as network capability
- **Intuitive and Easy Operation** with user centric design and lens cover



SPECIAL CHARACTERISTICS

Auto Power ON/OFF, Automatic and manual Keystone Correction (V= +/-30°), Carbon Savings Meter, Colour Management, Content Transmission via Network, Control and administration via LAN, Crestron RoomView, DICOM Simulation, Direct Power-Off Function, High Altitude Mode, Kensington security slot, Keypad Lock, Lens Cover, Magnify, Off-Timer, Optional User Logo, OSD with 27 languages, Password Security System, Quick On/Off, RS-232 Control, Security Bar, USB Display, USB Viewer for JPEG, Virtual Remote for direct PC control, Wall Colour Correction



ECO Innovation Auto ECO Mode; Green one touch ECO and AV mute button; 75% AV mute function

Energy Efficiency ECO scheduler; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0,4W stand-by; Software scheduling

Ecological Materials 100% recyclable packaging; Downloadable manuals; ECO packaging

Ecological Standards RoHs compliant; TCO certified; ErP compliant

Technical Specification NEC M260X

IMAGE	
Display	3 x 1.6 cm (0.63") p-Si LCD Panel
Native Resolution	1024 x 768 (XGA)
Brightness ¹	2600 ANSI Lumen (approx. 80% in Eco Mode)
Contrast Ratio ¹	2000:1
Lamp	180 W AC (145 W AC Eco Mode)
Lamp Life [hrs]	5000 (6000 Eco Mode)
Lens	F= 1.7-2.2, f= 17.5-29 mm
Projection Factor	1.3 - 2.2 : 1
Projection Distance [m]	0.6 - 13.8
Screen Size (diagonal) [cm]	Minimum: 63.5 / 25"; Maximum: 762 / 300"
Zoom	Manual
Focus Adjustment	Manual
Supported Resolutions	1920 x 1080 (HDTV 1080i/60; HDTV 1080i/50); 1680 x 1050 (WSXGA+); 1600 x 1200 (UXGA); 1600 x 900 (WXGA++); 1440 x 900 (WXGA+); 1400 x 1050 (SXGA+); 1366 x 768 (WXGA); 1360 x 768 (WXGA); 1280 x 1024 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 1152 x 870 (MAC 21"); 1152 x 864 (XGA); 1024 x 768 (XGA); 832 x 624 (MAC 16"); 800 x 600 (SVGA); 720 x 576 SDTV 480p/480i; 720 x 576 (SDTV 576p/576i); 720 x 480 SDTV 576p/576i; 720 x 480 (SDTV 480p/480i); 640 x 480 (VGA/MAC 13")
Frequency	Horizontal: 15-100 kHz (RGB: 24 kHz- 100 kHz); Vertical: 50 - 120 Hz
CONNECTIVITY	
RGB (analog)	Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
HDMI™	Input: 1 x HDMI™ (Deep Color, Lip sync)
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 2 x 3.5 mm Stereo Mini Jack; 2 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
USB	1 x Type B; 2 x Type A (USB 2.0 high speed)
Video Signals	PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M
REMOTE CONTROL	
Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Freeze; Help Eco Mode; ID set; Picture Adjust; Picture Mode; Presentation and Mouse Control; Source Select
ELECTRICAL	
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	239 (Normal) / 193 (Eco) / 8 (Network Stand-by) / 0.4 (Stand-by)
MECHANICAL	
Dimensions (W x H x D) [mm]	339 x 99 x 257 (without lens and feet)
Weight [kg]	2.9
Fan Noise [dB (A)]	27 / 34 (Eco / Normal)
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80
OPTIONAL ACCESSORIES	
Optional Accessories	Lamp (NP15LP); Wireless LAN module (NP02LM2)
ERGONOMICS	
Safety and Ergonomics	CE; ErP; TÜV GS; RoHS; TCO; Gost-R
Speakers [W]	1 x 10 (mono)
WARRANTY	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
SHIPPING CONTENT	
Shipping Contents	IR Remote Control (RD-448E); Mini D-SUB Signal Cable (1.8 m); Power Cord (1.8 m); Utility software; Security Sticker; Soft Case; Users Manual on CD-ROM; Quick Setup Guide

¹ Compliance with ISO21118-2005