


Overview



1. External 3.5" Bay
2. External 5.25" Bay
3. Power button
4. Standard Front I/O: 4 USB 2.0, headphone, microphone
5. Tower stand (optional)

Form Factor	Small Form Factor
Operating Systems	Preinstalled: <ul style="list-style-type: none">• Genuine Windows® 7 Ultimate 64-bit]

Overview

	<ul style="list-style-type: none"> • Genuine Windows® 7 Professional 32/64 • Genuine Windows® 7 Home Premium 32/64 • HP Installer Kit for Linux [includes drivers for 64-bit OS versions of Red Hat Enterprise Linux 5 & 6, 64-bit SUSE Linux Enterprise Desktop (SLED) 11] • SUSE Linux Enterprise Desktop 11 64-bit <p>Supported:</p> <ul style="list-style-type: none"> • Genuine Windows® 7 Enterprise 32/64 • Genuine Windows® XP Professional 32/64 • Red Hat Enterprise Linux Desktop (1 year paper license available; Preinstall not available) <p>Certified:</p> <ul style="list-style-type: none"> • Ubuntu 11.04 <p>NOTES: Systems may require upgraded and/or separately purchased hardware and/or DVD drive to install the Windows 7 software and take full advantage of Windows 7 functionality. See http://www.microsoft.com/windows/windows-7/ for details.</p> <p>NOTES: For detailed OS/hardware support information for Linux, see: http://www.hp.com/support/linux_hardware_matrix</p>
<p>Available Processors</p>	<p>Intel® Xeon® processor E3-1280, 3.50 GHz, 95W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel® vPro Technology</p> <p>Intel® Xeon® processor E3-1270, 3.40 GHz, 80W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel® vPro Technology</p> <p>Intel® Xeon® processor E3-1245, 3.30 GHz, 95W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, Intel® HD Graphics P3000, featuring Intel® vPro Technology</p> <p>Intel® Xeon® processor E3-1240, 3.30 GHz, 80W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel® vPro Technology</p> <p>Intel® Xeon® processor E3-1230, 3.20 GHz, 80W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel® vPro Technology</p> <p>Intel® Xeon® processor E3-1225, 3.10 GHz, 95W, 6 MB cache, 1333 MHz memory, Quad-Core, no HT, Intel® HD Graphics P3000, featuring Intel® vPro Technology</p> <p>Intel® Core i7-2600 processor, 3.40 GHz, 95W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, Intel® HD Graphics 2000, featuring Intel® vPro Technology</p> <p>Intel® Core i5-2500 processor, 3.30 GHz, 95W, 6 MB cache, 1333 MHz memory, Quad-Core, no HT, Intel® HD Graphics 2000, featuring Intel® vPro Technology</p> <p>Intel® Core i5-2400 processor, 3.10 GHz, 95W, 6 MB cache, 1333 MHz memory, Quad-Core, no HT, Intel® HD Graphics 2000, featuring Intel® vPro Technology</p> <p>Intel® Core i3-2130 processor, 3.40 GHz, 65W, 3 MB cache, 1333 MHz memory, Dual-Core, HT, Intel® HD Graphics 2000</p> <p>Intel® Core i3-2120 processor, 3.30 GHz, 65W, 3 MB cache, 1333 MHz memory, Dual-Core, HT, Intel® HD Graphics 2000</p> <p>Intel Pentium processor G850, 2.9 GHz, 65W, 3MB cache, 1333 MHz memory, Dual-Core, Intel HD Graphics</p> <p>Intel Pentium processor G620, 2.6 GHz, 65W, 3MB cache, 1066 MHz memory, Dual-Core, Intel HD Graphics</p>
<p>Available Processor Disclaimers</p>	<p>Integrated Intel® HD graphics is not supported on the Intel® Xeon E3-1230, E3-1240, E3-1270 or E3-1280 Processors.</p> <p>Intel® Xeon E3, Intel Core i3 and Intel Pentium processors can support either ECC or non-ECC memory; Intel® Core i5/i7 processors only support non-ECC memory.</p> <p>Intel's numbering is not a measurement of higher performance. Processor numbers differentiate features</p>

Overview

	<p>within each processor family, not across different processor families. See: http://www.intel.com/products/processor_number/ for details.</p> <p>64-bit computing on Intel® 64 architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel 64 architecture. Processor will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See: http://www.intel.com/info/em64t for more information.</p> <p>Dual-Core and Quad-Core technologies are designed to improve performance of multithreaded software products and hardware-aware multitasking operating systems and may require appropriate operating system software for full benefits; check with software provider to determine suitability; Not all customers or software applications will necessarily benefit from use of these technologies.</p>	
Color	Jack Black	
Convertibility	The Z210 SFF can either be placed flat on the desktop or made to stand on the desk with the optional tower stand.	
Expansion Slots (see system board section for more details)	<ul style="list-style-type: none"> • 1 PCI Express Gen2 slot x1 mechanical/x1 electrical (Low Profile) • 1 PCI Express Gen2 slot x16 mechanical/ x16 electrical (Low Profile, dedicated for graphics) • 1 PCI Express Gen2 slot x16 mechanical/x4 electrical (Low Profile) • 1 PCI slot (Low Profile) 	
Expansion Bays (see storage section for more details)	<ul style="list-style-type: none"> • 1 internal 3.5" bay, and 1 shared internal/external 3.5" bay. • 1 external 5.25" bay. 	
Front I/O	4 USB 2.0, 1 Headphone, and 1 Microphone; Microphone can be re-tasked to function as Line-in or Headphone	
Internal I/O	4 USB 2.0 ports available by two separate 9-pin headers	
Rear I/O	1 VGA and 1 DisplayPort output from Intel HD graphics (available on specific processors only); 6 USB 2.0, 1 standard and 1 optional serial port, 1 optional parallel port, 2 PS/2, RJ-45 (NIC), 1 Audio Line-in, and 1 Audio Line-out; Line-in can be re-tasked to function as Microphone; 2 IEEE 1394a/1394b ports(optional).	
Interfaces Supported	22-in-1 Media Card Reader (optional)	
Chassis Dimensions (H x W x D)	Standard desktop orientation: 100 x 338 x 381 mm (3.95 x 13.3 x 15.0 in); Optional SFF Tower orientation (excluding stand dimension): 338 x 100 x 381 mm (13.3 x 3.95 x 15.0 in)	
Weight	<p>Exact weights depend upon configuration;</p> <p>System Weight* 7.6 kg (16.72 lbs)</p> <p>Shipping Weight* 8.1 kg (17.86 lbs)</p> <p>Max Supported Weight (desktop orientation) 35 kg (77 lb)</p> <p>*Configured with 1 hard drive, 1 optical drive and one NVIDIA Quadro NVS 295 low profile graphics card.</p>	
Temperature	Operating:	40° to 95°F (5° to 35°C)
	Non-operating:	-40° to 140°F (-40° to 60°C)
Humidity	Operating:	8% to 85%
	Non-operating:	8% to 90%
Maximum Altitude (non-pressurized)	Operating:	3,000 m (10,000 ft)
	Non-operating:	9,100 m (30,000 ft).
Power Supply	<p>240 watts wide-ranging, active Power Factor Correction, 90% Efficient</p> <p>The Power Supply Efficiency Report for this product may be found at the following links: The Power Supply Efficiency Report for this product may be found at the following links:</p> <p>http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD_PS-4241-</p>	

Overview

	<p>9HB_ECOS%202398_240W_Report.pdf</p> <p>http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD_PC9055-020H_ECOS%202342_240W_Report.pdf http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_D10-240P1A_ECOS%202307_240W_Report.pdf</p> <p>http://www.plugloadsolutions.com/psu_reports/HP_DPS-240TB%20A_ECOS%202299_240W_Report.pdf</p> <p>http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_CFH240EWWB_ECOS%202304_240W_Report.pdf</p>
Backup Devices	For a complete listing of compatible DAT tape drives, LTO tape drives and RDX Removable Disk Backup System offerings, please visit: http://www.hp.com/go/connect
Chipset	Intel® C206 chipset
Memory	4 DIMM slots, supporting up to 32GB ECC/16GB non-ECC, DDR3 1333 MHz

Supported Components

Processors

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Intel® Xeon® processor E3 family (Z210)				
Intel Xeon processor E3-1280, 3.50 GHz, 95W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel vPro Technology	Y	N		See Note 2
Intel Xeon processor E3-1270, 3.40 GHz, 80W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel vPro Technology	Y	N		See Note 2
Intel Xeon processor E3-1245, 3.30 GHz, 95W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, HD Graphics P3000, featuring Intel vPro Technology	Y	N		See Note 2
Intel Xeon processor E3-1240, 3.30 GHz, 80W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel vPro Technology	Y	N		See Note 2
Intel Xeon processor E3-1230, 3.20 GHz, 80W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel vPro Technology	Y	N		See Note 2
Intel Xeon processor E3-1225, 3.10 GHz, 95W, 6 MB cache, 1333 MHz memory, Quad-Core, no HT, HD Graphics P3000, featuring Intel vPro Technology	Y	N		See Note 2
2nd generation Intel® Core™ processor family				
Intel Core i7-2600 processor, 3.40 GHz, 95W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, Intel HD Graphics 2000, featuring Intel vPro Technology	Y	N		See Note 3
Intel Core i5-2500 processor, 3.30 GHz, 95W, 6 MB cache, 1333 MHz memory, Quad-Core, no HT, Intel HD Graphics 2000, featuring Intel vPro Technology	Y	N		See Note 3
Intel Core i5-2400 processor, 3.10 GHz, 95W, 6 MB cache, 1333 MHz memory, Quad-Core, no HT, Intel HD Graphics 2000, featuring Intel vPro Technology	Y	N		See Note 3
Intel Core i3-2130 processor, 3.40 GHz, 65W, 3 MB cache, 1333 MHz memory, Dual-Core, HT, Intel HD Graphics 2000	Y	N		See Note 2
Intel Core i3-2120 processor, 3.30 GHz, 65W, 3 MB cache, 1333 MHz memory, Dual-Core, HT, Intel HD Graphics 2000	Y	N		See Note 2
Dual-Core Intel Pentium processors (Z210)				
Intel Pentium processor G850, 2.9 GHz, 65W, 3MB cache, 1333 MHz memory, Dual-Core, Intel HD Graphics	Y	N		See Note 2
Intel Pentium processor G620, 2.6 GHz, 65W, 3MB cache, 1066 MHz memory, Dual-Core, Intel HD Graphics	Y	N		See Note 2

Supported Components

NOTE 1: Intel HD Graphics P3000 provides improved desktop performance and supports workstation-specific graphics drivers for improved compatibility and performance on select professional applications*, compared to Intel HD Graphics 2000.

NOTE 2: These processors support either ECC or non-ECC memory

NOTE 3: These processors support only non-ECC memory

Monitors / Displays

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP ZR30w 30-inch S-IPS LCD Monitor	N	Y	VM617A8	
HP DreamColor LP2480zx Professional Display	N	Y	GV546A	
HP LP2475w 24-inch Widescreen LCD Monitor	N	Y	KD911A	
HP ZR2740w 27-inch LED Backlit IPS Monitor	N	Y	XW476A8	
HP ZR2440w 24-inch LED Backlit IPS Monitor	N	Y	XW477A8	
HP ZR2240w 21.5-inch LED Backlit IPS Monitor	N	Y	XW475A8	
HP ZR2040w 20-inch LED Backlit IPS Monitor	N	Y	LM975A8	

Supported by all Operating Systems available from HP

Screen Size Diagonally Measured

Hard Drives

SATA Hard Drives

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
SATA (Serial ATA) Hard Drives for HP Workstations				
250GB SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	LQ034AA	
500GB SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	LQ036AA	
1TB SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	LQ037AA	
160GB SATA 10K rpm SFF in 3.5" Frame HDD	Y	Y	EW222AA	
300GB SATA 10K rpm SFF in 3.5" Frame HDD	Y	Y	FM802AA	
600GB SATA 10K rpm SFF in 3.5" Frame HDD	Y	Y	XP309AA	
HP 320GB SATA 7.2K SED SFF HDD	Y	N	(not available as AMO today)	

SATA Solid State Drives

HP Solid State Drives for Workstations

HP 160GB SATA SSD	Y	Y	LZ704AA	
HP 300GB SATA SSD	Y	Y	LZ069AA	
HP 128GB SATA SSD	Y	Y	A3D25AA	
HP 256GB SATA SSD	Y	Y	A3D26AA	

Supported Components

Hard Drive Controllers

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Integrated SATA Controller (Z210)				
Integrated SATA Controller (SFF), RAID 0,1 supported: 2 ports 3 Gb/s, 2 ports 6 Gb/s	Y	N		
Factory integrated RAID on motherboard for SATA drives				
RAID 0 Configuration - Striped Array	Y	N		
RAID 1 Configuration - Mirrored Array	Y	N		
<p>SATA hardware RAID is not supported on Linux systems. The Linux kernel, with built-in software RAID, provides excellent functionality and performance. It is a good alternative to hardware-based RAID. All drives must be identical in type and capacity Boot volume/RAID array must be less than 2 TB. NOTE 1: Requires identical hard drives (speeds, capacity, interface).</p>				

Graphics

Integrated Graphics

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes	Supported Multi Mixed
Integrated Intel HD Graphics Media Accelerators (Z210)					
Intel HD Graphics P3000	Y	N		Available on Intel Xeon E3-12x5 processors only	1
Intel HD Graphics 2000	Y	N		Available on Intel Core i3/i5/i7 processors only	1
Intel HD Graphics	Y	N		Supported on Pentium G6xx/G8xx processors. Even though graphics on this part is branded as Intel HD Graphics, it is similar to Intel HD Graphics 2000 but	1

Supported Components

lacks some premium media capabilities.

Professional 2D

NVIDIA Quadro NVS 295 256MB PCIe Graphics Card	Y	Y	FY943AA	2
NVIDIA NVS300 512MB PCIe Graphics Card	Y	Y	XP612AA	2

Entry 3D

ATI FirePro V3800 512MB PCIe Graphics Card	Y	Y	WL048AA	1
NVIDIA Quadro 400 512MB Graphics Card	Y	Y	LD542AA	1
NVIDIA Quadro 600 1GB Graphics Card	Y	Y	WS093AA	1

Intermixing integrated Intel HD graphics and discrete graphics cards in order to drive more than two displays can be enabled using the Computer (F10) Setup Utility. However, HP recommends using only discrete graphics cards when attaching three or more displays.

Memory

Sub-Section Description/Notes

Intel® Xeon E3, Intel Core i3 and Intel Pentium processors can support either ECC or non-ECC memory; Intel® Core i5/i7 processors only support non-ECC memory.

CTO

Option Kit Part Number

Support Notes

PC3-10600 DDR3-1333 ECC Unbuffered DIMMs CTO

- 2GB (1x2GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 4GB (2x2GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 8GB (4x2GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 8GB (2x4GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 12GB (2x4GB+2x2GB) DDR3-1333 ECC Unbuffered RAM 1-CPU
- 16GB (4x4GB) DDR3-1333 ECC Unbuffered RAM 1-CPU

PC3-10600 DDR3-1333 nECC Unbuffered DIMMs CTO

- 2 GB (1x2GB) DDR3-1333 nECC Unbuffered RAM 1-CPU
- 4 GB (2x2GB) DDR3-1333 nECC Unbuffered RAM 1-CPU
- 8 GB (4x2GB) DDR3-1333 nECC Unbuffered RAM 1-CPU
- 8 GB (2x4GB) DDR3-1333 nECC Unbuffered RAM 1-CPU
- 12 GB (2x4GB+2x2GB) DDR3-1333 nECC Unbuffered RAM 1-CPU
- 16 GB (4x4GB) DDR3-1333 nECC Unbuffered RAM 1-CPU

Sub-Section Description/Notes

Supported Components

Two channels of DDR3 memory are supported. To realize full performance at least one DIMM must be inserted into each channel.

The CPUs determine the speed at which the memory is clocked. If a 1066 MHz capable CPU is used in the system, the maximum speed the memory will run at is 1066 MHz regardless of the specified speed of the memory.

AM0

PC3-10600 DDR3-1333 ECC Unbuffered DIMMs AM0

HP Z210 2GB (1x2GB) DDR3-1333 ECC Unbuffered RAM QC447AA

HP Z210 4GB (1x4GB) DDR3-1333 ECC Unbuffered RAM QC852AA

PC3-10600 DDR3-1333 nECC Unbuffered DIMMs AM0

HP 2GB DDR3-1333 non-ECC UDIMM XC440AA

HP 4GB DDR3-1333 non-ECC UDIMM LB435AA

NOTE: Only unbuffered DDR3 DIMMs are supported.

Multimedia and Audio Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Integrated Intel/Realtek HD ALC261 Audio	Y	N		
HP Thin USB Powered Speakers, BFR-PVC free	Y	Y	KK912AA	

Optical and Removable Storage

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP 16X DVD-ROM SATA Drive (non-Lightscribe)	Y	Y	AR629AA	
HP 16X DVD+/-RW SuperMulti SATA Drive (non-Lightscribe)	Y	Y	QS208AA	
HP Blu-ray Writer	Y	Y	AR482AA	
HP 22-in-1 Media Card Reader Kit (Workstations)	Y	Y	NK361AA	

Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players. As Blu-ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.

Supported Components

Controller Cards

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP FireWire IEEE 1394a PCIe x1 Card	Y	Y	BW851AA	See Note 1
HP IEEE 1394b FireWire PCIe Card	Y	Y	NK653AA	See Note 1

NOTE 1: For the Z210 SFF Workstation, this card is only supported on Slots 1 or 2

Networking and Communications

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Integrated Intel 82579LM PCIe GbE Controller	Y	N		
Intel Gigabit CT Desktop NIC	Y	Y		
Broadcom NetXtreme Gigabit Ethernet Plus NIC (PCIe)	Y	Y	FS215AA	

NOTE 1: "Gigabit" Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/sec. For high speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

The Intel Gigabit CT NIC is supported on the following operating systems:
 Microsoft Windows XP Pro 32-bit and 64-bit and Microsoft Windows 7 32-bit and 64-bit versions.
 Red Hat Enterprise Linux(RHEL), 5 Desktop/Workstation
 Novell SLED 10 & 11

NOTE 2: The integrated network connection is required to support Intel vPro Technology.

NOTE 3: If AMT is enabled network teaming with the built in LAN port is not possible.

Racking and Physical Security

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Security Cable with Kensington Lock	N	Y	PC766A	
HP 2009 (SFF) Solenoid Lock and Hood Sensor	Y	Y		
HP Business PC Security Lock Kit	N	Y	PV606AA	

Supported Components

Input Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP USB Standard Keyboard	Y	Y	DT528A	
HP PS/2 Standard Keyboard	Y	Y	DT527A	
HP USB Smart Card Keyboard	N	Y	ED707AA	
HP USB CCID SmartCard Keyboard	Y	Y	BV813AA	
HP 2.4GHz Wireless Keyboard & Mouse	N	Y	NB896AA	
HP USB Laser Mouse	Y	Y	GW405AA	
HP USB 2-Button Optical Scroll Mouse	Y	Y	DC172B	
HP PS/2 Optical Scroll Mouse	Y	Y	EY703AA	
HP USB Optical 3-Button Mouse	Y	Y	DY651A	
HP SpaceExplorer 3D USB Controller	N	Y	RY429AA	

Other Hardware

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Power Cord Kit	N	Y	DM293A	
HP Workstation Mouse Pad	Y	N		Japan only
HP Serial Port Adapter	Y	Y	PA716A	
HP ENERGY STAR 5.0 Enabled Configuration	Y	N		
HP Parallel Port Adapter Kit	N	Y	KD061AA	
HP Internal USB Port Kit	N	Y		
HP eSATA PCI Cable Kit	Y	Y	FH966AA	
HP 2009 (SFF) Chassis Tower Stand	Y	Y	VN569AA	

Software

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Performance Advisor	Y	N		Supports Windows 7 only. Available as a web download, or preloaded with all Windows 7 preinstalls.
Roxio Easy Media Creator (DVD/Blu-ray Disc burner software)	Y	N		

Supported Components

Intervideo WinDVD (DVD player/burner software)	Y	N	
HP ProtectTools Security	Y	N	Available June 2011. Must be selected as a Configure to Order option. Delivered in the form of a "Drop in the Box" CD.
PDF Complete - Trial Edition	Y	N	
HP Support Assistant	Y	N	
Buy Office	Y	N	

Operating Systems

Support Notes

Genuine Windows® 7 Ultimate 64-bit	
Genuine Windows® 7 Professional 32-bit	See http://www.microsoft.com/windows/windows-7/ for support details.
Genuine Windows® 7 Professional 64-bit	See http://www.microsoft.com/windows/windows-7/ for support details.
Genuine Windows® 7 Home Premium 32-bit	See http://www.microsoft.com/windows/windows-7/ for support details.
Genuine Windows® 7 Home Premium 64-bit	See http://www.microsoft.com/windows/windows-7/ for support details.
HP Linux Installer Kit	
Red Hat Enterprise Linux (RHEL) Workstation - Paper License (1yr)	See http://www.redhat.com/rhel/desktop/
SUSE Linux Enterprise Desktop 11	See http://www.suse.com/products/desktop/
Windows XP 32-bit/64-bit OS supported. Drivers available on HP support web site.	

System Technical Specifications

System Board																																									
System Board Form Factor	BTX 21.2mm x 26.7mm																																								
Processor Socket	Single LGA 1155																																								
CPU Bus Speed	DMI																																								
Chipset	Intel® PCH C206																																								
Memory Expansion Slots	4 DDR3 memory slots																																								
Memory Type Supported	DDR3, UDIMM (Unbuffered), ECC & non-ECC																																								
Memory Modes	Non-Interleaved for single channel. Interleaved when both channels are populated.																																								
Memory Speed Supported	1333MHz DDR3																																								
Memory Protection	ECC available on data.																																								
Maximum Memory	16GB																																								
MEMORY LOADING CONFIGURATIONS																																									
<table border="1"> <thead> <tr> <th>Memory Size (GB)</th> <th>DIMM1</th> <th>DIMM2</th> <th>DIMM3</th> <th>DIMM4</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1 GB</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>1 GB</td> <td></td> <td>1 GB</td> <td></td> </tr> <tr> <td>3</td> <td>1 GB</td> <td>1 GB</td> <td>1 GB</td> <td></td> </tr> <tr> <td>4</td> <td>2 GB</td> <td></td> <td>2 GB</td> <td></td> </tr> <tr> <td>8</td> <td>2 GB</td> <td>2 GB</td> <td>2 GB</td> <td>2 GB</td> </tr> <tr> <td>8</td> <td>4 GB</td> <td></td> <td>4 GB</td> <td></td> </tr> <tr> <td>16</td> <td>4 GB</td> <td>4 GB</td> <td>4 GB</td> <td>4 GB</td> </tr> </tbody> </table>		Memory Size (GB)	DIMM1	DIMM2	DIMM3	DIMM4	1	1 GB				2	1 GB		1 GB		3	1 GB	1 GB	1 GB		4	2 GB		2 GB		8	2 GB	2 GB	2 GB	2 GB	8	4 GB		4 GB		16	4 GB	4 GB	4 GB	4 GB
Memory Size (GB)	DIMM1	DIMM2	DIMM3	DIMM4																																					
1	1 GB																																								
2	1 GB		1 GB																																						
3	1 GB	1 GB	1 GB																																						
4	2 GB		2 GB																																						
8	2 GB	2 GB	2 GB	2 GB																																					
8	4 GB		4 GB																																						
16	4 GB	4 GB	4 GB	4 GB																																					
Memory Configuration (Supported)	1GB, 2GB and 4GB ECC and non-ECC unbuffered DIMMs are supported, but not if mixed. NOTE: * Maximum memory capacities assume 64-bit operating systems, such as genuine Genuine Windows® 7 Professional 64-Bit, Genuine Windows® 7 Professional 64-bit Downgrade to Genuine Microsoft® Windows® XP Professional 64-bit Red Hat Linux 64-bit. Genuine Windows Vista Home 32 and XP Professional (32-bit) support up to 4 GB. 32-bit Linux supports up to 8 GB.																																								
PCI Express Connectors	1 PCI Express Gen2 x16 LP slot (x16 electrical/x16 mechanical) 1 PCI Express Gen2 x16 LP slot (x4 electrical/x16 mechanical) 1 PCI Express Gen2 x1 LP slot (x1 electrical/x1 mechanical) NOTE: LP = low profile NOTES: In the PCIe x16 (x16 electrical/x16 mechanical) Gen 2 slot, if it is not being used for a graphics card, only cards certified as After Market Options for this platform are supported.																																								
PCI Connectors (5.0V)	1 PCI LP slot																																								
Supported Drive Interfaces	SATA Integrated (4) Serial ATA interfaces (2x 6Gb/s SATA in blue, 2x 3Gb/s SATA in black). One port can optionally be used for eSATA. NOTE: the Z210 SFF supports a maximum of two SATA/SSD drives only. RAID 0 and 1 supported.																																								

System Technical Specifications

		(Factory integrated RAID is Microsoft Windows only).
	Serial Attached SCSI	None
	Integrated RAID	NOTE: Requires identical hard drives (speeds, capacity, interface)
	Integrated Graphics	Integrated Intel HD Graphics (on Intel Core i3/Core i5/Core i7 processors). Integrated Intel HD Graphics P3000 (on Intel Xeon E3-12x5 processors). Unified Memory Architecture (UMA)- A region of system memory is reserved and dedicated to the graphics display. DirectX 10.0 compliant; (OpenGL 3.0 on Intel HD Graphics P3000); 1 VGA & 1 DP graphics ports integrated in motherboard. Integrated graphics can support dual display across DP & VGA outputs.
	Network Controller	Integrated Gbit LAN MAC by Intel PHY Lewisville 82579LM; Management capabilities WOL, PXE 2.1 and AMT 7
	External SATA (eSATA)	1 port eSATA capable with optional eSATA After-Market Option cable kit.
	IDE connector	No
	Floppy connector	No
	Network Controller	Management capabilities WOL, PXE 2.1 and AMT 7
	Serial	1 rear port
	2nd Serial	Yes- requires optional Serial Port Adapter Kit
	Parallel	1 internal header (optional parallel port adapter required)
	HD Integrated Audio	Yes
	CD-ROM input (Audio)	No
	AUX input (Audio)	No
IEEE 1394 Connector(s)	Front	No
	Rear	2 IEEE 1394a (requires optional PCIe card)
	Internal	No
USB Connector(s)	Front	4 USB 2.0
	Rear	6 USB 2.0
	Internal	4 USB 2.0
HD Integrated Audio	Yes	
Flash ROM	Yes	
CPU Fan Header	Not applicable - passive CPU heatsink	
Chassis Fan Header	Yes	
Front PCI Fan Header	Yes	
Front Control Panel/Speaker Header	Yes	
CMOS Battery Holder - Lithium	Yes	
Integrated Trusted Platform Module	Integrated TPM 1.2. The TPM module disabled where restricted by law, i.e. Russia.	
Power Supply Headers	Yes	

System Technical Specifications

Power Switch, Power LED & Hard Drive LED Header	Yes
Clear Password Jumper	Yes
Keyboard/Mouse	USB or PS/2
Power Supply	240W, 90% efficiency, Wide-Ranging, Active PFC Power Supply
Operating Voltage Range	90-264 VAC
Rated Voltage Range	100-240 VAC
Rated Line Frequency	50-60 Hz
Operating Line Frequency Range	47-63 Hz
Rated Input Current	4A @ 100-240V
Heat Dissipation	Typical 541 btu/hr (136.3 kg-cal/hr) Maximum 1098 btu/hr (276.6 kg-cal/ hr)
Power Supply Fan	92x25 mm variable speed
ENERGY STAR® qualified (Config Dependent)	Yes
80 PLUS Compliant	Yes, Gold. For the PSU Efficiency Report for the power supply, please go to these links: http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD_PS-4241-9HB_ECOS%202398_240W_Report.pdf http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD_PC9055-020H_ECOS%202342_240W_Report.pdf http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_D10-240P1A_ECOS%202307_240W_Report.pdf http://www.plugloadsolutions.com/psu_reports/HP_DPS-240TB%20A_ECOS%202299_240W_Report.pdf http://www.plugloadsolutions.com/psu_reports/HEWLETT-PACKARD%20COMPANY_CFH240EWWB_ECOS%202304_240W_Report.pdf
FEMP Standby Power Compliant	Yes, with Wake-on-LAN disabled: <2W in S5- Power Off
Power consumption in sleep mode (as defined by ENERGY STAR) - Suspend to RAM (S3)	<4W
Built-in Self Test (BIST) LED	No
Surge Tolerant Full Ranging Power Supply (withstands power surges up to 2000V)	Yes
ErP Lot 6- Tier 1 Compliance @ 230V (<1W in S5- Power Off)	Yes

System Technical Specifications

ErP Lot 6- Tier 2 Compliance @ 230V (<0.5W in S5- Power Off)	Yes
--	-----

Energy Consumption and Heat Dissipation: Configurations

System Configuration

<i>Example Configuration #1</i>	Processor Info	1x Intel Core i3-2120 3.3 3MB 2C 65W GT1 CPU
	Memory Info	1GB (1x 1GB) 1333MHz DDR3 ECC
	Graphics Info	1x ATI FireGL V3800 512MB PCIe Graphics
	Disks/Optical/Floppy	2x SATA 500GB 7.2k rpm / 1 Optical / 0 Floppy
	PSU	240W 90% Rev 0A
	OS /BIOS	Win7 32 / v0.57

Energy Consumption

	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows Idle (S0)	33.9 W		34.8 W		34.3 W	
Windows Busy Typ(S0)	85.1 W		83.4 W		85.2 W	
Windows Busy Max (S0)	105.1 W		100.4 W		106.6 W	
Sleep (S3)	2.21 W	1.83 W	2.39 W	2.00 W	2.20 W	1.81W
Off (S5)	1.22 W	1.06 W	1.37 W	1.21 W	1.20 W	1.05 W
Zero Power Mode (EuP)	0.17 W		0.27 W		0.16W	

Heat Dissipation**

	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows Idle (S0)	115.7 btu/hr		118.7 btu/hr		117.0 btu/hr	
Windows Busy Typ(S0)	290.4 btu/hr		284.6 btu/hr		290.7 btu/hr	
Windows Busy Max (S0)	358.6 btu/hr		342.6 btu/hr		363.7 btu/hr	
Sleep (S3)	7.54 btu/hr	6.24 btu/hr	8.15 btu/hr	6.82 btu/hr	7.51 btu/hr	6.18 btu/hr
Off (S5)	4.16 btu/hr	3.62 btu/hr	4.67 btu/hr	4.13 btu/hr	4.09 btu/hr	3.58 btu/hr
Zero Power Mode (EuP)	0.58 btu/hr		0.92 btu/hr		0.55 btu/hr	

System Technical Specifications

<i>Example Configuration #2</i>	Processor Info	1x Intel Xeon E3-1280 3.5 8MB 4C 95W GT0 CPU
	Memory Info	1x 2GB 1333MHz DDR3 ECC
	Graphics Info	1x NVIDIA Quadro 600 1GB PCIe Graphics
	Disks/Optical/Floppy	2x SATA 1000GB 7.2k rpm / 1 Optical / 0 Floppy
	PSU	240W 90% Rev 0A
	OS /BIOS	Win7 32 / v0.57

Energy Consumption	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows Idle (S0)	27.3 W		28.1 W		27.4 W	
Windows Busy Typ(S0)	153.7 W		150.8 W		154.2 W	
Windows Busy Max (S0)	172.5 W		170.3 W		176.2 W	
Sleep (S3)	2.32 W	2.26W	2.50 W	2.45 W	2.31 W	2.25W
Off (S5)	1.22 W	1.06 W	1.37 W	1.21 W	1.20 W	1.05 W
0.17 W	0.17 W		0.27 W		0.16W	

Heat Dissipation**	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows Idle (S0)	93.1 btu/hr		95.9 btu/hr		93.5 btu/hr	
Windows Busy Typ(S0)	524.4 btu/hr		514.5 btu/hr		526.1 btu/hr	
Windows Busy Max (S0)	58836 btu/hr		581.1 btu/hr		601.2 btu/hr	
Sleep (S3)	7.92 btu/hr	7.71 btu/hr	8.53 btu/hr	8.36 btu/hr	7.88 btu/hr	7.68 btu/hr
Off (S5)	4.16 btu/hr	3.62 btu/hr	4.67 btu/hr	4.13 btu/hr	4.09 btu/hr	3.58 btu/hr
Zero Power Mode (EuP)	0.58 btu/hr		0.92 btu/hr		0.55 btu/hr	

<i>Example Configuration #3</i>	Processor Info	1x Intel Xeon E3-1280 3.5 8MB 4C 95W GT0 CPU
	Memory Info	4x 4GB 1333MHz DDR3 ECC
	Graphics Info	1x NVIDIA Quadro 600 1GB PCIe Graphics
	Disks/Optical/Floppy	2x SATA 1000GB 7.2k rpm / 1 Optical / 0 Floppy
	PSU	240W 90% Rev 0A
	OS /BIOS	Win7 64 / v0.57

Energy Consumption	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows Idle (S0)	34.7 W		35.3 W		35.1 W	
Windows Busy Typ(S0)	173.7 W		175.6 W		173.5 W	
Windows Busy Max (S0)	196.8 W		190.2 W		198.5 W	
Sleep (S3)	2.79W	2.42 W	2.98 W	2.62 W	2.77 W	2.41 W
Off (S5)	1.22 W	1.06 W	1.37 W	1.21 W	1.20 W	1.05 W
Zero Power Mode (EuP)	0.17 W		0.27 W		0.16W	

Heat Dissipation**	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
Windows Idle (S0)	118.4 btu/hr		120.4 btu/hr		119.8 btu/hr	
Windows Busy Typ(S0)	592.7 btu/hr		599.1 btu/hr		592.0 btu/hr	
Windows Busy Max (S0)	671.48 btu/hr		649.0 btu/hr		677.3 btu/hr	
Sleep (S3)	9.52 btu/hr	8.26 btu/hr	10.17 btu/hr	8.94 btu/hr	9.45 btu/hr	8.22 btu/hr
Off (S5)	4.16 btu/hr	3.62 btu/hr	4.67 btu/hr	4.13 btu/hr	4.09 btu/hr	3.58 btu/hr
Zero Power Mode (EuP)	0.58 btu/hr		0.92 btu/hr		0.55 btu/hr	

System Technical Specifications

Example Configuration #4 (ENERGY STAR Qualified)

Processor Info 1x Intel Core i3-2120 3.3 3MB 2C 65W GT1 CPU
Memory Info 4x 4GB 1333MHz DDR3 nECC
Graphics Info Integrated Graphics
Disks/Optical/Floppy 2x SATA 1000GB 7.2k rpm / 1 Optical / 0 Floppy
PSU 240W 90% Rev 0A
OS /BIOS Win7 64 / v0.57

Energy Consumption

	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
<i>On-Idle (ENERGY STAR® Idle (S0))</i>	29.6 W		30.6 W		29.8 W	
<i>ENERGY STAR® P_{MAX} Windows running Linpack and Viewperf</i>	212.17 W		208.04W		210.42 W	
<i>ENERGY STAR® "Sleep" (S3)</i>	2.74W	2.35 W	2.93 W	2.53 W	2.74 W	2.35 W
<i>ENERGY STAR® "Standby" (Off) (S5)</i>	1.22 W	1.06 W	1.37 W	1.21 W	1.20 W	1.05 W

Heat Dissipation**

	115 VAC		230 VAC		100 VAC	
	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
<i>On-Idle (ENERGY STAR® Idle (S0))</i>	101.0 btu/hr		104.4 btu/hr		101.7 btu/hr	
<i>ENERGY STAR® P_{MAX} Windows running Linpack and Viewperf</i>	723.9 btu/hr		709.8 btu/hr		718.0 btu/hr	
<i>ENERGY STAR® "Sleep" (S3)</i>	9.35 btu/hr	8.02 btu/hr	10.00 btu/hr	8.63 btu/hr	9.35 btu/hr	8.02 btu/hr
<i>ENERGY STAR® "Standby" (Off) (S5)</i>	4.16 btu/hr	3.62 btu/hr	4.67 btu/hr	4.13 btu/hr	4.09 btu/hr	3.58 btu/hr

NOTES:

** Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noise Emissions (Entry-level and High-end configurations)

Declared Noise Emissions (Entry-level and High-end configurations)		
System Configuration (Entry level)	Processor Info	Intel Xeon E3-1270 3.4 GHz
	Memory Info	2 x 2GB DDR3 1333 MHz
	Graphics Info	NVIDIA Quadro NVS 300
	Disks/Optical/Floppy	1 x 250 GB 7200 RPM SATA/ DVD-ROM

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (LWAd, bels)		Desktop operator Sound Pressure (LpAm, decibels)
	Idle	3.3 Bels	22 dB
	Hard drive Operating (random reads)	3.4 Bels	24 dB
	DVD-ROM Operating (sequential reads)	5.0 Bels	40 dB

System Technical Specifications

System Configuration (High-end)	Processor Info	Intel Xeon E3-1280 3.5 GHz
	Memory Info	4 x 4GB DDR3 1333 MHz
	Graphics Info	NVIDIA Quadro 600
	Disks/Optical/Floppy	2 x 300GB 10K rpm SATA/ DVD-ROM

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Desktop operator Sound Pressure (LpAm, decibels)
	Idle	3.6 Bels	27 dB
	Hard drive Operating (random reads)	4.0 Bels	30 dB
	DVD-ROM Operating (sequential reads)	5.0 Bels	40 db

Environmental Requirements	Temperature	Operating: 40° to 95° F (5° to 35° C) Non-operating: -40° to 140° F (-40° to 60° C)
	Humidity	Operating: 8% to 85% RH, non-condensing Non-operating: 8% to 90% RH, non-condensing
	Maximum Altitude	Operating: 10,000 feet (3,000 m) Non-operating: 30,000 feet (9,100 m)
	Dynamic (new)	Shock Operating: ½-sine: 40g, 2-3ms Non-operating: ½-sine: 160 cm/s, 2-3ms (~100g) square: 422 cm/s, 20g Vibration Operating random: 0.5g (rms), 5-300 Hz Non-operating random: 2.0g (rms), 10-500 Hz NOTE: Values represent individual shock events and do not indicate repetitive shock events.Values do not indicate continuous vibration.
	Cooling	Above 5,000 ft (1524 m) altitude, maximum operating temperature is de-rated by 1.8° F (1° C) per 1,000 ft (305 m) elevation increase

Physical Security and Serviceability	
Access Panel	Tool-less Includes system board and memory information
Expansion Cards	Tool-less
Processor Socket	Tool-less, except for the processor heatsink.
Green User Touch Points	Yes, on tool-free internal chassis mechanisms
Color-coordinated Cables and Connectors	Yes
Memory	Tool-less

System Technical Specifications

System Board	Screw-In
Dual Color Power and HD LED on Front of Computer	Yes
Configuration Record SW	Yes
Over-Temp Warning on Screen	Yes
Restore CD/DVD Set	Restores the computer to its original factory shipping operating system. Orderable with the workstation, or available from Support.
Dual Function Front Power Switch	Yes, causes a fail-safe power off when held for 4 seconds
Padlock Support	Yes (optional): Locks side cover and secures chassis from theft 0.22-in diameter padlock loop at rear of system
Cable Lock Support	Yes, Kensington Cable Lock (optional): Locks side cover and secures chassis from theft 3 mm x 7 mm slot at rear of system
Universal Chassis Clamp Lock Support	Yes (optional): Locks side cover and locks cables to chassis. Secures chassis from theft and allows multiple units to be chained together when used with optional cable Threaded feature at rear of system
Solenoid Lock and Hood Sensor	Yes (optional) The Solenoid Hood Lock eliminates the need for a physical key by making the chassis lockable through software and a password. You can also lock and unlock the chassis remotely over the network. The Sensor Kit detects when the access panel has been removed.
Rear Port Control Cover	Yes, locks rear IO cables to prevent cable theft
Serial, Parallel, USB, Audio, Network, Enable/Disable Port Control	Yes, enables or disables serial, USB, audio, and network ports
Removable Media Write/Boot Control	Yes, prevents ability to boot from removable media on supported devices (and can disable writes to media)
Power-On Password	Yes, prevents an unauthorized person from booting up the workstation
Setup Password	Yes, prevents an unauthorized person from changing the workstation configuration
3.3V Aux Power LED on System PCA	Yes
NIC LEDs (integrated) (Green & Amber)	Yes
CPUs and Heatsinks	A T-15 Torx or flat blade screwdriver is needed to remove the CPU heatsink before the CPU can be removed. CPU removal is tool-less.
Power Supply Diagnostic LED	No
Front Power Button	Yes, ACPI multi-function
Front Power LED	Yes, blue (normal), red (fault)
Front Hard Drive Activity LED	Yes, green
Front ODD Activity LED	Yes

System Technical Specifications

Internal Speaker	Yes
System/Emergency ROM Flash Recovery	Recovers corrupted system BIOS.
Cooling Solutions	Air cooled forced convection
Power Supply Fans	92 mm x 92 mm x 25 mm 4-wire PWM (non-serviceable)
CPU Heatsink Fan	Not applicable- CPU heatsink is passive.
MXM Heatsink Fan	92 mm x 92mm x 25 mm 4-wire PWM
Memory Heatsink Fan	No
HP Vision Diagnostics Offline Edition	HP Vision Diagnostics utility must be booted from USB or CD, and enables you to perform testing and to view critical computer hardware and software configuration information from various sources.
Access Panel Key Lock	No
ACPI-Ready Hardware	Advanced Configuration and Power Management Interface (ACPI). <ul style="list-style-type: none"> Allows the system to wake from a low power mode. Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system
Trusted Platform Module Chip with optional ProtectTools Software	Yes
Integrated Chassis Handles	No
Power Supply	Tool-less
PCI Card Retention	Yes, rear (all), middle (none), front (none)
Flash ROM	Yes
Diagnostic Power Switch LED on board	Yes
Clear Password Jumper	Yes
Clear CMOS Button	Yes
CMOS Battery Holder	Yes
DIMM Connectors	Yes
HP ProtectTools Security Manager	Yes - Not supported on Microsoft XP x64 or Linux

BIOS	
BIOS 32-bit Services	Standard BIOS 32-bit Service Directory Proposal v0.4
PCI 3.0 Support	Full BIOS support for PCI Express through industry standard interfaces.
ATAPI	ATAPI Removable Media Device BIOS Specification Version 1.0.
BBS	BIOS Boot Specification v1.01.
WMI Support	WMI is Microsoft's implementation of Web-Based Enterprise Management (WBEM) for Windows. WMI is fully compliant with the Distributed Management Task Force (DMTF) Common Information Model (CIM) and WBEM specifications.

System Technical Specifications

BIOS Boot Spec 1.01+	Provides more control over how and from what devices the workstation will boot.
BIOS Power On	Users can define a specific date and time for the system to power on.
ROM Based Computer Setup Utility (F10)	Review and customize system configuration settings controlled by the BIOS.
System/Emergency ROM Flash Recovery with Video	Recovers system BIOS in corrupted Flash ROM.
Replicated Setup	Saves BIOS settings to USB flash device in human readable file. Repset.exe utility can then replicate these settings on machines being deployed without entering Computer Configuration Utility (F10 Setup).
SMBIOS	System Management BIOS 2.7.1, for system management information.
Boot Control	Disables the ability to boot from removable media on supported devices.
Memory Change Alert	Alerts management console if memory is removed or changed.
Thermal Alert	Monitors the temperature state within the chassis. Three modes: <ul style="list-style-type: none"> ● NORMAL - normal temperature ranges. ● ALERTED - excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown. ● SHUTDOWN - excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs.
Remote ROM Flash	Provides secure, fail-safe ROM image management from a central network console.
ACPI (Advanced Configuration and Power Management Interface)	Allows the system to enter and resume from low power modes (sleep states). Enables an operating system to control system power consumption based on the dynamic workload. Makes it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system.
Ownership Tag	A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen.
Remote Wakeup/Remote Shutdown	System administrators can power on, restart, and power off a client computer from a remote location.
ASF 2.0 Compliant	No.
Instantly Available PC (Suspend to RAM - ACPI sleep state S3)	Allows for very low power consumption with quick resume time.
Remote System Installation via F12 (PXE 2.1) (Remote Boot from Server)	Allows a new or existing system to boot over the network and download software, including the operating system.
ROM revision levels	Reports the system BIOS revision level in Computer Configuration Utility (F10 Setup). Version is available through an industry standard interface (SMBIOS) so that management SW applications can use and report this information.
System board revision level	Allows management SW to read revision level of the system board. Revision level is digitally encoded into the HW and cannot be modified.
Start-up Diagnostics (Power-on Self-Test)	Assesses system health at boot time with selectable levels of testing.
Auto Setup when new hardware installed	System automatically detects addition of new hardware.
Keyboard-less Operation	The system can be booted without a keyboard.

System Technical Specifications

Localized ROM Setup	Common BIOS image supports System Configuration Utility (F10 Setup) menus in 12 languages with local keyboard mappings.
Asset Tag	The user or MIS to set a unique tag string in non-volatile memory.
Per-slot Control	Allows I/O slot parameters (option ROM enable/disable, bus latency) to be configured individually.
Adaptive Cooling	Control parameters are set according to detected hardware configuration for optimal acoustics.
Pre-boot Diagnostics	(Pre-video) critical errors are reported via beeps and blinks on the power LED.
Intel® Active Management Technology (AMT)	AMT 7.0; Allows workstation status to be monitored on a remote console
Industry Standard Specification Support	
Industry Standard	Revision Supported by the BIOS
ACPI	Advanced Configuration and Power Management Interface, Version 1.0
ATA (IDE)	AT Attachment 6 with Packet Interface (ATA/ATAPI-6), Revision 3b
CD Boot	"El Torito" Bootable CD-ROM Format Specification Version 1.0
EDD	<ul style="list-style-type: none"> Enhanced Disk Drive Specification Version 1.1 BIOS Enhanced Disk Drive Specification Version 3.0
EHCI	Enhanced Host Controller Interface for Universal Serial Bus, Revision 1.0
PCI	PCI Local Bus Specification, Revision 2.3 PCI Power Management Specification, Revision 1.1 PCI Firmware Specification, Revision 3.0, Draft .7
PCI Express	PCI Express Base Specification, Revision 2.0
PMM	POST Memory Manager Specification, Version 1.01
SATA	<ul style="list-style-type: none"> Serial ATA Specification, Revision 1.0a Serial ATA II: Extensions to Serial ATA 1.0, Revision 1.0a Serial ATA II Cables and Connectors Volume 2 Gold
SPD	PC SDRAM Serial Presence Detect (SPD) Specification, Revision 1.2B
TPM	Trusted Computing Group TPM Specification Version 1.2
USB	Universal Serial Bus Revision 1.1 Specification Universal Serial Bus Revision 2.0 Specification
UEFI	UEFI 2.1

Social and Environmental Responsibility

Eco-Label Certifications & Declarations	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none"> ENERGY STAR® (energy-saving features available on selected configurations -Windows only) US Federal Energy Management Program (FEMP) China Energy Conservation Program IT ECO declaration
Batteries	The battery in this product complies with EU Directive 2006/66/EC Battery size: CR2032 (coin cell)

System Technical Specifications

	<p>Battery type: Lithium Metal</p> <p>Batteries used in the product do not contain:</p> <ul style="list-style-type: none"> ● Mercury greater than 5ppm by weight ● Cadmium greater than 10ppm by weight ● Lead greater than 40 ppm by weight.
Restricted Material Usage	<p>This product meets the material restrictions specified in HP's General Specification for the the Environment: http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</p> <p>Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis.</p> <p>This product is brominated flame retardant and polyvinyl chloride free (BFR/PVC-free); meeting the evolving definition of "BFR/PVC-free" as set forth in the "iNEMI Position Statement on the 'Definition of Low-Halogen Electronics (BFR/CFR/PVC-Free).'" Plastic parts contain <1,000 ppm (0.1 percent) of bromine (if the Br source is from BFRs) and <1,000 ppm (0.1 percent) of chlorine (if the Cl source is from CFRs or PVC or PVC copolymers). All printed circuit board (PCB) and substrate laminates contain bromine/chlorine total <1,500 ppm (0.15 percent) with a maximum chlorine of 900 ppm (0.09 percent) and maximum bromine being 900 ppm (0.09 percent). Service parts after purchase may not be BFR/PVC-free. Exceptions to this claim that may be shipped with the product include the power cord, keyboard, mouse and video adapters which may not be BFR/PVC-free.</p>
End-of-Life Management and Recycling	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. This product is greater than 90% recyclable by weight when properly disposed of at end of life. This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.</p>
Hewlett-Packard Corporate Environmental Information	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</p>
Additional Information	<ul style="list-style-type: none"> ● This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC. ● This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC. ● Plastic parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043. ● This product contains 0% recycled materials (by weight) ● This product is >90% recycle-able when properly disposed of at end of life. <p>For more details on the following please refer to the respective sections:</p> <ul style="list-style-type: none"> ● Energy Consumption and Power Supply Efficiency ● Heat Dissipation ● Declared Noise Emissions
Packaging	<p>This product meets the packaging requirements specified in HP's General Specification for the Environment. http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</p> <ul style="list-style-type: none"> ● Design packaging materials for ease of disassembly.

System Technical Specifications

	<ul style="list-style-type: none"> ● Maximize the use of post-consumer recycled content materials in packaging materials. ● Use readily recyclable packaging materials such as paper and corrugated materials. ● Reduce size and weight of packages to improve transportation fuel efficiency.
Packaging Materials	
Internal	<p>EPE - Expanded Polyethylene, Polyethylene low density foam.</p> <p>The EPE - Expanded Polyethylene packaging material is made from 100% recycled content</p> <p>The Polyethylene low density foam packaging material is made from 100% recycled content</p>
External	<p>Corrugated Carton.</p> <p>The Corrugated Carton packaging material is made from 100% recycled content.</p>

Manageability	
Industry Standard Specifications	<p>This product meets the following industry standard specifications for manageability functionality:</p> <ul style="list-style-type: none"> ● DASH 1.1 (via integrated Intel LAN)
Intel Active Management Technology (AMT)	<p>Intel Active Management Technology (AMT) 7.0</p> <p>An advanced set of remote management features and functionality which provides network administrators the latest and most effective tools to remotely discover, heal, and protect networked client systems regardless of the system's health or power state. AMT 7.0 includes the following advanced management functions:</p> <ul style="list-style-type: none"> ● Power Management (on, off, reset) ● Hardware Inventory (includes BIOS and firmware revisions) ● Hardware Alerting ● Agent Presence ● System Defense Filters ● SOL/IDER ● Cisco NAC/SDN Support ● ME Wake-on-LAN ● DASH 1.1 compliance ● IPv6 Support ● Fast Call for Help - a client inside or outside the firewall may initiate a call for help via BIOS screen, periodic connections, or alert triggered connection ● Remote Scheduled Maintenance - pre-schedule when the PC connects to the IT or service provider console for maintenance. Remote PCs can get required patches, be inventoried, etc by connecting to their IT console or Service Provider when it's convenient ● Remote Alerts - automatically alert IT or service provider if issues arise ● Access Monitor - Provides oversight into Intel® AMT actions to support security requirements ● PC Alarm Clock ● Microsoft NAP Support ● Host Base set-up and configuration ● Management Engine (ME) firmware roll back ● Enhanced KVM resolution
Intel® vPro™ Technology	<p>The HP Z210 workstations support Intel vPro technology when purchased with a vPro technology capable CPU: Intel® Xeon® processor E3-1200 family or 2nd Generation Intel Core i5/i7 processors with Intel VT and Intel TXT technology</p>
Remote Manageability Software Solutions	<p>The HP Z210 Workstation is supported on the following remote manageability software consoles:</p>

System Technical Specifications

	<ul style="list-style-type: none"> ● LANDesk Management Suite (PSG recommended solution) ● Microsoft System Center Configuration Manager ● HP Client Automation Enterprise <p>For questions or support for manageability needs, please visit: http://www.hp.com/go/easydeploy</p>
System Software Manager	<p>For questions or support for SSM, please visit: http://www.hp.com/go/ssm</p>
Service, Support, and Warranty	<p>On-site Warranty and Service (Note 1): One and Three-years, limited warranty and service offering delivers on-site, next business-day (Note 2) service for parts and labor and includes free telephone support (Note 3) 8am - 5pm. Global coverage (Note 2) ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering.</p> <p>NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply.</p> <p>NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.</p> <p>NOTE 3: Technical telephone support applies only to HP-configured, HP and HP-qualified, third-party hardware and software. Toll-free calling and 24x7 support service may not be available in some countries. HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/lookuptool. Additional HP Care Pack Services information by product is available at: http://www.hp.com/hps/carepack. Service levels and response times for HP Care Packs may vary depending on your geographic location.</p>
Product Change Notification	<ul style="list-style-type: none"> ● Program to proactively communicate Product Change Notifications (PCNs) and Customer Advisories by email to customers, based on a user-defined profile. ● PCNs provide advance notification of hardware and software changes to be implemented in the factory providing time to plan for transition. ● Customer Advisories provide concise, effective problem resolution, greatly reducing the need to call technical support.

Stable & Consistent Offerings

As part of its commitment to hardware, software, and solution innovation, HP is proud to introduce this breakthrough platform configuration stability to HP Workstation customers. HP Stable & Consistent Offerings are built on the foundation of a carefully chosen set of hardware and software designed and tested to work with all HP Z Workstation platforms through their end of life. These components and their corresponding HP Workstation platform compatibility are outlined in this section. HP Stable & Consistent Offerings are available worldwide to all HP Workstation customers—no special programs, no additional cost—no kidding. Simply select your hardware and software components when you customize your HP Workstation and be assured that you'll be able to buy that same configuration throughout the lifecycle of the product.

Technical Specifications - Processors

Processors

- Intel Xeon processor E3-1225, 3.10 GHz, 95W, 6 MB cache, 1333 MHz memory, Quad-Core, no HT, HD Graphics P3000, featuring Intel vPro Technology
- Intel Xeon processor E3-1230, 3.20 GHz, 80W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel vPro Technology
- Intel Xeon processor E3-1240, 3.30 GHz, 80W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel vPro Technology
- Intel Xeon processor E3-1245, 3.30 GHz, 95W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, HD Graphics P3000, featuring Intel vPro Technology
- Intel Xeon processor E3-1270, 3.40 GHz, 80W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel vPro Technology
- Intel Xeon processor E3-1280, 3.50 GHz, 95W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, featuring Intel vPro Technology

- Intel Core i3-2120 processor, 3.30 GHz, 65W, 3 MB cache, 1333 MHz memory, Dual-Core, HT, Intel HD Graphics 2000
- Intel Core i3-2130 processor, 3.40 GHz, 65W, 3 MB cache, 1333 MHz memory, Dual-Core, HT, Intel HD Graphics 2000
- Intel Core i5-2400 processor, 3.10 GHz, 95W, 6 MB cache, 1333 MHz memory, Quad-Core, no HT, Intel HD Graphics 2000, featuring Intel vPro Technology
- Intel Core i5-2500 processor, 3.30 GHz, 95W, 6 MB cache, 1333 MHz memory, Quad-Core, no HT, Intel HD Graphics 2000, featuring Intel vPro Technology
- Intel Core i7-2600 processor, 3.40 GHz, 95W, 8 MB cache, 1333 MHz memory, Quad-Core, HT, Intel HD Graphics 2000, featuring Intel vPro Technology

- Intel Pentium processor G850, 2.9 GHz, 65W, 3MB cache, 1333 MHz memory, Dual-Core, Intel HD Graphics
- Intel Pentium processor G620, 2.6 GHz, 65W, 3MB cache, 1066 MHz memory, Dual-Core, Intel HD Graphics

Technical Specifications - Monitors / Displays

HP ZR24w 24-inch S-IPS LCD Monitor	QuickSpecs URL Part Number	http://h18000.www1.hp.com/products/quickspecs/13557_div/13557_div.html VM633A8
HP ZR22w 21.5-inch S-IPS LCD Monitor	QuickSpecs URL Part Number	http://h18000.www1.hp.com/products/quickspecs/13556_div/13556_div.html VM626A4
HP LP3065 30-inch Widescreen LCD Monitor	QuickSpecs URL Part Number	http://h18000.www1.hp.com/products/quickspecs/12621_div/12621_div.html Workstation Volume and Business Desktop Channel EZ320A4#XXX Workstation Value Channel EZ320A5#XXX
HP LP2475w 24-inch Widescreen LCD Monitor	QuickSpecs URL Part Number	http://h18000.www1.hp.com/products/quickspecs/13134_div/13134_div.html KD911A8
HP LP2275w 22-inch Widescreen LCD Monitor	Part Number	KE289A4
HP DreamColor LP2480zx Professional Display	QuickSpecs URL Part Number	http://h18000.www1.hp.com/products/quickspecs/13081_div/13081_div.html GV546A8
HP LP2065 20-inch LCD Monitor	QuickSpecs URL Part Number	http://h18000.www1.hp.com/products/quickspecs/12377_div/12377_div.html Workstation Volume Channel EF227A4 Workstation Value Channel EF227A5

Technical Specifications - Hard Drives

SATA (Serial ATA) Hard Drives for HP Workstations	600GB SATA 10K rpm SFF in 3.5" Frame HDD	Capacity	600GB	
		Height	1 in; 2.54 cm	
		Width		
			Media Diameter	2.5 in; 6.36 cm
			Physical Size	4 in; 10.17 cm
		Interface	Serial ATA (3.0Gb/s)	
		Synchronous Transfer Rate (Maximum)	Up to 300MB/s	
		Buffer	32MB	
		Cache	Segmentable	
		Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.4 ms (max)
			Average	3.6 ms
			Full Stroke	9.0 ms
		Rotational Speed	10,000 rpm	
		Logical Blocks	1,172,123,568	
Operating Temperature	41° to 131° F (5° to 55° C)			
	300GB SATA 10K rpm SFF in 3.5" Frame HDD	Capacity	300,069,052,416 bytes	
		Height	1 in; 2.54 cm	
		Width		
			Media Diameter	2.5 in; 6.36 cm
			Physical Size	4 in; 10.17 cm
		Interface	Serial ATA (3.0 Gb/s), Native Command Queuing enabled	
		Synchronous Transfer Rate (Maximum)	Up to 300 MB/s	
		Cache	16 MB	
		Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.7 ms (maximum)
			Average	4.4 ms
			Full Stroke	9.5 ms
		Rotational Speed	10,000 rpm	
		Logical Blocks	586,072,368	
		Operating Temperature	41° to 131° F (5° to 55° C)	
	160GB SATA 10K rpm SFF in 3.5" Frame HDD	Capacity	160,041,885,696 bytes	
		Height	1 in; 2.54 cm	
		Width		
			Media Diameter	2.5 in; 6.36 cm
			Physical Size	4 in; 10.17 cm
		Interface	Serial ATA (1.5 Gb/s), Native Command Queuing enabled	

Technical Specifications - Hard Drives

	Synchronous Transfer Rate (Maximum)	Up to 300 MB/s	
	Buffer	16 MB	
	Seek Time (typical reads, includes controller overhead, including settling)		Single Track 0.7 ms (maximum)
			Average 4.4 ms
			Full Stroke 9.5 ms
	Rotational Speed	10,000 rpm	
	Logical Blocks	312,581,808	
	Operating Temperature	41° to 131° F (5° to 55° C)	
1TB SATA 7200 rpm 6Gb/s 3.5" HDD	Capacity	1 Terabyte (1000 GB)	
	Height	1 in; 2.54 cm	
	Width		Media Diameter 3.5 in; 8.9 cm
			Physical Size 4 in; 10.17 cm
	Interface	Serial ATA (6.0Gb/s), NCQ enabled	
	Synchronous Transfer Rate (Maximum)	Up to 600 MB/s	
	Buffer	32MB	
	Seek Time (typical reads, includes controller overhead, including settling)		Single Track 2 ms
			Average 11 ms
			Full Stroke 21 ms
	Rotational Speed	7,200 rpm	
	Logical Blocks	1,953,525,168	
	Operating Temperature	41° to 131° F (5° to 55° C)	
500GB SATA 7200 rpm 6Gb/s 3.5" HDD	Capacity	500GB	
	Height	1 in; 2.54 cm	
	Width		Media Diameter 3.5 in; 8.9 cm
			Physical Size 4 in; 10.17 cm
	Interface	Serial ATA (6.0Gb/s), NCQ enabled	
	Synchronous Transfer Rate (Maximum)	Up to 600MB/s	
	Buffer	16MB	
	Seek Time (typical reads, includes controller overhead, including settling)		Single Track 2 ms
			Average 11 ms
			Full Stroke 21 ms
	Rotational Speed	7,200 rpm	
	Logical Blocks	976,773,168	
	Operating Temperature	41° to 131° F (5° to 55° C)	

Technical Specifications - Hard Drives

250GB SATA 7200 rpm 6Gb/s 3.5" HDD	Capacity	250 GB		
	Height	1 in; 2.54 cm		
	Width		Media Diameter 3.5 in; 8.9 cm	
			Physical Size 4 in; 10.17 cm	
	Interface	Serial ATA (6.0Gb/s), NCQ enabled		
	Synchronous Transfer Rate (Maximum)	Up to 600MB/s		
	Buffer	8 MB		
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2 ms	
		Average	11 ms	
		Full Stroke	21 ms	
	Rotational Speed	7,200 rpm		
	Logical Blocks	488,397,168		
	Operating Temperature	41° to 131° F (5° to 55° C)		
	HP 320GB SATA 7.2K SED SFF HDD	Capacity	320GB	
Height		0.275 in; 0.7 cm		
Width			Media Diameter 2.5 in; 6.36 cm	
			Physical Size 2.75 in; 7 cm	
Interface		Serial ATA (3.0Gb/s), NCQ enabled		
Synchronous Transfer Rate (Maximum)		Up to 166MB/s		
Buffer		16MB		
Cache		16MB		
Seek Time (typical reads, includes controller overhead, including settling)		Single Track	2.0ms (read) 2.2ms (write)	
		Average	13ms	
		Full Stroke	30ms	
Rotational Speed		7,200 rpm		
Logical Blocks		625,142,448		
Operating Temperature		32° to 140° F (0° to 60° C)		

Technical Specifications - Hard Drives

HP Solid State Drives for Workstations

HP 160GB SATA SSD	Capacity	160GB	
	Width		Media Diameter NaN in; NaN cm
			Physical Size 2.5 in; 6.36 cm
	Interface	SATA	
	Synchronous Transfer Rate (Maximum)	3Gb/s	
	Operating Temperature	32° to 158° F (0° to 70° C)	
HP 300GB SATA SSD	Capacity	300GB	
	Width		Physical Size 2.5 in; 6.36 cm
	Interface	SATA	
	Synchronous Transfer Rate (Maximum)	3Gb/s	
	Operating Temperature	32° to 158° F (0° to 70° C)	

Technical Specifications - Graphics

Integrated Intel HD Graphics Media Accelerators (Z210)	Form Factor	Integrated
	Graphics Controller	Intel Integrated Graphics Media Accelerator HD
	Bus Type	PCI Express x16
	Memory	Unified Memory Architecture (UMA) frame buffer. Graphics memory is shared with system memory. Size selectable between 64 MB to 512 MB via BIOS setting. Default size is 64 MB. Additional memory is allocated for graphics as needed using Intel's Dynamic Video Memory Technology (Intel DVMT 5.0), to provide an optimal balance between graphics and system memory use.
	Connectors	Z210: 1 Single Link DVI-I, 1 DisplayPort Z210 SFF: 1 VGA, 1 DisplayPort Graphics adapters are orderable as an accessory as necessary.
	Maximum Resolution	DVI-I: 1920 x 1200 Display Port: 2560 x 1600
	RAMDAC	Integrated, 350 MHz
	Display Output	Z210: Integrated dual independent monitor support facilitated via one DVI port and one DisplayPort integrated on the back plane of the system board and presented as part of the rear I/O set of interfaces. Second DVI supported via optional DisplayPort to DVI-D adapter. VGA support via optional DVI to VGA adapter or DisplayPort to VGA adapter. Z210 SFF: Integrated dual independent monitor support facilitated via one VGA port and one DisplayPort integrated on the back plane of the system board and presented as part of the rear I/O set of interfaces. Second VGA supported via optional DisplayPort to VGA adapter. DVI support via optional DisplayPort to DVI adapter.
	Supported Graphics APIs	Intel HD Graphics 2000: Microsoft DirectX 10, OpenGL 2.1 Intel HD Graphics P3000: Microsoft DirectX 10.1, OpenGL 3.0
	<hr/>	
NVIDIA Quadro NVS 295 256MB Graphics Card	Form Factor	2.731 inches (H) × 6.600 inches (L), Half-Height
	Graphics Controller	NVIDIA Quadro NVS 295 Graphics Board
	Bus Type	PCI Express x16, Generation 2.0
	Memory	256 MB GDDR3 SDRAM unified graphics memory
	Connectors	2 DisplayPort Comes with 2 DisplayPort to DVI-D Adapters ('DisplayPort to VGA' and 'DisplayPort to DL DVI' adapters available as an accessory)
	Maximum Resolution	Two DisplayPort outputs drive two digital displays up to 2560 x 1600
Display Output	<p>NOTE: This card supports up to two displays</p> <ul style="list-style-type: none"> • Drives DisplayPort enabled digital displays at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking • Drives DVI enabled digital displays at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking (through DisplayPort to DVI-D (single link) cable) 	

Technical Specifications - Graphics

Supported Graphics APIs	OpenGL 3.0 DirectX 10.0
Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) WS4 (64-bit and 32-bit) <i>* WS4 not supported on Z200 & Z200 SFF</i> Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation (64-bit and 32-bit) SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)
	HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html
	SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
Power Consumption	<24 Watts

NVIDIA NVS 300 512MB Graphics Card

Form Factor	2.7 inches (H) x 5.7 inches (L), Half-Height
Graphics Controller	NVIDIA NVS 300 Graphics Board
Bus Type	PCI Express x16, Generation 2.0
Memory	512 MB GDDR3 SDRAM unified graphics memory
Connectors	DMS-59 Includes DMS-59 to Dual DVI-I adapter DMS-59 to Dual DisplayPort adapter and DMS-59 to Dual VGA adapter available as an option DMS-59 to Dual DisplayPort adapter required for HP ZR30w Display
Maximum Resolution	DVI: two digital displays up to 1920 x 1200 DisplayPort: two digital displays up to 2560 x 1600 VGA: two analog displays up to 1920 x 1080
Image Quality Features	
Display Output	This card support up to two displays: <ul style="list-style-type: none"> • Drives DVI enabled digital displays at resolutions up to 1920 x 1200 at 60 Hz with reduced blanking • Drives DisplayPort enabled digital displays at resolutions up to 2560 x 1600 at 60 Hz with reduced blanking (through optional DMS-59 to DisplayPort adapter) • Drives VGA enabled analog displays at resolutions up to 1920 x 1080 (through optional DMS-59 to VGA adapter)
Supported Graphics APIs	OGL 3.3 DirectX 10.1
Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation

Technical Specifications - Graphics

SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or available from the HP support Web site: <http://welcome.hp.com/country/us/en/support.html>

Novell SUSE Linux Enterprise drivers may also be obtained from: <ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

Power Consumption

<18 Watts

NVIDIA Quadro 400 512MB Form Factor Graphics Card

Graphics Controller

Low Profile, 2.7 inches (H) x 5.6 inches (L)

NVIDIA Quadro 400 Graphics Board

Bus Type

PCI Express x 16, Generation 2.0

Memory

512MB DDR3 SDRAM

Connectors

One (1) Dual-link DVI-I

One (1) DisplayPort 1.1

Includes one DisplayPort to DVI-D adapter

Maximum Resolution

DisplayPort 1.1: 2560 x 1600 @ 60 Hz

Dual Link DVI-I: 2560 x 1600 @ 60 Hz

Analog: 2048 x 1536 @ 85 Hz

RAMDAC

Dual internal 400 MHz DACs

Display Output

This card supports up to two displays

Supported Graphics APIs

OpenGL 3.2

DirectX 10.1 Shader Model 4.1

Available Graphics Drivers

Genuine Windows 7 Professional (64-bit and 32-bit)

Genuine Windows Vista Business (64-bit and 32-bit)

Microsoft Windows XP Professional (64-bit and 32-bit)

Red Hat Enterprise Linux(RHEL) WS4 (64-bit and 32-bit)

Red Hat Enterprise Linux(RHEL) 5 Desktop/Workstation

SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or available from the HP support Web site: <http://welcome.hp.com/country/us/en/support.html>

Novell SUSE Linux Enterprise drivers may also be obtained from: <ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

Power Consumption

< 35 Watts

Technical Specifications - Graphics

NVIDIA Quadro 600 1GB Graphics Card	Form Factor	2.731" H x 6.6" L Single Slot Small Form Factor
	Graphics Controller	NVIDIA Quadro 600 Graphics Card
	Bus Type	PCI Express 2.0 x16
	Memory	1 GB GDDR3 128-bit
	Connectors	1 DVI-I output, 1 DisplayPort output One DP to DVI adapter included with card
		DVI to VGA, DisplayPort to VGA and DisplayPort to DVI adapters available as accessories
	Maximum Resolution	DisplayPort (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz) Dual-link DVI-I output (up to 2560 x 1600 @ 60Hz and 1920x1200 @ 120Hz)
	Shading Architecture	Shader Model 5.0
	Supported Graphics APIs	OpenGL 4.1 DirectX 11
		CUDA API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
	Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Genuine Windows Vista Business (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux (RHEL) 5 Desktop/Workstation (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)
		HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html
		SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
	Power Consumption	40 Watts

Technical Specifications - Multimedia and Audio Devices

**Integrated Intel/Realtek
HD ALC261 Audio**

**Minimum System
Requirements**

Integrated

Technical Specifications - Optical and Removable Storage

HP DVD-ROM Drive	Description	5.25-inch, half-height, tray-load	
	Mounting Orientation	Either horizontal or vertical	
	Interface Type	SATA/ATAPI	
	Dimensions (WxHxD)	(15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in))	
	Disc Capacity	DVD-ROM Single layer: Up to 4.7 GB Double layer: Up to 8.5 GB	
	Access Times	DVD-ROM Single Layer	< 140 ms (typical)
		CD-ROM Mode 1	< 125 ms (typical)
		Full Stroke DVD	< 250 ms (seek)
		Full Stroke CD	< 210 ms (seek)
	Power	Source	SATA DC power receptacle
		DC Power Requirements	5 VDC \pm 5%-100 mV ripple p-p 12 VDC \pm 5%-200 mV ripple p-p
		DC Current	5 VDC - <1000 mA typical, < 1600 mA maximum 12 VDC - < 600 mA typical, < 1400 mA maximum
	Operating Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
		Relative Humidity	10% to 90%
		Maximum Wet Bulb Temperature	86° F (30° C)
Operating Systems Supported	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation, Removed reference to "Novell" because of acquisition and changed product reference to "SUSE Linux Enterprise Desktop 10 & 11", No driver is required for this device. Native support is provided by the operating system.		

Technical Specifications - Optical and Removable Storage

HP DVD+/-RW Drive	Description	5.25-inch, half-height, tray-load
	Mounting Orientation	Either horizontal or vertical
	Interface Type	SATA/ATAPI
	Dimensions (WxHxD)	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)
	Supported Media Types	DVD-RAM DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R DVD-RW CD-R CD-RW
	Disc Capacity	DVD-ROM 8.5 GB DL or 4.7 GB standard
	Access Times	Full Stroke DVD < 250 ms (seek) Full Stroke CD < 210 ms (seek)
	Maximum Data Transfer Rates	CD ROM Read CD-ROM, CD-R Up to 40X CD-RW Up to 32X DVD ROM Read DVD-RAM Up to 12X DVD+RW Up to 8X DVD-RW Up to 8X DVD+R DL Up to 8X DVD-R DL Up to 8X DVD-ROM Up to 16X DVD-ROM DL Up to 8X DVD+R Up to 16X DVD-R Up to 16X
	Power	Source SATA DC power receptacle DC Power Requirements 5 VDC ± 5%-100 mV ripple p-p 12 VDC ± 5%-200 mV ripple p-p DC Current 5 VDC -<1000 mA typical, <1600 mA maximum 12 VDC -<600 mA typical, <1400 mA maximum
	Operating Environmental (all conditions non-condensing)	Temperature 41° to 122° F (5° to 50° C) Relative Humidity 10% to 90% Maximum Wet Bulb Temperature 86° F (30° C)
	Operating Systems Supported	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation SUSE Linux Enterprise Desktop 10 & 11
	Kit Contents	HP SATA SuperMulti DVD Writer Drive, Roxio Easy Media Creator software, Intervideo WinDVD Software, installation guide, and DVD+R media.

Technical Specifications - Optical and Removable Storage

HP Blu-ray Writer	Description	5.25-inch, half-height, tray-load	
	Mounting Orientation	Either horizontal or vertical	
	Interface Type	SATA	
	Dimensions (WxHxD)	15.0 x 4.4 x 20.3 cm (5.9 x 1.7 x 8.0 in)	
	Supported Media Types	BD-ROM BD-R BD-RE DVD-RAM DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R DVD-RW CD-R CD-RW	
	Disc Capacity	DVD-ROM 8.5 GB DL or 4.7 GB standard Blu-ray 50 GB DL or 25 GB standard	
	Access Times	Full Stroke DVD	< 250 ms (seek)
		Full Stroke CD	< 210 ms (seek)
		Blu-ray	< 275 ms (seek)
		Startup Time	(Time to drive ready from tray loading) BD-ROM (SL/DL) 25S / 28S BD-R (SL/DL) 25S / 28S BD-RE (SL/DL) 25S / 28S DVD-ROM (SL/DL) 18S / 18S DVD-R (SL/DL) 25S / 25S DVD-RW 25S DVD+R (SL/DL) 25S / 25S DVD+RW 25S DVD-RAM 45S CD-ROM 15S
Maximum Data Transfer Rates	CD ROM Read	CD-ROM Up to 40X CD-R Up to 40X CD-RW Up to 40X	
	DVD ROM Read	DVD-RAM Up to 5X DVD+RW Up to 10X DVD-RW Up to 10X DVD+R DL Up to 8X DVD-R DL Up to 8X DVD-ROM Up to 16X DVD-ROM DL Up to 8X DVD+R Up to 12X DVD-R Up to 12X	

Technical Specifications - Optical and Removable Storage

	Blu-ray	BD-ROM Up to 6X BD-ROM DL Up to 4.8X BD-R Up to 6X BD-R DL Up to 4.8X BD-R Up to 6X BD-RE SL/DL Up to 4.8X
Power	Source	SATA DC power receptacle
	DC Power Requirements	5 VDC \pm 5%-100 mV ripple p-p 12 VDC \pm 10%-100 mV ripple p-p
	DC Current	5 VDC -900 mA typical, 1200 mA maximum 12 VDC -1000 mA typical, 1600 mA maximum
Operating Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative Humidity	15% to 80%
	Maximum Wet Bulb Temperature	86° F (30° C)
Operating Systems Supported		Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation, SUSE Linux Enterprise Desktop 10 & 11
		<p>* No driver is required for this device. Native support is provided by the operating system.</p> <p>** RHEL WS4 not supported on Z200/Z200SFF</p>
Kit Contents		HP Blue Laser RW Drive, Roxio Easy Media Creator software, Intervideo WinDVD Software, installation guide.
Disclaimer		As Blu-ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.

Technical Specifications - Optical and Removable Storage

HP 22-in-1 Media Card Reader	Description	The Media Card Reader device uses the same physical form factor and mounting as a Floppy Disk Drive. The device connects to a 2x5 two-channel USB header on the motherboard of the system. There is no USB controller card provided. Please see the Disc Formats section below for a list of flash memory card formats that are supported.
	Mounting Orientation	The Media Card Reader can be mounted in a dedicated Floppy Drive bay (if the chassis provides one) or in an appropriate Optical Bay adapter. It will operate in any orientation.
	Interface Type	USB 2.0 (one channel dedicated to the separate USB port; one channel dedicated to the flash memory card slots)
	Dimensions (WxHxD)	124.5 x 101.6 x 25.4 mm (4.9 x 4.0 x 1.0 in)
	Supported Media Types	Picture Micro SD Micro SDHC SD SDHC SDXC Mini SD Mini SDHC MultiMediaCard Reduced Size MultiMediaCard (RS MultiMediaCard) MultiMedia Card 4.2 (MultiMediaCard Plus, including MultiMediaCard Plus HC) Reduced Size MultiMedia Card 4.2 (MultiMediaCard Mobile, including MultiMediaCard Mobile HC) CompactFlash Card Type I CompactFlash Card Type II MicroDrive Memory Stick (MS) MagicGate Memory Stick (MG) MagicGate Memory Stick Duo Memory Stick Select Memory Stick Duo (MS Duo) Memory Stick PRO (MS PRO) Memory Stick PRO Duo (MS PRO Duo) Memory Stick PRO-HG Duo Two additional formats are usable with adapters (not supplied): MultiMediaCard Micro Memory Stick Micro (M2)

Technical Specifications - Controller Cards

HP USB 3.0 2x2 Port SuperSpeed PCIe x1 Card	Dimensions (HxD)	TBD
	Ports	2 External, 2 internal
	Operating Systems Supported	Microsoft Windows 7, Windows Vista*, Windows XP Professional (32-bit and 64-bit); Red Hat Enterprise Linux 6, SUSE Linux Enterprise Desktop 11 Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: http://www.windowsvista.com/upgradeadvisor . For Windows Vista system requirements, visit: http://www.windowsvista.com/systemrequirements .
	Kit Contents	I/O and Security Software and Documentation CD with software drivers and documentation, HP SuperSpeed USB 3.0 PCIe x1 card (with full-height expansion bracket attached), SATA to SATA split power extension cable, Low profile expansion bracket to replace the full-height expansion bracket required on some computer models and HP SuperSpeed USB 3.0 PCIe x1 Card Quick Setup.
	Regulatory Approvals and registrations	FCC 15B, CE EN55022+ EN55024, VCCI, CISPR 22 AS/NZS CISPR 22, LCIE CB service(ITE/AV) IEC 60950-1, Korea EMC, UL USB-IF
	Weight	0.21 lb (95.0 g)
	Warranty	The HP USB 3.0 2x2 Port Super Speed PCIe x1 Card has either a one-year limited warranty or the remainder of the warranty of the HP product in which it is installed. Technical support is available seven days a week, 24 hours a day, by phone, as well as online support forums. Certain restrictions and exclusions apply.

Technical Specifications - Networking and Communications

Integrated Intel 82579LM PCIe GbE Controller	Connector	RJ-45
	Controller	Intel 82579LM GbE platform LAN connect networking controller
	Memory	24 KB FIFO packet buffer memory
	Data Rates Supported	10/100/1000 Mbps
	Compliance	802.1P, 802.1Q, 802.2, 802.3, 802.3ab, 802.3az, 802.3u
	Bus Architecture	PCI Express and SMBus
	Data Transfer Mode	PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic (Sx low power state)
	Power Requirement	Requires 3.3V and 1.05V or just 3.3V with integrated regulators
	Boot ROM Support	Yes
	Network Transfer Mode	Full-duplex; Half-duplex (not supported for the 1000BASE-T transceiver)
	Network Transfer Rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
	Management Capabilities	WOL, auto MDI crossover, PXE, Multi-port teaming, RSS, Advanced cable diagnostic. AMT 7.0 support

Intel Gigabit CT Desktop NIC	Connector	RJ-45
	Controller	Intel WG82574L Gigabit Ethernet Controller
	Memory	Integrated Dual 48K configurable transmit receive FIFO Buffers
	Data Rates Supported	10/100/1000 Mb/s
	Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
	Bus Architecture	PCI-E 1.0a
	Data Path Width	X1, 250 MB/s, Bi-directional interface
	Data Transfer Mode	Bus-master DMA
	Hardware Certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power Requirement	Aux 3.3V, 3.0 Watts in 1000base-T and 2.0 Watts in 100Base-T
	Boot ROM Support	Yes
	Network Transfer Rate	10BASE-T (half-duplex) 10 Mb/s 10BASE-T (full-duplex) 20 Mb/s 100BASE-TX (half-duplex) 100 Mb/s 100BASE-TX (full-duplex) 200 Mb/s 1000BASE-T (full-duplex) 2000 Mb/s
	Operating Temperature	32° to 131°F (0° to 55°C)
Operating Humidity	85% at 131°F (55°C)	
Dimensions (H x W x D)	12.1 x 5.7 x 2.0 cm (4.75 x 2.25 x 0.8 in)	

Technical Specifications - Networking and Communications

Operating System Driver Support	Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64, Windows Vista Business 32, Windows XP Professional, Windows XP x64. Red Hat Enterprise Linux 4 (RHEL4.8 or newer)*, Red Hat Enterprise Linux 5 (RHEL5.3 or newer), Red Hat Enterprise Linux 6, SUSE Linux Enterprise Desktop (SLED) 11
	RHEL 4 and 5, SLED 10, are not supported on the Z220 CMT/SFF
Management Capabilities	WOL , PXE, DMI, WFM 2.0
Kit Contents	Intel Gigabit CT Desktop NIC, low profile bracket, CD containing Intel PROset II NIC drivers, quick install guide, product warranty statement

Broadcom (5761) NetXtreme Gigabit Ethernet Plus NIC

Connector	RJ-45
Controller	Broadcom 5761 PCI-Express LAN Controller
Memory	8 MB NVRAM serial Flash
Data Rates Supported	10/100/1000 Mbps
Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB, 802.3u, and 802.3x
Bus Architecture	PCI-Express
Data Path Width	Single Channel PCI-Express
Data Transfer Mode	Bus Master DMA
Hardware Certifications	FCC class B, Canada and US NRTL Mark, C-Tick for Australia, BSMI for Taiwan, VCCI for Japan, MIC for Korea, GOST for Russia, UL listed (E212044), European Union Notice (CE 0682)
Power Requirement	1.8W @ 3.3V
Boot ROM Support	Yes
Network Transfer Mode	Full-duplex Half-duplex (not available for the 1000BASE-T transceiver)
Network Transfer Rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
Operating Temperature	32° to 131°F (0° to 55° C)
Operating Humidity	131° F (55° C) with 5% to 95% non-condensing humidity
Dimensions	7 cm x 10.5 cm (2.75 in x 4.13 in), low profile compatible
Operating System Driver Support	Windows 7 Professional 32-bit and 64-bit, Windows Vista 32-bit SP1, Windows Vista x64 SP1, Windows XP 32 bit professional, Windows XP x64 Red Hat Enterprise Linux (RHEL) 5, 6; Novell SLED 10 & 11
Management Capabilities	ACPI, WOL and DMI 2.0, PXE 2.0, WfM 2.0, Broadcom mgmt utility, ASF2.0, DASH 1.0 and DASH 1.1 profiles
Kit Contents	Broadcom NetXtreme Gigabit Ethernet Plus NIC, Broadcom NetXtreme Gigabit Ethernet Plus NIC USB Cable Assembly, CD, drivers, quick install guide, product warranty statement

Technical Specifications - Networking and Communications

© 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Xeon are trademarks of Intel Corporation in the U.S. and other countries. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. Windows 7 and Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries.