

Make Your Event Dynamic / Z-1500II Fog Machine

Antari proposes to you the Z-1500II, the rigorous research and development resulting stability, durability, and reliability. When it comes to ultimate performance and precision control, the Z-1500II will suit virtually any applications.

These fog machine provide significant advantages in a wide array of applications where volume of fog output is critical. Around 25% electricity is saved due to high efficient power control system allowing the fogger to operate at low-level temperature.

An electronic low fluid detector is also installed which automatically weakens pump power and stops pumping when running-out of fluid. They are fully controllable via Z-20 LCD control module supplied allowing the operator to set the volume control and timing precisely to the exact percentage from 1% to 100% output. DMX connection can be worked by either 3 or 5 pin connector.

These machines are Antari' s proud innovation; they are dedicated to most demanding professionals. Ideal for very large venues, outdoor event, movie production or for fire training concept.

Specification

- Voltage : U.S. version : 120 Volt
Europe version : 230 Volt
U.K. version : 240 Volt
Japan version : 100 Volt
- Heater : 1,500 W
- Output : 20,000 cu.ft / min
- First Heat-up Time : 8.5 min
- Tank Capacity : 6 liter
- Fluid Consumption Rate : 9 min / liter (100% Output)
- Remote Included : Z-20 Control Module
- Optional Remotes : Z-30PRO Wireless Control Module
- Weight : 14 Kg
- Dimensions (mm) : L 688 x W 285 x H 188
- DMX : On board
- Liquid Used : Antari FLR / FLG Liquid



• Z-1500II Effect



• Z-20 Control Module



• Z-30PRO Wireless Control Module (Optional)



• FLR-5 Light Fog Liquid
• FLG-5 Heavy Fog Liquid

Z Series II
Ideal Fog