

# Delock Audio Converter Digital > Analogue

## Description

The Delock audio converter changes your digital signal into an analogue stereo signal. At the input port of the device you can connect e. g. your digital DVD or Blu-ray player to input the digital signal whether optical via Toslink or via coaxial connection. At the output port the analogue signal will be transmitted through the RCA connection to the analogue device.



## Specification

- Connector:
  - Input: 1 x Toslink S/PDIF
  - 1 x Coaxial S/PDIF
  - Output: 2 x RCA red / white
  - 1 x DC power supply connector 5 V
- Electromagnetic-noise-free transmission
- Supports different audio rates, e. g. 32, 44.1, 48 and 96 KHz
- Dimension (LxWxH): ca. 63 x 41 x 21 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A
- Output: 5 V / 2 A
- Ground outside, plus inside
- Dimensions:
  - inside:  $\varnothing$  ca. 2.1 mm
  - outside:  $\varnothing$  ca. 5.5 mm
  - length: ca. 9 mm

## System requirements

- Digital audio signal
- Connection cables

## Item No. 62444



EAN 4043619624447

Country of origin China

## Package content

- Converter digital > analogue
- Power supply
- User manual

## Package

- White Box

## Images

