

PRODUCT CATALOGUE AND PRICE LIST 07-2019



ALL PRODUCTS IN THIS CATALOGUE ARE MANUFACTURED IN BELGIUM BY



Labelmate
Chaussée de Ruisbroek 290
1620 Drogenbos (Belgium)

+32 2 375 69 60
brussels@labelmate.com
BTW BE 0674 877 993

ING BELGIUM
IBAN BE89 3630 6607 1285
BIC BBRUBEBB

labelmate.com



End user Prices as of 07/2019

LABEL DISPENSERS

CHOOSING THE RIGHT DISPENSER	3
LD-RS & LD-U POWERED LABEL DISPENSERS.....	5

LABEL REWINDERS

Zero Tension Loop Controlled Label Rewinder ZCAT.....	9
Choosing the right CAT Rewinder	11
Heavy-Duty CAT- Label Rewinders	12
Low-Cost Mini-CAT Label Rewinders.....	16
Mini-CAT Integrated.....	18
TWIN-CAT-2 Dual Spindle Unwind / Rewind Stations.....	19

LABEL UNWINDERS

Choosing the right Unwinder	22
UCAT Heavy-Duty Label Unwinders	24

"QUICK-CHUCKS"™ & VANES

QUICK-CHUCKS™ Quick-Loading Core Chucks & VANES.....	27
---	-----------

LABEL SLITTERS & SLITTING STATIONS

Heavy-Duty Label Slitters & Slitting Stations.....	29
SP Label Separator Plates for Slitters	32

LABEL COUNTING SYSTEMS

RRC-330 Reel-to-Reel Counting Systems.....	33
COUNT Heavy-Duty Label Counters	35

LABEL PRINT MECHANISMS

PM-300-LS & PM-300-HS Reel-to-Reel Label Printer Mechanism for Inkjet and Laser Heads	37
PM-300-CS Constant Speed Reel-to-Reel Label Printer Mechanism for Inkjet and Laser Heads	38
PM-300-CS-STEP Reel-to-Reel Constant Speed System	39



Labelmate
Chaussée de Ruisbroek 290
1620 Drogenbos (Belgium)

+32 2 375 69 60
brussels@labelmate.com
BTW BE 0674 877 993

ING BELGIUM
IBAN BE89 3630 6607 1285
BIC BBRUBEBB

labelmate.com

IMPORTANT INFORMATION

At Labelmate, we do not settle for "good enough". We strive to make the best products, with high quality components, ensuring your Labelmate product will perform for many years. Our unmatched Warranty Program makes this statement tangible!

All Labelmate Products are warranted to the original end-user customer to be free from defects in materials and workmanship. If it is determined by Labelmate that a product has failed under the terms of this warranty, the product will be repaired or replaced at no charge to the customer. Labelmate reserves all rights to determination of coverage and liability under this warranty. The warranty period for all new Labelmate products is outlined below:

Warranty Period

Products Covered

5 years

Label Rewinders
Label Unwinders

3 years

Label Counters & Slitters (mechanical parts only)
Label Dispensers
Printer mechanisms

1 year

Power Supply Modules
Counter Modules
Encoders
Any products not specified above


- Any device returned for repair or exchange must have an RMA form.
- If you made a mistake in your order, don't worry, we will help you out. However, we will charge a restocking & repacking fee of 15% with a minimum of 25 Euros.
- Prices are in Euros, Ex-Works shipping point. **PRICES DO NOT INCLUDE DELIVERY COSTS.** Shipping is done with UPS Standard Service unless specified otherwise in the order.
- Drop-shipments (delivery directly to your customer) are possible at the cost of 12 euro, not including the UPS Shipment Cost.
- For orders below 100 euro (delivery cost not included) we will bring a cost of 12 euro into account
- Prices and specifications are subject to change without notice & pictures are non-contractual

WHAT'S NEW IN THIS CATALOGUE?


- The new LD-300-XX Dispensers: perfect for labels up to A4 size wide.
- The new entry-level UCAT-S-MINI label unwinder, for rolls of max 220mm and 125mm wide.
- New pricing for the PM-300-CS and PM-300-CS-STEP
- Several new and exciting products coming up in the next months, so stay tuned !



CHOOSING THE RIGHT DISPENSER




COUNTING OPTIONS



*The Pre-set counter stops the dispenser when pre-set count is reached.



CHOOSING THE RIGHT DISPENSER (Cont.)



“LD-RS & LD-U” POWERED LABEL DISPENSERS

The LD-RS Type Automatic Label Dispensers for all regular labels (not for transparent or black labels).

The LD-100/200/300-RS Label Dispensers offer state of the art convenience and durability. Using the latest opto-electronic technology, they are incredibly easy to setup!

A special Reflective Sensor sits below the label and reliably and accurately senses the leading edge of your label. As you pick up a label the next one is automatically and instantly advanced. The modern design presents the label right at the front of the machine, providing optimum convenience for both left-handed and right-handed operators. A “HIGH-LOW” Speed Switch allows adjustment for label length or operator preference. As there are no mechanical position switches to cause adjustment or operational problems, the heavy-duty product design will stand up to the most demanding environments.

The LD-U Type Automatic Label Dispensers are using a “state of the art” reflective detector that allows the machine to dispense all types of labels, including transparent and black labels.

The LD-U range is using a compact photoelectric sensor with optic-fibre cable. The LD-100/200/300-U offer the same advantages, convenience and durability as the popular LD-RS models with the extra benefit of dispensing any kind of labels.

Both models of LD-RS and LD-U are available in "SS" version, that features a stainless-steel chassis and cover that can be used in humid environments. They are ideal for the food & beverage industry, chemical and pharmaceutical applications.

The LD-S Type for very small, long or unusual shape labels.

The LD-100S or LD-200S do not have a sensor detection; the foot pedal allows you to continually advance labels at the rate you choose. The LD-100S and LD-200S also include an ON-OFF Foot Switch for production applications. It is ideal for very small or long labels.

All LABELMATE Label Dispensers are easy to set up: just slide your roll of labels onto the built-in Core Holder, thread the label web through to the take-up spindle and your Label Dispenser is ready for use! Rugged, heavy-gauge steel construction and precision parts yield products of the highest quality. Designed for all-day, every-day use, these Dispensers are backed by LABELMATE's famous [3-Year Parts and Labour Limited Warranty](#) (1-Year on power supplies), assuring you trouble-free performance.

Check-out the Label-Dispenser video on our website: www.labelmate.com





LD-100-RS



LD-100-U-SS



LD-200-U



LD-200-S



LD-100-RS- with AWB



LD-100-RS with flanges 220



NEW

LD-300-RS-SS



P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	LABEL LENGTH (mm)	SPEED (cm/sec)	PRICE EURO
LMD001	LD-100-RS	Automatically advances the next label ready to pick. Fast label loading. Quick and convenient operation! Not for transparent labels. Size: W x D x H: 210 x 200 x 270 mm.	Up to 115	6 to 150*	11 Minimum	565 €
LMD002	LD-200-RS	Same features as LD-100-RS but with wider label capacity. Size: W x D x H: 270 x 200 x 270 mm.	Up to 165	6 to 150*	11 Minimum	620 €
LMD003	LD-100-RS-SS	Same features as LD-100-RS but in stainless steel. Size: W x D x H: 210 x 200 x 270 mm.	Up to 115	6 to 150*	11 Minimum	690 €
LMD004	LD-200-RS-SS	Same features as LD-200-RS but in stainless steel. Size: W x D x H: 270 x 200 x 270 mm.	Up to 165	6 to 150*	11 Minimum	745 €
LMD014	LD-300-RS-SS	Same features as LD-200-RS but in stainless steel and wider capacity Size: W x D x H: 300 x 250 x 295 mm.	Up to 218	6 to 300	11 Minimum	820 €

LMD005	LD-100-U	Automatically advances the next label ready to pick. Fast label loading. Quick and convenient operation! For transparent and black labels. Size: W x D x H: 210 x 200 x 270 mm.	Up to 115	20 to 150	11 Minimum	665 €
LMD006	LD-200-U	Same features as LD-100-U but with wider label capacity. Size: W x D x H: 270 x 200 x 270 mm.	Up to 165	20 to 150	11 Minimum	720 €
LMD007	LD-100-U-SS	Same features as LD-100-U but in stainless steel. Size: W x D x H: 210 x 200 x 270 mm.	Up to 115	20 to 150	11 Minimum	790 €
LMD008	LD-200-U-SS	Same features as LD-200-U but in stainless steel. Size: W x D x H: 270 x 200 x 270 mm.	Up to 165	20 to 150	11 Minimum	845 €
LMD016	LD-300-U-SS	Same features as LD-200-RS but in stainless steel and wider capacity Size: W x D x H: 300 x 250 x 295 mm.	Up to 218	6 to 300	11 Minimum	920 €

LMD009	LD-100S	Label Dispenser with variable speed control and foot switch. Ideal for very small or long labels. Size: W x D x H: 210 x 200 x 270 mm.	Up to 115	5 to unlim.	11 Minimum	640 €
LMD010	LD-200S	Same features as LD-100S but with wider label capacity. Size: W x D x H: 270 x 200 x 270 mm.	Up to 165	5 to unlim.	11 Minimum	720 €

Our Label Dispensers (except with AWB option) are equipped with 38mm core holders that accept all cores from 40 to 76mm.

External roll diameter:

- Standard : 220mm (300 mm on LD-300-XX models)
- With AWB option : 265mm
- With LD-DE option: 300mm (not available on LD-300-XX models)

MAXIMUM LABEL ROLL WEIGHT: 6 KG



LABEL DISPENSERS OPTIONS

P/N	MODEL	DESCRIPTION	ROLL DIAM (mm)	SPEED (cm/sec)	PRICE EURO
LMX445	C-1	Counter option for all Label Dispensers LD-U & LD-RS & SS	-	-	150 €
LMX446	PC-1	Pre-set counter that will stop the label dispenser after a pre-set count is reached. Factory installed	-	-	389 €
LMX447	LD-AWB	Adjustable "wearless" brake system. Available on all LD-100/200 models. Allows varying the roll tension to facilitate peeling of the labels. Increases the maximum roll diameter to 265 mm. 76mm standard. Available on request in 38, 40, 44, 50, 70 or 100mm. * Factory installed - replaces the standard nylon shaft.	265	-	95 €
LMX448	LD-FLANGES-220	Inner and outer Flange option for Label Dispenser (per pair). Fits all models (<i>not compatible with LD-AWB</i>). Recommended for narrow labels.	220	-	24 €
LMX449	LD-FLANGES-300	Inner and outer Flange option for Label Dispenser (per pair). Fits all models (<i>not compatible with LD-AWB</i>). To be used with LD-DE or on LD-300-models. Recommended for narrow labels.	300	-	39 €
LMX366	LD-DE	Diameter extension for LD-100/200: Allows using rolls with outer diameters up to 300mm (factory installed).	300	-	25 €
LMX367	LD-DE-SS	Diameter extension for LD-100/200: Allows using rolls with outer diameters up to 300mm (factory installed). Stainless steel version.	300	-	25 €
LMX472	FOOT SWITCH	To start and stop the dispenser. <i>Included with LD-100S and LD-200S.</i> Available for RS and U models only if combined with Ext. Command option.	-	-	80€
LMX537	PS-15V	220-240V – 50Hz DC Power Supply for LD. Output: 15V – 4.33A. <i>Included with LD.</i>	-	-	40 €
LMX537-UK	PS-15V-UK	220-240V – 50Hz DC Power Supply for LD. Output: 15V – 4.33A. <i>UK PLUG</i>	-	-	40 €
LMX056	PS-18V	High-speed power supply to increase speed of the dispenser.	-	14 Minimum	80 €
LMX450	EXT. COMMAND	The LD dispenses one label when receives a signal (contact closure). Factory installed. Only for LD-RS / LD-U models.	-	-	80 €
LMX451	BATTERY PACK	Complete kit to operate the LD on a battery. Includes: battery, charger and cables. Replace the standard power supply. Battery works for +/- 8 hours and needs 8 hours to re-charge. Output: DC 12V.	-	-	325 €

Shipping Weight: Approximately 6 to 8 Kg.

Power: 220/240-vac 50-Hz. 120-vac 60-Hz power supply is also available.



Zero Tension Loop Controlled Label Rewinder ZCAT

The revolutionary new ZCAT Zero Tension Loop Rewinder is the ideal solution for colour inkjet printers, printers that back-feed, as well as for extremely sensitive printers that cannot tolerate any rewind force without causing undesirable registration or artifact problems. A free-hanging “loop” of label stock is created between the printer and the Tensioning Roller of the ZCAT thereby eliminating all tension whatsoever on the printer. A special chassis mounted photo-detector starts and stops the rewinding action based on the optimum depth of the loop. Fully adjustable tension exists between the Tensioning Roller and the Rewinder thus yielding a consistent and tightly wound finished roll.

With an unmatched 5-Year Parts and Labor Limited Warranty, the ZCAT is designed for worry-free 24/7 operation.

P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	ROLL DIAM (mm)	SPEED* (cm/sec)	PRICE EURO
LMR035	ZCAT-6-R/L	Heavy-duty Label Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core: 76mm Rewind direction: Right to left. Size: W x D x H: 483 x 381 x 400mm	170	300	125	1345 €
LMR036	ZCAT-6-L/R	Heavy-duty Label Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core 76mm Rewind direction: Left to Right. Size: W x D x H: 483 x 381 x 400mm	170	300	125	1345 €
LMR037	ZCAT-8-R/L	Heavy-duty Label Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core 76mm Rewind direction: Right to left. Size: W x D x H: 483 x 381 x 400mm	220	300	125	1395 €
LMR038	ZCAT-8-L/R	Heavy-duty Label Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core 76mm Rewind direction: Left to Right. Size: W x D x H: 483 x 381 x 400mm	220	300	125	1395 €
LMR039	ZCAT-10-R/L	Heavy-duty Label Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core 76mm Rewind direction: Right to Left Size: W x D x H: 483 x 381 x 400mm	255	300	125	1545 €
LMR040	ZCAT-10-L/R	Heavy-duty Label Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core 76mm Rewind direction: Left to Right. Size: W x D x H: 483 x 381 x 400mm	255	300	125	1545 €

MAXIMUM LABEL ROLL WEIGHT: 9KG

* maximum speed at beginning of a 76mm core roll.



ZCAT Options

P/N	MODEL	DESCRIPTION	PRICE EURO
LMX537	PS-15V	220-240V – 50Hz DC Power Supply for ZCAT. Output: 15V – 4.33A. <i>Included with the unit</i>	40 €
LMX537-UK	PS-15V-UK	220-240V – 50Hz DC Power Supply for ZCAT. Output: 15V – 4.33A. <i>UK PLUG</i>	40 €
LMX508	Optional 300mm outer Flange for Quick-Chuck. Ideal for narrow labels.		48 €
LMX549	PC-4	Optional 6-digit pre-set Counter. Allows to count labels or show instantaneous web speed. Factory installed.**	389 €
LMX553	6" PAPER LOOP GUIDE	6" Paper-loop-guide: for guiding thick or curling media into a loop for ZCAT 6	39 €
LMX554	8" PAPER LOOP GUIDE	8" Paper-loop-guide: for guiding thick or curling media into a loop for ZCAT8/10	52 €


** To be ordered with a ZCAT unit: eg.: LMR036/LMX549



ZCAT-6-R/L




PAPER PATH



ZCAT-6-L/R

Choosing the right CAT-3 or CAT-4 Rewinder *



Heavy-Duty “CAT” Label Rewinders

LABELMATE's Constant Adjustable Torque™ (“CAT”) technology has made the silent, easy-to-use CAT-3 & CAT-4 the "Industry Standard" Label Rewinder. There are no awkward troublesome belts or clutches.

The CAT-3 Heavy-Duty Label Rewinders

The CAT-3-STANDARD handles labels up to 155 mm wide and will wind a roll of labels up to a 300 mm diameter. Torque and Direction are fully controllable from the Control Panel. Dual torque ranges provide plenty of power for use with a LABELMATE Slitter, too. For wider labels up to 255 mm (10”), choose the CAT-3-10-INCHES.

Model CAT-3-ACH includes an Adjustable Core Holder that accepts any core size from 25 mm to 101 mm in diameter and up to 155 mm in width.

The CAT-3-CHUCK includes LABELMATE's durable "Quick-Chuck"™ quick-locking Core Chuck, permitting the fastest loading and unloading of cores and label rolls.

The CAT-40G is gear motor driven for more torque. It accepts bigger rolls with a diameter up to 400 mm. It is equipped with the LABELMATE "Quick-Chuck"™ quick-locking Core Chuck.

Please note that if to be used in combination with a printer, you need the CAT-40G-TA.

The CAT-3-TA Heavy-Duty Label Rewinders

The CAT-3-TA is a CAT-3 with tension arm specially engineered for applications that require fixed web tension. The TA is available for all models of CAT-3.

IMPORTANT NOTE: The CAT-3-TA can be also be used as a regular CAT-3 with the same features.

Rugged, heavy-gauge steel construction allows your CAT-3 / CAT-3-TA Rewinder to be simply set in place.

Special anti-slip feet keep the unit from moving

The CAT-4 Rewinders with Versatile Control Input and Optional Start Delay

Created to extend the capabilities of our heavy-duty rewriter range, the CAT-4 can be controlled by the printer through the external control input. More and more printers offer the required signal as a standard feature. Ideally, the printer should activate the rewriter only when printing or feeding forward. The CAT-4 can react to different types of signals provided by the printer. The selection of the signal nature is done via 3 jumpers on the internal PCB. Four modes are selectable: Open Collector High Active, Open Collector Low Active, Logic Level High Active (Max 10VDC) & Logic Level Low Active (Max 10VDC).

The factory setting is “Open Collector High”. Other default setting on request.

The CAT-4 offers also an optional adjustable Start Delay to allow the printer to execute back-feed without resistance from the rewriter. The CAT-4 has a 3-position torque switch (compared to 2 on the CAT-3). Together with the speed adjustment, it allows the user to control the tightness of the rewound rolls. The absence of a tension arm allows better rewound rolls and increases the overall reliability of the rewriter.

For applications where the tension arm is required, the CAT-3-TA will be recommended.

Reliable, high quality and maintenance-free, the Heavy-Duty CAT-4 / CAT-3 / CAT-3-TA Label Rewinders feature a [5-Year Parts and Labour Limited Warranty](#) (1-Year on power supplies), the longest in the industry.

Check-out the CAT-Label- Rewinders video on our website: www.labelmate.com



LMR004	CAT-3-STANDARD	The 'Industry Standard' Heavy-duty Label Rewinder. 76mm standard.* Size: W x D x H: 300 x 350 x 320 mm.	155	300	125	682 €
LMR005	CAT-3-ACH	CAT-3 with an Adjustable Core Holder for any core size from 25 to 101mm in diameter. With inner flange. Use APG-CAT if you wish to also guide the outer edge of your label. Size: W x D x H: 280 x 310 x 310 mm.	155	280	125	744 €
LMR006	CAT-3-CHUCK	The industry standard Heavy-duty Label Rewinder with an easy-loading 'Quick-Chuck'. Ideal for production work. 76mm standard.* Size: W x D x H: 300 x 385 x 320 mm.	170	300	125	892 €
LMR007	CAT-3-10-INCHES	CAT-3 for labels up to 255mm wide. 76mm standard; 38, 40, 44 or 70mm on request. Size: W x D x H: 300 x 455 x 320 mm.	255	300	125	756 €
LMR008	CAT-3-1-INCH	CAT-3 for 25.4mm diameter cores. Size: W x D x H: 220 x 350 x 280 mm.	155	220	125	682 €
LMR009	CAT-40G	Gear motor driven. Tight rewind up to 400mm. 76mm 'Quick-Chuck' standard.* Size: W x D x H: 400 x 450 x 460 mm.	170	400	38	1250 €

LMR010	CAT-3-TA-STANDARD	Same features as CAT-3-STANDARD but with Tension Arm.	155	300	125	832 €
LMR011	CAT-3-TA-ACH	Same features as CAT-3-ACH but with Tension Arm.	155	280	125	894 €
LMR012	CAT-3-TA-CHUCK	Same features as CAT-3-CHUCK but with Tension Arm.	170	300	125	1042 €
LMR013	CAT-3-TA-10-INCHES	Same features as CAT-3-10-INCHES but with Tension Arm.	255	300	125	906 €
LMR014	CAT-3-TA-1-INCH	Same features as CAT-3-1-INCH but with Tension Arm.	155	220	125	832 €
LMR015	CAT-40G-TA	Same features as CAT-40G but with Tension Arm.	170	400	38	1400 €



CAT-3-STANDARD



CAT-3-ACH



CAT-3-TA-CHUCK



P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	ROLL DIAM (mm)	SPEED * (cm/sec)	PRICE EURO
LMR025	CAT-4-STANDARD	Heavy-duty Label Rewinder. 76mm standard.* Size: W x D x H: 300 x 350 x 320 mm.	155	300	125	705 €
LMR026	CAT-4-ACH	CAT-4 with an Adjustable Core Holder for any core size from 25 to 101mm in diameter. With inner flange. Use APG-CAT if you wish to also guide the outer edge of your label. Size: W x D x H: 280 x 310 x 310 mm.	155	280	125	767 €
LMR027	CAT-4-CHUCK	Heavy-duty Label Rewinder with an easy-loading 'Quick-Chuck'. Ideal for production work. 76mm standard.* Size: W x D x H: 300 x 385 x 320 mm.	170	300	125	915 €
LMR028	CAT-4-10-INCHES	CAT-4 for labels up to 255mm wide. 76mm standard; 38, 40, 44 or 70mm on request. Size: W x D x H: 300 x 455 x 320 mm.	255	300	125	779 €
LMR029	CAT-4-1-INCH	CAT-4 for 25.4mm diameter cores. Size: W x D x H: 220 x 350 x 280 mm.	155	220	125	705 €

* CAT-CHUCK, Standard, CAT-40 and 10-Inches are available for 38-, 40-, 44-, 70-, 76- and 100 mm diameter cores. To order your size, please refer to p28 – “Chucks & Vanes”.

* A Second flange is included with all models except ACH and CHUCKS.

* The indicated speeds are the maximum speeds at beginning of a 76mm core roll.

MAXIMUM LABEL ROLL WEIGHT:

- **STANDARD:** 8Kg.
- **ACH:** 7Kg.
- **10-INCHES:** 10Kg.
- **CHUCK:** 10Kg
- **CAT-40G:** 14Kg.



CAT-4-ACH



CAT-4 REAR PANNEL



LABEL REWINDERS CAT-4 / CAT-3 / CAT-3-TA OPTIONS

P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	PRICE EURO
LMX444	APG-CAT / UCAT	Optional Adjustable Paper Guide For CAT-(TA)-ACH or CAT-(TA)-CHUCK. Guides the outer edge of the label web to ensure an even roll edge.	-	34 €
LMX489	FLANGE-CAT-INT	Internal flange for CAT-(TA)-STANDARD and CAT-(TA)-10-INCHES (also for TA models). Diam. 300 mm.	-	30 €
LMX490	FLANGE-CAT-EXT	External flange for CAT-(TA)-STANDARD and CAT-(TA)-10-INCHES (also for TA models). Diam. 300 mm.	-	30 €
LMX491	STANDARD SHAFT	Standard shaft for CAT-(TA) with vanes, internal and external flanges.	155	106 €
LMX492	10" SHAFT	10-Inches shaft for CAT (-TA) with vanes, internal and external flanges.	255	138 €
LMX500	ACH-CAT	Adjustable Core Holder for any core size from 25 to 101mm in diameter. With inner flange.	155	145 €
LMX501	BAIL STD	For rewind on shaft, no core is needed.	-	15 €
LMX502	BAIL 10"	For rewind on shaft on CAT-(TA)-10-INCHES, no core is needed.	-	18 €
LMX541	START DELAY	Optional Adjustable Start Delay to allow back-feed without resistance. <i>Only for CAT-4.</i>	-	25 €
LMX472	FOOT SWITCH	Foot Switch to start and stop the TWIN-CAT-2, CAT-4, CAT-3 or MC Rewinders.	-	80 €
LMX537	PS-15V	220-240V – 50Hz DC Power Supply for CAT. Output: 15V – 4.33A. Included with CAT Rewinders.	-	40 €
LMX537	PS-15V-UK	220-240V – 50Hz DC Power Supply for CAT. Output: 15V – 4.33A. UK PLUG	-	40€
LMX546	1' SHAFT	1-Inches for CAT (-TA) with vane, internal and external flanges.	155	106 €


CAT-3-10-INCHES

CAT-3-TA-ACH

CAT-40G-TA


Low-Cost “Mini-CAT” Label Rewinders

The MINI-CAT (MC) Label Rewinders are the world’s most popular low-price Label Rewinders. MC and MC+ Rewinders use LABELMATE’s proprietary Constant Adjustable Torque™ (“CAT”) technology to achieve impressive, reliable performance at an unprecedented low price. A special motor, designed specifically for the MINI-CATs, offers bi-directional operation and trouble-free performance.

Mini-CAT

Mini-CAT Rewinders are capable of rewinding label rolls up to 125mm wide (115 mm for MC-11), up to 220 mm in diameter at speeds up to 50 cm/s. The MC-10 have a 76 mm diameter vane style core holder. You can also use the included “coreless rewind” feature to rewind directly on-shaft. The MC-11 includes a precision-crafted Adjustable Core Holder that adjusts in seconds to accept any core diameter from 25- to 101-mm.

The MINI-CATs have an inner label flange to keep the edge of the label web aligned as the labels are being rewound. Also available is an optional Adjustable Paper Guide (APG-MC) that mounts directly to the rewinder base plate and guides the outer edge of the labels. The **new build-in potentiometer** allows to control the amount of rewind speed/torque. No awkward, troublesome belts or clutches are used and no speed adjustments are required.



MC-11/MC-11+ with APG



MC-11/MC-11+



MC-10/MC-10+

Mini-CAT “PLUS”

Our Mini-CAT + rewinder combines the handy size of our MC range and the functionality of our Heavy-Duty Rewinder (CAT). One main innovation makes the MC+ complete and reliable; **the external control** enables the printer to control the rewinder, activating it only when printing or feeding forward. The MC+ can react to different types of signals provided by the printer. The selection of the signal nature is done via 2 jumpers on the internal PCB. Four modes are selectable: Open Collector High Active, Open Collector Low Active, Logic Level High Active (Max 10VDC) & Logic Level Low Active (Max 10VDC).

The factory setting is “Open Collective High”. Other default setting on request.

The MINI-CAT features a [5-Year Parts and Labour Limited Warranty](#), the longest in the industry (1-year on power supply).

Check-out the MINI-CAT-Label- Rewinders video on our website: www.labelmate.com



P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	ROLL DIAM (mm)	SPEED * (cm/sec)	PRICE EURO
LMR030	MC-10+	Quality, Rewinder & Unwinder, coreless or 76mm standard. 38, 40, 44, 50, 70 or 100mm core rewinding on request. * * Bi-directional with multiple rewind force settings, build-in potentiometer and external control. Size: W x D x H: 220 x 305 x 195mm.	125	220	50	454 €
LMR031	MC-10+/1-INCH	Same as above, with a 25,4mm core.	125	220	50	454€
LMR032	MC-11+	Same as MC-10+ but with continuously Adjustable Core Holder for 25 to 101mm diameter cores. Size: W x D x H: 220 x 305 x 195mm	115	220	50	479 €
LMR001	MC-10	Quality, Rewinder & Unwinder, coreless or 76mm standard. 38, 40, 44, 50, 70 or 100mm core rewinding on request. * * Bi-directional with multiple rewind force settings. Size: W x D x H: 220 x 305 x 195mm	125	220	50	404 €
LMR002	MC-10-1-INCH	Same as above, with a 25,4mm core.	125	220	50	404 €
LMR003	MC-11	Same as MC-10 but with continuously Adjustable Core Holder for 25 to 101mm diameter cores. Size: W x D x H: 220 x 305 x 195mm	115	220	50	429 €

* SPEED: The indicated speeds are the maximum speeds at beginning of a 76mm core roll.

** To order your size, please refer to p28 – “Chucks & Vanes”.

MAXIMUM LABEL ROLL WEIGHT: 4Kg

LABEL REWINDERS MC and MC+ OPTIONS

P/N	MODEL	DESCRIPTION	PRICE EURO
LMX441	APG-MC	Adjustable Paper Guide. Guides outer edge of label to ensure an even roll edge.	32 €
LMX440	EXT. FLANGE MC-10	External flange, for MC-10 and MC-10+only. Diam. 220 mm.	30 €
LMX442	STANDARD SHAFT MC	Standard shaft for MC with vanes, bail and internal flange.	60 €
LMX443	ACH-MC	Adjustable Core Holder for any core size from 25 to 101mm in diameter. With inner flange.	145 €
LMX162	BAIL MC	Standard on MC-10 and MC-10+. For rewind on shaft, no core is needed.	8 €
LMX472	FOOT SWITCH	Foot Switch to start and stop the Rewinder. To be modified at factory.	80 €
LMX550	PS-MC-15V (NEW)	Power Supply for MC/MC+ 15V-DC. For rewinders with speed/torque control adjustment, sold as from 26.01.2018. EU Plug.	25 €
LMX551	PS-MC-15V-UK (NEW)	Power Supply for MC/MC+ 15V-DC. For rewinders with speed/torque control adjustment, sold as from 26.01.2018. UK Plug.	25 €
LMX060	PS-MC	220-240V - 50Hz Power Supply for MC with slide switch 3-11V. EU Plug. Old model.	20 €
LMX061	PS-MC-UK	220-240V - 50Hz Power Supply for MC with slide switch 3-11V. UK Plug. Old model.	20 €



MINI-CAT Integrated Rewinder



The MINI-CAT Integrated Rewinder is the perfect supplement for any desktop barcode printer, creating a stand-alone unit to print and rewind the backing paper in combination with the peel-off function of your barcode printer. Without the peel-off function, the MINI-CAT Integrated Rewinder allows to roll the printed labels on a 1" core holder.

It keeps your workplace clean and avoids backing paper falling on the ground. Cables to collect the printer power for the rewinder are available on request.

P/N	Model	Description	LABEL WIDTH (mm)	ROLL DIAM Take-up core (mm)	PRICE EURO
LMR033	MC-Integrated	Creates a roll to roll print system, on a 1" core. Size: 190 x 225mm	112	85	390€



"TWIN-CAT-2" Dual Spindle Unwind / Rewind Stations

LABELMATE's Dual-Spindle Heavy Duty Unwinder / Rewinder, the TWIN-CAT-2 has two powerful motors and your choice of core holders. You therefore have maximum versatility in setting up the operation you need. Both spindles can rewind and unwind. You control the direction and torque on each spindle independently. An External Halt Control allows you to STOP and START the TWIN-CAT-2 with a foot switch or other external device if desired. A worldwide universal switching power supply is included.

Here are some of the many possible applications:

- Unwind and Rewind labels on one machine. Ideal for "wind-in / wind-out" operations.
- Reverse the order of serialized labels on a roll.
- Conveniently rewind labels onto a different core size. With universal Adjustable Core Holders you can unwind from any diameter core and rewind onto any diameter core within the range of 25 to 101 mm in diameter! Great for production shops with varied jobs.
- Add the Label Inspection option to create a stand-alone Inspection Station. You can also add a Label Counter if you need one.
- Wind small rolls of labels from larger ones.
- Conveniently strip the unwanted matrix from die-cut labels for easy disposal as you rewind them in-line with your printer or off-line.

LABELMATE's Unwind / Rewind Stations are available in many different configurations to fit perfectly into your label production. All TWIN-CAT-2 Models operate at up to 125 cm per second.

The TWIN-CAT features a [5-Year Parts and Labour Limited Warranty](#) (1-Year on power supplies), the longest in the industry.



TWIN-CAT-2 ACH



TWIN-CAT-2 STANDARD



**TWIN-CAT-2
STANDARD/C-76170**



P/N	MODEL	DESCRIPTION	ROLL DIAM (mm)	SPEED * (cm/sec)	PRICE EURO
LMR016	TWIN-CAT-2 (BASE UNIT)	TWIN-CAT-2 base unit without any core holder. Size: W x D x H: 180 x 370 x 470 mm.	220	125	975 €

To configure your TWIN-CAT-2, please select as well 2 core holders from the list below.

“TWIN-CAT-2, [*specify FIRST Core Holder*] Upper Spindle, [*specify SECOND Core Holder*] Lower Spindle.”
Add prices of the two selected core holders to the Base Price of 975.

P/N	ADD 2 CORE HOLDERS FROM THE LIST (MIX OR MATCH)	CORE DIAMETER	LABEL WIDTH (mm)	NUMBER OF FLANGES	PRICE EURO
LMX460	1-INCH	25,4 mm (1") standard shaft and flanges.	155	2	70 €
LMX461	STANDARD	Standard shaft with vanes and flanges. Specify 38, 40, 44, 70, 76 or 100 mm.*	155	2	70 €
LMX462	10-INCHES	Standard shaft with vanes in 255 mm length and flanges. Specify 38, 40, 44, 70, 76 or 100 mm.	255	2	144 €
LMX463	ACH-TWIN (No Mix*)	Adjustable core holder shaft for cores from 25 to 101 mm. <i>*The ACH-TWIN core holder cannot be mixed with another type.</i>	155	1	170 €
LMX464	CHUCK – C-76170	Quick-Chuck shaft in 170 mm length and inner flange. Specify 38, 40, 44, 70, 76 or 100 mm.	170	1	268 €
LMX465	CHUCK – C-76220	Quick-Chuck shaft in 76 mm core diameter and 220 mm length and inner flange.	220	1	320 €
LMX466	CHUCK – C-76270	Quick-Chuck shaft in 76 mm core diameter and 270 mm length and flanges.	270	1	390 €
LMX467	CHUCK – C-100170	Quick-Chuck shaft in 100 mm core diameter and 170 mm length and inner flange.	170	1	328 €
LMX468	CHUCK – C-100220	Quick-Chuck shaft in 100 mm core diameter and 220 mm length and inner flange.	220	1	400 €
LMX469	CHUCK – C-100270	Quick-Chuck shaft in 100 mm core diameter and 270 mm length and inner flange.	270	1	450 €

* To order your size, please refer to p28 – “Chucks & Vanes”.


MAXIMUM LABEL ROLL WEIGHT: 2 x 5 Kg.

TWIN-CAT-2 LABEL INSPECTION AND COUNTER OPTIONS

The Label Inspection option, INSP-1, adds a handy Label Inspection Fixture to the side of your TWIN-CAT-2. It has two rollers over which your labels run as they are presented for inspection. You can also wind-in or wind-out at the same time as you perform the inspection operation. If you want to, when inspection is complete, you can conveniently rewind the labels back onto their original core one the same machine by just reversing the direction of the Rewind Spindles.

You can also order a PC-1 Label Counter for your inspection station. This will count the labels as they pass by a sensor mounted on the Inspection Fixture. The PC-1 counts single- or multi-across labels and you can preset a batch size. Counts up. Includes a Halt Control Cable to optionally stop your TWIN-CAT-2 automatically when your job is finished.

P/N	MODEL	DESCRIPTION	PRICE EURO
LMX470	INSP-1	Inspection Fixture mounts in minutes on the side of your TWIN-CAT-2. Includes two rollers that your labels glide over as they are presented for inspection. Bi-directional, variable speed operation allows control over winding tightness as well. Can be started and stopped with the optional Foot Switch listed below.	150 €
LMX471	INSP-1 +PC-1	Optional Preset Counter with adjustable counter sensitivity. Conveniently pre-mounted on the INSP-1 Inspection Fixture ready to plug in and use.	539 €
LMX472	FOOT SWITCH	Foot Switch to start and stop the TWIN-CAT-2.	80 €
LMX473	OUTER FLANGE TWIN QC76	220 mm outer flange for "Quick-Chuck" 76 mm core diameter.	30 €
LMX504	PS-15V	230V - 50Hz DC Heavy-Duty Power Supply. Output: 15V - 4.6A. <i>Included with TWIN-CAT-2.</i>	99 €




**TWIN-CAT-2 C-76170 / C-76170
with INSP-1 & PC-1**



TWIN-CAT-2 C-40170/C-76170



Choosing the right Unwinder




IMPORTANT INFORMATION:

1. The **UCAT-1-ACH** has an Adjustable Core Holder that accepts all core sizes from 25 to 101mm.
2. The **UCAT-3-Standard**, **UCAT-1-10-INCHES** and **UCAT-1-CHUCK** are available in various core sizes.
3. The **UCAT-1-1-INCH** is used for core diameter of 1" (25,4mm).



Choosing the right Unwinder (Cont.)



IMPORTANT INFORMATION:

1. The **UCAT-3-ACH** has an Adjustable Core Holder that accepts all core sizes from 25 to 101mm.
2. The Quick-Chuck used on the **UCAT-40** and **UCAT-3-CHUCK** is available in 3 different lengths: 170, 220 and 270mm.
3. The **UCAT-3-Standard**, **UCAT-3-10-INCHES** and **UCAT-3-CHUCK** are available in various core sizes.
4. The **UCAT-3-1-INCH** is used for core diameter of 1" (25,4mm).



“UCAT” Heavy-Duty Label Unwinders

UCAT-S and UCAT-S-MINI Heavy-Duty Unpowered Label Unwinders

This is the world's least expensive professional Unwinder. It is unpowered and comes with a "wearless" brake. The UCAT-S accepts up to 300 mm diameter rolls and up to 155 mm width, 76mm core holder as standard. The UCAT-S-MINI accepts up to 220 mm diameter rolls and up to 125 mm width, 76mm core holder as standard

UCAT-1 Heavy-Duty Unpowered Label Unwinders

This is the classic LABELMATE Unwinder with Adjustable Speed-Proportional Braking. Up to 300 mm diameter rolls and 155 mm width, 76 mm cores. A 255 mm width and a 25 mm to 101 mm Adjustable Core Holder, models are available. Please see the table of available models next page.

UCAT-3 Heavy-Duty Powered Label Unwinders

This powered Unwinder automatically tracks label usage and provides powered label feed at speeds up to 125 cm/sec. The UCAT-3 accepts standard 76 mm cores and rolls up to 300 mm in diameter. 255 mm width is available. It can also be used as a full-featured Label Rewinder without any special setup. LABELMATE's renowned Constant Adjustable Torque™ control system allows precise adjustment of feed speeds and rewind torque. External STOP / RUN Input included.

UCAT-40 Heavy-Duty Powered Label Unwinders

A powered Unwinder like the UCAT-3, but with an impressive 40 cm roll diameter capacity. Supplied with LABELMATE's 76 mm "Quick-Chuck"™, the UCAT-40 gives you the ultimate label Unwinder for volume production.

NOTE: UCAT-S & UCAT-1 are unpowered and do not rewind, they only unwind. The UCAT-3 & UCAT-40 are powered and can also rewind (without the tension arm function). All UCAT feature a [5-Year Parts and Labour Limited Warranty](#) (1-Year on power supplies), the longest in the industry.



UCAT-S



UCAT-3-ACH



UCAT-40



UCAT-S-MINI



UCAT-3-CHUCK



UCAT-1-10-INCHES



P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	ROLL DIAM (mm)	SPEED * (cm/sec)	PRICE EURO
LMU014	UCAT-S-MINI	Economy Label Unwinder. Unpowered with brake. 76mm standard. ** Size: 220 (W) x 305 (D) x 195 (H) mm	125	220	Same as printer	195 €
LMU001	UCAT-S	Economy Label Unwinder. Unpowered with adjustable brake. 76mm standard. ** Size: W x D x H: 300 x 365 x 320 mm.	155	300	Same as printer	242 €
LMU002	UCAT-1-STANDARD	Heavy-duty Unwinder 76mm standard. Self-powered adjustable Speed-Proportional Frictionless Braking. ** Size: W x D x H: 300 x 350 x 320 mm.	155	300	Same as printer	545 €
LMU003	UCAT-1-ACH	UCAT-1 with an Adjustable Core Holder for core sizes from 25 to 101mm diameter cores. Size: W x D x H: 300 x 350 x 320 mm.	155	280	Same as printer	607 €
LMU004	UCAT-1-CHUCK	UCAT-1 with 76mm 'Quick-Chuck'. ** Size: W x D x H: 300 x 385 x 320 mm.	170	300	Same as printer	769 €
LMU005	UCAT-1-10-INCHES	UCAT-1 for Labels up to 255mm wide. 76mm standard. ** Size: W x D x H: 300 x 455 x 320 mm.	255	300	Same as printer	620 €
LMU006	UCAT-1-1-INCH	UCAT-1 for 25.4mm diameter cores. Size: W x D x H: 300 x 455 x 320 mm.	155	220	Same as printer	545 €

LMU007	UCAT-3-STANDARD	Powered Unwinder for label rolls with 76mm core diam. Standard * * Continuously adjustable feed rate. Control arm tracks label unwind usage and starts & stops unwinding automatically. Also rewinds. Size: W x D x H: 300 x 350 x 320mm.	155	300	125	821 €
LMU008	UCAT-3-ACH	Powered Unwinder with an Adjustable Core Holder for any core size from 25 to 101mm. Also rewinds. Size: W x D x H: 300 x 350 x 320mm.	155	280	125	883 €
LMU009	UCAT-3-CHUCK	UCAT-3 with 76mm 'Quick-Chuck'. ** Also rewinds. Size: W x D x H: 300 x 385 x 320mm.	170	300	125	1031 €
LMU010	UCAT-3-10-INCHES	UCAT-3 for Labels up to 255mm wide. 76mm standard. ** Also rewinds. Size: W x D x H: 300 x 455 x 320mm.	255	300	125	895 €
LMU011	UCAT-3-1-INCH	UCAT-3 for 25.4mm diameter cores. Size: W x D x H: 300 x 455 x 320mm.	155	220	125	821 €

LMU012	UCAT-40	Heavy-duty 400mm diameter Powered Unwinder with 76mm 'Quick-Chuck'. * * Continuously adjustable feed rate. Control arm tracks label usage and starts & stops unwinding automatically. Also rewinds. Size: W x D x H: 400 x 450 x 460mm.	170	400	125	1116 €
---------------	----------------	---	-----	-----	-----	--------

* SPEED: The indicated speeds are the maximum speeds at beginning of a 76mm core roll.

* * Standard, S, CHUCK and 10-Inches Models are available for 38-, 40-, 44-, 70-, 76- and 100 mm diameter cores. Specify when ordering. To order your size, please refer to p28 – "Chucks & Vanes".

MAXIMUM LABEL ROLL WEIGHT:

- **STANDARD:** 8Kg.
 - **ACH:** 7Kg.
 - **10-INCHES:** 10Kg.
- CHUCK:** 10Kg
UCAT-40: 14Kg.

LABEL UNWINDERS UCAT-1 / UCAT-3 OPTIONS

P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	PRICE EURO
LMX457	R-16	Option available on UCAT-1-STANDARD and UCAT-1-CHUCK to accept rolls up to 400mm in diameter . Factory installed.	-	99 €
LMX444	APG-CAT / UCAT	Optional Adjustable Paper Guide. Guides the outer edge of the label web to ensure an even roll edge.	-	34 €
LMX489	FLANGE-CAT-INT	Inner flange for UCAT-1 & 3 – STANDARD & 10-INCHES.	-	30 €
LMX490	FLANGE-CAT-EXT	Outer flange for UCAT-1 & 3 – STANDARD & 10-INCHES.	-	30 €
LMX491	STANDARD SHAFT	Standard shaft for UCAT-1 & 3 with vanes, internal and external flanges.	155	106 €
LMX492	10" SHAFT	10-Inches shaft for UCAT-1 & 3 with vanes, internal and external flanges.	255	138 €
LMX500	ACH-UCAT	Adjustable Core Holder for any core size from 25 to 101mm in diameter. With inner flange.	155	145 €
LMX501	BAIL STD	For rewind on shaft, no core is needed.	-	15 €
LMX502	BAIL 10"	For rewind on shaft on UCAT-1/3-10-INCHES, no core is needed.	-	18 €
LMX472	FOOT SWITCH	Foot Switch to start and stop the TWIN-CAT-2, UCAT-3 or MC Rewinders.	-	80 €
LMX537	PS-15V	220-240V – 50Hz DC Power Supply for UCAT. Output: 15V – 4.33A. Included with UCAT-3 Rewinder & UCAT-40 Unwinders.	-	40 €
LMX537-UK	PS-15V-UK	220-240V – 50Hz DC Power Supply for UCAT. Output: 15V – 4.33A. UK PLUG	-	40 €
LMX546	1' SHAFT	1-Inch shaft for UCAT-1 & 3 with vanes, internal and external flanges.	155	106 €



“QUICK-CHUCKS”™ Quick-Loading Core Chucks for Volume Label Production

Here is the best answer for quick loading and unloading of label rolls. LABELMATE’s precision, maintenance-free “Quick-Chuck”™ Core Chucks permit you to mount or remove a roll of labels on your Rewinder or Unwinder in seconds. They are ideal for heavy rolls, production operations, or for holding multiple cores for slitting. Quality European design and construction insure smooth and trouble-free operation.

To use a *Quick-Chuck*, just slide your label roll over the Chuck and turn the convenient lock knob. Instantly your roll is locked in place. To remove the roll, just give the lock knob a quick turn to the left and pull the roll off your machine!

LABELMATE’s *Quick-Chucks* are now available in six different diameters to accept popular core sizes. An optional Outer Flange is available for the 76 mm (3-inch) “Quick-Chuck” Models. An Adjustable Paper Guide (APG-CAT) can also be used to guide the outer edge of the label web.

The UCAT-1-CHUCK, UCAT-3-CHUCK, UCAT-40 and LC-CAT-3-CHUCK Unwinders and the CAT-4-CHUCK, CAT-3-CHUCK, TWIN-CAT-2, CAT-40G, CAT-2-TA-CHUCK & CAT-40G-TA Rewinders come equipped with a *Quick-Chuck* as standard. Or, you can buy *Quick-Chucks* individually for your in-house or OEM Applications.

The Quick-Chucks fit a 15.85mm diameter shaft.



“VANES” for fins style core holder

Vanes are metal plates made out of stainless steel to be placed on Standard core holders and 10-Inches core holders. By changing the vanes, user can define or adapt the core holder size to rewind/unwind different core diameters. Easy to install, you will only need a cross-head screw driver to loosen/tighten the screws.

76 mm Vanes are placed by default. Other cores are on request. Please, note that you will need **two** sets of vanes for 10-INCHES shaft.

Related models: CAT-4-ST, CAT-3-(TA)-ST, TWIN-CAT-2-ST, LC-CAT-3-ST, MC-10, MC10+, UCAT-1-ST, UCAT-3-ST, CAT-4-10-INCHES, CAT-3-(TA)-10-INCHES, TWIN-CAT-2-10-INCHES, LC-CAT-3-10-INCHES, UCAT-1-10-INCHES, UCAT-3-10-INCHES.



P/N	MODEL	DIAMETER	WIDTH	ROLL WEIGHT	PRICE EURO
LMX479	C-38170	38 mm	170 mm	Maximum 12 Kg.	268 €
LMX480	C-40170	40 mm			268 €
LMX481	C-44170	44 mm			268 €
LMX482	C-70170	70 mm			268 €
LMX483	C-76170	76 mm			268 €
LMX484	C-76220	76 mm	220 mm		320 €
LMX485	C-76270*	76 mm	270 mm		390 €
LMX486	C-100170	100 mm	170 mm		328 €
LMX487	C-100220	100 mm	220 mm		400 €
LMX488	C-100270*	100 mm	270 mm		450 €
LMX506	220mm outer Flange for "Quick-Chuck" 76mm core diameter.				43 €
LMX144	220mm inner Flange for "Quick-Chuck" 70, 76 & 100mm core diameter.				20 €
LMX507	220mm inner Flange for "Quick-Chuck" 38, 40 & 44 core diameter.				27 €
LMX508	300mm outer Flange for "Quick-Chuck" 76mm core diameter.				48 €
LMX509	300mm inner Flange for "Quick-Chuck" 70, 76 & 100mm core diameter.				23 €
LMX510	300mm inner Flange for "Quick-Chuck" 38, 40 & 44 core diameter.				30 €
LMX511	400mm outer Flange for "Quick-Chuck" 76mm core diameter.				85 €
LMX512	400mm inner Flange "Quick-Chuck" 76mm core diameter.				46 €
LMX513	400mm inner Flange for "Quick-Chuck" 38, 40 & 44 core diameter.				52 €

When ordering, please specify the chuck you need.

Ex : For a CAT-3-CHUCK with a 40 mm diameter chuck, order: LMR006 / LMX 480.

The price is calculated based on the difference between the standard chuck (LMX483) value and the ordered chuck.

LMX493	VANES 38	Set of 3 vanes (fins) for 38 mm cores.	13 €
LMX494	VANES 40	Set of 3 vanes (fins) for 40 mm cores.	13 €
LMX495	VANES 44	Set of 3 vanes (fins) for 44 mm cores.	13 €
LMX496	VANES 50	Set of 3 vanes (fins) for 50 mm cores.	13 €
LMX497	VANES 70	Set of 3 vanes (fins) for 70 mm cores.	13 €
LMX498	VANES 76	Set of 3 vanes (fins) for 76 mm cores.	13 €
LMX499	VANES 100	Set of 3 vanes (fins) for 100 mm cores.	13 €

When ordering, you can change the standard Vanes 76 mm without any additional charge.

Ex : For a MC-10 with Vanes 44, order: LMR001 / LMX 495

For a TWIN-CAT-2-10-INCHES with Vanes 70, order: LMR016 / LMX 497 x 2



Heavy-Duty Label Slitters & Slitting Stations

The SR-6 & SR-10 Label Slitters/Rewinders

NEW

The SR-6 or SR-10 combination Label Slitter & Rewinder allows you to slit and rewind in-line directly from a printer without placing any tension whatsoever on the printer. A free-hanging loop of material is created between the SR-6/SR-10 and the printer thereby eliminating all tension on the printer. A special chassis-mounted optical sensor on the SR-6/SR-10 starts and stops the slit/rewind action based on the optimum depth of the loop. Fully adjustable tension on the SR-6/SR-10 provides complete control over the slitting action and the tightness of the finish rolls.



SR-6 Slitter/Rewinder

The S-100 & S-200 Label Slitters

The most convenient solution for slitting and rewinding narrow labels. LABELMATE Label Slitters allow you to print small labels several across and then slit them to the desired width. This multiplies your print efficiency and dramatically increases your print head life and ribbon usage efficiency. The rugged LABELMATE S-100 and S-200 are High-Speed, Heavy-Duty Label Slitters identical in construction except for size.

The Slitters can be used either “in-line” or “off-line”. In “in-line” use, the Slitter is placed between the printer output and the Label Rewinder. The slitting speed is determined by the printer output speed. In “off-line” use, the Slitter is placed between a UCAT Unwinder and a CAT-3 Rewinder. Off-line slitting is recommended for production work or for use with three or more blades. With slitting speeds up to 125cm/sec in “off-line” mode, you’ll make fast work of your slitting jobs.

An optional six- (6) digit PC-1 Pre-set Counter allows you to pre-set the number of labels to be slit. When the counter reaches the preset number, it sends a “HALT” signal to the Rewinder. Power to the Rewinder motor is then shut off and braking is applied. You’ll have no annoying label spills to contend with.

S-100S and S-200S Slitting Stations

Complete off-line slitting stations including all elements needed to start slitting immediately. The station comprises a slitter, a rewinder, an unwinder and the accessories.

The S-100, S-200 & S-100-SP feature a [5-Year Parts and Labour Limited Warranty](#) (1-Year on power supplies), the longest in the industry.



P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	SPEED (cm/sec)	PRICE EURO
LMS001	S-100	Heavy-Duty Label Slitter. Requires a CAT-3 Rewinder. Recommended: CAT-3-CHUCK. Size: W x D x H: 355 x 280 x 250 mm.	170	Same as Rewinder or printer.	466 €
LMS002	S-200	Wide Heavy-Duty Label Slitter. Requires a CAT-3 Rewinder. Recommended: CAT-3-CHUCK-10". Size: W x D x H: 435 x 280 x 250 mm.	255	Same as Rewinder or printer.	595 €
LMS004	S-100S	<ul style="list-style-type: none"> - UCAT-S Economy Heavy-Duty Label Unwinder with fixed brake; - S-100 Heavy-Duty Label Slitter; - 2 Blade Holders with Blades; - CAT-3-CHUCK Heavy-Duty Rewinder; 76mm diameter 'Quick-Chuck' is Standard; specify if 38, 40, 44 or 70mm diameter is desired instead. - 1 Aluminium and 2 Thin Plastic Separator Plates (220mm diameter); - 'LINK': Adjustable Locking Bar to lock units together in position, - 15V Power Supply. 	170	125	1562 €
LMS005	S-200S	<ul style="list-style-type: none"> - UCAT-1-10" Heavy-Duty Label Unwinder; - S-200 Heavy-Duty Label Slitter; - 3 Blade Holders with blades; - CAT-3-CHUCK-10" Heavy-Duty Rewinder; - 1 Aluminium and 3 Thin Plastic Separator Plates (220mm diameter); - 'LINK': Adjustable Locking Bar to lock units together in position; - 15V Power Supply. 	255	125	2216 €
LMS006	SR-6-R/L	NEW Heavy-duty Label Slitter-Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core 76mm, 2 blades, 2 ALU separator plates and outer/inner flanges included (220mm). Roll diam: 220mm Rewind direction: Right to left. Size: W x D x H: 483 x 381 x 400mm	170	125	1695 €
LMS007	SR-6-L/R	NEW Heavy-duty Label Slitter-Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core 76mm, 2 blades, 2 ALU separator plates and outer/inner flanges included (220mm) Roll diam: 220mm Rewind direction: Left to right. Size: W x D x H: 483 x 381 x 400mm	170	125	1695 €
LMS008	SR-10-R/L	NEW Heavy-duty Label Slitter-Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core 76mm, 3 blades, 3 ALU separator plates and outer/inner flanges included (220mm). Roll Diam: 220mm Rewind direction: Right to left. Size: W x D x H: 483 x 381 x 400mm	255	125	1995 €
LMS009	SR-10-L/R	NEW Heavy-duty Label Slitter-Rewinder with Zero Tension Loop and easy-loading quick-chuck. Core 76mm, 3 blades, 3 ALU separator plates and outer/inner flanges included (220mm). Roll diam: 220mm Rewind direction: Left to right Size: W x D x H: 483 x 381 x 400mm	255	125	1995 €



S-100 With PC-1 Counter




S-200




BH-1

LABEL SLITTER OPTIONS SR-6/10, S-100, S-200

P/N	MODEL	DESCRIPTION	PRICE EURO
LMX549	PC-4	Pre-set Counter for all SR-models. Allows to count labels or show instantaneous web speed. Factory installed.	389 €
LMX553	6" PAPER LOOP GUIDE	6" Paper-loop-guide: for guiding thick or curling media into a loop for ZCAT 6	39 €
LMX554	8" PAPER LOOP GUIDE	8" Paper-loop-guide: for guiding thick or curling media into a loop for ZCAT8/10	52 €
LMX514	PC-1	Pre-set Counter for S-100/200. Counts label batch size. Stops Rewinder automatically when job is finished. Factory installed.	389 €
LMX515	BH-1	Additional blade holder assembly. Includes precision high-speed blade.	30 €
LMX516	HSB-10	10 precision high-speed blades for slitters.	16 €
LMX517	LINK SLITTER	Adjustable locking bar to lock units together in position (Unwinder, Slitter & Rewinder).	60 €
LMX537	PS-15V	220-240V – 50Hz DC Power Supply for UCAT. Output: 15V – 4.33A. Included with the unit.	40 €
LMX537-UK	PS-15V-UK	220-240V – 50Hz DC Power Supply for UCAT. Output: 15V – 4.33A. UK PLUG	40€



S-100S



S-200S



"SP" Label Separator Plates for Slitters


Keeps slit label rolls from interleaving or telescoping. Makes removal of slit rolls easy.

Aluminium separator Plates are recommended for the outer Plates, Thin Plastic for the Plates in-between slit rolls. Suggested order: 1 Aluminium Separator Plate + Plastic Plates in-between slit rolls.

P/N	MODEL (mm)	DESCRIPTION	MATERIAL	PRICE EURO
LMX518	SP-25-220	220mm diameter for 25mm cores	Aluminium	20 €
LMX519	SP-25-220	220mm diameter for 25mm cores	Plastic	13 €
LMX520	SP-38-220	220mm diameter for 38mm cores	Aluminium	20 €
LMX521	SP-38-220	220mm diameter for 38mm cores	Plastic	13 €
LMX522	SP-40-220	220mm diameter for 40mm cores	Aluminium	20 €
LMX523	SP-40-220	220mm diameter for 40mm cores	Plastic	13 €
LMX524	SP-40-300	300mm diameter for 40mm cores	Aluminium	27 €
LMX525	SP-44-220	220mm diameter for 44mm cores	Aluminium	20 €
LMX526	SP-44-220	220mm diameter for 44mm cores	Plastic	13 €
LMX527	SP-70-220	220mm diameter for 70mm cores	Aluminium	20 €
LMX528	SP-70-220	220mm diameter for 70mm cores	Plastic	13 €
LMX529	SP-76-220	220mm diameter for 76mm cores	Aluminium	20 €
LMX530	SP-76-220	220mm diameter for 76mm cores	Plastic	13 €
LMX531	SP-76-300	300mm diameter for 76mm cores	Aluminium	27 €
LMX532	SP-76-400	400mm diameter for 76mm cores	Aluminium	32 €
LMX533	SP-ACH-220	220mm diameter for Adjustable Core Holders	Aluminium	20 €
LMX534	SP-ACH-220	220mm diameter for Adjustable Core Holders	Plastic	13 €
LMX535	SP-ACH-300	300mm diameter for Adjustable Core Holders	Aluminium	27 €



SP-ACH



Various SP



"RRC-330" Reel-to-Reel Counting Systems

RRC-330 Reel-to-Reel Counting Systems – For regular labels.

The RRC-330 Reel-to-Reel Counting Systems brings you new convenience in a self-contained table-top Label Counting System using a pre-set counter. The RRC-330 accepts rolls with a maximum size of 330mm.

RRC-330-U Universal Reel-to-Reel Counting Systems – For all type of labels.

The RRC-330-U Universal Reel-to-Reel Counting System uses a state of the art ultrasonic fork detector that allows the RRC-330-U to count any type of labels, including transparent or dark labels. The ultrasonic detector detects the labels by sensing the difference in thickness between the backing paper and the backing paper plus label.

All RRC-330 accept rolls with a maximum outer diameter of 330mm. Take-up core are available both in Standard and Adjustable Core Holder.

The Standard take-up shaft is fitted with a "Quick-Change" shaft that allows to quickly change the core holder diameter (38, 40, 44, 50, 70, 76 and 100mm available). Both shafts are supplied in both 40mm and 76mm (other core diameters available on-demand).

The ACH (Adjustable Core Holder) take-up shaft accepts cores from 25 to 101mm. The unwind shaft is equipped with the new Adjustable Wearless Brake system to adjust the web tension for tighter rewound rolls.

Designed for all-day, every-day use, the RRC-330 and RRC-330-U Reel-to-Reel Counting Systems are backed by LABELMATE's famous [3-Year Parts and Labor Limited Warranty](#) (1-Year on power supplies), assuring you trouble-free performance.



RRC-330-U-ACH



RRC-330-STANDARD



	MODEL	DESCRIPTION	LABEL WIDTH (mm)	ROLL DIAM (mm)	SPEED * (cm/sec)	PRICE EURO
LMC001	RRC-330-STANDARD	Self-contained Counter System with 220-240VAC, 50-60Hz, 150VA Universal Power Supply. 40 & 76mm for the unwind and take-up shafts (other diameters on demand). Size: W x D x H: 830 x 330 x 330 mm.	152	330	72 ¹ 235 ²	1550 €
LMC002	RRC-330-ACH	Self-contained Counter System with 220-240VAC, 50-60Hz, 150VA Universal Power Supply. 40 & 76mm for the unwind shaft. Adjustable Core Holder (25mm to 101mm) for the take-up shaft. Size: W x D x H: 830 x 330 x 330 mm.	152	330	72 ¹ 235 ²	1750 €
LMC003	RRC-330-U-STANDARD	Self-contained Counter System with 220-240VAC, 50-60Hz, 150VA Universal Power Supply. 40 & 76mm for the unwind and take-up shafts (other diameters on demand). Size: W x D x H: 830 x 330 x 330 mm.	152	330	72 ¹ 235 ²	2400 €
LMC004	RRC-330-U-ACH	Self-contained Counter System with 220-240VAC, 50-60Hz, 150VA Universal Power Supply. 40 & 76mm for the unwind shaft. Adjustable Core Holder (25mm to 101mm) for the take-up shaft. Size: W x D x H: 830 x 330 x 330 mm.	152	330	72 ¹ 235 ²	2600 €

¹ Maximum speed with a 76mm take-up roll diameter, at the beginning of the roll.

² Maximum speed at end of 330mm roll.

MAXIMUM LABEL ROLL WEIGHT: 7Kg.

RRC-330 REEL-TO-REEL COUNTING SYSTEMS OPTIONS

P/N	MODEL	DESCRIPTION	PRICE EURO
LMX453	NO COUNTER	RRC without counter for simple reel-to-reel operations.	-200 €
LMX454	Quick-Change Shaft	Complete take-up shaft with vanes. NOT AVAILABLE FOR UNWINDING SHAFT.	52 €



“COUNT” Heavy-Duty Label Counters

COUNT-100 and COUNT-200 Counters

The PC-1 Label Counter is a popular option on our S-100 and S-200 Label Slitters. Many times, however, users don't need to slit labels, just count them. To save users money, LABELMATE has two Label Counters based on the S-100 and S-200 Slitter chassis but without the Slitter function. The COUNT-100 and COUNT-200 will handle label webs up to 170 mm and 255 mm wide respectively. A CAT-3 Rewinder pulls the labels through the counter. The versatile Counters can be used at the output of a printer, or can be used with an Unwinder and a CAT-3 Rewinder to form a stand-alone off-line label inspection / counting station.

If desired, when the pre-set count is reached, the COUNT-100 and COUNT-200 can send a “HALT” signal to the CAT-3 Rewinder, causing it to stop.

The counter sensor itself is a state-of-the-art infra-red transmitting device that shines through the label web and detects the gap between successive labels. There is a sensitivity control to adjust for different kinds of label webs.


COUNT-100-U Universal Counter

The new COUNT-100-U Universal Counter uses a state of the art ultrasonic fork detector that allows the COUNT-100-U to count almost any type of labels, including transparent or dark labels. The ultrasonic detector detects the labels by sensing the difference in thickness between the backing paper and the backing paper plus label.

Quality and reliability are cornerstones of the LABELMATE Product Line. Rugged, heavy-gauge welded steel construction and precision parts yield a product of the highest quality. LABELMATE Products are trouble-free and covered by our famous [3-Year Parts and Labour Limited Warranty](#) (1-Year on power supplies), by far the longest in the industry.



COUNT-100



COUNT-100-U



P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	PRICE EURO
LMC005	COUNT-100	PC-1 Preset Counter mounted on chassis with guides to position label web through sensor gap. Adjustable counter sensitivity. Counts single labels or preset batch size. Can stop rewinder (CAT-3) automatically when job is finished. Size: W x D x H: 355 x 280 x 250 mm.	170	659 €
LMC006	COUNT-200	Same as COUNT-100 with wider width capacity. Size: W x D x H: 435 x 280 x 250 mm.	255	805 €
LMC007	COUNT-100-U	With ultrasonic fork detector to count any type of labels PC-1 Preset Counter mounted on chassis with guides to position label web through sensor gap. Adjustable counter sensitivity. Counts single labels or preset batch size. Can stop rewinder (CAT-3) automatically when job is finished. Size: W x D x H: 355 x 280 x 250 mm.	170	1564 €

NOTE: Requires a CAT-3 Rewinder to pull your labels through the Counter. Can also be used with a Label Unwinder to form a complete off-line label counting and manual inspection station. No slitting function is included.

“PM-300-LS” & “PM-300-HS” Reel-to-Reel Label Printer Mechanism for Inkjet and Laser Heads

The **PM-300** Reel-to-Reel Printer Mechanism from LABELMATE. At speeds up to 235cm/sec, you can conveniently and economically print or overprint labels using your preferred inkjet head. With full status indicators and control features, the PM-300 is an ideal table top platform for OEM applications that use an ink-jet or laser head. When not used as a printer, the PM-300 can be used as a reel-to-reel Counter – Rewinder. The built-in encoder has a resolution of 0,041mm.

The **PM-300-LS** will print a 28cm diameter roll (425 meters) of labels in less than 7 minutes; the PM-300-HS will print the same roll in less than 5 minutes. The model choice is dictated by the performance of the print head being used.

The **PM-300-U**, with the same features as the PM-300, uses an ultrasonic detector that allows the printer to work on any type of labels, including transparent or dark labels. It detects the difference in thickness between the backing paper and the backing paper plus label.

Designed for all-day, every-day use, the PM-300 Reel-to-Reel Printer Mechanism is backed by LABELMATE's famous [3-Year Parts and Labour Limited Warranty](#) (1-Year on power supplies), assuring you trouble-free performance (1-year power supply).



PM-300-LS/HS

KEY FEATURES

- **ENC:** Built-in encoder with resolution of 0,041mm. Output: Square waves: 0 – 15V.
- **Maximum roll diameter:** 300mm.
- **Max. roll weight:** 6Kg.
- **Label width:** up to 125mm.
- **Speeds:** reached at the end of the roll.
LS-Version: Max. 150cm/sec. For a roll of 28cm diameter and a core of 76mm.
E.g.: 7 min. for a roll of 28cm diameter with a 76mm core at full speed. Average speed: 100cm/sec.
HS-Version: Max. 235cm/sec. For a roll of 28cm diameter and a core of 76mm.
E.g.: 4,5 min. for a roll of 28cm diameter with a 76mm core at full speed. Average speed: 150cm/sec.
- Rugged construction.
- Secured DB-9 Print Head Connector.

KEY FEATURES (cont.)

- Adjustable Label Guide.
- 220/240V – 50-60Hz AC Input.
- Label sensor: Open collector output.

OPTIONS

- **PC-2:** Optional 6-digit pre-set counter.
- **PC-3:** Dual function preset counter. Allows to count labels or show instantaneous web speed.
- **HSA™-BC:** Mounting bracket and cable for HSA™ printhead.
- **WEB-BC:** Mounting bracket and cable for Markoprint (Weber)™ X1-Jet print head.

The Speed specifications apply for a machine used in normal office room temperatures.



“PM-300-CS” Constant Speed Reel-to-Reel Label Printer Mechanism for Inkjet and Laser Heads

For applications requiring constant speed.

The PM-300-CS Constant Speed Reel-to-Reel Printer Mechanism from LABELMATE. This machine works at constant adjustable speed (independently of the supply and rewind roll diameters). The maximum speed is 65cm/sec. The long-term speed stability is +/-5%. For more precise print jobs, an optional encoder can be added.

The PM-300 is an ideal table top platform for OEM applications that use an ink-jet head. When not used as a printer, the PM-300 can be used as a reel-to-reel Counter – Rewinder. The optional built-in encoder has a resolution of 0,041mm.

Other options include a label counter or a more sophisticated counter that can be used to count labels or indicate the speed at which the labels are moving.

The PM-300-CS can also be used with certain laser heads.

Designed for all-day, every-day use, the PM-300 Reel-to-Reel Printer Mechanism is backed by LABELMATE's famous [3-Year Parts and Labour Limited Warranty](#) (1-Year on power supplies), assuring you trouble-free performance.



PM-300-CS

KEY FEATURES

- **Maximum roll diameter:** 300mm.
- **Max. roll weight:** 6Kg.
- **Label width:** up to 125mm.
- **Speed:** Adjustable constant speed to choose from 0 to max. 40cm/sec or 0 to max 61cm/sec, depending on the request.
- Accuracy: +/- 5%.
- Rugged Construction.
- Secured DB-9 Print Head Connector.
- Adjustable Label Guide.
- 220-240V – 50-60Hz AC Input
- Label sensor: Open collector output.

The speed specifications apply for a machine used in normal office room temperatures.

OPTIONS

- **ENC:** Optional built-in encoder with resolution of 0,041mm. Output: Square waves: 0 – 15V.
- **PC-2:** Optional 6-digit pre-set counter.
- **PC-3:** Dual function preset counter. Allows to count labels or show instantaneous web speed.
- **HSA™-BC:** Mounting bracket and cable for HSA™ printhead.
- **WEB-BC:** Mounting bracket and cable for Markoprint (Weber)™ X1-Jet print head.
- **CUST.:** Customised version.



“PM-300-CS-STEP” Reel-to-Reel Constant Speed System

For applications requiring pausing between each label.

The PM-300-CS-STEP works at constant adjustable speed (independently of the supply and rewind roll diameters). The maximum speed is 65cm/sec. (or 61cm/sec. upon request). The long-term speed stability is +/- 5%. This model has a "1 by 1" mode that allows to stop automatically after each label and advances to the next label by a push button or by an external command. For more precise print jobs, an optional encoder can be added.

The PM-300-CS-STEP is an ideal table top platform for programming and reading RFID tags. When not used for programming, the PM-300-CS-STEP can be used as a reel-to-reel Counter – Rewinder. The optional built-in encoder has a resolution of 0,041mm.

Other options include a label counter or a more sophisticated counter that can be used to count labels or indicate the speed at which the labels are moving.

Designed for all-day, every-day use, the PM-300-CS-STEP Reel-to-Reel Constant Speed System is backed by LABELMATE's famous [3-Year Parts and Labour Limited Warranty](#) (1-Year on power supplies), assuring you trouble-free performance.



PM-300-CS-STEP with Encoder

KEY FEATURES

- **Maximum roll diameter:** 300mm.
- **Max. roll weight:** 6Kg.
- **Label width:** up to 125mm.
- **Speed:** Adjustable constant speed from 0 to max. 40cm/sec. Accuracy: +/- 5%.
- Rugged Construction.
- Secured DB-9 Print Head Connector.
- Adjustable Label Guide.
- 220-240V – 50-60Hz AC Input
- Label sensor: Open collector output.

OPTIONS

- **ENC:** Optional built-in encoder with resolution of 0,041mm. Output: Square waves: 0 – 15V.
- **PC-2:** Optional 6-digit pre-set counter.
- **PC-3:** Dual function preset counter. Allows counting labels or showing instantaneous web speed.

The speed specifications apply for a machine used in normal office room temperatures.



P/N	MODEL	DESCRIPTION	LABEL WIDTH (mm)	ROLL DIAM. (mm)	MAX SPEED* (cm/sec)	PRICE EURO
LMP003	PM-300-LS	Reel-to-Reel Label printer mechanism. Low speed model. Size: W x D x H: 800 x 380 x 330 mm.	125	300	150	2250 €
LMP004	PM-300-HS	Reel-to-Reel Label printer mechanism. High speed model. Size: W x D x H: 800 x 380 x 330 mm.	125	300	235	2350 €
LMP005	PM-300-CS	Reel-to-Reel Label printer mechanism. Constant speed model. Size: W x D x H: 800 x 380 x 330 mm.	125	300	40 or 61	3565 €
LMP006	PM-300-CS-STEP	Reel-to-Reel Label printer mechanism with constant speed and "1 by 1" mode Size: W x D x H: 800 x 380 x 330 mm.	125	300	40	3665 €
LMP007	PM-300-U-LS	Reel-to-Reel Label printer mechanism. Low speed model. For all types of labels. Size: W x D x H: 800 x 380 x 330 mm.	125	300	150	3100 €
LMP008	PM-300-U-HS	Reel-to-Reel Label printer mechanism. High speed model. For all types of Labels. Size: W x D x H: 800 x 380 x 330 mm.	125	300	235	3200 €

* Maximum speeds are specified with a 76mm take-up roll diameter and reached at the end of the roll. (OD : 300mm)

E.g.: With the PM-300-HS 4.5 min. for a roll of 28cm diameter with a 76mm core at full speed. Average speed: 1.5m/sec.

MAXIMUM LABEL ROLL WEIGHT: 6Kg.

PM-300 REEL-TO-REEL SYSTEMS OPTIONS

P/N	MODEL	DESCRIPTION	PRICE EURO
LMX454	Quick-Change Shaft	Complete take-up shaft with vanes. NOT AVAILABLE FOR UNWINDING SHAFT.	52 €
LMX478	ENC PM-CS	Optional built-in encoder with resolution of 0,041mm. For PM-300-CS & PM-300-CS-STEP.	390 €
LMX474	PC-2	Optional 6-digit pre-set counter. Counts label batch size. Factory installed.	250 €
LMX475	PC-3	Dual function preset counter. Allows to counts labels or show instantaneous web speed. Factory installed.	460 €
LMX477	WEB-BC	Mounting bracket and cable for Markoprint (Weber) [™] X1-Jet print head.	165 €







ALL PRODUCTS IN THIS CATALOGUE ARE MANUFACTURED IN BELGIUM BY



Labelmate
Chaussée de Ruisbroek 290
1620 Drogenbos (Belgium)

+32 2 375 69 60
brussels@labelmate.com
BTW BE 0674 877 993

ING BELGIUM
IBAN BE89 3630 6607 1285
BIC BBRUBEBB

labelmate.com

