

# Tandberg StorageLoader LTO

*The 1U AutoLoader that Evolves with the LTO Roadmap*

The Tandberg StorageLoader LTO offers the largest storage capacity, highest performance and best value for money of any product in its class. The StorageLoader LTO costs slightly more than a standalone tape drive, but offers a considerable greater return on investment as it automates the swapping of daily backup tapes reducing the risk of data loss, saving you time and money.

The StorageLoader LTO offers scalable capacities up to 12.8TB\* in a compact 1U form factor, providing the highest capacity, highest performance (up to 576GB/hr) and data density on the market. The StorageLoader LTO is available with either LTO-2, LTO-3 and LTO-4 tape drives, with a choice of LVD SCSI or SAS connectivity.

The StorageLoader LTO contains two 4-slot removable magazines storing a total of 8 data cartridges. Each magazine can be ejected using the front panel interface, in the event of a power failure there is an emergency magazine eject feature.

The StorageLoader LTO is easy to install, easy to use and is supplied with a barcode scanner, barcode labels and a rack-mount kit. The StorageLoader LTO includes the latest security and data protection features, such as Encryption and WORM (Write Once Read Many) to assist you with meeting today's data storage and archiving regulatory requirements.

The Web browser-based remote management interface allows you to monitor, control, configure and diagnose problems from anywhere in the world. The StorageLoader LTO also supports SNMP, which will immediately send an e-mail on any error.

The StorageLoader LTO provides outstanding value for IT managers that require a easy to use, scalable, flexible, reliable and future proof backup and data protection solution.



## Key Benefits

- == **High Capacity in a small footprint**  
Up to 12.8TB\* storage capacity in a compact 1U form factor
- == **High Performance**  
Transfer rates up to 160MB/s\* or 576GB/hr\*
- == **Grow with LTO Roadmap**  
Select LTO-2, LTO-3 or LTO-4 Half Height Drives
- == **3yrs Warranty and 1yr Advanced Replacement**  
Component level: drive, power supply & fan
- == **Minimise Downtime**  
Field replaceable drives and power supplies and fans
- == **Ease of Use**  
Remote management and removable magazines for bulk loading and easy off-site storage

\* Assumes a 2:1 compression ratio

The Tandberg StorageLoader LTO combines high capacity and performance in a scalable 1U form factor.

**TANBERG DATA**  
Securing your Information



## Specifications

	StorageLoader LTO-2	StorageLoader LTO-3	StorageLoader LTO-4
Capacity (native/compr.)	<b>1.6TB / 3.2TB</b>	<b>3.2TB / 6.4TB</b>	<b>6.4TB / 12.8TB</b>
Performance (native/compr)	<b>86/172 GB/hr</b>	<b>216/432 GB/hr</b>	<b>288/576 GB/hr</b>
Interface	<b>Ultra SCSI LVD</b>	<b>Ultra SCSI LVD</b>	<b>Ultra SCSI LVD / SAS</b>
External Connector	<b>68pin VHD</b>	<b>68pin HD</b>	<b>68pin HD / SFF-8088</b>
Drive Technology	<b>LTO-2 HH</b>	<b>LTO-3 HH</b>	<b>LTO-4 HH</b>
Read Compatability	<b>LTO-1 / LTO-2</b>	<b>LTO-1 / LTO-2 / LTO-3</b>	<b>LTO-2 / LTO-3 / LTO-4</b>
Write Compatability	<b>LTO-1 / LTO-2</b>	<b>LTO-2 / LTO-3</b>	<b>LTO-3 / LTO-4</b>
Number of Cartridges	<b>8</b>	<b>8</b>	<b>8</b>
Number of Removable Magazines	<b>2</b>	<b>2</b>	<b>2</b>
Barcode Reader	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>
WORM (Write Once Read Many)	<b>No</b>	<b>Yes</b>	<b>Yes</b>
Encryption	<b>No</b>	<b>No</b>	<b>Yes</b>
Soft Power	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>
MCBF	<b>500,000</b>	<b>500,000</b>	<b>500,000</b>
MTBF	<b>250,000 hours</b>	<b>250,000 hours</b>	<b>250,000 hours</b>
Temperature (operating)	<b>10 C to 35 C</b>	<b>10 C to 35 C</b>	<b>10 C to 35 C</b>
Temperature (non-operating)	<b>-35 C to 60 C</b>	<b>-35 C to 60 C</b>	<b>-35 C to 60 C</b>
Relative Humidity (operating)	<b>20% to 80%</b>	<b>20% to 80%</b>	<b>20% to 80%</b>
Relative Humidity (non-operating)	<b>10% to 90%</b>	<b>10% to 90%</b>	<b>10% to 90%</b>
Power consumption	<b>90-264 VAC; 47-63 Hz, less than 30 A bei 115 VAC-less than 60 A at 230 VAC</b>		
Certification Marks	<b>CE,UL,C-UL, GS / TUV, VCCI, C-Tick, UL-60950 / C-UL C22.2 No. 60950; TUV EN60950</b>		
Safety	<b>FC Part 15, Class A; EN 55022, Class A; EN 61000-3-2</b>		
EMC	<b>EN 61000-3-3, IEC60333, Class A; CISPR22, Class A, EN 55024</b>		
Web Administration	<b>System Status, Drive Operations, Remote Diagnostics, Remote Management</b>		
Language Support	<b>German, English, French, Italian, Spanish, Japanese</b>		
System Interface	<b>LC Display, Media Configuration and Diagnostic Status, Power and Alarm LED, 4-Button Keypad</b>		
Turnkey Solution	<b>Includes Barcode Reader and Labels, Rackmount kit, Cable and Symantec Backup Exec QuickStart Edition</b>		
Warranty	<b>3yrs and 1yr ARS for components</b>		

\* Assumes a 2:1 compression ratio

Form Factor	1U / 19" rack	1U / 19" rack	1U / 19" rack
Height	<b>13.6mm / 1.72"</b>	<b>13.6mm / 1.72"</b>	<b>13.6mm / 1.72"</b>
Width	<b>446.6mm / 17.58"</b>	<b>446.6mm / 17.58"</b>	<b>446.6mm / 17.58"</b>
Depth	<b>736.6mm / 29.0 (behind the front rail)</b>	<b>736.6mm / 29.0 (behind the front rail)</b>	<b>736.6mm / 29.0 (behind the front rail)</b>
Weight	<b>14.6kg</b>	<b>14.6kg</b>	<b>14.6kg</b>

### About Tandberg Data

Tandberg Data is a leading global supplier of backup and archiving technologies. Tandberg Data offers a complete range of tape libraries, tape autoloaders and tape drives (based on the LTO™, SLR™, VXA® tape technology platforms), storage software, data media and disk-based storage such as the RDX™ QuikStor. These solutions are marketed exclusively through a channel of qualified resellers and distributors. These solutions are underpinned by OEM agreements with major server manufacturers including IBM, Hitachi, Fujitsu, Fujitsu-Siemens, Apple and Dell and supported by all major operating systems and storage software applications to operate in heterogeneous network environments. All solutions are designed to meet the growing storage requirements of small and medium-sized organisations with scalability, reliability and backward compatibility features that ensure cost effective operation and long-term investment protection.

Tandberg Data ASA  
Økernveien 94  
N-0579 Oslo  
Norway  
Tel: +47 (0) 2218 9090  
Fax: +47 (0) 2218 9550

Tandberg Data GmbH  
Feldstrasse 81  
44141 Dortmund  
Germany  
Tel: +49 (0) 231 5436 - 0  
Fax: +49 (0) 231 5436 - 111

Tandberg Data Limited  
Bloxham Mill Business Centre  
Barford Road, Bloxham  
Banbury, England, OX15 4FF  
Tel: +44 (0) 845 070 6916  
Fax: +44 (0) 1295 722 109

Tandberg Data S.A.S.  
16-18, avenue Morane Saulnier  
78941 Vélizy Cedex  
France  
Tel: +33 (0)1 39 26 01 01  
Fax: +33 (0)1 34 65 02 89

Tandberg Data Corporation  
2108 55th Street  
Boulder, CO 80301  
USA  
Tel: 303.442.4333  
Fax: 303.417.7170

Tandberg Data (Asia) Pte Ltd  
20 Bendemeer Road  
#04-05 Cyberhub  
Singapore 339914  
Tel: +65 (0) 6396 0786  
Fax: +65 (0) 6396 0787

In addition to the offices above TANBERG DATA ASA has branch offices in the United Kingdom, France, Italy, India, China (PRC), Thailand and Brazil. TANBERG DATA ASA is a publicly held company based in Oslo, Norway and is traded on the Oslo Stock Exchange (ticker=TAD). Specifications subject to change without notice. RDX QuikStor, BAKStor, and SLR are trademarks of Tandberg Data ASA. RDX is a registered trademark of ProStor Systems. LTO is a trademark of HP, IBM and Quantum. All other trademarks are the property of their respective owners. ©2007 TANBERG DATA. All rights reserved.

DS-SLLT03\_EMEA\_2008

salesemea@tandbergdata.com 00 800 8263 2374 (00 800 TANBERG)

www.tandbergdata.com