



# CorePro LEDcapsule LV

## CorePro LEDcapsuleLV 2-20W 830 G4

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

### Product data


General Information		Power Consumption	
Cap-Base	G4 [G4]	Lamp Current (Nom)	290 mA
Nominal lifetime	15,000 hour(s)	Wattage Equivalent	20 W
Switching Cycle	50,000	Starting Time (Nom)	0.5 s
Lighting Technology	LED	Warm-up time to 60% light	0.5 s
EU RoHS compliant	Yes	Power Factor (Fraction)	0.5
		Voltage (Nom)	12 V
Light Technical		Controls and Dimming	
Color Code	830 [CCT of 3000K]	Dimmable	No
Luminous Flux	200 lm	Mechanical and Housing	
Color Designation	White (WH)	Bulb Shape	Capsule
Correlated Color Temperature (Nom)	3000 K	Approval and Application	
Luminous Efficacy (rated) (Nom)	100 lm/W	Energy Consumption kWh/1000 h	3 kWh
Color Consistency	<6	Product Data	
Color rendering index (CRI)	80	Order product name	CorePro LEDcapsuleLV 2-20W 830 G4
LLMF At End Of Nominal Lifetime (Nom)	70 %	Full product name	CorePro LEDcapsuleLV 2-20W 830 G4
Operating and Electrical			
Line Frequency	50 to 60 Hz		
Input Frequency	50 to 60 Hz		

# CorePro LEDcapsule LV

Full product code	871869641916800
Order code	324558
Material Nr. (12NC)	929001131802
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696419168



Numerator - Packs per outer box	12
EAN/UPC - Case	8718696419175

## Dimensional drawing



Product	D	C
CorePro LEDcapsuleLV 2-20W 830 G4	9/16 inch	1-13/16 inch

## Photometric data



Light Distribution Diagram - CorePro LEDcapsuleLV 2-20W 830 G4

Spectral Power Distribution Colour - CorePro LEDcapsuleLV 2-20W 830 G4

