

Tridonic DALI Driver for 15W LED Downlight

- Tridonic Driver LCA 17W 250–700mA one4all SC PRE
- Power factor >0,95
- DALI dimmable
- DALI-2 DT 6, DSI, switchDIM, corridorFUNCTION

Order Code	52947
General Data	
Primary Voltage Range (V)	200-240
Operating Frequency (Hz)	50-60
Input Current (A)	0.071
Output Current (A)	0.38
Secondary Voltage (V)	42max., 35V with Verbatim LED Downlight
Input Wattage (W)	16.5W max., 30W with Verbatim LED Downlight
Power Factor	>0.95
Ambient Temperature t_a (°C)	-25 to 60
Max Case Temperature t_c (°C)	80
Dimensions LxWxH (mm)	190x43x30
Weight (g)	168
Primary Terminal	2-pole, pre-wired with dedicated connector
Secondary Terminal	2-pole, pre-wired with dedicated connector
Standards	EN 61347-1
	EN 61347-2-13
	EN 55015
	EN 61000-3-2
	EN 61000-3-3
	EN 61547
	EN 62384
	EN 62386-101 (according to DALI standard V2)
	EN 62386-102
	EN 62386-207

According to EN 50172 for use in central battery systems

According to EN 60598-2-22 suitable for emergency lighting installations

Specifications are subject to operating with halogen lamps



Created October 2018

www.verbatimlighting.com

Tridonic DALI Driver for 15W LED Downlight

Order Code 52947

Product Description Tridonic DALI Driver for 15W LED Downlight

Technical Packaging Details

Barcode 23942529477

Outer EAN 14 50023942529472

Inner EAN 128 (02)00023942529477(37)10(91)814

Pack Dimensions (HxWxL) 45mm x 48mm x 202mm

Pack Weight (g) 195

Carton Qty (Shipping Unit) 1

Cartons/pallet 108

Layers/Pallet 4

Units/Pallet 1080