




Personal Systems Reference Lenovo® ThinkVision® Monitors

May 2013 - Version 436




ThinkVision LT2323z Wide Monitor


Visit www.lenovo.com/psref for the latest version

<p>Name D186 Wide Flat Panel Monitor Case color Business black Type-model 2580-AB1 Panel TFT-LCD, twisted nematic (TN), CCFL backlight Viewable image size 18.5" (470mm) diagonal Max view area (W x H) 16.1" x 9.1" / 409.8mm x 230.4mm Optimum resolution 1366x768 at 60Hz Maximum resolution 1366x768 at 60Hz (135MHz max pixel rate) Aspect ratio 16:9 Pixel pitch (mm) .300mm Dot/Pixel per Inch 85 dpi Brightness 200 nits or cd/m² (typical) Contrast ratio 600:1 (typical) Pixel response time 5ms (typical) Color gamut 67% Anti-reflective Anti-reflective, anti-glare Viewing angle at 10:1 CR 90° (+/- 45°) horizontal, 50° (+/- 25°) vertical Stand Tilt adjustable stand Bezel width Sides: 0.61" (15.6mm); top: 0.67" (17.1mm); bottom: 1.19" (30.1mm)</p> <p>Dimensions (HxWxD) 14.6" H x 17.4" W x 8.3" D; 370mm H x 442mm W x 210mm D</p> <p>Power supply 16 watts typical, 24 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply)</p> <p>Weight 7.28 lb; 3.3kg</p> <p>Limited warranty⁴ 3 years (includes backlight)</p> <p>Available date January 2010</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 18.5-inch monitor • High Definition (HD) ready; 1366x768 resolution • Detachable stand tilts for comfortable viewing • Supports VESA mount (100mm) • 50% less mercury • Kensington® lock slot ready for enhanced security 						
<p>VESA-compliant² VESA DDC2B/C1, VESA DPMS-compliant</p> <p>Power management None</p> <p>Ergonomics ISO 9241-307</p> <p>Pixel defect ISO 9241-307 pixel defect standard</p> <p>Emission standards FCC Class B</p> <p>Environmental WEEE, RoHS (EU Directive 2002/95/EC),</p> <p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 WXGA: 1280x720, 1280x768 1360x768, 1366x768</p> <p>Presets Standard presets: 20; user settings: 16</p>	 <p>Lenovo D186 Wide Monitor</p>						
<p>Viewing adjustments Tilt: 20° back, -5° forward; no lift; no swivel; detachable stand</p> <p>Rotating screen None</p> <p>On screen display On screen display with digital user controls (8 languages)</p> <p>Control features Direct access (control buttons on front) for automatic image setup and adjustment for brightness</p> <p>USB hub None</p> <p>Multiple input None</p> <p>Monitor connectors VGA 15-pin D-shell, analog, blue</p> <p>Signal cables Detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</p> <p>Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</p> <p>Security Security keyhole for attachment of optional cable lock (Kensington lock-compatible)</p>							
<p>Ship group Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter black power cord</p>							
<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ⇒ 3 year limited warranty⁴ ⇒ International Warranty Service⁵ ⇒ Replacement normally arrives in two business days, excluding holidays ⇒ Lenovo pays all shipping costs for valid warranty claims⁶ ⇒ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ⇒ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td style="text-align: right;">55Y9258</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision</p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington MicroSaver® Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						
Lenovo Easy Reach Monitor Stand	55Y9258						


See footnotes for important warranty information
 US model announced January 12, 2010

<p>Name LS1922 Wide Flat Panel Monitor Case color Business black Type-model 2580-AF1 Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 18.5" (470mm) diagonal Max view area (W x H) 16.1" x 9.1" / 409.8mm x 230.4mm Native resolution 1366x768 Aspect ratio 16:9 Pixel pitch (mm) .300mm Dot/Pixel per Inch 85 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt adjustable stand Bezel width <i>Sides: 0.61" (15.6mm); top: 0.67" (17.1mm); bottom: 1.19" (30.1mm)</i> Dimensions (HxWxD) 14.54" H x 17.38" W x 8.25" D; 370.1mm H x 442.2mm W x 210.0mm D Power supply 14 watts typical, 18 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 6.55 lb; 2.97 kg Limited warranty⁴ 3 year (includes backlight) Available date February 2012</p>	<p style="text-align: center;">Features</p> <ul style="list-style-type: none"> • Widescreen 18.5-inch monitor • Supports HD 1366x768 resolution • Supports VESA mount (100mm) • Mercury free panel and arsenic free glass • Kensington® lock slot ready for enhanced security • Microsoft® Windows® 7 certified • Support Lenovo Tiny PC via VESA mount 										
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR® 5.1 Ergonomics ISO 9241-307 Emission standards FCC Class B Environmental TCO (TCO Displays 5.2), WEEE, RoHS</p>	<div style="text-align: center;">  <p>ThinkVision LS1922 Wide Monitor</p> </div>										
<p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 WXGA: 1280x720, 1280x768, 1360x768, 1366x768</p> <p>Presets / user settings Standard presets: 16 (VGA); user settings: 16</p>											
<p>Viewing adjustments <i>Tilt: 20° backward, -5° forward</i> Rotating screen None On screen display On screen display with digital user controls (8 languages) Control features Direct access (control buttons on front) for automatic image setup and adjustment for brightness Multiple input None Monitor connectors VGA 15-pin D-shell, analog, blue Signal cables detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>											
<p>Ship group Monitor, attached stand, Setup poster with Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter black power cord</p>											
<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td style="text-align: right;">57Y4303</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td style="text-align: right;">55Y9258</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td style="text-align: right;">57Y4352</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm	57Y4352
Kensington® MicroSaver® Cable Lock	73P2582										
Kensington Twin Head Cable Lock	45K1620										
Lenovo Security Cable Lock	57Y4303										
Lenovo Easy Reach Monitor Stand	55Y9258										
ThinkCentre Extend Arm	57Y4352										


See footnotes for important warranty information
 US model announced February 28, 2012

<p>Name LS2023 Wide Flat Panel Monitor Case color Business black Type-model 3778-HB2 Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 20.0" (508mm) diagonal Max view area (W x H) 17.4" x 9.8" (443mm x 249mm) Native resolution 1600x900 Aspect ratio 16:9 Pixel pitch (mm) .276mm Dot/Pixel per Inch 92 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt adjustable stand Bezel width <i>Sides:</i> 0.598" (15.2mm); <i>top:</i> 0.606" (15.4mm); <i>bottom:</i> 1.020" (25.9mm) Dimensions (HxWxD) 14.28" H x 18.71" W x 6.19" D; 362.8mm H x 475.1mm W x 157.4mm D Power supply 19 watts typical, 22 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 7.01 lb; 3.18 kg Limited warranty⁴ 3 year (includes backlight) Available date September 2012</p>	<p style="text-align: center;">Features</p> <ul style="list-style-type: none"> • Widescreen 20-inch monitor • Supports 1600x900 resolution • Includes dual input connection for attachment to two systems concurrently (analog and digital) • Arsenic free glass • EPEAT Gold certified • Microsoft® Windows® 7 certified 				
<p>VESA-compliant² VESA DDC2B/CI Power management ENERGY STAR® qualified Ergonomics ISO 9241-307 Emission standards FCC Class B Environmental TCO (TCO Displays 6.0), WEEE, RoHS EPEAT™ Gold rating</p>	<div style="text-align: center;">  <p>ThinkVision LS2023 Wide Monitor</p> </div>				
<p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 WXGA: 1280x800, 1280x768, 1280x720, 1360x768 WXGA+: 1440x900, 1600x900 Presets / user settings Standard presets: 16 user settings: 16</p>					
<p>Viewing adjustments <i>Tilt:</i> 21° backward, -5° forward Rotating screen None On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup, dual input and brightness Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Ship group Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</p>				
<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington® MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				


See footnotes for important warranty information
 US model announced September 18, 2012

<p>Name LS2223 Wide Flat Panel Monitor Case color Business black Type-model 3783-HB2 Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 21.5" (546mm) diagonal Max view area (W x H) 18.76" x 10.55" (476.6mm x 268.1mm) Native resolution 1920x1080 Aspect ratio 16:9 Pixel pitch (mm) .248mm Dot/Pixel per Inch 103 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt adjustable stand Bezel width <i>Sides:</i> 0.591" (15.0mm); <i>top:</i> 0.701" (17.8mm); <i>bottom:</i> 0.996" (25.3mm) Dimensions (HxWxD) 15.08" H x 20.00" W x 6.19" D; 383.0mm H x 508.0mm W x 157.4mm D Power supply 21 watts typical, 25 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 7.74 lb; 3.51 kg Limited warranty⁴ 3 year (includes backlight) Available date September 2012</p>	<p style="text-align: center;">Features</p> <ul style="list-style-type: none"> • Widescreen 21.5-inch monitor • Supports Full HD 1920x1080 resolution • Includes dual input connection for attachment to two systems concurrently (analog and digital) • Arsenic free glass • EPEAT Gold certified • Microsoft® Windows® 7 certified 				
<p>VESA-compliant² VESA DDC2B/CI Power management ENERGY STAR® qualified Ergonomics ISO 9241-307 Emission standards FCC Class B Environmental TCO (TCO Displays 6.0), WEEE, RoHS EPEAT™ Gold rating</p>	<div style="text-align: center;">  <p>ThinkVision LS2223 Wide Monitor</p> </div>				
<p>Preset resolutions VGA: 640x350, 640x480, 720x480 SVGA: 800x600 XGA: 1024x768 SXGA: 1280x1024 WXGA: 1280x800, 1280x768, 1280x720, 1360x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080 Presets / user settings Standard presets: 16 user settings: 16</p>					
<p>Viewing adjustments <i>Tilt:</i> 21° backward, -5° forward Rotating screen None On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup, dual input and brightness Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Ship group Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</p>				
<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington® MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

See footnotes for important warranty information
 US model announced September 18, 2012


<p>Name LS2323 Wide Flat Panel Monitor Case color Raven black Type-model 3794-HB1 Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 23" (584mm) diagonal Max view area (W x H) 20.04" x 11.28" (509.2mm x 286.4mm) Native resolution 1920x1080 Aspect ratio 16:9 Pixel pitch (mm) .265mm Dot/Pixel per Inch 96 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt adjustable stand Bezel width <i>Sides: 0.709" (18.0mm); top: 0.709" (18.0mm); bottom: 1.197" (30.4mm)</i></p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 23-inch monitor • Supports Full HD 1920x1080 resolution • Includes dual input connection for attachment to two systems concurrently (analog and digital) • Arsenic free glass • EPEAT Gold certified • Microsoft® Windows® 7 certified 				
<p>Dimensions (HxWxD) 15.92" H x 21.57" W x 7.67" D; 403.9mm H x 547.8mm W x 194.9mm D Power supply 30 watts typical, 35 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 8.20 lb; 3.72 kg Limited warranty⁴ 3 year (includes backlight) Available date September 2012</p>	 <p>ThinkVision LS2323 Wide Monitor</p>				
<p>VESA-compliant² VESA DDC/CI, VESA DPMS-compliant Power management ENERGY STAR® qualified Ergonomics ISO 9241-307 Emission standards FCC Class B Environmental TCO (TCO Displays 5.2), RoHS EPEAT™ Gold rating</p>	<p>Preset resolutions VGA: 640x350, 640x480, 720x400, 700x570 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080 Presets / user settings Standard presets: 26; user settings: 26</p>				
<p>Viewing adjustments <i>Tilt: 21° backward, -5° forward</i> Rotating screen None On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons at the middle bottom of the front bezel) for automatic image setup and brightness Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington® MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				
<p>Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 					

See footnotes for important warranty information
 US model announced September 18, 2012


<p>Name LT1421 Wide Mobile Monitor Case color Raven black Type-model 1452-DS6 (with Protective Screen Cover) Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 14.0" (355.6mm) diagonal Max view area (W x H) 12.2" x 6.9" (310.8mm x 175.3mm) Optimum resolution 1366x768 Aspect ratio 16:9 Pixel pitch (mm) .227mm Dot/Pixel per Inch 112 dpi Brightness 200 nits or cd/m² (typical) Contrast ratio 400:1 (typical) Pixel response time 8ms (typical) Color gamut 45% Viewing angle at 10:1 CR 90° (+/- 45°) horizontal, 50° (+/- 25°) vertical Stand Tilt adjustable stand Bezel width Sides: 0.476" (12.1mm) Dimensions (HxWxD) 8.58" H x 13.19" W x 0.37-0.85" D; 217.9mm H x 335mm W x 9.3-21.5mm D Power supply 4.2 watts typical, 5 watts maximum, <0.1 watts standby/suspend, universal, USB 2.0 cable (no external brick-like power supply) Weight monitor only: 1.91 lb; 0.87 kg; with Protective Screen Cover: 2.31 lb; 1.05 kg Limited warranty⁴ 3 year (includes backlight) Available date September 2011</p>	<p style="text-align: center;">Features</p> <ul style="list-style-type: none"> • Widescreen 14-inch mobile monitor designed for ThinkPad • Light and Slim • Super low power (<5 watts) • Supports 1366x768 resolution • Ergonomic stand tilts, provides a 12° - 40° backward tilt adjustment for comfortable viewing • Detachable USB cable for power and signal • Microsoft® Windows® 7 certified  <p style="text-align: center;">ThinkVision LT1421 Wide Mobile Monitor</p>  <p style="text-align: center;">ThinkVision LT1421 Wide Mobile Monitor with ThinkPad Edge E420s</p>  <p style="text-align: center;">ThinkVision LT1421 with Protective Screen Cover</p>
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR[®] 5.1 Emission standards FCC Class B Environmental WEEE, RoHS Preset resolutions Display mode and resolution auto setup</p>	
<p>Protective Screen Cover Polycarbonate Snap-On Cover protects the LCD Screen while not in use</p>	
<p>Viewing adjustments Tilt: 12° - 40° backward Screen control Brightness (16 levels) Input USB input Monitor connectors USB 2.0 Signal cables detachable, USB Y-Type cable, 1.8 meter Mounting features None Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	
<p>Ship group Monitor, attached tile stand that cannot be removed, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter USB Y-Type cable, Protective Screen Cover</p>	

<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ⇒ 3 year limited warranty⁴ ⇒ International Warranty Service⁵ ⇒ Replacement normally arrives in two business days, excluding holidays ⇒ Lenovo pays all shipping costs for valid warranty claims⁶ ⇒ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ⇒ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington® MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

See footnotes for important warranty information
 US model announced August 16, 2011

<p>Name L1711p Flat Panel Monitor Case color Business black Type-model 5047-HB2 Panel TFT-LCD, twisted nematic (TN), CCFL backlight Viewable image size 17.0" (432mm) diagonal Max view area (W x H) 13.3" x 10.6" (337.9mm x 270.3mm) Optimum resolution 1280x1024 at 60Hz Maximum resolution 1280x1024 at 75Hz (165MHz max pixel rate) Aspect ratio 5:4 Pixel pitch (mm) 0.264mm Dot/Pixel per Inch 96 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Anti-reflective Anti-reflective, anti-glare Vertical frequency 50 to 75Hz Horizontal frequency 30 to 83kHz Viewing angle at 10:1 CR 160° (+/- 80°) horizontal, 160° (+/- 80°) vertical Stand Tilt height adjustable stand Bezel width <i>Sides: 0.6" (15.3mm); top: 0.72" (18.4mm); bottom: 1.11" (28.1mm)</i> Dimensions (HxWxD) 16-20.33" H x 14.6" W x 6.1" D; 405.7-515.7mm H x 370mm W x 155.2mm D Power supply 18 watts typical, 21 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 9.3 lb; 4.21kg Limited warranty⁴ 3 year (includes backlight) Available date November 2009</p>	<p style="text-align: center;">Features</p> <ul style="list-style-type: none"> • Regular screen 17-inch monitor • Supports SXGA 1280x1024 resolution • Ergonomic stand tilts and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Includes dual input connection for attachment to two systems concurrently (analog and digital) • Reduces mercury content by 50% and arsenic free glass • Up to 70% recycled packaging materials • Privacy Filter Slot • Microsoft® Windows® 7 certified 						
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR® 5.0 Ergonomics ISO 9241-307 Emission standards MPR-2, MPR-3A, FCC Class B Environmental TCO (TCO Displays 5.0), WEEE, RoHS, EPEAT™ Gold rating</p> <p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 SXGA: 1280x1024</p> <p>Presets / user settings Standard presets: 17; user settings: 22</p>	<div style="text-align: center;">  <p>ThinkVision L1711p Monitor</p> </div>						
<p>Viewing adjustments <i>Tilt: 20° back, -3° forward; lift: 4.3" (110mm); detachable stand</i> Rotating screen None On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Ship group Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</p>						
<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ⇒ 3 year limited warranty⁴ ⇒ International Warranty Service⁵ ⇒ Replacement normally arrives in two business days, excluding holidays ⇒ Lenovo pays all shipping costs for valid warranty claims⁶ ⇒ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9215) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ⇒ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td style="text-align: right;">55Y9258</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington® MicroSaver® Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						
Lenovo Easy Reach Monitor Stand	55Y9258						

See footnotes for important warranty information
 US model announced October 20, 2009

<p>Name LT1712p Flat Panel Monitor Case color Business black Type-model 5047-HC2 Panel TFT-LCD, twisted nematic (TN), CCFL backlight Viewable image size 17.0" (432mm) diagonal Max view area (W x H) 13.3" x 10.6" (337.9mm x 270.3mm) Optimum resolution 1280x1024 Aspect ratio 5:4 Pixel pitch (mm) 0.264mm Dot/Pixel per Inch 96 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt height adjustable stand Bezel width <i>Sides:</i> 0.60" (15.3mm); <i>top:</i> 0.72" (18.4mm); <i>bottom:</i> 1.11" (28.1mm) Dimensions (HxWxD, excluding stand) 12.5" H x 14.6" W x 2.1" D; 318.3mm H x 370.0mm W x 53.0mm D Dimensions (HxWxD, including stand) 16.0" H x 14.6" W x 6.1" D; 405.7mm H x 370.0mm W x 155.2mm D Power supply 15.5 watts typical, 19.0 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 9.35 lb; 4.24kg Limited warranty⁴ 3 year (includes backlight) Available date January 2013</p>	<p>Features</p> <ul style="list-style-type: none"> • 17-inch Square LCD monitor • Supports SXGA 1280x1024 resolution • Ergonomic stand tilts and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Includes dual input connection for attachment to two systems concurrently (analog and digital) • Arsenic free glass • Supports Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket • Microsoft® Windows® 7 certified 						
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR® 6.0 Ergonomics ISO 9241-307 Emission standards MPR-2, FCC Class B Environmental TCO Displays 6.0, TCO Certified Edge 1.1, WEEE, RoHS, EPEAT™ Gold rating</p>	 <p>ThinkVision LT1712p Monitor</p>						
<p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 SXGA: 1280x1024 Presets / user settings Standard presets: 17; user settings: 22</p>							
<p>Viewing adjustments <i>Tilt:</i> 20° back, -3° forward; <i>lift:</i> 4.3" (110mm); detachable stand Rotating screen None On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>							
<p>Ship group Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</p>							
<p>Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</p>	<p>Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington® MicroSaver® Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						
Lenovo Easy Reach Monitor Stand	55Y9258						

See footnotes for important warranty information
 US model announced July 3, 2012

Flat Panel Monitors - US model	Features						
<p>Name L197 Wide Flat Panel Monitor Case color Business black Type-model 4434-HE1 Stand Tilt stand Screen LCD Active Matrix TFT (Thin Film Transistor) Viewable image size (diag) 19.0" / 481mm (diagonal) Aspect ratio 16:10 Pixel pitch (mm) .285mm Max view area (inches) 16.1" x 10.0" (horizontal x vertical) Max view area (mm) 408mm x 255mm (horizontal x vertical) Viewing angle at 5:1 CR 176° vertical, 176° horizontal Viewing angle at 10:1 CR 160° vertical, 170° horizontal Video input Digital or analog (two separate connectors) Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Rotating screen No pivot USB Hub None</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 19-inch flat panel monitor • EPEAT™ Gold rating • View images in a 16:10 wide aspect ratio • Resolution of 1440x900 provides crisp screen images • Slim 14.3mm (0.56") side bezel • High-bandwidth Digital Content Protection (HDCP)-compliant • Includes dual input connection for attachment to two systems concurrently (analog and digital) • Complements the ThinkCentre® and ThinkPad® systems • Microsoft® Windows® Vista™ Premium certified 						
<p>Optimum resolution 1440x900 at 60Hz Maximum resolution 1440x900 at 75Hz (137MHz maximum pixel rate) Vertical frequency 50 to 76Hz Horizontal frequency 30 to 81kHz Preset display modes VGA: 640x480 60, 66, 72, 75Hz 640x350 70Hz 720x400 70Hz SVGA: 800x600 56, 60, 72, 75Hz 832x624 75Hz XGA: 1024x768 60, 70, 75Hz 1152x864 75Hz SXGA: 1280x1024 60, 70, 75Hz WXGA+: 1440x900 60, 75Hz Presets / user settings Standard presets: 20; user settings: 20 Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72%</p>	 <p style="text-align: center;">Lenovo ThinkVision L197 Wide</p>						
<p>On screen display On screen display with digital user controls (7 languages) Control features Direct access (buttons on front) for automatic image setup Monitor connectors Two connectors: (1) analog VGA 15-pin D-shell [blue], (2) Digital Visual Interface (DVI-D) for digital (not analog) attach [white], HDCP-compliant Signal cables Two cables: (1) detachable, VGA 15-pin D-shell at each end (for analog connector), 1.8 meter, matches color of monitor (2) detachable digital, DVI-D at each end (for digital connector), 1.8 meter, matches color of monitor Anti-reflective Anti-reflective, anti-glare Dimensions 15.0"H x 17.3"W x 7.0"D / 381mm height x 440mm width x 179mm depth Weight 9.15lb / 4.15kg Viewing adjustments Tilt: 30° back, 4° forward / no lift, no swivel, detachable stand Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>							
<p>VESA-compliant² VESA DDC2B/C1, VESA DPMS-compliant Power management ENERGY STAR®³ 5.0 Ergonomics ISO 13406 Part 2¹ Pixel defect ISO 13406-2 Class II pixel defect standard Emission standards MPR-2, MPR-3A, FCC Class B Environmental TCO 03, WEEE, RoHS (EU Directive 2002/95/EC), EPEAT™ Gold rating Ship group Monitor, attached stand, Setup Guide, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, digital signal cable, 1.8m black power cord Power supply 90-264Vac (universal), integrated (no external brick-like power supply), 22 watts typical, <2 watts standby/suspend Limited warranty⁴ 3 year (includes backlight) Available date April 2008</p>							
<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ↔ 3 year limited warranty⁴ ↔ International Warranty Service⁵ ↔ Replacement normally arrives in two business days, excluding holidays ↔ Lenovo pays all shipping costs for valid warranty claims⁶ ↔ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↔ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td style="text-align: right;">55Y9258</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington® MicroSaver® Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						
Lenovo Easy Reach Monitor Stand	55Y9258						

See footnotes for important warranty information
 US model announced April 15, 2008

Name	L1900p Flat Panel Monitor
Case color	Business black
Type-model	4431-HE1
Panel	TFT-LCD, twisted nematic (TN), CCFL backlight
Viewable image size	19.0" (483mm) diagonal
Max view area (W x H)	14.8" x 11.85" (376mm x 301mm)
Optimum resolution	1280x1024 at 60Hz
Maximum resolution	1280x1024 at 75Hz (135MHz max pixel rate)
Aspect ratio	5:4
Pixel pitch (mm)	.294mm
Dot/Pixel per Inch	86 dpi
Brightness	250 nits or cd/m ² (typical)
Contrast ratio	800:1 (typical)
Pixel response time	5ms (typical)
Color gamut	72%
Anti-reflective	Anti-reflective, anti-glare
Vertical frequency	56 to 76Hz
Horizontal frequency	30 to 81kHz
Viewing angle at 10:1 CR	160° (+/- 80°) horizontal, 160° (+/- 80°) vertical
Stand	Tilt, swivel, pivot, and height adjustable stand
Bezel width	<i>Sides:</i> 0.6" (15.3mm); <i>top:</i> 0.66" (16.8mm); <i>bottom:</i> 1.05" (26.8mm)
Dimensions (HxWxD)	14.9-19.2" H x 16.1" W x 7.4-9.5" D; 378.7-488.7mm H x 408mm W x 188-241.1mm D
Power supply	17 watts typical, 24 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply)
Weight	12.5 lb; 5.7kg
Limited warranty ⁴	3 year (includes backlight)
Available date	November 2008

VESA-compliant ²	VESA DDC2B/CI, VESA DPMS-compliant
Power management	ENERGY STAR ^{®3} 5.0
Ergonomics	ISO 13406 Part 2 ¹
Pixel defect	ISO 13406-2 Class II pixel defect standard
Emission standards	MPR-2, MPR-3A, FCC Class B
Environmental	TCO 03, WEEE, RoHS (EU Directive 2002/95/EC), EPEAT™ Gold rating , GREENGUARD [®] certified

Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 SXGA: 1280x1024
Presets / user settings	Standard presets: 21; user settings: 17

Viewing adjustments	<i>Tilt:</i> 30° back, 0° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand
Rotating screen	Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller)
On screen display	On screen display with digital user controls (8 languages)
Control features	Direct access (buttons on front) for automatic image setup
Multiple input	Multiple input (two different PCs attach to two different connectors; one PC shows image; select via button)
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI [®] (100mm mount)
Security	Security keyhole for attachment of optional cable lock (Kensington [®] lock-compatible)

Ship group	Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord
------------	--

- Features**
- Regular screen 19-inch monitor
 - Supports SXGA 1280x1024 resolution
 - Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing
 - Detachable rear stand cable cover and clip to hide cables
 - Microsoft® Windows® Vista® certified



ThinkVision L1900p Monitor with optional ThinkVision Soundbar


Limited Warranty	
↪	3 year limited warranty⁴
↪	International Warranty Service⁵
↪	Replacement normally arrives in two business days, excluding holidays
↪	Lenovo pays all shipping costs for valid warranty claims⁶
↪	Service upgrade options:⁷
•	3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209)
•	4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233)
•	4 year, mail exchange (51J0589)
•	5 year, mail exchange (51J0590)
↪	24x7⁸ day toll-free support for warranty issues during the warranty period⁴

Accessories	
Kensington® MicroSaver® Cable Lock	73P2582
Kensington Twin Head Cable Lock	45K1620
Lenovo Easy Reach Monitor Stand	55Y9258
See details at www.lenovo.com/support/monitoraccessories	
See all monitors at www.lenovo.com/thinkvision	

See footnotes for important warranty information
US model announced November 11, 2008


<p>Name LT1952p Wide Flat Panel Monitor Case color Business black Type-model 2448-MB6 Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 19" (482.6mm) diagonal Max view area (W x H) 16.07" x 10.05" (408.2mm x 255.2mm) Optimum resolution 1440x900 Max pixel rate 137MHz Aspect ratio 16:10 Pixel pitch (mm) 0.2835mm Dot/Pixel per Inch 89.4 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Anti-reflective Anti-reflective, anti-glare Viewing angle at 10:1 CR 170° horizontal, 160° vertical Stand Tilt, swivel, and height adjustable stand Bezel width Sides: 0.61" (15.6mm); top: 0.67" (17.1mm); bottom: 1.2" (30.5mm)</p> <p>Dimensions (HxWxD) 15.66-19.99" H x 17.36" W x 6.74" D; 397.7-507.7mm H x 440.9mm W x 171.3mm D</p> <p>Power supply 13 watts typical, 17 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</p> <p>Weight 9.49 lb; 4.30kg</p> <p>Limited warranty⁴ 3 year (includes backlight)</p> <p>Available date September 2011</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 19-inch monitor • Supports 1440x900 resolution • Ergonomic stand tilts, swivel, and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Cable Management for better user experience • Mercury and arsenic free glass • Recycled content in plastic material • Privacy Filter Slot • Microsoft® Windows® 7 certified 												
<p>VESA-compliant² VESA DDC2B/CI</p> <p>Power management ENERGY STAR® 5.1</p> <p>Ergonomics ISO 9241-307</p> <p>Emission standards MPR-2, FCC Class B</p> <p>Environmental TCO Displays 5.2, TCO Certified Edge 1.1, WEEE, RoHS, EPEAT™ Gold rating, ULE Gold</p>	<div data-bbox="980 443 1471 1003" data-label="Image"> </div> <p>ThinkVision LT1952p Wide Monitor</p>												
<p>Preset resolutions</p> <table border="0"> <tr> <td>VGA:</td> <td>640x350, 640x480, 720x400</td> </tr> <tr> <td>SVGA:</td> <td>800x600</td> </tr> <tr> <td>XGA:</td> <td>1024x768, 1152x864</td> </tr> <tr> <td>SXGA:</td> <td>1280x1024</td> </tr> <tr> <td>WXGA:</td> <td>1280x768, 1366x768</td> </tr> <tr> <td>WXGA+:</td> <td>1440x900</td> </tr> </table> <p>Presets / user settings</p> <p>Standard presets: 22; user settings: 22</p>		VGA:	640x350, 640x480, 720x400	SVGA:	800x600	XGA:	1024x768, 1152x864	SXGA:	1280x1024	WXGA:	1280x768, 1366x768	WXGA+:	1440x900
VGA:	640x350, 640x480, 720x400												
SVGA:	800x600												
XGA:	1024x768, 1152x864												
SXGA:	1280x1024												
WXGA:	1280x768, 1366x768												
WXGA+:	1440x900												
<p>Viewing adjustments Tilt: 20° back, -3° forward; lift: 4.3" (110mm); swivel: +/-180°; detachable stand</p> <p>Rotating screen None</p> <p>On screen display On screen display with digital user controls (8 languages)</p> <p>Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness</p> <p>Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</p> <p>Monitor connectors</p> <ol style="list-style-type: none"> (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant (3) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant <p>Signal cables</p> <ol style="list-style-type: none"> (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter <p>Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)</p> <p>Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</p> <p>Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Ship group Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord</p>												
<p>Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p>Accessories</p> <table border="0"> <tr> <td>DisplayPort to DisplayPort Monitor Cable</td> <td>0A36537</td> </tr> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	DisplayPort to DisplayPort Monitor Cable	0A36537	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258
DisplayPort to DisplayPort Monitor Cable	0A36537												
Kensington MicroSaver Cable Lock	73P2582												
Kensington Twin Head Cable Lock	45K1620												
Lenovo Security Cable Lock	57Y4303												
ThinkCentre Extend Arm	57Y4352												
Lenovo Easy Reach Monitor Stand	55Y9258												

See footnotes for important warranty information
 US model announced September 13, 2011


<p>Name LT1953 Wide Flat Panel Monitor Case color Business black Type-model 1453-HB1 (Latin America) Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 19" (482.6mm) diagonal Max view area (W x H) 16.07" x 10.05" (408.2mm x 255.2mm) Optimum resolution 1440x900 Max pixel rate 205MHz(VGA), 165MHz(DVI) Aspect ratio 16:10 Pixel pitch (mm) 0.2835mm Dot/Pixel per Inch 89.4 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Viewing angle at 10:1 CR 170° horizontal, 160° vertical Stand Tilt stand Bezel width Sides: 0.66" (16.8mm); top: 0.66" (16.8mm); bottom: 0.66" (16.8mm) Dimensions (HxWxD, excluding stand) 290.2mm H x 443.2mm W x 50.5mm D Dimensions (HxWxD, including stand) 354.0mm H x 443.2mm W x 160.7mm D Power supply 17 watts typical, 20 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 6.61 lb; 3.00kg Limited warranty⁴ 3 year (includes backlight) Available date March 2013</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 19-inch monitor • Supports 1440x900 resolution • VGA and DVI connections • Arsenic free glass • Support Lenovo Tiny PC via VESA mount • 85% PCC plastic resins • Microsoft® Windows® 7 certified • Microsoft Windows 8 certified
<p>VESA-compliant² VESA DDC2B/CI Power management ENERGY STAR® 6.0 Ergonomics ISO 9241-307 Emission standards MPR-2, FCC Class B Environmental TCO Displays 6.0, TCO Certified Edge 1.1, WEEE, RoHS, EPEAT™ Gold rating, ULE Gold</p>	<div style="text-align: center;">  <p>ThinkVision LT1953 Wide Monitor</p> </div>
<p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA+: 1440x900 Presets / user settings Standard presets: 20; user settings: 20</p>	
<p>Viewing adjustments Tilt: 22° back, -5° forward; Rotating screen None On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	
<p>Ship group Monitor, tilt stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord</p>	

<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington MicroSaver Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td style="text-align: right;">57Y4303</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303
Kensington MicroSaver Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						
Lenovo Security Cable Lock	57Y4303						

See footnotes for important warranty information
 Latin America model announced March 5, 2013 (This model is not available in the US)


<p>Name LT2013p Wide Flat Panel Monitor Case color Business black Type-model 60A0MAR1US Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 19.5" (494mm) diagonal Max view area (W x H) 17.05" x 9.44" / 433.0mm x 239.8mm Optimum resolution 1600x900 Aspect ratio 16:9 Pixel pitch (mm) .27mm Dot/Pixel per Inch 94 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt, swivel, pivot, and height adjustable stand (toolless detachable)</p>	<p style="text-align: center;">Features</p> <ul style="list-style-type: none"> • Widescreen 19.5-inch monitor • HD support, HDCP-compliant • Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Compliance with ENERGY STAR 6.0 • Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket • Arsenic/Lead/Mercury free • EPEAT Gold certified • Microsoft® Windows® 7 certified • Microsoft Windows 8 certified 										
<p>Bezel width Sides: 0.66" (16.8mm); top: 0.66" (16.8mm); bottom: 0.66" (16.8mm)</p> <p>Dimensions (HxWxD, excluding stand) 10.82" H x 18.39" W x 2.07" D; 274.8mm H x 467.0mm W x 52.8mm D Dimensions (HxWxD, including stand) 13.25" H x 18.39" W x 7.87" D; 336.5mm H x 467.0mm W x 200.0mm D</p> <p>Power supply 17 watts typical, 36 watts maximum, <1.0 watts sleep/off (w/o USB hub); <0.5 watts switch off (w/o USB hub) integrated (no external brick-like power supply)</p> <p>Weight 9.70 lb; 4.40kg (excluding stand) Limited warranty⁴ 3 year (includes backlight) Available date March 2013</p>	<div style="text-align: center;">  <p>ThinkVision LT2013p Wide Monitor</p> </div>										
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR^{®3} 6.0 Ergonomics ISO 9241-307 Emission standards MPR-2, FCC Class B Environmental TCO Displays 6.0, TCO Certified Edge 1.1, RoHS, EPEAT™ Gold rating</p> <p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900 WSXGA+: 1600x900</p> <p>Presets / user settings Presets: 24; user settings: 24</p>	<p>Viewing adjustments Tilt: 30° back, -5° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand Rotating screen Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller, do not support image rotation under dual image modes)</p> <p>On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness</p> <p>USB hub USB 2.0 Hub (1 port into PC, 4 ports for accessories)</p> <p>Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</p> <p>Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant (3) HDMI (1.4), digital, HDCP-compliant</p> <p>Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</p> <p>Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI[®] (100mm mount)</p> <p>Security Security keyhole for attachment of optional cable lock (Kensington[®] lock-compatible)</p>										
<p>Ship group Monitor, toolless detachable stand, Quick start and safety poster, CD with multilingual User's Guide, setup test pattern, and monitor installation files, analog signal cable, 1.8 meter USB cable, 1.8 meter black power cord</p>	<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ <p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington[®] MicroSaver[®] Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td style="text-align: right;">57Y4303</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td style="text-align: right;">55Y9258</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td style="text-align: right;">57Y4352</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington [®] MicroSaver [®] Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm	57Y4352
Kensington [®] MicroSaver [®] Cable Lock	73P2582										
Kensington Twin Head Cable Lock	45K1620										
Lenovo Security Cable Lock	57Y4303										
Lenovo Easy Reach Monitor Stand	55Y9258										
ThinkCentre Extend Arm	57Y4352										

See footnotes for important warranty information
 US model announced March 12, 2013


<p>Name ThinkVision LT2223p 21.5-inch FHD LED Backlit LCD Monitor</p> <p>Case color Business black</p> <p>Type-model 60A1MAR2US</p> <p>Panel TFT-LCD, twisted nematic (TN), White LED backlight</p> <p>Viewable image size 21.5" (546mm) diagonal</p> <p>Max view area (W x H) 18.74" x 10.54" / 476.1mm x 267.8mm</p> <p>Optimum resolution 1920x1080</p> <p>Aspect ratio 16:9</p> <p>Pixel pitch (mm) 0.248mm</p> <p>Dot/Pixel per Inch 103 dpi</p> <p>Brightness 250 nits or cd/m² (typical)</p> <p>Contrast ratio 1000:1 (typical)</p> <p>Dynamic Contrast ratio 2000000:1</p> <p>Pixel response time 5ms (typical)</p> <p>Color gamut 72%</p> <p>Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</p> <p>Stand Tilt, swivel, pivot, and height adjustable stand (toolless detachable)</p> <p>Bezel width <i>Sides:</i> 0.68" (17.3mm); <i>top:</i> 0.68" (17.3mm); <i>bottom:</i> 0.68" (17.3mm)</p> <p>Dimensions (HxWxD, excluding stand) 304.1mm H x 512.6mm W x 56.4mm D</p> <p>Dimensions (HxWxD, including stand) 362.9mm H x 512.6mm W x 218.4mm D</p> <p>Power supply 23 watts typical, 27 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</p> <p>Weight (including stand) 10.94 lb; 4.96kg</p> <p>Weight (Head only) 6.77 lb; 3.07kg</p> <p>Limited warranty⁴ 3 year (includes backlight)</p> <p>Available date March 2013</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 21.5-inch monitor • 1080p full HD support • Integrated USB Hub (4 USB 2.0) • Supports VGA, DisplayPort 1.2 and HDMI 1.4 interfaces (HDCP-compliant) • Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Compliance with ENERGY STAR 6.0 • Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket • Arsenic/Lead/Mercury free • EPEAT Gold certified • Microsoft® Windows® 7 certified • Microsoft Windows 8 certified
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant</p> <p>Power management ENERGY STAR^{®3} 6.0</p> <p>Ergonomics ISO 9241-307</p> <p>Emission standards MPR-2, FCC Class B</p> <p>Environmental TCO Displays 6.0, TCO Certified Edge 1.1, RoHS, EPEAT™ Gold rating</p>	 <p>ThinkVision LT2223p Wide Monitor</p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p> <p>Presets / user settings Presets: 27; user settings: 20</p>	
<p>Viewing adjustments <i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand</p> <p>Rotating screen Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller, do not support image rotation under dual image modes)</p> <p>On screen display On screen display with digital user controls (8 languages)</p> <p>Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness</p> <p>USB hub USB 2.0 Hub: 1 port into PC (USB 2.0); 4 ports for accessories (4 USB 2.0)</p> <p>Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</p> <p>Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort (1.2), digital, black, HDCP-compliant (3) HDMI (1.4), digital, HDCP-compliant</p> <p>Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</p> <p>Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI[®] (100mm mount)</p> <p>Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Ship group Monitor, toolless detachable stand, Quick start and safety poster, CD with multilingual User's Guide, setup test pattern, and monitor installation files, analog signal cable, 1.8 meter USB cable, 1.8 meter black power cord</p>

<p>Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p>Accessories</p> <table border="0"> <tr> <td>Lenovo USB Soundbar</td> <td>0A36190</td> </tr> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Lenovo USB Soundbar	0A36190	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm	57Y4352
Lenovo USB Soundbar	0A36190												
Kensington® MicroSaver® Cable Lock	73P2582												
Kensington Twin Head Cable Lock	45K1620												
Lenovo Security Cable Lock	57Y4303												
Lenovo Easy Reach Monitor Stand	55Y9258												
ThinkCentre Extend Arm	57Y4352												

See footnotes for important warranty information
US model announced March 12, 2013


<p>Name ThinkVision LT2223z 21.5-inch FHD LED Backlit LCD VoIP Monitor Business black 60A2MAR2US Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 21.5" (546mm) diagonal Max view area (W x H) 18.74" x 10.54" / 476.1mm x 267.8mm Optimum resolution 1920x1080 Aspect ratio 16:9 Pixel pitch (mm) 0.248mm Dot/Pixel per Inch 103 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Dynamic Contrast ratio 2000000:1 Pixel response time 5ms (typical) Color gamut 72% Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt, swivel, pivot, and height adjustable stand (toolless detachable) Bezel width <i>Sides:</i> 0.68" (17.3mm); <i>top:</i> 1.33" (33.8mm); <i>bottom:</i> 1.88" (47.8mm) Dimensions (HxWxD, excluding stand) 351.1mm H x 512.6mm W x 56.4mm D Dimensions (HxWxD, including stand) 14.94" H x 20.18" W x 8.60" D 379.4mm H x 512.6mm W x 218.4mm D Power supply 24 watts typical, 28 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight (including stand) 11.98 lb; 5.43kg Weight (Head only) 7.79 lb; 3.53kg Limited warranty⁴ 3 year (includes backlight) Available date April 2013</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 21.5-inch monitor • 1080p full HD support • Integrated camera (FHD), speakers & dual digital microphone • Integrated USB 3.0 Hub (2 USB 3.0) • Supports VGA, DisplayPort 1.2 and HDMI 1.4 interfaces (HDCP-compliant) • Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Compliance with ENERGY STAR 6.0 • Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket • Arsenic/Lead/Mercury free • EPEAT Gold certified • Microsoft® Windows® 7 certified • Microsoft Windows 8 certified 										
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR^{®3} 6.0 Ergonomics ISO 9241-307 Emission standards MPR-2, FCC Class B Environmental TCO Displays 6.0, TCO Certified Edge 1.1, RoHS, EPEAT™ Gold rating</p> <p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900 WSXGA+: 1600x900, 1600x1050 Full HD: 1920x1080</p> <p>Presets / user settings Presets: 25; user settings: 20</p>	 <p>ThinkVision LT2223z Wide Monitor</p>										
<p>Viewing adjustments <i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand Rotating screen Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller, do not support image rotation under dual image modes) On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for MIC mute, speaker mute and hook switch buttons USB hub USB 3.0 Hub: 1 port into PC (USB 3.0); 2 ports for accessories (2 USB 3.0) Multimedia Integrated digital speakers (3 watts x 2) Camera Integrated camera (FHD) and digital dual microphone array, with Camera lock button for security Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort (1.2), digital, black, HDCP-compliant (3) HDMI (1.4), digital, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI[®] (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington[®] lock-compatible)</p>	<p>Ship group Monitor, toolless detachable stand, Quick start and safety poster, CD with multilingual User's Guide, setup test pattern, and installation files, analog signal cable, 1.8 meter USB 3.0 cable, 1.8 meter black power cord</p>										
<p>Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p>Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm	57Y4352
Kensington® MicroSaver® Cable Lock	73P2582										
Kensington Twin Head Cable Lock	45K1620										
Lenovo Security Cable Lock	57Y4303										
Lenovo Easy Reach Monitor Stand	55Y9258										
ThinkCentre Extend Arm	57Y4352										

See footnotes for important warranty information
 US model announced March 12, 2013

<p>Name L2250p Wide Flat Panel Monitor Case color Business black Type-model 2572-HB6 Panel TFT-LCD, twisted nematic (TN), CCFL backlight Viewable image size 22.0" (559mm) diagonal Max view area (W x H) 18.7" x 11.7" (473.8mm x 296.1mm) Optimum resolution 1680x1050 at 60Hz Maximum resolution 1680x1050 at 75Hz (205MHz max pixel rate) Aspect ratio 16:10 Pixel pitch (mm) .282mm Dot/Pixel per Inch 90 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Anti-reflective Anti-reflective, anti-glare Vertical frequency 50 to 75Hz Horizontal frequency 30 to 83kHz Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt and height adjustable stand Bezel width Sides: 0.60" (15.3mm); top: 0.79" (20.0mm); bottom: 1.10" (28.0mm) Dimensions (HxWxD) 15.68-18.83" H x 19.92" W x 6.11" D; 398.3-478.3mm H x 506mm W x 155.2mm D Power supply 21 watts typical, 28 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 11.49 lb; 5.21kg Limited warranty⁴ 3 year (includes backlight) Available date October 2009</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 22-inch monitor • Supports WSXGA+ 1680x1050 resolution • Ergonomic stand tilts and provides a 3.1" (80mm) range height adjustment for comfortable viewing • Includes dual input connection for attachment to two systems concurrently (analog and digital) • Reduces mercury content by 50% and arsenic free glass • Up to 65% recycled packaging materials • Privacy Filter Slot • Microsoft® Windows® 7 certified
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR® 5.0 Ergonomics ISO 9241-307 Emission standards MPR-2, MPR-3A, FCC Class B Environmental TCO (TCO Displays 5.0), WEEE, RoHS, EPEAT™ Gold rating</p>	 <p>ThinkVision L2250p Wide Monitor</p>
<p>Preset resolutions VGA: 640x350, 640x480, 720x480 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA+: 1440x900 UXGA: 1600x1000 WSXGA+: 1680x1050 Presets / user settings Standard presets: 24; user settings: 20</p>	
<p>Viewing adjustments Tilt: 20° back, -3° forward; lift: 3.1" (80mm); detachable stand Rotating screen None On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup USB hub None Camera None Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Ship group Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</p>

<p>Limited Warranty</p> <ul style="list-style-type: none"> ⇒ 3 year limited warranty⁴ ⇒ International Warranty Service⁵ ⇒ Replacement normally arrives in two business days, excluding holidays ⇒ Lenovo pays all shipping costs for valid warranty claims⁶ ⇒ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ⇒ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p>Accessories</p> <table border="0"> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington MicroSaver® Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						
Lenovo Easy Reach Monitor Stand	55Y9258						


See footnotes for important warranty information
 US model announced October 20, 2009

<p>Name LT2252p Wide Flat Panel Monitor Business black Case color Business black Type-model 2572-MB6 / 2572-MB1 Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 22" (559mm) diagonal Max view area (W x H) 18.7" x 11.7" (473.8mm x 296.1mm) Optimum resolution 1680x1050 Max pixel rate 205MHz Aspect ratio 16:10 Pixel pitch (mm) 0.282mm Dot/Pixel per Inch 90 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Anti-reflective Anti-reflective, anti-glare Viewing angle at 10:1 CR 170° horizontal, 160° vertical Stand Tilt, swivel, pivot, and height adjustable stand Bezel width Sides: 0.60" (15.3mm); top: 0.79" (20.0mm); bottom: 1.10" (28.0mm)</p> <p>Dimensions (HxWxD) 14.46-18.79" H x 19.92" W x 9.50" D; 367.3-477.3mm H x 506mm W x 241.2mm D</p> <p>Power supply 20 watts typical, 26 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</p> <p>Weight 12.97lb; 5.89kg</p> <p>Limited warranty⁴ 3 year (includes backlight)</p> <p>Available date September 2011</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 22-inch monitor • Supports 1680x1050 resolution • Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Cable Management for better user experience • Mercury and arsenic free glass • Recycled content in plastic material • Privacy Filter Slot • Microsoft® Windows® 7 certified • Model 2572-MB1 supports Lenovo Tiny PC via optional Lenovo bracket
<p>VESA-compliant² VESA DDC2B/CI</p> <p>Power management ENERGY STAR® 5.1 (2572-MB6) ENERGY STAR® 6.0 (2572-MB1)</p> <p>Ergonomics ISO 9241-307</p> <p>Emission standards MPR-2, FCC Class B</p> <p>Environmental TCO Displays 5.2, TCO Certified Edge 1.1, WEEE, RoHS, EPEAT™ Gold rating, ULE Gold</p>	 <p>ThinkVision LT2252p Wide Monitor</p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1280x800, 1366x768 WXGA+: 1440x900 1600x900 WSXGA+: 1680x1050</p> <p>Presets / user settings</p> <p>Standard presets: <i>VGA/DisplayPort</i>: 26; <i>DVI-D</i>: 25; user settings: 25</p>	
<p>Viewing adjustments Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</p> <p>Rotating screen Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller)</p> <p>On screen display On screen display with digital user controls (8 languages)</p> <p>Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness</p> <p>USB hub None</p> <p>Camera None</p> <p>Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</p> <p>Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant (3) Digital Visual Interface (DVI-D) for digital attach [white], HDCP-compliant</p> <p>Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter</p> <p>Mounting features Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)</p> <p>Security Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p> <p>Ship group Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord</p>	

Limited Warranty
<ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴


Accessories	
DisplayPort to DisplayPort Monitor Cable Kensington® MicroSaver® Cable Lock Kensington Twin Head Cable Lock Lenovo Security Cable Lock ThinkCentre Extend Arm Lenovo Easy Reach Monitor Stand	0A36537 73P2582 45K1620 57Y4303 57Y4352 55Y9258
See details at www.lenovo.com/support/monitoraccessories	
See all monitors at www.lenovo.com/thinkvision	

See footnotes for important warranty information
 US model announced September 13, 2011 or December 18, 2012


<p>Name L2251x Wide Flat Panel Monitor Case color Business black Type-model 2578-HB6 Panel TFT-LCD, twisted nematic (TN), white LED backlight Viewable image size 22.0" (559mm) diagonal Max view area (W x H) 18.7" x 11.7" / 473.8mm x 296.1mm Optimum resolution 1680x1050 at 60Hz Maximum resolution 1680x1050 at 75Hz (205MHz max pixel rate) Aspect ratio 16:10 Pixel pitch (mm) .282mm Dot/Pixel per Inch 90 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 68% Anti-reflective Anti-reflective, anti-glare Vertical frequency 50 to 75Hz Horizontal frequency 30 to 83kHz Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt, swivel, pivot, and height adjustable stand Bezel width Sides: 0.60" (15.3mm); top: 0.79" (20.0mm); bottom: 1.10" (28.0mm) Dimensions (HxWxD) 14.97-19.3" H x 19.92" W x 9.50" D; 380.3-490.3mm H x 506mm W x 241.2mm D Power supply 21 watts typical, 28 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 12.39 lb; 5.63kg Limited warranty⁴ 3 year (includes backlight) Available date November 2009</p>	<p style="text-align: center;">Features</p> <ul style="list-style-type: none"> • Widescreen 22-inch monitor with white LED backlight • Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Detachable rear stand cable cover and clip to hide cables • Integrated camera (0.3 megapixel) and microphone • Integrated ambient light sensor and a proximity sensor, save more energy and make viewing more comfortable • Low halogen, mercury free, and arsenic free glass, 92% recycled packaging materials • Privacy Filter Slot • Microsoft® Windows® 7 certified
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR[®] 5.0 Ergonomics ISO 9241-307 Emission standards MPR-2, MPR-3A, FCC Class B Environmental TCO (TCO Certified Edge), WEEE, RoHS, EPEAT™ Gold rating</p>	<div style="text-align: center;">  <p>ThinkVision L2251x Wide Monitor</p> </div>
<p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA+: 1440x900 UXGA: 1600x1000 WSXGA+: 1680x1050 Presets / user settings Standard presets: 24; user settings: 20</p>	
<p>Viewing adjustments Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand Rotating screen Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller) On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup USB hub USB 2.0 Hub (1 port into PC, 3 ports for accessories) Camera Integrated camera (0.3 megapixel) and microphone Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Ship group Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DisplayPort cable, 1.8 meter USB cable, 1.8 meter black power cord</p>

<p style="text-align: center;">Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p style="text-align: center;">Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td style="text-align: right;">73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td style="text-align: right;">45K1620</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td style="text-align: right;">55Y9258</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington® MicroSaver® Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						
Lenovo Easy Reach Monitor Stand	55Y9258						

See footnotes for important warranty information
 US model announced October 20, 2009

<p>Name LT2323p Wide Flat Panel Monitor Case color Raven black Type-model 3024-HC1 Panel TFT-LCD, twisted nematic (TN), White LED backlight Viewable image size 23.0" (584mm) diagonal Max view area (W x H) 18.65" x 11.66" / 473.8mm x 296.1mm Optimum resolution 1920x1080 Aspect ratio 16:9 Pixel pitch (mm) .265mm Dot/Pixel per Inch 96 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 5ms (typical) Color gamut 72% Anti-reflective Anti-reflective, anti-glare Vertical frequency 50 to 75Hz Horizontal frequency 30 to 83kHz Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Stand Tilt, swivel, pivot, and height adjustable stand (toolless detachable)</p> <p>Bezel width <i>Sides:</i> 0.68" (17.2mm); <i>top:</i> 0.70" (17.7mm); <i>bottom:</i> 0.94" (24.0mm)</p> <p>Dimensions (HxWxD) 14.66" H x 21.49" W x 2.06" D; (excluding stand) 372.3mm H x 546.0mm W x 52.3mm D</p> <p>Power supply 20 watts typical, 38 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</p> <p>Weight 12.65 lb; 5.74kg (excluding stand) Limited warranty⁴ 3 year (includes backlight) Available date May 2012</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 23-inch monitor • 1080p full HD support, HDCP-compliant • Built-in VGA, DVI and DisplayPort connectors for attachment to three systems concurrently • Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Compliance with ENERGY STAR 6.0 DRAFT • Microsoft® Windows® 7 certified 												
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR® 6.0 DRAFT Ergonomics ISO 9241-307 Emission standards MPR-2, FCC Class B Environmental TCO (TCO Certified Edge 1.1), WEEE, RoHS, EPEAT™ Gold rating</p> <p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1360x768 WXGA+: 1440x900 WSXGA+: 1680x1050 Full HD: 1920x1080</p> <p>Presets / user settings Presets: 26; user settings: 25</p>	 <p>ThinkVision LT2323p Wide Monitor</p>												
<p>Viewing adjustments <i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand Rotating screen Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller, do not support image rotation under dual image modes) On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness USB hub USB 2.0 Hub (1 port into PC, 4 ports for accessories) Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant (3) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537) Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Viewing adjustments <i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand Rotating screen Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller, do not support image rotation under dual image modes) On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness USB hub USB 2.0 Hub (1 port into PC, 4 ports for accessories) Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant (3) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537) Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>												
<p>Ship group Monitor, toolless detachable stand, Quick start and safety poster, CD with multilingual User's Guide, setup test pattern, and monitor installation files, analog signal cable, DVI-D cable, 1.8 meter USB cable, 1.8 meter black power cord</p> <p>Limited Warranty</p> <ul style="list-style-type: none"> ⇒ 3 year limited warranty⁴ ⇒ International Warranty Service⁵ ⇒ Replacement normally arrives in two business days, excluding holidays ⇒ Lenovo pays all shipping costs for valid warranty claims⁶ ⇒ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ⇒ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p>Accessories</p> <table border="0"> <tr> <td>Lenovo DisplayPort to DisplayPort Monitor Cable</td> <td>0A36537</td> </tr> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	Lenovo DisplayPort to DisplayPort Monitor Cable	0A36537	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm	57Y4352
Lenovo DisplayPort to DisplayPort Monitor Cable	0A36537												
Kensington® MicroSaver® Cable Lock	73P2582												
Kensington Twin Head Cable Lock	45K1620												
Lenovo Security Cable Lock	57Y4303												
Lenovo Easy Reach Monitor Stand	55Y9258												
ThinkCentre Extend Arm	57Y4352												

See footnotes for important warranty information
 US model announced May 1, 2012

<p>Name LT2323z Wide Flat Panel Monitor Case color Raven black Type-model 3028-LB2 Panel TFT-LCD, In-Plane Switching (IPS), White LED backlight Viewable image size 23.0" (584mm) diagonal Max view area (W x H) 20.05" x 11.28" / 509.2mm x 286.4mm Optimum resolution 1920x1080 Aspect ratio 16:9 Pixel pitch (mm) .265mm Dot/Pixel per Inch 96 dpi Brightness 250 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 7ms (typical) Color gamut 72% Anti-reflective Anti-glare Vertical frequency 50 to 75Hz Horizontal frequency VGA: 30 to 81kHz; DP: 30 to 75kHz Viewing angle at 10:1 CR 178° (+/- 89°) horizontal, 178° (+/- 89°) vertical Stand Tilt, swivel, pivot, and height adjustable stand (toolless detachable) Bezel width Sides: 0.68" (17.3mm); top: 1.15" (29.1mm); bottom: 2.76" (70.1mm) Dimensions (HxWxD) 15.24" H x 21.47" W x 2.22" D; (excluding stand) 387.2mm H x 545.3mm W x 56.4mm D Power supply 25 watts typical, 40 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight 13.71 lb; 6.22kg (excluding stand) Limited warranty⁴ 3 year (includes backlight) Available date June 2012</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 23-inch IPS monitor • 1080p full HD support, HDCP-compliant • Built-in VGA and DisplayPort connectors for attachment to two systems concurrently • Integrated camera (HD) and dual digital microphone • Integrated USB 3.0 Hub • Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Compliance with ENERGY STAR 6.0 DRAFT • Ambient light sensor to automatically adjust the backlight • Microsoft® Lync™ certified VoIP monitor • EPEAT Gold certified 										
<p>VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant Power management ENERGY STAR® 6.0 DRAFT Ergonomics ISO 9241-307 Emission standards MPR-2, FCC Class B Environmental TCO (TCO Certified Edge 1.1), WEEE, RoHS, EPEAT™ Gold rating</p> <p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1360x768 WXGA+: 1440x900 WSXGA+: 1600x1050 UXGA: 1600x1200 Full HD: 1920x1080</p> <p>Presets / user settings Presets: 26; user settings: 20</p>	 <p>ThinkVision LT2323z Wide Monitor</p>										
<p>Viewing adjustments Tilt: 30° back, -5° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand Rotating screen Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller, do not support image rotation under dual image modes) On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front and side) for MIC mute, speaker mute, hook switch and volume +/- buttons USB hub USB 3.0 Hub: 1 port into PC; 5 ports for accessories (3 USB 3.0 + 2 USB 2.0) Multimedia Integrated digital speakers (3 watts x 2) Camera Integrated camera (HD) and digital dual microphone array, with Camera lock button for security Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p> <p>Ship group Monitor, toolless detachable stand, Quick start and safety poster, CD with multilingual User's Guide, setup test pattern, and installation files, analog signal cable, DisplayPort cable, 1.8 meter USB 3.0 cable, 1.8 meter black power cord</p>	<p>Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm	57Y4352
Kensington® MicroSaver® Cable Lock	73P2582										
Kensington Twin Head Cable Lock	45K1620										
Lenovo Security Cable Lock	57Y4303										
Lenovo Easy Reach Monitor Stand	55Y9258										
ThinkCentre Extend Arm	57Y4352										


<p>Limited Warranty</p> <ul style="list-style-type: none"> ↪ 3 year limited warranty⁴ ↪ International Warranty Service⁵ ↪ Replacement normally arrives in two business days, excluding holidays ↪ Lenovo pays all shipping costs for valid warranty claims⁶ ↪ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ↪ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴
--

<p>Accessories</p> <table border="0"> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision</p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm	57Y4352
Kensington® MicroSaver® Cable Lock	73P2582									
Kensington Twin Head Cable Lock	45K1620									
Lenovo Security Cable Lock	57Y4303									
Lenovo Easy Reach Monitor Stand	55Y9258									
ThinkCentre Extend Arm	57Y4352									

See footnotes for important warranty information
 US model announced June 5, 2012

<p>Name LT2452p Wide Flat Panel Monitor Case color Business black Type-model 4420-MB2 / 60A6MAR2US Panel TFT-LCD, e-IPS, White LED backlight Viewable image size 24" (610mm) diagonal Max view area (W x H) 20.4" x 12.8" (518.4mm x 324.0mm) Optimum resolution 1920x1200 Max pixel rate 202.5MHz Aspect ratio 16:10 Pixel pitch (mm) 0.270mm Dot/Pixel per Inch 94 dpi Brightness 300 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 7ms (GtG) Color gamut 72% Anti-reflective Anti-reflective, anti-glare Viewing angle at 10:1 CR 178° horizontal, 178° vertical Stand Tilt, swivel, pivot, and height adjustable stand Bezel width Sides: 0.78" (19.9mm); top: 0.78" (19.9mm); bottom: 1.12" (28.4mm)</p> <p>Dimensions (HxWxD) 15.54-19.87" H x 22" W x 10.13" D; 394.8-504.8mm H x 559.6mm W x 257.3mm D</p> <p>Power supply 30 watts typical (w/o USB hub), 40 watts maximum (w/o USB hub), <0.5 watts standby/suspend (w/o USB hub), universal, integrated (no external brick-like power supply)</p> <p>Weight 14.70 lb; 6.67kg Limited warranty⁴ 3 year (includes backlight) Available date September 2011 / April 2013</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 24-inch monitor • Supports 1920x1200 resolution • High Definition (HD) ready; supports 1080p video • Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Cable Management for better user experience • Carrying handle • Recycled content in plastic material • Microsoft® Windows® 8 certified • PVC/Arsenic/Lead/Mercury free (60A6MAR2US) 												
<p>VESA-compliant² VESA DDC2B/CI Power management ENERGY STAR® 5.1 (4420-MB2) ENERGY STAR® 6.0 (60A6MAR2US) Ergonomics ISO 9241-307 Emission standards MPR-2, FCC Class B Environmental TCO Displays 5.2 (4420-MB2), TCO Displays 6.0 (60A6MAR2US), TCO Certified Edge 1.1, WEEE, RoHS, EPEAT™ Gold rating, ULE Gold</p>	 <p>ThinkVision LT2452p Wide Monitor</p>												
<p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1280x800, 1366x768 WXGA+: 1440x900 UXGA: 1600x1200 WSXGA+: 1680x1050 Full HD: 1920x1080 WUXGA: 1920x1200</p> <p>Presets / user settings Standard presets: 30; User settings: 20</p>													
<p>Viewing adjustments Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand Rotating screen Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller) On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness USB hub USB 2.0 Hub (1 port into PC, 4 ports for accessories) Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant (3) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant</p> <p>Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)</p> <p>Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Ship group Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter USB cable, 1.8 meter black power cord</p>												
<p>Limited Warranty</p> <ul style="list-style-type: none"> ⇒ 3 year limited warranty⁴ ⇒ International Warranty Service⁵ ⇒ Replacement normally arrives in two business days, excluding holidays ⇒ Lenovo pays all shipping costs for valid warranty claims⁶ ⇒ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ⇒ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p>Accessories</p> <table border="0"> <tr> <td>DisplayPort to DisplayPort Monitor Cable</td> <td>0A36537</td> </tr> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories</p> <p>See all monitors at www.lenovo.com/thinkvision</p>	DisplayPort to DisplayPort Monitor Cable	0A36537	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258
DisplayPort to DisplayPort Monitor Cable	0A36537												
Kensington MicroSaver Cable Lock	73P2582												
Kensington Twin Head Cable Lock	45K1620												
Lenovo Security Cable Lock	57Y4303												
ThinkCentre Extend Arm	57Y4352												
Lenovo Easy Reach Monitor Stand	55Y9258												

See footnotes for important warranty information
 US model announced September 13, 2011 or April 16, 2013

<p>Name LT3053p Wide Flat Panel Monitor Case color Business black Type-model 60A4RAR1US Panel TFT-LCD, AH-IPS, White LED backlight Viewable image size 30" (762mm) diagonal Max view area (W x H) 25.2" x 15.8" (641.3mm x 400.8mm) Optimum resolution 2560x1600 Max pixel rate 205MHz Aspect ratio 16:10 Pixel pitch (mm) 0.251mm Dot/Pixel per Inch 101 dpi Brightness 350 nits or cd/m² (typical) Contrast ratio 1000:1 (typical) Pixel response time 6ms (Grey To Grey average) Color gamut 99% (Adobe RGB) Viewing angle at 10:1 CR 178° horizontal, 178° vertical Stand Tilt, swivel, pivot, and height adjustable stand Bezel width <i>Sides:</i> 0.91" (23.1mm); <i>top:</i> 0.91" (23.2mm); <i>bottom:</i> 0.91" (23.1mm) Dimensions (HxWxD, excluding stand) 449.3mm H x 690mm W x 62mm D Dimensions (HxWxD, including stand) 471.1mm H x 690mm W x 241.5mm D Power supply 88 watts typical (w/o USB hub), 130 watts maximum (w/o USB hub), <1.2 watts sleep/off (w/o USB hub); <0.5 watts switch off (w/o USB hub) integrated (no external brick-like power supply) Weight 25.35 lb; 11.5kg (including stand and shading hood) Limited warranty⁴ 3 year (includes backlight) Available date March 2013</p>	<p>Features</p> <ul style="list-style-type: none"> • Widescreen 30-inch monitor • Supports 2560x1600 resolution • PiP(Picture in Picture) Anywhere Solution (software) • 5-Ports USB hub, support USB 3.0 and USB 2.0 • Support VGA, DVI, HDMI, DisplayPort and MHL • Support DaisyChain • Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing • Bundled Professional Hood • Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket • Arsenic/Lead/Mercury free • Microsoft® Windows® 7 certified • Microsoft Windows 8 certified
<p>VESA-compliant² VESA DDC2B/CI Power management ENERGY STAR[®] 6.0 Ergonomics ISO 9241-307 Emission standards FCC Class B Environmental TCO Displays 6.0, TCO Certified Edge 1.2, RoHS, EPEAT™ Gold rating, ULE Gold</p> <p>Preset resolutions VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x720, 1280x768, 1280x800, 1360x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080 WUXGA: 1920x1200 WQXGA: 2560x1600 other: 640x1600, 1280x1600, 1920x1600, Standard presets: 21; user settings: 20</p>	 <p>ThinkVision LT3053p Wide Monitor</p>
<p>Viewing adjustments <i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand Rotating screen Screen pivots 90 degrees from landscape to portrait On screen display On screen display with digital user controls (8 languages) Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness USB hub USB Hub (1 USB 3.0 w/Battery charger, 2 USB 3.0, 2 USB 2.0) Multiple input Support VGA, DVI-D, HDMI, DisplayPort, MHL connections (Mobile High-definition Link) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort (1.2), digital, black, HDCP-compliant (3) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant (4) HDMI (1.4), digital, HDCP-compliant</p> <p>Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter (3) detachable, DVI-D at each end, digital, 1.8 meter Note: HDMI cable is not included</p> <p>Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	
<p>Ship group Monitor, toolless detachable stand, shading hood, Quick start and safety poster, CD with multilingual User's Guide, setup test pattern, Picture In Picture Anywhere installation files and user guide, 1.8 meter analog signal cable, 1.8 meter DisplayPort cable, 1.8 meter DVI-D cable, 1.8 meter USB 3.0 cable, 1.8 meter USB 2.0 cable, 1.8 meter black power cord</p>	

<p>Limited Warranty</p> <ul style="list-style-type: none"> ⇒ 3 year limited warranty⁴ ⇒ International Warranty Service⁵ ⇒ Replacement normally arrives in two business days, excluding holidays ⇒ Lenovo pays all shipping costs for valid warranty claims⁶ ⇒ Service upgrade options:⁷ <ul style="list-style-type: none"> • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ⇒ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴ 	<p>Accessories</p> <table border="0"> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> </table> <p>See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision</p>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington MicroSaver Cable Lock	73P2582										
Kensington Twin Head Cable Lock	45K1620										
Lenovo Security Cable Lock	57Y4303										
ThinkCentre Extend Arm	57Y4352										
Lenovo Easy Reach Monitor Stand	55Y9258										

See footnotes for important warranty information
 US model announced March 12, 2013



Kensington® MicroSaver® Cable Lock from Lenovo
(73P2582)
Kensington Twin Head Cable Lock from Lenovo
(45K1620)
Lenovo Security Cable Lock
(57Y4303)



Lenovo USB Soundbar
(0A36190)



Lenovo Easy Reach Monitor Stand
(55Y9258)



ThinkCentre Extend Arm
(57Y4352)



Lenovo DisplayPort to VGA Monitor Cable
(57Y4393)

Lenovo DisplayPort to Single-link DVI-D Monitor Cable
(45J7915)

Lenovo Mini-DisplayPort to VGA Monitor Cable
(0A36536)

Lenovo DisplayPort to DisplayPort Monitor Cable
(0A36537)

Monitor Accessories⁴⁶ (all part numbers listed are US option P/N) Lenovo DisplayPort to VGA Monitor Cable ** 57Y4393 <i>ann 08/04/09</i> DisplayPort to Single-link DVI-D Cable ** 45J7915 <i>ann 08/05/08</i> Lenovo Mini-DisplayPort to VGA Monitor Cable ** 0A36536 <i>ann 05/17/11</i> ** Supports a maximum 1920 x 1200 monitor resolution. Lenovo DisplayPort to DisplayPort Monitor Cable*** 0A36537 <i>ann 09/13/11</i> ***Hardware requirement: All Lenovo systems and monitors with DisplayPort 1.1a or 1.2 interface.		Lenovo USB Soundbar 0A36190 <i>ann 05/01/12</i> Kensington® MicroSaver® Cable Lock 73P2582 <i>ann 12/29/03</i> Kensington Twin Head Cable Lock 45K1620 <i>ann 09/30/08</i> Lenovo Security Cable Lock 57Y4303 <i>ann 08/24/10</i> Lenovo Easy Reach Monitor Stand 55Y9258 <i>ann 09/22/09</i> ThinkCentre Extend Arm 57Y4352 <i>ann 07/06/10</i>
--	--	---

⁴⁶Compatible on selected Lenovo and ThinkVision monitors.

Compatibility matrix

	DisplayPort to VGA Cable (57Y4393)	DisplayPort to DVI-D Cable (45J7915)	Mini-Display-Port to VGA Monitor Cable (0A36536)	DisplayPort to DisplayPort Monitor Cable (0A36537)	Lenovo USB Soundbar (0A36190)	MicroSaver Cable Lock (73P2582)	Twin Head Cable Lock (45K1620)	Security Cable Lock (57Y4303)	Easy Reach Monitor Stand (55Y9258)	Extend Arm (57Y4352)
LT1421						73P2582	45K1620	57Y4303		
L1711p	57Y4393	45J7915	0A36536		0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
D186	57Y4393		0A36536			73P2582	45K1620	57Y4303	55Y9258	57Y4352
L197	57Y4393	45J7915	0A36536			73P2582	45K1620	57Y4303	55Y9258	57Y4352
L1900p	57Y4393	45J7915	0A36536		0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
L1951p	57Y4393	45J7915	0A36536		0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
LT1952p	57Y4393	45J7915	0A36536	0A36537	0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
L2021	57Y4393	45J7915	0A36536		0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
LS2221			0A36536			73P2582	45K1620	57Y4303	55Y9258	57Y4352
L2250p	57Y4393	45J7915	0A36536		0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
X L2251p	57Y4393		0A36536	0A36537	0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
LT2252p	57Y4393	45J7915	0A36536	0A36537	0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
L2251x	57Y4393		0A36536	0A36537	0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
X L2321x	57Y4393		0A36536	0A36537	0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
LS2421p			0A36536	0A36537		73P2582	45K1620	57Y4303	55Y9258	57Y4352
X L2440p	57Y4393	45J7915	0A36536		0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
LT2452p	57Y4393	45J7915	0A36536	0A36537	0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
LS1922	57Y4393		0A36536			73P2582	45K1620	57Y4303	55Y9258	57Y4352
LT2323p	57Y4393	45J7915	0A36536	0A36537	0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
X L2461x	57Y4393		0A36536			73P2582	45K1620	57Y4303	55Y9258	57Y4352
X L151	57Y4393					73P2582	45K1620		55Y9258	
X L151p	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L171	57Y4393					73P2582	45K1620		55Y9258	
X L171p	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L172	57Y4393					73P2582	45K1620		55Y9258	
X L174	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L1700p	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X D185	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L190x	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L191	57Y4393					73P2582	45K1620		55Y9258	
X L192p	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L193p	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L194	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L1940p	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L200p	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L201p	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L2060	57Y4393	45J7915				73P2582	45K1620	57Y4303	55Y9258	57Y4352
X L215	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L215p	57Y4393					73P2582	45K1620		55Y9258	
X L220x	57Y4393					73P2582	45K1620		55Y9258	
X L2230x	57Y4393				0A36190	73P2582	45K1620	57Y4303	55Y9258	57Y4352
X L2240p	57Y4393	45J7915				73P2582	45K1620		55Y9258	
X L2440x	57Y4393	45J7915			0A36190	73P2582	45K1620		55Y9258	

X Monitors withdrawn from marketing.

More information at www.lenovo.com/support/monitoraccessories

Other accessories at www.lenovo.com/accessories

Accessories Guide pdf at www.lenovo.com/accessoriesguide

Availability: All offers subject to availability. Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo is not responsible for photographic or typographic errors.

Warranty: For a copy of applicable product warranties, go to: http://support.lenovo.com/en_US/product-service/warranty-status/WarrantyPolicies.page. Lenovo makes no representation or warranty regarding third party products or services.

¹ **ISO-compliant:** Compliance with ISO 9241 Part 3, ISO Part 7, ISO Part 8, and/or ISO 13406 Part 2 is dependent on a complete ISO-capable platform of a system unit, monitor, video subsystem, operating system and fonts.

² **VESA:** Requires attachment to suitably configured system with similarly enabled operating system.

³ **ENERGY STAR:** As an ENERGY STAR partner, Lenovo has determined that this product meets the ENERGY STAR 4.0 or 4.1 guidelines for energy efficiency. Requires attachment to suitably configured system.

⁴ **Limited warranty:** Support unrelated to a warranty issue may be subject to additional charges.

⁵ **International Warranty Service** is available in any country in which this product is sold and serviced. Service delivery methods and parts availability vary by country, may be different from that in the country of purchase, and are subject to change without notice. Fees and restrictions may apply in some countries.

⁶ **Lenovo pays all shipping costs** for warranty repairs during limited warranty period.

⁷ **Lenovo Services:** These services are available for machines normally used for business, professional, or trade purposes, rather than personal, family, or household purposes. Not all machine types and models are covered. Service period begins with the equipment date of purchase. Service must be purchased during the original limited product warranty period. Service levels are response time objectives and are not guarantees. If the machine problem turns out to be a Customer Replaceable Unit (CRU), a part will be express shipped to you for quick replacement. Onsite 24x7x2-hour service is not available in all locations. P&L means parts and labor. P/U means pick-up. See terms and conditions for complete details and restrictions.

⁸ **Telephone support** may be subject to additional charges, even during the limited warranty period. Response times may vary. May exclude some holidays. If a machine is listed as having "On-site service for select repairs", this means that onsite service is available only for the replacement of select parts. For all other warranty repairs, Lenovo will provide the customer a replacement part for customer installation. The parts for which onsite service is available varies by machine, but may include the processor, power supply, heat sink, system board, or base cover. For machines with EasyServ or Courier service, Lenovo will attempt to diagnose and resolve the problem remotely before sending a courier.

¹⁰ **TAA:** Monitor is compliant with the U.S. Federal Government's country-of-origin requirements prescribed in 48 C.F.R. Subpart 25.4; Trade Act Agreement (TAA) model.

¹¹ **Post-warranty annual maintenance agreement:** Service begins at the end of the base warranty or the end of any other applied warranty and maintenance option, whichever occurs last. Service delivery is not available the same day the maintenance agreement is purchased. Maintenance agreements must be purchased and the registration successfully completed prior to the service being available.

¹² **Halogen:** Less than 900 Parts Per Million. Low halogen is defined in accordance with IPC-401B and draft IPC-J-STD 709 Class 1 requirements.

ThinkVision®

Trademarks: Lenovo, the Lenovo logo, New World. New Thinking., Access Connections, Rescue and Recovery, ThinkCentre, ThinkPad, ThinkStation, ThinkVantage, and ThinkVision are trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Other company, product, or service names may be trademarks or service marks of others.

This publication was developed for products and services offered in the United States. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to alter specifications and other product information at any time without prior notice. Lenovo is not responsible for photographic or typographical errors. **LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore this disclaimer may not apply to you. This publication was developed in the US.

Visit www.lenovo.com/safecomputing periodically for the latest information on safe and effective computing.

Visit www.lenovo.com/psref for the latest version of **Personal Systems Reference**.

© Lenovo, 2013.
All rights reserved.

Lenovo
1009 Think Place
Morrisville, NC 27560
U.S.A.

May 2013
mbook.pdf